
65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311

www.kctl.co.kr

Report No.: KR24-SRF0096 Page (53) of (64)






65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311

3-1021 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR24-SRF0096 Page (54) of (64)



Test results (Above 18 (址) - Worst case: 802.11n HT20 / 2 472 址



Note: The Worst case was based on the lowest margin condition considering Harmonic and Spurious Emission

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311

www.kctl.co.kr

Report No.: KR24-SRF0096 Page (55) of (64)



# 7.5. Conducted Spurious Emission

<u>Test setup</u>	_		_	
EUT		Attenuator		Spectrum analyzer

#### Limit

# According to §15.247(d),

In any 100  $^{kHz}$  bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20  $^{dB}$  below that in the 100  $^{kHz}$  bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30  $^{dB}$  instead of 20  $^{dB}$ . Attenuation below the general field strength limits specified in RSS-Gen is not required.

Limit: 20 dBc

# **Test procedure**

ANSI C63.10 - Section 11.11.3 KDB 558074 D01 v05 - Section 8.5

# **Test settings**

Establish an emission level by using the following procedure:

- 1) Set the center frequency and span to encompass frequency range to be measured.
- 2) Set the RBW = 100 kHz
- 3) Set the VBW  $\geq$  [3 x RBW]
- 4) Detector = peak
- 5) Sweep time = auto couple
- 6) Trace mode = max hold
- 7) Allow trace to fully stabilize.
- 8) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.


65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311

www.kctl.co.kr

Report No.: KR24-SRF0096 Page (56) of (64)



# **Test results**




65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311

www.kctl.co.kr

Report No.: KR24-SRF0096 Page (57) of (64)






65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311

www.kctl.co.kr

Report No.: KR24-SRF0096 Page (58) of (64)






65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311

www.kctl.co.kr

Report No.: KR24-SRF0096 Page (59) of (64)





65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311

www.kctl.co.kr

Report No.: KR24-SRF0096 Page (60) of (64)



