

FCC Sub6 REPORT

Certification

Applicant Name:

SAMSUNG Electronics Co., Ltd.

Date of Issue:

December 27, 2022

Location:

HCT CO., LTD.,

 74, Seoicheon-ro 578beon-gil, Majang-myeon,
 Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Report No.: HCT-RF-2212-FC014

FCC ID:
A3LSMM146B
APPLICANT:
SAMSUNG Electronics Co., Ltd.

Model(s): SM-M146B/DSN
 EUT Type: Mobile Phone
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 FCC Rule Part(s): §27, §2

SA

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
Sub6 n66 (5)	1712.5 – 1777.5	4M55G7D	PI/2 BPSK	0.155	21.89
		4M53G7D	QPSK	0.153	21.84
		4M52W7D	16QAM	0.124	20.93
		4M55W7D	64QAM	0.086	19.32
		4M53W7D	256QAM	0.055	17.40
Sub6 n66 (10)	1715.0 – 1775.0	9M01G7D	PI/2 BPSK	0.153	21.86
		9M99G7D	QPSK	0.152	21.82
		8M99W7D	16QAM	0.118	20.71
		8M99W7D	64QAM	0.086	19.33
		8M98W7D	256QAM	0.053	17.27
Sub6 n66 (15)	1717.5 – 1772.5	13M5G7D	PI/2 BPSK	0.153	21.84
		13M4G7D	QPSK	0.150	21.77
		13M5W7D	16QAM	0.117	20.70
		13M4W7D	64QAM	0.088	19.43
		13M5W7D	256QAM	0.053	17.28
Sub6 n66 (20)	1720.0 – 1770.0	17M9G7D	PI/2 BPSK	0.158	22.00
		17M9G7D	QPSK	0.157	21.96
		17M9W7D	16QAM	0.128	21.06
		17M9W7D	64QAM	0.088	19.44
		17M9W7D	256QAM	0.057	17.58

NSA

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
Sub6 n66 (5)	1712.5 – 1777.5	4M52G7D	PI/2 BPSK	0.197	22.95
		4M52G7D	QPSK	0.195	22.90
		4M51W7D	16QAM	0.157	21.96
		4M52W7D	64QAM	0.111	20.46
		4M49W7D	256QAM	0.070	18.46
Sub6 n66 (10)	1715.0 – 1775.0	8M98G7D	PI/2 BPSK	0.166	22.20
		8M99G7D	QPSK	0.162	22.09
		9M00W7D	16QAM	0.142	21.52
		8M98W7D	64QAM	0.109	20.36
		9M00W7D	256QAM	0.068	18.31
Sub6 n66 (15)	1717.5 – 1772.5	13M5G7D	PI/2 BPSK	0.185	22.68
		13M4G7D	QPSK	0.178	22.51
		13M5W7D	16QAM	0.153	21.86
		13M5W7D	64QAM	0.110	20.40
		13M4W7D	256QAM	0.069	18.36
Sub6 n66 (20)	1720.0 – 1770.0	17M9G7D	PI/2 BPSK	0.169	22.29
		18M0G7D	QPSK	0.168	22.25
		17M9W7D	16QAM	0.149	21.72
		18M0W7D	64QAM	0.111	20.46
		17M9W7D	256QAM	0.071	18.49

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

REVIEWED BY



Report prepared by : Jung Ki Lim
Engineer of Telecommunication Testing Center

Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked *.
The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

* The report shall not be reproduced except in full(only partly) without approval of the laboratory.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2212-FC014	December 27, 2022	- First Approval Report

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

Table of Contents

REVIEWED BY	3
1. GENERAL INFORMATION	6
2. INTRODUCTION	7
2.1. DESCRIPTION OF EUT	7
2.2. MEASURING INSTRUMENT CALIBRATION	7
2.3. TEST FACILITY	7
3. DESCRIPTION OF TESTS.....	8
3.1 TEST PROCEDURE	8
3.2 RADIATED POWER.....	9
3.3 RADIATED SPURIOUS EMISSIONS	10
3.4 PEAK- TO- AVERAGE RATIO.....	11
3.5 OCCUPIED BANDWIDTH.....	13
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	14
3.7 BAND EDGE	15
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	16
3.9 WORST CASE(RADIATED TEST)	17
3.10 WORST CASE(CONDUCTED TEST)	18
4. LIST OF TEST EQUIPMENT	19
5. MEASUREMENT UNCERTAINTY	20
6. SUMMARY OF TEST RESULTS	21
7. SAMPLE CALCULATION	22
8. TEST DATA (SA)	24
8.1 EQUIVALENT ISOTROPIC RADIATED POWER.....	24
8.2 RADIATED SPURIOUS EMISSIONS	28
8.3 PEAK-TO-AVERAGE RATIO.....	29
8.4 OCCUPIED BANDWIDTH	30
8.5 CONDUCTED SPURIOUS EMISSIONS	31
8.6 BAND EDGE	31
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	32
9. TEST DATA (NSA)	36
9.1 EQUIVALENT ISOTROPIC RADIATED POWER.....	36
9.2 RADIATED SPURIOUS EMISSIONS	40
9.3 PEAK-TO-AVERAGE RATIO.....	41
9.4 OCCUPIED BANDWIDTH	42
9.5 CONDUCTED SPURIOUS EMISSIONS	43
9.6 BAND EDGE	43
9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	44
10. TEST PLOTS (SA)	48
11. TEST PLOTS (NSA)	137
12. ANNEX A_ TEST SETUP PHOTO.....	226

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMM146B
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s):	§27, §2
EUT Type:	Mobile Phone
Model(s):	SM-M146B/DSN
SCS(kHz):	15
Bandwidth(MHz):	5, 10, 15, 20
Waveform:	CP-OFDM, DFT-S-OFDM
Modulation:	DFT-S-OFDM: PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM CP-OFDM: QPSK, 16QAM, 64QAM, 256QAM
Tx Frequency:	1712.5 MHz – 1777.5 MHz (Sub6 n66(5 MHz)) 1715.0 MHz – 1775.0 MHz (Sub6 n66(10 MHz)) 1717.5 MHz – 1772.5 MHz (Sub6 n66(15 MHz)) 1720.0 MHz – 1770.0 MHz (Sub6 n66(20 MHz))
Date(s) of Tests:	November 25, 2022 ~ December 23, 2022
Serial number:	Radiated: R3CTA0GVSYB Conducted: R3CTA0GW2KB

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS and LTE, Sub6.

It also supports IEEE 802.11 a/b/g/n/ac (20/40/80 MHz), NFC, Bluetooth, BT LE.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4 - ANSI C63.26-2015 – Section 5.2.6(only GSM)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d \text{ (dBm)} = P_g \text{ (dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference

between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

Test Settings

1. RBW = 100kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz
2. VBW \geq 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points > 2 x span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The spurious emissions is calculated by the following formula;


$$\text{Result (dBm)} = P_g (\text{dBm}) - \text{cable loss (dB)} + \text{antenna gain (dBi)}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP (dBm)} = \text{ERP (dBm)} + 2.15$$

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - .- for continuous transmissions, set to 1 ms,
 - .- or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R \text{ (dB)} = P_{Pk \text{ (dBm)}} - P_{Avg \text{ (dBm)}} \quad (P_{Avg} = \text{Average Power + Duty cycle Factor})$$

Test Settings(Peak Power)


The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.

1. Set the RBW \geq OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times$ (number of points in sweep) \times (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW \geq OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:
Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep
(automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6 \text{ dB}$ if the duty cycle is a constant 25 %.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5 % of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99 % occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic.


All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW \geq 3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time = auto
6. Number of points in sweep \geq 2 x Span / RBW

3.7 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1 % of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times$ Span/RBW
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes

According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels (low and high operational frequency range).

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

Where Margin < 1 dB the emission level is either corrected by $10 \log(1 \text{ MHz} / \text{RB})$ or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.

2. Primary Supply Voltage:

- .- Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.
- .- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 WORST CASE(RADIATED TEST)

- Waveform : All Waveform of operation were investigated and the worst case configuration results are reported.
(Worst case: DFT-S-OFDM)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.

- All modes of operation were investigated and the worst case configuration results are reported.

Mode : Stand alone, Stand alone + External accessories (Earphone, AC adapter, etc)

Worst case : Stand alone

- We were performed the RSE test in condition of co-location.

Mode : Stand alone, Simultaneous transmission scenarios

Worst case : Stand alone

- Because the target power of SA mode and NSA mode is different, all results for both modes are reported.

- Radiated Spurious emissions are measured while operating in EN-DC mode with Sub 6 NR carrier as well as an LTE carrier (anchor).

All EN-DC mode of operation were investigated and the worst case configuration results are reported.

(Worst case: 5A-n66A(10 MHz))

- All RB sizes, offsets of operation were investigated and the worst case configuration results are reported.

Please refer to the table below.

-In the case of radiated spurious emissions, all bandwidth of operation were investigated and the worst case bandwidth results are reported.

(SA Worst case : 20 MHz)

(NSA Worst case : 5 MHz)

[SA Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM	See Section 8.1		X
Radiated Spurious and Harmonic Emissions	PI/2 BPSK	See Section 8.2		Z

[NSA Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM	See Section 8.1		X
Radiated Spurious and Harmonic Emissions	PI/2 BPSK	See Section 8.2		Z

3.10 WORST CASE(CONDUCTED TEST)

- Waveform : All Waveform of operation were investigated and the worst case configuration results are reported.

(Worst case: DFT-S-OFDM)

- Modulation : All Modulation of operation were investigated and the worst case configuration results are reported.

(Worst case: PI/2 BPSK)

- All modes of operation were investigated and the worst case configuration results are reported.

- Because the target power of SA mode and NSA mode is different, all results for both modes are reported.

- All RB sizes, offsets of operation were investigated and the worst case configuration results are reported.

Please refer to the table below.

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth, Peak-To-Average Ratio	PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM	5, 10, 15, 20	Mid	Full RB	0
Band Edge	PI/2 BPSK	5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	51
		15	Low	1	0
			High	1	78
		20	Low	1	0
			High	1	105
		5, 10, 15, 20	Low, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	PI/2 BPSK	5, 10, 15, 20	Low, Mid, High	1	1

4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacture	Serial No.	Due to Calibration	Calibration Interval
Precision Dipole Antenna	UHAP	Schwarzbeck	01273	03/27/2024	Biennial
Precision Dipole Antenna	UHAP	Schwarzbeck	01274	03/27/2024	Biennial
Horn Antenna(1~18 GHz)	BBHA 9120D	Schwarzbeck	02289	03/21/2024	Biennial
Horn Antenna(1~18 GHz)	BBHA 9120D	Schwarzbeck	9120D-1299	05/04/2023	Biennial
Horn Antenna(15~40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170342	09/29/2024	Biennial
Horn Antenna(15~40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170124	04/12/2023	Biennial
Loop Antenna(9 kHz~30 MHz)	FMZB1513	Rohde & Schwarz	1513-175	06/04/2023	Biennial
Bilog Antenna	VULB9160	Schwarzbeck	3150	03/03/2023	Biennial
Hybrid Antenna	VULB9160	Schwarzbeck	760	02/22/2023	Biennial
High Pass Filter	WHKX10-900-1000-15000-40SS	Wainwright Instruments	15	05/18/2023	Annual
High Pass Filter	WHKX10-2700-3000-18000-40SS	Wainwright Instruments	145	05/18/2023	Annual
High Pass Filter	WHNX6-4740-6000-26500-40CC	Wainwright Instruments	11	05/18/2023	Annual
LOW NOISE AMP (100 MHz ~ 18 GHz)	CBLU1183540B-01	CERNEX	26822	05/18/2023	Annual
Power Amplifier	CBL18265035	CERNEX	22966	12/01/2023	Annual
Power Amplifier	CBL26405040	CERNEX	25956	03/11/2023	Annual
DC Power Supply	E3632A	Hewlett Packard	MY40004427	09/05/2023	Annual
Power Splitter(DC~26.5 GHz)	11667B	Hewlett Packard	11275	03/11/2023	Annual
Chamber	SU-642	ESPEC	93008124	03/04/2023	Annual
Signal Analyzer(10 Hz~26.5 GHz)	N9020A	Agilent	MY51110063	04/19/2023	Annual
ATTENUATOR(20 dB)	8493C	Hewlett Packard	17280	05/18/2023	Annual
Spectrum Analyzer(10 Hz~40 GHz)	FSV40	REOHDE & SCHWARZ	101436	02/25/2023	Annual
Base Station	8960 (E5515C)	Agilent	MY48360800	08/18/2023	Annual
Wideband Radio Communication Tester	MT8821C	Anritsu Corp.	6262287700	05/19/2023	Annual
Wideband Radio Communication Tester	MT8000A	Anritsu Corp.	6262302511	05/18/2023	Annual
SIGNAL GENERATOR (100 kHz~40 GHz)	SMB100A	REOHDE & SCHWARZ	177633	07/05/2023	Annual
Signal Analyzer(5 Hz~40.0 GHz)	N9030B	KEYSIGHT	MY55480167	05/30/2023	Annual
4-Way Divider	ZC4PD-K1844+	Mini-Circuits	942907	09/27/2023	Annual
FCC LTE Mobile Conducted RF Automation Test Software	-	HCT CO., LTD.,	-	-	-

Note:

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
2. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (\pm dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	2.00 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.40 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.74 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.51 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.92 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (Above 40 GHz)	5.48 (Confidence level about 95 %, $k=2$)

6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §27.53(h)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§2.1046	N/A	<u>See Note1</u>
Peak- to- Average Ratio	§27.50(d)(5)	< 13 dB	PASS
Frequency stability / variation of ambient temperature	§2.1055, §27.54	Emission must remain in band	PASS

Note:

1. See SAR Report
2. All conducted tests were tested using 5G Wireless Tester.

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§27.50(d)(4)	< 1 Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §27.53(h)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

Note:

1. Radiated tests were tested using 5G Wireless Tester.

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

ERP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
349000	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

EIRP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

PSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA (SA)

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP			RB	
									W	W	dBm	Size	Offset
1712.5	Sub6 n66/ 5 MHz [15 kHz]	PI/2 BPSK	-19.07	14.29	9.60	2.00	H	< 1.00	0.155	21.89		1	12
		QPSK	-19.12	14.24	9.60	2.00	H		0.153	21.84			
		16-QAM	-20.03	13.33	9.60	2.00	H		0.124	20.93			
		64-QAM	-21.64	11.72	9.60	2.00	H		0.086	19.32			
		256-QAM	-23.56	9.80	9.60	2.00	H		0.055	17.40			
1745.0	Sub6 n66/ 5 MHz [15 kHz]	PI/2 BPSK	-19.87	13.73	9.75	2.04	H	< 1.00	0.139	21.44		1	1
		QPSK	-20.00	13.60	9.75	2.04	H		0.135	21.31			
		16-QAM	-21.03	12.57	9.75	2.04	H		0.107	20.28			
		64-QAM	-22.57	11.03	9.75	2.04	H		0.075	18.74			
		256-QAM	-24.45	9.15	9.75	2.04	H		0.049	16.86			
1777.5	Sub6 n66/ 5 MHz [15 kHz]	PI/2 BPSK	-19.97	13.57	9.90	2.08	H	< 1.00	0.138	21.39		1	12
		QPSK	-20.03	13.51	9.90	2.08	H		0.136	21.33			
		16-QAM	-20.90	12.64	9.90	2.08	H		0.111	20.46			
		64-QAM	-22.39	11.15	9.90	2.08	H		0.079	18.97			
		256-QAM	-24.42	9.12	9.90	2.08	H		0.049	16.94			

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP			RB	
									W	W	dBm	Size	Offset
1715.0	Sub6 n66/ 10 MHz [15 kHz]	PI/2 BPSK	-19.10	14.26	9.60	2.00	H	< 1.00	0.153	21.86		1	26
		QPSK	-19.14	14.22	9.60	2.00	H		0.152	21.82			
		16-QAM	-20.25	13.11	9.60	2.00	H		0.118	20.71			
		64-QAM	-21.63	11.73	9.60	2.00	H		0.086	19.33			
		256-QAM	-23.69	9.67	9.60	2.00	H		0.053	17.27			
		PI/2 BPSK	-19.85	13.75	9.75	2.04	H	> 1.00	0.140	21.46		1	1
		QPSK	-19.87	13.73	9.75	2.04	H		0.139	21.44			
		16-QAM	-20.89	12.71	9.75	2.04	H		0.110	20.42			
		64-QAM	-22.46	11.14	9.75	2.04	H		0.077	18.85			
		256-QAM	-24.27	9.33	9.75	2.04	H		0.051	17.04			
1745.0		PI/2 BPSK	-20.05	13.49	9.90	2.08	H	> 1.00	0.135	21.31		1	1
		QPSK	-20.06	13.48	9.90	2.08	H		0.135	21.30			
		16-QAM	-21.05	12.49	9.90	2.08	H		0.107	20.31			
		64-QAM	-22.54	11.00	9.90	2.08	H		0.076	18.82			
		256-QAM	-24.58	8.96	9.90	2.08	H		0.048	16.78			
1775.0		PI/2 BPSK	-20.05	13.49	9.90	2.08	H	> 1.00	0.135	21.31		1	1
		QPSK	-20.06	13.48	9.90	2.08	H		0.135	21.30			
		16-QAM	-21.05	12.49	9.90	2.08	H		0.107	20.31			
		64-QAM	-22.54	11.00	9.90	2.08	H		0.076	18.82			
		256-QAM	-24.58	8.96	9.90	2.08	H		0.048	16.78			

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP			RB	
									W	W	dBm	Size	Offset
1717.5	Sub6 n66/ 15 MHz [15 kHz]	PI/2 BPSK	-19.12	14.24	9.60	2.00	H	< 1.00	0.153	21.84		1	39
		QPSK	-19.19	14.17	9.60	2.00	H		0.150	21.77			
		16-QAM	-20.26	13.10	9.60	2.00	H		0.117	20.70			
		64-QAM	-21.53	11.83	9.60	2.00	H		0.088	19.43			
		256-QAM	-23.68	9.68	9.60	2.00	H		0.053	17.28			
		PI/2 BPSK	-19.89	13.71	9.75	2.04	H	> 1.00	0.139	21.42		1	1
		QPSK	-19.90	13.70	9.75	2.04	H		0.138	21.41			
		16-QAM	-20.90	12.70	9.75	2.04	H		0.110	20.41			
		64-QAM	-22.39	11.21	9.75	2.04	H		0.078	18.92			
		256-QAM	-24.36	9.24	9.75	2.04	H		0.050	16.95			
1745.0		PI/2 BPSK	-20.00	13.54	9.90	2.08	H	> 1.00	0.137	21.36		1	39
		QPSK	-20.06	13.48	9.90	2.08	H		0.135	21.30			
		16-QAM	-21.04	12.50	9.90	2.08	H		0.108	20.32			
		64-QAM	-22.47	11.07	9.90	2.08	H		0.077	18.89			
		256-QAM	-24.44	9.10	9.90	2.08	H		0.049	16.92			

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP			RB	
									W	W	dBm	Size	Offset
1720.0	Sub6 n66/ 20 MHz [15 kHz]	PI/2 BPSK	-19.10	14.40	9.60	2.00	H	< 1.00	0.158	22.00		1	53
		QPSK	-19.14	14.36	9.60	2.00	H		0.157	21.96			
		16-QAM	-20.04	13.46	9.60	2.00	H		0.128	21.06			
		64-QAM	-21.66	11.84	9.60	2.00	H		0.088	19.44			
		256-QAM	-23.52	9.98	9.60	2.00	H		0.057	17.58			
		PI/2 BPSK	-19.72	13.88	9.75	2.04	H	> 1.00	0.144	21.59		1	1
		QPSK	-19.76	13.84	9.75	2.04	H		0.143	21.55			
		16-QAM	-20.78	12.82	9.75	2.04	H		0.113	20.53			
		64-QAM	-22.19	11.41	9.75	2.04	H		0.082	19.12			
		256-QAM	-24.18	9.42	9.75	2.04	H		0.052	17.13			
1745.0		PI/2 BPSK	-20.00	13.64	9.90	2.09	H	> 1.00	0.140	21.45		1	53
		QPSK	-20.02	13.62	9.90	2.09	H		0.139	21.43			
		16-QAM	-21.10	12.54	9.90	2.09	H		0.108	20.35			
		64-QAM	-22.57	11.07	9.90	2.09	H		0.077	18.88			
		256-QAM	-24.42	9.22	9.90	2.09	H		0.050	17.03			

8.2 RADIATED SPURIOUS EMISSIONS

- | | |
|--------------------------------------|------------------|
| <input type="checkbox"/> NR Band: | <u>N66</u> |
| <input type="checkbox"/> Bandwidth: | <u>20 MHz</u> |
| <input type="checkbox"/> Modulation: | <u>PI/2 BPSK</u> |
| <input type="checkbox"/> Distance: | <u>3 meters</u> |
| <input type="checkbox"/> SCS: | <u>15 kHz</u> |

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
344000 (1720.0)	3 440.00	-56.98	11.10	-57.93	2.97	H	-49.80	-13.00	1	53
	5 160.00	-59.55	11.00	-54.72	3.69	H	-47.41	-13.00		
	6 880.00	-60.81	10.80	-49.12	4.28	V	-42.60	-13.00		
	8 600.00	-62.17	10.40	-48.62	4.80	V	-43.02	-13.00		
	10 320.00	-62.43	11.10	-44.66	5.34	V	-38.90	-13.00		
349000 (1745.0)	3 490.00	-58.99	11.20	-60.43	3.00	H	-52.23	-13.00	1	1
	5 235.00	-59.62	11.10	-54.69	3.70	V	-47.29	-13.00		
	6 980.00	-60.34	10.90	-47.63	4.30	H	-41.03	-13.00		
	8 725.00	-62.89	10.30	-48.53	4.88	V	-43.11	-13.00		
	10 470.00	-63.33	11.30	-45.60	5.43	V	-39.73	-13.00		
354000 (1770.0)	3 540.00	-55.00	11.30	-56.80	3.02	H	-48.52	-13.00	1	53
	5 310.00	-59.53	11.40	-55.17	3.65	V	-47.42	-13.00		
	7 080.00	-60.19	10.70	-46.31	4.34	H	-39.95	-13.00		
	8 850.00	-61.87	10.50	-47.78	4.95	V	-42.23	-13.00		
	10 620.00	-63.25	11.20	-44.73	5.41	V	-38.94	-13.00		

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)		
Sub6 n66	5 MHz	1745.0	BPSK	25	0	4.14		
			QPSK			5.38		
			16-QAM			5.90		
			64-QAM			5.96		
			256-QAM			6.59		
	10 MHz		BPSK	50		4.31		
			QPSK			5.31		
			16-QAM			5.84		
			64-QAM			5.86		
			256-QAM			6.52		
	15 MHz		BPSK	75		4.03		
			QPSK			5.24		
			16-QAM			5.80		
			64-QAM			6.00		
			256-QAM			6.57		
	20 MHz		BPSK	100		4.08		
			QPSK			5.29		
			16-QAM			5.86		
			64-QAM			6.01		
			256-QAM			6.59		

Note:

- Plots of the EUT's Peak- to- Average Ratio are shown Page 69 ~ 88.

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)		
Sub6 n66	5 MHz	1745.0	BPSK	25	0	4.5504		
			QPSK			4.5263		
			16-QAM			4.5216		
			64-QAM			4.5463		
			256-QAM			4.5301		
	10 MHz		BPSK	50		9.0074		
			QPSK			8.9900		
			16-QAM			8.9862		
			64-QAM			8.9866		
			256-QAM			8.9834		
	15 MHz		BPSK	75		13.450		
			QPSK			13.418		
			16-QAM			13.448		
			64-QAM			13.430		
			256-QAM			13.480		
	20 MHz		BPSK	100		17.937		
			QPSK			17.880		
			16-QAM			17.909		
			64-QAM			17.924		
			256-QAM			17.921		

Note:

- Plots of the EUT's Occupied Bandwidth are shown Page 49 ~ 68.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
Sub6 n66	5	1712.5	8.8644	29.815	-70.227	-40.412	-13.00
		1745.0	8.8091	29.815	-71.097	-41.282	
		1777.5	5.1994	29.815	-70.775	-40.960	
	10	1715.0	9.7647	29.815	-70.374	-40.559	
		1745.0	9.0957	29.815	-70.976	-41.161	
		1775.0	4.0115	29.200	-70.226	-41.026	
	15	1717.5	8.2991	29.815	-70.627	-40.812	
		1745.0	8.0000	29.815	-71.037	-41.222	
		1772.5	5.2079	29.815	-70.883	-41.068	
	20	1720.0	3.7568	29.200	-70.125	-40.925	
		1745.0	8.8609	29.815	-70.338	-40.523	
		1770.0	9.6959	29.815	-70.227	-40.412	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 113 ~ 136.
2. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
3. Factor(dB) = Cable Loss + Ext. Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	26.494
1 – 5	29.200
5 – 10	29.815
10 – 15	30.340
15 – 20	30.713
Above 20	31.355

8.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 89 ~ 112.

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

- BandWidth: 5 MHz
 Voltage(100 %): 4.200 VDC
 Batt. Endpoint: 3.400 VDC
 LIMIT: Emission must remain in band

Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
1712.5	100 %	+20(Ref)	1712 500 001	0.0	0.000 000	0.000
	100 %	-30	1712 500 001	0.5	0.000 000	0.000
	100 %	-20	1712 500 000	-0.7	0.000 000	0.000
	100 %	-10	1712 500 002	0.7	0.000 000	0.000
	100 %	0	1712 500 001	-0.2	0.000 000	0.000
	100 %	+10	1712 500 002	1.4	0.000 000	0.001
	100 %	+30	1712 500 001	0.6	0.000 000	0.000
	100 %	+40	1712 500 001	0.7	0.000 000	0.000
	100 %	+50	1712 500 002	1.0	0.000 000	0.001
	Batt. Endpoint	+20	1712 500 001	0.0	0.000 000	0.000
1777.5	100 %	+20(Ref)	1777 499 999	0.0	0.000 000	0.000
	100 %	-30	1777 499 999	-0.1	0.000 000	0.000
	100 %	-20	1777 499 999	0.0	0.000 000	0.000
	100 %	-10	1777 499 999	-0.5	0.000 000	0.000
	100 %	0	1777 499 999	-0.2	0.000 000	0.000
	100 %	+10	1777 499 998	-1.6	0.000 000	-0.001
	100 %	+30	1777 499 999	0.3	0.000 000	0.000
	100 %	+40	1777 500 000	0.8	0.000 000	0.000
	100 %	+50	1777 499 999	-0.6	0.000 000	0.000
	Batt. Endpoint	+20	1777 499 998	-0.7	0.000 000	0.000

BandWidth: 10 MHz
 Voltage(100 %): 4.200 VDC
 Batt. Endpoint: 3.400 VDC
 LIMIT: Emission must remain in band

Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
1715.0	100 %	+20(Ref)	1715 000 001	0.0	0.000 000	0.000
	100 %	-30	1715 000 001	0.0	0.000 000	0.000
	100 %	-20	1715 000 000	-0.9	0.000 000	-0.001
	100 %	-10	1715 000 001	-0.2	0.000 000	0.000
	100 %	0	1715 000 000	-0.5	0.000 000	0.000
	100 %	+10	1715 000 001	-0.2	0.000 000	0.000
	100 %	+30	1715 000 001	0.3	0.000 000	0.000
	100 %	+40	1715 000 001	0.3	0.000 000	0.000
	100 %	+50	1715 000 002	0.8	0.000 000	0.000
	Batt. Endpoint	+20	1715 000 001	0.0	0.000 000	0.000
1775.0	100 %	+20(Ref)	1775 000 000	0.0	0.000 000	0.000
	100 %	-30	1775 000 000	0.0	0.000 000	0.000
	100 %	-20	1775 000 000	-0.7	0.000 000	0.000
	100 %	-10	1775 000 000	0.1	0.000 000	0.000
	100 %	0	1775 000 000	-0.7	0.000 000	0.000
	100 %	+10	1775 000 001	0.5	0.000 000	0.000
	100 %	+30	1775 000 000	-0.2	0.000 000	0.000
	100 %	+40	1775 000 001	0.4	0.000 000	0.000
	100 %	+50	1775 000 000	-0.6	0.000 000	0.000
	Batt. Endpoint	+20	1775 000 000	0.1	0.000 000	0.000

BandWidth: 15 MHz
 Voltage(100 %): 4.200 VDC
 Batt. Endpoint: 3.400 VDC
 LIMIT: Emission must remain in band

Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
1717.5	100 %	+20(Ref)	1717 500 000	0.0	0.000 000	0.000
	100 %	-30	1717 500 000	0.4	0.000 000	0.000
	100 %	-20	1717 500 000	-0.4	0.000 000	0.000
	100 %	-10	1717 500 000	-0.2	0.000 000	0.000
	100 %	0	1717 499 999	-0.6	0.000 000	0.000
	100 %	+10	1717 500 001	1.2	0.000 000	0.001
	100 %	+30	1717 500 000	-0.1	0.000 000	0.000
	100 %	+40	1717 500 000	-0.3	0.000 000	0.000
	100 %	+50	1717 499 999	-1.1	0.000 000	-0.001
	Batt. Endpoint	+20	1717 500 000	-0.1	0.000 000	0.000
1772.5	100 %	+20(Ref)	1772 500 001	0.0	0.000 000	0.000
	100 %	-30	1772 500 001	0.5	0.000 000	0.000
	100 %	-20	1772 500 002	1.0	0.000 000	0.001
	100 %	-10	1772 500 002	0.7	0.000 000	0.000
	100 %	0	1772 500 002	1.6	0.000 000	0.001
	100 %	+10	1772 500 001	0.5	0.000 000	0.000
	100 %	+30	1772 500 001	0.3	0.000 000	0.000
	100 %	+40	1772 500 002	1.4	0.000 000	0.001
	100 %	+50	1772 500 003	1.9	0.000 000	0.001
	Batt. Endpoint	+20	1772 500 001	0.6	0.000 000	0.000

BandWidth: 20 MHz
 Voltage(100 %): 4.200 VDC
 Batt. Endpoint: 3.400 VDC
 LIMIT: Emission must remain in band

Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
1720.0	100 %	+20(Ref)	1720 000 000	0.0	0.000 000	0.000
	100 %	-30	1719 999 999	-0.8	0.000 000	0.000
	100 %	-20	1719 999 999	-1.0	0.000 000	-0.001
	100 %	-10	1719 999 999	-0.7	0.000 000	0.000
	100 %	0	1720 000 001	0.5	0.000 000	0.000
	100 %	+10	1720 000 002	1.4	0.000 000	0.001
	100 %	+30	1720 000 000	-0.4	0.000 000	0.000
	100 %	+40	1720 000 001	0.8	0.000 000	0.000
	100 %	+50	1720 000 001	0.8	0.000 000	0.000
	Batt. Endpoint	+20	1720 000 000	-0.1	0.000 000	0.000
1770.0	100 %	+20(Ref)	1770 000 000	0.0	0.000 000	0.000
	100 %	-30	1769 999 999	-0.4	0.000 000	0.000
	100 %	-20	1770 000 000	0.1	0.000 000	0.000
	100 %	-10	1770 000 000	-0.4	0.000 000	0.000
	100 %	0	1769 999 999	-0.7	0.000 000	0.000
	100 %	+10	1769 999 999	-0.5	0.000 000	0.000
	100 %	+30	1770 000 001	0.6	0.000 000	0.000
	100 %	+40	1770 000 000	0.1	0.000 000	0.000
	100 %	+50	1770 000 000	0.1	0.000 000	0.000
	Batt. Endpoint	+20	1770 000 000	0.4	0.000 000	0.000

9. TEST DATA (NSA)

9.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP			RB	
									W	W	dBm	Size	Offset
1712.5	Sub6 n66/ 5 MHz [15 kHz]	PI/2 BPSK	-18.92	14.44	9.60	2.00	H	< 1.00	0.160	22.04		1	12
		QPSK	-18.94	14.42	9.60	2.00	H		0.159	22.02			
		16-QAM	-19.90	13.46	9.60	2.00	H		0.128	21.06			
		64-QAM	-21.36	12.00	9.60	2.00	H		0.091	19.60			
		256-QAM	-23.40	9.96	9.60	2.00	H		0.057	17.56			
1745.0	Sub6 n66/ 5 MHz [15 kHz]	PI/2 BPSK	-19.64	13.96	9.75	2.04	H	< 1.00	0.147	21.67		1	1
		QPSK	-19.66	13.94	9.75	2.04	H		0.146	21.65			
		16-QAM	-20.67	12.93	9.75	2.04	H		0.116	20.64			
		64-QAM	-22.16	11.44	9.75	2.04	H		0.082	19.15			
		256-QAM	-24.20	9.40	9.75	2.04	H		0.051	17.11			
1777.5	Sub6 n66/ 5 MHz [15 kHz]	PI/2 BPSK	-18.41	15.13	9.90	2.08	H	< 1.00	0.197	22.95		1	12
		QPSK	-18.46	15.08	9.90	2.08	H		0.195	22.90			
		16-QAM	-19.40	14.14	9.90	2.08	H		0.157	21.96			
		64-QAM	-20.90	12.64	9.90	2.08	H		0.111	20.46			
		256-QAM	-22.90	10.64	9.90	2.08	H		0.070	18.46			

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP			RB	
									W	W	dBm	Size	Offset
1715.0	Sub6 n66/ 10 MHz [15 kHz]	PI/2 BPSK	-19.00	14.36	9.60	2.00	H	< 1.00	0.157	21.96		1	26
		QPSK	-19.03	14.33	9.60	2.00	H		0.156	21.93			
		16-QAM	-19.97	13.39	9.60	2.00	H		0.126	20.99			
		64-QAM	-21.47	11.89	9.60	2.00	H		0.089	19.49			
		256-QAM	-23.43	9.93	9.60	2.00	H		0.057	17.53			
		PI/2 BPSK	-19.45	14.15	9.75	2.04	H	> 1.00	0.153	21.86		1	1
		QPSK	-19.50	14.10	9.75	2.04	H		0.152	21.81			
		16-QAM	-20.49	13.11	9.75	2.04	H		0.121	20.82			
		64-QAM	-21.99	11.61	9.75	2.04	H		0.086	19.32			
		256-QAM	-24.07	9.53	9.75	2.04	H		0.053	17.24			
1745.0		PI/2 BPSK	-19.16	14.38	9.90	2.08	H	> 1.00	0.166	22.20		1	1
		QPSK	-19.27	14.27	9.90	2.08	H		0.162	22.09			
		16-QAM	-19.84	13.70	9.90	2.08	H		0.142	21.52			
		64-QAM	-21.00	12.54	9.90	2.08	H		0.109	20.36			
		256-QAM	-23.05	10.49	9.90	2.08	H		0.068	18.31			

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP			RB	
									W	W	dBm	Size	Offset
1717.5	Sub6 n66/ 15 MHz [15 kHz]	PI/2 BPSK	-18.90	14.46	9.60	2.00	H	< 1.00	0.161	22.06		1	39
		QPSK	-18.91	14.45	9.60	2.00	H		0.160	22.05			
		16-QAM	-19.92	13.44	9.60	2.00	H		0.127	21.04			
		64-QAM	-21.40	11.96	9.60	2.00	H		0.090	19.56			
		256-QAM	-23.42	9.94	9.60	2.00	H		0.057	17.54			
		PI/2 BPSK	-19.60	14.00	9.75	2.04	H		0.148	21.71			
1745.0	Sub6 n66/ 15 MHz [15 kHz]	QPSK	-19.62	13.98	9.75	2.04	H	< 1.00	0.148	21.69		1	1
		16-QAM	-20.59	13.01	9.75	2.04	H		0.118	20.72			
		64-QAM	-22.09	11.51	9.75	2.04	H		0.084	19.22			
		256-QAM	-24.08	9.52	9.75	2.04	H		0.053	17.23			
		PI/2 BPSK	-18.68	14.86	9.90	2.08	H		0.185	22.68			
		QPSK	-18.85	14.69	9.90	2.08	H		0.178	22.51			
1772.5	Sub6 n66/ 15 MHz [15 kHz]	16-QAM	-19.50	14.04	9.90	2.08	H	< 1.00	0.153	21.86		1	39
		64-QAM	-20.96	12.58	9.90	2.08	H		0.110	20.40			
		256-QAM	-23.00	10.54	9.90	2.08	H		0.069	18.36			

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP			RB	
									W	W	dBm	Size	Offset
1720.0	Sub6 n66/ 20 MHz [15 kHz]	PI/2 BPSK	-18.82	14.68	9.60	2.00	H	< 1.00	0.169	22.28		1	53
		QPSK	-18.85	14.65	9.60	2.00	H		0.168	22.25			
		16-QAM	-19.87	13.63	9.60	2.00	H		0.133	21.23			
		64-QAM	-21.38	12.12	9.60	2.00	H		0.094	19.72			
		256-QAM	-23.40	10.10	9.60	2.00	H		0.059	17.70			
		PI/2 BPSK	-19.36	14.24	9.75	2.04	H	> 1.00	0.157	21.95		1	1
		QPSK	-19.38	14.22	9.75	2.04	H		0.156	21.93			
		16-QAM	-20.40	13.20	9.75	2.04	H		0.123	20.91			
		64-QAM	-21.90	11.70	9.75	2.04	H		0.087	19.41			
		256-QAM	-23.89	9.71	9.75	2.04	H		0.055	17.42			
1745.0		PI/2 BPSK	-19.16	14.48	9.90	2.09	H	> 1.00	0.169	22.29		1	53
		QPSK	-19.20	14.44	9.90	2.09	H		0.168	22.25			
		16-QAM	-19.73	13.91	9.90	2.09	H		0.149	21.72			
		64-QAM	-20.99	12.65	9.90	2.09	H		0.111	20.46			
		256-QAM	-22.96	10.68	9.90	2.09	H		0.071	18.49			

9.2 RADIATED SPURIOUS EMISSIONS

- | | |
|---------------------------------------|------------------|
| <input type="checkbox"/> NR Band: | <u>N66</u> |
| <input type="checkbox"/> Anchor Band: | <u>B5</u> |
| <input type="checkbox"/> Bandwidth: | <u>5 MHz</u> |
| <input type="checkbox"/> Modulation: | <u>PI/2 BPSK</u> |
| <input type="checkbox"/> Distance: | <u>3 meters</u> |
| <input type="checkbox"/> SCS: | <u>15 kHz</u> |

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
342500 (1712.5)	3 425.00	-54.06	11.10	-55.01	2.96	V	-46.87	-13.00	1	12
	5 137.50	-53.79	10.80	-48.52	3.62	H	-41.34	-13.00		
	6 850.00	-63.47	10.80	-52.52	4.32	H	-46.04	-13.00		
	8 562.50	-59.29	10.50	-45.53	4.88	H	-39.91	-13.00		
	10 275.00	-63.51	11.00	-46.17	5.35	H	-40.52	-13.00		
349000 (1745.0)	3 490.00	-55.59	11.20	-57.03	3.00	H	-48.83	-13.00	1	1
	5 235.00	-52.00	11.10	-47.07	3.70	H	-39.67	-13.00		
	6 980.00	-61.65	10.90	-48.94	4.30	H	-42.34	-13.00		
	8 725.00	-61.25	10.30	-46.89	4.88	H	-41.47	-13.00		
	10 470.00	-62.42	11.30	-44.69	5.43	H	-38.82	-13.00		
355500 (1777.5)	3 555.00	-54.50	11.40	-56.47	3.02	H	-48.09	-13.00	1	12
	5 332.50	-57.05	11.40	-52.00	3.73	H	-44.33	-13.00		
	7 110.00	-63.66	10.50	-49.72	4.36	H	-43.58	-13.00		
	8 887.50	-61.82	10.50	-47.78	4.92	H	-42.20	-13.00		
	10 665.00	-58.58	11.10	-39.26	5.48	V	-33.64	-13.00		

- ENDC-Mode : 5A(10 MHz)-n66A(5 MHz)

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)
20525 (836.5)	1673.00	-58.98	9.52	-68.63	2.03	H	-61.14	-13.00
	2509.50	-60.45	10.28	-65.43	2.51	V	-57.66	-13.00
	3346.00	-60.92	11.28	-63.70	2.99	H	-55.41	-13.00

9.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)		
Sub6 n66	5 MHz	1745.0	BPSK	25	0	4.59		
			QPSK			5.45		
			16-QAM			6.23		
			64-QAM			6.59		
			256-QAM			6.66		
	10 MHz		BPSK	50		4.61		
			QPSK			5.44		
			16-QAM			6.19		
			64-QAM			6.50		
			256-QAM			6.72		
	15 MHz		BPSK	75		4.74		
			QPSK			5.40		
			16-QAM			6.21		
			64-QAM			6.51		
			256-QAM			6.54		
	20 MHz		BPSK	100		4.29		
			QPSK			5.49		
			16-QAM			6.24		
			64-QAM			6.38		
			256-QAM			6.64		

Note:

- Plots of the EUT's Peak- to- Average Ratio are shown Page 158 ~ 177.

9.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)		
Sub6 n66	5 MHz	1745.0	BPSK	25	0	4.5226		
			QPSK			4.5224		
			16-QAM			4.5094		
			64-QAM			4.5156		
			256-QAM			4.4890		
	10 MHz		BPSK	50		8.9843		
			QPSK			8.9900		
			16-QAM			8.9961		
			64-QAM			8.9844		
			256-QAM			8.9962		
	15 MHz		BPSK	75		13.482		
			QPSK			13.435		
			16-QAM			13.499		
			64-QAM			13.469		
			256-QAM			13.444		
	20 MHz		BPSK	100		17.913		
			QPSK			17.953		
			16-QAM			17.916		
			64-QAM			17.954		
			256-QAM			17.847		

Note:

- Plots of the EUT's Occupied Bandwidth are shown Page 138 ~ 157.

9.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
Sub6 n66	5	1712.5	4.9083	30.200	-70.731	-40.531	-13.00
		1745.0	8.2662	30.815	-70.438	-39.623	
		1777.5	9.7178	30.815	-71.041	-40.226	
	10	1715.0	8.8544	30.815	-69.961	-39.146	
		1745.0	4.5678	30.200	-70.602	-40.402	
		1775.0	9.7084	30.815	-70.475	-39.660	
	15	1717.5	3.7224	30.200	-70.667	-40.467	
		1745.0	8.2951	30.815	-70.890	-40.075	
		1772.5	4.0414	30.200	-70.305	-40.105	
	20	1720.0	9.4367	30.815	-70.720	-39.905	
		1745.0	8.6157	30.815	-70.717	-39.902	
		1770.0	6.0349	30.815	-70.288	-39.473	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 202 ~ 225.
2. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
3. Factor(dB) = Cable Loss + Ext. Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	27.494
1 – 5	30.200
5 – 10	30.815
10 – 15	31.340
15 – 20	31.713
Above 20	32.355

9.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 178 ~ 201.

9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

- BandWidth: 5 MHz
 Voltage(100 %): 4.200 VDC
 Batt. Endpoint: 3.400 VDC
 LIMIT: Emission must remain in band

Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
1712.5	100 %	+20(Ref)	1712 500 001	0.0	0.000 000	0.000
	100 %	-30	1712 500 000	-0.8	0.000 000	0.000
	100 %	-20	1712 500 001	-0.3	0.000 000	0.000
	100 %	-10	1712 500 001	0.2	0.000 000	0.000
	100 %	0	1712 500 002	0.8	0.000 000	0.000
	100 %	+10	1712 500 002	0.3	0.000 000	0.000
	100 %	+30	1712 500 003	2.3	0.000 000	0.001
	100 %	+40	1712 500 002	1.2	0.000 000	0.001
	100 %	+50	1712 500 002	1.2	0.000 000	0.001
	Batt. Endpoint	+20	1712 500 003	1.9	0.000 000	0.001
1777.5	100 %	+20(Ref)	1777 499 999	0.0	0.000 000	0.000
	100 %	-30	1777 500 000	1.2	0.000 000	0.001
	100 %	-20	1777 499 998	-1.3	0.000 000	-0.001
	100 %	-10	1777 499 999	0.0	0.000 000	0.000
	100 %	0	1777 499 999	-0.6	0.000 000	0.000
	100 %	+10	1777 499 998	-1.2	0.000 000	-0.001
	100 %	+30	1777 499 999	-0.5	0.000 000	0.000
	100 %	+40	1777 500 001	1.6	0.000 000	0.001
	100 %	+50	1777 499 998	-1.1	0.000 000	-0.001
	Batt. Endpoint	+20	1777 500 000	0.8	0.000 000	0.000

BandWidth: 10 MHz
 Voltage(100 %): 4.200 VDC
 Batt. Endpoint: 3.400 VDC
 LIMIT: Emission must remain in band

Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
1715.0	100 %	+20(Ref)	1715 000 001	0.0	0.000 000	0.000
	100 %	-30	1715 000 002	1.5	0.000 000	0.001
	100 %	-20	1715 000 003	2.6	0.000 000	0.002
	100 %	-10	1715 000 002	1.2	0.000 000	0.001
	100 %	0	1715 000 000	-0.7	0.000 000	0.000
	100 %	+10	1715 000 000	-0.2	0.000 000	0.000
	100 %	+30	1715 000 000	-0.8	0.000 000	0.000
	100 %	+40	1715 000 000	-0.5	0.000 000	0.000
	100 %	+50	1715 000 001	0.1	0.000 000	0.000
	Batt. Endpoint	+20	1714 999 999	-1.8	0.000 000	-0.001
1775.0	100 %	+20(Ref)	1775 000 000	0.0	0.000 000	0.000
	100 %	-30	1774 999 999	-1.0	0.000 000	-0.001
	100 %	-20	1775 000 000	0.5	0.000 000	0.000
	100 %	-10	1774 999 999	-1.0	0.000 000	-0.001
	100 %	0	1775 000 001	1.1	0.000 000	0.001
	100 %	+10	1774 999 999	-0.8	0.000 000	0.000
	100 %	+30	1775 000 000	0.2	0.000 000	0.000
	100 %	+40	1775 000 000	0.5	0.000 000	0.000
	100 %	+50	1774 999 999	-0.9	0.000 000	-0.001
	Batt. Endpoint	+20	1775 000 000	-0.1	0.000 000	0.000

BandWidth: 15 MHz
 Voltage(100 %): 4.200 VDC
 Batt. Endpoint: 3.400 VDC
 LIMIT: Emission must remain in band

Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
1717.5	100 %	+20(Ref)	1717 500 000	0.0	0.000 000	0.000
	100 %	-30	1717 500 000	-0.4	0.000 000	0.000
	100 %	-20	1717 499 999	-0.8	0.000 000	0.000
	100 %	-10	1717 500 000	-0.2	0.000 000	0.000
	100 %	0	1717 500 000	-0.2	0.000 000	0.000
	100 %	+10	1717 500 000	0.2	0.000 000	0.000
	100 %	+30	1717 500 001	0.5	0.000 000	0.000
	100 %	+40	1717 500 001	0.6	0.000 000	0.000
	100 %	+50	1717 500 001	1.0	0.000 000	0.001
	Batt. Endpoint	+20	1717 500 002	2.0	0.000 000	0.001
1772.5	100 %	+20(Ref)	1772 500 001	0.0	0.000 000	0.000
	100 %	-30	1772 500 001	0.1	0.000 000	0.000
	100 %	-20	1772 500 000	-0.6	0.000 000	0.000
	100 %	-10	1772 500 001	0.4	0.000 000	0.000
	100 %	0	1772 500 001	0.2	0.000 000	0.000
	100 %	+10	1772 500 001	0.5	0.000 000	0.000
	100 %	+30	1772 500 001	0.6	0.000 000	0.000
	100 %	+40	1772 500 000	-0.3	0.000 000	0.000
	100 %	+50	1772 500 001	0.4	0.000 000	0.000
	Batt. Endpoint	+20	1772 500 001	0.3	0.000 000	0.000

BandWidth: 20 MHz
 Voltage(100 %): 4.200 VDC
 Batt. Endpoint: 3.400 VDC
 LIMIT: Emission must remain in band

Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
1720.0	100 %	+20(Ref)	1719 999 999	0.0	0.000 000	0.000
	100 %	-30	1719 999 998	-1.2	0.000 000	-0.001
	100 %	-20	1719 999 999	-0.7	0.000 000	0.000
	100 %	-10	1720 000 000	0.2	0.000 000	0.000
	100 %	0	1719 999 998	-0.8	0.000 000	0.000
	100 %	+10	1719 999 999	-0.7	0.000 000	0.000
	100 %	+30	1719 999 999	0.0	0.000 000	0.000
	100 %	+40	1719 999 999	-0.6	0.000 000	0.000
	100 %	+50	1719 999 998	-1.0	0.000 000	-0.001
	Batt. Endpoint	+20	1720 000 000	0.3	0.000 000	0.000
1770.0	100 %	+20(Ref)	1770 000 000	0.0	0.000 000	0.000
	100 %	-30	1770 000 001	0.3	0.000 000	0.000
	100 %	-20	1770 000 001	1.0	0.000 000	0.001
	100 %	-10	1770 000 001	0.5	0.000 000	0.000
	100 %	0	1770 000 002	1.5	0.000 000	0.001
	100 %	+10	1770 000 001	0.3	0.000 000	0.000
	100 %	+30	1770 000 001	0.7	0.000 000	0.000
	100 %	+40	1770 000 001	0.5	0.000 000	0.000
	100 %	+50	1770 000 001	0.4	0.000 000	0.000
	Batt. Endpoint	+20	1770 000 000	0.0	0.000 000	0.000

10. TEST PLOTS (SA)


Sub6 n66. Occupied Bandwidth Plot (5 M BW Ch.349000 BPSK Full RB)




Sub6 n66. Occupied Bandwidth Plot (5 M BW Ch.349000 QPSK Full RB)



Sub6 n66. Occupied Bandwidth Plot (5 M BW Ch.349000 16QAM Full RB)



Sub6 n66. Occupied Bandwidth Plot (5 M BW Ch.349000 64QAM Full RB)



Sub6 n66. Occupied Bandwidth Plot (5 M BW Ch.349000 256QAM Full RB)




Sub6 n66. Occupied Bandwidth Plot (10 M BW Ch.349000 BPSK Full RB)



Sub6 n66. Occupied Bandwidth Plot (10 M BW Ch.349000 QPSK Full RB)




Sub6 n66. Occupied Bandwidth Plot (10 M BW Ch.349000 16QAM Full RB)




Sub6 n66. Occupied Bandwidth Plot (10 M BW Ch.349000 64QAM Full RB)




Sub6 n66. Occupied Bandwidth Plot (10 M BW Ch.349000 256QAM Full RB)



Sub6 n66. Occupied Bandwidth Plot (15 M BW Ch.349000 BPSK Full RB)



Sub6 n66. Occupied Bandwidth Plot (15 M BW Ch.349000 QPSK Full RB)




Sub6 n66. Occupied Bandwidth Plot (15 M BW Ch.349000 16QAM Full RB)



Sub6 n66. Occupied Bandwidth Plot (15 M BW Ch.349000 64QAM Full RB)



Sub6 n66. Occupied Bandwidth Plot (15 M BW Ch.349000 256QAM Full RB)




Sub6 n66. Occupied Bandwidth Plot (20 M BW Ch.349000 BPSK Full RB)




Sub6 n66. Occupied Bandw idth Plot (20 M BW Ch.349000 QPSK Full RB)




Sub6 n66. Occupied Bandwidth Plot (20 M BW Ch.349000 16QAM Full RB)



Sub6 n66. Occupied Bandwidth Plot (20 M BW Ch.349000 64QAM Full RB)



Sub6 n66. Occupied Bandwidth Plot (20 M BW Ch.349000 256QAM Full RB)



















Sub6 n66. PAR Plot (10 M BW_Ch.349000_64QAM_Full RB)


















Sub6 n66. PAR Plot (20 M BW_Ch.349000_ BPSK_ Full RB)



Sub6 n66. PAR Plot (20 M BW_Ch.349000_QPSK_Full RB)



Sub6 n66. PAR Plot (20 M BW_Ch.349000_16QAM_Full RB)




Sub6 n66. PAR Plot (20 M BW_Ch.349000_64QAM_Full RB)






Sub6 n66. Lower Band Edge Plot (5 M BW Ch.342500 BPSK RB 1, Offset 0) -1




Sub6 n66. Lower Band Edge Plot (5 M BW Ch.342500 BPSK Full RB) -2



Sub6 n66. Lower Extended Band Edge Plot (5 M BW Ch.342500 BPSK_ Full RB) -3




Sub6 n66. Lower Band Edge Plot (10 M BW Ch.343000 BPSK RB 1, Offset 0) -1




Sub6 n66. Lower Band Edge Plot (10 M BW Ch.343000 BPSK Full RB) -2



Sub6 n66. Lower Extended Band Edge Plot (10 M BW Ch.343000 BPSK_Full RB) -3




Sub6 n66. Lower Band Edge Plot (15 M BW Ch.343500 BPSK RB 1, Offset 0) -1




Sub6 n66. Lower Band Edge Plot (15 M BW Ch.343500 BPSK Full RB) -2



Sub6 n66. Lower Extended Band Edge Plot (15 M BW Ch.343500 BPSK_Full RB) -3



Sub6 n66. Lower Band Edge Plot (20 M BW Ch.344000 BPSK RB 1, Offset 0) -1




Sub6 n66. Lower Band Edge Plot (20 M BW Ch.344000 BPSK Full RB) -2



Sub6 n66. Lower Extended Band Edge Plot (20 M BW Ch.344000 BPSK_ Full RB) -3




Sub6 n66. Upper Band Edge Plot (5 M BW Ch.355500 BPSK_RB1_Offset 24) -1




Sub6 n66. Upper Band Edge Plot (5 M BW Ch.355500 BPSK_ Full RB) -2



Sub6 n66. Upper Extended Band Edge Plot (5 M BW Ch.355500 BPSK_ Full RB) -3




Sub6 n66. Upper Band Edge Plot (10 M BW Ch.355000 BPSK_RB1_Offset 51) -1



Sub6 n66. Upper Band Edge Plot (10 M BW Ch.355000 BPSK_ Full RB) -2



Sub6 n66. Upper Extended Band Edge Plot (10 M BW Ch.355000 BPSK_Full RB) -3



Sub6 n66. Upper Band Edge Plot (15 M BW Ch.354500 BPSK_RB1_Offset 78) -1



Sub6 n66. Upper Band Edge Plot (15 M BW Ch.354500 BPSK_ Full RB) -2



Sub6 n66. Upper Extended Band Edge Plot (15 M BW Ch.354500 BPSK_Full RB) -3



Sub6 n66. Upper Band Edge Plot (20 M BW Ch.354000 BPSK_RB1_Offset 105) -1



Sub6 n66. Upper Band Edge Plot (20 M BW Ch.354000 BPSK_ Full RB) -2




Sub6 n66. Upper Extended Band Edge Plot (20 M BW Ch.354000 BPSK_Full RB) -3



Sub6 n66. Conducted Spurious Plot_1 (342500ch_5 MHz_BPSK_RB 1_1)




Sub6 n66. Conducted Spurious Plot_2 (342500ch_5 MHz_BPSK_RB 1_1)



Sub6 n66. Conducted Spurious Plot_1 (349000ch_5 MHz_BPSK_RB 1_1)




Sub6 n66. Conducted Spurious Plot_2 (349000ch_5 MHz_BPSK_RB 1_1)




Sub6 n66. Conducted Spurious Plot_1 (355500ch_5 MHz_BPSK_RB 1_1)




Sub6 n66. Conducted Spurious Plot_2 (355500ch_5 MHz_BPSK_RB 1_1)



Sub6 n66. Conducted Spurious Plot_1 (343000ch_10 MHz_BPSK_RB 1_1)




Sub6 n66. Conducted Spurious Plot_2 (343000ch_10 MHz_BPSK_RB 1_1)



Sub6 n66. Conducted Spurious Plot_1 (349000ch_10 MHz_BPSK_RB 1_1)




Sub6 n66. Conducted Spurious Plot_2 (349000ch_10 MHz_BPSK_RB 1_1)




Sub6 n66. Conducted Spurious Plot_1 (355000ch_10 MHz_BPSK_RB 1_1)



Sub6 n66. Conducted Spurious Plot_2 (355000ch_10 MHz_BPSK_RB 1_1)




Sub6 n66. Conducted Spurious Plot_1 (343500ch_15 MHz_BPSK_RB 1_1)




Sub6 n66. Conducted Spurious Plot_2 (343500ch_15 MHz_BPSK_RB 1_1)




Sub6 n66. Conducted Spurious Plot_1 (349000ch_15 MHz_BPSK_RB 1_1)




Sub6 n66. Conducted Spurious Plot_2 (349000ch_15 MHz_BPSK_RB 1_1)



Sub6 n66. Conducted Spurious Plot_1 (354500ch_15 MHz_BPSK_RB 1_1)



Sub6 n66. Conducted Spurious Plot_2 (354500ch_15 MHz_BPSK_RB 1_1)



Sub6 n66. Conducted Spurious Plot_1 (344000ch_20 MHz_BPSK_RB 1_1)




Sub6 n66. Conducted Spurious Plot_2 (344000ch_20 MHz_BPSK_RB 1_1)




Sub6 n66. Conducted Spurious Plot_1 (349000ch_20 MHz_BPSK_RB 1_1)




Sub6 n66. Conducted Spurious Plot_2 (349000ch_20 MHz_BPSK_RB 1_1)



Sub6 n66. Conducted Spurious Plot_1 (354000ch_20 MHz_BPSK_RB 1_1)



Sub6 n66. Conducted Spurious Plot_2 (354000ch_20 MHz_BPSK_RB 1_1)



11. TEST PLOTS (NSA)


Sub6 n66. Occupied Bandwidth Plot (5 M BW Ch.349000 BPSK Full RB)



Sub6 n66. Occupied Bandwidth Plot (5 M BW Ch.349000 QPSK Full RB)




Sub6 n66. Occupied Bandwidth Plot (5 M BW Ch.349000 16QAM Full RB)



Sub6 n66. Occupied Bandwidth Plot (5 M BW Ch.349000 64QAM Full RB)




Sub6 n66. Occupied Bandwidth Plot (5 M BW Ch.349000 256QAM Full RB)



Sub6 n66. Occupied Bandwidth Plot (10 M BW Ch.349000 BPSK Full RB)



Sub6 n66. Occupied Bandwidth Plot (10 M BW Ch.349000 QPSK Full RB)



Sub6 n66. Occupied Bandwidth Plot (10 M BW Ch.349000 16QAM Full RB)

