

FCC DTS REPORT

Certification

Applicant Name:
SAMSUNG Electronics Co., Ltd.

Address:
129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Date of Issue:
December 18, 2023

Test Site/Location:
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA

Report No.: HCT-RF-2312-FC008

FCC ID: A3LSMM156B

APPLICANT: SAMSUNG Electronics Co., Ltd.

Model: SM-M156B/DSN

Additional Model: -

EUT Type: Mobile Phone

Average. RF Output Power: 802.11b : 18.54 dBm, 802.11g : 16.68 dBm, 802.11n(HT20) : 16.58 dBm

Frequency Range: 2 412 MHz ~ 2 472 MHz

Modulation type: CCK/DSSS/OFDM

FCC Classification: Digital Transmission System(DTS)

FCC Rule Part(s): Part 15.247

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

REVIEWED BY



Report prepared by : Sang Hoon Lee
Engineer of Telecommunication Testing Center

Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.
This test results were applied only to the test methods required by the standard.

Test Report Statement:

The above Test Report is not related to the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA.

The report shall not be reproduced except in full(only partly) without approval of the laboratory.



HCT CO., LTD.

Report No.: HCT-RF-2312-FC008

FCC ID: A3LSMM156B

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2312-FC008	December 18, 2023	- First Approval Report

Table of Contents

REVIEWED BY	2
1. EUT DESCRIPTION	5
2. TEST METHODOLOGY	6
EUT CONFIGURATION	6
EUT EXERCISE	6
GENERAL TEST PROCEDURES	6
DESCRIPTION OF TEST MODES	6
3. INSTRUMENT CALIBRATION.....	7
4. FACILITIES AND ACCREDITATIONS	7
FACILITIES	7
EQUIPMENT	7
5. ANTENNA REQUIREMENTS	8
6. MEASUREMENT UNCERTAINTY	8
7. DESCRIPTION OF TESTS.....	9
8. SUMMARY TEST OF RESULTS	24
9. TEST RESULT	25
9.1 DUTY CYCLE.....	25
9.2 6 dB BANDWIDTH	27
9.3 OUTPUT POWER	29
9.4 POWER SPECTRAL DENSITY	31
9.5 BAND EDGE / CONDUCTED SPURIOUS EMISSIONS.....	33
9.6 RADIATED SPURIOUS EMISSIONS	36
9.7 RADIATED RESTRICTED BAND EDGES	46
9.8 POWERLINE CONDUCTED EMISSIONS	51
10. LIST OF TEST EQUIPMENT	53
11. ANNEX A_ TEST SETUP PHOTO	55

1. EUT DESCRIPTION

Model	SM-M156B/DSN	
Additional Model	-	
EUT Type	Mobile Phone	
Power Supply	DC 4.20 V	
Frequency Range	2 412 MHz ~ 2 472 MHz	
Max. RF Output Power	<u>Average Power</u>	802.11b : 18.54 dBm 802.11g : 16.68 dBm 802.11n(HT20) : 16.58 dBm
	<u>Peak Power</u> (For information only)	802.11b : 23.89 dBm 802.11g : 24.79 dBm 802.11n(HT20) : 24.38 dBm
Modulation Type	DSSS/CCK : 802.11b OFDM : 802.11g, 802.11n	
Number of Channels	13 Channels	
Antenna Specification	Type: MFA Peak Gain : -6.0 dBi	
Date(s) of Tests	November 14, 2023 ~ December 14, 2023	
Serial number	Conducted : R3CWA0QSYTA Radiated : R3CWA0QSXYD	

2. TEST METHODOLOGY

FCC KDB 558074 D01 15.247 Meas Guidance v05r02 dated April 02, 2019 entitled "guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices and the measurement procedure described in ANSI C63.10(Version : 2013) 'the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices'.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1 GHz. Above 1 GHz with 1.5 m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013)

DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment's, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

4. FACILITIES AND ACCREDITATIONS

FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated March 31, 2022 (Registration Number: KR0032).

EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

(1) The antennas of this E.U.T are permanently attached.

(2) The E.U.T Complies with the requirement of §15.203

6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.


The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.90 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.14 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.82 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.74 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.76 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (Above 40 GHz)	5.52 (Confidence level about 95 %, $k=2$)

7. DESCRIPTION OF TESTS

7.1. Duty Cycle

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to the zero-span measurement method.

The largest available value of RBW is 8 MHz and VBW is 50 MHz.

The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.


1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz (\geq RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = T_{on} / T_{total} and Duty Cycle Factor = $10\log(1/\text{Duty Cycle})$

7.2. 6 dB Bandwidth

Limit

The minimum permissible 6 dB bandwidth is 500 kHz.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Procedure 11.8.1 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW $\geq 3 \times$ RBW
- 3) Detector = Peak
- 4) Trace mode = max hold
- 5) Sweep = auto couple
- 6) Allow the trace to stabilize
- 7) We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.


Note : We tested OBW using the automatic bandwidth measurement capability of a spectrum analyzer.

7.3. Output Power

Limit

The maximum permissible conducted output power is 1 Watt.

Test Configuration



Test Procedure

The transmitter output is connected to the Power Meter.

- Peak Power (Procedure 11.9.1.3 in ANSI 63.10-2013)
 - : Measure the peak power of the transmitter.

- Average Power (Procedure 11.9.2.3 in ANSI 63.10-2013)
 - 1) Measure the duty cycle.
 - 2) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
 - 3) Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

Sample Calculation


- Conducted Output Power(Peak) = Measured Value + ATT loss + Cable loss
- Conducted Output Power(Average) = Measured Value + ATT loss + Cable loss + Duty Cycle Factor

7.4. Power Spectral Density

Limit

The transmitter power density average over 1-second interval shall not be greater than 8 dBm in any 3 kHz BW.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to Procedure 8.4 in KDB 558074 v05r02, Procedure 11.10 in ANSI 63.10-2013.

The spectrum analyzer is set to :

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set span to at least 1.5 times the OBW.
- 3) RBW = 3 kHz ≤ RBW ≤ 100 kHz.
- 4) VBW ≥ 3 x RBW.
- 5) Sweep = auto couple
- 6) Detector = power averaging (rms) or sample detector (when rms not available).
- 7) Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
- 8) Employ trace averaging (rms) mode over a minimum of 100 traces
- 9) Use the peak marker function to determine the maximum amplitude level.
- 10) Use the peak marker function to determine the maximum amplitude level within the RBW.
If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11) if then duty factor shall be added to adjust the result if the duty cycle is less than 98 %

Sample Calculation

- Power Spectral Density = Measured Value + ATT loss + Cable loss + Duty Cycle Factor


7.5. Conducted Band Edge(Out of Band Emissions) & Conducted Spurious Emissions

Limit

The maximum conducted (Average) output power was used to demonstrate compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least relative to the maximum in-band peak PSD level in 100 kHz.

[Conducted > 30 dBc]

Test Configuration



Test Procedure

The transmitter output is connected to the spectrum analyzer.

(Procedure 11.11 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW \geq 3 x RBW
- 3) Set span to encompass the spectrum to be examined
- 4) Detector = Peak
- 5) Trace Mode = max hold
- 6) Sweep time = auto couple
- 7) Ensure that the number of measurement points \geq 2 x Span/RBW
- 8) Allow trace to fully stabilize.
- 9) Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

Factors for frequency

Freq(MHz)	Factor(dB)
30	20.06
100	20.14
200	20.17
300	20.21
400	20.28
500	20.28
600	20.28
700	20.28
800	20.30
900	20.31
1 000	20.35
2 000	20.55
2 400	20.62
3 000	20.67
4 000	20.74
5 000	20.86
5 850	20.84
6 000	20.83
7 000	20.93
8 000	20.97
9 000	21.09
10 000	21.18
11 000	21.27
12 000	21.33
13 000	21.33
14 000	21.40
15 000	21.49
16 000	21.52
17 000	21.55
18 000	21.63
19 000	21.65
20 000	21.66
21 000	21.76
22 000	21.82
23 000	21.86
24 000	21.90
25 000	21.92
26 000	22.04

Note : 1. 2400 ~ 2500 MHz is fundamental frequency range.

2. Factor = Attenuator loss + Cable loss
3. Spectrum offset Loss = Attenuator loss + Cable loss + EUT Cable loss(0.36 dB) = 20.98 dB


7.6. Radiated Test

Limit


Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 – 0.490	$2400/F(\text{kHz})$	300
0.490 – 1.705	$24000/F(\text{kHz})$	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



Test Procedure of Radiated spurious emissions (Below 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3 m from the EUT
3. The EUT is placed on a turntable, which is 0.8 m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the ground plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor($0.009 \text{ MHz} - 0.490 \text{ MHz}$) = $40\log(3 \text{ m}/300 \text{ m}) = -80 \text{ dB}$
Measurement Distance : 3 m
7. Distance Correction Factor($0.490 \text{ MHz} - 30 \text{ MHz}$) = $40\log(3 \text{ m}/30 \text{ m}) = -40 \text{ dB}$
Measurement Distance : 3 m
8. Spectrum Setting
 - Frequency Range = 9 kHz ~ 30 MHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 9 kHz
 - VBW $\geq 3 \times \text{RBW}$
9. Total = Measured Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

KDB 414788 OFS and Chamber Correlation Justification

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

Test Procedure of Radiated spurious emissions (Below 1 GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8 m above ground plane.
3. The Hybrid antenna was placed at a location 3 m from the EUT, which is varied from 1 m to 4 m to find out the highest emissions.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Spectrum Setting

(1) Measurement Type(Peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 100 kHz
- VBW \geq 3 x RBW

(2) Measurement Type(Quasi-peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Quasi-Peak
- RBW = 120 kHz

In general, (1) is used mainly

7. Total = Measured Value + Antenna Factor(A.F) + Cable Loss(C.L)
8. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

Test Procedure of Radiated spurious emissions (Above 1 GHz)

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3 m away from the receiving antenna, which is varied from 1 m to 4 m to find out the highest emissions.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.
8. Spectrum Setting (Method 8.6 in KDB 558074 v05r02, Procedure 11.12 in ANSI 63.10-2013)

(1) Measurement Type(Peak):

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = Peak

- Trace = Maxhold
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW

(2) Measurement Type(Average): Duty cycle $\geq 98\%$

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).

(3) Measurement Type(Average): Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 % duty cycle.
- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.

9. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

10. Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance})$ (dB)

11. Total(Measurement Type : Peak)

$$= \text{Measured value} + \text{Antenna Factor(A.F)} + \text{Cable Loss(C.L)} - \text{Amp Gain(A.G)} + \text{Distance Factor(D.F)}$$

Total(Measurement Type : Average, Duty cycle $\geq 98\%$)

$$= \text{Measured value} + \text{Antenna Factor(A.F)} + \text{Cable Loss(C.L)} - \text{Amp Gain(A.G)} + \text{Distance Factor(D.F)}$$

Total(Measurement Type : Average, Duty cycle $< 98\%$)

$$\begin{aligned} &= \text{Measured value} + \text{Antenna Factor(A.F)} + \text{Cable Loss(C.L)} - \text{Amp Gain(A.G)} + \text{Distance Factor(D.F)} \\ &\quad + \text{Duty Cycle Factor} \end{aligned}$$

Test Procedure of Radiated Restricted Band Edge

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3 m away from the receiving antenna, which is varied from 1 m to 4 m to find out the highest emissions.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.
8. Spectrum Setting

(1) Measurement Type(Peak):

- Measured Frequency Range : 2310 MHz ~ 2390 MHz / 2483.5 MHz ~ 2500 MHz
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW \geq 3 x RBW

(2) Measurement Type(Average): Duty cycle \geq 98 %,

- Measured Frequency Range : 2310 MHz ~ 2390 MHz / 2483.5 MHz ~ 2500 MHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW \geq 3 x RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).

(3) Measurement Type(Average): Duty cycle < 98 %, duty cycle variations are less than \pm 2 %

- Measured Frequency Range : 2310 MHz ~ 2390 MHz / 2483.5 MHz ~ 2500 MHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW \geq 3 x RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 % duty cycle.
- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.

9. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

10. Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance})$ (dB)

11. Total(Measurement Type : Peak)

= Measured value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle $\geq 98\%$)

= Measured value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle $< 98\%$)

= Measured value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F) + Duty Cycle Factor

7.7. AC Power line Conducted Emissions

Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56 ^(a)	56 to 46 ^(a)
0.50 to 5	56	46
5 to 30	60	50

^(a)Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

Sample Calculation

Quasi-peak(Final Result) = Measured Value + Correction Factor

7.8. Worst case configuration and mode

Radiated test

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone, Stand alone + External accessories(Earphone, etc)
 - Worstcase : Stand alone
2. EUT Axis
 - Radiated Spurious Emissions : X
 - Radiated Restricted Band Edge : X, Z
3. Duty cycle factor applies only 802.11g/n (Duty cycle < 98 %).
4. All data rate of operation were investigated and the test results are worst case in lowest Data Rate of each mode.
 - 802.11b : 1 Mbps
 - 802.11g : 6 Mbps
 - 802.11n(HT20): MCS0
5. All position of loop antenna were investigated and the test result is a no critical peak found at all positions.
 - Position : Horizontal, Vertical, Parallel to the ground plane
6. Radiated Spurious Emission
 - Channel 12 and 13 are less powerful than channel 11 so the test for high channel was performed at channel 11.
 - Mode: 802.11b, 802.11g, 802.11n(HT20)

AC Power line Conducted Emissions

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone + External accessories(Earphone, etc) + Travel Adapter,
Stand alone + Travel Adapter
 - Worstcase : Stand alone + Travel Adapter

Conducted test

1. The EUT was configured with data rate of the highest power.




8. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§15.247(a)(2)	> 500 kHz	Conducted	PASS
Conducted Maximum Output Power	§15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge (Out of Band Emissions)	§15.247(d)	Conducted > 30 dBc		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 7.7		PASS
Radiated Spurious Emissions	§15.247(d), 15.205, 15.209	cf. Section 7.6	Radiated	PASS
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 7.6		PASS

9. TEST RESULT

9.1 DUTY CYCLE


Mode	Data Rate (Mbps)	T _{on} (ms)	T _{total} (ms)	Duty Cycle	Duty Cycle Factor (dB)
802.11b	1	8.380	8.421	0.995	0.021
	2	4.290	4.327	0.991	0.037
	5.5	1.680	1.720	0.976	0.104
	11	0.935	0.975	0.958	0.184
802.11g	6	1.391	1.436	0.968	0.140
	9	0.935	0.980	0.953	0.207
	12	0.709	0.755	0.940	0.271
	18	0.479	0.524	0.913	0.395
	24	0.364	0.408	0.891	0.499
	36	0.251	0.414	0.606	2.174
	48	0.193	0.409	0.471	3.271
	54	0.177	0.410	0.432	3.643
	6.5 (MCS0)	1.300	1.345	0.966	0.150
802.11n (HT20)	13 (MCS1)	0.669	0.714	0.936	0.286
	19.5 (MCS2)	0.459	0.504	0.910	0.412
	26 (MCS3)	0.352	0.414	0.851	0.700
	39 (MCS4)	0.248	0.410	0.606	2.178
	52 (MCS5)	0.198	0.414	0.478	3.209
	58.5 (MCS6)	0.180	0.414	0.435	3.617
	65 (MCS7)	0.164	0.408	0.403	3.949


Test Plots
Duty cycle plot (802.11b(1 Mbps))

Duty cycle plot (802.11g(6 Mbps))

Duty cycle plot (802.11n(MCS0))

Note:

In order to simplify the report, attached plots were only the lowest data rate.

9.2 6 dB BANDWIDTH

Mode	Frequency [MHz]	Channel No.	6dB Bandwidth [MHz]	Limit [MHz]
802.11b	2412	1	8.111	0.50
	2417	2	8.131	0.50
	2422	3	8.129	0.50
	2427	4	8.134	0.50
	2432	5	8.131	0.50
	2437	6	8.124	0.50
	2462	11	8.121	0.50
	2467	12	8.111	0.50
	2472	13	8.107	0.50
802.11g	2412	1	15.17	0.50
	2437	6	15.17	0.50
	2462	11	15.16	0.50
	2467	12	15.17	0.50
	2472	13	15.17	0.50
802.11n(HT20)	2412	1	15.16	0.50
	2437	6	15.17	0.50
	2462	11	15.16	0.50
	2467	12	15.15	0.50
	2472	13	15.17	0.50

Test Plots
6 dB Bandwidth plot (802.11b-CH 13)

6 dB Bandwidth plot (802.11g-CH 11)

6 dB Bandwidth plot (802.11n-HT20-CH 12)

Note:

In order to simplify the report, attached plots were only the narrowest 6 dB BW channel.

9.3 OUTPUT POWER

Peak Output Power

Mode	Frequency [MHz]	Channel No.	Data Rate	Conducted Peak Power [dBm]	Limit [dBm]
802.11b	2412	1	11M	23.32	30
	2417	2	11M	22.32	30
	2422	3	11M	22.44	30
	2427	4	11M	23.03	30
	2432	5	11M	22.76	30
	2437	6	11M	23.89	30
	2462	11	11M	23.75	30
	2467	12	11M	10.14	30
	2472	13	11M	6.80	30
802.11g	2412	1	54M	24.79	30
	2437	6	54M	24.34	30
	2462	11	54M	24.09	30
	2467	12	24M	12.21	30
	2472	13	9M	8.48	30
802.11n (HT20)	2412	1	MCS6	24.38	30
	2437	6	MCS6	23.89	30
	2462	11	MCS6	23.68	30
	2467	12	MCS0	11.76	30
	2472	13	MCS0	7.95	30



Average Output Power

Mode	Frequency [MHz]	Channel No.	Data Rate	Conducted Average Power [dBm]			Limit [dBm]
				Measured Value	D.C.F	Summed	
802.11b	2412	1	5.5M	17.67	0.104	17.77	30
	2417	2	5.5M	16.73	0.104	16.83	30
	2422	3	5.5M	16.88	0.104	16.98	30
	2427	4	5.5M	17.47	0.104	17.58	30
	2432	5	5.5M	17.38	0.104	17.48	30
	2437	6	5.5M	18.43	0.104	18.54	30
	2462	11	5.5M	18.18	0.104	18.29	30
	2467	12	5.5M	4.48	0.104	4.59	30
	2472	13	5.5M	0.66	0.104	0.77	30
802.11g	2412	1	6M	16.54	0.140	16.68	30
	2437	6	6M	16.14	0.140	16.28	30
	2462	11	6M	15.91	0.140	16.05	30
	2467	12	6M	3.95	0.140	4.09	30
	2472	13	6M	0.22	0.140	0.36	30
802.11n (HT20)	2412	1	MCS0	16.43	0.150	16.58	30
	2437	6	MCS0	16.02	0.150	16.17	30
	2462	11	MCS0	15.79	0.150	15.94	30
	2467	12	MCS0	3.83	0.150	3.98	30
	2472	13	MCS0	0.10	0.150	0.25	30

9.4 POWER SPECTRAL DENSITY

BW	Frequency [MHz]	Channel No.	Data Rate	Power Spectral Density [dBm]			Limit [dBm/kHz]
				Measured Value	D.C.F	Summed	
802.11b	2412	1	5.5M	-3.733	0.104	-3.629	8 dBm / 3 kHz
	2417	2	5.5M	-4.055	0.104	-3.951	
	2422	3	5.5M	-4.018	0.104	-3.914	
	2427	4	5.5M	-2.923	0.104	-2.819	
	2432	5	5.5M	-3.286	0.104	-3.182	
	2437	6	5.5M	-2.921	0.104	-2.817	
	2462	11	5.5M	-2.984	0.104	-2.880	
	2467	12	5.5M	-16.768	0.104	-16.664	
	2472	13	5.5M	-20.414	0.104	-20.310	
802.11g	2412	1	6M	-7.211	0.140	-7.071	8 dBm / 3 kHz
	2437	6	6M	-7.470	0.140	-7.330	
	2462	11	6M	-7.812	0.140	-7.672	
	2467	12	6M	-20.057	0.140	-19.917	
	2472	13	6M	-23.318	0.140	-23.178	
802.11n (HT20)	2412	1	MCS0	-7.902	0.150	-7.752	8 dBm / 3 kHz
	2437	6	MCS0	-7.499	0.150	-7.349	
	2462	11	MCS0	-8.101	0.150	-7.951	
	2467	12	MCS0	-19.960	0.150	-19.810	
	2472	13	MCS0	-24.047	0.150	-23.897	

Test Plots
Power Spectral Density (802.11b-CH 6)


Power Spectral Density (802.11g-CH 1)

Power Spectral Density (802.11n_HT20-CH 6)

Note :

In order to simplify the report, attached plots were only the worst case PSD channel.

9.5 BAND EDGE / CONDUCTED SPURIOUS EMISSIONS

Test Result : please refer to the plot below.


In order to simplify the report, attached plots were only the worst case channel and data rate.

Test Plots(Band Edge)


☒ Test Plots(Conducted Spurious Emission)

In order to simplify the report, attached plots were only the worst case channel and data rate.

(Worst case : 802.11g_Ch.1_6 Mbps)



Note:

Limit : -26.62 dBm

9.6 RADIATED SPURIOUS EMISSIONS

Frequency Range : 9 kHz – 30 MHz

Frequency	Measured Value	A.F+C.L+D.F	Ant. POL	Total	Limit	Margin
[MHz]	[dB μ V]	[dB/m]	[H/V]	[dB μ V/m]	[dB μ V/m]	[dB]
No Critical peaks found						

Note:

1. The Measured value of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor = $40\log(\text{specific distance} / \text{test distance})$ (dB)
3. Limit line = specific Limits (dB μ V) + Distance extrapolation factor

Frequency Range : Below 1 GHz

Frequency	Measured Value	A.F+C.L	Ant. POL	Total	Limit	Margin
[MHz]	[dB μ V]	[dB/m]	[H/V]	[dB μ V/m]	[dB μ V/m]	[dB]
No Critical peaks found						

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

Frequency Range : Above 1 GHz

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2412 MHz
Channel No.	01 Ch

Frequency [MHz]	Measured Value [dB μ V]	C.L+A.F+ D.F-A.G [dB]	ANT. POL	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4824	49.32	4.83	V	54.15	73.98	19.83	PK
4824	44.95	4.83	V	49.78	53.98	4.20	AV
7236	39.51	12.62	V	52.13	73.98	21.85	PK
7236	26.71	12.62	V	39.33	53.98	14.65	AV
4824	49.64	4.83	H	54.47	73.98	19.51	PK
4824	45.82	4.83	H	50.65	53.98	3.33	AV
7236	39.63	12.62	H	52.25	73.98	21.73	PK
7236	26.88	12.62	H	39.50	53.98	14.48	AV

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2417 MHz
Channel No.	2 Ch

Frequency [MHz]	Measured Value [dB μ V]	C.L+A.F+ D.F-A.G [dB]	ANT. POL	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4834	49.02	4.90	V	53.92	73.98	20.06	PK
4834	44.85	4.90	V	49.75	53.98	4.23	AV
7251	38.88	12.69	V	51.57	73.98	22.41	PK
7251	26.59	12.69	V	39.28	53.98	14.70	AV
4834	49.28	4.90	H	54.18	73.98	19.80	PK
4834	45.20	4.90	H	50.10	53.98	3.88	AV
7251	38.92	12.69	H	51.61	73.98	22.37	PK
7251	26.62	12.69	H	39.31	53.98	14.67	AV

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2422 MHz
Channel No.	3 Ch

Frequency [MHz]	Measured Value [dB μ V]	C.L+A.F+ D.F-A.G [dB]	ANT. POL [H/V]	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4844	48.95	4.94	V	53.89	73.98	20.09	PK
4844	44.02	4.94	V	48.96	53.98	5.02	AV
7266	38.71	12.64	V	51.35	73.98	22.63	PK
7266	26.65	12.64	V	39.29	53.98	14.69	AV
4844	49.21	4.94	H	54.15	73.98	19.83	PK
4844	45.45	4.94	H	50.39	53.98	3.59	AV
7266	38.88	12.64	H	51.52	73.98	22.46	PK
7266	26.71	12.64	H	39.35	53.98	14.63	AV

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2427 MHz
Channel No.	4 Ch

Frequency [MHz]	Measured Value [dB μ V]	C.L+A.F+ D.F-A.G [dB]	ANT. POL [H/V]	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4854	49.32	5.00	V	54.32	73.98	19.66	PK
4854	45.21	5.00	V	50.21	53.98	3.77	AV
7281	38.51	12.69	V	51.20	73.98	22.78	PK
7281	26.59	12.69	V	39.28	53.98	14.70	AV
4854	49.59	5.00	H	54.59	73.98	19.39	PK
4854	45.45	5.00	H	50.45	53.98	3.53	AV
7281	38.66	12.69	H	51.35	73.98	22.63	PK
7281	26.62	12.69	H	39.31	53.98	14.67	AV

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2432 MHz
Channel No.	5 Ch

Frequency [MHz]	Measured Value [dB μ V]	C.L+A.F+ D.F-A.G [dB]	ANT. POL [H/V]	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4864	48.62	5.09	V	53.71	73.98	20.27	PK
4864	44.51	5.09	V	49.60	53.98	4.38	AV
7296	38.71	12.65	V	51.36	73.98	22.62	PK
7296	26.71	12.65	V	39.36	53.98	14.62	AV
4864	48.98	5.09	H	54.07	73.98	19.91	PK
4864	44.89	5.09	H	49.98	53.98	4.00	AV
7296	38.88	12.65	H	51.53	73.98	22.45	PK
7296	26.92	12.65	H	39.57	53.98	14.41	AV

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2437 MHz
Channel No.	6 Ch

Frequency [MHz]	Measured Value [dB μ V]	C.L+A.F+ D.F-A.G [dB]	ANT. POL [H/V]	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4874	48.62	5.20	V	53.82	73.98	20.16	PK
4874	44.71	5.20	V	49.91	53.98	4.07	AV
7311	39.71	12.63	V	52.34	73.98	21.64	PK
7311	27.41	12.63	V	40.04	53.98	13.94	AV
4874	48.87	5.20	H	54.07	73.98	19.91	PK
4874	45.07	5.20	H	50.27	53.98	3.71	AV
7311	39.89	12.63	H	52.52	73.98	21.46	PK
7311	27.54	12.63	H	40.17	53.98	13.81	AV

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2462 MHz
Channel No.	11 Ch

Frequency [MHz]	Measured Value [dB μ V]	C.L+A.F+ D.F-A.G [dB]	ANT. POL [H/V]	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4924	49.05	5.29	V	54.34	73.98	19.64	PK
4924	45.02	5.29	V	50.31	53.98	3.67	AV
7386	39.51	12.51	V	52.02	73.98	21.96	PK
7386	27.41	12.51	V	39.92	53.98	14.06	AV
4924	49.41	5.29	H	54.70	73.98	19.28	PK
4924	45.66	5.29	H	50.95	53.98	3.03	AV
7386	39.95	12.51	H	52.46	73.98	21.52	PK
7386	27.53	12.51	H	40.04	53.98	13.94	AV

Note:

Channel 12 and 13 are less powerful than channel 11. So, the test for high channel was performed at channel 11.

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2412 MHz
Channel No.	01 Ch

Frequency [MHz]	Measured Value [dB μ V]	Duty Cycle Factor [dB]	C.L+A.F+ D.F-A.G [dB]	ANT. POL	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4824	44.89	0.00	4.83	V	49.72	73.98	24.26	PK
4824	32.88	0.14	4.83	V	37.85	53.98	16.13	AV
7236	39.41	0.00	12.62	V	52.03	73.98	21.95	PK
7236	26.32	0.14	12.62	V	39.08	53.98	14.90	AV
4824	45.12	0.00	4.83	H	49.95	73.98	24.03	PK
4824	32.96	0.14	4.83	H	37.93	53.98	16.05	AV
7236	39.51	0.00	12.62	H	52.13	73.98	21.85	PK
7236	26.44	0.14	12.62	H	39.20	53.98	14.78	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2437 MHz
Channel No.	06 Ch

Frequency [MHz]	Measured Value [dB μ V]	Duty Cycle Factor [dB]	C.L+A.F+ D.F-A.G [dB]	ANT. POL	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4874	44.22	0.00	5.20	V	49.42	73.98	24.56	PK
4874	31.95	0.14	5.20	V	37.29	53.98	16.69	AV
7311	39.55	0.00	12.63	V	52.18	73.98	21.80	PK
7311	26.77	0.14	12.63	V	39.54	53.98	14.44	AV
4874	44.49	0.00	5.20	H	49.69	73.98	24.29	PK
4874	32.01	0.14	5.20	H	37.35	53.98	16.63	AV
7311	39.62	0.00	12.63	H	52.25	73.98	21.73	PK
7311	26.84	0.14	12.63	H	39.61	53.98	14.37	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2462 MHz
Channel No.	11 Ch

Frequency [MHz]	Measured Value [dB μ V]	Duty Cycle Factor [dB]	C.L+A.F+ D.F-A.G [dB]	ANT. POL	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4924	44.01	0.00	5.29	V	49.30	73.98	24.68	PK
4924	31.88	0.14	5.29	V	37.31	53.98	16.67	AV
7386	39.22	0.00	12.51	V	51.73	73.98	22.25	PK
7386	26.85	0.14	12.51	V	39.50	53.98	14.48	AV
4924	44.29	0.00	5.29	H	49.58	73.98	24.40	PK
4924	32.05	0.14	5.29	H	37.48	53.98	16.50	AV
7386	39.41	0.00	12.51	H	51.92	73.98	22.06	PK
7386	26.91	0.14	12.51	H	39.56	53.98	14.42	AV

Note:

Channel 12 and 13 are less powerful than channel 11. So, the test for high channel was performed at channel 11.

Operation Mode:	802.11n(HT20)
Transfer Rate:	MCS0
Operating Frequency	2412 MHz
Channel No.	01 Ch

Frequency [MHz]	Measured Value [dB μ V]	Duty Cycle Factor [dB]	C.L+A.F+ D.F-A.G [dB]	ANT. POL	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4824	45.41	0.00	4.83	V	50.24	73.98	23.74	PK
4824	32.32	0.15	4.83	V	37.30	53.98	16.68	AV
7236	39.35	0.00	12.62	V	51.97	73.98	22.01	PK
7236	26.44	0.15	12.62	V	39.21	53.98	14.77	AV
4824	45.51	0.00	4.83	H	50.34	73.98	23.64	PK
4824	32.59	0.15	4.83	H	37.57	53.98	16.41	AV
7236	39.45	0.00	12.62	H	52.07	73.98	21.91	PK
7236	26.59	0.15	12.62	H	39.36	53.98	14.62	AV

Operation Mode:	802.11n(HT20)
Transfer Rate:	MCS0
Operating Frequency	2437 MHz
Channel No.	06 Ch

Frequency [MHz]	Measured Value [dB μ V]	Duty Cycle Factor [dB]	C.L+A.F+ D.F-A.G [dB]	ANT. POL	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4874	44.28	0.00	5.20	V	49.48	73.98	24.50	PK
4874	31.71	0.15	5.20	V	37.06	53.98	16.92	AV
7311	39.81	0.00	12.63	V	52.44	73.98	21.54	PK
7311	26.62	0.15	12.63	V	39.40	53.98	14.58	AV
4874	44.55	0.00	5.20	H	49.75	73.98	24.23	PK
4874	31.85	0.15	5.20	H	37.20	53.98	16.78	AV
7311	39.91	0.00	12.63	H	52.54	73.98	21.44	PK
7311	26.77	0.15	12.63	H	39.55	53.98	14.43	AV

Operation Mode:	802.11n(HT20)
Transfer Rate:	MCS0
Operating Frequency	2462 MHz
Channel No.	11 Ch

Frequency [MHz]	Measured Value [dB μ V]	Duty Cycle Factor [dB]	C.L+A.F+ D.F-A.G [dB]	ANT. POL	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
4924	44.05	0.00	5.29	V	49.34	73.98	24.64	PK
4924	31.71	0.15	5.29	V	37.15	53.98	16.83	AV
7386	39.22	0.00	12.51	V	51.73	73.98	22.25	PK
7386	26.85	0.15	12.51	V	39.51	53.98	14.47	AV
4924	44.21	0.00	5.29	H	49.50	73.98	24.48	PK
4924	31.85	0.15	5.29	H	37.29	53.98	16.69	AV
7386	39.36	0.00	12.51	H	51.87	73.98	22.11	PK
7386	26.95	0.15	12.51	H	39.61	53.98	14.37	AV


Note:

Channel 12 and 13 are less powerful than channel 11. So, the test for high channel was performed at channel 11.


Test Plots (Worst case : X-H)

Note: In order to simplify the report, Plot of worst case are only reported.

Radiated Spurious Emissions plot – Average Result (802.11b_1 Mbps, Ch.11 2nd Harmonic)



Radiated Spurious Emissions plot – Peak Result (802.11b_1 Mbps, Ch.11 2nd Harmonic)



9.7 RADIATED RESTRICTED BAND EDGES

Operation Mode:	802.11b	
Transfer Rate:	1 Mbps	
Operating Frequency	2412 MHz, 2462 MHz	
Channel No.	01 Ch, 11 Ch	

Channel No	Frequency [MHz]	Measured Value [dB μ V]	A.F.+C.L+D.F [dB]	ANT. POL [H/V]	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
1	2390.0	19.63	35.41	H	55.04	73.98	18.94	PK
	2390.0	8.76	35.41	H	44.17	53.98	9.81	AV
	2390.0	18.95	35.41	V	54.36	73.98	19.62	PK
	2390.0	7.95	35.41	V	43.36	53.98	10.62	AV
11	2483.5	20.12	35.99	H	56.11	73.98	17.87	PK
	2483.5	10.88	35.99	H	46.87	53.98	7.11	AV
	2483.5	19.52	35.99	V	55.51	73.98	18.47	PK
	2483.5	10.55	35.99	V	46.54	53.98	7.44	AV

Operation Mode:	802.11b	
Transfer Rate:	1 Mbps	
Operating Frequency	2467 MHz, 2472 MHz	
Channel No.	12 Ch, 13 Ch	

Channel No	Frequency [MHz]	Measured Value [dB μ V]	A.F.+C.L+D.F [dB]	ANT. POL [H/V]	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
12	2483.5	18.78	35.99	H	54.77	73.98	19.21	PK
	2483.5	6.77	35.99	H	42.76	53.98	11.22	AV
	2483.5	18.41	35.99	V	54.40	73.98	19.58	PK
	2483.5	6.55	35.99	V	42.54	53.98	11.44	AV
13	2483.5	18.55	35.99	H	54.54	73.98	19.44	PK
	2483.5	6.85	35.99	H	42.84	53.98	11.14	AV
	2483.5	18.75	35.99	V	54.74	73.98	19.24	PK
	2483.5	7.11	35.99	V	43.10	53.98	10.88	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Channel No	Frequency [MHz]	Measured Value [dB μ V]	Duty Cycle Factor [dB]	A.F.+C.L+D.F [dB]	ANT. POL [H/V]	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
1	2390.0	28.74	0.00	35.41	H	64.15	73.98	9.83	PK
	2390.0	13.45	0.14	35.41	H	49.00	53.98	4.98	AV
	2390.0	28.55	0.00	35.41	V	63.96	73.98	10.02	PK
	2390.0	13.12	0.14	35.41	V	48.67	53.98	5.31	AV
11	# 2483.5	26.33	0.00	35.99	H	62.32	73.98	11.66	PK
	# 2483.5	13.79	0.14	35.99	H	49.92	53.98	4.06	AV
	# 2483.5	26.02	0.00	35.99	V	62.01	73.98	11.97	PK
	# 2483.5	13.51	0.14	35.99	V	49.64	53.98	4.34	AV

Note : # integration method Used (ANSI C63.10 Section11.13.3)

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2467 MHz, 2472 MHz
Channel No.	12 Ch, 13 Ch

Channel No	Frequency [MHz]	Measured Value [dB μ V]	Duty Cycle Factor [dB]	A.F.+C.L+D.F [dB]	ANT. POL [H/V]	Total [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Measurement Type
12	2483.5	20.42	0.00	35.99	H	56.41	73.98	17.57	PK
	2483.5	6.80	0.14	35.99	H	42.93	53.98	11.05	AV
	2483.5	19.24	0.00	35.99	V	55.23	73.98	18.75	PK
	2483.5	6.72	0.14	35.99	V	42.85	53.98	11.13	AV
13	2483.5	19.23	0.00	35.99	H	55.22	73.98	18.76	PK
	2483.5	6.90	0.14	35.99	H	43.03	53.98	10.95	AV
	2483.5	18.97	0.00	35.99	V	54.96	73.98	19.02	PK
	2483.5	7.33	0.14	35.99	V	43.46	53.98	10.52	AV

Operation Mode:	802.11n (HT20)
Transfer MCS Index:	0
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Channel No	Frequency [MHz]	Measured Value [dBμV]	Duty Cycle Factor [dB]	A.F.+C.L+D.F [dB]	ANT. POL	Total [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Measurement Type
1	# 2390	24.35	0.00	35.41	H	59.76	73.98	14.22	PK
	# 2390	14.14	0.15	35.41	H	49.70	53.98	4.28	AV
	# 2390	23.95	0.00	35.41	V	59.36	73.98	14.62	PK
	# 2390	13.75	0.15	35.41	V	49.31	53.98	4.67	AV
11	# 2483.5	26.42	0.00	35.99	H	62.41	73.98	11.57	PK
	# 2483.5	15.82	0.15	35.99	H	51.96	53.98	2.02	AV
	# 2483.5	25.61	0.00	35.99	V	61.60	73.98	12.38	PK
	# 2483.5	14.62	0.15	35.99	V	50.76	53.98	3.22	AV

Note : # integration method Used (ANSI C63.10 Section11.13.3)

Operation Mode:	802.11n (HT20)
Transfer MCS Index:	0
Operating Frequency	2467 MHz, 2472 MHz
Channel No.	12 Ch, 13 Ch


Channel No	Frequency [MHz]	Measured Value [dBμV]	Duty Cycle Factor [dB]	A.F.+C.L+D.F [dB]	ANT. POL	Total [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Measurement Type
12	2483.5	25.78	0.00	35.99	H	61.77	73.98	12.21	PK
	2483.5	6.90	0.15	35.99	H	43.04	53.98	10.94	AV
	2483.5	25.22	0.00	35.99	V	61.21	73.98	12.77	PK
	2483.5	6.77	0.15	35.99	V	42.91	53.98	11.07	AV
13	2483.5	29.55	0.00	35.99	H	65.54	73.98	8.44	PK
	2483.5	8.06	0.15	35.99	H	44.20	53.98	9.78	AV
	2483.5	30.46	0.00	35.99	V	66.45	73.98	7.53	PK
	2483.5	9.15	0.15	35.99	V	45.29	53.98	8.69	AV

Test Plots


Note:

In order to simplify the report, Plots of worst case are only reported.


Radiated Restricted Band Edges plot – Average Result (802.11n (HT20), MCS0, Ch.11, X-H)
[Integration method Used]




Radiated Restricted Band Edges plot – Peak Result (802.11n (HT20), MCS0, Ch.11, X-H)
[Integration method Used]



Radiated Restricted Band Edges plot – Average Result (802.11n (HT20), MCS0, Ch.13, Z-V)



Radiated Restricted Band Edges plot – Peak Result (802.11n (HT20), MCS0, Ch.13, Z-V)



9.8 POWERLINE CONDUCTED EMISSIONS

Conducted Emissions

WLAN 2.4G MODE


1 / 2

Test Report

Common Information

EUT : SM-M156B/DSN
 Operating Conditions : WLAN 2.4G MODE

Full Spectrum



Final Result_QPK

Frequency (MHz)	QuasiPeak (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.1568	57.07	65.63	8.57	9.000	L1	9.7
0.1680	55.58	65.06	9.48	9.000	L1	9.7
0.1748	55.86	64.73	8.88	9.000	N	9.7
0.1838	55.01	64.31	9.31	9.000	L1	9.7
0.1928	53.83	63.92	10.08	9.000	N	9.7
0.2108	52.89	63.18	10.28	9.000	L1	9.7
0.9095	23.03	56.00	32.97	9.000	N	9.8
0.9275	22.99	56.00	33.01	9.000	N	9.8
0.9365	22.86	56.00	33.14	9.000	N	9.8
0.9703	22.55	56.00	33.45	9.000	N	9.8
0.9860	23.26	56.00	32.74	9.000	N	9.8
0.9928	22.50	56.00	33.50	9.000	N	9.8
20.9053	30.87	60.00	29.13	9.000	L1	10.9
20.9300	30.05	60.00	29.95	9.000	L1	10.9
20.9750	30.18	60.00	29.82	9.000	L1	10.9
21.0493	30.24	60.00	29.76	9.000	L1	10.9
21.1753	30.01	60.00	29.99	9.000	L1	10.9
21.2000	30.01	60.00	29.99	9.000	L1	10.9

2023-12-08

오전 9:14:52

WLAN 2.4G MODE

2 / 2

Final Result CAV

Frequency (MHz)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.1523	34.77	55.88	21.11	9.000	L1	9.7
0.1748	32.56	54.73	22.18	9.000	L1	9.7
0.1995	29.84	53.63	23.79	9.000	L1	9.7
0.2243	27.34	52.66	25.32	9.000	L1	9.7
0.2378	27.07	52.17	25.10	9.000	L1	9.7
0.2648	26.07	51.28	25.21	9.000	N	9.7
0.8983	7.81	46.00	38.19	9.000	N	9.8
0.9118	8.20	46.00	37.80	9.000	N	9.8
0.9230	8.06	46.00	37.94	9.000	N	9.8
0.9365	7.85	46.00	38.15	9.000	N	9.8
0.9613	9.88	46.00	36.12	9.000	L1	9.8
0.9725	9.05	46.00	36.95	9.000	L1	9.8
20.6893	21.96	50.00	28.04	9.000	L1	10.9
20.8085	21.93	50.00	28.07	9.000	L1	10.9
21.0313	22.41	50.00	27.59	9.000	L1	10.9
21.1595	22.21	50.00	27.79	9.000	L1	10.9
21.1843	21.75	50.00	28.25	9.000	L1	10.9
21.2090	21.79	50.00	28.21	9.000	L1	10.9

2023-12-08

오전 9:14:52

10. LIST OF TEST EQUIPMENT

Conducted Test

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
LISN	ENV216	Rohde & Schwarz	102245	08/02/2024	Annual
EMI Test Receiver	ESR	Rohde & Schwarz	101910	05/26/2024	Annual
Temperature Chamber	SU-642	ESPEC	0093008124	02/22/2024	Annual
Signal Analyzer	N9030A	Agilent	MY49432108	03/02/2024	Annual
Power Measurement Set	OSP 120	Rohde & Schwarz	101231	06/09/2024	Annual
Power Meter	N1911A	Agilent	MY45100523	03/06/2024	Annual
Power Sensor	N1921A	Agilent	MY57820067	03/06/2024	Annual
Directional Coupler	87300B	Agilent	3116A03621	10/30/2024	Annual
Power Splitter	11667B	Hewlett Packard	10545	02/06/2024	Annual
DC Power Supply	E3632A	Agilent	KR75303243	04/24/2024	Annual
Attenuator(10 dB)(DC-26.5 GHz)	8493C	HP	07560	06/12/2024	Annual
Attenuator(10 dB)(DC-26.5 GHz)	8493C	HP	08285	06/02/2024	Annual
Attenuator(20 dB)	18N-20dB	Rohde & Schwarz	8	03/08/2024	Annual
Software	EMC32	Rohde & Schwarz	N/A	N/A	N/A
FCC WLAN&BT&BLE Conducted Test Software v3.0	N/A	HCT CO., LTD.	N/A	N/A	N/A
Bluetooth Tester	CBT	Rohde & Schwarz	100752	01/12/2024	Annual

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Radiated Test

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
Controller(Antenna mast)	CO3000	Innco system	CO3000-4p	N/A	N/A
Antenna Position Tower	MA4640/800-XP-EP	Innco system	N/A	N/A	N/A
EM1000 / Controller	EM1000	Audix	060520	N/A	N/A
Turn Table	N/A	Audix	N/A	N/A	N/A
Amp & Filter Bank Switch Controller	FBSM-01B	T&M system	TM19050002	N/A	N/A
Loop Antenna	1513	Schwarzbeck	1513-333	03/17/2024	Biennial
Hybrid Antenna	VULB 9168	Schwarzbeck	9168-0895	08/16/2024	Biennial
Horn Antenna	BBHA 9120D	Schwarzbeck	9120D-1300	01/18/2024	Biennial
Horn Antenna	BBHA 9120D	Schwarzbeck	9120D-2296	05/18/2024	Biennial
Horn Antenna(15 GHz ~ 40 GHz)	BBHA9170	Schwarzbeck	BBHA9170342	09/29/2024	Biennial
Spectrum Analyzer	FSV(10 Hz ~ 40 GHz)	Rohde & Schwarz	101055	05/12/2024	Annual
Band Reject Filter	WRCJV2400/2483.5-2370/2520-60/12SS	Wainwright Instruments	2	01/05/2024	Annual
Band Reject Filter	WRCJV12-4900-5100-5900-6100-50SS	Wainwright Instruments	5	06/12/2024	Annual
Band Reject Filter	WRCJV12-4900-5100-5900-6100-50SS	Wainwright Instruments	6	06/12/2024	Annual
High Pass Filter(7 GHz ~ 18 GHz)	WHKX10-7150-8000-18000-50SS	Wainwright Instruments	1	03/02/2024	Annual
Power Amplifier	CBL18265035	CERNEX	22966	11/17/2024	Annual
Power Amplifier	CBL26405040	CERNEX	25956	03/02/2024	Annual
Bluetooth Tester	TC-3000C	TESCOM	3000C000175	03/28/2024	Annual
RF Switching System	FMSR-05B (HPF(3~18GHz) + LNA1(1~18GHz))	T&M system	S1L1	01/17/2024	Annual
RF Switching System	FMSR -05B (ATT(10dB) + LNA1(1~18GHz))	T&M system	S1L2	01/17/2024	Annual
RF Switching System	FMSR -05B (ATT(3dB) + LNA1(1~18GHz))	T&M system	S1L3	01/17/2024	Annual
RF Switching System	FMSR -05B (LNA1(1~18GHz))	T&M system	S1L4	01/17/2024	Annual
RF Switching System	FMSR -05B (HPF(7~18GHz) + LNA2(6~18GHz))	T&M system	S1L5	01/17/2024	Annual
RF Switching System	FMSR -05B (Thru(30MHz ~ 18GHz))	T&M system	S1L6	01/17/2024	Annual

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
3. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5(Version : 2017).

11. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2312-FC008-P