

TEST REPORT

65, Sinwon-ro Suwon-si, Gyeong TEL: 82-31-285-0894 www.ł	KCTL Inc. y Yeongtong-gu, ggi-do, 16677, Korea FAX: 82-505-299-8311 <u>cctl.co.kr</u>	Repo KR20-S Page (ort No.: SRF0264 1) of (18)	KCTL	
1. Client					
∘ Name	: Samsung Electr	onics Co.,	Ltd.		
 Address 	 Address 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea 				
 Date of Rece 	eipt:2020-09-28				
2. Use of Report	: Class II Permiss	sive change	Э		
3. Name of Produ	ct / Model : Mo	bile phone	/ SM-F415F/	DS	
4. Manufacturer /	Country of Origin : Sa	imsung Ele	ectronics Co.	, Ltd. / Vietnam	
5. FCC ID	: A3	LSMM315	F		
6. Date of Test	: 2020-10-06 to 2	020-10-15			
7. Location of Tes	st : ■ Permanent Testing	g Lab 🗆 On S	ite Testing (Add	ress: Address of testing location)	
8. Test method us	sed : FCC Part 15 Su	bpart C, 1	5.247		
9. Test Result	: Refer to the tes	t result in tl	ne test repor	t	
Test	ed by		Technical M	anager	
Affirmation					
Nam	ne : Kwonse Kim (S	ignatore)	Name : Seun	gyong Kim (signalord)	
2020-10-16					
KCTL Inc.					
As a test result of the sample which was submitted from the client, this report does not guara ntee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.					

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311

www.kctl.co.kr

Report No.: KR20-SRF0264



Page (2) of (18)

REPORT REVISION HISTORY

Date	Revision	Page No
2020-10-16	Originally issued	-

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.

General remarks for test reports

Nothing significant to report.



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <u>www.kctl.co.kr</u> Report No.: KR20-SRF0264



Page (3) of (18)

CONTENTS

1.	General information	4
2.	Device information	4
2.1	. Accessory information	6
2.2	P. Frequency/channel operations	6
2.3	B. Duty Cycle Factor	7
3.	Summary of tests	8
4.	Measurement uncertainty	9
5.	Test results	10
5.1	. Spurious Emission, Band Edge and Restricted bands	10
6.	Measurement equipment	18



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <u>www.kctl.co.kr</u> Report No.: KR20-SRF0264



Page (4) of (18)

1. General information

Client	:	Samsung Electronics Co., Ltd.			
Address	:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea			
Manufacturer	:	Samsung Electronics Co., Ltd.			
Address	:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea			
Factory	:	Samsung Electronics Vietnam Thai Nguyen Co., Ltd			
Address	:	506-723 16000 Yen Phong 1 Industrial Zone, Yen Trung Commu, Yen Phong District, Bac Ninh Province, Vietnm			
Factory	:	Samsung India Electronics PVT. Ltd			
Address	:	3-1, Sector-8 NOIDA Uttar Pradeshe, India 201-305			
Factory	:	Samsung Electronics Co., Ltd.			
Address	:	94-1, Imsu-dong, Gumi-si, Gyengsangbuk-ro, 730-722, Republic of Korea			
Laboratory	:	KCTL Inc.			
Address	:	65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea			
Accreditations	:	FCC Site Designation No: KR0040, FCC Site Registration No: 687132			
		VCCI Registration No. : R-20080, G-20078, C-20059, T-20056			
		Industry Canada Registration No. : 8035A			
		KOLAS No.: KT231			

2. Device information

Equipment under test :	Mobile phone
Model :	SM-F415F/DS
Modulation technique :	Bluetooth(BDR/EDR)_ GFSK, π/4DQPSK, 8DPSK
	Bluetooth(BLE)_GFSK
	WIFI(802.11b/g/n20/n40/ac20/ac40/ac80)_DSSS, OFDM
	LTE_QPSK, 16QAM
	WCDMA_QPSK
	GSM_GMSK, 8-PSK
Number of channels :	Bluetooth(BDR/EDR)_79 ch / Bluetooth(BLE)_40 ch
	WIFI(802.11b/g/n20)_11 ch
	UNII-1 : 4 ch (20 Mz), 2 ch (40 Mz), 1 ch (80 Mz)
	UNII-2A : 4 ch (20 ‱), 2 ch (40 ∞), 1 ch (80 ∞)
	UNII-2C : 12 ch (20 Mz), 6 ch (40 Mz), 3 ch (80 Mz)
	UNII-3 : 5 ch (20 Mz), 2 ch (40 Mz), 1 ch (80 Mz)
Power source :	DC 3.85 V
Antenna specification :	LTE/GSM/WCDMA_LDS Antenna
	WIFI/Bluetooth(BDR/EDR/BLE)_LDS Antenna

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <u>www.kctl.co.kr</u> Report No.: KR20-SRF0264

Page (5) of (18)



Antenna gain	:	WIFI/Bluetooth(BDR/EDR/BLE): -3.4 dBi UNII-1 -5.9 dBi UNII-2A -6.3 dBi UNII-2C -5.3 dBi UNII-3 -6.6 dBi
Frequency range	:	Bluetooth(BDR/EDR/BLE)_2 402 Mlz ~ 2 480 Mlz 2 412 Mlz ~ 2 462 Mlz (802.11b/g/n_HT20) UNII-1: 5 180 Mlz ~ 5 240 Mlz (802.11a/n_HT20/ac_VHT20) UNII-1: 5 190 Mlz ~ 5 230 Mlz (802.11a_n_HT40/ac_VHT40) UNII-1: 5 210 Mlz ~ 5 320 Mlz (802.11a_n_HT20/ac_VHT20) UNII-2A: 5 260 Mlz ~ 5 320 Mlz (802.11a_n_HT20/ac_VHT40) UNII-2A: 5 270 Mlz ~ 5 310 Mlz (802.11a_n_HT20/ac_VHT40) UNII-2A: 5 290 Mlz (802.11ac_VHT80) UNII-2C: 5 500 Mlz ~ 5 720 Mlz (802.11a_n_HT20/ac_VHT40) UNII-2C: 5 500 Mlz ~ 5 720 Mlz (802.11a_n_HT20/ac_VHT40) UNII-2C: 5 530 Mlz ~ 5 690 Mlz (802.11a_VHT80) UNII-2C: 5 530 Mlz ~ 5 690 Mlz (802.11a_VHT80) UNII-3: 5 745 Mlz ~ 5 825 Mlz (802.11a_VHT80) UNII-3: 5 755 Mlz ~ 5 795 Mlz (802.11a_VHT80) LTE Band 2_1 850.7 Mlz ~ 1 909.3 Mlz LTE Band 4_1 710.7 Mlz ~ 1 754.3 Mlz LTE Band 5_824.7 Mlz ~ 848.3 Mlz LTE Band 12_699.7 Mlz ~ 715.3 Mlz LTE Band 13_779.5 Mlz ~ 784.5 Mlz LTE Band 14_2 498.5 Mlz ~ 2 687.5 Mlz LTE Band 26_824.7 Mlz ~ 848.3 Mlz, 814.7 Mlz ~ 823.3 Mlz LTE Band 26_824.7 Mlz ~ 848.3 Mlz, 814.7 Mlz ~ 823.3 Mlz LTE Band 66_1 710.7 Mlz ~ 1 779.3 Mlz GSM 850_824.2 Mlz ~ 848.8 Mlz GSM 1900_1 850.2 Mlz ~ 1 909.8 Mlz WCDMA 850_826.4 Mlz ~ 846.6 Mlz WCDMA 1700_1 712.4 Mlz ~ 1 752.6 Mlz
0 (WCDMA 1900_1 852.4 Mtz ~ 1 907.6 Mtz
Software version	:	
Hardware version	:	REV1.0
Test device serial No.	:	Conducted(R38N101EBQY), Radiated(R38N8004GRZ)
Operation temperature	:	-30 °C ~ 50 °C

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0264



Page (6) of (18)

2.1. Accesso	ry information			
Equipment	Manufacturer	Model	Serial No.	Power source
Travel Adapter	Samsung Electronics Co., Ltd.	EP-TA200	R37M4NR27T1SE3	AC 100-240V 50-60 Hz, 0.5A, 9.0V-1.67A, 5.0V-2.0A
Micro USB Data Cable	Samsung Electronics Co., Ltd.	-	-	-

2.2. Frequency/channel operations

This device contains the following capabilities:

WIFI (802.11a/b/g/n/ac), Bluetooth (BDR/EDR/BLE),

LTE Band 2, LTE Band 4, LTE Band 5, LTE Band 12, LTE Band 13, LTE Band 17, LTE Band 26, LTE Band 41, LTE Band 66, WCDMA 850, WCDMA 1700, WCDMA 1900, GSM 850, GSM 1900

Ch.	Frequency (Mb)
00	2 402
19	2 440
39	2 480

Table 2.2.1. Bluetooth Low Energy

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0264

Page (7) of (18)

KCTL

2.3. Duty Cycle Factor

Toot mode	Period	On time	Duty cycle		Duty Cycle Factor
rest mode	(ms)	(ms)	(Linear)	(%)	(dB)
1M Bits/s, 37 Packet	0.626 0	0.380 0	0.607 0	60.70	2.17
1M Bits/s, 255 Packet	2.498 0	2.106 0	0.843 0	84.30	0.74
2M Bits/s, 37 Packet	0.626 0	0.194 0	0.310 0	31.00	5.09
2M Bits/s, 255 Packet	1.874 0	1.066 0	0.569 0	56.90	1.07

Notes.

- 1. Duty cycle (Linear) = Ton time / Period
- 2. DCF(Duty cycle factor) = 10log(1/duty cycle)



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <u>www.kctl.co.kr</u> Report No.: KR20-SRF0264



Page (8) of (18)

3. Summary of tests

FCC Part section(s)	Parameter	Test condition	Test results
15.247(d),	Spurious emission		Pass
15.205(a), 15.209(a)	Band-edge, restricted band	Radiated	Pass

Notes:

- 1. According to exploratory test no any obvious emission were detected from 9 klz to 30 Mlz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
- 2. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that **X** orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in **X** orientation
- 3. The test procedure(s) in this report were performed in accordance as following.
 - ANSI C63.10-2013
 - KDB 558074 D01 v05r02
- 4. This is the C2PC test report to add a variant model, SM-F415F/DS as documented in the C2PC letter. Because the change does not affect RF characteristics, therefore, only radiated spurious emission test was done against the worst case from the main model, SM-M315F/DS, documented in the original filing and approved in 02/07/2020. All rest tests documented in original filing under model SM-M315F/DS remains representative of the variant model, SM-F415F/DS.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0264



4. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of k=2 to indicated a 95 % level of confidence. The measurement data shown herein meets of exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty (±)			
	9 kHz ~ 30 MHz:	2.3 dB		
Radiated sourious emissions	30 MHz ~ 300 MHz	5.4 dB		
Naulated spundus emissions	300 MHz ~ 1 000 MHz	5.5 dB		
	Above 1 GHz	6.7 dB		



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0264



Page (10) of (18)

5. Test results

5.1. Spurious Emission, Band Edge and Restricted bands

<u>Test setup</u>

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kl_2 to 30 Ml_2 Emissions



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 Mz to 1 Gz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 \oplus to the tenth harmonic of the highest fundamental frequency or to 40 \oplus emissions, whichever is lower.



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0264



<u>Limit</u>

According to section 15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (Mz)	Field strength (μ N/m)	Measurement distance (m)
0.009 - 0.490	2 400/F(kHz)	300
0.490 - 1.705	24 000/F(kHz)	30
1.705 - 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 Mb, 76-88 Mb, 174-216 Mb or 470-806 Mb. However, operation within these frequency bands is permitted under other sections of this part, e.g., Section 15.231 and 15.241.

According to section 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 – 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 – 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 – 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 – 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 – 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 – 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 – 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 – 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525	2 483.5 – 2 500	17.7 - 21.4
8.376 25 - 8.386 75	25	2 690 – 2 900	22.01 - 23.12
8.414 25 - 8.414 75	156.7 - 156.9	3 260 – 3 267	23.6 - 24.0
12.29 - 12.293	162.012 5 - 167.17	3 332 – 3 339	31.2 - 31.8
12.519 75 - 12.520 25	167.72 - 173.2	3 345.8 – 3 358	36.43 - 36.5
12.576 75 - 12.577 25	240 - 285	3 600 – 4 400	Above 38.6
13.36 - 13.41	322 - 335.4		

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in section 15.209. At frequencies equal to or less than 1 000 Mb, compliance with the limits in section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasipeak detector. Above 1 000 Mb, compliance with the emission limits in section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in section 15.35 apply to these measurements.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0264



Page (12) of (18)

Test procedure

ANSI C63.10-2013

Test settings

Peak field strength measurements

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = as specified in table
- 3. VBW \geq (3×RBW)
- 4. Detector = peak
- 5. Sweep time = auto
- 6. Trace mode = max hold
- 7. Allow sweeps to continue until the trace stabilizes

Table. Row as a function of frequency								
Frequency	RBW							
9 kHz to 150 kHz	200 Hz to 300 Hz							
0.15 MHz to 30 MHz	9 kHz to 10 kHz							
30 MHz to 1 000 MHz	100 kHz to 120 kHz							
> 1 000 M±z	1 MHz							

Table. RBW as a function of frequency

Average field strength measurements

Trace averaging with continuous EUT transmission at full power

If the EUT can be configured or modified to transmit continuously ($D \ge 98\%$), then the average emission levels shall be measured using the following method (with EUT transmitting continuously):

- 1. RBW = 1 $M_{\mathbb{Z}}$ (unless otherwise specified).
- 2. VBW \geq (3×RBW).
- 3. Detector = RMS (power averaging), if [span / (# of points in sweep)] ≤ (RBW / 2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- 4. Averaging type = power (i.e., rms):
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
- 5. Sweep time = auto.
- 6. Perform a trace average of at least 100 traces.

Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT ($D \ge 98\%$) cannot be achieved and the duty cycle is constant (duty cycle variations are less than ±2%), then the following procedure shall be used:

- 1. The EUT shall be configured to operate at the maximum achievable duty cycle.
- 2. Measure the duty cycle D of the transmitter output signal as described in 11.6.
- 3. RBW = 1 M_{2} (unless otherwise specified).
- 4. VBW \geq [3 \times RBW].
- 5. Detector = RMS (power averaging), if [span / (# of points in sweep)] ≤ (RBW / 2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0264



- 6. Averaging type = power (i.e., rms):
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
- 7. Sweep time = auto.
- 8. Perform a trace average of at least 100 traces.
- 9. A correction factor shall be added to the measurement results prior to comparing with the emission limit to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (rms) mode was used in step f), then the applicable correction factor is [10 log (1 / D)], where D is the duty cycle.
 - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is [20 log (1 / D)], where D is the duty cycle.
 - If a specific emission is demonstrated to be continuous (D ≥ 98%) rather than turning ON and OFF with with the transmit cycle, then no duty cycle correction is required for that emission.

Notes:

- 1. f < 30 Mz, extrapolation factor of 40 dB/decade of distance. $F_d = 40 \log(D_m/Ds)$
 - $f \ge 30$ Mb, extrapolation factor of 20 dB/decade of distance. $F_d = 20log(D_m/Ds)$ Where:
 - F_d = Distance factor in dB
 - D_m= Measurement distance in meters
 - D_s= Specification distance in meters
- 2. Factors(dB) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB) + or $F_d(dB)$
- 3. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
- 4. Average test would be performed if the peak result were greater than the average limit.
- 5.¹⁾ means restricted band.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <u>www.kctl.co.kr</u> Report No.: KR20-SRF0264

Page (14) of (18)

KCTL

Test results (Above 1 000 胍)_1 MBits/s(37 Bytes) / Band-edge

High Channel

Frequency	Pol.	Reading	Antenna Factor	Amp. + Cable	DCF	Result	Limit	Margin
[MHz]	[V/H]	[dB(µV)]	[dB]	[dB]	[dB]	[dB(µV/m)]	[dB(µV/m)]	[dB]
Peak data								
2 483.50 ¹⁾	Н	56.10	32.07	-29.21	-	58.96	74.00	15.04
Average Data								
2 483.50 ¹⁾	Н	37.67	32.07	-29.21	2.17	42.70	54.00	11.30



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <u>www.kctl.co.kr</u> Report No.: KR20-SRF0264



Page (15) of (18)

1 MBits/s(37 Bytes) / Harmonic

Low Channel

Frequency	Pol.	Reading	Antenna Factor	Amp. + Cable	DCF	Result	Limit	Margin
[MHz]	[V/H]	[dB(µV)]	[dB]	[dB]	[dB]	[dB(µV/m)]	[dB(µV/m)]	[dB]
Peak data								
4 801.38 ¹⁾	V	60.97	33.92	-52.94	-	41.95	74.00	32.05
7 202.94 ¹⁾	V	62.18	35.40	-53.09	-	44.49	74.00	29.51
Average Data								
No spurious emissions were detected within 20 dB of the limit.								



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <u>www.kctl.co.kr</u> Report No.: KR20-SRF0264



Page (16) of (18)

2 MBits/s(37 Bytes) / Band-edge

High Channel

Frequency	Pol.	Reading	Antenna Factor	Amp. + Cable	DCF	Result	Limit	Margin
[MHz]	[V/H]	[dB(µV)]	[dB]	[dB]	[dB]	[dB(µV/m)]	[dB(µV/m)]	[dB]
Peak data								
2 483.54 ¹⁾	Н	50.68	32.07	-29.21	-	53.54	74.00	20.46
Average Data								
2 483.54 ¹⁾	Н	35.01	32.07	-29.21	5.09	42.96	54.00	11.04



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <u>www.kctl.co.kr</u> Report No.: KR20-SRF0264



Page (17) of (18)

2 MBits/s(37 Bytes) / Harmonic

Low Channel

Frequency	Pol.	Reading	Antenna Factor	Amp. + Cable	DCF	Result	Limit	Margin
[MHz]	[V/H]	[dB(µV)]	[dB]	[dB]	[dB]	[dB(µV/m)]	[dB(µV/m)]	[dB]
Peak data								
4 815.88 ¹⁾	V	61.92	33.93	-53.35	-	42.50	74.00	31.50
7 202.94 ¹⁾	Н	62.04	35.40	-53.09	-	44.35	74.00	29.65
Average Data								
No spurious emissions were detected within 20 dB of the limit.								



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <u>www.kctl.co.kr</u> Report No.: KR20-SRF0264

Page (18) of (18)



6. Measurement equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum Analyzer	R&S	FSV30	100806	21.07.29
Spectrum Analyzer	R&S	FSV40	100989	21.01.03
Attenuator	Weinschel ENGINEERING	56-10	51395	21.01.22
Signal Generator	R&S	SMB100A	176206	21.01.21
Vector Signal Generator	R&S	SMBV100A	257566	21.07.13
Signal Generator	R&S	SMR40	100007	21.04.08
Highpass Filter	WT	WT-A1698-HS	WT160411001	21.05.11
Horn antenna	ETS.lindgren	3117	155787	20.10.24
Horn antenna	ETS.lindgren	3116	00086632	21.02.17
Attenuator	API Inmet	40AH2W-10	12	21.05.12
Broadband PreAmplifier	SCHWARZBECK	BBV9718	216	21.07.28
AMPLIFIER	L-3 Narda-MITEQ	AMF-7D-01001800 -22-10P	2031196	21.02.12
AMPLIFIER	L-3 Narda-MITEQ	JS44-18004000-33-8P	2000996	21.01.22
Antenna Mast	Innco Systems	MA4000-EP	303	-
Turn Table	Innco Systems	DT2000	79	-

End of test report