

FCC BT REPORT

Certification

Applicant Name:
SAMSUNG Electronics Co., Ltd.

Date of Issue:
May 27, 2021

Address:
129, Samsung-ro, Yeongtong-gu, Suwon-si,
Gyeonggi-do, 16677, Rep. of Korea

Test Site/Location:
74, Seoicheon-ro 578beon-gil, Majang-myeon,
Icheon-si, Gyeonggi-do, 17383 KOREA

Report No.: HCT-RF-2105-FC060

FCC ID: A3LSMM325FV

APPLICANT: SAMSUNG Electronics Co., Ltd.

Model: SM-M325FV/DS

Additional Model: -

EUT Type: Mobile Phone

Max. RF Output Power: 9.648 dBm (9.22 mW)

Frequency Range: 2 402 MHz – 2 480 MHz (Bluetooth)

Modulation type GFSK(Normal), π /4DQPSK and 8DPSK(EDR)

FCC Classification: FCC Part 15 Spread Spectrum Transmitter (DSS)

FCC Rule Part(s): Part 15 subpart C 15.247

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

Report No.: HCT-RF-2105-FC060

REVIEWED BY



Report prepared by : Sang Hoon Lee
Engineer of Telecommunication Testing Center

Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked *.

The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

* The report shall not be reproduced except in full(only partly) without approval of the laboratory.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2105-FC060	May 27, 2021	- First Approval Report

Table of Contents

REVIEWED BY	2
1. EUT DESCRIPTION	5
2. Requirements for Bluetooth transmitter(15.247).....	6
3. TEST METHODOLOGY	7
EUT CONFIGURATION	7
EUT EXERCISE	7
GENERAL TEST PROCEDURES	7
DESCRIPTION OF TEST MODES	7
4. INSTRUMENT CALIBRATION.....	8
5. FACILITIES AND ACCREDITATIONS	8
FACILITIES	8
EQUIPMENT	8
6. ANTENNA REQUIREMENTS	8
7. MEASUREMENT UNCERTAINTY	9
8. DESCRIPTION OF TESTS	10
9. SUMMARY OF TEST RESULTS	28
10. TEST RESULT	29
10.1 PEAK POWER	29
10.2 BAND EDGES.....	35
10.3 FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (99% BW).....	42
10.4 NUMBER OF HOPPING FREQUENCY	50
10.5 TIME OF OCCUPANCY (DWELL TIME)	54
10.6 SPURIOUS EMISSIONS.....	60
10.6.1 CONDUCTED SPURIOUS EMISSIONS	60
10.6.2 RADIATED SPURIOUS EMISSIONS.....	68
10.6.3 RADIATED RESTRICTED BAND EDGES	74
10.7 POWERLINE CONDUCTED EMISSIONS	78
11. LIST OF TEST EQUIPMENT	82
12. ANNEX A_ TEST SETUP PHOTO.....	84

1. EUT DESCRIPTION

Model	SM-M325FV/DS
Additional Model	-
EUT Type	Mobile Phone
Power Supply	DC 3.86 V
Frequency Range	2 402 MHz ~ 2 480 MHz
Max. RF Output Power	9.648 dBm (9.22 mW)
BT Operating Mode	Normal, EDR, AFH
Modulation Type	GFSK(Normal), $\pi/4$ DQPSK and 8DPSK(EDR)
Modulation Technique	FHSS
Number of Channels	79 Channels, Minimum 20 Channels(AFH)
Date(s) of Tests	April 19, 2021 ~ May 27, 2021
Serial number	Radiated: UDU1500M Conducted: UDN0325H

2. Requirements for Bluetooth transmitter(15.247)

This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:

- 1) This system is hopping pseudo-randomly.
- 2) Each frequency is used equally on the average by each transmitter.
- 3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
- 4) The receiver shifts frequencies in synchronization with the transmitted signals.
 - 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.
 - 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

3. TEST METHODOLOGY

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Device (ANSI C63.10-2013, KDB 558074) is used in the measurement of the test device.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013). To record the final measurements, the analyzer detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 120 kHz for frequencies below 1 GHz or 1 MHz for frequencies above 1 GHz. For average measurements above 1 GHz, the analyzer was set to peak detector with a reduced VBW setting(RBW = 1 MHz, VBW = 1/T Hz, where T = Pulse width).

DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. FACILITIES AND ACCREDITATIONS

FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil,

Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.

The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032).

EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

(1) The antennas of this E.U.T are permanently attached.

(2) The E.U.T Complies with the requirement of §15.203

7. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05

8. DESCRIPTION OF TESTS


8.1. Conducted Maximum Peak Output Power

Limit

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 W. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 W.
2. The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer. The Spectrum Analyzer is set to the peak detector mode. This test is performed with hopping off.

The Spectrum Analyzer is set to (7.8.5 in ANSI 63.10-2013 & Procedure 10(b)(6)(i) in KDB 558074 v05r02)

- 1) Span: approximately 5 times the 20 dB bandwidth, centered on a hopping channel
- 2) RBW > the 20 dB bandwidth of the emission being measured
- 3) VBW ≥ RBW
- 4) Sweep = Auto
- 5) Detector = Peak
- 6) Trace = Max hold

Sample Calculation


$$\begin{aligned}\text{Output Power} &= \text{Spectrum Reading Power} + \text{Power Splitter loss} + \text{Cable loss}(2 \text{ ea}) \\ &= 10 \text{ dBm} + 6 \text{ dB} + 1.5 \text{ dB} = 17.5 \text{ dBm}\end{aligned}$$

8.2. Conducted Band Edge(Out of Band Emissions)

Limit

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Configuration



Test Procedure

This test is performed with hopping off and hopping on.

The Spectrum Analyzer is set to (6.10.4 in ANSI 63.10-2013 & Procedure 8.5 and 8.6 in KDB 558074 v05r02)


- 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation
- 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level.
- 3) Attenuation: Auto (at least 10 dB preferred).
- 4) Sweep time: Coupled.
- 5) RBW: 100 kHz
- 6) VBW: 300 kHz
- 7) Detector: Peak
- 8) Trace: Max hold

8.3. Frequency Separation & 20 dB Bandwidth

Limit

According to §15.247(a)(1), Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Test Configuration



Test Procedure(Frequency Separation)

The Channel Separation test is performed with hopping on.

And the 20 dB Bandwidth test is performed with hopping off.

The Spectrum Analyzer is set to (7.8.2 in ANSI 63.10-2013 & Procedure 10(b)(6)(iii) in KDB 558074 v05r02)

- 1) Span: Wide enough to capture the peaks of two adjacent channels
- 2) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- 3) VBW \geq RBW
- 4) Sweep: Auto
- 5) Detector: Peak
- 6) Trace: Max hold
- 7) All the trace to stabilize.
- 8) Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

Test Procedure (20 dB Bandwidth)

And the 20 dB Bandwidth test is performed with hopping off.

The Spectrum Analyzer is set to (6.9.2 in ANSI 63.10-2013)


- 1) Span: Set between two times and five times the OBW
- 2) RBW: 1% to 5% of the OBW.
- 3) VBW $\geq 3 \times$ RBW
- 4) Sweep: Auto
- 5) Detector: Peak
- 6) Trace: Max hold
- 7) All the trace to stabilize.

8.4. Number of Hopping Frequencies

Limit

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands shall use at least 15 hopping frequencies.

Test Configuration



Test Procedure

The Bluetooth frequency hopping function of the EUT was enabled.

The Spectrum Analyzer is set to (7.8.3 in ANSI 63.10-2013 & Procedure 10(b)(4) in KDB 558074 v05r02)


- 1) Span: the frequency band of operation
- 2) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- 3) VBW \geq RBW
- 4) Sweep: Auto
- 5) Detector: Peak
- 6) Trace: Max hold
- 7) Allow the trace to stabilize.

8.5. Time of Occupancy

Limit

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

Test Configuration



Test Procedure

This test is performed with hopping off.

The Spectrum Analyzer is set to (7.8.4 in ANSI 63.10-2013 & Procedure 10(b)(6)(iv) in KDB 558074 v05r02)

- 1) Span: Zero span, centered on a hopping channel
- 2) RBW shall be \leq channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel.
- 3) Sweep = as necessary to capture the entire dwell time per hopping channel
- 4) Detector: Peak
- 5) Trace: Max hold

The marker-delta function was used to determine the dwell time.

Sample Calculation

The following calculation process is not relevant to our measurement results. It is just an example.

(1) Non-AFH Mode

- DH 5 (GFSK) : $2.890 \times (1600/6)/79 \times 31.6 = 308.27$ (ms)
- 2-DH 5 ($\pi/4$ DQPSK) : $2.890 \times (1600/6)/79 \times 31.6 = 308.27$ (ms)
- 3-DH 5 (8DPSK) : $2.890 \times (1600/6)/79 \times 31.6 = 308.27$ (ms)

(2) AFH Mode

- DH 5 (GFSK) : $2.890 \times (800/6)/20 \times 8.0 = 154.13$ (ms)
- 2-DH 5 ($\pi/4$ DQPSK) : $2.890 \times (800/6)/20 \times 8.0 = 154.13$ (ms)
- 3-DH 5 (8DPSK) : $2.890 \times (800/6)/20 \times 8.0 = 154.13$ (ms)

Note :

DH5 Packet need 5 time slot for transmitting and 1 time slot for receiving.

Then the system makes worst case 1600/6 hops per second with 79 channels. So the system have each channel 3.3755 times per second and so for 31.6 seconds the system have 106.667 times of appearance.

Each tx-time per appearance of DH5 is 2.890 ms.


Dwell time = Tx-time x 106.667 = 308.27 (ms)

8.6. Conducted Spurious Emissions

Limit

Conducted > 20 dBc

Test Configuration



Test Procedure

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer.

The Spectrum Analyzer is set to (7.8.8 in ANSI 63.10-2013 & Procedure 8.5 and 8.6 in KDB 558074 v05r02)

- 1) Span: 30 MHz to 10 times the operating frequency in GHz.
- 2) RBW: 100 kHz
- 3) VBW: 300 kHz
- 4) Sweep: Coupled
- 5) Detector: Peak

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

This test is performed with hopping off.

Factors for frequency

Freq(MHz)	Factor(dB)
30	26.09
100	26.19
200	26.26
300	26.37
400	26.43
500	26.46
600	26.46
700	26.50
800	26.53
900	26.57
1000	26.60
2000	26.88
2400	26.99
2480	26.99
2500	26.99
3000	27.09
4000	27.27
5000	27.43
5150	27.46
5850	27.55
6000	27.55
7000	27.72
8000	27.86
9000	27.99
10000	28.14
11000	28.21
12000	28.37
13000	28.55
14000	28.50
15000	28.57
16000	28.66
17000	28.74
18000	28.87
19000	28.94
20000	29.04
21000	29.42
22000	29.38
23000	29.61
24000	29.48
25000	29.55
26000	29.64

Note : 1. 2400 ~ 2500 MHz is fundamental frequency range.

2. Factor = Cable loss(2 EA) + Splitter loss(6 dB) + ATT (20dB)


8.7. Radiated Test

Limit


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



Test Procedure of Radiated spurious emissions(Below 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the ground plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor(0.009 MHz – 0.490 MHz) = $40\log(3\text{ m}/300\text{ m}) = - 80\text{ dB}$
Measurement Distance : 3 m
7. Distance Correction Factor(0.490 MHz – 30 MHz) = $40\log(3\text{ m}/30\text{ m}) = - 40\text{ dB}$

Measurement Distance : 3 m

8. Spectrum Setting

- Frequency Range = 9 kHz ~ 30 MHz
- Detector = Peak
- Trace = Maxhold
- RBW = 9 kHz
- VBW \geq 3 x RBW

9. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

KDB 414788 OFS and Chamber Correlation Justification

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

Test Procedure of Radiated spurious emissions(Below 1GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. The Hybrid antenna was placed at a location 3m from the EUT, which is varied from 1m to 4m to find out the highest emissions.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Spectrum Setting

(1) Measurement Type(Peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 100 kHz
- VBW \geq 3 x RBW

(2) Measurement Type(Quasi-peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Quasi-Peak
- RBW = 120 kHz

※ In general, (1) is used mainly

7. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L)

8. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already

beyond the background noise floor.

Test Procedure of Radiated spurious emissions (Above 1 GHz)

1. Radiated test is performed with hopping off.
2. The EUT is placed on a turntable, which is 1.5 m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting
 - (1) Measurement Type(Peak):
 - Measured Frequency Range : 1 GHz – 25 GHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 1 MHz
 - VBW $\geq 3 \times$ RBW
 - (2) Measurement Type(Average):
 - Average value of pulsed emissions
 - Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission and pulsed operation is employed, the average measurement shall determined from the peak field strength after correcting for the worst-case duty cycle as described in Number.14 (On Page. 23)
 - ◆ Duty Cycle Correction(AFH) = $20\log(\text{Worst Case Dwell Time} / 100\text{ms}) \text{ dB} = -24.7314 \text{ dB}$
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
11. Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance}) \text{ (dB)}$
12. Total
 - (1)Measurement(Peak)
Reading Value(Peak) + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(A.G) + Distance Factor(D.F)
 - (2)Measurement(Avg)
Reading Value(Peak) + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(A.G) + Distance Factor(D.F) + + DCCF(AFH)

13. Duty Cycle Correction Factor (79 channel hopping)

- a. Time to cycle through all channels= $\Delta t = \tau$ [ms] x 79 channels = 229.100 ms, where τ = pulse width
- b. $100 \text{ ms} / \Delta t$ [ms] = H \rightarrow Round up to next highest integer, H' =1
- c. Worst Case Dwell Time = τ [ms] x H' = 2.9 ms
- d. Duty Cycle Correction = $20\log$ (Worst Case Dwell Time/ 100ms) dB = -30.752 dB

14. Duty Cycle Correction Factor(AFH mode – minimum channel number case - 20 channels)

- a. Time to cycle through all channels= $\Delta t = \tau$ [ms] x 20 channels = 58.00 ms, where τ = pulse width
- b. $100 \text{ ms} / \Delta t$ [ms] = H \rightarrow Round up to next highest integer, H' = 2
- c. Worst Case Dwell Time = τ [ms] x H' = 5.800 ms
- d. Duty Cycle Correction(AFH) = $20\log$ (Worst Case Dwell Time/ 100ms) dB = -24.7314 dB

Test Procedure of Radiated Restricted Band Edge

1. Radiated test is performed with hopping off.
2. The EUT is placed on a turntable, which is 1.5 m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.
8. Spectrum Setting
 - (1) Measurement Type(Peak):
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 1 MHz
 - VBW $\geq 3 \times$ RBW
 - (2) Measurement Type(Average):
 - Average value of pulsed emissions
 - Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission and pulsed operation is employed, the average measurement shall determined from the peak field strength after correcting for the worst-case duty cycle as described in Number.14 (On Page. 23)
 - ◆ Duty Cycle Correction(AFH) = $20\log(\text{Worst Case Dwell Time} / 100\text{ms})$ dB = -24.7314 dB
9. Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance})$ (dB)
10. Total
 - [1]Normal (Peak)
= Reading Value(Peak) + Antenna Factor(A.F) + Cable Loss(C.L) – Amp Gain(A.G) + Attenuator(ATT)
+ Distance Factor(D.F)
 - [2]Normal (Avg)
= Reading Value(Peak) + Antenna Factor(A.F) + Cable Loss(C.L) – Amp Gain(A.G) + Attenuator(ATT)
+ Distance Factor(D.F) + D.C.C.F
11. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

8.8. AC Power line Conducted Emissions

Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56 ^(a)	56 to 46 ^(a)
0.50 to 5	56	46
5 to 30	60	50

^(a)Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.
5. The EUT is the device operating below 30 MHz.
 - For unterminated the Antenna, the AC line conducted tests are performed with the antenna connected
 - For terminated the Antenna, the AC line conducted tests are performed with a dummy load connected to the EUT antenna output terminal.

Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

8.9. Worst case configuration and mode

Radiated test

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone, Stand alone + External accessories (Earphone, etc)
 - Worstcase : Stand alone
2. EUT Axis
 - Radiated Spurious Emissions : X
 - Radiated Restricted Band Edge : X
3. All data rate of operation were investigated and the test results are worst case in highest datarate of each mode.
 - GFSK : DH5
 - $\pi/4$ DQPSK : 2-DH5
 - 8DPSK : 3-DH5
4. All position of loop antenna were investigated and the test result is a no critical peak found at all positions.
 - Position : Horizontal, Vertical, Parallel to the ground plane
5. We were performed the RSE test in condition of co-location. There has no significant emission raised.
 - WWAN+WLAN 5GHz+BT

Radiated test(DBS)

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone, Stand alone + External accessories(Earphone, etc)
 - Worstcase : Stand alone
2. EUT Axis
 - Radiated Spurious Emissions : X
3. The following tables show the worst case configurations determined during testing.

Description	Bluetooth Emission	5 GHz Emission
Antenna	WIFI/BT	WIFI/BT
Channel	78	165
Data Rate	339bytes	6 Mbps
Mode	GFSK : DH5	802.11a

AC Power line Conducted Emissions

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone + External accessories(Earphone, etc)+Travel Adapter, Stand alone+Travel Adapter
 - Worstcase : Stand alone + Travel Adapter

Conducted test

1. The EUT was configured with data rate of highest power.
 - GFSK : DH5
 - $\pi/4$ DQPSK : 2-DH5
 - 8DPSK : 3-DH5
2. AFH & Non-AFH were tested and the worst case results are reported.
 - Worst case : Non-AFH

9. SUMMARY OF TEST RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
20 dB Bandwidth	§15.247(a)(1)	N/A	Conducted	PASS
Occupied Bandwidth	N/A	N/A		N/A
Conducted Maximum Peak Output Power	§15.247(b)(1)	< 0.125 W		PASS
Carrier Frequency Separation	§15.247(a)(1)	> 25 kHz or >2/3 of the 20dB BW		PASS
Number of Hopping Frequencies	§15.247(a)(1)(iii)	≥ 15		PASS
Time of Occupancy	§15.247(a)(1)(iii)	< 400 ms		PASS
Conducted Spurious Emissions	§15.247(d)	> 20 dB for all out-of band emissions		PASS
Band Edge (Out of Band Emissions)	§15.247(d)	> 20 dB for all out-of band emissions		PASS
AC Power line Conducted Emissions	§15.207(a)	cf. Section 8.8		PASS
Radiated Spurious Emissions	§15.247(d), 15.205, 15.209	cf. Section 8.7		Radiated
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 8.7	PASS	

Note: Average Power data refer to SAR report

10. TEST RESULT

10.1 PEAK POWER

Channel	Frequency (MHz)	Output Power (GFSK)		Limit (mW)
		(dBm)	(mW)	
Low	2402	9.625	9.17	125
Mid	2441	9.648	9.22	
High	2480	9.256	8.43	

Channel	Frequency (MHz)	Output Power (8DPSK)		Limit (mW)
		(dBm)	(mW)	
Low	2402	8.805	7.59	125
Mid	2441	8.845	7.66	
High	2480	8.538	7.14	

Channel	Frequency (MHz)	Output Power ($\pi/4$ DQPSK)		Limit (mW)
		(dBm)	(mW)	
Low	2402	8.841	7.66	125
Mid	2441	8.838	7.65	
High	2480	8.583	7.22	

Note:

1. Spectrum reading values are not plot data.


The power results in plot is already including the actual values of loss for the splitter and cable combination.

2. Actual value of loss for the splitter and cable combination is 26.99 dB at 2400 MHz

and is 26.99 dB at 2500 MHz.

So, 26.99 dB is offset. And the offset gap in the 2.4 GHz range do not affect the conducted peak power final result.

Test Plots (GFSK)
Peak Power (CH.0)



Test Plots (GFSK)
Peak Power (CH.39)



Test Plots (GFSK)
Peak Power (CH.78)




Test Plots (8DPSK)
Peak Power (CH.0)



Test Plots (8DPSK)

Peak Power (CH.39)



Test Plots (8DPSK)

Peak Power (CH.78)



Test Plots ($\pi/4$ DQPSK)

Peak Power (CH.0)




Test Plots ($\pi/4$ DQPSK)

Peak Power (CH.39)



Test Plots ($\pi/4$ DQPSK)

Peak Power (CH.78)



10.2 BAND EDGES

Without hopping

Outside Frequency Band	GFSK (dB)	8DPSK (dB)	$\pi/4$ DQPSK (dB)	Limit (dBc)
Lower	61.787	55.793	56.576	20
Upper	62.600	62.386	62.426	

With hopping

Outside Frequency Band	GFSK (dB)	8DPSK (dB)	$\pi/4$ DQPSK (dB)	Limit (dBc)
Lower	63.471	58.635	58.421	20
Upper	63.253	62.232	62.633	

Note :

1. Spectrum reading values are not plot data.


The power results in plot is already including the actual values of loss for the splitter and cable combination.

2. Actual value of loss for the splitter and cable combination is 26.99 dB at 2400 MHz


and is 26.99 dB at 2500 MHz.

So, 26.99 dB is offset. And the offset gap in the 2.4 GHz range do not affect the conducted peak power final result.

Test Plots without hopping (GFSK)
Band Edges (CH.0)



Test Plots without hopping (GFSK)
Band Edges (CH.78)



Test Plots without hopping (8DPSK)
Band Edges (CH.0)




Test Plots without hopping (8DPSK)
Band Edges (CH.78)



Test Plots with hopping (GFSK)
Band Edges (CH.0)



Test Plots with hopping (GFSK)
Band Edges (CH.78)



Test Plots with hopping (8DPSK)
Band Edges (CH.0)




Test Plots with hopping (8DPSK)
Band Edges (CH.78)



Test Plots with hopping ($\pi/4$ DQPSK)
Band Edges (CH.0)



Test Plots with hopping ($\pi/4$ DQPSK)
Band Edges (CH.78)



10.3 FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (99% BW)

99% BW (kHz)			
Channel	GFSK	8DPSK	$\pi/4$ DQPSK
CH.0	757.96	1153.5	1146.3
CH.39	756.35	1150.6	1148.9
CH.78	752.73	1149.7	1145.9


20dB BW (kHz)			
Channel	GFSK	8DPSK	$\pi/4$ DQPSK
CH.0	848.5	1271	1261
CH.39	853.8	1268	1255
CH.78	849.6	1267	1257

Channel Separation(kHz)			Limit (kHz)
GFSK	8DPSK	$\pi/4$ DQPSK	
1004	998	994	>25 kHz or >2/3 of the 20dB BW

Test Plots (GFSK)
Channel Separation




Test Plots (8DPSK)
Channel Separation




Test Plots ($\pi/4$ DQPSK)

Channel Separation




Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (CH.0)




Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (CH.39)



Test Plots (GFSK)

20 dB Bandwidth & Occupied Bandwidth (CH.78)




Test Plots (8DPSK)

20 dB Bandwidth & Occupied Bandwidth (CH.0)



Test Plots (8DPSK)
20 dB Bandwidth & Occupied Bandwidth (CH.39)




Test Plots (8DPSK)
20 dB Bandwidth & Occupied Bandwidth (CH.78)



Test Plots ($\pi/4$ DQPSK)

20 dB Bandwidth & Occupied Bandwidth (CH.0)




Test Plots ($\pi/4$ DQPSK)

20 dB Bandwidth & Occupied Bandwidth (CH.39)



Test Plots ($\pi/4$ DQPSK)

20 dB Bandwidth & Occupied Bandwidth (CH.78)



10.4 NUMBER OF HOPPING FREQUENCY


Result (No. of CH)			Limit
GFSK	8DPSK	$\pi/4$ DQPSK	
79	79	79	>15

Note :

In case of AFH mode, minimum number of hopping channels is 20.

Test Plots (GFSK)

Number of Channels (2.4 GHz - 2.441 GHz)




Test Plots (GFSK)

Number of Channels (2.441 GHz - 2.483.5 GHz)




Test Plots (8DPSK)

Number of Channels (2.4 GHz - 2.441 GHz)




Test Plots (8DPSK)

Number of Channels (2.441 GHz - 2.483.5 GHz)




Test Plots ($\pi/4$ DQPSK)

Number of Channels (2.4 GHz - 2.441 GHz)



Test Plots ($\pi/4$ DQPSK)

Number of Channels (2.441 GHz - 2.483.5 GHz)



10.5 TIME OF OCCUPANCY (DWELL TIME)

Pulse Time (ms)	Channel	GFSK	8DPSK	$\pi/4$ DQPSK
	Low	2.885	2.890	2.885
	Mid	2.885	2.885	2.890
	High	2.885	2.885	2.885


Non-AFH Mode

Total of Dwell (ms)	Channel	GFSK	8DPSK	$\pi/4$ DQPSK	Period Time (s)	Limit (ms)
	Low	307.73	308.27	307.73	31.6	400
	Mid	307.73	307.73	308.27	31.6	
	High	307.73	307.73	307.73	31.6	

AFH Mode

Total of Dwell (ms)	Channel	GFSK	8DPSK	$\pi/4$ DQPSK	Period Time (s)	Limit (ms)
	Low	153.87	154.13	153.87	8.0	400
	Mid	153.87	153.87	154.13	8.0	
	High	153.87	153.87	153.87	8.0	

Test Plots (GFSK)
Dwell Time (CH.0)




Test Plots (GFSK)
Dwell Time (CH.39)




Test Plots (GFSK)
Dwell Time (CH.78)




Test Plots (8DPSK)
Dwell Time (CH.0)



Test Plots (8DPSK)
Dwell Time (CH.39)




Test Plots (8DPSK)
Dwell Time (CH.78)




Test Plots ($\pi/4$ DQPSK)

Dwell Time (CH.0)




Test Plots ($\pi/4$ DQPSK)

Dwell Time (CH.39)



Test Plots ($\pi/4$ DQPSK)

Dwell Time (CH.78)




10.6 SPURIOUS EMISSIONS

10.6.1 CONDUCTED SPURIOUS EMISSIONS


Test Result : please refer to the plot below.

In order to simplify the report, attached plots were only the worst case channel and data rate.


Test Plots (GFSK)- 30 MHz - 1 GHz
Spurious Emission (CH.39)




Test Plots (GFSK)- 1 GHz – 3 GHz
Spurious Emission (CH.39)




Test Plots(GFSK)- 3 GHz - 5 GHz
Spurious Emission (CH.39)




Test Plots (GFSK)- 5 GHz - 7 GHz
Spurious Emission (CH.39)




Test Plots(GFSK)- 7 GHz - 9 GHz
Spurious Emission (CH.39)




Test Plots(GFSK)- 9 GHz - 11 GHz
Spurious Emission (CH.39)




Test Plots(GFSK) 11 GHz - 13 GHz
Spurious Emission (CH.39)




Test Plots (GFSK)- 13 GHz – 15 GHz
Spurious Emission (CH.39)



Test Plots(GFSK)- 15 GHz - 17 GHz
Spurious Emission (CH.39)




Test Plots(GFSK)- 17 GHz - 19 GHz
Spurious Emission (CH.39)




Test Plots (GFSK)- 19 GHz - 21 GHz

Spurious Emission (CH.39)




Test Plots (GFSK)- 21 GHz - 23 GHz

Spurious Emission (CH.39)



Test Plots (GFSK)- 23 GHz - 25 GHz
Spurious Emission (CH.39)



10.6.2 RADIATED SPURIOUS EMISSIONS

Frequency Range : 9 kHz – 30MHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor = $40\log(\text{specific distance} / \text{test distance})$ (dB)
3. Limit line = specific Limits (dBuV) + Distance extrapolation factor
4. Radiated test is performed with hopping off.

Frequency Range : Below 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
2. Radiated test is performed with hopping off.

Frequency Range : Above 1 GHz

Operation Mode: CH Low(GFSK)

Frequency [MHz]	Reading [dBuV]	A.F+C.L-A.G+D.F [dB]	Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	42.41	4.08	V	0.00	46.49	73.98	27.49	PK
4804	42.41	4.08	V	-24.73	21.76	53.98	32.22	AV
7206	38.10	12.05	V	0.00	50.15	73.98	23.83	PK
7206	38.10	12.05	V	-24.73	25.42	53.98	28.56	AV
4804	42.98	4.08	H	0.00	47.06	73.98	26.92	PK
4804	42.98	4.08	H	-24.73	22.33	53.98	31.65	AV
7206	38.72	12.05	H	0.00	50.77	73.98	23.21	PK
7206	38.72	12.05	H	-24.73	26.04	53.98	27.94	AV

Operation Mode: CH Mid(GFSK)

Frequency [MHz]	Reading [dBuV]	A.F+C.L-A.G+D.F [dB]	Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4882	43.49	4.01	V	0.00	47.50	73.98	26.48	PK
4882	43.49	4.01	V	-24.73	22.77	53.98	31.21	AV
7323	38.68	12.49	V	0.00	51.17	73.98	22.81	PK
7323	38.68	12.49	V	-24.73	26.44	53.98	27.54	AV
4882	43.85	4.01	H	0.00	47.86	73.98	26.12	PK
4882	43.85	4.01	H	-24.73	23.13	53.98	30.85	AV
7323	39.27	12.49	H	0.00	51.76	73.98	22.22	PK
7323	39.27	12.49	H	-24.73	27.03	53.98	26.95	AV

Operation Mode: CH High(GFSK)

Frequency [MHz]	Reading [dBuV]	A.F+C.L-A.G+D.F [dB]	Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	45.42	4.55	V	0.00	49.97	73.98	24.01	PK
4960	45.42	4.55	V	-24.73	25.24	53.98	28.74	AV
7440	39.25	12.60	V	0.00	51.85	73.98	22.13	PK
7440	39.25	12.60	V	-24.73	27.12	53.98	26.86	AV
4960	45.84	4.55	H	0.00	50.39	73.98	23.59	PK
4960	45.84	4.55	H	-24.73	25.66	53.98	28.32	AV
7440	39.59	12.60	H	0.00	52.19	73.98	21.79	PK
7440	39.59	12.60	H	-24.73	27.46	53.98	26.52	AV

Operation Mode: CH Low($\pi/4$ DQPSK)

Frequency [MHz]	Reading [dBuV]	A.F+C.L-A.G+D.F [dB]	Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	41.36	4.08	V	0.00	45.44	73.98	28.54	PK
4804	41.36	4.08	V	-24.73	20.71	53.98	33.27	AV
7206	37.65	12.05	V	0.00	49.70	73.98	24.28	PK
7206	37.65	12.05	V	-24.73	24.97	53.98	29.01	AV
4804	41.81	4.08	H	0.00	45.89	73.98	28.09	PK
4804	41.81	4.08	H	-24.73	21.16	53.98	32.82	AV
7206	38.25	12.05	H	0.00	50.30	73.98	23.68	PK
7206	38.25	12.05	H	-24.73	25.57	53.98	28.41	AV

Operation Mode: CH Mid($\pi/4$ DQPSK)

Frequency [MHz]	Reading [dBuV]	A.F+C.L-A.G+D.F [dB]	Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4882	42.40	4.01	V	0.00	46.41	73.98	27.57	PK
4882	42.40	4.01	V	-24.73	21.68	53.98	32.30	AV
7323	38.33	12.49	V	0.00	50.82	73.98	23.16	PK
7323	38.33	12.49	V	-24.73	26.09	53.98	27.89	AV
4882	42.81	4.01	H	0.00	46.82	73.98	27.16	PK
4882	42.81	4.01	H	-24.73	22.09	53.98	31.89	AV
7323	38.76	12.49	H	0.00	51.25	73.98	22.73	PK
7323	38.76	12.49	H	-24.73	26.52	53.98	27.46	AV

Operation Mode: CH High($\pi/4$ DQPSK)

Frequency [MHz]	Reading [dBuV]	A.F+C.L-A.G+D.F [dB]	Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	45.73	4.55	V	0.00	50.28	73.98	23.70	PK
4960	44.73	4.55	V	-24.73	24.55	53.98	29.43	AV
7440	38.96	12.60	V	0.00	51.56	73.98	22.42	PK
7440	38.96	12.60	V	-24.73	26.83	53.98	27.15	AV
4960	45.18	4.55	H	0.00	49.73	73.98	24.25	PK
4960	45.18	4.55	H	-24.73	25.00	53.98	28.98	AV
7440	39.39	12.60	H	0.00	51.99	73.98	21.99	PK
7440	39.39	12.60	H	-24.73	27.26	53.98	26.72	AV

Operation Mode: CH Low(8DPSK)

Frequency [MHz]	Reading [dBuV]	A.F+C.L-A.G+D.F [dB]	Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4804	41.29	4.08	V	0.00	45.37	73.98	28.61	PK
4804	41.29	4.08	V	-24.73	20.64	53.98	33.34	AV
7206	38.07	12.05	V	0.00	50.12	73.98	23.86	PK
7206	38.07	12.05	V	-24.73	25.39	53.98	28.59	AV
4804	41.83	4.08	H	0.00	45.91	73.98	28.07	PK
4804	41.83	4.08	H	-24.73	21.18	53.98	32.80	AV
7206	38.63	12.05	H	0.00	50.68	73.98	23.30	PK
7206	38.63	12.05	H	-24.73	25.95	53.98	28.03	AV

Operation Mode: CH Mid(8DPSK)


Frequency [MHz]	Reading [dBuV]	A.F+C.L-A.G+D.F [dB]	Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4882	42.42	4.01	V	0.00	46.43	73.98	27.55	PK
4882	42.42	4.01	V	-24.73	21.70	53.98	32.28	AV
7323	38.67	12.49	V	0.00	51.16	73.98	22.82	PK
7323	38.67	12.49	V	-24.73	26.43	53.98	27.55	AV
4882	42.84	4.01	H	0.00	46.85	73.98	27.13	PK
4882	42.84	4.01	H	-24.73	22.12	53.98	31.86	AV
7323	39.03	12.49	H	0.00	51.52	73.98	22.46	PK
7323	39.03	12.49	H	-24.73	26.79	53.98	27.19	AV

Operation Mode: CH High(8DPSK)


Frequency [MHz]	Reading [dBuV]	A.F+C.L-A.G+D.F [dB]	Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4960	44.78	4.55	V	0.00	49.33	73.98	24.65	PK
4960	44.78	4.55	V	-24.73	24.60	53.98	29.38	AV
7440	38.94	12.60	V	0.00	51.54	73.98	22.44	PK
7440	38.94	12.60	V	-24.73	26.81	53.98	27.17	AV
4960	45.27	4.55	H	0.00	49.82	73.98	24.16	PK
4960	45.27	4.55	H	-24.73	25.09	53.98	28.89	AV
7440	39.15	12.60	H	0.00	51.75	73.98	22.23	PK
7440	39.15	12.60	H	-24.73	27.02	53.98	26.96	AV

RESULT PLOTS


Radiated Spurious Emissions plot – Average & Peak Reading (GFSK, Ch.78 3rd Harmonic, X- H)



Radiated Spurious Emissions plot – Average & Peak Reading ($\pi/4$ DQPSK, Ch.78 3rd Harmonic, X- H)



Radiated Spurious Emissions plot – Average & Peak Reading (8DPSK, Ch.78 3rd Harmonic, X- H)



Note:

Plot of worst case are only reported.

10.6.3 RADIATED RESTRICTED BAND EDGES

Operation Mode	Normal(GFSK)
Operating Frequency	2402 MHz, 2480 MHz
Channel No	CH 0, CH 78

Frequency [MHz]	Reading [dBuV]	* A.F+C.L-AMP+ATT+D.F [dB]	Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	47.76	3.32	H	0	51.08	73.98	22.90	PK
2390.0	47.76	3.32	H	-24.73	26.35	53.98	27.63	AV
2390.0	47.69	3.32	V	0	51.01	73.98	22.97	PK
2390.0	47.69	3.32	V	-24.73	26.28	53.98	27.70	AV
2483.5	60.58	3.78	H	0	64.36	73.98	9.62	PK
2483.5	60.58	3.78	H	-24.73	39.63	53.98	14.35	AV
2483.5	56.77	3.78	V	0	60.55	73.98	13.43	PK
2483.5	56.77	3.78	V	-24.73	35.82	53.98	18.16	AV

Operation Mode	EDR($\pi/4$ DQPSK)
Operating Frequency	2402 MHz, 2480 MHz
Channel No	CH 0, CH 78


Frequency [MHz]	Reading [dBuV]	* A.F+C.L-AMP+ATT+D.F [dB]	Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	47.32	3.32	H	0	50.64	73.98	23.34	PK
2390.0	47.32	3.32	H	-24.73	25.91	53.98	28.07	AV
2390.0	47.30	3.32	V	0	50.62	73.98	23.36	PK
2390.0	47.30	3.32	V	-24.73	25.89	53.98	28.09	AV
2483.5	60.40	3.78	H	0	64.18	73.98	9.80	PK
2483.5	60.40	3.78	H	-24.73	39.45	53.98	14.53	AV
2483.5	56.82	3.78	V	0	60.60	73.98	13.38	PK
2483.5	56.82	3.78	V	-24.73	35.87	53.98	18.11	AV

Operation Mode	EDR(8DPSK)
Operating Frequency	2402 MHz, 2480 MHz
Channel No	CH 0, CH 78


Frequency [MHz]	Reading [dBuV]	* A.F+C.L-AMP+ATT+D.F [dB]	Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	47.18	3.32	H	0	50.50	73.98	23.48	PK
2390.0	47.18	3.32	H	-24.73	25.77	53.98	28.21	AV
2390.0	47.12	3.32	V	0	50.44	73.98	23.54	PK
2390.0	47.12	3.32	V	-24.73	25.71	53.98	28.27	AV
2483.5	60.35	3.78	H	0	64.13	73.98	9.85	PK
2483.5	60.35	3.78	H	-24.73	39.40	53.98	14.58	AV
2483.5	57.00	3.78	V	0	60.78	73.98	13.20	PK
2483.5	57.00	3.78	V	-24.73	36.05	53.98	17.93	AV

RESULT PLOTS


Radiated Restricted Band Edges plot – Average & Peak Reading (GFSK, Ch.78, X-H)



Radiated Restricted Band Edges plot – Average & Peak Reading ($\pi/4$ DQPSK, Ch.78, X-H)



Radiated Restricted Band Edges plot – Average & Peak Reading (8DPSK, Ch.78, X-H)



Note:

Plot of worst case are only reported.

10.7 POWERLINE CONDUCTED EMISSIONS

Conducted Emissions (Line 1)

BT MODE_L1


1 / 2

Test Report

Common Information

EUT : SM-M325FV/DS
 Manufacturer : SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions : BT MODE_L1

Full Spectrum



Final Result QPK

Frequency (MHz)	QuasiPeak	Limit (dBuV)	Margin	Bandwidth	Line	Filter	Corr. (dB)
0.1500	30.07	66.00	35.93	9.000	L1	OFF	9.6
0.1770	30.75	64.63	33.88	9.000	L1	OFF	9.6
0.2063	29.42	63.36	33.94	9.000	L1	OFF	9.6
0.2355	28.10	62.25	34.16	9.000	L1	OFF	9.6
0.2648	35.21	61.28	26.07	9.000	L1	OFF	9.6
0.7070	29.93	56.00	26.07	9.000	L1	OFF	9.6
1.1165	21.18	56.00	34.82	9.000	L1	OFF	9.6
1.9130	16.26	56.00	39.74	9.000	L1	OFF	9.6
4.0010	17.05	56.00	38.95	9.000	L1	OFF	9.7
4.2328	20.89	56.00	35.11	9.000	L1	OFF	9.7
4.3498	14.04	56.00	41.96	9.000	L1	OFF	9.7
4.7908	16.07	56.00	39.93	9.000	L1	OFF	9.7
11.3045	22.71	60.00	37.29	9.000	L1	OFF	9.9
11.3338	26.10	60.00	33.90	9.000	L1	OFF	9.9
11.5093	21.15	60.00	38.85	9.000	L1	OFF	9.9
11.5385	21.00	60.00	39.00	9.000	L1	OFF	9.9
11.5678	20.46	60.00	39.54	9.000	L1	OFF	9.9
11.7883	21.06	60.00	38.94	9.000	L1	OFF	9.9

2021-04-21

오전 3:36:57

BT MODE_L1

2 / 2

Final Result_CAV

Frequency (MHz)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.1500	8.83	56.00	47.17	9.000	L1	OFF	9.6
0.1770	7.95	54.63	46.68	9.000	L1	OFF	9.6
0.2063	10.70	53.36	42.66	9.000	L1	OFF	9.6
0.2355	7.39	52.25	44.86	9.000	L1	OFF	9.6
0.2648	7.30	51.28	43.98	9.000	L1	OFF	9.6
0.7070	13.49	46.00	32.51	9.000	L1	OFF	9.6
1.1188	5.54	46.00	40.46	9.000	L1	OFF	9.6
1.9130	5.42	46.00	40.58	9.000	L1	OFF	9.6
4.0010	7.40	46.00	38.60	9.000	L1	OFF	9.7
4.0595	7.97	46.00	38.03	9.000	L1	OFF	9.7
4.1180	7.80	46.00	38.20	9.000	L1	OFF	9.7
4.5883	7.53	46.00	38.47	9.000	L1	OFF	9.7
11.2348	9.13	50.00	40.87	9.000	L1	OFF	9.9
11.3203	9.51	50.00	40.49	9.000	L1	OFF	9.9
11.3518	9.97	50.00	40.03	9.000	L1	OFF	9.9
11.4980	9.94	50.00	40.06	9.000	L1	OFF	9.9
11.5385	15.64	50.00	34.36	9.000	L1	OFF	9.9
11.5655	9.56	50.00	40.44	9.000	L1	OFF	9.9

2021-04-21

오전 3:36:57

Conducted Emissions (Line 2)

BT MODE_N


1 / 2

Test Report

Common Information

EUT : SM-M325FV/DS
 Manufacturer : SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions : BT MODE_N

Full Spectrum



Preview Result 2-AVG Preview Result 1-PK+ FCC CLASS B_QP
 FCC CLASS B_AV Final_Result QPK Final_Result CAV

Final Result QPK

Frequency (MHz)	QuasiPeak	Limit (dBuV)	Margin	Bandwidth	Line	Filter	Corr. (dB)
0.1545	20.89	65.75	44.87	9.000	N	OFF	9.6
0.1613	14.43	65.40	50.97	9.000	N	OFF	9.6
0.1680	20.43	65.06	44.63	9.000	N	OFF	9.6
0.1725	26.82	64.84	38.02	9.000	N	OFF	9.6
0.1815	25.32	64.42	39.10	9.000	N	OFF	9.6
0.1950	14.63	63.82	49.20	9.000	N	OFF	9.6
3.7040	15.75	56.00	40.25	9.000	N	OFF	9.7
3.7310	13.05	56.00	42.95	9.000	N	OFF	9.7
3.7445	17.90	56.00	38.10	9.000	N	OFF	9.7
3.7693	20.48	56.00	35.52	9.000	N	OFF	9.7
4.0640	15.93	56.00	40.07	9.000	N	OFF	9.7
4.1338	8.41	56.00	47.59	9.000	N	OFF	9.7
11.2978	17.07	60.00	42.93	9.000	N	OFF	9.8
11.3293	16.25	60.00	43.75	9.000	N	OFF	9.8
11.3450	16.45	60.00	43.55	9.000	N	OFF	9.8
11.3743	17.19	60.00	42.81	9.000	N	OFF	9.8
11.3855	20.66	60.00	39.34	9.000	N	OFF	9.8
11.4733	16.52	60.00	43.48	9.000	N	OFF	9.8

2021-04-21

오전 3:31:40

BT MODE_N

2 / 2

Final Result CAV

Frequency (MHz)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.1500	7.95	56.00	48.05	9.000	N	OFF	9.6
0.1770	7.39	54.63	47.24	9.000	N	OFF	9.6
0.2063	7.04	53.36	46.32	9.000	N	OFF	9.6
0.2355	6.76	52.25	45.50	9.000	N	OFF	9.6
0.2648	6.77	51.28	44.51	9.000	N	OFF	9.6
0.3098	3.05	49.98	46.93	9.000	N	OFF	9.6
0.7070	12.18	46.00	33.82	9.000	N	OFF	9.6
3.7670	8.85	46.00	37.15	9.000	N	OFF	9.7
3.7963	9.02	46.00	36.98	9.000	N	OFF	9.7
3.8255	9.01	46.00	36.99	9.000	N	OFF	9.7
4.0618	15.97	46.00	30.03	9.000	N	OFF	9.7
4.0910	8.09	46.00	37.91	9.000	N	OFF	9.7
4.2665	7.34	46.00	38.66	9.000	N	OFF	9.7
11.2663	7.55	50.00	42.45	9.000	N	OFF	9.8
11.2978	7.34	50.00	42.66	9.000	N	OFF	9.8
11.3293	7.44	50.00	42.56	9.000	N	OFF	9.8
11.3878	7.68	50.00	42.32	9.000	N	OFF	9.8
11.4125	7.88	50.00	42.12	9.000	N	OFF	9.8

2021-04-21

오전 3:31:40

11. LIST OF TEST EQUIPMENT

Conducted Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216 / LISN	09/04/2020	Annual	102245
Rohde & Schwarz	ESR / EMI Test Receiver	09/16/2020	Annual	101910
ESPEC	SU-642 / Temperature Chamber	07/30/2020	Annual	0093000718
Agilent	N9020A / Signal Analyzer	05/03/2021	Annual	MY51110085
Agilent	N9030A / Signal Analyzer	03/09/2021	Annual	MY49432108
Agilent	N1911A / Power Meter	04/08/2021	Annual	MY45100523
Agilent	N1921A / Power Sensor	04/08/2021	Annual	MY57820067
Agilent	87300B / Directional Coupler	11/10/2020	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	02/09/2021	Annual	10545
HP	E3632A / DC Power Supply	09/16/2020	Annual	MY40004427
HP	8493C / Attenuator(10 dB)(DC-26.5 GHz)	06/26/2020	Annual	07560
HP	8493C / Attenuator(10 dB)(DC-26.5 GHz)	07/03/2020	Annual	08285
Rohde & Schwarz	18N-20dB / Attenuator(20 dB)	03/08/2021	Annual	8
Rohde & Schwarz	EMC32 / Software	N/A	N/A	N/A
HCT CO., LTD.	FCC WLAN&BT&BLE Conducted Test Software v3.0	N/A	N/A	N/A
Rohde & Schwarz	CBT / Bluetooth Tester	02/23/2021	Annual	100808

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Radiated Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Innco system	CO3000 / Controller(Antenna mast)	N/A	N/A	CO3000-4p
Innco system	MA4640/800-XP-EP / Antenna Position Tower	N/A	N/A	N/A
Audix	EM1000 / Controller	N/A	N/A	060520
Audix	Turn Table	N/A	N/A	N/A
TNM system	FBSM-01B / Amp & Filter Bank Switch Controller	N/A	N/A	N/A
Schwarzbeck	Loop Antenna	03/19/2020	Biennial	1513-333
Schwarzbeck	VULB 9168 / Hybrid Antenna	08/02/2019	Biennial	01039
Schwarzbeck	BBHA 9120D / Horn Antenna	08/01/2019	Biennial	912D-1151
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	02/11/2020	Biennial	BBHA9170124
Rohde & Schwarz	FSV(10 Hz ~ 40 GHz) / Spectrum Analyzer	05/14/2021	Annual	101055
Wainwright Instruments	WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter	01/06/2021	Annual	2
Wainwright Instruments	WRCJV12-4900-5100-5900-6100-50SS	06/24/2021	Annual	5
Wainwright Instruments	WRCJV12-4900-5100-5900-6100-50SS	06/24/2021	Annual	6
CERNEX	CBL18265035 / Power Amplifier	12/04/2020	Annual	22966
CERNEX	CBL26405040 / Power Amplifier	03/23/2021	Annual	25956
TESCOM	TC-3000C / Bluetooth Tester	04/19/2021	Annual	3000C000175
TNM system	FBSM-05B / HPF(3~18GHz) + LNA1(1~18GHz)	01/20/2021	Annual	F6
TNM system	FBSM-05B / ATT(10dB) + LNA1(1~18GHz)	01/20/2021	Annual	None
TNM system	FBSM-05B / ATT(3dB) + LNA1(1~18GHz)	01/20/2021	Annual	None
TNM system	FBSM-05B / LNA1(1~18GHz)	01/20/2021	Annual	25540
TNM system	FBSM-05B / HPF(7~18GHz) + LNA2(6~18GHz)	01/20/2021	Annual	28550
TNM system	FBSM-05B / Thru(30MHz ~ 18GHz)	01/20/2021	Annual	None

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
3. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5(Version : 2017).

12. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2105-FC060-P