


PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

http://www.pctestlab.com



MEASUREMENT REPORT FCC Part 15.407 UNII 802.11a/n/ac

Applicant Name:
Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:
5/4 - 7/13/2017
Test Site/Location:
PCTEST Lab, Columbia, MD, USA
Test Report Serial No.:
1M1705180172-06.A3L

| | |
|-------------------|--------------------------------------|
| FCC ID: | A3LSMN950F |
| APPLICANT: | Samsung Electronics Co., Ltd. |

Application Type: Certification
Model: SM-N950F, SM-N950F/DS, SM-N950X
EUT Type: Portable Handset
FCC Classification: Unlicensed National Information Infrastructure (UNII)
FCC Rule Part(s): Part 15.407
Test Procedure(s): KDB 789033 D02 v01r04, KDB 648474 D03 v01r04, KDB 662911 D01 v02r01

| UNII Band | Channel Bandwidth (MHz) | Tx Frequency (MHz) | ANT1 | | ANT2 | | MIMO | |
|-----------|-------------------------|--------------------|-----------------|------------------|-----------------|------------------|-----------------|------------------|
| | | | Max. Power (mW) | Max. Power (dBm) | Max. Power (mW) | Max. Power (dBm) | Max. Power (mW) | Max. Power (dBm) |
| 1 | 20 | 5180 - 5240 | 54.954 | 17.40 | 47.534 | 16.77 | 101.391 | 20.06 |
| 2A | | 5260 - 5320 | 50.933 | 17.07 | 48.084 | 16.82 | 98.628 | 19.94 |
| 2C | | 5500 - 5720 | 48.753 | 16.88 | 53.951 | 17.32 | 99.660 | 19.99 |
| 3 | | 5745 - 5825 | 50.119 | 17.00 | 52.845 | 17.23 | 102.390 | 20.10 |
| 1 | 40 | 5190 - 5230 | 34.754 | 15.41 | 33.266 | 15.22 | 67.488 | 18.29 |
| 2A | | 5270 - 5310 | 31.623 | 15.00 | 34.119 | 15.33 | 65.274 | 18.15 |
| 2C | | 5510 - 5710 | 35.075 | 15.45 | 32.734 | 15.15 | 67.509 | 18.29 |
| 3 | | 5755 - 5795 | 32.509 | 15.12 | 33.343 | 15.23 | 65.851 | 18.19 |
| 1 | 80 | 5210 | 21.827 | 13.39 | 22.336 | 13.49 | 44.163 | 16.45 |
| 2A | | 5290 | 18.923 | 12.77 | 19.011 | 12.79 | 37.934 | 15.79 |
| 2C | | 5530 - 5690 | 21.827 | 13.39 | 21.528 | 13.33 | 43.060 | 16.34 |
| 3 | | 5775 | 21.878 | 13.40 | 22.336 | 13.49 | 44.213 | 16.46 |

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 789033 D02 v01r04. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Randy Ortanez
President



| | | | | |
|--|---------------------------------------|--|---------------|--|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 1 of 228 | |

© 2017 PCTEST Engineering Laboratory, Inc.

V 6.4

05/03/2017

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

TABLE OF CONTENTS


| | | |
|---|--|-----|
| FCC PART 15.407 MEASUREMENT REPORT | | 3 |
| 1.0 INTRODUCTION..... | | 4 |
| 1.1 Scope | | 4 |
| 1.2 PCTEST Test Location..... | | 4 |
| 2.0 PRODUCT INFORMATION | | 5 |
| 2.1 Equipment Description | | 5 |
| 2.2 Device Capabilities..... | | 5 |
| 2.3 Test Configuration..... | | 7 |
| 2.4 EMI Suppression Device(s)/Modifications | | 7 |
| 3.0 DESCRIPTION OF TESTS | | 8 |
| 3.1 Evaluation Procedure | | 8 |
| 3.2 AC Line Conducted Emissions | | 8 |
| 3.3 Radiated Emissions..... | | 9 |
| 3.4 Environmental Conditions..... | | 9 |
| 4.0 ANTENNA REQUIREMENTS | | 10 |
| 5.0 MEASUREMENT UNCERTAINTY..... | | 11 |
| 6.0 TEST EQUIPMENT CALIBRATION DATA..... | | 12 |
| 7.0 TEST RESULTS | | 13 |
| 7.1 Summary..... | | 13 |
| 7.2 26dB Bandwidth Measurement – 802.11«anac» | | 14 |
| 7.3 6dB Bandwidth Measurement – 802.11«anac» | | 47 |
| 7.4 UNII Output Power Measurement – 802.11«anac» | | 58 |
| 7.5 Maximum Power Spectral Density – 802.11«anac» | | 64 |
| 7.6 Frequency Stability..... | | 108 |
| 7.7 Radiated Spurious Emission Measurements – Above 1GHz | | 112 |
| 7.7.1 Antenna-1 Radiated Spurious Emission Measurements | | 116 |
| 7.7.2 Antenna-2 Radiated Spurious Emission Measurements | | 130 |
| 7.7.3 Simultaneous Tx Radiated Spurious Emissions Measurements..... | | 144 |
| 7.7.4 Antenna-1 Radiated Band Edge Measurements (20MHz BW)..... | | 153 |
| 7.7.5 Antenna-1 Radiated Band Edge Measurements (40MHz BW)..... | | 158 |
| 7.7.6 Antenna-1 Radiated Band Edge Measurements (80MHz BW)..... | | 163 |
| 7.7.7 Antenna-2 Radiated Band Edge Measurements (20MHz BW)..... | | 168 |
| 7.7.8 Antenna-2 Radiated Band Edge Measurements (40MHz BW)..... | | 173 |
| 7.7.9 Antenna-2 Radiated Band Edge Measurements (80MHz BW)..... | | 178 |
| 7.7.10 MIMO Radiated Band Edge Measurements (20MHz BW) | | 183 |
| 7.7.11 MIMO Radiated Band Edge Measurements (40MHz BW) | | 191 |
| 7.7.12 MIMO Radiated Band Edge Measurements (80MHz BW) | | 199 |
| 7.8 Radiated Spurious Emissions Measurements – Below 1GHz..... | | 207 |
| 7.9 Line-Conducted Test Data..... | | 212 |
| 8.0 CONCLUSION..... | | 218 |
| Appendix A. 802.11a Dual Tx | | 219 |
| A.2 Dual Tx Radiated Restricted Band Edge Measurements..... | | 220 |

| | | | |
|--|---|---|--|
| FCC ID: A3LSMN950F |  FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 2 of 228 |



MEASUREMENT REPORT

FCC Part 15.407



§ 2.1033 General Information

APPLICANT: Samsung Electronics Co., Ltd.

APPLICANT ADDRESS: 129, Samsung-ro,
Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea

TEST SITE: PCTEST ENGINEERING LABORATORY, INC.

TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA

FCC RULE PART(S): Part 15.407

BASE MODEL: SM-N950F, SM-N950F/DS, SM-N950X

FCC ID: A3LSMN950F

FCC CLASSIFICATION: Unlicensed National Information Infrastructure (UNII)

Test Device Serial No.: 2A50A, 142D3, 15B51, 2A4C1, 2A4C3, 78045
 Production Pre-Production Engineering

DATE(S) OF TEST: 5/4 - 7/13/2017

TEST REPORT S/N: 1M1705180172-06.A3L

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

| | | | | |
|--|---|--|---|--|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 3 of 228 | |

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern'tl (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

| | | | | |
|---|--------------------------------|--|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 4 of 228 |

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMN950F**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC, ANT+

| Band 1 | | Band 2A | | Band 2C | | Band 3 | |
|--------|-----------------|---------|-----------------|---------|-----------------|--------|-----------------|
| Ch. | Frequency (MHz) | Ch. | Frequency (MHz) | Ch. | Frequency (MHz) | Ch. | Frequency (MHz) |
| 36 | 5180 | 52 | 5260 | 100 | 5500 | 149 | 5745 |
| : | : | : | : | : | : | : | : |
| 42 | 5210 | 56 | 5280 | 120 | 5600 | 157 | 5785 |
| : | : | : | : | : | : | : | : |
| 48 | 5240 | 64 | 5320 | 144 | 5720 | 165 | 5825 |

Table 2-1. 802.11a / 802.11n / 802.11ac (20MHz) Frequency / Channel Operations

| Band 1 | | Band 2A | | Band 2C | | Band 3 | |
|--------|-----------------|---------|-----------------|---------|-----------------|--------|-----------------|
| Ch. | Frequency (MHz) | Ch. | Frequency (MHz) | Ch. | Frequency (MHz) | Ch. | Frequency (MHz) |
| 38 | 5190 | 54 | 5270 | 102 | 5510 | 151 | 5755 |
| : | : | : | : | : | : | : | : |
| 46 | 5230 | 62 | 5310 | 118 | 5590 | 159 | 5795 |
| | | | | : | : | | |
| | | | | 142 | 5710 | | |

Table 2-2. 802.11n / 802.11ac (40MHz BW) Frequency / Channel Operations

| Band 1 | | Band 2A | | Band 2C | | Band 3 | |
|--------|-----------------|---------|-----------------|---------|-----------------|--------|-----------------|
| Ch. | Frequency (MHz) | Ch. | Frequency (MHz) | Ch. | Frequency (MHz) | Ch. | Frequency (MHz) |
| 42 | 5210 | 58 | 5290 | 106 | 5530 | 155 | 5775 |
| | | | | : | : | | |
| | | | | 138 | 5690 | | |

Table 2-3. 802.11ac (80MHz BW) Frequency / Channel Operations

| | | | | |
|---|---|--|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 5 of 228 |

Notes:

1. 5GHz NII operation is possible in 20MHz, and 40MHz, and 80MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) of KDB 789033 D02 v01r04. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

| Maximum Achievable Duty Cycles | | | | |
|--------------------------------|-----------|----------------|------|------|
| 802.11 Mode/Band | | Duty Cycle [%] | | |
| | | ANT1 | ANT2 | MIMO |
| 5GHz | a | 99.0 | 99.5 | N/A |
| | n (HT20) | 99.0 | 99.0 | 99.5 |
| | ac (HT20) | 99.3 | 99.0 | 98.1 |
| | n (HT40) | 98.5 | 98.5 | 99.0 |
| | ac (HT40) | 99.5 | 98.5 | 98.1 |
| | ac (HT80) | 99.0 | 98.0 | 96.7 |

Table 2-4. Measured Duty Cycles

2. The device employs MIMO technology. Below are the possible configurations.

| WiFi Configurations | | SISO | | SDM | | CDD | |
|---------------------|--------------|------|------|------|------|------|------|
| | | ANT1 | ANT2 | ANT1 | ANT2 | ANT1 | ANT2 |
| 5GHz | 11a | ✓ | ✓ | ✗ | ✗ | ✓ | ✓ |
| | 11n (20MHz) | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | 11n (40MHz) | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | 11ac (80MHz) | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

Table 2-5. Frequency / Channel Operations

✓ = Support ; ✗ = NOT Support
SISO = Single Input Single Output
SDM = Spatial Diversity Multiplexing – MIMO function
CDD = Cyclic Delay Diversity - 2Tx Function

Data Rate(s) Tested: 6, 9, 12, 18, 24, 36, 48, 54Mbps (802.11a)
6.5/7.2, 13/14.4, 19.5/21.7, 26/28.9, 39/43.3, 52/57.8, 58.5/65, 65/72.2 (n – 20MHz)
13.5/15, 27/30, 40.5/45, 54/60, 81/90, 108/120, 121.5/135, 135/150 (n – 40MHz BW)
29.3/32.5, 58.5/65, 87.8/97.5, 117/130, 175.5/195, 234/260, 263.3/292.5, 292.5/325, 351/390, 390/433.3 (ac – 80MHz BW)
13/14.4, 26.28.9, 39/43.3, 52/57.8, 78/86.7, 104/115.6, 117/130, 130/144.4Mbps (MIMO n/ac – 20MHz)
156/173Mbps (MIMO ac – 20MHz)
27/30, 54/60, 81/90, 108/120, 162/180, 216/240, 243/270, 270/300Mbps (MIMO n/ac – 40MHz) 324/360, 360/400Mbps (MIMO ac – 40MHz)
58.5/65, 117/130, 175.5/195, 234/260, 351/390, 468/520, 526.5/585, 585/650, 702/780, 780/866.7Mbps (MIMO ac – 80MHz)

| | | | | |
|---|---|---|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 6 of 228 | |

3. This device supports simultaneous transmission operation, which allows for two SISO channels to operate independent of one another in the 2.4GHz and 5GHz bands simultaneously on each antenna. The following tables show the worst case configurations determined during testing. The data for these configurations is contained in this test report.

Configuration 1: ANT1 transmitting in 2.4GHz mode and ANT2 in 5GHz mode

| Description | 2.4 GHz Emission | 5 GHz Emission |
|---------------------------|------------------|----------------|
| Antenna | 1 | 2 |
| Channel | 11 | 149 |
| Operating Frequency (MHz) | 2462 | 5745 |
| Data Rate (Mbps) | 6 | 6 |
| Mode | 802.11g | 802.11a |

Table 2-6. Config-1 (ANT1 2.4GHz & ANT2 5GHz)

Configuration 2: ANT1 transmitting in 5GHz mode and ANT2 in 2.4GHz mode

| Description | 2.4 GHz Emission | 5 GHz Emission |
|---------------------------|------------------|----------------|
| Antenna | 2 | 1 |
| Channel | 11 | 36 |
| Operating Frequency (MHz) | 2462 | 5180 |
| Data Rate (Mbps) | 6 | 6 |
| Mode | 802.11g | 802.11a |

Table 2-7. Config-2 (ANT1 5GHz & ANT2 2.4GHz)

Configuration 3: ANT1 and ANT2 both transmitting in 2.4GHz and 5GHz modes simultaneously

| Description | 2.4 GHz Emission | 5 GHz Emission |
|---------------------------|------------------|----------------|
| Antenna | ALL | ALL |
| Channel | 11 | 165 |
| Operating Frequency (MHz) | 2462 | 5825 |
| Data Rate (Mbps) | 6 | 6 |
| Mode | 802.11g | 802.11a |

Table 2-8. Config-3 (ANT1 MIMO & ANT2 MIMO)

2.3 Test Configuration

The EUT was tested per the guidance of KDB 789033 D02 v01r04. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, and 7.5 for antenna port conducted emissions test setups.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on a certified wireless charging pad (WCP) while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

| | | | | |
|---|---|--|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 7 of 228 | |

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 789033 D02 v01r04 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.9. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

| | | | | |
|---|---|--|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 8 of 228 | |

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. A raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. A 72.4cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm. For measurements above 1GHz, a high density expanded polystyrene block is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

| | | | | |
|---|---|---|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 9 of 228 | |

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

| | | | | |
|---|---|--|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 10 of 228 | |

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Contribution | Expanded Uncertainty (\pm dB) |
|----------------------------------|----------------------------------|
| Conducted Bench Top Measurements | 1.13 |
| Line Conducted Disturbance | 3.09 |
| Radiated Disturbance (<1GHz) | 4.98 |
| Radiated Disturbance (>1GHz) | 5.07 |
| Radiated Disturbance (>18GHz) | 5.09 |

| | | | | |
|---|---|--|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 11 of 228 | |

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2006.

| Manufacturer | Model | Description | Cal Date | Cal Interval | Cal Due | Serial Number |
|-------------------|--------------------|--|------------|--------------|------------|----------------------|
| - | RE1 | Radiated Emissions Cable Set (UHF/EHF) | 7/11/2016 | Annual | 7/11/2017 | RE1 |
| - | WL25-1 | Conducted Cable Set (25GHz) | 10/3/2016 | Annual | 10/3/2017 | WL25-1 |
| Agilent | N9020A | MXA Signal Analyzer | 10/28/2016 | Annual | 10/28/2017 | US46470561 |
| Agilent | N9038A | MXE EMI Receiver | 4/26/2017 | Annual | 4/26/2018 | MY51210133 |
| Anritsu | ML2495A | Power Meter | 10/16/2015 | Biennial | 10/16/2017 | 941001 |
| Anritsu | MA2411B | Pulse Power Sensor | 10/14/2015 | Biennial | 10/14/2017 | 846215 |
| Com-Power | AL-130 | 9kHz - 30MHz Loop Antenna | 7/30/2015 | Biennial | 7/30/2017 | 121034 |
| Com-Power | PAM-103 | Pre-Amplifier (1-1000MHz) | 7/11/2016 | Annual | 7/11/2017 | 441128 |
| Emco | 3115 | Horn Antenna (1-18GHz) | 3/10/2016 | Biennial | 3/10/2018 | 9704-5182 |
| Emco | 3116 | Horn Antenna (18 - 40GHz) | 3/27/2015 | Triennial | 3/27/2018 | 9203-2178 |
| EMCO | 3160-10 | Small Horn (26.5 - 40GHz) | 8/23/2016 | Biennial | 8/23/2018 | 130993 |
| Espec | ESX-2CA | Environmental Chamber | 4/11/2017 | Annual | 4/11/2018 | 17620 |
| ETS-Lindgren | 3816/2NM | Line Impedance Stabilization Network | 12/27/2016 | Biennial | 12/27/2018 | 114451 |
| Huber+Suhner | Sucoflex 102A | 40GHz Radiated Cable | 10/3/2016 | Annual | 10/3/2017 | 251425001 |
| K & L | 11SH10-6000/T18000 | High Pass Filter | 7/11/2016 | Annual | 7/11/2017 | 11SH10-6000/T18000-1 |
| Pasternack | NMLC-1 | Line Conducted Emissions Cable (NM) | 10/5/2016 | Annual | 10/5/2017 | NMLC-1 |
| PCTEST | - | EMC Switch System | 7/11/2016 | Annual | 7/11/2017 | NM1 |
| PCTEST | - | EMC Switch System | 7/6/2016 | Annual | 7/6/2017 | NM2 |
| Rhode & Schwarz | TS-PR18 | Pre-Amplifier | 7/6/2016 | Annual | 7/6/2017 | 101622 |
| Rohde & Schwarz | TS-PR18 | 1-18 GHz Pre-Amplifier | 7/11/2016 | Annual | 7/11/2017 | 100071 |
| Rohde & Schwarz | TS-PR26 | 18-26.5 GHz Pre-Amplifier | 5/11/2017 | Annual | 5/11/2018 | 100040 |
| Rohde & Schwarz | ESU26 | EMI Test Receiver (26.5GHz) | 4/19/2017 | Annual | 4/19/2018 | 100342 |
| Rohde & Schwarz | TS-PR40 | 26.5-40 GHz Pre-Amplifier | 5/11/2017 | Annual | 5/11/2018 | 100037 |
| Rohde & Schwarz | ESU40 | EMI Test Receiver (40GHz) | 7/15/2016 | Annual | 7/15/2017 | 100348 |
| Rohde & Schwarz | FSW67 | Signal / Spectrum Analyzer | 7/27/2016 | Annual | 7/27/2017 | 103200 |
| Seekonk | NC-100 | Torque Wrench 5/16", 8" lbs | 3/2/2016 | Biennial | 3/2/2018 | N/A |
| Solar Electronics | 8012-50-R-24-BNC | Line Impedance Stabilization Network | 7/30/2015 | Biennial | 7/30/2017 | 310233 |
| Sunol | DRH-118 | Horn Antenna (1-18GHz) | 7/30/2015 | Biennial | 7/30/2017 | A050307 |
| Sunol | JB5 | Bi-Log Antenna (30M - 5GHz) | 3/14/2016 | Biennial | 3/14/2018 | A051107 |

Table 6-1. Annual Test Equipment Calibration Schedule

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

| | | | | |
|---|---|--|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 12 of 228 | |

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMN950F
 Method/System: Unlicensed National Information Infrastructure (UNII)

| FCC Part Section(s) | Test Description | Test Limit | Test Condition | Test Result | Reference |
|------------------------------------|---|--|----------------|-------------|---------------------|
| N/A | 26dB Bandwidth | N/A | CONDUCTED | PASS | Section 7.2 |
| 15.407(e) | 6dB Bandwidth | >500kHz(5725-5850MHz) | | PASS | Section 7.3 |
| 15.407 (a.1.iv), (a.2), (a.3) | Maximum Conducted Output Power | Maximum conducted powers must meet the limits detailed in 15.407 (a) | | PASS | Section 7.4 |
| 15.407 (a.1.iv), (a.2), (a.3) | Maximum Power Spectral Density | Maximum power spectral density must meet the limits detailed in 15.407 (a) | | PASS | Section 7.5 |
| 15.407(g) | Frequency Stability | N/A | | PASS | Section 7.6 |
| 15.407(h) | Dynamic Frequency Selection | See DFS Test Report | | PASS | See DFS Test Report |
| 15.407(b.1), (2), (3), (4) | Undesirable Emissions | Undesirable emissions must meet the limits detailed in 15.407(b) | RADIATED | PASS | Section 7.7 |
| 15.205, 15.407(b.1), (4), (5), (6) | General Field Strength Limits (Restricted Bands and Radiated Emission Limits) | Emissions in restricted bands must meet the radiated limits detailed in 15.209 | | PASS | Section 7.7, 7.8 |
| 15.407 | AC Conducted Emissions 150kHz – 30MHz | < FCC 15.207 limits | LINE CONDUCTED | PASS | Section 7.9 |

Table 7-1. Summary of Test Results

Notes:

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST “UNII Automation,” Version 4.4.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST “Chamber Automation,” Version 1.1.5.

| | | | | |
|---|---|---|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 13 of 228 | |

7.2 26dB Bandwidth Measurement – 802.11a/n/ac

Test Overview and Limit

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in KDB 789033 D02 v01r04, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

The 26dB bandwidth is used to determine the conducted power limits.

Test Procedure Used

KDB 789033 D02 v01r04 – Section C

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 26$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Test Instrument & Measurement Setup

Test Notes

None.


| | | | | |
|---|---|--|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 14 of 228 | |

Antenna-1 26 dB Bandwidth Measurements


| | Frequency [MHz] | Channel No. | 802.11 Mode | Data Rate [Mbps] | Measured 26dB Bandwidth [MHz] |
|---------|-----------------|-------------|-------------|------------------|-------------------------------|
| Band 1 | 5180 | 36 | a | 6 | 21.43 |
| | 5200 | 40 | a | 6 | 21.43 |
| | 5240 | 48 | a | 6 | 22.00 |
| | 5180 | 36 | n (20MHz) | 6.5/7.2 (MCS0) | 21.56 |
| | 5200 | 40 | n (20MHz) | 6.5/7.2 (MCS0) | 22.01 |
| | 5240 | 48 | n (20MHz) | 6.5/7.2 (MCS0) | 22.02 |
| | 5190 | 38 | n (40MHz) | 13.5/15 (MCS0) | 39.97 |
| | 5230 | 46 | n (40MHz) | 13.5/15 (MCS0) | 39.78 |
| | 5210 | 42 | ac (80MHz) | 29.3/32.5 (MCS0) | 81.32 |
| Band 2A | 5260 | 52 | a | 6 | 24.73 |
| | 5280 | 56 | a | 6 | 24.87 |
| | 5320 | 64 | a | 6 | 23.48 |
| | 5260 | 52 | n (20MHz) | 6.5/7.2 (MCS0) | 23.27 |
| | 5280 | 56 | n (20MHz) | 6.5/7.2 (MCS0) | 22.35 |
| | 5320 | 64 | n (20MHz) | 6.5/7.2 (MCS0) | 22.07 |
| | 5270 | 54 | n (40MHz) | 13.5/15 (MCS0) | 39.89 |
| | 5310 | 62 | n (40MHz) | 13.5/15 (MCS0) | 39.95 |
| | 5290 | 58 | ac (80MHz) | 29.3/32.5 (MCS0) | 81.38 |
| Band 2C | 5500 | 100 | a | 6 | 22.00 |
| | 5600 | 120 | a | 6 | 21.64 |
| | 5720 | 144 | a | 6 | 21.29 |
| | 5500 | 100 | n (20MHz) | 6.5/7.2 (MCS0) | 21.71 |
| | 5600 | 120 | n (20MHz) | 6.5/7.2 (MCS0) | 21.67 |
| | 5720 | 144 | n (20MHz) | 6.5/7.2 (MCS0) | 21.59 |
| | 5510 | 102 | n (40MHz) | 13.5/15 (MCS0) | 39.46 |
| | 5590 | 118 | n (40MHz) | 13.5/15 (MCS0) | 39.93 |
| | 5710 | 142 | n (40MHz) | 13.5/15 (MCS0) | 39.97 |
| | 5530 | 106 | ac (80MHz) | 29.3/32.5 (MCS0) | 80.78 |
| | 5610 | 122 | ac (80MHz) | 29.3/32.5 (MCS0) | 81.79 |
| | 5690 | 138 | ac (80MHz) | 29.3/32.5 (MCS0) | 81.38 |

Table 7-2. Conducted Bandwidth Measurements

| | | | | |
|---|---|--|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 15 of 228 |




Plot 7-1. 26dB Bandwidth Plot (802.11a (UNII Band 1) – Ch. 36)




Plot 7-2. 26dB Bandwidth Plot (802.11a (UNII Band 1) – Ch. 40)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 16 of 228 |




Plot 7-3. 26dB Bandwidth Plot (802.11a (UNII Band 1) – Ch. 48)




Plot 7-4. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 17 of 228 |




Plot 7-5. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 40)




Plot 7-6. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 48)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 18 of 228 |




Plot 7-7. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)




Plot 7-8. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 19 of 228 |




Plot 7-9. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)




Plot 7-10. 26dB Bandwidth Plot (802.11a (UNII Band 2A) – Ch. 52)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 20 of 228 |




Plot 7-11. 26dB Bandwidth Plot (802.11a (UNII Band 2A) – Ch. 56)




Plot 7-12. 26dB Bandwidth Plot (802.11a (UNII Band 2A) – Ch. 64)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 21 of 228 |




Plot 7-13. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 52)




Plot 7-14. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 56)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 22 of 228 |




Plot 7-15. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 64)




Plot 7-16. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 54)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 23 of 228 |




Plot 7-17. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 62)




Plot 7-18. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2A) – Ch. 58)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 24 of 228 |




Plot 7-19. 26dB Bandwidth Plot (802.11a (UNII Band 2C) – Ch. 100)




Plot 7-20. 26dB Bandwidth Plot (802.11a (UNII Band 2C) – Ch. 120)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 25 of 228 |




Plot 7-21. 26dB Bandwidth Plot (802.11a (UNII Band 2C) – Ch. 144)




Plot 7-22. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 100)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 26 of 228 |




Plot 7-23. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 120)




Plot 7-24. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 144)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 27 of 228 |




Plot 7-25. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 102)




Plot 7-26. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 118)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 28 of 228 |




Plot 7-27. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 142)




Plot 7-28. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 106)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 29 of 228 |



Plot 7-29. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 122)



Plot 7-30. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 138)


| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 30 of 228 |

Antenna-2 26dB Bandwidth Measurements


| | Frequency [MHz] | Channel No. | 802.11 Mode | Data Rate [Mbps] | Measured 26dB Bandwidth [MHz] |
|---------|-----------------|-------------|-------------|------------------|-------------------------------|
| Band 1 | 5180 | 36 | a | 6 | 21.27 |
| | 5200 | 40 | a | 6 | 21.37 |
| | 5240 | 48 | a | 6 | 21.46 |
| | 5180 | 36 | n (20MHz) | 6.5/7.2 (MCS0) | 21.69 |
| | 5200 | 40 | n (20MHz) | 6.5/7.2 (MCS0) | 22.98 |
| | 5240 | 48 | n (20MHz) | 6.5/7.2 (MCS0) | 23.16 |
| | 5190 | 38 | n (40MHz) | 13.5/15 (MCS0) | 39.77 |
| | 5230 | 46 | n (40MHz) | 13.5/15 (MCS0) | 39.83 |
| | 5210 | 42 | ac (80MHz) | 29.3/32.5 (MCS0) | 81.35 |
| Band 2A | 5260 | 52 | a | 6 | 21.43 |
| | 5280 | 56 | a | 6 | 21.64 |
| | 5320 | 64 | a | 6 | 21.49 |
| | 5260 | 52 | n (20MHz) | 6.5/7.2 (MCS0) | 21.60 |
| | 5280 | 56 | n (20MHz) | 6.5/7.2 (MCS0) | 21.80 |
| | 5320 | 64 | n (20MHz) | 6.5/7.2 (MCS0) | 21.68 |
| | 5270 | 54 | n (40MHz) | 13.5/15 (MCS0) | 39.71 |
| | 5310 | 62 | n (40MHz) | 13.5/15 (MCS0) | 39.78 |
| | 5290 | 58 | ac (80MHz) | 29.3/32.5 (MCS0) | 81.39 |
| Band 2C | 5500 | 100 | a | 6 | 21.41 |
| | 5600 | 120 | a | 6 | 21.20 |
| | 5720 | 144 | a | 6 | 21.24 |
| | 5500 | 100 | n (20MHz) | 6.5/7.2 (MCS0) | 21.62 |
| | 5600 | 120 | n (20MHz) | 6.5/7.2 (MCS0) | 21.65 |
| | 5720 | 144 | n (20MHz) | 6.5/7.2 (MCS0) | 21.82 |
| | 5510 | 102 | n (40MHz) | 13.5/15 (MCS0) | 39.68 |
| | 5590 | 118 | n (40MHz) | 13.5/15 (MCS0) | 39.62 |
| | 5710 | 142 | n (40MHz) | 13.5/15 (MCS0) | 39.94 |
| | 5530 | 106 | ac (80MHz) | 29.3/32.5 (MCS0) | 81.29 |
| | 5610 | 122 | ac (80MHz) | 29.3/32.5 (MCS0) | 81.32 |
| | 5690 | 138 | ac (80MHz) | 29.3/32.5 (MCS0) | 81.58 |

Table 7-3. Conducted Bandwidth Measurements

| | | | | |
|---|---|--|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 31 of 228 |




Plot 7-31. 26dB Bandwidth Plot (802.11a (UNII Band 1) – Ch. 36)




Plot 7-32. 26dB Bandwidth Plot (802.11a (UNII Band 1) – Ch. 40)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 32 of 228 |




Plot 7-33. 26dB Bandwidth Plot (802.11a (UNII Band 1) – Ch. 48)




Plot 7-34. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 33 of 228 |




Plot 7-35. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 40)




Plot 7-36. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 48)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 34 of 228 |




Plot 7-37. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)




Plot 7-38. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

| | | | | |
|---|--------------------------------|--|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 35 of 228 |




Plot 7-39. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)




Plot 7-40. 26dB Bandwidth Plot (802.11a (UNII Band 2A) – Ch. 52)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 36 of 228 |




Plot 7-41. 26dB Bandwidth Plot (802.11a (UNII Band 2A) – Ch. 56)




Plot 7-42. 26dB Bandwidth Plot (802.11a (UNII Band 2A) – Ch. 64)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 37 of 228 |




Plot 7-43. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 52)




Plot 7-44. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 56)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 38 of 228 |




Plot 7-45. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 64)




Plot 7-46. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 54)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 39 of 228 |




Plot 7-47. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 62)




Plot 7-48. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2A) – Ch. 58)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 40 of 228 |




Plot 7-49. 26dB Bandwidth Plot (802.11a (UNII Band 2C) – Ch. 100)




Plot 7-50. 26dB Bandwidth Plot (802.11a (UNII Band 2C) – Ch. 120)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 41 of 228 |




Plot 7-51. 26dB Bandwidth Plot (802.11a (UNII Band 2C) – Ch. 144)




Plot 7-52. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 100)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 42 of 228 |




Plot 7-53. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 120)




Plot 7-54. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 144)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 43 of 228 |




Plot 7-55. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 102)




Plot 7-56. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 118)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 44 of 228 |




Plot 7-57. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 142)




Plot 7-58. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 106)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 45 of 228 |



Plot 7-59. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 122)



Plot 7-60. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 138)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 46 of 228 |

7.3 6dB Bandwidth Measurement – 802.11a/n/ac §15.407 (e)

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in KDB 789033 D02 v01r04, and at the appropriate frequencies. The spectrum analyzer’s bandwidth measurement function is configured to measure the 6dB bandwidth.

In the 5.725 – 5.850GHz band, the 6dB bandwidth must be ≥ 500 kHz.

Test Procedure Used

KDB 789033 D02 v01r04 – Section C

Test Settings

1. The signal analyzers’ automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The “X” dB bandwidth parameter was set to X = 6. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100 kHz
3. VBW ≥ 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-2. Test Instrument & Measurement Setup

Test Notes


None.

| | | | | |
|---|---|--|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 47 of 228 | |

Antenna-1 6 dB Bandwidth Measurements


| | Frequency [MHz] | Channel No. | 802.11 Mode | Data Rate [Mbps] | Measured 6dB Bandwidth [MHz] |
|---------------|-----------------|-------------|-------------|------------------|------------------------------|
| Band 3 | 5745 | 149 | a | 6 | 16.36 |
| | 5785 | 157 | a | 6 | 16.33 |
| | 5825 | 165 | a | 6 | 16.36 |
| | 5745 | 149 | n (20MHz) | 6.5/7.2 (MCS0) | 17.60 |
| | 5785 | 157 | n (20MHz) | 6.5/7.2 (MCS0) | 17.61 |
| | 5825 | 165 | n (20MHz) | 6.5/7.2 (MCS0) | 17.59 |
| | 5755 | 151 | n (40MHz) | 13.5/15 (MCS0) | 36.33 |
| | 5795 | 159 | n (40MHz) | 13.5/15 (MCS0) | 36.34 |
| | 5775 | 155 | ac (80MHz) | 29.3/32.5 (MCS0) | 75.69 |

Table 7-4. Conducted Bandwidth Measurements




Plot 7-61. 6dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 149)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 48 of 228 |




Plot 7-62. 6dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 157)




Plot 7-63. 6dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 165)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 49 of 228 |




Plot 7-64. 6dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 149)




Plot 7-65. 6dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 157)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 50 of 228 |




Plot 7-66. 6dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 165)




Plot 7-67. 6dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 151)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 51 of 228 |



Plot 7-68. 6dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 159)



Plot 7-69. 6dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 3) – Ch. 155)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 52 of 228 |

Antenna-2 6dB Bandwidth Measurements


| | Frequency [MHz] | Channel No. | 802.11 Mode | Data Rate [Mbps] | Measured 6dB Bandwidth [MHz] |
|---------------|-----------------|-------------|-------------|------------------|------------------------------|
| Band 3 | 5745 | 149 | a | 6 | 16.36 |
| | 5785 | 157 | a | 6 | 16.37 |
| | 5825 | 165 | a | 6 | 16.36 |
| | 5745 | 149 | n (20MHz) | 6.5/7.2 (MCS0) | 17.62 |
| | 5785 | 157 | n (20MHz) | 6.5/7.2 (MCS0) | 17.61 |
| | 5825 | 165 | n (20MHz) | 6.5/7.2 (MCS0) | 17.59 |
| | 5755 | 151 | n (40MHz) | 13.5/15 (MCS0) | 36.31 |
| | 5795 | 159 | n (40MHz) | 13.5/15 (MCS0) | 36.33 |
| | 5775 | 155 | ac (80MHz) | 29.3/32.5 (MCS0) | 75.45 |

Table 7-5. Conducted Bandwidth Measurements




Plot 7-70. 6dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 149)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 53 of 228 |




Plot 7-71. 6dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 157)




Plot 7-72. 6dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 165)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 54 of 228 |




Plot 7-73. 6dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 149)




Plot 7-74. 6dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 157)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 55 of 228 |




Plot 7-75. 6dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 165)




Plot 7-76. 6dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 151)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 56 of 228 |



Plot 7-77. 6dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 159)



Plot 7-78. 6dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 3) – Ch. 155)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 57 of 228 |

7.4 UNII Output Power Measurement – 802.11a/n/ac

§15.407(a.1.iv) §15.407(a.2) §15.407(a.3)

Test Overview and Limits

A transmitter antenna terminal of the EUT is connected to the input of an RF pulse power sensor. Measurement is made using a broadband average power meter while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in KDB 789033 D02 v01r04, and at the appropriate frequencies.

In the 5.15 – 5.25GHz band, the maximum permissible conducted output power is 250mW (23.98dBm).

In the 5.25 – 5.35GHz band, the maximum permissible conducted output power is the lesser of 250mW (23.98dBm) and $11 \text{ dBm} + 10\log_{10}(26\text{dB BW}) = 11 \text{ dBm} + 10\log_{10}(22.07) = 24.44\text{dBm}$.

In the 5.47 – 5.725GHz band, the maximum permissible conducted output power is the lesser of 250mW (23.98dBm) and $11 \text{ dBm} + 10\log_{10}(26\text{dB BW}) = 11 \text{ dBm} + 10\log_{10}(21.29) = 24.28\text{dBm}$.

In the 5.725 – 5.850GHz band, the maximum permissible conducted output power is 1W (30dBm).

Test Procedure Used

KDB 789033 D02 v01r04 – Section E)3)b) Method PM-G
KDB 662911 v02r01 – Section E)1) Measure-and-Sum Technique

Test Settings

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup

Test Notes

None

| | | | | |
|---|---|--|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 58 of 228 |

Antenna-1 Conducted Output Power Measurements

| Freq [MHz] | Channel | Detector | 5GHz (20MHz) Conducted Power [dBm] | | |
|------------|---------|----------|------------------------------------|---------|----------|
| | | | IEEE Transmission Mode | | |
| | | | 802.11a | 802.11n | 802.11ac |
| 5180 | 36 | AVG | 17.39 | 17.15 | 17.15 |
| 5200 | 40 | AVG | 17.40 | 17.14 | 17.12 |
| 5220 | 44 | AVG | 17.13 | 17.21 | 17.20 |
| 5240 | 48 | AVG | 17.05 | 17.23 | 17.19 |
| 5260 | 52 | AVG | 16.86 | 17.00 | 17.00 |
| 5280 | 56 | AVG | 16.86 | 16.96 | 17.00 |
| 5300 | 60 | AVG | 16.90 | 17.07 | 17.00 |
| 5320 | 64 | AVG | 16.81 | 17.00 | 17.00 |
| 5500 | 100 | AVG | 16.69 | 16.87 | 16.80 |
| 5600 | 120 | AVG | 16.76 | 16.75 | 16.80 |
| 5620 | 124 | AVG | 16.80 | 16.71 | 16.81 |
| 5720 | 144 | AVG | 16.88 | 16.61 | 16.60 |
| 5745 | 149 | AVG | 16.95 | 16.66 | 17.00 |
| 5785 | 157 | AVG | 16.89 | 16.50 | 16.61 |
| 5825 | 165 | AVG | 16.76 | 16.56 | 16.61 |

Table 7-6. 20MHz BW (UNII) Maximum Conducted Output Power

| Freq [MHz] | Channel | Detector | 5GHz (40MHz) Conducted Power [dBm] | |
|------------|---------|----------|------------------------------------|----------|
| | | | IEEE Transmission Mode | |
| | | | 802.11n | 802.11ac |
| 5190 | 38 | AVG | 15.40 | 15.41 |
| 5230 | 46 | AVG | 14.70 | 14.65 |
| 5270 | 54 | AVG | 14.87 | 15.00 |
| 5310 | 62 | AVG | 14.88 | 15.00 |
| 5510 | 102 | AVG | 15.45 | 15.40 |
| 5590 | 118 | AVG | 15.40 | 15.37 |
| 5710 | 142 | AVG | 15.33 | 15.25 |
| 5755 | 151 | AVG | 15.00 | 15.00 |
| 5795 | 159 | AVG | 15.00 | 15.12 |

Table 7-7. 40MHz BW (UNII) Maximum Conducted Output Power

| 5GHz (80MHz) Conducted Power [dBm] | | | |
|------------------------------------|---------|----------|------------------------|
| Freq [MHz] | Channel | Detector | IEEE Transmission Mode |
| | | | 802.11ac |
| 5210 | 42 | AVG | 13.39 |
| 5290 | 58 | AVG | 12.77 |
| 5530 | 106 | AVG | 13.25 |
| 5610 | 122 | AVG | 13.39 |
| 5690 | 138 | AVG | 13.30 |
| 5775 | 155 | AVG | 13.40 |

Table 7-8. 80MHz BW (UNII) Maximum Conducted Output Power

| | | | | |
|---|---|---|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 59 of 228 | |

Antenna-2 Conducted Output Power Measurements

| Freq [MHz] | Channel | Detector | 5GHz (20MHz) Conducted Power [dBm] | | |
|------------|---------|----------|------------------------------------|---------|----------|
| | | | IEEE Transmission Mode | | |
| | | | 802.11a | 802.11n | 802.11ac |
| 5180 | 36 | AVG | 16.58 | 16.55 | 16.55 |
| 5200 | 40 | AVG | 16.66 | 16.64 | 16.60 |
| 5220 | 44 | AVG | 16.56 | 16.63 | 16.77 |
| 5240 | 48 | AVG | 16.66 | 16.66 | 16.70 |
| 5260 | 52 | AVG | 16.42 | 16.65 | 16.74 |
| 5280 | 56 | AVG | 16.39 | 16.70 | 16.75 |
| 5300 | 60 | AVG | 16.45 | 16.78 | 16.75 |
| 5320 | 64 | AVG | 16.46 | 16.80 | 16.82 |
| 5500 | 100 | AVG | 17.17 | 16.52 | 16.56 |
| 5600 | 120 | AVG | 17.13 | 16.51 | 16.51 |
| 5620 | 124 | AVG | 16.98 | 16.52 | 16.52 |
| 5720 | 144 | AVG | 16.89 | 17.30 | 17.32 |
| 5745 | 149 | AVG | 17.23 | 16.80 | 16.78 |
| 5785 | 157 | AVG | 17.21 | 16.70 | 16.80 |
| 5825 | 165 | AVG | 17.20 | 16.65 | 16.66 |

Table 7-9. 20MHz BW (UNII) Maximum Conducted Output Power

| Freq [MHz] | Channel | Detector | 5GHz (40MHz) Conducted Power [dBm] | |
|------------|---------|----------|------------------------------------|----------|
| | | | IEEE Transmission Mode | |
| | | | 802.11n | 802.11ac |
| 5190 | 38 | AVG | 15.00 | 15.15 |
| 5230 | 46 | AVG | 15.22 | 15.16 |
| 5270 | 54 | AVG | 15.33 | 15.27 |
| 5310 | 62 | AVG | 15.33 | 15.25 |
| 5510 | 102 | AVG | 15.11 | 15.15 |
| 5590 | 118 | AVG | 15.08 | 15.10 |
| 5710 | 142 | AVG | 15.00 | 15.05 |
| 5755 | 151 | AVG | 15.22 | 15.20 |
| 5795 | 159 | AVG | 15.15 | 15.23 |

Table 7-10. 40MHz BW (UNII) Maximum Conducted Output Power

| 5GHz (80MHz) Conducted Power [dBm] | | | |
|------------------------------------|---------|----------|------------------------|
| Freq [MHz] | Channel | Detector | IEEE Transmission Mode |
| | | | 802.11ac |
| 5210 | 42 | AVG | 13.49 |
| 5290 | 58 | AVG | 12.79 |
| 5530 | 106 | AVG | 13.32 |
| 5610 | 122 | AVG | 13.27 |
| 5690 | 138 | AVG | 13.33 |
| 5775 | 155 | AVG | 13.49 |

Table 7-11. 80MHz BW (UNII) Maximum Conducted Output Power

| | | | | |
|---|---|---|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 60 of 228 | |

MIMO Maximum Conducted Output Power Measurements

| Freq [MHz] | Channel | Detector | 5GHz (20MHz) Conducted Power [dBm] | | |
|------------|---------|----------|------------------------------------|-------|-------|
| | | | IEEE Transmission Mode | | |
| | | | ANT1 | ANT2 | MIMO |
| 5180 | 36 | AVG | 17.39 | 16.58 | 20.01 |
| 5200 | 40 | AVG | 17.40 | 16.66 | 20.06 |
| 5220 | 44 | AVG | 17.13 | 16.56 | 19.86 |
| 5240 | 48 | AVG | 17.05 | 16.66 | 19.87 |
| 5260 | 52 | AVG | 16.86 | 16.42 | 19.66 |
| 5280 | 56 | AVG | 16.86 | 16.39 | 19.64 |
| 5300 | 60 | AVG | 16.90 | 16.45 | 19.69 |
| 5320 | 64 | AVG | 16.81 | 16.46 | 19.65 |
| 5500 | 100 | AVG | 16.69 | 17.17 | 19.95 |
| 5600 | 120 | AVG | 16.76 | 17.13 | 19.96 |
| 5620 | 124 | AVG | 16.80 | 16.98 | 19.90 |
| 5720 | 144 | AVG | 16.88 | 16.89 | 19.90 |
| 5745 | 149 | AVG | 16.95 | 17.23 | 20.10 |
| 5785 | 157 | AVG | 16.89 | 17.21 | 20.06 |
| 5825 | 165 | AVG | 16.76 | 17.20 | 20.00 |

Table 7-12. CDD 20MHz BW 802.11a (UNII) Maximum Conducted Output Power

| Freq [MHz] | Channel | Detector | 5GHz (20MHz) Conducted Power [dBm] | | |
|------------|---------|----------|------------------------------------|-------|-------|
| | | | IEEE Transmission Mode | | |
| | | | ANT1 | ANT2 | MIMO |
| 5180 | 36 | AVG | 17.15 | 16.55 | 19.87 |
| 5200 | 40 | AVG | 17.14 | 16.64 | 19.91 |
| 5220 | 44 | AVG | 17.21 | 16.63 | 19.94 |
| 5240 | 48 | AVG | 17.23 | 16.66 | 19.96 |
| 5260 | 52 | AVG | 17.00 | 16.65 | 19.84 |
| 5280 | 56 | AVG | 16.96 | 16.70 | 19.84 |
| 5300 | 60 | AVG | 17.07 | 16.78 | 19.94 |
| 5320 | 64 | AVG | 17.00 | 16.80 | 19.91 |
| 5500 | 100 | AVG | 16.87 | 16.52 | 19.71 |
| 5600 | 120 | AVG | 16.75 | 16.51 | 19.64 |
| 5620 | 124 | AVG | 16.71 | 16.52 | 19.63 |
| 5720 | 144 | AVG | 16.61 | 17.30 | 19.98 |
| 5745 | 149 | AVG | 16.66 | 16.80 | 19.74 |
| 5785 | 157 | AVG | 16.50 | 16.70 | 19.61 |
| 5825 | 165 | AVG | 16.56 | 16.65 | 19.62 |

Table 7-13. MIMO 20MHz BW 802.11n (UNII) Maximum Conducted Output Power

| | | | | |
|---|---|--|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 61 of 228 | |

| Freq [MHz] | Channel | Detector | 5GHz (20MHz) Conducted Power [dBm] | | |
|------------|---------|----------|------------------------------------|-------|-------|
| | | | IEEE Transmission Mode | | |
| | | | ANT1 | ANT2 | MIMO |
| 5180 | 36 | AVG | 17.15 | 16.55 | 19.87 |
| 5200 | 40 | AVG | 17.12 | 16.60 | 19.88 |
| 5220 | 44 | AVG | 17.20 | 16.77 | 20.00 |
| 5240 | 48 | AVG | 17.19 | 16.70 | 19.96 |
| 5260 | 52 | AVG | 17.00 | 16.74 | 19.88 |
| 5280 | 56 | AVG | 17.00 | 16.75 | 19.89 |
| 5300 | 60 | AVG | 17.00 | 16.75 | 19.89 |
| 5320 | 64 | AVG | 17.00 | 16.82 | 19.92 |
| 5500 | 100 | AVG | 16.80 | 16.56 | 19.69 |
| 5600 | 120 | AVG | 16.80 | 16.51 | 19.67 |
| 5620 | 124 | AVG | 16.81 | 16.52 | 19.68 |
| 5720 | 144 | AVG | 16.60 | 17.32 | 19.99 |
| 5745 | 149 | AVG | 17.00 | 16.78 | 19.90 |
| 5785 | 157 | AVG | 16.61 | 16.80 | 19.72 |
| 5825 | 165 | AVG | 16.61 | 16.66 | 19.65 |

Table 7-14. MIMO 20MHz BW 802.11ac (UNII) Maximum Conducted Output Power

| Freq [MHz] | Channel | Detector | 5GHz (40MHz) Conducted Power [dBm] | | |
|------------|---------|----------|------------------------------------|-------|-------|
| | | | IEEE Transmission Mode | | |
| | | | ANT1 | ANT2 | MIMO |
| 5190 | 38 | AVG | 15.40 | 15.00 | 18.21 |
| 5230 | 46 | AVG | 14.70 | 15.22 | 17.98 |
| 5270 | 54 | AVG | 14.87 | 15.33 | 18.12 |
| 5310 | 62 | AVG | 14.88 | 15.33 | 18.12 |
| 5510 | 102 | AVG | 15.45 | 15.11 | 18.29 |
| 5590 | 118 | AVG | 15.40 | 15.08 | 18.25 |
| 5710 | 142 | AVG | 15.33 | 15.00 | 18.18 |
| 5755 | 151 | AVG | 15.00 | 15.22 | 18.12 |
| 5795 | 159 | AVG | 15.00 | 15.15 | 18.09 |

Table 7-15. MIMO 40MHz BW 802.11n (UNII) Maximum Conducted Output Power

| | | | | |
|---|---|--|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 62 of 228 | |

| Freq [MHz] | Channel | Detector | 5GHz (40MHz) Conducted Power [dBm] | | |
|------------|---------|----------|------------------------------------|-------|-------|
| | | | IEEE Transmission Mode | | |
| | | | ANT1 | ANT2 | MIMO |
| 5190 | 38 | AVG | 15.41 | 15.15 | 18.29 |
| 5230 | 46 | AVG | 14.65 | 15.16 | 17.92 |
| 5270 | 54 | AVG | 15.00 | 15.27 | 18.15 |
| 5310 | 62 | AVG | 15.00 | 15.25 | 18.14 |
| 5510 | 102 | AVG | 15.40 | 15.15 | 18.29 |
| 5590 | 118 | AVG | 15.37 | 15.10 | 18.25 |
| 5710 | 142 | AVG | 15.25 | 15.05 | 18.16 |
| 5755 | 151 | AVG | 15.00 | 15.20 | 18.11 |
| 5795 | 159 | AVG | 15.12 | 15.23 | 18.19 |

Table 7-16. MIMO 40MHz BW 802.11ac (UNII) Maximum Conducted Output Power

| Freq [MHz] | Channel | Detector | 5GHz (80MHz) Conducted Power [dBm] | | |
|------------|---------|----------|------------------------------------|-------|-------|
| | | | IEEE Transmission Mode | | |
| | | | ANT1 | ANT2 | MIMO |
| 5210 | 42 | AVG | 13.39 | 13.49 | 16.45 |
| 5290 | 58 | AVG | 12.77 | 12.79 | 15.79 |
| 5530 | 106 | AVG | 13.25 | 13.32 | 16.30 |
| 5610 | 122 | AVG | 13.39 | 13.27 | 16.34 |
| 5690 | 138 | AVG | 13.30 | 13.33 | 16.33 |
| 5775 | 155 | AVG | 13.40 | 13.49 | 16.46 |

Table 7-17. MIMO 80MHz BW 802.11ac (UNII) Maximum Conducted Output Power

Note:

Per KDB 662911 v02r01 Section E)1), the conducted powers at Antenna 1 and Antenna 2 were first measured separately during MIMO transmission as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Sample MIMO Calculation:

At 5180MHz the average conducted output power was measured to be 17.15 dBm for Antenna-1 and 16.55 dBm for Antenna-2.

$$\text{Antenna 1} + \text{Antenna 2} = \text{MIMO}$$

$$(17.15 \text{ dBm} + 16.55 \text{ dBm}) = (51.88 \text{ mW} + 45.19 \text{ mW}) = 97.07 \text{ mW} = 19.87 \text{ dBm}$$

| | | | | |
|---|---|---|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 63 of 228 | |

7.5 Maximum Power Spectral Density – 802.11a/n/ac §15.407(a.1.iv) §15.407(a.2) §15.407(a.3)

Test Overview and Limit

The spectrum analyzer was connected to the antenna terminal while the EUT was operating at its maximum duty cycle, at its maximum power control level, as defined in KDB 789033 D02 v01r04, and at the appropriate frequencies. Method SA-1, as defined in KDB 789033 D02 v01r04, was used to measure the power spectral density.

In the 5.15 – 5.25GHz, 5.25 – 5.35GHz, 5.47 – 5.725GHz bands, the maximum permissible power spectral density is 11dBm/MHz.

In the 5.725 – 5.850GHz band, the maximum permissible power spectral density is 30dBm/500kHz.

Test Procedure Used

KDB 789033 D02 v01r04 – Section F
KDB 662911 v02r01 – Section E)2) Measure-and-Sum Technique

Test Settings

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire emission bandwidth of the signal
3. RBW = 1MHz
4. VBW = 3MHz
5. Number of sweep points $\geq 2 \times$ (span/RBW)
6. Sweep time = auto
7. Detector = power averaging (RMS)
8. Trigger was set to free run for all modes
9. Trace was averaged over 100 sweeps
10. The peak search function of the spectrum analyzer was used to find the peak of the spectrum.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Test Instrument & Measurement Setup

Test Notes

None

| | | | | |
|---|---|--|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 64 of 228 | |

Antenna-1 Power Spectral Density Measurements


| | Frequency [MHz] | Channel No. | 802.11 Mode | Data Rate [Mbps] | Measured Power Density [dBm] | Max Permissible Power Density [dBm/MHz] | Margin [dB] | Pass / Fail |
|---------|-----------------|-------------|------------------|------------------|------------------------------|---|-------------|-------------|
| Band 1 | 5180 | 36 | a | 6 | 4.95 | 11.0 | -6.05 | Pass |
| | 5200 | 40 | a | 6 | 5.07 | 11.0 | -5.93 | Pass |
| | 5240 | 48 | a | 6 | 6.02 | 11.0 | -4.98 | Pass |
| | 5180 | 36 | n (20MHz) | 6.5/7.2 (MCS0) | 4.42 | 11.0 | -6.58 | Pass |
| | 5200 | 40 | n (20MHz) | 6.5/7.2 (MCS0) | 4.77 | 11.0 | -6.23 | Pass |
| | 5240 | 48 | n (20MHz) | 6.5/7.2 (MCS0) | 4.63 | 11.0 | -6.37 | Pass |
| | 5190 | 38 | n (40MHz) | 13.5/15 (MCS0) | -0.29 | 11.0 | -11.29 | Pass |
| | 5230 | 46 | n (40MHz) | 13.5/15 (MCS0) | -1.09 | 11.0 | -12.09 | Pass |
| | 5210 | 42 | ac (80MHz) | 29.3/32.5 (MCS0) | -5.17 | 11.0 | -16.17 | Pass |
| Band 2A | 5260 | 52 | a | 6 | 6.44 | 11.0 | -4.56 | Pass |
| | 5280 | 56 | a | 6 | 6.16 | 11.0 | -4.84 | Pass |
| | 5320 | 64 | a | 6 | 6.07 | 11.0 | -4.93 | Pass |
| | 5260 | 52 | n (20MHz) | 6.5/7.2 (MCS0) | 4.74 | 11.0 | -6.26 | Pass |
| | 5280 | 56 | n (20MHz) | 6.5/7.2 (MCS0) | 4.48 | 11.0 | -6.52 | Pass |
| | 5320 | 64 | n (20MHz) | 6.5/7.2 (MCS0) | 4.65 | 11.0 | -6.35 | Pass |
| | 5270 | 54 | n (40MHz) | 13.5/15 (MCS0) | -0.35 | 11.0 | -11.35 | Pass |
| | 5310 | 62 | n (40MHz) | 13.5/15 (MCS0) | -0.19 | 11.0 | -11.19 | Pass |
| | 5290 | 58 | ac (80MHz) | 29.3/32.5 (MCS0) | -5.33 | 11.0 | -16.33 | Pass |
| Band 2C | 5500 | 100 | a | 6 | 6.22 | 11.0 | -4.78 | Pass |
| | 5600 | 120 | a | 6 | 5.71 | 11.0 | -5.29 | Pass |
| | 5720 | 144 | a | 6 | 5.59 | 11.0 | -5.41 | Pass |
| | 5500 | 100 | n (20MHz) | 6.5/7.2 (MCS0) | 4.32 | 11.0 | -6.68 | Pass |
| | 5600 | 120 | n (20MHz) | 6.5/7.2 (MCS0) | 3.97 | 11.0 | -7.03 | Pass |
| | 5720 | 144 | n (20MHz) | 6.5/7.2 (MCS0) | 4.07 | 11.0 | -6.93 | Pass |
| | 5510 | 102 | n (40MHz) | 13.5/15 (MCS0) | 0.07 | 11.0 | -10.93 | Pass |
| | 5590 | 118 | n (40MHz) | 13.5/15 (MCS0) | -0.84 | 11.0 | -11.84 | Pass |
| | 5710 | 142 | n (40MHz) | 13.5/15 (MCS0) | -0.40 | 11.0 | -11.40 | Pass |
| | 5530 | 106 | ac (80MHz) | 29.3/32.5 (MCS0) | -5.00 | 11.0 | -16.00 | Pass |
| 5610 | 122 | ac (80MHz) | 29.3/32.5 (MCS0) | -5.54 | 11.0 | -16.54 | Pass | |
| 5690 | 138 | ac (80MHz) | 29.3/32.5 (MCS0) | -8.42 | 11.0 | -19.42 | Pass | |

Table 7-18. Bands 1, 2A, 2C Conducted Power Spectral Density Measurements

| | | | | |
|---|---|---|---|---------------------------------|
| FCC ID: A3LSMN950F |  | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) |  | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | Page 65 of 228 | |



Plot 7-79. Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 36)




Plot 7-80. Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 40)

| | | | | |
|---|--------------------------------|--|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 66 of 228 |




Plot 7-81. Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 48)



Plot 7-82. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)

| | | | | |
|---|--------------------------------|--|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 67 of 228 |




Plot 7-83. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 40)




Plot 7-84. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 48)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 68 of 228 |




Plot 7-85. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)




Plot 7-86. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

| | | | | |
|---|--------------------------------|--|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 69 of 228 |



Plot 7-87. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)




Plot 7-88. Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 52)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 70 of 228 |




Plot 7-89. Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 56)




Plot 7-90. Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 64)

| | | | | |
|---|--------------------------------|--|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 71 of 228 |




Plot 7-91. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 52)




Plot 7-92. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 56)

| | | | | |
|---|--------------------------------|--|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 72 of 228 |




Plot 7-93. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 64)




Plot 7-94. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 54)

| | | | | |
|---|--------------------------------|--|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 73 of 228 |




Plot 7-95. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 62)




Plot 7-96. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2A) – Ch. 58)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 74 of 228 |




Plot 7-97. Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 100)




Plot 7-98. Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 120)

| | | | | |
|---|--------------------------------|--|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 75 of 228 |




Plot 7-99. Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 144)



Plot 7-100. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 100)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 76 of 228 |




Plot 7-101. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 120)




Plot 7-102. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 144)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 77 of 228 |




Plot 7-103. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 102)




Plot 7-104. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 118)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 78 of 228 |




Plot 7-105. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 142)




Plot 7-106. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 106)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 79 of 228 |



Plot 7-107. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 122)




Plot 7-108. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 138)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 80 of 228 |

| | Frequency [MHz] | Channel No. | 802.11 Mode | Data Rate [Mbps] | Measured Power Density [dBm] | Max Permissible Power Density [dBm/500kHz] | Margin [dB] | Pass / Fail |
|---------------|-----------------|-------------|-------------|------------------|------------------------------|--|-------------|-------------|
| Band 3 | 5745 | 149 | a | 6 | 2.54 | 30.0 | -27.46 | Pass |
| | 5785 | 157 | a | 6 | 2.53 | 30.0 | -27.47 | Pass |
| | 5825 | 165 | a | 6 | 2.69 | 30.0 | -27.31 | Pass |
| | 5745 | 149 | n (20MHz) | 6.5/7.2 (MCS0) | 1.34 | 30.0 | -28.66 | Pass |
| | 5785 | 157 | n (20MHz) | 6.5/7.2 (MCS0) | 1.42 | 30.0 | -28.58 | Pass |
| | 5825 | 165 | n (20MHz) | 6.5/7.2 (MCS0) | 1.56 | 30.0 | -28.44 | Pass |
| | 5755 | 151 | n (40MHz) | 13.5/15 (MCS0) | -3.15 | 30.0 | -33.15 | Pass |
| | 5795 | 159 | n (40MHz) | 13.5/15 (MCS0) | -3.29 | 30.0 | -33.29 | Pass |
| | 5775 | 155 | ac (80MHz) | 29.3/32.5 (MCS0) | -5.14 | 30.0 | -35.14 | Pass |

Table 7-19. Band 3 Conducted Power Spectral Density Measurements




Plot 7-109. Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 149)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 81 of 228 |



Plot 7-110. Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 157)




Plot 7-111. Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 165)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 82 of 228 |



Plot 7-112. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 149)




Plot 7-113. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 157)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 83 of 228 |




Plot 7-114. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 165)



Plot 7-115. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 151)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 84 of 228 |



Plot 7-116. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 159)



Plot 7-117. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 3) – Ch. 155)

| | | | | |
|---|--------------------------------|---|--|---------------------------------|
| FCC ID: A3LSMN950F | | FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) | | Approved by: Quality Manager |
| Test Report S/N: 1M1705180172-06.A3L | Test Dates: 5/4 - 7/13/2017 | EUT Type: Portable Handset | | Page 85 of 228 |