

|           |            |
|-----------|------------|
| FCC ID's: | A3LSMN9600 |
| Date:     | 6/20/2018  |

| Frequency [MHz] | Probe Orientation (X, Y, Z) | Distance (cm) | Operational Correction Factor | Corrected H-field (A/m) |          |          |          |          |          | Limit [A/m] |
|-----------------|-----------------------------|---------------|-------------------------------|-------------------------|----------|----------|----------|----------|----------|-------------|
|                 |                             |               |                               | EUT Sides               |          |          |          |          |          |             |
|                 |                             |               |                               | A                       | B        | C        | D        | E        | F        |             |
| 0.594           | X                           | 15.0          | 0.064                         | 0.000187                | 0.000122 | 0.000097 | 0.000148 | 0.000155 | 0.000200 | 1.63        |
| 0.594           | X                           | 5.0           | 0.064                         | 0.000767                | 0.000290 | 0.000290 | 0.000445 | 0.000644 | 0.001695 | 1.63        |
| 0.594           | X                           | 4.0           | 0.064                         |                         |          |          |          |          | 0.002778 | 1.63        |
| 0.594           | X                           | 3.0           | 0.064                         |                         |          |          |          |          | 0.005175 | 1.63        |
| 0.594           | X                           | 2.0           | 0.064                         |                         |          |          |          |          | 0.008236 | 1.63        |
| 0.594           | X                           | 1.0           | 0.064                         |                         |          |          |          |          | 0.013636 | 1.63        |
| 0.594           | X                           | 0.0           | 0.064                         |                         |          |          |          |          | 0.035606 | 1.63        |

**Table 1. H-field Measurement by distance**

| Frequency [MHz] | Probe Orientation (X, Y, Z) | Distance (cm) | Operational Correction Factor | Corrected H-field (A/m) | Limit [A/m] |
|-----------------|-----------------------------|---------------|-------------------------------|-------------------------|-------------|
|                 |                             |               |                               | EUT Sides               |             |
|                 |                             |               |                               | F                       |             |
| 0.594           | X                           | 5.0           | 0.064                         | 0.001695                | 1.63        |
| 0.594           | Y                           | 5.0           | 0.064                         | 0.001469                | 1.63        |
| 0.594           | Z                           | 5.0           | 0.064                         | 0.001572                | 1.63        |

**Table 2. H-field Isotropy Measurement**

| A          | B        | C         | D        | E              | F    |
|------------|----------|-----------|----------|----------------|------|
| RIGHT EDGE | BOT EDGE | LEFT EDGE | TOP EDGE | FRONT (Screen) | BACK |

**Table 3. EUT Position Description**

**Corrected H-Field measurement**

- $0.5525 \text{ A/m} * 0.064 = 0.03536 \text{ A/m}$

**Operational Correction Factor**

- Charge time: 1 minute initial charge + 4 second for every 2 minutes Tx
- Over 30 minute period (per 1.1310): 1 minute + 14 cycles \* 4 sec = 1.93 minutes total charge Tx
- Operational Correction Factor = 1.93 minute / 30 minute = 0.064