



HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_0018724	6GHz_HP[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Limit Non-Restricted (dBuV/m)	Margin (dB)	Asimuth (Degs)	Height (cm)	Polarity
1	8.738	24.7	PK	36.3	-23.4	0	37.5	-	-	-	-	68.2	-30.6	0-360	150	H
3	* 11.646	24.44	PK	38.4	-19.9	0	42.94	-	-	74	-31.06	-	-	0-360	250	H
5	17.476	23.93	PK	41.4	-18.2	0	47.13	-	-	-	-	68.2	-21.07	0-360	150	H
2	8.738	25.11	PK	36.3	-23.5	0	37.91	-	-	-	-	68.2	-30.29	0-360	150	V
4	* 11.649	24.43	PK	38.4	-20	0	42.83	-	-	74	-31.17	-	-	0-360	150	V
6	17.473	23.84	PK	41.4	-18.2	0	47.04	-	-	-	-	68.2	-21.16	0-360	250	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

11.4.2.TX ABOVE 1GHz 802.11n HT20 2Tx CDD MODE IN THE 5.8GHz BAND BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK PLOT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	3117_001687 17	10dB[dB]	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.72499	-55.87	Pk	34.8	-21.1	11.8	0	-30.37	26.97	-57.34	214	236	H
2	5.64847	-64.41	Pk	34.7	-21.1	11.8	0	-39.01	-27	-12.01	214	236	H

Pk - Peak detector

VERTICAL PEAK PLOT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	3117_001687 17	10dB[dB]	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.72499	-62.39	Pk	34.8	-21.1	11.8	0	-36.89	26.97	-63.86	273	269	V
2	5.62947	-64.41	Pk	34.7	-21.1	11.8	0	-39.01	-27	-12.01	273	269	V

Pk - Peak detector

BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE DATA




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	3117_001687 17	10dB(dB)	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.85003	-61.21	Pk	35	-21	11.8	0	-35.41	26.94	-62.35	251	201	H
2	5.95918	-64.52	Pk	35.1	-20.7	11.8	0	-38.32	-27	-11.32	251	201	H

Pk - Peak detector

VERTICAL PEAK PLOT




Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBm)	Det	3117_001687 17	10dB(dB)	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.85003	-63.76	Pk	35	-21	11.8	0	-37.96	26.94	-64.9	277	262	V
2	5.97293	-64.9	Pk	35.1	-20.7	11.8	0	-38.7	-27	-11.7	277	262	V

Pk - Peak detector

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	6GHz_HF(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Asimuth (Degs)	Height (cm)	Polarity
1	8.619	23.63	PK	36.1	-22.1	0	37.63	-	-	-	-	68.2	-30.57	0-360	150	H
3	* 11.489	26.98	PK	38.3	-20	0	45.28	-	-	74	-28.72	-	-	0-360	250	H
5	17.24	23.51	PK	41.3	-18.7	0	46.11	-	-	-	-	68.2	-22.09	0-360	250	H
2	8.617	23.86	PK	36.1	-22	0	37.96	-	-	-	-	68.2	-30.24	0-360	250	V
4	* 11.491	25.8	PK	38.3	-19.9	0	44.2	-	-	74	-29.8	-	-	0-360	150	V
6	17.239	23.46	PK	41.3	-18.8	0	45.96	-	-	-	-	68.2	-22.24	0-360	250	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 PK – Peak Detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	6GHz_HF(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Asimuth (Degs)	Height (cm)	Polarity
* 11.49	35.44	PK-U	38.3	-19.9	0	53.84	-	-	74	-20.16	-	-	177	246	H
* 11.488	23.48	ADR	38.3	-19.9	0	41.88	54	-12.12	-	-	-	-	177	246	H
* 11.49	36.41	PK-U	38.3	-19.9	0	54.81	-	-	74	-19.19	-	-	177	152	V
* 11.491	23.93	ADR	38.3	-20	0	42.23	54	-11.77	-	-	-	-	177	152	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 PK-U - U-NII: Maximum Peak
 ADR - U-NII AD primary method, RMS average

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA


Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	6GHz_HP(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Limit Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	8.67612	24.22	PK	36.2	-22.9	0	37.52	-	-	-	-	68.2	-30.68	0-360	250	H
3	* 11.56882	24.43	PK	38.4	-20	0	42.83	-	-	74	-31.17	-	-	0-360	250	H
5	17.3557	24.02	PK	41.3	-18.9	0	46.42	-	-	-	-	68.2	-21.78	0-360	150	H
2	8.67686	24.2	PK	36.2	-22.9	0	37.5	-	-	-	-	68.2	-30.7	0-360	250	V
4	* 11.57252	24.73	PK	38.4	-20	0	43.13	-	-	74	-30.67	-	-	0-360	150	V
6	17.35496	23.57	PK	41.3	-18.8	0	46.07	-	-	-	-	68.2	-22.13	0-360	150	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_0018724	6GHz_HP[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Limit Non-Restricted (dBuV/m)	Margin (dB)	Asimuth (Degs)	Height (cm)	Polarity
1	8.737	25.05	PK	36.3	-23.4	0	37.95	-	-	-	-	68.2	-30.25	0-360	250	H
3	* 11.651	24.19	PK	38.4	-20	0	42.59	-	-	74	-31.41	-	-	0-360	250	H
5	17.476	23.77	PK	41.4	-18.2	0	46.97	-	-	-	-	68.2	-21.23	0-360	150	H
2	8.738	24.8	PK	36.3	-23.4	0	37.7	-	-	-	-	68.2	-30.5	0-360	150	V
4	* 11.649	24.28	PK	38.4	-20	0	42.68	-	-	74	-31.32	-	-	0-360	150	V
6	17.476	23.74	PK	41.4	-18.2	0	46.94	-	-	-	-	68.2	-21.26	0-360	250	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

11.4.3.TX ABOVE 1GHz 802.11n HT40 2Tx CDD MODE IN THE 5.8GHz BAND BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK PLOT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	3117_001687 17	10dB[dB]	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.72499	-55.94	Pk	34.8	-21.1	11.8	0	-30.44	26.97	-57.41	156	211	H
2	5.63837	-65.51	Pk	34.7	-21.1	11.8	0	-40.11	-27	-13.11	156	211	H

Pk - Peak detector

VERTICAL PEAK PLOT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	3117_001687 17	10dB[dB]	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.72499	-61.06	Pk	34.8	-21.1	11.8	0	-35.56	26.97	-62.53	273	270	V
2	5.63621	-63.97	Pk	34.7	-21.1	11.8	0	-38.57	-27	-11.57	273	270	V

Pk - Peak detector

BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK PLOT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	3117_001687 17	10dB(dB)	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.85003	-66.25	Pk	35	-21	11.8	0	-40.45	26.94	-67.39	158	216	H
2	5.99495	-64.35	Pk	35.1	-20.7	11.8	0	-38.15	-27	-11.15	158	216	H

Pk - Peak detector

VERTICAL PEAK PLOT




Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBm)	Det	3117_001687 17	10dB[dB]	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.85003	-66.79	Pk	35	-21	11.8	0	-40.99	26.94	-67.93	266	195	V
2	5.99743	-64.9	Pk	35.1	-20.7	11.8	0	-38.7	-27	-11.7	266	195	V

Pk - Peak detector

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA


Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_0018724	6GHz_HP[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Limit Non-Restricted (dBuV/m)	Margin (dB)	Asimuth (Degs)	Height (cm)	Polarity
1	8.631	23.85	PK	36.2	-22.2	0	37.85	-	-	-	-	68.2	-30.35	0-360	150	H
3	* 11.513	24.76	PK	38.3	-20	0	43.06	-	-	74	-30.94	-	-	0-360	250	H
5	17.265	23.68	PK	41.3	-18.8	0	46.18	-	-	-	-	68.2	-22.02	0-360	150	H
2	8.632	23.71	PK	36.2	-22.3	0	37.61	-	-	-	-	68.2	-30.59	0-360	150	V
4	* 11.512	23.86	PK	38.3	-19.9	0	42.26	-	-	74	-31.74	-	-	0-360	150	V
6	17.265	23.54	PK	41.3	-18.8	0	46.04	-	-	-	-	68.2	-22.16	0-360	150	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_0018724	6GHz_HP[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Limit Non-Restricted (dBuV/m)	Margin (dB)	Asimuth (Degs)	Height (cm)	Polarity
1	8.692	24.31	PK	36.2	-23.2	0	37.31	-	-	-	-	68.2	-30.89	0-360	150	H
3	* 11.591	23.95	PK	38.4	-20.2	0	42.15	-	-	74	-31.85	-	-	0-360	150	H
5	17.386	23.64	PK	41.4	-18.8	0	46.24	-	-	-	-	68.2	-21.96	0-360	150	H
2	8.692	23.99	PK	36.2	-23.2	0	36.99	-	-	-	-	68.2	-31.21	0-360	250	V
4	* 11.593	23.42	PK	38.4	-20.3	0	41.52	-	-	74	-32.48	-	-	0-360	150	V
6	17.386	23.6	PK	41.4	-18.8	0	46.2	-	-	-	-	68.2	-22	0-360	150	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

11.4.4. TX ABOVE 1GHz 802.11ac VHT80 2Tx CDD MODE IN THE 5.8GHz BAND BANDEDGE (Lower side)

HORIZONTAL PEAK PLOT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	3117_001687 17	10dB[dB]	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.72499	-64.17	Pk	34.8	-21.1	11.8	0	-38.67	26.97	-65.64	250	191	H
2	5.6374	-64.82	Pk	34.7	-21.1	11.8	0	-39.42	-27	-12.42	250	191	H

Pk - Peak detector

VERTICAL PEAK PLOT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	3117_001687 17	10dB[dB]	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.72499	-63.09	Pk		-21.1	11.8	0	-37.59	26.97	-64.56	271	270	V
2	5.64239	-65.01	Pk		-21.1	11.8	0	-39.61	-27	-12.61	271	270	V

Pk - Peak detector

BANDEDGE (Upper side)

HORIZONTAL PEAK PLOT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	3117_001687 17	10dB(dB)	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.85003	-66.88	Pk	35	-21	11.8	0	-41.08	26.94	-68.02	246	203	H
2	5.98413	-65.22	Pk	35.1	-20.7	11.8	0	-39.02	-27	-12.02	246	203	H

Pk - Peak detector

VERTICAL PEAK PLOT




Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBm)	Det	3117_001687 17	10dB[dB]	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.85003	-66.64	Pk	35	-21	11.8	0	-40.84	26.94	-67.78	272	276	V
2	5.93	-64.47	Pk	35.1	-20.8	11.8	0	-38.37	-27	-11.37	272	276	V

Pk - Peak detector

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	6GHz_HF[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	8.66204	25.26	PK	36.2	-22.6	0	38.86	-	-	-	-	68.2	-29.34	0-360	250	H
3	* 11.54956	23.92	PK	38.3	-19.8	0	42.42	-	-	74	-31.58	-	-	0-360	150	H
5	17.32534	23.06	PK	41.3	-18.9	0	45.46	-	-	-	-	68.2	-22.74	0-360	150	H
2	8.6613	24.51	PK	36.2	-22.6	0	38.11	-	-	-	-	68.2	-30.09	0-360	250	V
4	* 11.55178	23.63	PK	38.3	-19.9	0	42.03	-	-	74	-31.97	-	-	0-360	250	V
6	17.32534	23.85	PK	41.3	-18.9	0	46.25	-	-	-	-	68.2	-21.95	0-360	250	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK – Peak Detector


Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

12. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)



Below 1G Data

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163_750	Below_1G[dB]	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	59.585	32.58	Pk	18.6	-30.3	20.88	40	-19.12	0-360	400	H
3	104.108	37.01	Pk	17.9	-29.6	25.31	43.52	-18.21	0-360	300	H
5	175.015	36.67	Pk	15.1	-28.8	22.97	43.52	-20.55	0-360	200	H
2	60.846	40.19	Pk	18.4	-30.3	28.29	40	-11.71	0-360	100	V
4	104.884	33.62	Pk	17.8	-29.6	21.82	43.52	-21.7	0-360	200	V
6	* 171.038	34.1	Pk	14.8	-28.8	20.1	43.52	-23.42	0-360	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

13. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)
IC RSS-GEN Clause 8.8

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 [*]	56 to 46 [*]
0.5-5	56	46
5-30	60	50

^{*}Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

6 WORST EMISSIONS

LINE 1 PLOT



LINE 1 RESULTS

Trace Markers


Range 1: Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	ENV216_10183 6_With ex-cord_L1	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
1	.153	40.46	Pk	9.8	.1	50.36	65.84	-15.48	-	-
2	.174	17.44	Av	10	.2	27.64	-	-	54.77	-27.13
3	.459	31.98	Pk	9.9	.2	42.08	56.71	-14.63	-	-
4	.462	15.06	Av	9.9	.2	25.16	-	-	46.66	-21.5
5	1.548	13.35	Pk	9.8	.3	23.45	56	-32.55	-	-
6	1.542	3.61	Av	9.8	.3	13.71	-	-	46	-32.29
7	3.423	14.82	Pk	9.9	.3	25.02	56	-30.98	-	-
8	3.432	6.76	Av	9.9	.3	16.96	-	-	46	-29.04
9	11.652	20.37	Pk	10.1	.3	30.77	60	-29.23	-	-
10	11.652	10.06	Av	10.1	.3	20.46	-	-	50	-29.54
11	17.949	18.15	Pk	10.4	.4	28.95	60	-31.05	-	-
12	17.913	10.35	Av	10.3	.4	21.05	-	-	50	-28.95

Pk - Peak detector

Av - Average detection

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Range 2: Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	ENV216_10183 6_With ex-cord_N	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
13	.153	41.2	Pk	9.8	.1	51.1	65.84	-14.74	-	-
14	.171	17.67	Av	10	.2	27.87	-	-	54.91	-27.04
15	.459	29.21	Pk	9.5	.2	38.91	56.71	-17.8	-	-
16	.462	16.98	Av	9.6	.2	26.78	-	-	46.66	-19.88
17	1.536	17.4	Pk	9.7	.3	27.4	56	-28.6	-	-
18	1.572	5.19	Av	9.7	.3	15.19	-	-	46	-30.81
19	3.519	20.26	Pk	9.8	.3	30.36	56	-25.64	-	-
20	3.516	9.04	Av	9.8	.3	19.14	-	-	46	-26.86
21	5.349	19.42	Pk	9.8	.3	29.52	60	-30.48	-	-
22	5.349	9.28	Av	9.8	.3	19.38	-	-	50	-30.62
23	17.781	24.44	Pk	10.4	.4	35.24	60	-24.76	-	-
24	17.781	13.3	Av	10.4	.4	24.1	-	-	50	-25.9

Pk - Peak detector

Av - Average detection

14. DYNAMIC FREQUENCY SELECTION

14.1. OVERVIEW

14.1.1. LIMITS

FCC

§15.407 (h), FCC KDB 905462 D02 "COMPLIANCE MEASUREMENT PROCEDURES FOR UNLICENSED-NATIONAL INFORMATION INFRASTRUCTURE DEVICES OPERATING IN THE 5250-5350 MHz AND 5470-5725 MHz BANDS INCORPORATING DYNAMIC FREQUENCY SELECTION" and KDB 905462 D03 "U-NII CLIENT DEVICES WITHOUT RADAR DETECTION CAPABILITY".

Table 1: Applicability of DFS requirements prior to use of a channel

Requirement	Operational Mode		
	Master	Client (without radar detection)	Client (with radar detection)
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode		
	Master	Client (without DFS)	Client (with DFS)
DFS Detection Threshold	Yes	Not required	Yes
Channel Closing Transmission Time	Yes	Yes	Yes
Channel Move Time	Yes	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required	Yes

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar DFS	Client (without DFS)
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required
<p>Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in all 20 MHz channel blocks and a null frequency between the bonded 20 MHz channel blocks.</p>		

Table 3: Interference Threshold values, Master or Client incorporating In-Service Monitoring

Maximum Transmit Power	Value (see notes)
E.I.R.P. \geq 200 mill watt	-64 dBm
E.I.R.P. $<$ 200 mill watt and power spectral density $<$ 10 dBm/MHz	-62 dBm
E.I.R.P. $<$ 200 mill watt that do not meet power spectral density requirement	-64 dBm
<p>Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note 3: E.I.R.P. is based on the highest antenna gain. For MIMO devices refer to KDB publication 662911 D01.</p>	

Table 4: DFS Response requirement values

Parameter	Value
<i>Non-occupancy period</i>	30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds (See Note 1)
<i>Channel Closing Transmission Time</i>	200 milliseconds + approx. 60 milliseconds over remaining 10 second period. (See Notes 1 and 2)
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U- NII 99% transmission power bandwidth. (See Note 3)
<p>Note 1: <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel move</i> (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.</p>	

Table 5 – Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (usec)	PRI (usec)	Pulses	Minimum Percentage of Successful Detection	Minimum Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in table 5a	Roundup: $\{(1/360) \times (19 \times 10^6 \text{ PRI}_{\text{usec}})\}$	60%	30
		Test B: 15 unique PRI values randomly selected within the range of 518-3066 usec. With a minimum increment of 1 usec, excluding PRI values selected in Test A			
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the <i>Detection Bandwidth</i> test, <i>Channel Move Time</i> , and <i>Channel Closing Time</i> tests.					

Table 6 – Long Pulse Radar Test Signal


Radar Waveform Type	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Pulses per Burst	Number of Bursts	Minimum Percentage of Successful Detection	Minimum Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

Table 7 – Frequency Hopping Radar Test Signal

Radar Waveform Type	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Trials
6	1	333	9	0.333	300	70%	30

14.1.1. TEST AND MEASUREMENT SYSTEM

CONDUCTED METHOD SYSTEM BLOCK DIAGRAM



SYSTEM OVERVIEW

The short pulse and long pulse signal generating system utilizes the Keysite Signal Studio for Pulse Building as N5172B. The Vector Signal Generator has been validated by the NTIA. The hopping signal generating system utilizes the CCS simulated hopping method and system, which has been validated by the DoD, FCC and NTIA. The software selects waveform parameters from within the bounds of the signal type on a random basis using uniform distribution.

The short pulse types 1, 2, 3 and 4, and the long pulse type 5 parameters are randomized at run-time.

The hopping type 6 pulse parameters are fixed while the hopping sequence is based on the August 2005 NTIA Hopping Frequency List. The initial starting point randomized at run-time and each subsequent starting point is incremented by 475. Each frequency in the 100-length segment is compared to the boundaries of the EUT Detection Bandwidth and the software creates a hopping burst pattern in accordance with Section 7.4.1.3 Method #2 Simulated Frequency Hopping Radar Waveform Generating Subsystem of KDB 905462 D02. The frequency of the signal generator is incremented in 1 MHz steps from F_L to F_H for each successive trial. This incremental sequence is repeated as required to generate a minimum of 30 total trials and to maintain a uniform frequency distribution over the entire Detection Bandwidth.

The signal monitoring equipment consists of a spectrum analyzer. The aggregate ON time is calculated by multiplying the number of bins above a threshold during a particular observation period by the dwell time per bin, with the analyzer set to peak detection and max hold.

SYSTEM CALIBRATION

A 50-ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to a horn antenna via a coaxial cable, with the reference level offset set to (horn antenna gain – coaxial cable loss). The signal generator is set to CW mode. The amplitude of the signal generator is adjusted to yield a level of –64 dBm as measured on the spectrum analyzer.

Without changing any of the instrument settings, the spectrum analyzer is reconnected to the Common port of the Spectrum Analyzer Combiner/Divider. The Reference Level Offset of the spectrum analyzer is adjusted so that the displayed amplitude of the signal is –64 dBm.

The spectrum analyzer displays the level of the signal generator as received at the antenna ports of the Master Device. The interference detection threshold may be varied from the calibrated value of –64 dBm and the spectrum analyzer will still indicate the level as received by the Master Device.

ADJUSTMENT OF DISPLAYED TRAFFIC LEVEL

A link is established between the Master and Slave and the distance between the units is adjusted as needed to provide a suitable received level at the Master and Slave devices. The video test file is streamed to generate WLAN traffic. The monitoring antenna is adjusted so that the WLAN traffic level, as displayed on the spectrum analyzer, is at lower amplitude than the radar detection threshold.


TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the DFS tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	S/N	Next Cal Due
Spectrum Analyzer, 7 GHz	Agilent / HP	N9010A	MY54200580	08-07-19
Vector Signal Generator, 6GHz	Agilent / HP	N5182B	MY53051241	08-07-19

14.1.2. SETUP OF EUT

CONDUCTED METHOD EUT TEST SETUP



SUPPORT EQUIPMENT

The following support equipment was utilized for the DFS tests documented in this report:

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
Wireless Access Point	Cisco	AIR-CAP3702E-A-K9	FTX182276QX	LDK102087
Notebook PC (Controller/Server)	HP	HP EliteDesk 800 G1 TWR	CZC4125J25	DoC

14.1.3. DESCRIPTION OF EUT

The EUT operates over the 5250-5350 MHz and 5470-5725 MHz ranges.

The EUT is a Slave Device without Radar Detection.

The highest power level within these bands is 16.03 dBm in the 5250-5350 MHz band and 15.77 dBm in the 5470-5725 MHz band.

The antenna assembly utilized two antenna.

Gain of antenna 1 : -6.44 dBi for UNII 2A and -7.01 dBi for UNII 2C.

Gain of antenna 2 : -6.29 dBi for UNII 2A and -6.15 dBi for UNII 2C.

The rated output power of the Master unit is > 23dBm (EIRP). Therefore the required interference threshold level is -64 dBm. After correction for procedural adjustments, the required conducted threshold at the antenna port is $-64 + 1 = -63$ dBm.

The calibrated radiated DFS Detection Threshold level is set to -64 dBm. The tested level is lower than the required level hence it provides a margin to the limit.

The EUT uses one transmitter/receiver chain connected to an antenna to perform radiated tests.

WLAN traffic that meets or exceeds the minimum required loading was generated by transferring a data stream from the controller/server PC to the EUT using iPerf version 2.0.5 software package.

TPC is not required since the maximum EIRP is less than 500 mW (27 dBm).

The EUT utilizes the 802.11ac architecture. Three nominal channel bandwidths are implemented: 20 MHz, 40 MHz and 80 MHz.

The software installed in the access point is 12.4(25d)JA1.

UNIFORM CHANNEL SPREADING

This requirement is not applicable to Slave radio devices.

OVERVIEW OF MASTER DEVICE WITH RESPECT TO §15.407 (h) REQUIREMENTS

The Master Device is a Cisco Access Point, FCC ID: LDK102087. The minimum antenna gain for the Master Device is 6 dBi.

The rated output power of the Master unit is > 23dBm (EIRP). Therefore the required interference threshold level is -64 dBm. After correction for procedural adjustments, the required radiated threshold at the antenna port is $-64 + 1 = -63$ dBm.

The calibrated radiated DFS Detection Threshold level is set to -64 dBm. The tested level is lower than the required level hence it provides a margin to the limit.


14.2. RESULTS FOR 20 MHz BANDWIDTH

14.2.1. TEST CHANNEL


All tests were performed at a channel center frequency of 5500 MHz.

14.2.2. RADAR WAVEFORM AND TRAFFIC

RADAR WAVEFORM



TRAFFIC



14.2.3. OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

14.2.4. MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS



Channel Move Time (sec)	Limit (sec)
0.727	10

Aggregate Channel Closing Transmission Time (msec)	Limit (msec)
6.000	60

MOVE TIME & CHANNEL CLOSING TIME

AGGREGATE CHANNEL CLOSING TRANSMISSION TIME


No transmissions are observed during the aggregate monitoring period.



NON-OCCUPANCY PERIOD

RESULTS

No EUT transmissions were observed on the test channel during the 10-minute observation time.




14.3. RESULTS FOR 40 MHz BANDWIDTH

14.3.1. TEST CHANNEL


All tests were performed at a channel center frequency of 5510 MHz.

14.3.2. RADAR WAVEFORM AND TRAFFIC

RADAR WAVEFORM



TRAFFIC



14.3.3. OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

14.3.4. MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS



Channel Move Time (sec)	Limit (sec)
0.775	10

Aggregate Channel Closing Transmission Time (msec)	Limit (msec)
5.250	60

MOVE TIME & CHANNEL CLOSING TIME

AGGREGATE CHANNEL CLOSING TRANSMISSION TIME

No transmissions are observed during the aggregate monitoring period.




14.4. RESULTS FOR 80 MHz BANDWIDTH

14.4.1. TEST CHANNEL


All tests were performed at a channel center frequency of 5530 MHz.

14.4.2. RADAR WAVEFORM AND TRAFFIC

RADAR WAVEFORM



TRAFFIC



14.4.3. OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

14.4.4. MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS



Channel Move Time (sec)	Limit (sec)
0.740	10

Aggregate Channel Closing Transmission Time (msec)	Limit (msec)
6.375	60

MOVE TIME & CHANNEL CLOSING TIME

AGGREGATE CHANNEL CLOSING TRANSMISSION TIME

No transmissions are observed during the aggregate monitoring period.



NON-OCCUPANCY PERIOD

RESULTS

No EUT transmissions were observed on the test channel during the 10-minute observation time.

