



**FCC CFR47 PART 15 SUBPART C**

**ANT+**

**CERTIFICATION TEST REPORT**

**FOR**

**GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax, ANT+, NFC and WPT**

**MODEL NUMBER : SM-N976B**

**FCC ID: A3LSMN976B**

**REPORT NUMBER: 4789009800-E10V3**

**ISSUE DATE: JUN 26, 2019**

*Prepared for*  
**SAMSUNG ELECTRONICS CO., LTD.**  
**129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,**  
**GYEONGGI-DO, 16677, KOREA**

*Prepared by*  
**UL Korea, Ltd.**  
**26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea**

**Suwon Test Site: UL Korea, Ltd. Suwon Laboratory**  
**218 Maeyeong-ro, Yeongtong-gu,**  
**Suwon-si, Gyeonggi-do, 16675, Korea**  
**TEL: (031) 337-9902**  
**FAX: (031) 213-5433**



Testing  
Laboratory

**TL-637**

---

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	06/17/19	Initial issue	Junwhan Lee
V2	06/19/19	Updated to address TCB's question	Junwhan Lee
V3	06/26/19	Updated to address TCB's question	Junwhan Lee

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>4</b>
<b>2. TEST METHODOLOGY .....</b>	<b>5</b>
<b>3. FACILITIES AND ACCREDITATION .....</b>	<b>5</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>5</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION.....</i>	<i>5</i>
4.2. <i>SAMPLE CALCULATION.....</i>	<i>5</i>
4.3. <i>MEASUREMENT UNCERTAINTY .....</i>	<i>5</i>
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>6</b>
5.1. <i>DESCRIPTION OF EUT.....</i>	<i>6</i>
5.2. <i>MAXIMUM E-FIELD STRENGTH.....</i>	<i>6</i>
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	<i>6</i>
5.4. <i>WORST-CASE CONFIGURATION AND MODE .....</i>	<i>6</i>
5.5. <i>DESCRIPTION OF TEST SETUP .....</i>	<i>7</i>
<b>6. TEST AND MEASUREMENT EQUIPMENT .....</b>	<b>9</b>
<b>7. LIMITS AND RESULTS.....</b>	<b>10</b>
7.1. <i>99% BANDWIDTH .....</i>	<i>10</i>
7.2. <i>TRANSMITTER RADIATED EMISSIONS .....</i>	<i>12</i>
7.2.1. <i>DUTY CYCLE .....</i>	<i>14</i>
7.2.1. <i>FUNDAMENTAL FIELD STRENGTH LEVEL .....</i>	<i>15</i>
7.2.2. <i>TRANSMITTER BAND EDGES .....</i>	<i>21</i>
7.2.3. <i>HARMONICS AND SPURIOUS EMISSIONS .....</i>	<i>24</i>
7.2.4. <i>SPURIOUS BELOW 1 GHz .....</i>	<i>31</i>
<b>8. AC POWER LINE CONDUCTED EMISSIONS .....</b>	<b>33</b>
<b>9. SETUP PHOTOS.....</b>	<b>36</b>

# 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** SAMSUNG ELECTRONICS CO., LTD.  
**EUT DESCRIPTION:** GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax, ANT+, NFC and WPT  
**MODEL NUMBER:** SM-N976B  
**SERIAL NUMBER:** R3CM506PPMB (CONDUCTED)  
cea741c773197e35, R3CM506Q9KN (RADIATED);  
**DATE TESTED:** MAY 30, 2019 – JUN 17, 2019;

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For  
UL Korea, Ltd. By:

Tested By:



SungGil Park  
Suwon Lab Engineer  
UL Korea, Ltd.

Junwhan Lee  
Suwon Lab Engineer  
UL Korea, Ltd.

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. ANSI C63.10-2013.

## 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
<input checked="" type="checkbox"/>	Chamber 1
<input checked="" type="checkbox"/>	Chamber 2
<input type="checkbox"/>	Chamber 3

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

### 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, 30 MHz to 1 GHz	3.86 dB
Radiated Disturbance, 1 GHz to 18 GHz	5.97 dB
Radiated Disturbance, 18 GHz to 40 GHz	5.57 dB

Uncertainty figures are valid to a confidence level of 95%.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax, ANT+, NFC and WPT. This test report addresses the ANT+ operational mode.

### 5.2. MAXIMUM E-FIELD STRENGTH

The ANT+ mode has maximum output fundamental field strength as follows:

Frequency Range [MHz]	Mode	Peak E-field Strength [dBuV/m]	Avg E-field Strength [dBuV/m]	Distance [m]
2402 - 2480	ANT +	96.97	66.76	3.00

### 5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an internal antenna, with a maximum gain of -6.11 dBi

### 5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.

Note : All radiated and power line conducted tests were performed attached with travel adapter for the worst case condition mode.

## 5.5. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA800	R37M4PW4FW1SE3	N/A
Data Cable	SAMSUNG	EP-DG977	N/A	N/A

### I/O CABLE


I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	C Type	Shielded	1.0m	N/A

### TEST SETUP


The EUT is set to continuously transmit in ANT + test mode.  
 Test software in hidden menu exercised the EUT to enable ANT+ mode.

This EUT is able to equipped with S-pen on the inside. Spot check were performed both inserted and removed condition. Because there is no deviation between the two data, all tests were performed under equipped with the S-pen.

**SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)**



**SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)**



## 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	New Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	08-04-20
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	08-04-20
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	845	08-04-20
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	10-26-19
Antenna, Horn, 18 GHz	ETS	3115	00167211	08-04-20
Antenna, Horn, 18 GHz	ETS	3115	00161451	08-04-20
Antenna, Horn, 18 GHz	ETS	3117	00168724	08-04-20
Antenna, Horn, 18 GHz	ETS	3117	00168717	08-04-20
Antenna, Horn, 18 GHz	ETS	3117	00205959	08-04-20
Antenna, Horn, 40 GHz	ETS	3116C	00166155	08-14-20
Antenna, Horn, 40 GHz	ETS	3116C	00168645	12-04-19
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	08-09-19
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-07-19
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-07-19
Preamplifier, 1000 MHz	Sonoma	310N	370599	08-06-19
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	08-07-19
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-07-19
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	2029169	08-07-19
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-07-19
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-06-19
Spectrum Analyzer, 43.5 GHz	R&S	FSW43	104089	08-06-19
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-07-19
Attenuator	PASTERNAK	PE7087-10	A001	08-08-19
Attenuator	PASTERNAK	PE7087-10	A008	08-08-19
Attenuator	PASTERNAK	PE7004-10	2	08-07-19
Attenuator	PASTERNAK	PE7087-10	A009	08-08-19
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-06-19
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-06-19
EMI Test Receive, 44 GHz	R&S	ESW44	101590	08-06-19
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-06-19
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	08-07-19
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	08-07-19
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	020	08-06-19
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	08-07-19
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	08-07-19
High Pass Filter 3GHz	Micro-Tronics	HPM17543	020	08-06-19
High Pass Filter 6GHz	Micro-Tronics	HPS17542	009	08-07-19
High Pass Filter 6GHz	Micro-Tronics	HPS17542	016	08-07-19
High Pass Filter 6GHz	Micro-Tronics	HPS17542	021	08-06-19
LISN	R&S	ENV-216	101837	08-09-19
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	

## 7. LIMITS AND RESULTS

### 7.1. 99% BANDWIDTH

#### LIMITS

None; for reporting purposes only.

#### TEST PROCEDURE


The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

#### RESULTS


Channel	Frequency [MHz]	99% Bandwidth [kHz]	20 dB Bandwidth [kHz]
Low	2402	1008.7	1033.0
Mid	2441	1009.4	1033.0
High	2480	1009.6	1032.0
Worst		1009.6	1033.0

**99% BANDWIDTH PLOTS**


**LOW CHANNEL**



**MID CHANNEL**



**HIGH CHANNEL**



## 7.2. TRANSMITTER RADIATED EMISSIONS

### TEST PROCEDURE

ANSI C63.10: 2013

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and add duty cycle factor for average measurements.

Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 KHz for peak measurements.

### LIMIT

FCC §15.249

Operation within the bands 902–928 MHz, 2400–2483.5 MHz, 5725–5875 MHz, and 24.0–24.25 GHz.

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

<b>Fundamental frequency</b>	<b>Field strength of fundamental (millivolts/meter)</b>	<b>Field strength of harmonics (microvolts/meter)</b>
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

(e) As shown in Sec. 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3


\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

Note : Emission was pre-scanned from 9KHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit (consider distance correction factor).  
 Per FCC part 15.31(o), test results were not reported.

Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open are test site.  
 Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the one of tests made in an open field based on KDB 414788.


**RESULTS**

**7.2.1. DUTY CYCLE**



## 7.2.1. FUNDAMENTAL FIELD STRENGTH LEVEL

### LOW CHANNEL, HORIZONTAL



### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB[dB]	Corrected Reading (dBuV/m)	Azimuth (Degs)	Height (cm)	Polarity
1	2.40226	90.04	Pk	31.7	-25.4	96.34	316	154	H

### Pk - Peak detector

Peak reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)
96.34	114	17.66


\*\* For marker 1 used the following method to do averaging:

DCCF = -30.21

Corrected AV reading = Peak Reading + DCCF

= 96.34 + -30.21 = 66.13 dBuV/m, AVG Limit : 94 dBuV/m, Margin 27.87 dB]

**LOW CHANNEL, VERTICAL**



**Trace Markers**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB[dB]	Corrected Reading (dBuV/m)	Azimuth (Degs)	Height (cm)	Polarity
1	2.40185	90.51	Pk	31.7	-25.4	96.81	121	170	V

Pk - Peak detector

\*

Peak reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)
96.81	114	17.19


\*\* For marker 1 used the following method to do averaging:

DCCF = -30.21

Corrected AV reading = Peak Reading + DCCF

= 96.81 + -30.21 = 66.6 dBuV/m, AVG Limit : 94 dBuV/m, Margin 27.4 dB]

**MID CHANNEL, HORIZONTAL**



**Trace Markers**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB[dB]	Corrected Reading (dBuV/m)	Azimuth (Degs)	Height (cm)	Polarity
1	2.44105	90.02	Pk	31.8	-25.3	96.52	237	174	H

Pk - Peak detector

Peak reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)
96.52	114	17.48


\*\* For marker 1 used the following method to do averaging:

DCCF = -30.21

Corrected AV reading = Peak Reading + DCCF

= 96.52 + -30.21 = 66.31 dBuV/m, AVG Limit : 94 dBuV/m, Margin 27.69 dB]

**MID CHANNEL, VERTICAL**



**Trace Markers**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB[dB]	Corrected Reading (dBuV/m)	Azimuth (Degs)	Height (cm)	Polarity
1	2.44079	90.35	Pk	31.8	-25.4	96.75	110	181	V

Pk - Peak detector

Peak reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)
96.75	114	17.25


\*\* For marker 1 used the following method to do averaging:

DCCF = -30.21

Corrected AV reading = Peak Reading + DCCF

= 96.75 + -30.21 = 66.54 dBuV/m; AVG Limit : 94 dBuV/m, Margin 27.46 dB]

**HIGH CHANNEL, HORIZONTAL**



**Trace Markers**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB[dB]	Corrected Reading (dBuV/m)	Azimuth (Degs)	Height (cm)	Polarity
1	2.48014	90.37	Pk	31.9	-25.3	96.97	236	162	H

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

Peak reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)
96.97	114	17.03


\*\* For marker 1 used the following method to do averaging:

DCCF = -30.21

Corrected AV reading = Peak Reading + DCCF

= 96.97 + -30.21 = 66.76 dBuV/m AVG Limit : 94 dBuV/m, Margin 27.24 dB

**HIGH CHANNEL, VERTICAL**



**Trace Markers**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB[dB]	Corrected Reading (dBuV/m)	Azimuth (Degs)	Height (cm)	Polarity
1	2.47982	88.41	Pk	31.9	-25.3	95.01	96	156	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

Peak reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)
95.01	114	18.99

\*\* For marker 1 used the following method to do averaging:


DCCF = -30.21

Corrected AV reading = Peak Reading + DCCF

= 95.01 + -30.21 = 64.8 dBuV/m, AVG Limit : 94 dBuV/m, Margin 29.2 dB]

## 7.2.2. TRANSMITTER BAND EDGES

### BANDEDGE (LOW CHANNEL, HORIZONTAL)



### HORIZONTAL DATA

#### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB[dB]	Corrected Reading (dBuV/m)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.4	44.77	Pk	31.7	-25.5	50.97	74	-23.03	316	154	H
2	2.39988	48.12	Pk	31.7	-25.5	54.32	74	-19.68	316	154	H

Pk - Peak detector

\* For marker 1 used the following method to do averaging:

$$DCCF = -30.21 \quad / \quad \text{Peak Reading} = 50.97 \text{ dBuV/m}$$

$$\text{Corrected AV reading} = \text{Peak Reading} + DCCF$$

$$= 50.97 + -30.21 = 20.76 \text{ dBuV/m} \quad \text{AVG Limit : 54 dBuV/m, Margin 33.24 dB}$$


\* For marker 2 used the following method to do averaging:

$$DCCF = -30.21 \quad / \quad \text{Peak Reading} = 54.32 \text{ dBuV/m}$$

$$\text{Corrected AV reading} = \text{Peak Reading} + DCCF$$

$$= 54.32 + -30.21 = 24.11 \text{ dBuV/m} \quad \text{AVG Limit : 54 dBuV/m, Margin 29.89 dB}$$

### VERTICAL PEAK AND AVERAGE PLOT



**VERTICAL DATA**

**Trace Markers**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB[dB]	Corrected Reading (dBuV/m)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.4	50.94	Pk	31.7	-25.5	57.14	74	-16.86	121	170	V
2	2.39999	46.6	Pk	31.7	-25.5	52.8	74	-21.2	121	170	V

Pk - Peak detector

\* For marker 1 used the following method to do averaging:

$$DCCF = -30.21 \quad / \quad \text{Peak Reading} = \underline{57.14} \text{ dBuV/m}$$

$$\text{Corrected AV reading} = \text{Peak Reading} + DCCF$$

$$= 57.14 + -30.21 = 26.93 \text{ dBuV/m} \quad \text{AVG Limit : 54 dBuV/m, Margin 27.07 dB}$$

\* For marker 2 used the following method to do averaging:


$$DCCF = -30.21 \quad / \quad \text{Peak Reading} = \underline{52.8} \text{ dBuV/m}$$

$$\text{Corrected AV reading} = \text{Peak Reading} + DCCF$$

$$= 52.8 + -30.21 = 22.59 \text{ dBuV/m} \quad \text{AVG Limit : 54 dBuV/m, Margin 31.41 dB}$$

**AUTHORIZED BANDEDGE (HIGH CHANNEL)**

**HORIZONTAL PEAK AND AVERAGE PLOT**



**HORIZONTAL DATA**

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB[dB]	Corrected Reading (dBuV/m)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.48351	42.55	Pk	31.9	-25.3	49.15	74	-24.85	236	162	H
2	2.50576	45.71	Pk	32	-25.2	52.51	74	-21.49	236	162	H

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 Pk - Peak detector

\* For marker 1 used the following method to do averaging:

DCCF = -30.21 / Peak Reading = 49.15 dBuV/m

Corrected AV reading = Peak Reading + DCCF

= 49.15 + -30.21 = 18.94 dBuV/m AVG Limit : 54 dBuV/m, Margin 35.06 dB]


\* For marker 2 used the following method to do averaging:

DCCF = -30.21 / Peak Reading = 52.51 dBuV/m

Corrected AV reading = Peak Reading + DCCF

= 52.51 + -30.21 = 22.3 dBuV/m AVG Limit : 54 dBuV/m, Margin 31.7 dB]

**VERTICAL PEAK AND AVERAGE PLOT**



### VERTICAL DATA

#### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB[dB]	Corrected Reading (dBuV/m)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.48351	42.45	Pk	31.9	-25.3	49.05	74	-24.95	96	156	V
2	2.52176	45.73	Pk	32	-25.2	52.53	74	-21.47	96	156	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

\* For marker 1 used the following method to do averaging:

$$DCCF = -30.21 \quad / \quad \text{Peak Reading} = \underline{49.05} \text{ dBuV/m}$$

$$\text{Corrected AV reading} = \text{Peak Reading} + DCCF$$

$$= 49.05 + -30.21 = \underline{18.84} \text{ dBuV/m} \quad \text{AVG Limit : 54 dBuV/m, Margin } \underline{35.16} \text{ dB}$$

\* For marker 2 used the following method to do averaging:


$$DCCF = -30.21 \quad / \quad \text{Peak Reading} = \underline{52.53} \text{ dBuV/m}$$

$$\text{Corrected AV reading} = \text{Peak Reading} + DCCF$$


$$= 52.53 + -30.21 = \underline{22.32} \text{ dBuV/m} \quad \text{AVG Limit : 54 dBuV/m, Margin } \underline{31.68} \text{ dB}$$

### 7.2.3. HARMONICS AND SPURIOUS EMISSIONS

### LOW CHANNEL HORIZONTAL



### LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

## LOW CHANNEL DATA

### Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_0016871 7	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.80082	32.49	PK	34.2	-31.4	35.29	-	-	74	-38.71	0-360	250	H
3	7.20724	28.48	PK	35.8	-27.9	36.38	-	-	74	-37.62	0-360	250	H
5	9.60896	25.85	PK	37	-23.1	39.75	-	-	74	-34.25	0-360	250	H
2	* 4.80457	32.79	PK	34.2	-31.4	35.59	-	-	74	-38.41	0-360	250	V
4	7.20724	28.38	PK	35.8	-27.9	36.28	-	-	74	-37.72	0-360	150	V
6	9.60802	25.71	PK	37	-23.1	39.61	-	-	74	-34.39	0-360	150	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

### MID CHANNEL HORIZONTAL



### MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

### MID CHANNEL DATA


#### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_0016871 7	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.88144	31.33	PK	34.2	-31.5	34.03	-	-	74	-39.97	0-360	250	H
3	* 7.32348	28.62	PK	35.8	-27.3	37.12	-	-	74	-36.88	0-360	150	H
5	9.76457	26.77	PK	37.2	-23.9	40.07	-	-	74	-33.93	0-360	250	H
2	* 4.88332	31.67	PK	34.2	-31.5	34.37	-	-	74	-39.63	0-360	150	V
4	* 7.32348	28.42	PK	35.8	-27.3	36.92	-	-	74	-37.08	0-360	250	V
6	9.76176	26.74	PK	37.2	-23.9	40.04	-	-	74	-33.96	0-360	150	V


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

### HIGH CHANNEL HORIZONTAL



### HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

## HIGH CHANNEL DATA

### Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_0016871 7	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.95738	31.99	PK	34.2	-31.4	34.79	-	-	74	-39.21	0-360	250	H
3	* 7.44066	28.16	PK	35.8	-27	36.96	-	-	74	-37.04	0-360	150	H
5	9.91457	25.3	PK	37.5	-22.3	40.5	-	-	74	-33.5	0-360	250	H
2	* 4.96206	31.65	PK	34.2	-31.4	34.45	-	-	74	-39.55	0-360	250	V
4	* 7.43972	29	PK	35.8	-27	37.8	-	-	74	-36.2	0-360	150	V
6	9.91082	25.37	PK	37.5	-22.3	40.57	-	-	74	-33.43	0-360	250	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band  
 PK – Peak Detector


Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

### 7.2.4. SPURIOUS BELOW 1 GHz

#### SPURIOUS EMISSIONS 30 TO 1000 MHz (HORIZONTAL)



#### SPURIOUS EMISSIONS 30 TO 1000 MHz (VERTICAL)



**BELOW 1 GHz TABLE**

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163_750	Below_1G[dB]	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	51.049	32.2	Pk	19.8	-30.5	21.5	40	-18.5	0-360	400	H
3	99.549	36.47	Pk	17.8	-29.7	24.57	43.52	-18.95	0-360	300	H
5	177.246	38.48	Pk	15.2	-28.7	24.98	43.52	-18.54	0-360	100	H
2	50.467	35.65	Pk	19.7	-30.5	24.85	40	-15.15	0-360	100	V
4	97.997	32.5	Pk	17.7	-29.7	20.5	43.52	-23.02	0-360	100	V
6	176.761	33.56	Pk	15.2	-28.7	20.06	43.52	-23.46	0-360	200	V

Pk - Peak detector

## 8. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

FCC §15.207 (a)

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

**RESULTS**

**6 WORST EMISSIONS**

**LINE 1 PLOT**



**LINE 1 RESULTS**

Trace Markers


Range 1: Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	ENV216_10183 6_With ex-cord_L1	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
1	.474	30.45	Pk	9.9	.2	40.55	56.44	-15.89	-	-
2	.471	19.17	Av	9.9	.2	29.27	-	-	46.5	-17.23
3	.927	20.81	Pk	9.8	.3	30.91	56	-25.09	-	-
4	.906	9.62	Av	9.8	.3	19.72	-	-	46	-26.28
5	1.734	21.72	Pk	9.8	.3	31.82	56	-24.18	-	-
6	1.731	8.74	Av	9.8	.3	18.84	-	-	46	-27.16
7	3.57	20.11	Pk	9.9	.3	30.31	56	-25.69	-	-
8	3.57	8.58	Av	9.9	.3	18.78	-	-	46	-27.22
9	12	29.04	Pk	10.1	.3	39.44	60	-20.56	-	-
10	12.006	15.96	Av	10.1	.3	26.36	-	-	50	-23.64
11	18.264	26.24	Pk	10.4	.4	37.04	60	-22.96	-	-
12	18.252	14.4	Av	10.4	.4	25.2	-	-	50	-24.8

Pk - Peak detector

Av - Average detection

### LINE 2 PLOT



### LINE 2 RESULTS

#### Trace Markers

Range 2: Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	ENV216_10183 6_With ex-cord_N	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
13	.495	27.92	Pk	9.9	.2	38.02	56.08	-18.06	-	-
14	.501	13.08	Av	9.9	.2	23.18	-	-	46	-22.82
15	1.269	14.25	Pk	9.8	.3	24.35	56	-31.65	-	-
16	1.254	6.56	Av	9.8	.3	16.66	-	-	46	-29.34
17	2.25	13.18	Pk	9.7	.3	23.18	56	-32.82	-	-
18	2.25	7.78	Av	9.7	.3	17.78	-	-	46	-28.22
19	4.287	13.66	Pk	9.8	.3	23.76	56	-32.24	-	-
20	4.29	5.68	Av	9.8	.3	15.78	-	-	46	-30.22
21	12.558	14.5	Pk	10.1	.3	24.9	60	-35.1	-	-
22	12.573	3.14	Av	10.1	.3	13.54	-	-	50	-36.46
23	18.3	11.82	Pk	10.4	.4	22.62	60	-37.38	-	-
24	18.324	6.05	Av	10.4	.4	16.85	-	-	50	-33.15

Pk - Peak detector

Av - Average detection