

**MEASUREMENT REPORT
 FCC Part 22 & 90**

Applicant Name:
 Samsung Electronics Co., Ltd.
 129, Samsung-ro,
 Yeongtong-gu, Suwon-si
 Gyeonggi-do, 16677, Korea


Date of Testing:
 9/09 - 10/23/2019
Test Site/Location:
 PCTEST Lab. Columbia, MD USA
Test Report Serial No.:
 1M1909040147-04.A3L

FCC ID:	A3LSMN976U
APPLICANT:	Samsung Electronics Co., Ltd.

Application Type: Certification
Model: SM-N976U
EUT Type: Portable Handset
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part: §2.1049, §22(H), §90(S), §90(R)
Test Procedure(s): ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01, KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


 Randy Ortanez
 President




FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 1 of 54	

TABLE OF CONTENTS


1.0	INTRODUCTION	4
1.1	Scope	4
1.2	PCTEST Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description	5
2.2	Device Capabilities.....	5
2.3	Test Configuration	5
2.4	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Radiated Power and Radiated Spurious Emissions	6
4.0	MEASUREMENT UNCERTAINTY	7
5.0	TEST EQUIPMENT CALIBRATION DATA	8
6.0	SAMPLE CALCULATIONS	9
7.0	TEST RESULTS	10
7.1	Summary.....	10
7.2	Occupied Bandwidth	12
7.3	Spurious and Harmonic Emissions at Antenna Terminal	27
7.4	Band Edge Emissions at Antenna Terminal	31
7.5	Conducted Power Output Data	40
7.6	Radiated Power (ERP).....	41
7.7	Radiated Spurious Emissions Measurements.....	43
7.8	Frequency Stability / Temperature Variation	49
8.0	CONCLUSION.....	54

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 2 of 54	



MEASUREMENT REPORT

FCC Part 22(H) & 90



Mode	Tx Frequency (MHz)	Measurement	Max. Power (W)	Max. Power (dBm)	Emission Designator	Modulation
LTE Band 14	790.5 - 795.5	ERP	0.062	17.91	4M56G7D	QPSK
LTE Band 14	790.5 - 795.5	ERP	0.050	16.99	4M53W7D	16-QAM
LTE Band 14	790.5 - 795.5	ERP	0.040	16.04	4M46W7D	64-QAM
LTE Band 14	790.5 - 795.5	ERP	0.019	12.74	4M53W7D	256-QAM
LTE Band 14	793	ERP	0.055	17.43	9M02G7D	QPSK
LTE Band 14	793	ERP	0.051	17.06	9M03W7D	16-QAM
LTE Band 14	793	ERP	0.039	15.94	9M02W7D	64-QAM
LTE Band 14	793	ERP	0.014	11.31	8M99W7D	256-QAM
LTE Band 26	814.7 - 823.3	Conducted	0.334	25.24	1M09G7D	QPSK
LTE Band 26	814.7 - 823.3	Conducted	0.267	24.26	1M08W7D	16-QAM
LTE Band 26	814.7 - 823.3	Conducted	0.207	23.15	1M08W7D	64-QAM
LTE Band 26	815.5 - 822.5	Conducted	0.103	20.12	1M08W7D	256-QAM
LTE Band 26	815.5 - 822.5	Conducted	0.317	25.01	2M69G7D	QPSK
LTE Band 26	815.5 - 822.5	Conducted	0.257	24.10	2M69W7D	16-QAM
LTE Band 26	815.5 - 822.5	Conducted	0.193	22.85	2M69W7D	64-QAM
LTE Band 26	815.5 - 822.5	Conducted	0.103	20.11	2M69W7D	256-QAM
LTE Band 26	816.5 - 821.5	Conducted	0.305	24.85	4M54G7D	QPSK
LTE Band 26	816.5 - 821.5	Conducted	0.258	24.11	4M51W7D	16-QAM
LTE Band 26	816.5 - 821.5	Conducted	0.203	23.07	4M50W7D	64-QAM
LTE Band 26	816.5 - 821.5	Conducted	0.104	20.17	4M48W7D	256-QAM
LTE Band 26	819	Conducted	0.335	25.25	8M96G7D	QPSK
LTE Band 26	819	Conducted	0.277	24.42	8M98W7D	16-QAM
LTE Band 26	819	Conducted	0.183	22.63	8M97W7D	64-QAM
LTE Band 26	819	Conducted	0.100	20.02	8M95W7D	256-QAM
LTE Band 26	821.5	Conducted	0.316	24.99	13M4G7D	QPSK
LTE Band 26	821.5	Conducted	0.269	24.29	13M5W7D	16-QAM
LTE Band 26	821.5	Conducted	0.205	23.11	13M5W7D	64-QAM
LTE Band 26	821.5	Conducted	0.100	20.01	13M4W7D	256-QAM
LTE Band 26	821.5	ERP	0.044	16.42	13M4G7D	QPSK
LTE Band 26	821.5	ERP	0.038	15.78	13M5W7D	16-QAM
LTE Band 26	821.5	ERP	0.028	14.51	13M5W7D	64-QAM
LTE Band 26	821.5	ERP	0.011	10.57	13M4W7D	256-QAM

EUT Overview

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 3 of 54	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046 U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 4 of 54	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMN976U**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 90(R), 22(H) and 90(S).

Test Device Serial No.: 17907,12643, 12601, 12684,12619, 13898

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII, Bluetooth (1x, EDR, LE), NFC, ANT+, Wireless Power Transfer

This device uses a tuner circuit that dynamically updates the antenna impedance parameters to optimize antenna performance for certain bands and modes of operation. The tuner for this device was set to simulate a "free space" condition where the transmit antenna is matched to the medium into which it is transmitting and, thus, the power is at its maximum level.

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) FCC ID: EP-N5100 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMN976U	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 5 of 54

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

3.2 Radiated Power and Radiated Spurious Emissions §2.1053, §90.635, §90(S), §90(R)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer “Channel Power” function with the integration band set to the emissions’ occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03r01.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10 \log_{10}(\text{Power [Watts]})$ specified in 90(S).

For fundamental radiated power measurements, the guidance of KDB 971168 D01 v03r01 is used to record the EUT power level that is subsequently matched via the aforementioned substitution method given in ANSI/TIA-603-E-2016.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 6 of 54	

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMN976U	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 7 of 54

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTX1	Licensed Transmitter Cable Set	6/4/2019	Annual	6/4/2020	LTX1
-	LTX5	Licensed Transmitter Cable Set	6/5/2019	Annual	6/5/2020	LTX5
Agilent	N9020A	MXA Signal Analyzer	4/20/2019	Annual	4/20/2020	US46470561
Agilent	N9038A	MXE EMI Receiver	7/17/2019	Annual	7/17/2020	MY51210133
Agilent	N9030A	PXA Signal Analyzer (44GHz)	6/12/2019	Annual	6/12/2020	MY52350166
Com-Power	PAM-103	Pre-Amplifier (1-1000MHz)	5/10/2019	Annual	5/10/2020	441112
Emco	3115	Horn Antenna (1-18GHz)	3/28/2018	Biennial	3/28/2020	9704-5182
EMCO	3160-09	Small Horn (18 - 26.5GHz)	8/9/2018	Biennial	8/9/2020	135427
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	2/14/2019	Biennial	2/14/2021	125518
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	3/28/2018	Biennial	3/28/2020	128337
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	4/19/2019	Annual	4/19/2020	11401010036
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11403100002
Rohde & Schwarz	CMW500	Radio Communication Tester	N/A			100976
Rohde & Schwarz	CMW500	Radio Communication Tester	N/A			102060
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	6/5/2019	Annual	6/5/2020	100342
Seekonk	NC-100	Torque Wrench (8" lb)	5/10/2018	Biennial	5/10/2020	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	4/19/2018	Biennial	4/19/2020	A051107

Table 5-1. Test Equipment

Notes:

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 8 of 54	

6.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

- LTE BW = 8.62 MHz
- G = Phase Modulation
- 7 = Quantized/Digital Info
- D = Data transmission, telemetry, telecommand

16QAM Modulation

Emission Designator = 8M45W7D

- LTE BW = 8.45 MHz
- W = Amplitude/Angle Modulated
- 7 = Quantized/Digital Info
- D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm $- (-24.80)$.

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 9 of 54	

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMN976U
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): LTE
 Band: Band 26 / Band 14

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 90(S) 90(R)	Conducted Band Edge / Spurious Emissions	On all frequencies between 769-775 MHz and 799-805 MHz, attenuation by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations. On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, attenuation by at least $43 + 10 \log(P)$ dB.(Band 14) > $43 + 10 \log_{10}(P[\text{Watts}])$ for all out-of-band emissions except > $50 + 10 \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge (Band 26)		PASS	Sections 7.3, 7.4
2.1055 90.213	Frequency Stability	< 2.5 ppm		PASS	Section 7.8
2.1046 90.635	Conducted Power	< 100 Watts		PASS	Section 7.5
22.913(a.2)	Effective Radiated Power (Band 26)	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
90.542(a)(7)	Effective Radiated Power (Band 14)	< 3 Watts max. ERP		PASS	Section 7.6
2.1053 90(S) 90(R)	Radiated Spurious Emissions	> $43 + 10 \log_{10}(P[\text{Watts}])$ for all out-of-band emissions except > $50 + 10 \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge		PASS	Section 7.7

Table 7-1. Summary of Test Results

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 10 of 54	

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 4.2.

FCC ID: A3LSMN976U	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 11 of 54

7.2 Occupied Bandwidth

§2.1049

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 12 of 54




Plot 7-1. Occupied Bandwidth Plot (LTE Band 26, 1.4MHz QPSK – RB Size 6– Low Channel)




Plot 7-2. Occupied Bandwidth Plot (LTE Band 26, 1.4MHz 16-QAM – RB Size 6– Low Channel)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 13 of 54




Plot 7-3. Occupied Bandwidth Plot (LTE Band 26, 1.4MHz 64-QAM – RB Size 6– Low Channel)




Plot 7-4. Occupied Bandwidth Plot (LTE Band 26, 1.4MHz 256-QAM – RB Size 6– Low Channel)

FCC ID: A3LSMN976U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 14 of 54




Plot 7-5. Occupied Bandwidth Plot (LTE Band 26, 3MHz QPSK – RB Size 15– Low Channel)




Plot 7-6. Occupied Bandwidth Plot (LTE Band 26, 3MHz 16-QAM – RB Size 15– Low Channel)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 15 of 54




Plot 7-7. Occupied Bandwidth Plot (LTE Band 26, 3MHz 64-QAM – RB Size 15– Low Channel)




Plot 7-8. Occupied Bandwidth Plot (LTE Band 26, 3MHz 256-QAM – RB Size 15– Low Channel)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 16 of 54




Plot 7-9. Occupied Bandwidth Plot (LTE Band 26, 5MHz QPSK – RB Size 25– Low Channel)




Plot 7-10. Occupied Bandwidth Plot (LTE Band 26, 5MHz 16-QAM – RB Size 25– Low Channel)

FCC ID: A3LSMN976U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 17 of 54




Plot 7-11. Occupied Bandwidth Plot (LTE Band 26, 5MHz 64-QAM – RB Size 25– Low Channel)




Plot 7-12. Occupied Bandwidth Plot (LTE Band 26, 5MHz 256-QAM – RB Size 25– Low Channel)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 18 of 54




Plot 7-13. Occupied Bandwidth Plot (LTE Band 26, 10MHz QPSK – RB Size 50)




Plot 7-14. Occupied Bandwidth Plot (LTE Band 26, 10MHz 16-QAM – RB Size 50)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 19 of 54




Plot 7-15. Occupied Bandwidth Plot (LTE Band 26, 10MHz 64-QAM – RB Size 50)




Plot 7-16. Occupied Bandwidth Plot (LTE Band 26, 10MHz 256-QAM – RB Size 50)

FCC ID: A3LSMN976U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 20 of 54




Plot 7-17. Occupied Bandwidth Plot (LTE Band 26, 15MHz QPSK – RB Size 75)




Plot 7-18. Occupied Bandwidth Plot (LTE Band 26, 15MHz 16-QAM – RB Size 75)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 21 of 54




Plot 7-19. Occupied Bandwidth Plot (LTE Band 26, 15MHz 64-QAM – RB Size 75)




Plot 7-20. Occupied Bandwidth Plot (LTE Band 26, 15MHz 256-QAM – RB Size 75)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 22 of 54




Plot 7-21. Occupied Bandwidth Plot (LTE Band 14, 5MHz QPSK – RB Size 25)




Plot 7-22. Occupied Bandwidth Plot (LTE Band 14, 5MHz 16-QAM – RB Size 25)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 23 of 54



Plot 7-23. Occupied Bandwidth Plot (LTE Band 14, 5MHz 64-QAM – RB Size 25)




Plot 7-24. Occupied Bandwidth Plot (LTE Band 14, 5MHz 256-QAM – RB Size 25)

FCC ID: A3LSMN976U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 24 of 54




Plot 7-25. Occupied Bandwidth Plot (LTE Band 14, 10MHz QPSK – RB Size 50)




Plot 7-26. Occupied Bandwidth Plot (LTE Band 14, 10MHz 16-QAM – RB Size 50)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 25 of 54



Plot 7-27. Occupied Bandwidth Plot (LTE Band 14, 10MHz 64-QAM – RB Size 50)



Plot 7-28. Occupied Bandwidth Plot (LTE Band 14, 10MHz 256-QAM – RB Size 50)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 26 of 54

7.3 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §90(S) §90(R)

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz (separated into at least two plots per channel)
2. RBW \geq 100kHz
3. VBW \geq 3 x RBW
4. Detector = RMS
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup


Test Notes

Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 27 of 54




Plot 7-29. Conducted Spurious Plot (LTE Band 26, 10 MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)




Plot 7-30. Conducted Spurious Plot (LTE Band 26, 10 MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 28 of 54




Plot 7-31. Conducted Spurious Plot (LTE Band 26, 10 MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)




Plot 7-32. Conducted Spurious Plot (LTE Band 14, 10 MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 29 of 54



Plot 7-33. Conducted Spurious Plot (LTE Band 14, 10 MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)



Plot 7-34. Conducted Spurious Plot (LTE Band 14, 10 MHz QPSK – RB Size 1, RB Offset 0 – Mid Channel)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 30 of 54

7.4 Band Edge Emissions at Antenna Terminal

§2.1051 §90(S) §90(R)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

For LTE B26 operation under Part 90.691, the minimum permissible attenuation level of any spurious emission removed from the EA licensee’s frequency block by greater than 37.5 kHz is $43 + 10\log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts. The minimum permissible attenuation level of any spurious emission removed from the EA licensee’s frequency block by up to and including 37.5 kHz is $50 + 10\log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Span was set large enough so as to capture all out of band emissions near the band edge
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = RMS
5. Trace mode = trace average
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-3. Test Instrument & Measurement Setup

Test Notes


For channel edge emission, the signal analyzer’s “ACP” measurement capability is used.

Per 22.917(b) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 31 of 54




Plot 7-35. Channel Edge Plot (LTE Band 26, 1.4MHz QPSK – RB Size 6– Low Channel)




Plot 7-36. Channel Edge Plot (LTE Band 26, 1.4MHz QPSK – RB Size 6 – High Channel)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 32 of 54




Plot 7-37. Channel Edge Plot (LTE Band 26, 3MHz QPSK – RB Size 15– Low Channel)




Plot 7-38. Channel Edge Plot (LTE Band 26, 3MHz QPSK – RB Size 15 – High Channel)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 33 of 54




Plot 7-39. Channel Edge Plot (LTE Band 26, 5MHz QPSK – RB Size 25– Low Channel)




Plot 7-40. Channel Edge Plot (LTE Band 26, 5MHz QPSK – RB Size 25 – High Channel)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 34 of 54




Plot 7-41. Channel Edge Plot (LTE Band 26, 10MHz QPSK – RB Size 50)



Plot 7-42. Channel Edge Plot (LTE Band 26, 15MHz QPSK – RB Size 75)

FCC ID: A3LSMN976U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 35 of 54




Plot 7-43. Lower Band Edge Plot (LTE Band 14, 5MHz QPSK – RB Size 25)



Plot 7-44. Lower Emission Mask Plot (LTE Band 14, 5MHz QPSK – RB Size 25)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 36 of 54




Plot 7-45. Upper Band Edge Plot (LTE Band 14, 5MHz QPSK – RB Size 25)




Plot 7-46. Upper Emission Mask Plot (LTE Band 14, 5MHz QPSK – RB Size 25)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 37 of 54



Plot 7-47. Lower Band Edge Plot (LTE Band 14, 10MHz QPSK – RB Size 50)



Plot 7-48. Lower Emission Mask Plot (LTE Band 14, 10MHz QPSK – RB Size 50)

FCC ID: A3LSMN976U	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 38 of 54

7.5 Conducted Power Output Data

§2.1046 §90.635

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Cond. PWR [dBm]	Cond. PWR [Watts]	Cond. PWR Limit [dBm]	Margin [dB]
814.70	1.4	QPSK	25.24	0.334	50.00	-24.76
823.30	1.4	QPSK	24.70	0.295	50.00	-25.30
814.70	1.4	16-QAM	24.26	0.267	50.00	-25.74
823.30	1.4	16-QAM	23.99	0.251	50.00	-26.01
814.70	1.4	64-QAM	23.15	0.207	50.00	-26.85
823.30	1.4	64-QAM	23.09	0.204	50.00	-26.91
814.70	1.4	256-QAM	20.03	0.101	50.00	-29.97
823.30	1.4	256-QAM	20.12	0.103	50.00	-29.88
815.50	3	QPSK	25.01	0.317	50.00	-24.99
822.50	3	QPSK	24.71	0.296	50.00	-25.29
815.50	3	16-QAM	23.98	0.250	50.00	-26.02
822.50	3	16-QAM	24.10	0.257	50.00	-25.90
815.50	3	64-QAM	22.78	0.190	50.00	-27.22
822.50	3	64-QAM	22.85	0.193	50.00	-27.15
815.50	3	256-QAM	20.11	0.103	50.00	-29.89
822.50	3	256-QAM	20.09	0.102	50.00	-29.91
816.50	5	QPSK	25.00	0.316	50.00	-25.00
821.50	5	QPSK	24.85	0.305	50.00	-25.15
816.50	5	16-QAM	24.06	0.255	50.00	-25.94
821.50	5	16-QAM	24.11	0.258	50.00	-25.89
816.50	5	64-QAM	23.34	0.216	50.00	-26.66
821.50	5	64-QAM	23.07	0.203	50.00	-26.93
816.50	5	256-QAM	20.17	0.104	50.00	-29.83
821.50	5	256-QAM	20.02	0.100	50.00	-29.98
819.00	10	QPSK	24.75	0.299	50.00	-25.25
819.00	10	16-QAM	24.24	0.265	50.00	-25.76
819.00	10	64-QAM	22.91	0.195	50.00	-27.09
819.00	10	256-QAM	20.02	0.100	50.00	-29.98
821.50	15	QPSK	24.99	0.316	50.00	-25.01
821.50	15	16-QAM	24.29	0.269	50.00	-25.71
821.50	15	64-QAM	23.11	0.205	50.00	-26.89
821.50	15	256-QAM	20.01	0.100	50.00	-29.99

Table 7-2. LTE Band 26 Conducted Power Output Data

NOTES:

1. This unit was tested with its standard battery.

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 40 of 54	

7.6 Radiated Power (ERP)

§22.913(a.2) §90.542(a)(7)

Test Overview

Effective Radiated Power (ERP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17

Test Settings

The relevant equation for determining the ERP or EIRP from the conducted RF output power measured is:

$$ERP/EIRP = P_{Meas} - LC + GT$$

Where:

ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as P_{Meas}, typically dBW or dBm)

P_{Meas} = measured transmitter output power or PSD, in dBW or dBm

LC = signal attenuation in the connecting cable between the transmitter and antenna in dB

GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. ERP/EIRP Measurement Setup

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset		Page 41 of 54

Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
821.50	15	QPSK	V	100	265	1 / 0	12.27	6.30	16.42	0.044	38.45	-22.03
821.50	15	16-QAM	V	100	265	1 / 0	11.63	6.30	15.78	0.038	38.45	-22.67
821.50	15	64-QAM	V	100	265	1 / 0	10.36	6.30	14.51	0.028	38.45	-23.94
821.50	15	256-QAM	V	100	265	1 / 0	6.42	6.30	10.57	0.011	38.45	-27.88
821.50	15 (WCP)	QPSK	V	144	298	1 / 0	9.06	6.30	13.21	0.021	38.45	-25.24

Table 7-51. ERP Data (Band 26)

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
790.50	5	QPSK	V	206	301	1 / 0	14.06	5.80	17.71	0.059	34.77	-17.06	19.86	0.097	36.99	-17.13
793.00	5	QPSK	V	215	242	1 / 0	14.16	5.90	17.91	0.062	34.77	-16.86	20.06	0.101	36.99	-16.93
795.50	5	QPSK	V	187	254	1 / 0	13.54	5.95	17.34	0.054	34.77	-17.43	19.49	0.089	36.99	-17.50
793.00	5	16-QAM	V	215	242	1 / 0	13.24	5.90	16.99	0.050	34.77	-17.78	19.14	0.082	36.99	-17.85
793.00	5	64-QAM	V	215	242	1 / 0	12.29	5.90	16.04	0.040	34.77	-18.73	18.19	0.066	36.99	-18.80
793.00	5	256-QAM	V	215	242	1 / 0	12.74	5.90	12.74	0.019	34.77	-22.03	14.89	0.031	36.99	-22.10
793.00	10	QPSK	V	197	264	1 / 0	13.68	5.90	17.43	0.055	34.77	-17.34	19.58	0.091	36.99	-17.41
793.00	10	16-QAM	V	197	264	1 / 0	13.31	5.90	17.06	0.051	34.77	-17.71	19.21	0.083	36.99	-17.78
793.00	10	64-QAM	V	197	264	1 / 0	12.19	5.90	15.94	0.039	34.77	-18.83	18.09	0.064	36.99	-18.90
793.00	10	256-QAM	V	197	264	1 / 0	7.56	5.90	11.31	0.014	34.77	-23.46	13.46	0.022	36.99	-23.53
793.00	5	QPSK	H	133	290	1 / 0	12.66	5.80	16.31	0.043	34.77	-18.46	18.46	0.070	36.99	-18.53
793.00	5 (WCP)	QPSK	V	366	289	1 / 0	9.98	5.80	13.63	0.023	34.77	-21.14	15.78	0.038	36.99	-21.21

Table 7-52. ERP Data (Band 14)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 42 of 54	

7.7 Radiated Spurious Emissions Measurements

§2.1053 §90(S) §90(R)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8

ANSI/TIA-603-E-2016 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW \geq 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points \geq 2 x span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: A3LSMN976U	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 43 of 54

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-5. Test Instrument & Measurement Setup

Test Notes

1. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
4. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
5. Per 90(R)(f), emissions in the 1559 – 1610MHz band are subject to a limit of -40dBm/MHz for wideband signals. These emission measurements are shown in this section below.

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 44 of 54	



Plot 7-53. Radiated Spurious Plot above 1GHz (Band 26)

OPERATING FREQUENCY: 816.50 MHz
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: -13.00 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1633.00	H	154	9	-69.56	8.85	-60.71	-47.7
2449.50	H	147	21	-67.98	9.55	-58.43	-45.4
3266.00	H	-	-	-69.42	9.54	-59.88	-46.9
4082.50	H	-	-	-71.66	10.05	-61.61	-48.6

Table 7-3. Radiated Spurious Data (LTE Band 26 – Low Channel)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset			Page 45 of 54

OPERATING FREQUENCY: 821.50 MHz

MODULATION SIGNAL: QPSK

BANDWIDTH: 5.0 MHz

DISTANCE: 3 meters

LIMIT: -13.00 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1643.00	H	143	357	-70.91	8.91	-62.00	-49.0
2464.50	H	154	360	-66.92	9.61	-57.31	-44.3
3286.00	H	-	-	-69.81	9.56	-60.25	-47.2
4107.50	H	-	-	-72.51	10.14	-62.37	-49.4

Table 7-4. Radiated Spurious Data (LTE Band 26 – High Channel)

OPERATING FREQUENCY: 821.50 MHz

MODULATION SIGNAL: QPSK

BANDWIDTH: 5.0 MHz


DISTANCE: 3 meters

LIMIT: -13.00 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1643.00	H	146	351	-71.66	8.91	-62.75	-49.8
2464.50	H	160	5	-67.14	9.61	-57.53	-44.5
3286.00	H	-	-	-69.78	9.56	-60.22	-47.2
4107.50	H	-	-	-73.22	10.14	-63.08	-50.1

Table 7-5. Radiated Spurious Data with WCP (LTE Band 26 – High Channel)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 46 of 54	



Plot 7-54. Radiated Spurious Plot above 1GHz (Band 14)

OPERATING FREQUENCY: 793.00 MHz
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
2379.00	H	335	8	-69.14	9.40	-59.74	-46.7
3172.00	H	-	-	-69.62	9.34	-60.28	-47.3
3965.00	H	-	-	-71.31	9.51	-61.80	-48.8

Table 7-6. Radiated Spurious Data (LTE Band 14 – Mid Channel)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset			Page 47 of 54

MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.00 MHz
 DISTANCE: 3 meters
 NARROWBAND EMISSION LIMIT: -50 dBm
 WIDEBAND EMISSION LIMIT: -40 dBm/MHz

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1586.00	H	171	5	-71.75	8.59	-63.15	-23.2

Table 7-7. Radiated Spurious Data (LTE Band 14 – Wide Band)

OPERATING FREQUENCY: 793.00 MHz
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
2379.00	H	346	12	-69.82	9.40	-60.42	-47.4
3172.00	H	-	-	-70.04	9.34	-60.70	-47.7
3965.00	H	-	-	-71.51	9.51	-62.00	-49.0

Table 7-8. Radiated Spurious Data with WCP (LTE Band 14 – Mid Channel)

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 48 of 54	

7.8 Frequency Stability / Temperature Variation

§2.1055 §90.213

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency.

Test Procedure Used

ANSI/TIA-603-E-2016

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 49 of 54	

Frequency Stability / Temperature Variation
§2.1055, §90.213

OPERATING FREQUENCY: 819,000,000 Hz
 CHANNEL: 26740
 REFERENCE VOLTAGE: 4.10 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %		- 30	818,999,997	-3	-0.0000004
100 %		- 20	819,000,051	51	0.0000062
100 %		- 10	818,999,942	-58	-0.0000071
100 %		0	818,999,891	-109	-0.0000133
100 %		+ 10	818,999,675	-325	-0.0000397
100 %		+ 20	818,999,701	-299	-0.0000365
100 %		+ 30	819,000,152	152	0.0000186
100 %		+ 40	819,000,006	6	0.0000007
100 %		+ 50	819,000,151	151	0.0000184
BATT. ENDPOINT		3.42	+ 20	819,000,092	92

Table 7-9. LTE Band 26 Frequency Stability Data

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 50 of 54	

Frequency Stability / Temperature Variation
\$2.1055, \$90.213





Table 7-10. LTE Band 26 Frequency Stability Data

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 51 of 54	

Frequency Stability / Temperature Variation
§2.1055, §90.213

OPERATING FREQUENCY: 793,000,000 Hz
 CHANNEL: 23330
 REFERENCE VOLTAGE: 4.10 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.10	- 30	792,999,962	-38	-0.0000048
100 %		- 20	793,000,075	75	0.0000095
100 %		- 10	793,000,097	97	0.0000122
100 %		0	792,999,882	-118	-0.0000149
100 %		+ 10	792,999,620	-380	-0.0000479
100 %		+ 20	792,999,720	-280	-0.0000353
100 %		+ 30	792,999,969	-31	-0.0000039
100 %		+ 40	793,000,318	318	0.0000401
100 %		+ 50	793,000,027	27	0.0000034
BATT. ENDPOINT		3.42	+ 20	793,000,062	62

Table 7-11. LTE Band 14 Frequency Stability Data

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 52 of 54	

Frequency Stability / Temperature Variation
\$2.1055, \$90.213




Table 7-12. LTE Band 14 Frequency Stability Data

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 53 of 54	

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMN976U** complies with all the requirements of Parts 22(H) and 90 of the FCC rules.

FCC ID: A3LSMN976U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1909040147-04.A3L	Test Dates: 9/09 - 10/23/2019	EUT Type: Portable Handset	Page 54 of 54	