

FCC ID:	A3LSMN976V	
Date:	07/02/2019	
Test Procedure:	KDB 680106 D01 v03	

E Measurements (V/m)	10% Battery		50% Battery		70% Battery		Limit (V/m)	
	Distance from probe (cm)		Distance from probe (cm)		Distance from probe (cm)			
	15	20	15	20	15	20		
A (Bottom)	0.245	0.172	0.218	0.154	0.228	0.154	614.00	
B (Right)	0.327	0.172	0.289	0.162	0.312	0.218	614.00	
C (Top)	0.266	0.230	0.245	0.172	0.227	0.172	614.00	
D (Left)	0.321	0.172	0.296	0.182	0.307	0.201	614.00	
E (Front)	0.608	0.378	0.608	0.369	0.655	0.396	614.00	
F (Back)	0.618	0.384	0.632	0.370	0.679	0.411	614.00	

Table 1. E-field Measurement by distance/battery level (D2D)

H Measurements (A/m)	10% Battery		50% Battery		70% Battery		Limit (A/m)	
	Distance from probe (cm)		Distance from probe (cm)		Distance from probe (cm)			
	15	20	15	20	15	20		
A (Bottom)	0.006	0.006	0.006	0.005	0.006	0.005	1.63	
B (Right)	0.007	0.005	0.007	0.006	0.007	0.006	1.63	
C (Top)	0.005	0.006	0.005	0.005	0.006	0.005	1.63	
D (Left)	0.010	0.006	0.007	0.005	0.007	0.005	1.63	
E (Front)	0.007	0.006	0.006	0.005	0.007	0.005	1.63	
F (Back)	0.007	0.006	0.007	0.006	0.006	0.005	1.63	

Table 2. H-field Measurement by distance/battery level (D2D)

Frequency [MHz]	Probe Orientation (X, Y, Z)	Distance (cm)	Operational Correction Factor	Corrected H-field (A/m)						Limit [A/m]	
				EUT Sides							
				A	B	C	D	E	F		
0.594	X	15.0	0.233	0.001307	0.001307	0.001423	0.001307	0.001307	0.001703	1.63	
0.594	X	5.0	0.233	0.002777	0.009683	0.004970	0.002893	0.005647	0.016777	1.63	
0.594	X	4.0	0.233						0.026717	1.63	
0.594	X	3.0	0.233						0.033437	1.63	
0.594	X	2.0	0.233						0.057447	1.63	
0.594	X	1.0	0.233						0.104673	1.63	
0.594	X	0.0	0.233						0.136103	1.63	

Table 3. H-field Measurement by distance (D2P)

Frequency [MHz]	Probe Orientation (X, Y, Z)	Distance (cm)	Operational Correction Factor	Corrected H-field (A/m)	Limit [A/m]
				EUT Sides	
				F	
0.594	X	5.0	0.233	0.016777	1.63
0.594	Y	5.0	0.233	0.015276	1.63
0.594	Z	5.0	0.233	0.016368	1.63

Table 3. H-field Isotropy Measurement (D2P)

A	B	C	D	E	F
BOTTOM EDGE	RIGHT EDGE	TOP EDGE	LEFT EDGE	FRONT (SCREEN)	Back

Table 4. EUT Position Description

Note:

The right and left edge are determined with the EUT screen facing the user.

Corrected H-Field measurement

- $0.5833 \text{ A/m} * 0.233 = 0.136103 \text{ A/m}$

Operational Correction Factor

The EUT charges for 7 minutes at maximum illumination to full charge. It recharges at maximum illumination when 10% or more of the battery level drop is detected. Therefore the operational correction factor is:

Correction Factor (applied over 30 minutes) = $7/30 = 0.233$.

Description of Test Setup

- Testing was performed with a calibrated field probe.
- Measurement was performed on each side of the EUT as described per Table 4.
- Testing was performed at the distances and different battery level as indicated on Table 1 and Table 2.
- Measurement procedure was performed per FCC Guidance.

Test Equipment

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Narda	EHP-200AC	Electric & Magnetic Field Probe	8/31/2018	Annual	8/31/2019	170WX60209

Conclusion: The theoretical H-field value based on approximations of the dimensions to a simple solenoid via Biot-Savart Law show good correlation for H-field and shows low H-field. Therefore per FCC discussion, SAR testing is excluded for this transmitter