

## EMI TEST REPORT FCC CERTIFICATION

**Applicant:**

**SAMSUNG Electronics Co., Ltd.**  
**129, Samsung-ro, Yeongtong-gu, Suwon-si,**  
**Gyeonggi-do, 16677, Korea**

**Date of Issue: June 30, 2020**

**Test Report No. HCT-EM-2006-FC019**

**Test Site: HCT CO., LTD.**

**FCC ID :**

**A3LSMN980F**

Rule Part(s) / Standard(s) : 47 CFR PART 15 Subpart B Class B  
ANSI C63.4-2014

Product Name : Mobile Phone

Model Name : SM-N980F/DS

Series Model Name : SM-N980F

Date of Test : June 23, 2020 to June 24, 2020

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

**Tested By**



**Ki-Min Lee**  
**Test Engineer**  
**EMC Team**  
**Certification Division**

**Reviewed**



**Jeong-Hyun Choi**  
**Technical Manager**  
**EMC Team**  
**Certification Division**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



## REVISION HISTORY

*The revision history for this document is shown in table.*

Report No.	Issue Date	Information About Changes
0	June 30, 2020	Initial Release

This Test Report is not related to the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS (Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA.

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



## TABLE OF CONTENTS

	<b>PAGE</b>
1. GENERAL INFORMATION .....	4
1.1 Description of EUT .....	4
1.2 Tested System Details .....	4
1.3 Cable Description.....	5
1.4 Noise Suppression Parts on Cable. (I/O Cable) .....	5
1.5 Test Facility .....	6
1.6 Calibration of Measuring Instrument .....	6
1.7 Measurement Uncertainty .....	6
2. LIST OF TEST EQUIPMENT .....	7
3. DESCRIPTION OF TEST.....	8
3.1 Measurement of Conducted Emission.....	8
3.2 Measurement of Radiated Emission.....	9
4. PRELIMINARY TEST.....	11
4.1 Conducted Emission.....	11
4.2 Rediated Emission.....	11
5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY.....	12
5.1 Conducted Emission.....	12
5.2 Radiated Emission.....	13
6. CONCLUSION .....	19
7. APPENDIX A. TEST SETUP PHOTO .....	22



## 1. GENERAL INFORMATION

### 1.1 Description of EUT

FCC ID	A3LSMN980F
Model Name	SM-N980F/DS
Series mode name	SM-N980F
Product Name	Mobile Phone
Frequency Band	GSM 850/1900, WCDMA B2/4/5, LTE B2/4/5/12/13/17/25/26/41/66, BT BDR/EDR/LE 5.0, WLAN a/b/g/n/ac/ax, NFC, MST, WPT
Power Supply	Travel adaptor: Input: AC (100 to 240) V, (50 to 60) Hz, 0.5 A Output: DC 5.0 V, 2.0 A or DC 9.0 V, 1.67 A

### 1.2 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Serial Number	Manufacturer
EUT	SM-N980F/DS	-	SAMSUNG
TA	EP-TA800	-	SOLUM
Data Cable	EP-DN980BBE	-	RFTECH
Earphone	YBD-19HS-026	-	ALMUS
Micro SD Card	-	-	SAMSUNG



### 1.3 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	USB Type C	Y	Y	(P,D) 1.0
	Earphone (Type C)	N/A	N	(D) 1.3

\* The marked "(D)" means the data cable and "(P)" means the power cable.

### 1.4 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	USB Type C	N	N/A	Y	Both End
	Earphone (Type C)	N	N/A	Y	EUT End



## 1.5 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014. The Normalized site attenuations (30 MHz to 1 GHz) and Site validation (1 GHz to 18 GHz) were performed in accordance with the standard in ANSI C63.4-2014

Measurement Facilities	Registration Number
Radiated Field strength measurement facility 3 m Semi Anechoic chamber	KR0032
Radiated Field strength measurement facility 10 m Semi Anechoic chamber #1	
Radiated Field strength measurement facility 10 m Semi Anechoic chamber #2	

## 1.6 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5:2017

## 1.7 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014.

All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Emission (0.15 MHz to 30 MHz)	1.8 dB
Radiated Emissions (30 MHz to 1 GHz)	4.8 dB
Radiated Emissions (1 GHz to 18 GHz)	5.4 dB
Radiated Emissions (18 GHz to 40 GHz)	5.7 dB



## 2. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Model Name</u>	<u>Manufacturer</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>Calibration Date</u>
<b>Conducted Emission (Not applicable)</b>					
<input type="checkbox"/> EMI Test Receiver	ESCI	Rohde & Schwarz	100584	1 year	06.10.2020
<input type="checkbox"/> LISN	ENV216	Rohde & Schwarz	102245	1 year	09.11.2019
<input type="checkbox"/> LISN	ENV216	Rohde & Schwarz	100073	1 year	04.27.2020
<input type="checkbox"/> Radio communication analyzer	MT8820C	ANRITSU	6201138643	1 year	08.20.2019
<input type="checkbox"/> Antenna (for Communication)	USLP9142	Schwarzbeck	VSLP 9142-200	-	-
<input type="checkbox"/> Software	EMC32	Rohde & Schwarz	-	-	-
<b>Radiated Emission</b>					
<b>-For measurement below 1 GHz</b>					
<input checked="" type="checkbox"/> EMI Test Receiver	ESU40	Rohde & Schwarz	100524	1 year	05.12.2020
<input checked="" type="checkbox"/> Bi-Log Antenna	VULB 9168	Schwarzbeck	255	2 year	03.26.2019
<input checked="" type="checkbox"/> Antenna master	MA4640-XP-ET	INNCO Systems	-	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	CO3000	INNCO Systems	CO3000/870/ 35990515/L	N/A	-
<input checked="" type="checkbox"/> Turn Table	1060	INNCO Systems	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	CO2000	INNCO Systems	CO2000/095/ 7590304/L	N/A	-
<input checked="" type="checkbox"/> Radio communication analyzer	MT8820C	ANRITSU	6201138643	1 year	08.20.2019
<input checked="" type="checkbox"/> Antenna (for Communication)	USLP9142	Schwarzbeck	VSLP 9142-200	-	-
<input type="checkbox"/> UXM 5G Wireless Test Platform	E7515B	KEYSIGHT	MY58300756	1 year	01.07.2020
<input type="checkbox"/> Antenna (for Communication)	USLP9142	Schwarzbeck	VSLP 9142-201	-	-
<input checked="" type="checkbox"/> Software	EMC32	Rohde & Schwarz	-	-	-
<b>-For measurement above 1 GHz</b>					
<input checked="" type="checkbox"/> EMI Test Receiver	ESU40	Rohde & Schwarz	100524	1 year	05.12.2020
<input checked="" type="checkbox"/> Antenna master	MA4640-XP-ET	INNCO Systems	-	N/A	-
<input checked="" type="checkbox"/> Antenna master controller	CO3000	INNCO Systems	CO3000/870/ 35990515/L	N/A	-
<input checked="" type="checkbox"/> Turn Table	1060	INNCO Systems	-	N/A	-
<input checked="" type="checkbox"/> Turn Table controller	CO2000	INNCO Systems	CO2000/095/ 7590304/L	N/A	-
<input checked="" type="checkbox"/> Horn Antenna	BBHA 9120D	Schwarzbeck	01836	1 year	07.19.2019
<input checked="" type="checkbox"/> Low Noise Amplifier	TK-PA18H	TESTEK	170034-L	1 year	03.03.2020
<input checked="" type="checkbox"/> Low Noise Amplifier	TK-PA1840H	TESTEK	170030-L	1 year	02.13.2020
<input checked="" type="checkbox"/> Horn Antenna	BBHA 9170	Schwarzbeck	BBHA 9170#786	1 year	12.03.2019
<input checked="" type="checkbox"/> Radio communication analyzer	MT8820C	ANRITSU	6201138643	1 year	08.20.2019
<input checked="" type="checkbox"/> Antenna (for Communication)	USLP9142	Schwarzbeck	VSLP 9142-200	-	-
<input type="checkbox"/> UXM 5G Wireless Test Platform	E7515B	KEYSIGHT	MY58300756	1 year	01.07.2020
<input type="checkbox"/> Antenna (for Communication)	USLP9142	Schwarzbeck	VSLP 9142-201	-	-
<input checked="" type="checkbox"/> Software	EMC32	Rohde & Schwarz	-	-	-



### 3. DESCRIPTION OF TEST

#### 3.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).  
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).  
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

#### [ Conducted Emission Limits ]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

*\*Decreases with the logarithm of the frequency.*





### 3.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- g. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.(1 GHz to 40 GHz)

#### [ Radiated Emission Limits ]

Frequency (MHz)	Antenna Distance (m)	Field Strength ( $\mu\text{V}/\text{m}$ )	Quasi-Peak (dB( $\mu\text{V}/\text{m}$ ))
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak (dB( $\mu\text{V}/\text{m}$ ))	Average (dB( $\mu\text{V}/\text{m}$ ))
Above 1 000	3	74	54




### 3.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower

### 3.3 Configuration of Tested System





## 4. PRELIMINARY TEST

During preliminary tests, the following operating mode was investigated.

Receiver mode(GSM 850 Low/Middle/High CH Idle)  
 Receiver mode(WCDMA B5 Low/Middle/High CH Idle)  
 Receiver mode(LTE B5 Low/Middle/High CH Idle)  
 Receiver mode(LTE B26 Low/Middle/High CH Idle)  
 Receiver mode(LTE B12 Low/Middle/High CH Idle)  
 Receiver mode(LTE B13 Low/Middle/High CH Idle)  
 Receiver mode(LTE B17 Low/Middle/High CH Idle)

NOTE. The worst band is tested.

### 4.1 Conducted Emission (Not applicable)

It was tested the following operating mode, after connecting all peripheral devices.

**Operating Mode:** Not Applicable

NOTE.

Compliance with Part 15B requirement for the conducted emissions is covered by SAMSUNG test report.

### 4.2 Radiated Emission

It was tested the following operating mode, after connecting all peripheral devices.

**Operating Mode:**

#### For Blow 1 GHz

**[EUT + Travel adaptor]**  
 LTE B26+B5 Low CH Idle  
 LTE B26+B5 Middle CH Idle\*  
 LTE B26+B5 High CH Idle  
 LTE B12+B13+B17 Low CH Idle  
 LTE B12+B13+B17 Middle CH Idle  
 LTE B12+B13+B17 High CH Idle

**[EUT + Earphone]**  
 LTE B26+B5 Middle CH Idle\*

#### For Above 1 GHz

**[EUT + Travel adaptor]**  
 LTE B26+B5 Middle CH Idle\*

**[EUT + Earphone]**  
 LTE B26+B5 Middle CH Idle\*

NOTE.

1. Three orientations have been investigated and the worst case orientation (x-axis: The display of EUT placed on the table is facing upwards) is reported.
2. The worst case of operating mode is reported. [\*].



## 5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

### 5.1 Conducted Emission(Not applicable)

The test results of conducted emission at mains ports provide the following information:

Rule Part / Standard	47 CFR PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operating Mode	Not applicable
Kind of Test Site	Shielded Room
Temperature	- °C
Relative Humidity	- %
Test Date	-



## 5.2 Radiated Emission

### 5.2.1 For Measurement Below 1 GHz

The test results of radiated emission provide the following information:

Applicable Standards	47 CFR PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Worst Case of Operating Mode	LTE B26+B5 Middle CH Idle
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.5 °C
Relative Humidity	44.8 %
Test Date	June 23, 2020


**- Calculation Formula:**

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



Figure 1: Radiated Emission (30 MHz to 1 GHz), [EUT + Travel adaptor] LTE B26+B5 Middle CH Idle

FCC PART 15 CLASS B




- NOTE. 1. Carrier Frequency: RX 874.967 MHz  
 2. These are signals for fundamental frequency from the base station

Frequency (MHz)	Quasi Peak (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
30.318236	19.2	100.0	V	0.0	18.3	20.8	40.0
43.155200	21.0	225.2	V	308.0	19.2	19.0	40.0
60.300400	27.5	116.7	V	279.0	19.3	12.5	40.0
114.576600	21.2	225.3	V	126.0	16.8	22.3	43.5
166.321600	22.9	100.0	V	213.0	19.4	20.6	43.5
313.939800	23.0	100.0	H	220.0	20.8	23.0	46.0



Figure 2: Radiated Emission (30 MHz to 1 GHz), [EUT + Earphone] LTE B26+B5 Middle CH Idle



- NOTE. 1. Carrier Frequency: RX 876.616 MHz  
 2. These are signals for fundamental frequency from the base station

Frequency (MHz)	Quasi Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
30.455450	19.3	225.3	V	60.0	18.3	20.7	40.0
49.908600	19.8	174.9	V	100.0	19.8	20.2	40.0
114.557800	21.1	225.0	V	205.0	16.8	22.4	43.5
155.397800	19.9	100.0	V	117.0	19.6	23.6	43.5
377.353800	21.1	100.0	H	280.0	22.3	24.9	46.0
460.766400	23.1	100.0	V	137.0	24.3	22.9	46.0



## 5.2.2 For Measurement Above 1 GHz

The test results of radiated emission provide the following information:

Applicable Standards	47 CFR PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Frequency	5 825 MHz
Tested Frequency Range	1 GHz to 30 GHz
Worst Case of Operating Mode	LTE B26+B5 Middle CH Idle
Kind of Test Site	3 m semi anechoic chamber
Temperature	22.7 °C
Relative Humidity	42.9 %
Test Date	June 24, 2020

### - Calculation Formula:


1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage






Figure 3: Radiated Emission (1 GHz to 30 GHz), [EUT + Travel adaptor] LTE B26+B5 Middle CH Idle

Tilting of GHz FCC PART 15 CLASS B



Tilting of GHz FCC PART 15 CLASS B\_18~40GHz






Frequency (MHz)	Peak (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
1753.130000	36.6	190.4	H	283.0	-27.2	37.4	74.0
2409.220000	32.5	289.7	H	0.0	-24.6	41.5	74.0
2496.770000	32.1	137.6	H	242.0	-24.1	41.9	74.0
9193.965000	42.3	162.5	V	300.0	-10.5	31.7	74.0
14199.645000	46.6	100.0	V	282.0	-1.8	27.4	74.0
17998.606220	55.4	189.6	H	330.0	9.6	18.6	74.0

Frequency (MHz)	CAverage (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
1753.130000	19.9	190.4	H	283.0	-27.2	34.1	54.0
2409.220000	19.4	289.7	H	0.0	-24.6	34.6	54.0
2496.770000	19.4	137.6	H	242.0	-24.1	34.6	54.0
9193.965000	29.8	162.5	V	300.0	-10.5	24.2	54.0
14199.645000	33.7	100.0	V	282.0	-1.8	20.3	54.0
17998.606220	42.8	189.6	H	330.0	9.6	11.2	54.0




Figure 4: Radiated Emission (1 GHz to 30 GHz), [EUT + Earphone] LTE B26+B5 Middle CH Idle

Tilting of GHz FCC PART 15 CLASS B



Tilting of GHz FCC PART 15 CLASS B\_18~40GHz





Frequency (MHz)	Peak (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
1754.355000	36.9	188.6	H	21.0	-27.2	37.1	74.0
4250.215000	34.8	113.4	V	146.0	-19.8	39.2	74.0
6256.660000	37.5	299.6	V	102.0	-15.6	36.5	74.0
9061.570000	42.2	150.0	V	211.0	-10.7	31.8	74.0
14140.465000	47.2	292.4	V	268.0	-1.9	26.8	74.0
17970.416490	55.0	139.6	V	0.0	9.2	19.0	74.0

Frequency (MHz)	CAverage (dB $\mu$ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
1754.355000	19.4	188.6	H	21.0	-27.2	34.6	54.0
4250.215000	22.0	113.4	V	146.0	-19.8	32.0	54.0
6256.660000	24.7	299.6	V	102.0	-15.6	29.3	54.0
9061.570000	29.3	150.0	V	211.0	-10.7	24.7	54.0
14140.465000	34.1	292.4	V	268.0	-1.9	19.9	54.0
17970.416490	42.6	139.6	V	0.0	9.2	11.4	54.0



## 6. CONCLUSION

The data collected shows that the **Product Name: Mobile Phone and Model Name: SM-N980F/DS** complies with §15.107 and §15.109 of the FCC rules.



## 7. APPENDIX A. TEST SETUP PHOTO

Please refer to EMI Test Setup Photo and test setup photo file no. as follows;

Rev. No.	Issue Date	File No.
0	June 30, 2020	HCT-EM-2006-FC019-P

End of report