

FCC LTE REPORT

Certification

Applicant Name: SAMSUNG Electronics Co., Ltd.	Date of Issue: July 09, 2020
Address: 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea	Location: HCT CO., LTD., 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA
Report No.: HCT-RF-2006-FC076-R1	

FCC ID:	A3LSMN980F
APPLICANT:	SAMSUNG Electronics Co., Ltd.
According to the Evaluation report, all of the data contained herein is reused from the reference FCC ID : A3LSMN981B report.	

Model(s): SM-N980F/DS
 Additional Model(s): SM-N980F
 EUT Type: Mobile Phone
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 FCC Rule Part(s): §27, §2

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band66/4 (1.4)	1710.7 – 1779.3	1M10G7D	QPSK	0.165	22.18
		1M10W7D	16QAM	0.140	21.46
		1M10W7D	64QAM	0.102	20.09
		1M10W7D	256QAM	0.050	16.98
LTE – Band66/4 (3)	1711.5 – 1778.5	2M72G7D	QPSK	0.167	22.22
		2M72W7D	16QAM	0.142	21.51
		2M71W7D	64QAM	0.100	20.01
		2M71W7D	256QAM	0.049	16.87
LTE – Band66/4 (5)	1712.5 – 1777.5	4M52G7D	QPSK	0.168	22.24
		4M56W7D	16QAM	0.143	21.55
		4M52W7D	64QAM	0.106	20.23
		4M53W7D	256QAM	0.051	17.04
LTE – Band66/4 (10)	1715.0 – 1775.0	9M03G7D	QPSK	0.168	22.25
		9M01W7D	16QAM	0.142	21.52
		8M99W7D	64QAM	0.104	20.16
		8M99W7D	256QAM	0.050	16.99
LTE – Band66/4 (15)	1717.5 – 1772.5	13M5G7D	QPSK	0.171	22.33
		13M5W7D	16QAM	0.145	21.61
		13M5W7D	64QAM	0.101	20.03
		13M5W7D	256QAM	0.049	16.87
LTE – Band66/4 (20)	1720.0 – 1770.0	18M0G7D	QPSK	0.171	22.32
		18M0W7D	16QAM	0.144	21.58
		18M0W7D	64QAM	0.103	20.14
		18M0W7D	256QAM	0.051	17.07

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)

Report No.: HCT-RF-2006-FC076-R1

REVIEWED BY



Report prepared by : Se Wook Park
Engineer of Telecommunication Testing Center

Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked *.

The above Test Report is the accredited test result by KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2006-FC076	July 03, 2020	- First Approval Report
HCT-RF-2006-FC076-R1	July 09, 2020	- Added the Calibration date on page 20 - Added the WPS on page 6

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

Table of Contents

REVIEWED BY	2
1. GENERAL INFORMATION	5
2. INTRODUCTION	6
2.1. DESCRIPTION OF EUT.....	6
2.2. MEASURING INSTRUMENT CALIBRATION	6
2.3. TEST FACILITY	6
3. DESCRIPTION OF TESTS.....	7
3.1 TEST PROCEDURE	7
3.2 RADIATED POWER.....	8
3.3 RADIATED SPURIOUS EMISSIONS	9
3.4 PEAK- TO- AVERAGE RATIO.....	10
3.5 OCCUPIED BANDWIDTH.	12
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	13
3.7 BAND EDGE	14
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	16
3.9 WORST CASE(RADIATED TEST)	17
3.10 WORST CASE(CONDUCTED TEST)	18
4. LIST OF TEST EQUIPMENT	19
5. MEASUREMENT UNCERTAINTY	21
6. SUMMARY OF TEST RESULTS	22
7. SAMPLE CALCULATION	23
8. TEST DATA	25
8.1 EQUIVALENT ISOTROPIC RADIATED POWER.....	25
8.2 RADIATED SPURIOUS EMISSIONS	28
8.3 PEAK-TO-AVERAGE RATIO.....	34
8.4 OCCUPIED BANDWIDTH	35
8.5 CONDUCTED SPURIOUS EMISSIONS	36
8.6 BAND EDGE	37
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	38
9. TEST PLOTS.....	56
10. ANNEX A_ TEST SETUP PHOTO.....	177

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMN980F
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s):	§27, §2
EUT Type:	Mobile Phone
Model(s):	SM-N980F/DS
Additional Model(s):	SM-N980F
Tx Frequency:	1710.7 MHz – 1779.3 MHz (LTE – Band 66/4 (1.4 MHz)) 1711.5 MHz – 1778.5 MHz (LTE – Band 66/4 (3 MHz)) 1712.5 MHz – 1777.5 MHz (LTE – Band 66/4 (5 MHz)) 1715.0 MHz – 1775.0 MHz (LTE – Band 66/4 (10 MHz)) 1717.5 MHz – 1772.5 MHz (LTE – Band 66/4 (15 MHz)) 1720.0 MHz – 1770.0 MHz (LTE – Band 66/4 (20 MHz))
Date(s) of Tests:	May 07, 2020 ~ June 23, 2020

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS and LTE.

It also supports IEEE 802.11 a/b/g/n/ac/ax (HT20/40/80), Bluetooth, BT LE, NFC, WPS.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4 - ANSI C63.26-2015 – Section 5.2.6(only GSM)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $> 2 \times$ span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(dBm)} = P_{g(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference

between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $> 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated. The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_{g(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundamatal frequency is below 1GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - for continuous transmissions, set to 1 ms,
 - or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1%.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R_{(dB)} = P_{Pk (dBm)} - P_{Avg (dBm)} \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)


The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.

1. Set the RBW \geq OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times$ (number of points in sweep) \times (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW \geq OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:
Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep (automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6$ dB if the duty cycle is a constant 25%.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic.


All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW \geq 3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time = auto
6. Number of points in sweep \geq 2 x Span / RBW

3.7 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1% of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span}/\text{RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize


Test Notes

According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels(low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30°C to $+50^{\circ}\text{C}$ in 10°C increments using an environmental chamber.

2. Primary Supply Voltage:

.- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.

.- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature

(20°C to provide a reference).

2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter.

Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.

3. Frequency measurements are made at 10°C intervals ranging from -30°C to $+50^{\circ}\text{C}$. A period of at

least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
- The worst case is reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data.
- Please refer to the table below.
- LTE Band 66 (1710 – 1780 MHz) overlaps the entire frequency range of LTE Band 4 (1710 - 1755 MHz) and they have the same Tune-up power.

Therefore, test data provided in this report covers Band 4 as well as Band 66.

-SM-N980F/DS & additional models were tested and the worst case results are reported.

(Worst case : SM-N980F/DS)

[Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	1	0	Z
Radiated Spurious and Harmonic Emissions	QPSK	1	0	Z

3.10 WORST CASE(CONDUCTED TEST)

- Worst case : Of all modulation, We have tested modulation of the high Conducted Output Power.

Conducted Output Power value can be confirmed on the SAR report.

- LTE Band 66 (1710 – 1780 MHz) overlaps the entire frequency range of LTE Band 4 (1710 - 1755 MHz) and they have the same Tune-up power.

Therefore, test data provided in this report covers Band 4 as well as Band 66.

-SM-N980F/DS & additional models were tested and the worst case results are reported.

(Worst case : SM-N980F/DS)

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM, 256QAM	1.4, 3, 5, 10, 15, 20	Mid	Full RB	0
Peak-To-Average Ratio	QPSK, 16QAM, 64QAM, 256QAM	1.4, 3, 5, 10, 15, 20	Mid	Full RB	0
Band Edge	QPSK	1.4	Low	1	0
			High	1	5
		3	Low	1	0
			High	1	14
		5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		15	Low	1	0
			High	1	74
		20	Low	1	0
			High	1	99
1.4, 3, 5, 10, 15, 20	Low, High	Full RB	0		
		0			
Spurious and Harmonic Emissions at Antenna Terminal	QPSK	1.4, 3, 5, 10, 15, 20	Low, Mid, High	1	0

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibrati on Interval	Calibration Due
T&M SYSTEM	FBSR-02B(WHK1.2/15G-10EF)/H.P.F	-	03/09/2020	Annual	03/09/2021
T&M SYSTEM	FBSR-02B(WHK3.3/18G-10EF)/H.P.F	-	03/09/2020	Annual	03/09/2021
WAINWRIGHT INSTRUMENT	WHNX6.0/26.5G-6SS/H.P.F	1	03/19/2020	Annual	03/19/2021
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	11275	04/27/2020	Annual	04/27/2021
Agilent	E3632A/DC Power Supply	MY40004326	07/01/2019	Annual	07/01/2020
Schwarzbeck	UHAP/ Dipole Antenna	557	03/29/2019	Biennial	03/29/2021
Schwarzbeck	UHAP/ Dipole Antenna	558	03/29/2019	Biennial	03/29/2021
ESPEC	SU-642 / Chamber	93000717	08/14/2019	Annual	08/14/2020
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	08/29/2019	Biennial	08/29/2021
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	9120D-1298	09/25/2019	Biennial	09/25/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/29/2019	Biennial	04/29/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	02/11/2020	Biennial	02/11/2022
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY51110063	04/27/2020	Annual	04/27/2021
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/04/2020	Annual	06/04/2021
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer(10Hz~40GHz)	100931	10/14/2019	Annual	10/14/2020
Agilent	8960 (E5515C)/ Base Station	MY48360800	08/27/2019	Annual	08/27/2020
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	04/26/2019	Biennial	04/26/2021
Schwarzbeck	VULB9160/ Bilog Antenna	9160-3368	08/09/2018	Biennial	08/09/2020
Schwarzbeck	VULB9160/ Hybrid Antenna	760	03/22/2019	Biennial	03/22/2021
Anritsu Corp.	MT8821C/Wideband Radio Communication Tester	6201502997	08/09/2019	Annual	08/09/2020
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	01/22/2020	Annual	01/22/2021
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/15/2019	Annual	07/15/2020
KEYSIGHT	E7515B / 5G Wireless Tester	MY58300756	01/07/2020	Annual	01/07/2021
KEYSIGHT	N9030B / Signal Analyzer(5Hz~40.0GHz)	MY55480167	06/04/2020	Annual	06/04/2021
Mini-Circuits	ZC4PD-K1844+ / 4-Way Divider	942907	09/05/2019	Annual	09/05/2020
HCT CO., LTD.,	FCC LTE Mobile Conducted RF Automation Test Software	-	-	-	-

Note:

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
2. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).
3. Model : 8493C(S/N: 17280)
 - Use date of Equipment : May 07, 2020 ~ June 03, 2020
 - Previous Calibration date : June 04, 2019 ~ June 04, 2020
4. Model : N9030B(S/N: MY55480167)
 - Use date of Equipment : June 07, 2020 ~ June 18, 2020

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (\pm dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05

6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §27.53(h)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§2.1046	N/A	<u>See Note1</u>
Peak- to- Average Ratio	27.50(d)(5)	< 13 dB	PASS
Frequency stability / variation of ambient temperature	§2.1055, § 27.54	Emission must remain in band	PASS

Note:

1. See SAR Report
2. The same samples were used for SAR and EMC

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	27.50(d)(4)	< 1 Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §27.53(h)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

ERP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
132322	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

EIRP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1710.7	LTE B66/ B4 1.4 MHz	QPSK	-19.92	13.38	9.85	1.88	V	< 1.00	0.137	21.35
		16-QAM	-20.66	12.64	9.85	1.88	V		0.115	20.61
		64-QAM	-22.15	11.15	9.85	1.88	V		0.082	19.12
		256-QAM	-25.26	8.04	9.85	1.88	V		0.040	16.01
1745.0		QPSK	-19.81	13.55	9.98	1.90	V		0.146	21.63
		16-QAM	-20.52	12.84	9.98	1.90	V		0.124	20.92
		64-QAM	-21.87	11.49	9.98	1.90	V		0.091	19.57
		256-QAM	-24.98	8.38	9.98	1.90	V		0.044	16.46
1779.3		QPSK	-19.21	14.05	10.05	1.92	V		0.165	22.18
		16-QAM	-19.93	13.33	10.05	1.92	V		0.140	21.46
		64-QAM	-21.30	11.96	10.05	1.92	V		0.102	20.09
		256-QAM	-24.41	8.85	10.05	1.92	V		0.050	16.98

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1711.5	LTE B66/ B4 3 MHz	QPSK	-19.94	13.36	9.85	1.88	V	< 1.00	0.136	21.33
		16-QAM	-20.67	12.63	9.85	1.88	V		0.115	20.60
		64-QAM	-22.45	10.85	9.85	1.88	V		0.076	18.82
		256-QAM	-25.52	7.78	9.85	1.88	V		0.038	15.75
1745.0		QPSK	-19.86	13.50	9.98	1.90	V		0.144	21.58
		16-QAM	-20.54	12.82	9.98	1.90	V		0.123	20.90
		64-QAM	-21.29	12.07	9.98	1.90	V		0.104	20.15
		256-QAM	-24.52	8.84	9.98	1.90	V		0.049	16.92
1778.5		QPSK	-19.17	14.09	10.05	1.92	V		0.167	22.22
		16-QAM	-19.88	13.38	10.05	1.92	V		0.142	21.51
		64-QAM	-21.38	11.88	10.05	1.92	V		0.100	20.01
		256-QAM	-24.52	8.74	10.05	1.92	V		0.049	16.87

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1712.5	LTE B66/ B4 5 MHz	QPSK	-19.97	13.33	9.85	1.88	V	< 1.00	0.135	21.30
		16-QAM	-20.71	12.59	9.85	1.88	V		0.114	20.56
		64-QAM	-22.37	10.93	9.85	1.88	V		0.078	18.90
		256-QAM	-25.55	7.75	9.85	1.88	V		0.037	15.72
1745.0		QPSK	-19.87	13.49	9.98	1.90	V		0.144	21.57
		16-QAM	-20.61	12.75	9.98	1.90	V		0.121	20.83
		64-QAM	-21.26	12.10	9.98	1.90	V		0.104	20.18
		256-QAM	-24.48	8.88	9.98	1.90	V		0.050	16.96
1777.5		QPSK	-19.15	14.11	10.05	1.92	V		0.168	22.24
		16-QAM	-19.84	13.42	10.05	1.92	V		0.143	21.55
		64-QAM	-21.16	12.10	10.05	1.92	V		0.106	20.23
		256-QAM	-24.35	8.91	10.05	1.92	V		0.051	17.04

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1715.0	LTE B66/ B4 10 MHz	QPSK	-19.99	13.33	9.88	1.88	V	< 1.00	0.136	21.32
		16-QAM	-20.75	12.57	9.88	1.88	V		0.114	20.56
		64-QAM	-22.39	10.93	9.88	1.88	V		0.078	18.92
		256-QAM	-25.54	7.78	9.88	1.88	V		0.038	15.77
1745.0		QPSK	-19.92	13.44	9.98	1.90	V		0.142	21.52
		16-QAM	-20.62	12.74	9.98	1.90	V		0.121	20.82
		64-QAM	-21.72	11.64	9.98	1.90	V		0.094	19.72
		256-QAM	-24.92	8.44	9.98	1.90	V		0.045	16.52
1775.0		QPSK	-19.18	14.12	10.05	1.92	V		0.168	22.25
		16-QAM	-19.91	13.39	10.05	1.92	V		0.142	21.52
		64-QAM	-21.27	12.03	10.05	1.92	V		0.104	20.16
		256-QAM	-24.44	8.86	10.05	1.92	V		0.050	16.99

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1717.5	LTE B66/ B4 15 MHz	QPSK	-20.18	13.15	9.90	1.88	V	< 1.00	0.131	21.17
		16-QAM	-20.82	12.51	9.90	1.88	V		0.113	20.53
		64-QAM	-22.43	10.90	9.90	1.88	V		0.078	18.92
		256-QAM	-25.57	7.76	9.90	1.88	V		0.038	15.78
1745.0		QPSK	-20.15	13.21	9.98	1.90	V		0.135	21.29
		16-QAM	-20.87	12.49	9.98	1.90	V		0.114	20.57
		64-QAM	-21.41	11.95	9.98	1.90	V		0.101	20.03
		256-QAM	-24.57	8.79	9.98	1.90	V		0.049	16.87
1772.5		QPSK	-19.14	14.20	10.05	1.92	V		0.171	22.33
		16-QAM	-19.86	13.48	10.05	1.92	V		0.145	21.61
		64-QAM	-21.76	11.58	10.05	1.92	V		0.094	19.71
		256-QAM	-24.93	8.41	10.05	1.92	V		0.045	16.54

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1720.0	LTE B66/ B4 20 MHz	QPSK	-20.03	13.30	9.90	1.88	V	< 1.00	0.135	21.32
		16-QAM	-20.81	12.52	9.90	1.88	V		0.113	20.54
		64-QAM	-22.35	10.98	9.90	1.88	V		0.079	19.00
		256-QAM	-25.48	7.85	9.90	1.88	V		0.039	15.87
1745.0		QPSK	-19.76	13.60	9.98	1.90	V		0.147	21.68
		16-QAM	-20.48	12.88	9.98	1.90	V		0.125	20.96
		64-QAM	-21.88	11.48	9.98	1.90	V		0.090	19.56
		256-QAM	-25.05	8.31	9.98	1.90	V		0.044	16.39
1770.0		QPSK	-19.15	14.19	10.05	1.92	V		0.171	22.32
		16-QAM	-19.89	13.45	10.05	1.92	V		0.144	21.58
		64-QAM	-21.33	12.01	10.05	1.92	V		0.103	20.14
		256-QAM	-24.40	8.94	10.05	1.92	V		0.051	17.07

8.2 RADIATED SPURIOUS EMISSIONS

- ▣ OPERATING FREQUENCY: 1779.3 MHz
- ▣ MEASURED OUTPUT POWER: 22.18 dBm = 0.165 W
- ▣ MODE: LTE B66 / B4
- ▣ MODULATION SIGNAL: 1.4 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $43 + 10 \log_{10}(W) =$ 35.18 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
131979 (1710.7)	3,421.40	-54.15	12.60	-61.13	2.73	V	-51.26	73.44
	5,132.10	-56.78	12.40	-54.45	3.40	H	-45.45	67.64
	6,842.80	-55.61	12.23	-49.55	4.04	H	-41.36	63.55
132322 (1745.0)	3,490.00	-55.49	12.35	-61.99	2.75	H	-52.39	74.57
	5,235.00	-56.41	13.09	-55.97	3.46	H	-46.33	68.52
	6,980.00	-56.02	11.85	-48.54	4.11	H	-40.80	62.98
132665 (1779.3)	3,558.60	-55.17	12.13	-61.29	2.78	V	-51.94	74.12
	5,337.90	-56.85	13.33	-56.22	3.49	H	-46.38	68.56
	7,117.20	-55.81	11.25	-47.51	4.15	V	-40.41	62.59

- ▣ OPERATING FREQUENCY: 1778.5 MHz
- ▣ MEASURED OUTPUT POWER: 22.22 dBm = 0.167 W
- ▣ MODE: LTE B66 / B4
- ▣ MODULATION SIGNAL: 3 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $43 + 10 \log_{10}(W) =$ 35.22 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
131987 (1711.5)	3,423.00	-55.88	12.60	-62.86	2.73	V	-52.99	75.21
	5,134.50	-57.14	12.43	-54.84	3.40	H	-45.81	68.03
	6,846.00	-55.81	12.22	-49.78	4.04	H	-41.60	63.82
132322 (1745.0)	3,490.00	-54.84	12.35	-61.34	2.75	V	-51.74	73.96
	5,235.00	-57.04	13.09	-56.60	3.46	H	-46.96	69.19
	6,980.00	-55.89	11.85	-48.41	4.11	V	-40.67	62.89
132657 (1778.5)	3,557.00	-56.40	12.13	-62.52	2.78	H	-53.17	75.39
	5,335.50	-57.49	13.34	-57.00	3.49	V	-47.14	69.37
	7,114.00	-56.31	11.27	-47.98	4.16	V	-40.87	63.09

- ▣ OPERATING FREQUENCY: 1777.5 MHz
- ▣ MEASURED OUTPUT POWER: 22.24 dBm = 0.168 W
- ▣ MODE: LTE B66 / B4
- ▣ MODULATION SIGNAL: 5 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $43 + 10 \log_{10}(W) =$ 35.24 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
131997 (1712.5)	3,425.00	-53.23	12.60	-60.07	2.73	V	-50.20	72.44
	5,137.50	-56.08	12.45	-53.79	3.39	H	-44.73	66.98
	6,850.00	-56.11	12.20	-50.11	4.03	H	-41.94	64.18
132322 (1745.0)	3,490.00	-55.82	12.35	-62.32	2.75	H	-52.72	74.96
	5,235.00	-56.78	13.09	-56.34	3.46	V	-46.70	68.95
	6,980.00	-57.12	11.85	-49.64	4.11	V	-41.90	64.14
132647 (1777.5)	3,555.00	-55.58	12.10	-61.60	2.79	H	-52.29	74.53
	5,332.50	-55.71	13.35	-55.36	3.48	H	-45.49	67.73
	7,110.00	-57.75	11.28	-49.39	4.16	H	-42.27	64.52

- ▣ OPERATING FREQUENCY: 1775.0 MHz
- ▣ MEASURED OUTPUT POWER: 22.25 dBm = 0.168 W
- ▣ MODE: LTE B66 / B4
- ▣ MODULATION SIGNAL: 10 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $43 + 10 \log_{10}(W) =$ 35.25 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
132022 (1715.0)	3,430.00	-55.45	12.60	-62.15	2.73	H	-52.28	74.53
	5,145.00	-57.72	12.43	-55.65	3.40	V	-46.62	68.87
	6,860.00	-56.03	12.18	-50.11	4.05	H	-41.98	64.23
132322 (1745.0)	3,490.00	-55.60	12.35	-62.10	2.75	H	-52.50	74.75
	5,235.00	-58.20	13.09	-57.76	3.46	H	-48.12	70.38
	6,980.00	-57.03	11.85	-49.55	4.11	V	-41.81	64.06
132622 (1775.0)	3,550.00	-55.56	12.10	-61.52	2.79	V	-52.21	74.46
	5,325.00	-57.09	13.35	-56.64	3.48	H	-46.77	69.02
	7,100.00	-57.17	11.30	-48.66	4.16	H	-41.52	63.77

- ▣ OPERATING FREQUENCY: 1772.5 MHz
- ▣ MEASURED OUTPUT POWER: 22.23 dBm = 0.171 W
- ▣ MODE: LTE B66 / B4
- ▣ MODULATION SIGNAL: 15 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $43 + 10 \log_{10}(W) =$ 35.33 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
132047 (1717.5)	3,435.00	-55.20	12.58	-61.96	2.74	V	-52.12	74.45
	5,152.50	-58.33	12.50	-56.58	3.40	V	-47.48	69.81
	6,870.00	-56.87	12.15	-50.66	4.06	V	-42.57	64.90
132322 (1745.0)	3,490.00	-56.10	12.35	-62.60	2.75	V	-53.00	75.33
	5,235.00	-57.60	13.09	-57.16	3.46	V	-47.52	69.85
	6,980.00	-56.08	11.85	-48.60	4.11	V	-40.86	63.19
132597 (1772.5)	3,545.00	-55.73	12.13	-61.72	2.79	H	-52.38	74.71
	5,317.50	-55.84	13.35	-55.30	3.47	H	-45.42	67.75
	7,090.00	-57.22	11.35	-48.75	4.14	H	-41.54	63.87

- ▣ OPERATING FREQUENCY: 1770.0 MHz
- ▣ MEASURED OUTPUT POWER: 22.32 dBm = 0.171 W
- ▣ MODE: LTE B66 / B4
- ▣ MODULATION SIGNAL: 20 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $43 + 10 \log_{10} (W) =$ 35.32 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
132072 (1720.0)	3,440.00	-55.42	12.55	-62.25	2.74	H	-52.44	74.76
	5,160.00	-57.67	12.60	-55.99	3.42	H	-46.81	69.13
	6,880.00	-56.07	12.15	-49.45	4.06	V	-41.36	63.68
132322 (1745.0)	3,490.00	-55.41	12.35	-61.91	2.75	H	-52.31	74.63
	5,235.00	-57.64	13.09	-57.20	3.46	V	-47.56	69.88
	6,980.00	-56.82	11.85	-49.34	4.11	V	-41.60	63.92
132572 (1770.0)	3,540.00	-54.24	12.15	-60.26	2.79	H	-50.90	73.22
	5,310.00	-57.67	13.38	-57.36	3.47	V	-47.45	69.77
	7,080.00	-57.99	11.40	-49.88	4.12	H	-42.60	64.92

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
66/4	1.4 MHz	1745.0	QPSK	6	0	5.95
			16-QAM			6.39
			64-QAM			6.51
			256-QAM			6.23
	3 MHz		QPSK	15		5.94
			16-QAM			6.49
			64-QAM			6.50
			256-QAM			6.21
	5 MHz		QPSK	25		5.80
			16-QAM			6.48
			64-QAM			6.48
			256-QAM			6.17
	10 MHz		QPSK	50		5.90
			16-QAM			6.38
			64-QAM			6.46
			256-QAM			6.18
	15 MHz		QPSK	75		5.74
			16-QAM			6.32
			64-QAM			6.44
			256-QAM			6.16
20 MHz	QPSK	100	5.72			
	16-QAM		6.40			
	64-QAM		6.46			
	256-QAM		6.24			

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 81 ~ 104.

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
66/4	1.4 MHz	1745.0	QPSK	6	0	1.0971
			16-QAM			1.1034
			64-QAM			1.1015
			256-QAM			1.0973
	3 MHz		QPSK	15		2.7189
			16-QAM			2.7213
			64-QAM			2.7137
			256-QAM			2.7128
	5 MHz		QPSK	25		4.5221
			16-QAM			4.5630
			64-QAM			4.5220
			256-QAM			4.5291
	10 MHz		QPSK	50		9.0302
			16-QAM			9.0071
			64-QAM			8.9944
			256-QAM			8.9942
	15 MHz		QPSK	75		13.512
			16-QAM			13.462
			64-QAM			13.449
			256-QAM			13.456
20 MHz	QPSK	100	17.948			
	16-QAM		17.952			
	64-QAM		17.973			
	256-QAM		17.975			

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 57~ 80.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
66/4	1.4	1710.7	3.4213	27.976	-76.028	-48.052	-13.00
		1745.0	3.4896	27.976	-77.160	-49.184	
		1779.3	3.5599	27.976	-77.047	-49.071	
	3	1711.5	3.4213	27.976	-77.097	-49.121	
		1745.0	3.4881	27.976	-76.643	-48.667	
		1778.5	3.5604	27.976	-76.459	-48.483	
	5	1712.5	3.4213	27.976	-76.515	-48.539	
		1745.0	3.7059	27.976	-77.418	-49.442	
		1777.5	3.5599	27.976	-76.598	-48.622	
	10	1715.0	3.4218	27.976	-76.722	-48.746	
		1745.0	3.4816	27.976	-77.440	-49.464	
		1775.0	3.5594	27.976	-77.086	-49.110	
	15	1717.5	3.4223	27.976	-76.524	-48.548	
		1745.0	3.6920	27.976	-77.175	-49.199	
		1772.5	3.5589	27.976	-77.115	-49.139	
	20	1720.0	3.4228	27.976	-77.231	-49.255	
		1745.0	3.6930	27.976	-77.228	-49.252	
		1770.0	3.5584	27.976	-77.475	-49.499	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 141 ~ 176.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131


8.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 105 ~ 140.

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1710,700,000 Hz
- ▣ CHANNEL: 131979 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1710 699 994	0.0	0.000 000	0.000
100%		-30	1710 700 001	6.9	0.000 000	0.004
100%		-20	1710 700 002	8.7	0.000 001	0.005
100%		-10	1710 699 986	-7.3	0.000 000	-0.004
100%		0	1710 700 002	8.6	0.000 001	0.005
100%		+10	1710 700 003	9.2	0.000 001	0.005
100%		+30	1710 699 988	-5.5	0.000 000	-0.003
100%		+40	1710 700 002	8.4	0.000 000	0.005
100%		+50	1710 700 003	9.1	0.000 001	0.005
Batt. Endpoint		3.400	+20	1710 700 003	9.4	0.000 001




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1711,500,000 Hz
- ▣ CHANNEL: 131987 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1711 499 995	0.0	0.000 000	0.000
100%		-30	1711 499 986	-8.4	0.000 000	-0.005
100%		-20	1711 499 987	-7.2	0.000 000	-0.004
100%		-10	1711 499 988	-6.4	0.000 000	-0.004
100%		0	1711 499 999	4.9	0.000 000	0.003
100%		+10	1711 500 007	12.4	0.000 001	0.007
100%		+30	1711 500 004	9.1	0.000 001	0.005
100%		+40	1711 500 005	10.1	0.000 001	0.006
100%		+50	1711 500 005	10.4	0.000 001	0.006
Batt. Endpoint	3.400	+20	1711 500 003	8.5	0.000 000	0.005




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1712,500,000 Hz
- ▣ CHANNEL: 131997 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1712 500 007	0.0	0.000 000	0.000
100%		-30	1712 500 015	8.3	0.000 000	0.005
100%		-20	1712 499 998	-8.8	-0.000 001	-0.005
100%		-10	1712 499 999	-7.5	0.000 000	-0.004
100%		0	1712 500 014	7.7	0.000 000	0.004
100%		+10	1712 500 014	7.1	0.000 000	0.004
100%		+30	1712 500 014	7.5	0.000 000	0.004
100%		+40	1712 500 015	8.0	0.000 000	0.005
100%		+50	1712 499 998	-8.2	0.000 000	-0.005
Batt. Endpoint	3.400	+20	1712 500 013	6.4	0.000 000	0.004




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1715,000,000 Hz
- ▣ CHANNEL: 132022 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1714 999 993	0.0	0.000 000	0.000
100%		-30	1715 000 001	7.1	0.000 000	0.004
100%		-20	1715 000 005	11.8	0.000 001	0.007
100%		-10	1715 000 000	6.5	0.000 000	0.004
100%		0	1715 000 002	8.4	0.000 000	0.005
100%		+10	1715 000 001	7.3	0.000 000	0.004
100%		+30	1715 000 002	8.6	0.000 001	0.005
100%		+40	1715 000 002	8.5	0.000 000	0.005
100%		+50	1715 000 000	7.0	0.000 000	0.004
Batt. Endpoint	3.400	+20	1715 000 000	6.9	0.000 000	0.004




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1717,500,000 Hz
- ▣ CHANNEL: 132047 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1717 500 009	0.0	0.000 000	0.000
100%		-30	1717 500 015	6.7	0.000 000	0.004
100%		-20	1717 500 014	5.7	0.000 000	0.003
100%		-10	1717 500 016	7.2	0.000 000	0.004
100%		0	1717 500 016	7.8	0.000 000	0.005
100%		+10	1717 500 017	7.9	0.000 000	0.005
100%		+30	1717 500 017	8.8	0.000 001	0.005
100%		+40	1717 500 016	7.3	0.000 000	0.004
100%		+50	1717 500 002	1717 500 002	-6.9	0.000 000
Batt. Endpoint	3.400	+20	1717 500 004	-4.9	0.000 000	-0.003




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1720,000,000 Hz
- ▣ CHANNEL: 132072 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1720 000 007	0.0	0.000 000	0.000
100%		-30	1720 000 014	7.0	0.000 000	0.004
100%		-20	1720 000 014	7.6	0.000 000	0.004
100%		-10	1720 000 013	6.4	0.000 000	0.004
100%		0	1720 000 014	7.3	0.000 000	0.004
100%		+10	1720 000 014	7.3	0.000 000	0.004
100%		+30	1720 000 015	8.6	0.000 000	0.005
100%		+40	1720 000 015	8.5	0.000 000	0.005
100%		+50	1720 000 015	7.9	0.000 000	0.005
Batt. Endpoint		3.400	+20	1720 000 015	7.8	0.000 000




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1745,000,000 Hz
- ▣ CHANNEL: 132322 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1745 000 010	0.0	0.000 000	0.000
100%		-30	1745 000 019	9.4	0.000 001	0.005
100%		-20	1745 000 017	7.5	0.000 000	0.004
100%		-10	1745 000 018	7.9	0.000 000	0.005
100%		0	1745 000 019	9.0	0.000 001	0.005
100%		+10	1745 000 017	7.1	0.000 000	0.004
100%		+30	1745 000 018	8.3	0.000 000	0.005
100%		+40	1745 000 018	7.9	0.000 000	0.005
100%		+50	1745 000 017	7.5	0.000 000	0.004
Batt. Endpoint	3.400	+20	1745 000 019	9.2	0.000 001	0.005




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1745,000,000 Hz
- ▣ CHANNEL: 132322 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1744 999 991	0.0	0.000 000	0.000
100%		-30	1744 999 998	6.6	0.000 000	0.004
100%		-20	1744 999 998	6.8	0.000 000	0.004
100%		-10	1745 000 001	9.8	0.000 001	0.006
100%		0	1744 999 999	7.8	0.000 000	0.004
100%		+10	1745 000 001	9.4	0.000 001	0.005
100%		+30	1745 000 001	9.4	0.000 001	0.005
100%		+40	1745 000 000	9.1	0.000 001	0.005
100%		+50	1744 999 984	-7.1	0.000 000	-0.004
Batt. Endpoint		3.400	+20	1744 999 999	8.2	0.000 000




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1745,000,000 Hz
- ▣ CHANNEL: 132322 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1745 000 007	0.0	0.000 000	0.000
100%		-30	1745 000 014	6.8	0.000 000	0.004
100%		-20	1745 000 015	7.9	0.000 000	0.005
100%		-10	1745 000 015	8.1	0.000 000	0.005
100%		0	1745 000 014	7.0	0.000 000	0.004
100%		+10	1745 000 016	9.0	0.000 001	0.005
100%		+30	1745 000 017	10.3	0.000 001	0.006
100%		+40	1745 000 013	6.6	0.000 000	0.004
100%		+50	1745 000 014	7.7	0.000 000	0.004
Batt. Endpoint	3.400	+20	1745 000 013	6.4	0.000 000	0.004




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1745,000,000 Hz
- ▣ CHANNEL: 132322 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1744 999 993	0.0	0.000 000	0.000
100%		-30	1744 999 999	5.7	0.000 000	0.003
100%		-20	1744 999 998	5.0	0.000 000	0.003
100%		-10	1745 000 004	10.2	0.000 001	0.006
100%		0	1744 999 988	-5.6	0.000 000	-0.003
100%		+10	1745 000 000	6.1	0.000 000	0.003
100%		+30	1745 000 000	6.2	0.000 000	0.004
100%		+40	1745 000 002	8.9	0.000 001	0.005
100%		+50	1744 999 988	-5.3	0.000 000	-0.003
Batt. Endpoint	3.400	+20	1745 000 003	9.5	0.000 001	0.005




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1745,000,000 Hz
- ▣ CHANNEL: 132322 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1745 000 008	0.0	0.000 000	0.000
100%		-30	1745 000 014	6.3	0.000 000	0.004
100%		-20	1745 000 014	6.1	0.000 000	0.003
100%		-10	1745 000 015	7.2	0.000 000	0.004
100%		0	1745 000 016	8.4	0.000 000	0.005
100%		+10	1745 000 015	7.1	0.000 000	0.004
100%		+30	1745 000 015	7.5	0.000 000	0.004
100%		+40	1745 000 016	8.0	0.000 000	0.005
100%		+50	1745 000 015	6.8	0.000 000	0.004
Batt. Endpoint	3.400	+20	1745 000 015	7.0	0.000 000	0.004




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1745,000,000 Hz
- ▣ CHANNEL: 132322 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1745 000 009	0.0	0.000 000	0.000
100%		-30	1745 000 017	8.7	0.000 000	0.005
100%		-20	1745 000 016	7.4	0.000 000	0.004
100%		-10	1745 000 015	6.4	0.000 000	0.004
100%		0	1745 000 017	8.3	0.000 000	0.005
100%		+10	1745 000 015	6.9	0.000 000	0.004
100%		+30	1745 000 014	5.6	0.000 000	0.003
100%		+40	1745 000 015	6.4	0.000 000	0.004
100%		+50	1745 000 016	7.7	0.000 000	0.004
Batt. Endpoint	3.400	+20	1745 000 016	7.9	0.000 000	0.005




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1779,300,000 Hz
- ▣ CHANNEL: 132665 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1779 299 990	0.0	0.000 000	0.000
100%		-30	1779 299 982	-7.9	0.000 000	-0.004
100%		-20	1779 299 999	8.8	0.000 000	0.005
100%		-10	1779 299 999	9.2	0.000 001	0.005
100%		0	1779 299 999	9.2	0.000 001	0.005
100%		+10	1779 300 000	10.1	0.000 001	0.006
100%		+30	1779 299 997	6.6	0.000 000	0.004
100%		+40	1779 299 999	8.4	0.000 000	0.005
100%		+50	1779 299 999	8.5	0.000 000	0.005
Batt. Endpoint	3.400	+20	1779 300 000	9.6	0.000 001	0.005




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1778,500,000 Hz
- ▣ CHANNEL: 132657 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1778 499 992	0.0	0.000 000	0.000
100%		-30	1778 500 005	13.0	0.000 001	0.007
100%		-20	1778 500 007	15.0	0.000 001	0.008
100%		-10	1778 500 002	9.8	0.000 001	0.006
100%		0	1778 500 004	11.9	0.000 001	0.007
100%		+10	1778 500 004	12.0	0.000 001	0.007
100%		+30	1778 500 003	10.4	0.000 001	0.006
100%		+40	1778 500 005	12.2	0.000 001	0.007
100%		+50	1778 500 003	10.6	0.000 001	0.006
Batt. Endpoint	3.400	+20	1778 500 004	11.7	0.000 001	0.007




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1777,500,000 Hz
- ▣ CHANNEL: 132647 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1777 500 007	0.0	0.000 000	0.000
100%		-30	1777 500 014	7.1	0.000 000	0.004
100%		-20	1777 500 014	6.8	0.000 000	0.004
100%		-10	1777 500 016	8.9	0.000 001	0.005
100%		0	1777 500 014	7.4	0.000 000	0.004
100%		+10	1777 500 016	9.1	0.000 001	0.005
100%		+30	1777 500 014	7.5	0.000 000	0.004
100%		+40	1777 500 015	8.0	0.000 000	0.005
100%		+50	1777 500 014	6.9	0.000 000	0.004
Batt. Endpoint	3.400	+20	1777 500 015	8.5	0.000 000	0.005




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1775,000,000 Hz
- ▣ CHANNEL: 132622 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1775 000 009	0.0	0.000 000	0.000
100%		-30	1775 000 016	7.4	0.000 000	0.004
100%		-20	1775 000 016	7.8	0.000 000	0.004
100%		-10	1775 000 016	7.0	0.000 000	0.004
100%		0	1775 000 016	7.1	0.000 000	0.004
100%		+10	1775 000 016	7.4	0.000 000	0.004
100%		+30	1775 000 016	7.0	0.000 000	0.004
100%		+40	1775 000 015	6.3	0.000 000	0.004
100%		+50	1775 000 017	8.0	0.000 000	0.005
Batt. Endpoint		3.400	+20	1775 000 015	6.0	0.000 000




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1772,500,000 Hz
- ▣ CHANNEL: 132597 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1772 500 006	0.0	0.000 000	0.000
100%		-30	1772 500 014	8.2	0.000 000	0.005
100%		-20	1772 500 014	7.5	0.000 000	0.004
100%		-10	1772 500 013	7.3	0.000 000	0.004
100%		0	1772 500 013	7.3	0.000 000	0.004
100%		+10	1772 500 013	6.8	0.000 000	0.004
100%		+30	1772 500 014	7.6	0.000 000	0.004
100%		+40	1772 500 014	7.8	0.000 000	0.004
100%		+50	1772 500 013	6.5	0.000 000	0.004
Batt. Endpoint		3.400	+20	1772 499 999	-6.9	0.000 000




- ▣ MODE: LTE 66/4
- ▣ OPERATING FREQUENCY: 1770,000,000 Hz
- ▣ CHANNEL: 132572 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.88 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.880	+20(Ref)	1770 000 009	0.0	0.000 000	0.000
100%		-30	1770 000 017	8.3	0.000 000	0.005
100%		-20	1770 000 017	8.0	0.000 000	0.005
100%		-10	1770 000 016	7.6	0.000 000	0.004
100%		0	1770 000 018	9.6	0.000 001	0.005
100%		+10	1770 000 016	7.9	0.000 000	0.004
100%		+30	1770 000 017	8.1	0.000 000	0.005
100%		+40	1770 000 017	8.7	0.000 000	0.005
100%		+50	1770 000 015	6.9	0.000 000	0.004
Batt. Endpoint	3.400	+20	1770 000 015	6.7	0.000 000	0.004




9. TEST PLOTS


BAND 66/4. Occupied Bandwidth Plot (1.4M BW Ch.132322 QPSK RB 6)




BAND 66/4. Occupied Bandwidth Plot (1.4M BW Ch.132322 16QAM RB 6)




BAND 66/4. Occupied Bandwidth Plot (1.4M BW Ch.132322 64QAM RB 6)




BAND 66/4. Occupied Bandwidth Plot (1.4M BW Ch.132322 256QAM RB 6)




BAND 66/4. Occupied Bandwidth Plot (3M BW Ch.132322 QPSK RB 15)




BAND 66/4. Occupied Bandwidth Plot (3M BW Ch.132322 16QAM RB 15)




BAND 66/4. Occupied Bandwidth Plot (3M BW Ch.132322 64QAM RB 15)




BAND 66/4. Occupied Bandwidth Plot (3M BW Ch.132322 256QAM RB 15)




BAND 66/4. Occupied Bandwidth Plot (5M BW Ch.132322 QPSK RB 25)




BAND 66/4. Occupied Bandwidth Plot (5M BW Ch.132322 16QAM RB 25)




BAND 66/4. Occupied Bandwidth Plot (5M BW Ch.132322 64QAM RB 25)




BAND 66/4. Occupied Bandwidth Plot (5M BW Ch.132322 256QAM RB 25)




BAND 66/4. Occupied Bandwidth Plot (10M BW Ch.132322 QPSK RB 50)




BAND 66/4. Occupied Bandwidth Plot (10M BW Ch.132322 16QAM RB 50)




BAND 66/4. Occupied Bandwidth Plot (10M BW Ch.132322 64QAM RB 50)




BAND 66/4. Occupied Bandwidth Plot (10M BW Ch.132322 256QAM RB 50)




BAND 66/4. Occupied Bandwidth Plot (15M BW Ch.132322 QPSK RB 75)




BAND 66/4. Occupied Bandwidth Plot (15M BW Ch.132322 16QAM RB 75)




BAND 66/4. Occupied Bandwidth Plot (15M BW Ch.132322 64QAM RB 75)




BAND 66/4. Occupied Bandwidth Plot (15M BW Ch.132322 256QAM RB 75)




BAND 66/4. Occupied Bandwidth Plot (20M BW Ch.132322 QPSK RB 100)




BAND 66/4. Occupied Bandwidth Plot (20M BW Ch.132322 16QAM RB 100)




BAND 66/4. Occupied Bandwidth Plot (20M BW Ch.132322 64QAM RB 100)




BAND 66/4. Occupied Bandwidth Plot (20M BW Ch.132322 256QAM RB 100)




BAND 66/4. PAR Plot (1.4M BW_Ch.132322_QPSK_RB6_0)




BAND 66/4. PAR Plot (1.4M BW_Ch.132322_16QAM_RB6_0)




BAND 66/4. PAR Plot (1.4M BW_Ch.132322_64QAM_RB6_0)




BAND 66/4. PAR Plot (1.4M BW_Ch.132322_256QAM_RB6_0)




BAND 66/4. PAR Plot (3M BW_Ch.132322_QPSK_RB15_0)




BAND 66/4. PAR Plot (3M BW_Ch.132322_16QAM_RB15_0)




BAND 66/4. PAR Plot (3M BW_Ch.132322_64QAM_RB15_0)




BAND 66/4. PAR Plot (3M BW_Ch.132322_256QAM_RB15_0)




BAND 66/4. PAR Plot (5M BW_Ch.132322_QPSK_RB25_0)




BAND 66/4. PAR Plot (5M BW_Ch.132322_16QAM_RB25_0)




BAND 66/4. PAR Plot (5M BW_Ch.132322_64QAM_RB25_0)




BAND 66/4. PAR Plot (5M BW_Ch.132322_256QAM_RB25_0)




BAND 66/4. PAR Plot (10M BW_Ch.132322_QPSK_RB50_0)




BAND 66/4. PAR Plot (10M BW_Ch.132322_16QAM_RB50_0)




BAND 66/4. PAR Plot (10M BW_Ch.132322_64QAM_RB50_0)




BAND 66/4. PAR Plot (10M BW_Ch.132322_256QAM_RB50_0)




BAND 66/4. PAR Plot (15M BW_Ch.132322_QPSK_RB75_0)




BAND 66/4. PAR Plot (15M BW_Ch.132322_16QAM_RB75_0)




BAND 66/4. PAR Plot (15M BW_Ch.132322_64QAM_RB75_0)




BAND 66/4. PAR Plot (15M BW_Ch.132322_256QAM_RB75_0)




BAND 66/4. PAR Plot (20M BW_Ch.132322_QPSK_RB100_0)




BAND 66/4. PAR Plot (20M BW_Ch.132322_16QAM_RB100_0)




BAND 66/4. PAR Plot (20M BW_Ch.132322_64QAM_RB100_0)




BAND 66/4. PAR Plot (20M BW_Ch.132322_256QAM_RB100_0)




BAND 66/4. Lower Band Edge Plot (1.4M BW Ch.131979 QPSK RB 1, Offset 0) -1



BAND 66/4. Lower Extended Band Edge Plot (1.4M BW Ch.131979 QPSK_RB6_0) -3




BAND 66/4. Lower Band Edge Plot (3M BW Ch.131987 QPSK RB 1, Offset 0) -1



BAND 66/4. Lower Band Edge Plot (3M BW Ch.131987 QPSK RB 15) -2



BAND 66/4. Lower Extended Band Edge Plot (3M BW Ch.131987 QPSK_RB15_0) -3




BAND 66/4. Lower Band Edge Plot (5M BW Ch.131997 QPSK RB 1, Offset 0) -1



BAND 66/4. Lower Band Edge Plot (5M BW Ch.131997 QPSK RB 25) -2



BAND 66/4. Lower Extended Band Edge Plot (5M BW Ch.131997 QPSK_RB25_0) -3




BAND 66/4. Lower Band Edge Plot (10M BW Ch.132022 QPSK RB 1, Offset 0) -1



BAND 66/4. Lower Band Edge Plot (10M BW Ch.132022 QPSK RB 50) -2



BAND 66/4. Lower Extended Band Edge Plot (10M BW Ch.132022 QPSK_RB50_0) -3




BAND 66/4. Lower Band Edge Plot (15M BW Ch.132047 QPSK RB 1, Offset 0) -1



BAND 66/4. Lower Band Edge Plot (15M BW Ch.132047 QPSK RB 75) -2



BAND 66/4. Lower Extended Band Edge Plot (15M BW Ch.132047 QPSK_RB75_0) -3




BAND 66/4. Lower Band Edge Plot (20M BW Ch.132072 QPSK RB 1, Offset 0) -1




BAND 66/4. Lower Band Edge Plot (20M BW Ch.132072 QPSK RB 100) -2




BAND 66/4. Lower Extended Band Edge Plot (20M BW Ch.132072 QPSK_RB100_0) -3



BAND 66/4. Upper Band Edge Plot (1.4M BW Ch.132665 QPSK_RB1_Offset 5) -1



BAND 66/4. Upper Extended Band Edge Plot (1.4M BW Ch. 132665 QPSK_RB6_0) -3



BAND 66/4. Upper Band Edge Plot (3M BW Ch.132657 QPSK_RB15) -2




BAND 66/4. Upper Extended Band Edge Plot (3M BW Ch.132657 QPSK_RB15_0) -3



BAND 66/4. Upper Band Edge Plot (5M BW Ch.132647 QPSK_RB1_Offset 24) -1



BAND 66/4. Upper Extended Band Edge Plot (5M BW Ch.132647 QPSK_RB25) -3




BAND 66/4. Upper Band Edge Plot (10M BW Ch.132622 QPSK_RB1_Offset 49) -1



BAND 66/4. Upper Band Edge Plot (10M BW Ch.132622 QPSK_RB50) -2



BAND 66/4. Upper Extended Band Edge Plot (10M BW Ch.132622 QPSK_RB50) -3




BAND 66/4. Upper Band Edge Plot (15M BW Ch.132597 QPSK_RB1_Offset 74) -1



BAND 66/4. Upper Band Edge Plot (15M BW Ch.132597 QPSK_RB75) -2




BAND 66/4. Upper Extended Band Edge Plot (15M BW Ch.132597 QPSK_RB75) -3




BAND 66/4. Upper Band Edge Plot (20M BW Ch.132572 QPSK_RB100) -2




BAND 66/4. Upper Extended Band Edge Plot (20M BW Ch.132572 QPSK_RB100) -3




BAND 66/4. Conducted Spurious Plot_2 (131979ch_1.4MHz_QPSK_RB 1_0)



BAND 66/4. Conducted Spurious Plot_1 (132322ch_1.4MHz_QPSK_RB 1_0)



BAND 66/4. Conducted Spurious Plot_2 (132322ch_1.4MHz_QPSK_RB 1_0)



BAND 66/4. Conducted Spurious Plot_2 (132665ch_1.4MHz_QPSK_RB 1_0)



