




# TEST REPORT

<b>KCTL Inc.</b> 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <a href="http://www.kctl.co.kr">www.kctl.co.kr</a>	Report No.: KR22-SRF0052 Page (1) of (17)	   <b>KCTL</b>
<p><b>1. Client</b></p> <ul style="list-style-type: none"> <li>◦ Name : Samsung Electronics Co., Ltd.</li> <li>◦ Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea</li> <li>◦ Date of Receipt : 2022-03-11</li> </ul> <p><b>2. Use of Report</b> : Certification</p> <p><b>3. Name of Product / Model</b> : Tablet PC / SM-P619</p> <p><b>4. Manufacturer / Country of Origin:</b> Samsung Electronics Co., Ltd. / Vietnam</p> <p><b>5. FCC ID</b> : A3LSMP619</p> <p><b>6. Date of Test</b> : 2022-03-11 to 2022-04-12</p> <p><b>7. Location of Test</b> : <input checked="" type="checkbox"/> Permanent Testing Lab <input type="checkbox"/> On Site Testing          (Address:65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea)          FCC Part 15 Subpart E, 15.407</p> <p><b>8. Test method used</b> : RSS-247 Issue 2 February 2017          RSS GEN Issue 5 April 2018</p> <p><b>9. Test Result</b> : Refer to the test result in the test report</p>		
Affirmation	Tested by  Name : Kwonse Kim (Signature)	Technical Manager  Name : Seungyong Kim (Signature)
2022-04-13		
<h2>KCTL Inc.</h2> <p>As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.</p>		

**REPORT REVISION HISTORY**

Date	Revision	Page No
2022-04-13	Originally issued	-

*This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.*

**General remarks for test reports**

**Statement concerning the uncertainty of the measurement systems used for the tests**

(may be required by the product standard or client)

Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:

**Procedure number, issue date and title:**

Calculations leading to the reported values are on file with the testing laboratory that conducted the testing.

Statement not required by the standard or client used for type testing

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0052  
Page (3) of (17)



# CONTENTS

- 1. General information .....4
- 2. Device information .....4
  - 2.1. Frequency/channel operations.....6
- 3. Summary of tests .....7
- 4 Test results .....8
  - 4.1. DFS (Dynamic Frequency Selection).....8
- 5. Measurement equipment .....17



# KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0052  
Page (4) of (17)



## 1. General information

Client : Samsung Electronics Co., Ltd.  
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea  
Manufacturer : Samsung Electronics Co., Ltd.  
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea  
Factory : Samsung Electronics Vietnam Thai Nguyen Co., Ltd  
Address : Yen Binh Industrial Park, Dong Tien Ward, Pho Yen Town, Thai Nguyen Province, Vietnam  
Laboratory : KCTL Inc.  
Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea  
Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132  
VCCI Registration No. : R-20080, G-20078, C-20059, T-20056  
CAB Identifier: KR0040  
ISED Number: 8035A  
KOLAS No.: KT231

## 2. Device information

Equipment under test : Tablet PC  
Model : SM-P619  
Modulation technique : Bluetooth(BDR/EDR) : GFSK,  $\pi/4$ DQPSK, 8DPSK  
Bluetooth(BLE) : GFSK  
WIFI(802.11a/b/g/n/ac) : DSSS, OFDM  
LTE : QPSK, 16QAM, 64QAM  
WCDMA : QPSK  
GSM : GMSK, 8-PSK  
Number of channels : Bluetooth : 79 ch  
BLE : 40 ch  
802.11b/g/n\_HT20 : 13 ch  
UNII-1 : 4 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz)  
UNII-2A : 4 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz)  
UNII-2C : 12 ch (20 MHz), 6 ch (40 MHz), 3 ch (80 MHz)  
UNII-3 : 5 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz)  
Power source : DC 3.85 V  
Antenna specification : LTE/WCDMA/GSM : Metal Antenna  
WLAN(2.4G)/Bluetooth/BLE : Metal Antenna  
WLAN(5G) : Metal Antenna  
Antenna gain :  
Antenna 1  
2.4 GHz Band : -7.20 dBi  
UNII-1 : -5.80 dBi  
UNII-2A : -5.80 dBi  
UNII-2C : -6.30 dBi  
UNII-3 : -6.80 dBi  
Antenna 2  
2.4 GHz Band : -7.30 dBi  
UNII-1 : -8.40 dBi  
UNII-2A : -8.40 dBi  
UNII-2C : -8.10 dBi  
UNII-3 : -7.00 dBi

# KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0052  
Page (5) of (17)



Frequency range	:	Bluetooth	:	2 402 MHz ~ 2 480 MHz	(BDR/EDR/BLE)
		2.4 GHz WALN	:	2 412 MHz ~ 2 472 MHz	(802.11b/g/n_HT20)
		UNII-1	:	5 180 MHz ~ 5 240 MHz	(802.11a/n/acHT20/VHT20)
		UNII-1	:	5 190 MHz ~ 5 230 MHz	(802.11n/ac_HT40/VHT40)
		UNII-1	:	5 210 MHz	(802.11ac_VHT80)
		UNII-2A	:	5 260 MHz ~ 5 320 MHz	(802.11a/n/ac_HT20/VHT20)
		UNII-2A	:	5 270 MHz ~ 5 310 MHz	(802.11n/ac_HT40/VHT40)
		UNII-2A	:	5 290 MHz	(802.11ac_VHT80)
		UNII-2C	:	5 500 MHz ~ 5 720 MHz	(802.11a/n/ac_HT20/VHT20)
		UNII-2C	:	5 510 MHz ~ 5 710 MHz	(802.11n/ac_HT40/VHT40)
		UNII-2C	:	5 530 MHz ~ 5 690 MHz	(802.11ac_VHT80)
		UNII-3	:	5 745 MHz ~ 5 825 MHz	(802.11a/n/ac_HT20/VHT20)
		UNII-3	:	5 755 MHz ~ 5 795 MHz	(802.11n/ac_HT40/VHT40)
		UNII-3	:	5 775 MHz	(802.11ac_VHT80)
		LTE Band 2	:	1 850.7 MHz ~ 1 909.3 MHz	
		LTE Band 4	:	1 710.7 MHz ~ 1 754.3 MHz	
		LTE Band 5	:	824.7 MHz ~ 848.3 MHz	
		LTE Band 12	:	699.7 MHz ~ 715.3 MHz	
		LTE Band 17	:	706.5 MHz ~ 713.5 MHz	
		LTE Band 41	:	2 498.5 MHz ~ 2 687.5 MHz	
		LTE Band 66	:	1 710.7 MHz ~ 1 779.3 MHz	
		GSM 850	:	824.2 MHz ~ 848.8 MHz	
		GSM 1900	:	1 850.2 MHz ~ 1 909.8 MHz	
		WCDMA 850	:	826.4 MHz ~ 846.6 MHz	
		WCDMA 1700	:	1 712.4 MHz ~ 1 752.6 MHz	
		WCDMA 1900	:	1 852.4 MHz ~ 1 907.6 MHz	
Software version	:	P619.001			
Hardware version	:	REV1.0			
Test device serial No.	:	Conducted	:	R32T2001R7V	
Operation temperature	:	-30 °C ~ 50 °C			

## 2.1. Frequency/channel operations

This device contains the following capabilities:

WLAN (11a/b/g/n/ac – 2TX MIMO), Bluetooth (BDR/EDR/BLE), LTE B2/4/5/12/17/41/66,  
GSM 850/1900, WCDMA 850/1700/1900

### UNII-2A

Ch.	Frequency (MHz)
52	5 260
56	5 280
64	5 320

### UNII-2C

Ch.	Frequency (MHz)
100	5 500
120	5 600
140	5 700
144	5 720

Table 2.1-1. 802.11a/n/ac\_HT20/VHT20 mode

### UNII-2A

Ch.	Frequency (MHz)
54	5 270
62	5 310

### UNII-2C

Ch.	Frequency (MHz)
102	5 510
118	5 590
134	5 670
142	5 710

Table 2.1-2. 802.11n/ac\_HT40/VHT40 mode

### UNII-2A

Ch.	Frequency (MHz)
58	5 290

### UNII-2C

Ch.	Frequency (MHz)
106	5 530
122	5 610
138	5 690

Table 2.1-3 802.11ac\_VHT80 mode

### Notes:

1. The device supports DFS bands between UNII-2A and UNII-2C and operates as a slave device controlled by master.

### 3. Summary of tests

FCC Part section(s)	IC Rule Reference	Parameter	Test results
15.407(h)	RSS-247 Issue 2, 6.3	DFS -Channel closing transmission time -Channel move time -Non occupied period	Pass

**Notes:**

1. The test procedure(s) in this report were performed in accordance as following.
  - ◆ KDB 905462 D02 UNII DFS compliance procedure new rules .
  - ◆ KDB 905462 D03 UNII client without radar detection new rules.
2. The device does not support radar detection feature.



## 4 Test results

### 4.1. DFS (Dynamic Frequency Selection)

#### Test description

#### - Applicability of DFS requirements prior to use of a channel

Requirement	Operational Mode		
	Master	Client (without radar detection)	Client (with radar detection)
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

#### - Applicability of DFS requirements during normal operation

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
DFS Detection Threshold	Yes	Not required
Channel Closing Transmission Time	Yes	<u>Yes</u>
Channel Move Time	Yes	<u>Yes</u>
Bandwidth	Yes	Not required

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	<u>Test using the widest BW mode available for the link</u>
All other tests	Any single BW mode	Not required

**Note:** Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.



**- Requirements of client devices**

- a) A Client Device will not transmit before having received appropriate control signals from a Master Device.
- b) A Client Device will stop all its transmissions whenever instructed by a Master Device to which it is associated and will meet the Channel Move Time and Channel Closing Transmission Time requirements. The Client Device will not resume any transmissions until it has again received control signals from a Master Device.
- c) If a Client Device is performing In-Service Monitoring and detects a Radar Waveform above the DFS Detection Threshold, it will inform the Master Device. This is equivalent to the Master Device detecting the Radar Waveform and d) through f) of section 5.1.1 apply.
- d) Irrespective of Client Device or Master Device detection the Channel Move Time and Channel Closing Transmission Time requirements remain the same.
- e) The client test frequency must be monitored to ensure no transmission of any type has occurred for 30 minutes. Note: If the client moves with the master, the device is considered compliant if nothing appears in the client non-occupancy

**- DFS Response requirement values**

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
<p>Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.</p> <p>Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.</p>	

**- Interference Threshold values, Master or Client incorporating In-Service Monitoring**

Maximum Transmit Power	Value (see note)
$\geq 200$ milliwatt	-64 dBm
$< 200$ milliwatt power spectral density $< 10$ dBm/MHz	-62 dBm
EIRP $< 200$ milliwatt that do not meet the power spectral density requirement	-64 dBm

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna  
 Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.  
 Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

**- Radar test waveforms**

Type	Pulse Width ( $\mu$ sec)	PRI ( $\mu$ sec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
<u>0</u>	<u>1</u>	<u>1428</u>	<u>18</u>	<u>See Note 1</u>	<u>See Note 1</u>
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a  Test B: 15 unique PRI values randomly selected within the range of 518-3066 $\mu$ sec, with a minimum increment of 1 $\mu$ sec, excluding PRI values selected in Test A	$\text{Roundup}\left\{\left(\frac{1}{360}\right) \cdot \left(\frac{19 \cdot 10^6}{PRI_{\mu\text{sec}}}\right)\right\}$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.

Note 2: This report was applied Short Pulse Radar Type 0.

\*Short Pulse Radar Test Waveforms

**KCTL Inc.**

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0052  
Page (11) of (17)




Radar Type	Pulse Width (μs)	Chirp Width (MHz)	PRI (μs)	Number of Pulses per Burst	Number of Bursts	Minimum percentage of Successful Detection	Minimum Number of Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

\*Long Pulse Radar Test Waveform

Radar Waveform	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (μs)	Minimum Percentage of Successful Detection	Minimum Trials
6	1	333	9	0.333	300	70%	30

\*Frequency Hopping Radar Test Waveform

**Test setup****- Setup for Client with injection at the Master****- Spectrum analyzer setting parameter**

This setting parameter is shown below and it according to the 905462 D02 UNII DFS Compliance Procedures New Rules.

- 1) RBW/VBW  $\geq 3$  MHz
- 2) Detector = peak
- 3) Span = zero span

**- Conducted test procedure**

- 1) One frequency will be chosen from the Operating Channels of the UUT within the 5 250-5 350 MHz or 5 470-5 725 MHz bands.
- 2) The Client Device (EUT) is set up the above diagram and communications between the Master device and the Client is established.
- 3) Stream the channel loading test file from the Master Device to the Client Device on the test Channel for the entire period of the test.
- 4) An additional 1 dB is added to the radar test signal to ensure it is at or above the DFS Detection Threshold, accounting for equipment variations/errors.
- 5) Observe the transmissions of the UUT at the end of the Burst on the Operating Channel for duration greater than 12 seconds for Radar Type 0 to ensure detection occurs.
- 6) After the initial radar burst the channel is monitored for 30 minutes to ensure no transmissions or beacons occur. A second monitoring setup is used to verify that the Master and Client have both moved to different channels.

**- Master device information**

Equipment Name	Manufacturer	Model No.	Serial No.	FCC ID
Access Point	ASUSTeK Computer Inc	RT-AX88U	J9IAHP000993	MSQ-RTAXHP00

# KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)


Report No.:  
KR22-SRF0052  
Page (13) of (17)




## Test result

### Plot of radar waveform

5 290 MHz



5 530 MHz



# KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0052  
Page (14) of (17)




## Plot of LAN traffic


5 290 MHz



5 530 MHz




Plot of channel move time and aggregate time



Channel move time = 0.772 500 s  
 Closing time = 0.000 625 s x 40 = 0.025 000 s  
 (Closing time : Burst unit time(20 s / 32 001 points) \* Number of burst(between 2 markers))

**UNII-2A: 802.11 ac VHT80, 5 290 MHz**



Channel move time = 0.728 750 s  
 Closing time = 0.000 625 s x 56 = 0.035 000 s  
 (Closing time : Burst unit time(20 s / 32 001 points) \* Number of burst(between 2 markers))

**UNII-2C: 802.11 ac VHT80, 5 530 MHz**

# KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR22-SRF0052  
Page (16) of (17)




## Plot of Non-occupancy period

5 290 MHz



5 530 MHz





## 5. Measurement equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum Analyzer	R&S	FSV3030	1330.5000K30-101710-Wt	22.12.02
SPLITTER	Mini-Circuits	ZX10-2-1252-S+	1633-1	23.01.19
SPLITTER	Mini-Circuits	ZX10-2-1252-S+	1633-2	23.01.19
Attenuator	API Inmet	40AH2W-10	13	22.05.11
Attenuator	API inmet	40AH2W-10	16	22.05.11
Step Attenuator	AGILENT	8495D	MY42144296	23.02.16
Step Attenuator	AGILENT	8495D	MY42144300	23.01.21
DC Power Supply	AGILENT	E3632A	KR75304571	22.05.10
Signal Generator	R&S	SMB100A	176206	23.01.19
Vector Signal Generator	R&S	SMBV100A	257566	22.07.09

**End of test report**