



FCC CFR47 PART 15 SUBPART C

DTS Wireless LAN

CERTIFICATION TEST REPORT

FOR

CDMA Watch + Bluetooth/BLE and DTS b/g/n

MODEL NUMBER : SM-R730V

FCC ID: A3LSMR730C

REPORT NUMBER: 15K21696-E1

ISSUE DATE: SEP 16, 2015

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16675, KOREA

Prepared by
UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



Revision History

Rev.	Issue Date	Revisions	Revised By
--	09/09/15	Initial issue	Junwhan Lee
--	09/15/15	Revised 6dB BW test result of page 14	Junwhan Lee
--	09/16/15	Revised Section 5.2	Junwhan Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>6</i>
4.2. <i>SAMPLE CALCULATION</i>	<i>6</i>
4.3. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>7</i>
5. EQUIPMENT UNDER TEST.....	8
5.1. <i>DESCRIPTION OF EUT</i>	<i>8</i>
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	<i>8</i>
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>8</i>
5.4. <i>WORST-CASE CONFIGURATION AND MODE.....</i>	<i>8</i>
5.5. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>9</i>
6. TEST AND MEASUREMENT EQUIPMENT	11
7. MEASUREMENT METHODS	12
8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS	12
8.1. <i>ON TIME AND DUTY CYCLE RESULTS.....</i>	<i>12</i>
9. SUMMARY TABLE	13
10. ANTENNA PORT TEST RESULTS	14
10.1. <i>6 dB BANDWIDTH</i>	<i>14</i>
10.1.1. <i>802.11b MODE IN THE 2.4 GHz BAND</i>	<i>14</i>
10.1.2. <i>802.11g MODE IN THE 2.4 GHz BAND</i>	<i>14</i>
10.1.3. <i>802.11n HT20 MODE IN THE 2.4 GHz BAND.....</i>	<i>14</i>
10.1.4. <i>6 dB BANDWIDTH PLOTS.....</i>	<i>15</i>
10.2. <i>99% BANDWIDTH</i>	<i>18</i>
10.2.1. <i>802.11b MODE IN THE 2.4 GHz BAND</i>	<i>18</i>
10.2.2. <i>802.11g MODE IN THE 2.4 GHz BAND</i>	<i>18</i>
10.2.3. <i>802.11n HT20 MODE IN THE 2.4 GHz BAND.....</i>	<i>18</i>
10.2.4. <i>99% BANDWIDTH PLOTS.....</i>	<i>19</i>
10.3. <i>OUTPUT POWER.....</i>	<i>22</i>
10.3.1. <i>802.11b MODE IN THE 2.4 GHz BAND</i>	<i>22</i>
10.3.2. <i>802.11g MODE IN THE 2.4 GHz BAND</i>	<i>23</i>
10.3.3. <i>802.11n HT20 MODE IN THE 2.4 GHz BAND.....</i>	<i>23</i>
10.4. <i>PSD.....</i>	<i>24</i>

10.4.1.	802.11b MODE IN THE 2.4 GHz BAND	24
10.4.2.	802.11g MODE IN THE 2.4 GHz BAND	24
10.4.3.	802.11n HT20 MODE IN THE 2.4 GHz BAND.....	24
10.4.4.	PSD PLOTS	25
10.5.	<i>OUT-OF-BAND EMISSIONS</i>	28
10.5.1.	802.11b MODE IN THE 2.4 GHz BAND	29
10.5.2.	802.11g MODE IN THE 2.4 GHz BAND	30
10.5.3.	802.11n HT20 MODE IN THE 2.4 GHz BAND.....	31
11.	RADIATED TEST RESULTS	32
11.1.	<i>LIMITS AND PROCEDURE</i>	32
11.2.	<i>TRANSMITTER ABOVE 1 GHz</i>	33
11.2.1.	TX ABOVE 1 GHz 802.11b MODE IN THE 2.4 GHz BAND.....	33
11.2.2.	TX ABOVE 1 GHz 802.11g MODE IN THE 2.4 GHz BAND.....	43
11.2.3.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 2.4 GHz BAND	53
11.3.	<i>WORST-CASE BELOW 1 GHz</i>	63
12.	AC POWER LINE CONDUCTED EMISSIONS	65
13.	SETUP PHOTOS	68

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: CDMA Watch + Bluetooth/BLE and DTS b/g/n
MODEL NUMBER: SM-R730V
MEID NUMBER: A0000048CC6C3A, A0000048CC6C26 (RADIATED);
A0000048CC6C41 (CONDUCTED)
DATE TESTED: SEP 03, 2015 - SEP 08, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



CY Choi
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
<input checked="" type="checkbox"/>	Chamber 1
<input checked="" type="checkbox"/>	Chamber 2

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	4.14 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a CDMA Watch + Bluetooth/BLE and DTS b/g/n.

This test report addresses the DTS (WLAN) operational mode.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum total conducted output power as follows:

Frequency Range [MHz]	Mode	Output Power [dBm]	Output Power [mW]
2412 - 2462	802.11b	16.85	48.42
	802.11g	13.84	24.21
	802.11n HT20	12.75	18.84

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antennas, with a antenna's maximum gain of -6.8 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Z orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Z orientation.

Based on the baseline scan, the worst-case data rates were:

802.11b mode: 1 Mbps

802.11g mode: 6 Mbps

802.11n HT20 mode: MCS0

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Adapter	SAMSUNG	ETA0U60JBE	DK1G401HS/7-E	N/A
Data Cable	SAMSUNG	ECB-DU2EBE	N/A	N/A
Wireless Charger	SAMSUNG	EP-OR720	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	0.8m	N/A

TEST SETUP

The EUT is a stand-alone unit during the tests. Test software exercised the radio card.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	11-17-15
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	04-25-16
Antenna, Horn, 18 GHz	ETS	3115	00167211	09-20-15
Antenna, Horn, 18 GHz	ETS	3115	00161451	05-17-16
Antenna, Horn, 18 GHz	ETS	3117	00168724	06-17-16
Antenna, Horn, 18 GHz	ETS	3117	00168717	06-17-16
Antenna, Horn, 40 GHz	ETS	3116C	00166255	09-23-15
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	09-29-15
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-18-16
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-18-16
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	08-18-16
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-18-16
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-19-16
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-19-16
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	08-18-16
Average Power Sensor	R&S	NRZ-Z91	102681	08-18-16
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-18-16
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-19-16
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-19-16
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-19-16
Attenuator / Switch driver	HP	11713A	3748A04272	N/A
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	009	08-18-16
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	015	08-18-16
High Pass Filter 5GHz	Micro-Tronics	HPS17542	009	08-18-16
High Pass Filter 6GHz	Micro-Tronics	HPM17543	010	08-18-16
High Pass Filter 5GHz	Micro-Tronics	HPS17542	016	08-18-16
High Pass Filter 6GHz	Micro-Tronics	HPM17543	015	08-18-16
LISN	R&S	ENV-216	101836	08-19-16
LISN	R&S	ENV-216	101837	08-19-16

7. MEASUREMENT METHODS

KDB 558074 D01 DTS Meas Guidance v03r03: Measurement Procedure §9.2.3.1 AVGPM is used for power and §10.2 AVGPSD-2 is used for power spectral density.

Unwanted emissions within Restricted Bands are measured using traditional radiated procedures.

Band edge emissions within Restricted Bands are measured using RMS with duty cycle factor offset method.


8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS

LIMITS

None; for reporting purposes only.

8.1. ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B [msec]	Period [msec]	Duty Cycle x [linear]	Duty Cycle [%]	Duty Cycle Correction Factor [dB]	1/T Minimum VBW [kHz]
2400MHz Bands						
802.11b	8.604	8.706	0.988	98.8%	0.00	0.010
802.11g	1.427	1.531	0.932	93.2%	0.31	0.701
802.11n HT20	1.336	1.437	0.930	93.0%	0.32	0.749



[802.11b Mode]

[802.11g Mode]

[802.11n Mode]

9. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.247 (a)(2)	Occupied Band width (6dB)	>500KHz	Conducted	Pass	8.551 MHz
2.1051, 15.247 (d)	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-29.090 dBm
15.247	TX conducted output power	<30dBm		Pass	16.85 dBm
15.247	PSD	<8dBm		Pass	-14.049 dBm
15.207 (a)	AC Power Line conducted emissions	Section 10	Power Line conducted	Pass	47.78 dBuV (QP)
15.205, 15.209	Radiated Spurious Emission	< 40dBuV/m	Radiated	Pass	36.9 dBuV/m (QP)

10. ANTENNA PORT TEST RESULTS

10.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE

Reference to KDB 558074 D01 DTS Meas Guidance v03r03: The transmitter output is connected to a spectrum analyzer with the RBW set to 100kHz, the VBW $\geq 3 \times$ RBW, peak detector and max hold.

RESULTS

10.1.1. 802.11b MODE IN THE 2.4 GHz BAND

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	Minimum Limit [MHz]
Low	2412	8.997	0.5
Mid	2437	8.551	0.5
High	2462	9.535	0.5
Worst		8.551	0.5


10.1.2. 802.11g MODE IN THE 2.4 GHz BAND


Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	Minimum Limit [MHz]
Low	2412	15.106	0.5
Mid	2437	15.110	0.5
High	2462	15.110	0.5
Worst		15.106	0.5


10.1.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	Minimum Limit [MHz]
Low	2412	15.117	0.5
Mid	2437	15.110	0.5
High	2462	15.101	0.5
Worst		15.101	0.5

10.1.4. 6 dB BANDWIDTH PLOTS







10.2. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

RESULTS

10.2.1. 802.11b MODE IN THE 2.4 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	2412	14.290
Mid	2437	14.191
High	2462	14.224
Worst		14.290

10.2.2. 802.11g MODE IN THE 2.4 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	2412	16.297
Mid	2437	16.269
High	2462	16.329
Worst		16.329




10.2.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	2412	17.445
Mid	2437	17.499
High	2462	17.437
Worst		17.499

10.2.4. 99% BANDWIDTH PLOTS

<p>802.11b Mode Low CH</p>	<p>Keylight Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.412000000 GHz Trig: Free Run #Atten: 34 dB Radio Std: None Radio Device: BTS</p> <p>Ref 20.00 dBm</p> <p>Center 2.412 GHz #Res BW 150 kHz #VBW 470 kHz Span 30 MHz #Sweep 100 ms</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Total Power</td> <td>16.4 dBm</td> </tr> <tr> <td>14.290 MHz</td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>OBW Power</td> <td>99.00 %</td> </tr> <tr> <td>-74.938 kHz</td> <td>x dB</td> <td>-6.00 dB</td> </tr> <tr> <td>x dB Bandwidth</td> <td></td> <td></td> </tr> <tr> <td>7.999 MHz</td> <td></td> <td></td> </tr> </table>	Occupied Bandwidth	Total Power	16.4 dBm	14.290 MHz			Transmit Freq Error	OBW Power	99.00 %	-74.938 kHz	x dB	-6.00 dB	x dB Bandwidth			7.999 MHz		
Occupied Bandwidth	Total Power	16.4 dBm																	
14.290 MHz																			
Transmit Freq Error	OBW Power	99.00 %																	
-74.938 kHz	x dB	-6.00 dB																	
x dB Bandwidth																			
7.999 MHz																			
<p>802.11b Mode Middle CH</p>	<p>Keylight Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.437000000 GHz Trig: Free Run #Atten: 34 dB Radio Std: None Radio Device: BTS</p> <p>Ref 20.00 dBm</p> <p>Center 2.437 GHz #Res BW 150 kHz #VBW 470 kHz Span 30 MHz #Sweep 100 ms</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Total Power</td> <td>16.6 dBm</td> </tr> <tr> <td>14.191 MHz</td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>OBW Power</td> <td>99.00 %</td> </tr> <tr> <td>-16.940 kHz</td> <td>x dB</td> <td>-6.00 dB</td> </tr> <tr> <td>x dB Bandwidth</td> <td></td> <td></td> </tr> <tr> <td>9.540 MHz</td> <td></td> <td></td> </tr> </table>	Occupied Bandwidth	Total Power	16.6 dBm	14.191 MHz			Transmit Freq Error	OBW Power	99.00 %	-16.940 kHz	x dB	-6.00 dB	x dB Bandwidth			9.540 MHz		
Occupied Bandwidth	Total Power	16.6 dBm																	
14.191 MHz																			
Transmit Freq Error	OBW Power	99.00 %																	
-16.940 kHz	x dB	-6.00 dB																	
x dB Bandwidth																			
9.540 MHz																			
<p>802.11b Mode High CH</p>	<p>Keylight Spectrum Analyzer - Occupied BW</p> <p>Center Freq: 2.462000000 GHz Trig: Free Run #Atten: 34 dB Radio Std: None Radio Device: BTS</p> <p>Ref 20.00 dBm</p> <p>Center 2.462 GHz #Res BW 150 kHz #VBW 470 kHz Span 30 MHz #Sweep 100 ms</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Total Power</td> <td>16.6 dBm</td> </tr> <tr> <td>14.224 MHz</td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>OBW Power</td> <td>99.00 %</td> </tr> <tr> <td>-43.955 kHz</td> <td>x dB</td> <td>-6.00 dB</td> </tr> <tr> <td>x dB Bandwidth</td> <td></td> <td></td> </tr> <tr> <td>7.959 MHz</td> <td></td> <td></td> </tr> </table> <p>Alignment Completed</p>	Occupied Bandwidth	Total Power	16.6 dBm	14.224 MHz			Transmit Freq Error	OBW Power	99.00 %	-43.955 kHz	x dB	-6.00 dB	x dB Bandwidth			7.959 MHz		
Occupied Bandwidth	Total Power	16.6 dBm																	
14.224 MHz																			
Transmit Freq Error	OBW Power	99.00 %																	
-43.955 kHz	x dB	-6.00 dB																	
x dB Bandwidth																			
7.959 MHz																			

<p>802.11g Mode Low CH</p>	<p>Center Freq: 2.412000000 GHz Span 30 MHz #Res BW 200 kHz #VBW 620 kHz #Sweep 100 ms</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Total Power</td> <td>13.2 dBm</td> </tr> <tr> <td>16.297 MHz</td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>OBW Power</td> <td>99.00 %</td> </tr> <tr> <td>-6.123 kHz</td> <td>x dB</td> <td>-6.00 dB</td> </tr> <tr> <td>x dB Bandwidth</td> <td></td> <td></td> </tr> <tr> <td>16.03 MHz</td> <td></td> <td></td> </tr> </table>	Occupied Bandwidth	Total Power	13.2 dBm	16.297 MHz			Transmit Freq Error	OBW Power	99.00 %	-6.123 kHz	x dB	-6.00 dB	x dB Bandwidth			16.03 MHz		
Occupied Bandwidth	Total Power	13.2 dBm																	
16.297 MHz																			
Transmit Freq Error	OBW Power	99.00 %																	
-6.123 kHz	x dB	-6.00 dB																	
x dB Bandwidth																			
16.03 MHz																			
<p>802.11g Mode Middle CH</p>	<p>Center Freq: 2.437000000 GHz Span 30 MHz #Res BW 200 kHz #VBW 620 kHz #Sweep 100 ms</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Total Power</td> <td>13.3 dBm</td> </tr> <tr> <td>16.269 MHz</td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>OBW Power</td> <td>99.00 %</td> </tr> <tr> <td>-35.220 kHz</td> <td>x dB</td> <td>-6.00 dB</td> </tr> <tr> <td>x dB Bandwidth</td> <td></td> <td></td> </tr> <tr> <td>14.33 MHz</td> <td></td> <td></td> </tr> </table>	Occupied Bandwidth	Total Power	13.3 dBm	16.269 MHz			Transmit Freq Error	OBW Power	99.00 %	-35.220 kHz	x dB	-6.00 dB	x dB Bandwidth			14.33 MHz		
Occupied Bandwidth	Total Power	13.3 dBm																	
16.269 MHz																			
Transmit Freq Error	OBW Power	99.00 %																	
-35.220 kHz	x dB	-6.00 dB																	
x dB Bandwidth																			
14.33 MHz																			
<p>802.11g Mode High CH</p>	<p>Center Freq: 2.462000000 GHz Span 30 MHz #Res BW 200 kHz #VBW 620 kHz #Sweep 100 ms</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Total Power</td> <td>13.4 dBm</td> </tr> <tr> <td>16.329 MHz</td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>OBW Power</td> <td>99.00 %</td> </tr> <tr> <td>-19.023 kHz</td> <td>x dB</td> <td>-6.00 dB</td> </tr> <tr> <td>x dB Bandwidth</td> <td></td> <td></td> </tr> <tr> <td>14.64 MHz</td> <td></td> <td></td> </tr> </table>	Occupied Bandwidth	Total Power	13.4 dBm	16.329 MHz			Transmit Freq Error	OBW Power	99.00 %	-19.023 kHz	x dB	-6.00 dB	x dB Bandwidth			14.64 MHz		
Occupied Bandwidth	Total Power	13.4 dBm																	
16.329 MHz																			
Transmit Freq Error	OBW Power	99.00 %																	
-19.023 kHz	x dB	-6.00 dB																	
x dB Bandwidth																			
14.64 MHz																			

<p>802.11n Mode Low CH</p>	 <p>Center Freq: 2.41200000 GHz Trig: Free Run #Atten: 34 dB Radio Std: None Radio Device: BTS</p> <p>10 dB/Div Ref 20.00 dBm</p> <p>Center 2.412 GHz #Res BW 200 kHz #VBW 620 kHz Span 30 MHz #Sweep 100 ms</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Total Power</td> <td>12.1 dBm</td> </tr> <tr> <td>17.445 MHz</td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>733 Hz</td> <td>OBW Power</td> </tr> <tr> <td></td> <td></td> <td>99.00 %</td> </tr> <tr> <td>x dB Bandwidth</td> <td>16.68 MHz</td> <td>x dB</td> </tr> <tr> <td></td> <td></td> <td>-6.00 dB</td> </tr> </table>	Occupied Bandwidth	Total Power	12.1 dBm	17.445 MHz			Transmit Freq Error	733 Hz	OBW Power			99.00 %	x dB Bandwidth	16.68 MHz	x dB			-6.00 dB
Occupied Bandwidth	Total Power	12.1 dBm																	
17.445 MHz																			
Transmit Freq Error	733 Hz	OBW Power																	
		99.00 %																	
x dB Bandwidth	16.68 MHz	x dB																	
		-6.00 dB																	
<p>802.11n Mode Middle CH</p>	 <p>Center Freq: 2.43700000 GHz Trig: Free Run #Atten: 34 dB Radio Std: None Radio Device: BTS</p> <p>10 dB/Div Ref 20.00 dBm</p> <p>Center 2.437 GHz #Res BW 200 kHz #VBW 620 kHz Span 30 MHz #Sweep 100 ms</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Total Power</td> <td>12.2 dBm</td> </tr> <tr> <td>17.499 MHz</td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>-7.149 kHz</td> <td>OBW Power</td> </tr> <tr> <td></td> <td></td> <td>99.00 %</td> </tr> <tr> <td>x dB Bandwidth</td> <td>16.28 MHz</td> <td>x dB</td> </tr> <tr> <td></td> <td></td> <td>-6.00 dB</td> </tr> </table>	Occupied Bandwidth	Total Power	12.2 dBm	17.499 MHz			Transmit Freq Error	-7.149 kHz	OBW Power			99.00 %	x dB Bandwidth	16.28 MHz	x dB			-6.00 dB
Occupied Bandwidth	Total Power	12.2 dBm																	
17.499 MHz																			
Transmit Freq Error	-7.149 kHz	OBW Power																	
		99.00 %																	
x dB Bandwidth	16.28 MHz	x dB																	
		-6.00 dB																	
<p>802.11n Mode High CH</p>	 <p>Center Freq: 2.46200000 GHz Trig: Free Run #Atten: 34 dB Radio Std: None Radio Device: BTS</p> <p>10 dB/Div Ref 20.00 dBm</p> <p>Center 2.462 GHz #Res BW 200 kHz #VBW 620 kHz Span 30 MHz #Sweep 100 ms</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>Total Power</td> <td>12.2 dBm</td> </tr> <tr> <td>17.437 MHz</td> <td></td> <td></td> </tr> <tr> <td>Transmit Freq Error</td> <td>-9.918 kHz</td> <td>OBW Power</td> </tr> <tr> <td></td> <td></td> <td>99.00 %</td> </tr> <tr> <td>x dB Bandwidth</td> <td>16.31 MHz</td> <td>x dB</td> </tr> <tr> <td></td> <td></td> <td>-6.00 dB</td> </tr> </table>	Occupied Bandwidth	Total Power	12.2 dBm	17.437 MHz			Transmit Freq Error	-9.918 kHz	OBW Power			99.00 %	x dB Bandwidth	16.31 MHz	x dB			-6.00 dB
Occupied Bandwidth	Total Power	12.2 dBm																	
17.437 MHz																			
Transmit Freq Error	-9.918 kHz	OBW Power																	
		99.00 %																	
x dB Bandwidth	16.31 MHz	x dB																	
		-6.00 dB																	

10.3. OUTPUT POWER

LIMITS

FCC §15.247

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt, based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Duty cycle correction factor is added to the average output power results for duty cycle < 98%.

DIRECTIONAL ANTENNA GAIN

There is only one transmitter output therefore the directional gain is equal to the antenna gain.

TEST PROCEDURE

The transmitter output is connected to a power meter.

The cable assembly insertion loss of 10.1 dB (including 10 dB pad and 0.1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

RESULTS

10.3.1. 802.11b MODE IN THE 2.4 GHz BAND

Limits

Channel	Frequency [MHz]	Directional Gain Primary [dBi]	FCC Power Limit [dBm]	IC Power Limit [dBm]	IC EIRP Limit [dBm]	Max Power [dBm]
Low	2412	-6.80	30.00	30.00	36.00	30.00
Mid	2437	-6.80	30.00	30.00	36.00	30.00
High	2462	-6.80	30.00	30.00	36.00	30.00

Results

Channel	Frequency [MHz]	Primary Meas Power [dBm]	Total Corr'd Power [dBm]	Power Limit [dBm]	Margin [dB]
Low	2412	16.68	16.68	36.00	-19.32
Mid	2437	16.78	16.78	36.00	-19.22
High	2462	16.85	16.85	36.00	-19.15
Worst			16.85	36.00	-19.15

10.3.2. 802.11g MODE IN THE 2.4 GHz BAND

Limits

Channel	Frequency [MHz]	Directional Gain Primary [dBi]	FCC Power Limit [dBm]	IC Power Limit [dBm]	IC EIRP Limit [dBm]	Max Power [dBm]
Low	2412	-6.80	30.00	30.00	36.00	30.00
Mid	2437	-6.80	30.00	30.00	36.00	30.00
High	2462	-6.80	30.00	30.00	36.00	30.00

Results

Channel	Frequency [MHz]	Primary Meas Power [dBm]	Total Corr'd Power [dBm]	Power Limit [dBm]	Margin [dB]
Low	2412	13.62	13.62	36.00	-22.38
Mid	2437	13.72	13.72	36.00	-22.28
High	2462	13.84	13.84	36.00	-22.16
Worst			13.84	36.00	-22.16

10.3.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND

Limits

Channel	Frequency [MHz]	Directional Gain Primary [dBi]	FCC Power Limit [dBm]	IC Power Limit [dBm]	IC EIRP Limit [dBm]	Max Power [dBm]
Low	2412	-6.80	30.00	30.00	36.00	30.00
Mid	2437	-6.80	30.00	30.00	36.00	30.00
High	2462	-6.80	30.00	30.00	36.00	30.00

Results

Channel	Frequency [MHz]	Primary Meas Power [dBm]	Total Corr'd Power [dBm]	Power Limit [dBm]	Margin [dB]
Low	2412	12.56	12.56	36.00	-23.44
Mid	2437	12.65	12.65	36.00	-23.35
High	2462	12.75	12.75	36.00	-23.25
Worst			12.75	36.00	-23.25

10.4. PSD

LIMITS

FCC §15.247

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST PROCEDURE

Power Spectral Density was performed utilizing the “Method AVGPSD-2” under KDB558074 D01 DTS Meas Guidance v03r03

RESULTS

10.4.1. 802.11b MODE IN THE 2.4 GHz BAND

PSD Results

Channel	Frequency [MHz]	PSD Meas [dBm]	Duty Factor [dB]	Final PSD [dBm]	Limit [dBm]	Margin [dB]
Low	2412	-14.502	0.00	-14.50	8.00	-22.50
Mid	2437	-14.778	0.00	-14.78	8.00	-22.78
High	2462	-14.049	0.00	-14.05	8.00	-22.05

10.4.2. 802.11g MODE IN THE 2.4 GHz BAND

PSD Results


Channel	Frequency [MHz]	PSD Meas [dBm]	Duty Factor [dB]	Final PSD [dBm]	Limit [dBm]	Margin [dB]
Low	2412	-19.748	0.31	-19.44	8.00	-27.75
Mid	2437	-20.081	0.31	-19.77	8.00	-28.08
High	2462	-20.025	0.31	-19.72	8.00	-28.03


10.4.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND


PSD Results

Channel	Frequency [MHz]	PSD Meas [dBm]	Duty Factor [dB]	Final PSD [dBm]	Limit [dBm]	Margin [dB]
Low	2412	-21.088	0.32	-20.77	8.00	-29.09
Mid	2437	-20.651	0.32	-20.33	8.00	-28.65
High	2462	-20.844	0.32	-20.52	8.00	-28.84

10.4.4. PSD PLOTS







10.5. OUT-OF-BAND EMISSIONS

LIMITS

FCC §15.247 (d)


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer with RBW = 100 kHz, VBW = 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, bandedge (where measurements to the general radiated limits will not be made) and out-of-band emissions.

RESULTS


10.5.1. 802.11b MODE IN THE 2.4 GHz BAND



10.5.2. 802.11g MODE IN THE 2.4 GHZ BAND



10.5.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND



11. RADIATED TEST RESULTS

11.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements and add duty cycle factor for average measurements. Duty cycle factor= $10\log(1/x)$ For this sample B mode = 0dB (duty cycle >98%); G mode = 0.29dB; N mode = 0.32dB.

The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

11.2. TRANSMITTER ABOVE 1 GHz

11.2.1. TX ABOVE 1 GHz 802.11b MODE IN THE 2.4 GHz BAND

RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117/001687 24_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	37.91	PK	31.7	-19.5	0	50.11	-	-	74	-23.89	190	193	H
2	* 2.386	40.83	PK	31.7	-19.5	0	53.03	-	-	74	-20.97	190	193	H
3	* 2.39	27.87	RMS	31.7	-19.5	0	40.07	54	-13.93	-	-	190	193	H
4	* 2.386	30.58	RMS	31.7	-19.5	0	42.78	54	-11.22	-	-	190	193	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	37.91	PK	31.7	-19.5	0	50.11	-	-	74	-23.89	197	100	V
2	* 2.385	44.49	PK	31.7	-19.5	0	56.69	-	-	74	-17.31	197	100	V
3	* 2.39	29.43	RMS	31.7	-19.5	0	41.63	54	-12.37	-	-	197	100	V
4	* 2.385	36.56	RMS	31.7	-19.5	0	48.76	54	-5.24	-	-	197	100	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	36.26	PK	31.8	-19.4	0	48.66	-	-	74	-25.34	13	110	H
2	2.502	40.66	PK	31.9	-19.3	0	53.26	-	-	74	-20.74	13	110	H
5	2.477	43.1	PK	31.8	-19.4	0	55.5	-	-	-	-	13	110	H
3	* 2.484	28.15	RMS	31.8	-19.4	0	40.55	54	-13.45	-	-	13	110	H
4	* 2.488	29.85	RMS	31.8	-19.4	0	42.25	54	-11.75	-	-	13	110	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	36.95	Pk	31.8	-19.4	0	49.35	-	-	74	-24.65	163	161	V
2	* 2.491	41.72	PK	31.8	-19.4	0	54.12	-	-	74	-19.88	163	161	V
3	* 2.484	27.96	RMS	31.8	-19.4	0	40.36	54	-13.64	-	-	163	161	V
4	* 2.489	32.47	RMS	31.8	-19.4	0	44.87	54	-9.13	-	-	163	161	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector


RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168724)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.92	34.43	PK	33.2	-25.6	0	42.03	-	-	74	-31.97	0-360	100	H
2	7.235	34.41	PK	35.8	-23	0	47.21	-	-	74	-26.79	0-360	200	H
4	9.648	23.97	PK	36.9	-19	0	41.87	-	-	74	-32.13	0-360	100	H
5	* 4.812	25.99	PK	33.9	-25.3	0	34.59	-	-	74	-39.41	0-360	100	H
3	7.236	37.08	PK	35.8	-23	0	49.88	-	-	74	-24.12	0-360	100	V
6	* 4.807	25.56	PK	33.9	-25.3	0	34.16	-	-	74	-39.84	0-360	100	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168724)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 3.918	37.37	PK2	33.2	-25.6	0	44.97	-	-	74	-29.03	16	329	H
* 3.918	24.46	MAv1	33.2	-25.7	0	31.96	54	-22.04	-	-	16	329	H
7.237	35.53	PK2	35.8	-23	0	48.33	-	-	74	-25.67	209	260	H
9.648	32.53	PK2	36.9	-19	0	50.43	-	-	74	-23.57	138	150	H
7.238	34.99	PK2	35.8	-23	0	47.79	-	-	74	-26.21	40	387	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168717_150619)	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.92	32.86	PK	33.3	-30	0	36.16	-	-	74	-37.84	0-360	200	H
4	* 4.874	29.31	PK	34	-29.2	0	34.11	-	-	74	-39.89	0-360	200	H
5	* 7.31	36.97	PK	35.7	-25.7	0	46.97	-	-	74	-27.03	0-360	200	H
2	* 3.92	32.04	PK	33.3	-30	0	35.34	-	-	74	-38.66	0-360	100	V
3	* 4.878	27.73	PK	34	-29.1	0	32.63	-	-	74	-41.37	0-360	100	V
6	* 7.31	33.25	PK	35.7	-25.7	0	43.25	-	-	74	-30.75	0-360	100	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168717_150619)	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 7.312	43.96	PK2	35.7	-25.7	0	53.96	-	-	74	-20.04	100	166	H
* 7.31	37.39	MAv1	35.7	-25.7	0	47.39	54	-6.61	-	-	100	166	H
* 3.915	40.47	PK2	33.3	-30	0	43.77	-	-	74	-30.23	150	220	V
* 3.92	28.89	MAv1	33.3	-30	0	32.19	54	-21.81	-	-	150	220	V
* 3.92	41.22	PK2	33.3	-30	0	44.52	-	-	74	-29.48	191	308	H
* 3.92	30.56	MAv1	33.3	-30	0	33.86	54	-20.14	-	-	191	308	H
* 7.31	42.3	PK2	35.7	-25.7	0	52.3	-	-	74	-21.7	231	348	V
* 7.31	34.36	MAv1	35.7	-25.7	0	44.36	54	-9.64	-	-	231	348	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.92	32.41	PK	33.3	-30	0	35.71	-	-	74	-38.29	0-360	200	H
4	* 7.385	34.2	PK	35.8	-25.1	0	44.9	-	-	74	-29.1	0-360	200	H
5	* 4.924	28.12	PK	34	-29	0	33.12	-	-	74	-40.88	0-360	200	H
2	* 3.92	29.94	PK	33.3	-30	0	33.24	-	-	74	-40.76	0-360	200	V
3	* 7.386	29.13	PK	35.8	-25.1	0	39.83	-	-	74	-34.17	0-360	100	V
6	* 4.93	27.61	PK	34	-29	0	32.61	-	-	74	-41.39	0-360	100	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001 68717)_1 50619	Path_3_3 GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 7.387	41.78	PK2	35.8	-25.1	0	52.48	-	-	74	-21.52	137	185	H
* 7.387	34.63	MAv1	35.8	-25.1	0	45.33	54	-8.67	-	-	137	185	H
* 3.92	40.78	PK2	33.3	-30	0	44.08	-	-	74	-29.92	105	345	H
* 3.92	31.59	MAv1	33.3	-30	0	34.89	54	-19.11	-	-	105	345	H
* 7.386	39.54	PK2	35.8	-25.1	0	50.24	-	-	74	-23.76	232	320	V
* 7.385	31.35	MAv1	35.8	-25.1	0	42.05	54	-11.95	-	-	232	320	V
* 3.923	39.46	PK2	33.3	-30	0	42.76	-	-	74	-31.24	219	112	V
* 3.929	26.79	MAv1	33.3	-30	0	30.09	54	-23.91	-	-	219	112	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

11.2.2. TX ABOVE 1 GHz 802.11g MODE IN THE 2.4 GHz BAND RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24_150619)	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	40.15	PK	31.7	-19.5	0	52.35	-	-	74	-21.65	146	109	H
2	* 2.39	43.56	PK	31.7	-19.5	0	55.76	-	-	74	-18.24	146	109	H
3	* 2.39	30.94	RMS	31.7	-19.5	.3	43.44	54	-10.56	-	-	146	109	H
4	* 2.39	30.78	RMS	31.7	-19.5	.3	43.28	54	-10.72	-	-	146	109	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	40.42	Pk	31.7	-19.5	0	52.62	-	-	74	-21.38	160	100	V
2	* 2.388	42.07	PK	31.7	-19.5	0	54.27	-	-	74	-19.73	160	100	V
3	* 2.39	29.72	RMS	31.7	-19.5	.3	42.22	54	-11.78	-	-	160	100	V
4	* 2.39	29.82	RMS	31.7	-19.5	.3	42.32	54	-11.68	-	-	160	100	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24_150619)	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	38.94	PK	31.8	-19.4	0	51.34	-	-	74	-22.66	4	103	H
2	* 2.484	44.73	PK	31.8	-19.4	0	57.13	-	-	74	-16.87	4	103	H
3	* 2.484	29.32	RMS	31.8	-19.4	.3	42.02	54	-11.98	-	-	4	103	H
4	* 2.484	29.88	RMS	31.8	-19.4	.3	42.58	54	-11.42	-	-	4	103	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	41.06	Pk	31.8	-19.4	0	53.46	-	-	74	-20.54	128	100	V
2	* 2.484	43.65	PK	31.8	-19.4	0	56.05	-	-	74	-17.95	128	100	V
3	* 2.484	30.31	RMS	31.8	-19.4	.3	43.01	54	-10.99	-	-	128	100	V
4	* 2.484	30.44	RMS	31.8	-19.4	.3	43.14	54	-10.86	-	-	128	100	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector


RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168717_150619)	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 3.92	31.99	PK	33.3	-30	0	35.29	-	-	74	-38.71	0-360	200	H
3	7.232	29.45	PK	35.7	-25.5	0	39.65	-	-	74	-34.35	0-360	200	H
6	* 4.824	28.01	PK	34	-29.6	0	32.41	-	-	74	-41.59	0-360	100	H
1	* 3.92	32.42	PK	33.3	-30	0	35.72	-	-	74	-38.28	0-360	200	V
4	7.235	26.17	PK	35.7	-25.5	0	36.37	-	-	74	-37.63	0-360	100	V
5	* 4.822	29.19	PK	34	-29.6	0	33.59	-	-	74	-40.41	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168717)_150619	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 3.917	39.71	PK2	33.3	-30	0	43.01	-	-	74	-30.99	35	378	H
* 3.929	27.83	MAv1	33.3	-30	0	31.13	54	-22.87	-	-	35	378	H
7.234	40.72	PK2	35.7	-25.5	0	50.92	-	-	74	-23.08	235	346	H
7.236	26.01	MAv1	35.7	-25.5	.31	36.52	-	-	-	-	235	346	H
* 3.921	39.87	PK2	33.3	-30	0	43.17	-	-	74	-30.83	123	384	V
* 3.921	27.48	MAv1	33.3	-30	0	30.78	54	-23.22	-	-	123	384	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 7.308	29.84	PK	35.7	-25.7	0	39.84	-	-	74	-34.16	0-360	200	H
4	* 4.874	28.29	PK	34	-29.2	0	33.09	-	-	74	-40.91	0-360	100	H
5	9.748	24.19	PK	37.2	-21.9	0	39.49	-	-	74	-34.51	0-360	200	H
2	* 7.31	27.11	PK	35.7	-25.7	0	37.11	-	-	74	-36.89	0-360	200	V
3	* 4.874	28.23	PK	34	-29.2	0	33.03	-	-	74	-40.97	0-360	200	V
6	9.748	24.05	PK	37.2	-21.9	0	39.35	-	-	74	-34.65	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001 68717)_1 50619	Path_3_3 GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 7.306	41.34	PK2	35.7	-25.7	0	51.34	-	-	74	-22.66	128	166	H
* 7.31	26.09	MAV1	35.7	-25.7	.31	36.4	54	-17.6	-	-	128	166	H
* 7.305	39.71	PK2	35.7	-25.7	0	49.71	-	-	74	-24.29	329	100	V
* 7.311	26.72	MAV1	35.7	-25.7	.31	37.03	54	-16.97	-	-	329	100	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAV1 - KDB558074 Option 1 Maximum RMS Average

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168717)_150619	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.92	34.67	PK	33.3	-30	0	37.97	-	-	74	-36.03	0-360	200	H
2	* 4.917	28.26	PK	34	-29.1	0	33.16	-	-	74	-40.84	0-360	200	H
6	* 7.387	27.03	PK	35.8	-25.1	0	37.73	-	-	74	-36.27	0-360	200	H
3	* 4.917	28.64	PK	34	-29.1	0	33.54	-	-	74	-40.46	0-360	100	V
4	* 3.935	28.82	PK	33.3	-29.9	0	32.22	-	-	74	-41.78	0-360	100	V
5	* 7.389	25.11	PK	35.8	-25.1	0	35.81	-	-	74	-38.19	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168717)_150619	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 3.929	40.13	PK2	33.3	-30	0	43.43	-	-	74	-30.57	347	101	H
* 3.928	27.99	MAv1	33.3	-30	0	31.29	54	-22.71	-	-	347	101	H


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

11.2.3. TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 2.4 GHz BAND RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	43.96	Pk	31.7	-19.5	0	56.16	-	-	74	-17.84	354	110	H
2	* 2.39	44.7	PK	31.7	-19.5	0	56.9	-	-	74	-17.1	354	110	H
3	* 2.39	31.22	RMS	31.7	-19.5	.32	43.74	54	-10.26	-	-	354	110	H
4	* 2.39	31.28	RMS	31.7	-19.5	.32	43.8	54	-10.2	-	-	354	110	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	38.32	PK	31.7	-19.5	0	50.52	-	-	74	-23.48	225	247	V
2	* 2.39	41.32	PK	31.7	-19.5	0	53.52	-	-	74	-20.48	225	247	V
3	* 2.39	29.51	RMS	31.7	-19.5	.32	42.03	54	-11.97	-	-	225	247	V
4	* 2.39	29.22	RMS	31.7	-19.5	.32	41.74	54	-12.26	-	-	225	247	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	39.32	PK	31.8	-19.4	0	51.72	-	-	74	-22.28	135	107	H
2	* 2.484	43.66	PK	31.8	-19.4	0	56.06	-	-	74	-17.94	135	107	H
3	* 2.484	30.12	RMS	31.8	-19.4	.32	42.84	54	-11.16	-	-	135	107	H
4	* 2.484	30.24	RMS	31.8	-19.4	.32	42.96	54	-11.04	-	-	135	107	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	38.11	PK	31.8	-19.4	0	50.51	-	-	74	-23.49	147	157	V
2	* 2.484	42.67	PK	31.8	-19.4	0	55.07	-	-	74	-18.93	147	157	V
3	* 2.484	29.61	RMS	31.8	-19.4	.32	42.33	54	-11.67	-	-	147	157	V
4	* 2.484	29.6	RMS	31.8	-19.4	.32	42.32	54	-11.68	-	-	147	157	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector


RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168724)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.92	35.56	PK	33.2	-25.6	0	43.16	-	-	74	-30.84	0-360	100	H
2	7.233	24.53	PK	35.8	-23	0	37.33	-	-	74	-36.67	0-360	100	H
5	9.647	22.99	PK	36.9	-19	0	40.89	-	-	74	-33.11	0-360	100	H
3	7.235	27.8	PK	35.8	-23	0	40.6	-	-	74	-33.4	0-360	100	V
4	9.647	23.12	PK	36.9	-19	0	41.02	-	-	74	-32.98	0-360	100	V
6	* 3.92	26.85	PK	33.2	-25.6	0	34.45	-	-	74	-39.55	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168724)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 3.919	37.49	PK2	33.2	-25.6	0	45.09	-	-	74	-28.91	91	180	H
* 3.919	24.66	MAv1	33.2	-25.6	0	32.26	54	-21.74	-	-	91	180	H
9.648	32.45	PK2	36.9	-19	0	50.35	-	-	74	-23.65	137	167	H
7.235	40.12	PK2	35.8	-23	0	52.92	-	-	74	-21.08	148	164	V
9.648	32.4	PK2	36.9	-19	0	50.3	-	-	74	-23.7	193	157	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168724)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.92	33.43	PK	33.2	-25.6	0	41.03	-	-	74	-32.97	0-360	100	H
2	* 7.317	24.63	PK	35.9	-22.6	0	37.93	-	-	74	-36.07	0-360	200	H
5	* 4.85	25.66	PK	33.9	-25.3	0	34.26	-	-	74	-39.74	0-360	100	H
6	9.748	21.76	PK	37	-19.3	0	39.46	-	-	74	-34.54	0-360	100	H
3	* 7.312	26.39	PK	35.9	-22.6	0	39.69	-	-	74	-34.31	0-360	100	V
4	* 4.854	26.01	PK	33.9	-25.3	0	34.61	-	-	74	-39.39	0-360	100	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak Detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168724)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 3.919	36.89	PK2	33.2	-25.6	0	44.49	-	-	74	-29.51	340	380	H
* 3.919	24.05	MAv1	33.2	-25.6	0	31.65	54	-22.35	-	-	340	380	H
* 7.318	34.34	PK2	35.9	-22.6	0	47.64	-	-	74	-26.36	238	221	H
* 7.318	21.49	MAv1	35.9	-22.6	.32	35.11	54	-18.89	-	-	238	221	H
* 7.312	34.32	PK2	35.9	-22.6	0	47.62	-	-	74	-26.38	144	199	V
* 7.312	22.14	MAv1	35.9	-22.6	.32	35.76	54	-18.24	-	-	144	199	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168717_150619)	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.92	34.67	Avg	33.3	-30	0	37.97	-	-	74	-36.03	0-360	200	H
2	* 4.917	28.26	Avg	34	-29.1	0	33.16	-	-	74	-40.84	0-360	200	H
6	* 7.387	27.03	Avg	35.8	-25.1	0	37.73	-	-	74	-36.27	0-360	200	H
3	* 4.917	28.64	Avg	34	-29.1	0	33.54	-	-	74	-40.46	0-360	100	V
4	* 3.935	28.82	Avg	33.3	-29.9	0	32.22	-	-	74	-41.78	0-360	100	V
5	* 7.389	25.11	Avg	35.8	-25.1	0	35.81	-	-	74	-38.19	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Avg - Video bandwidth < Resolution bandwidth

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00168717_150619)	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 3.929	40.13	PK2	33.3	-30	0	43.43	-	-	74	-30.57	347	101	H
* 3.928	27.99	MAv1	33.3	-30	0	31.29	54	-22.71	-	-	347	101	H


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK2 - KDB558074 Method: Maximum Peak


MAv1 - KDB558074 Option 1 Maximum RMS Average

11.3. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)



Below 1G Data
 Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163-749	Below_1G	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	50.1025	46.04	Pk	14.1	-30.7	29.44	40	-10.56	0-360	300	H
2	85.6325	61.25	Pk	8.5	-30.6	39.15	40	-.85	0-360	200	H
4	* 37.65	52.7	Pk	11.8	-30.8	33.7	40	-6.3	0-360	300	V
5	50.485	58.2	Pk	14	-30.7	41.5	40	1.5	0-360	100	V
6	60.1325	56.21	Pk	12.7	-30.7	38.21	40	-1.79	0-360	100	V
3	236.3	59.77	Pk	12.2	-30.1	41.87	46.02	-4.15	0-360	100	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

Radiated Emissions

Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163-749	Below_1G	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
50.1025	42.35	Qp	14.1	-30.7	25.75	40	-14.25	43	300	H
85.6325	58.11	Qp	8.5	-30.6	36.01	40	-3.99	179	200	H
* 37.65	40.41	Qp	11.8	-30.8	21.41	40	-18.59	118	300	V
50.485	53.6	Qp	14	-30.7	36.9	40	-3.1	80	101	V
60.1325	52.78	Qp	12.7	-30.7	34.78	40	-5.22	140	101	V
236.3	54.67	Qp	12.2	-30.1	36.77	46.02	-9.25	99	101	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Qp - Quasi-Peak detector

12. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10 2009.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

6 WORST EMISSIONS

LINE 1 PLOT



LINE 1 RESULTS


Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_w ith ex-cord_L1	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
1	.267	26.31	Pk	9.8	0	36.11	61.21	-25.1	-	-
2	.2805	16.4	Av	9.8	0	26.2	-	-	50.8	-24.6
3	.564	27.96	Pk	10.1	0	38.06	56	-17.94	-	-
4	.564	18.92	Av	10.1	0	29.02	-	-	46	-16.98
5	.654	30.53	Pk	10.1	0	40.63	56	-15.37	-	-
6	.654	20.51	Av	10.1	0	30.61	-	-	46	-15.39
7	3.7365	33.85	Pk	9.8	.1	43.75	56	-12.25	-	-
8	3.714	19.96	Av	9.8	.1	29.86	-	-	46	-16.14
9	5.7615	36.05	Pk	9.8	.1	45.95	60	-14.05	-	-
10	5.7705	21.24	Av	9.8	.1	31.14	-	-	50	-18.86
11	7.3545	35.34	Pk	9.9	.1	45.34	60	-14.66	-	-
12	7.359	20.46	Av	9.9	.1	30.46	-	-	50	-19.54

Pk - Peak detector

Av - Average detection

LINE 2 PLOT



LINE 2 RESULTS

Phase N .15 - 30MHz										
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_w ith ex-cord_N	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
13	.1905	28.82	Pk	10	0	38.82	64.01	-25.19	-	-
14	.186	14.26	Av	10	0	24.26	-	-	54.21	-29.95
15	.564	29.22	Pk	10.1	0	39.32	56	-16.68	-	-
16	.564	18.6	Av	10.1	0	28.7	-	-	46	-17.3
17	.654	31.62	Pk	10	0	41.62	56	-14.38	-	-
18	.645	20.94	Av	10	0	30.94	-	-	46	-15.06
19	3.6195	34.88	Pk	9.8	.1	44.78	56	-11.22	-	-
20	3.6375	18.49	Av	9.8	.1	28.39	-	-	46	-17.61
21	5.9145	36.34	Pk	9.8	.1	46.24	60	-13.76	-	-
22	5.9145	19.9	Av	9.8	.1	29.8	-	-	50	-20.2
23	7.251	35.51	Pk	9.9	.1	45.51	60	-14.49	-	-
24	7.251	19.24	Av	9.9	.1	29.24	-	-	50	-20.76

Pk - Peak detector

Av - Average detection