



SAR EVALUATION REPORT

FCC 47 CFR § 2.1093
IEEE Std 1528-2013

For
Bluetooth/BLE & WLAN 2.4GHz b/g/n Wrist Device

FCC ID: A3LSMR732DG
Model Name: SM-R732

Report Number: 16K23469-S1V1
Issue Date: 6/7/2016

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 443-742, KOREA

Prepared by
UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-823, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



TL-637

Revision History

Rev.	Date	Revisions	Revised By
V1	6/7/2016	Initial Issue	Sunghoon Kim

Table of Contents

1. Attestation of Test Results	4
2. Test Specification, Methods and Procedures.....	5
3. Facilities and Accreditation.....	5
4. SAR Measurement System & Test Equipment	6
4.1. <i>SAR Measurement System.....</i>	6
4.2. <i>SAR Scan Procedures.....</i>	7
4.3. <i>Test Equipment.....</i>	9
5. Measurement Uncertainty.....	9
6. Device Under Test (DUT) Information	10
6.1. <i>DUT Description</i>	10
6.2. <i>Wireless Technologies.....</i>	10
6.3. <i>Nominal and Maximum Output Power.....</i>	11
7. RF Exposure Conditions (Test Configurations)	11
8. Dielectric Property Measurements & System Check	12
8.1. <i>Dielectric Property Measurements</i>	12
8.2. <i>System Check.....</i>	14
9. Conducted Output Power Measurements.....	16
9.1. <i>Wi-Fi 2.4GHz (DTS Band)</i>	16
9.2. <i>Bluetooth</i>	16
10. Measured and Reported (Scaled) SAR Results.....	17
10.1. <i>Wi-Fi (DTS Band)</i>	18
10.2. <i>Bluetooth.....</i>	18
11. SAR Measurement Variability.....	19
12. Simultaneous Transmission SAR Analysis	19
Appendices	20
16K23469-S1V1 FCC Report SAR_App A_Photos & Ant. Locations.....	20
16K23469-S1V1 FCC Report SAR_App B_Highest SAR Test Plots.....	20
16K23469-S1V1 FCC Report SAR_App C_System Check Plots.....	20
16K23469-S1V1 FCC Report SAR_App D_SAR Tissue Ingredients	20
16K23469-S1V1 FCC Report SAR_App E_Probe Cal. Certificates	20
16K23469-S1V1 FCC Report SAR_App F_Dipole Cal. Certificates.....	20

1. Attestation of Test Results

Applicant Name	SAMSUNG ELECTRONICS CO.,LTD.		
FCC ID	A3LSMR732DG		
Model Name	SM-R732		
Applicable Standards	FCC 47 CFR § 2.1093 Published RF exposure KDB procedures IEEE Std 1528-2013		

SAR Limits (W/Kg)

Exposure Category	Peak spatial-average(1g of tissue)	Extremities (hands, wrists, ankles, etc.) (10g of tissue)
General population / Uncontrolled exposure	1.6	4.0

The Highest Reported SAR (W/kg)

RF Exposure Conditions	Equipment Class				
	Licensed	DTS	U-NII	DSS (BT)	
Extremity (Wrist)	N/A	0.516	N/A	0.224	
Next-to-Mouth		0.185		0.061	
Date Tested	5/20/2016 to 6/2/2016				
Test Results	Pass				

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released By:



Prepared By:



Justin Park
Senior Engineer
UL Korea, Ltd. Suwon Laboratory

Sunghoon Kim
Laboratory Engineer
UL Korea, Ltd. Suwon Laboratory

2. Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1093, IEEE STD 1528-2013, the following FCC Published RF exposure [KDB](#) procedures:

- o 248227 D01 802.11 Wi-Fi SAR v02r02
- o 447498 D01 General RF Exposure Guidance v06
- o 690783 D01 SAR Listings on Grants v01r03
- o 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04
- o 865664 D02 RF Exposure Reporting v01r02

3. Facilities and Accreditation

The test sites and measurement facilities used to collect data are located at

Suwon
SAR 1 Room
SAR 2 Room
SAR 3 Room


UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637.

The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. SAR Measurement System & Test Equipment

4.1. SAR Measurement System

The DASY5 system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

4.2. SAR Scan Procedures

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 2.1 mm. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE Standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

Zoom Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

		≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}		≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm*	$3 - 4$ GHz: ≤ 5 mm* $4 - 6$ GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$ graded grid	≤ 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
		$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$
Minimum zoom scan volume	x, y, z	≥ 30 mm	$3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the area scan based *1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

Step 5: Z-Scan (FCC only)

The Z Scan measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. In order to get a reasonable extrapolation the extrapolated distance should not be larger than the step size in Z-direction.

4.3. Test Equipment

The measuring equipment used to perform the tests documented in this report has been calibrated in accordance with the manufacturers' recommendations, and is traceable to recognized national standards.

Dielectric Property Measurements

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Network Analyzer	Agilent	E5071C	MY46522054	8-18-2016
Dielectric Assessment Kit	SPEAG	DAK-3.5	1196	8-4-2016
Shorting block	SPEAG	DAK-3.5 Short	SM DAK 200 BA	N/A
Thermometer	LKM	DTM3000	3424	8-19-2016
Thermometer	Lutron	MHB-382SD	AH.91478	8-12-2016

System Check

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
MXG Analog Signal Generator	Agilent	N5181A	MY50145882	8-18-2016
Power Sensor	Agilent	U2000A	MY54260010	8-18-2016
Power Sensor	Agilent	U2000A	MY54260007	8-18-2016
Power Amplifier	EXODUS	1410025-AMP2027-10003	10003	8-18-2016
Directional Coupler	Agilent	778D	MY52180432	8-18-2016
Low Pass Filter	FILTRON	L14012FL	1410003S	8-18-2016
Attenuator	Agilent	8491B/003	MY39269292	8-18-2016
Attenuator	Agilent	8491B/010	MY39269315	8-18-2016
Attenuator	Agilent	8491B/020	MY39269298	8-18-2016
E-Field Probe (SAR1)	SPEAG	EX3DV4	7314	9-25-2016
Data Acquisition Electronics (SAR1)	SPEAG	DAE4	1447	9-23-2016
System Validation Dipole	SPEAG	D2450V2	939	9-28-2016
Thermometer (SAR1)	Lutron	MHB-382SD	AH.91463	8-12-2016

Others

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	8-18-2016

5. Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

6. Device Under Test (DUT) Information

6.1. DUT Description

Intended Use	This device should be restricted to wrist-worn and no other operation configuration should be used		
Device Dimension	Overall (Length x Width): 45.4 mm x 41.0 mm		
Back Cover	<input checked="" type="checkbox"/> The rechargeable battery is not user accessible.		
Battery Options	<input checked="" type="checkbox"/> The rechargeable battery is not user accessible.		
Wireless Router (Hotspot)	Wi-Fi Hotspot mode permits the device to share its cellular data connection with other Wi-Fi-enabled devices. <input type="checkbox"/> Mobile Hotspot (Wi-Fi 2.4 GHz)		
Wi-Fi Direct	Wi-Fi Direct enabled devices transfer data directly between each other <input checked="" type="checkbox"/> Wi-Fi Direct (Wi-Fi 2.4 GHz)		
Test sample information	No.	S/N	Notes
	1	R3AG9004UL	CONDUCTED
	2	R3AG900E50X	SAR

6.2. Wireless Technologies

Wireless technologies	Frequency bands	Operating mode	Duty Cycle used for SAR testing
Wi-Fi	2.4 GHz	802.11b 802.11g 802.11n (HT20)	100%
Bluetooth	2.4 GHz	Version 4.1 LE	76.96 %

6.3. Nominal and Maximum Output Power

KDB 447498 sec.4.1.(3) at the maximum rated output power and within the tune-up tolerance range specified for the product, but not more than 2 dB lower than the maximum tune-up tolerance limit

Upper limit (dB):		0.5	Max. RF Output Power (dBm)	
RF Air interface	Mode	Target	Max. tune-up tolerance limit	
WiFi 2.4 GHz	802.11b (CH.2 ~ CH.11)	17.0	17.5	
	802.11b (CH.1)	15.0	15.5	
	802.11b (CH.12)	12.0	12.5	
	802.11b (CH.13)	6.0	6.5	
	802.11g (CH.1 ~ CH.11)	14.0	14.5	
	802.11g (CH.12)	12.0	12.5	
	802.11g (CH.13)	6.0	6.5	
	802.11n HT20 (CH.1 ~ CH.11)	13.0	13.5	
	802.11n HT20 (CH.12)	12.0	12.5	
	802.11n HT 20 (CH.13)	6.0	6.5	
Bluetooth		13.0	13.5	
Bluetooth LE		6.0	6.5	

7. RF Exposure Conditions (Test Configurations)

Refer to “SAR Photos and Ant locations” Appendix for the specific details of the antenna-to-antenna and antenna-to-edge(s) distances.

Wireless technologies	RF Exposure Conditions	DUT-to-User Separation	Test Position	Antenna-to-edge/surface	SAR Required	Note
WLAN	Extremity (Hand/Wrist/Ankle)	0 mm	Rear	N/A	Yes	
	Next-to-Mouth	10 mm	Front	N/A	Yes	
Bluetooth	Extremity (Hand/Wrist/Ankle)	0 mm	Rear	N/A	Yes	
	Next-to-Mouth	10 mm	Front	N/A	Yes	

8. Dielectric Property Measurements & System Check

8.1. Dielectric Property Measurements

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 – 4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

Tissue Dielectric Parameters

FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00

IEEE Std 1528-2013

Refer to Table 3 within the IEEE Std 1528-2013

Dielectric Property Measurements Results:**SAR 1 Room**

Date	Freq. (MHz)	Liquid Parameters		Measured	Target	Delta (%)	Limit ±(%)	
5-20-2016	Body 2450	e'	50.8500	Relative Permittivity (ϵ_r):	50.85	52.70	-3.51	5
		e"	14.3200	Conductivity (σ):	1.95	1.95	0.04	5
	Body 2410	e'	50.9800	Relative Permittivity (ϵ_r):	50.98	52.76	-3.37	5
		e"	14.1400	Conductivity (σ):	1.89	1.91	-0.66	5
	Body 2475	e'	50.7500	Relative Permittivity (ϵ_r):	50.75	52.67	-3.64	5
		e"	14.4200	Conductivity (σ):	1.98	1.99	-0.03	5
5-20-2016	Head 2450	e'	37.7100	Relative Permittivity (ϵ_r):	37.71	39.20	-3.80	5
		e"	13.8400	Conductivity (σ):	1.89	1.80	4.74	5
	Head 2410	e'	37.8900	Relative Permittivity (ϵ_r):	37.89	39.28	-3.54	5
		e"	13.7300	Conductivity (σ):	1.84	1.76	4.51	5
	Head 2475	e'	37.5900	Relative Permittivity (ϵ_r):	37.59	39.17	-4.03	5
		e"	13.9000	Conductivity (σ):	1.91	1.83	4.70	5
6-2-2016	Body 2450	e'	52.2300	Relative Permittivity (ϵ_r):	52.23	52.70	-0.89	5
		e"	14.5300	Conductivity (σ):	1.98	1.95	1.51	5
	Body 2410	e'	52.3300	Relative Permittivity (ϵ_r):	52.33	52.76	-0.81	5
		e"	14.3500	Conductivity (σ):	1.92	1.91	0.81	5
	Body 2475	e'	52.1400	Relative Permittivity (ϵ_r):	52.14	52.67	-1.00	5
		e"	14.6500	Conductivity (σ):	2.02	1.99	1.56	5
6-2-2016	Head 2450	e'	37.4400	Relative Permittivity (ϵ_r):	37.44	39.20	-4.49	5
		e"	13.6100	Conductivity (σ):	1.85	1.80	3.00	5
	Head 2410	e'	37.5500	Relative Permittivity (ϵ_r):	37.55	39.28	-4.40	5
		e"	13.5100	Conductivity (σ):	1.81	1.76	2.84	5
	Head 2475	e'	37.3500	Relative Permittivity (ϵ_r):	37.35	39.17	-4.64	5
		e"	13.6700	Conductivity (σ):	1.88	1.83	2.97	5

8.2. System Check

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are re-measured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

System Performance Check Measurement Conditions:

- The measurements were performed in the flat section of the TWIN SAM or ELI phantom, shell thickness: 2.0 ± 0.2 mm (bottom plate) filled with Body or Head simulating liquid of the following parameters.
- The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm for SAR measurements ≤ 3 GHz and ≥ 10.0 cm for measurements > 3 GHz.
- The DASY system with an E-Field Probe was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) and 15 mm (below 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole.
For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 7x7x7 (below 3 GHz) and/or 8x8x7 (above 3 GHz) fine cube was chosen for the cube.
- Distance between probe sensors and phantom surface was set to 3 mm.
For 5 GHz band - Distance between probe sensors and phantom surface was set to 2.5 mm
- The dipole input power (forward power) was 100 mW.
- The results are normalized to 1 W input power.

Reference Target SAR Values

The reference SAR values can be obtained from the calibration certificate of system validation dipoles

System Dipole	Serial No.	Cal. Date	Freq. (MHz)	Target SAR Values (W/kg)		
				1g/10g	Head	Body
D2450V2	939	9-28-2015	2450	1g	51.60	50.70
				10g	23.90	23.70

System Check Results

The 1-g and 10-g SAR measured with a reference dipole, using the required tissue-equivalent medium at the test frequency, must be within 10% of the manufacturer calibrated dipole SAR target.

SAR 1 Room

Date Tested	System Dipole		T.S. Liquid	Measured Results		Target (Ref. Value)	Delta ±10 %	Plot No.
	Type	Serial #		Zoom Scan to 100 mW	Normalize to 1 W			
05-20-2016	D2450V2	939	Body	1g	5.29	52.90	50.70	4.34
				10g	2.45	24.50	23.70	3.38
05-20-2016	D2450V2	939	Head	1g	5.31	53.10	51.60	2.91
				10g	2.43	24.30	23.90	1.67
06-02-2016	D2450V2	939	Body	1g	5.25	52.50	50.70	3.55
				10g	2.44	24.40	23.70	2.95
06-02-2016	D2450V2	939	Head	1g	5.28	52.80	51.60	2.33
				10g	2.43	24.30	23.90	1.67

9. Conducted Output Power Measurements

9.1. Wi-Fi 2.4GHz (DTS Band)

Measured Results

Band (GHz)	Mode	Data Rate	Ch #	Freq. (MHz)	Avg Pwr (dBm)	Max Output Power (dBm)	SAR Test (Yes/No)	Note(s)		
2.4	802.11b	1 Mbps	1	2412	15.0	15.5	Yes			
			6	2437	16.3	17.5				
			11	2462	16.4					
			12	2467	12.3	12.5				
			13	2472	5.6					
	802.11g	6 Mbps	1	2412	Not PWR Meas. require	14.5	No	1		
			6	2437						
			11	2462						
			12	2467		12.5				
			13	2472		6.5				
	802.11n (HT20)	6.5 Mbps	1	2412	Not PWR Meas. require	13.5	No	1		
			6	2437						
			11	2462						
			12	2467		12.5				
			13	2472		6.5				

Note(s):

1. Output Power and SAR is not required for 802.11g/n HT20 channels when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

9.2. Bluetooth

Band (GHz)	Mode	Ch #	Freq. (MHz)	Avg Pwr (dBm)
2.4	V3.0 + EDR, GFSK	0	2402	12.2
		39	2441	11.4
		78	2480	11.3
	V3.0 + EDR, $\pi/4$ DQPSK	0	2402	8.0
		39	2441	7.3
		78	2480	6.9
	V3.0 + EDR, 8-DPSK	0	2402	8.1
		39	2441	7.3
		78	2480	6.9
	V4.0 LE, GFSK	0	2402	0.8
		19	2440	0.2
		39	2480	-0.6

10. Measured and Reported (Scaled) SAR Results

SAR Test Reduction criteria are as follows:

KDB 248227 D01 SAR meas for 802.11 v02:

SAR test reduction for 802.11 Wi-Fi transmission mode configurations are considered separately for DSSS and OFDM. An initial test position is determined to reduce the number of tests required for certain exposure configurations with multiple test positions. An initial test configuration is determined for each frequency band and aggregated band according to maximum output power, channel bandwidth, wireless mode configurations and other operating parameters to streamline the measurement requirements. For 2.4 GHz DSSS, either the initial test position or DSSS procedure is applied to reduce the number of SAR tests; these are mutually exclusive. For OFDM, an initial test position is only applicable to next to the ear, UMPC mini-tablet and hotspot mode configurations, which is tested using the initial test configuration to facilitate test reduction. For other exposure conditions with a fixed test position, SAR test reduction is determined using only the initial test configuration.

The multiple test positions require SAR measurements in head, hotspot mode or UMPC mini-tablet configurations may be reduced according to the highest reported SAR determined using the initial test position(s) by applying the DSSS or OFDM SAR measurement procedures in the required wireless mode test configuration(s). The initial test position(s) is measured using the highest measured maximum output power channel in the required wireless mode test configuration(s). When the reported SAR for the initial test position is:

- $\leq 0.4/1$ W/kg, 1-g and 10-g respectively, further SAR measurement is not required for the other test positions in that exposure configuration and wireless mode combination within the frequency band or aggregated band. DSSS and OFDM configurations are considered separately according to the required SAR procedures.
- $> 0.4/1$ W/kg, 1-g and 10-g respectively, SAR is repeated using the same wireless mode test configuration tested in the initial test position to measure the subsequent next closest/smallest test separation distance and maximum coupling test position, on the highest maximum output power channel, until the reported SAR is $\leq 0.8/2$ W/kg, 1-g and 10-g respectively, or all required test positions are tested.
 - For subsequent test positions with equivalent test separation distance or when exposure is dominated by coupling conditions, the position for maximum coupling condition should be tested.
 - When it is unclear, all equivalent conditions must be tested.
- For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is $> 0.8/2$ W/kg, 1-g and 10-g respectively, measure the SAR for these positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is $\leq 1.2/3$ W/kg, 1-g and 10-g respectively, or all required test channels are considered.
 - The additional power measurements required for this step should be limited to those necessary for identifying subsequent highest output power channels to apply the test reduction.
- When the specified maximum output power is the same for both UNII 1 and UNII 2A, begin SAR measurements in UNII 2A with the channel with the highest measured output power. If the reported SAR for UNII 2A is $\leq 1.2/3$ W/kg, 1-g and 10-g respectively, SAR is not required for UNII 1; otherwise treat the remaining bands separately and test them independently for SAR.
- When the specified maximum output power is different between UNII 1 and UNII 2A, begin SAR with the band that has the higher specified maximum output. If the highest reported SAR for the band with the highest specified power is $\leq 1.2/3$ W/kg, 1-g and 10-g respectively, testing for the band with the lower specified output power is not required; otherwise test the remaining bands independently for SAR.

To determine the initial test position, Area Scans were performed to determine the position with the *Maximum Value of SAR (measured)*. The position that produced the highest *Maximum Value of SAR* is considered the worst case position; thus used as the initial test position.

10.1. Wi-Fi (DTS Band)

Frequency Band	Mode	RF Exposure Conditions	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Area Scan Max. SAR (W/kg)	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
								Tune-up limit	Meas.	Meas.	Scaled	Meas.	Scaled	
2.4GHz	802.11b 1 Mbps	Extremity	0	Flat / Rear	11	2462.0	1.024	17.5	16.4			0.398	0.516	1
		Next-to-Mouth	10	Flat / Front	11	2462.0	0.193	17.5	16.4	0.143	0.185			2

Note(s):

1. Highest *reported* SAR is $\leq 0.4/1.0$ W/kg, 1-g and 10-g respectively. Therefore, further SAR measurements within this exposure condition are not required.
2. Highest *reported* SAR is $> 0.4/1.0$ W/kg, 1-g and 10-g respectively. Due to the highest *reported* SAR for this test position, other test positions in Head exposure condition were evaluated until a SAR $\leq 0.8/2.0$ W/kg, for 1-g and 10-g respectively, was *reported*.
3. Testing for a second channel was required because the *reported* SAR for this test position was $>0.8/2.0$ W/kg, for 1-g and 10-g respectively.
4. Additional testing required in order satisfying FCC simultaneous transmission limit criteria.

10.2. Bluetooth

Frequency Band	Mode	RF Exposure Conditions	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		10-g SAR (W/kg)		Plot No.
							Tune-up limit	Meas.	Meas.	Scaled	Meas.	Scaled	
2.4GHz	GFSK	Extremity	0	Flat / Rear	0	2402.0	13.5	12.2			0.165	0.224	3
		Next-to-Mouth	10	Flat / Front	0	2402.0	13.5	12.2	0.045	0.061			4

11. SAR Measurement Variability

In accordance with published RF Exposure KDB 865664 D01 SAR measurement 100 MHz to 6 GHz. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 or 2.0 W/kg (1-g or 10-g respectively); steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 or 2.0 W/kg (1-g or 10-g respectively), repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 or 3.6 W/kg ($\sim 10\%$ from the 1-g or 10-g respective SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 or 3.75 W/kg (1-g or 10-g respectively) and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20

Extremity

Frequency Band (MHz)	Air Interface	RF Exposure Conditions	Test Position	Repeated SAR (Yes/No)	Highest Measured SAR (W/kg)	Repeated Measured SAR (W/kg)	Largest to Smallest SAR Ratio
2400	Wi-Fi 802.11b/g/n	Extremity (Hand/Wrist/Ankle)	Flat / Rear	No	0.398	N/A	N/A
	Bluetooth	Extremity (Hand/Wrist/Ankle)	Flat / Rear	No	0.165	N/A	N/A

Note(s):

Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.2

Next-to-Mouth

Frequency Band (MHz)	Air Interface	RF Exposure Conditions	Test Position	Repeated SAR (Yes/No)	Highest Measured SAR (W/kg)	Repeated Measured SAR (W/kg)	Largest to Smallest SAR Ratio
2400	Wi-Fi 802.11b/g/n	Next to Mouth	Flat / Front	No	0.143	N/A	N/A
	Bluetooth	Next to Mouth	Flat / Front	No	0.045	N/A	N/A

Note(s):

Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.2

12. Simultaneous Transmission SAR Analysis

N/A

Wi-Fi 2.4GHz Radio cannot transmit simultaneously with Bluetooth Radio.

Appendices

Refer to separated files for the following appendixes.

16K23469-S1V1 FCC Report SAR_App A_Photos & Ant. Locations

16K23469-S1V1 FCC Report SAR_App B_Highest SAR Test Plots

16K23469-S1V1 FCC Report SAR_App C_System Check Plots

16K23469-S1V1 FCC Report SAR_App D_SAR Tissue Ingredients

16K23469-S1V1 FCC Report SAR_App E_Probe Cal. Certificates

16K23469-S1V1 FCC Report SAR_App F_Dipole Cal. Certificates

END OF REPORT