EMC TEST REPORT				
Project No.	LBE20190879	Issue No. 1		
	Name of organization	Samsung Electronics Co., Ltd.		
Applicant	Address	(Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea		
	Date of application	July 8, 2019		
	Type of device	<ul> <li>All other Receivers subject to part15</li> <li>Class B Personal Computers and peripherals</li> <li>Other Class B digital devices and peripherals</li> <li>FM Broadcast Receiver</li> </ul>		
	Equipment authorization	Certification Supplier's Declaration of Conformity		
	FCC ID	A3LSMR835		
EUT	Kind of product	Smart Wearable		
	Model No.	SM-R835U		
	Variant Model No.	Refer to clause 4.6		
	Manufacturer	Samsung Electronics Co., Ltd. 94-1, Imsu-dong, Gumi-si, Gyengsangbuk-do, 730-722, Republic of Korea		
Applied Sta	ndards	47 CFR Part 15, Subpart B, Class B / ANSI C63.4-2014		
<b>Test Period</b>		July 10, 2019 ~ July 25, 2019		
Issue date		July 29, 2019		
Test result	: Complied			
The equipment under test has found to be compliant with the applied standards. (Refer to the attached test result for more detail.)				
Tested by : Ji-Yeon Lee     Reviewed by : Young-Hun Kim       J. J. Lee     J. Li				
The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from Global CS Center.				

Global CS Center of Samsung Electronics Co., Ltd.

(Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea

# Table of contents

1.	Report Information	
	1.1 Revision history	3
_		
2.	Summary of test results	
	2.1 Emission	3
3.	General Information	
	3.1 Test facility	3
4.	Test Configuration	
	4.1 Test Peripherals	4
	4.2 EUT operating mode	5
	4.3 Details of Sampling	5
	4.4 Used cable description	6
	4.5 Test arrangement	7
	4.6 EUT Description	9
	4.7 EUT Frequencies	9
	4.8 Test configuration and condition	10
	4.9 Measurement uncertainty	10
5.	Result of individual tests	
	5.1 Conducted disturbance	11
	5.2 Radiated disturbance	15

## 1. Report Information

## 1.1 Revision history

No.	Date of Issue	Revised detailed information	
Issue 0	July 26, 2019	There are no revisions and this version is basic test report.	
Issue 1	July 29, 2019	Variant model is added. (SM-R835F)	

## 1.2 Licensed band test report no.

No.	Remark	
KP19-SRF0098	The cellular receiver mode refers to the radiated spurious emissions test report.	

## 2. Summary of test results

### 2.1 Emission

The EUT has been tested according to the following specifications:

Applied	Test type	Applied standard	Result
	Conducted Disturbance (Mains port)	47 CFR Part 15 Subpart B / ANSI C63.4-2014	Complied
	Radiated Disturbance	(Class B)	Complied

## 3. General Information

### 3.1 Test facility

The Global CS Center is located on Samsung Electronics Co., Ltd. at (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea. All testing are performed in Semi-anechoic chambers conforming to the site attenuation characteristics defined by ANSI C63.4, CISPR 32, CISPR 16-1-4 and Shielded rooms. And all antennas are properly calibrated using ANSI C63.5:2017.

The Global CS Center is operated as testing laboratory in accordance with the requirements of ISO/IEC 17025:2005.

-3/22**-**

## 4. Test Setup configuration

#### **4.1 Test Peripherals**

The cables used for these peripherals are either permanently attached by the peripheral manufacturer or coupled with an assigned cable as defined below.

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

Mark	Description	Model No.	Serial No.	Manufacturer / Trademark	FCC ID
A	Smart Wearable	SM-R835U	-	SAMSUNG	A3LSMR835
В	Battery	EB-BR830ABY	-	SAMSUNG	-
С	Wireless Charger	EP-OR825	-	SAMSUNG	-
D	Travel Adapter	EP-TA50KWK	DK5KB12VS/A-E	SAMSUNG	-
_	Laptop Computer	Latitude5580	1CHRYM2	Dell	-
			D3HRYM2	Dell	-
F	Laptop		5D77	Dell	-
	AC Adapter	LAOSINIVITSU	5B3C	Dell	-
G	Mouse	Mouse AA-SM7PCP	CN57BA5903634ADV 8JK281082	SAMSUNG	-
			CNBA5903634ADV8J 31O3050	SAMSUNG	-
н	Router	DIR-806A	RF0F1D5000688	D-Link	-
			RF0F1D8011504	D-Link	-
I	OTG Gender	EE-UG970	-	SAMSUNG	-

## 4.2 EUT operating mode

To achieve compliance applied standard specification including both JAB and CXX requirement, the following mode(s) were made during compliance testing:

### 4.2.1 Conducted Emission

No.	Operating mode
1	Cellular receiver(LTE FDD B26 Center Frequency) + Wireless Charging (w/TA)
2	Audio playback from internal memory data + Wireless Charging (w/TA)
3	Wireless Charging (w/USB port of Laptop Computer)

## 4.2.2 Radiated Emission

No.	Operating mode
1	Wireless Charging (w/TA)
2	Audio playback from internal memory data
3	Wireless Charging (w/USB port of Laptop Computer)

## 4.3 Details of Sampling

Customer selected, single unit.

#### 4.4 Used cable description

The EUT is configured, installed, arranged and operated in a manner consistent with typical applications. Interface cables/loads/devices are connected to at least one of each type of interface port of the EUT, and where practical, each cable shall be terminated in a device typical of actual usage. The type(s) of interconnecting cables to be used and the interface port (of the EUT) to which these were connected:

No.	Connected cable	Length [m]	Shielded [Y/N]	Note
1	Wireless Charger cable	0.8	No	For Wireless Charger
2	Power	1.8	No	From Laptop to AC Adapter
3	Power	1.5	No	For AC Adapter
4	LAN	1.5	No	From Laptop to Router
5	USB	0.8	No	From Laptop to Router for DC Power
6	USB	1.2	No	From OTG Gender to Mouse

## 4.5 Test arrangement

## 4.5.1 Conducted Emission



[Mode 1 - 2]



[ Mode 3 ]

## 4.5.2 Radiated Emission



[ Mode 1 ]



[ Mode 2 ]



-8/22-

## 4.6 EUT Description

The EUT is a Watch type Smart Wearable which can operate on WCDMA FDD2/4/5, LTE FDD2/4/5/12/13/25/26/66 bands and incorporates a Bluetooth, Wi-Fi, GNSS, NFC, Wireless Charging and Audio.

4.6.1 The variant models

- SM-R835F

### **4.7 EUT Frequencies**

The highest frequencies (Generated and used)	Frequency [ MHz ]	
Bluetooth	2 480	

#### 4.8 Test configuration and condition

The system was configured for testing in a typical fashion that a customer would normally use. Cables were attached to each of the available I/O Ports. Where applicable, peripherals were attached to the I/O cables.

The EUT was investigated in three orientations and the worst case orientation is reported.

The EUT was charged with Wireless Charger connected to Travel Adapter and USB port of Laptop Computer.

Cellular RX mode testing was performed with the LTE FDD26 RX Test mode at center frequency. All licensed communication Cellular RX mode, WCDMA/LTE, test results are not significantly different.

The audio were repetitively played 1 kHz sound.

Power source for the EUT operating was supplied by CVCF made by the Pacific Corp.

#### - Test Voltage : AC 120 V, 60 Hz

#### 4.9 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus: (According to CISPR 16-4-2 and UKAS M3003)

4.9.1 Emission

Test type	Measurement uncertainty (C.L. 95 %, k = 2)	
Conducted disturbance	AC Mains	2.83 dB
Radiated Disturbance	Horizontal	4.99 dB
(Below 1 GHz)	Vertical	4.90 dB
Radiated Disturbance	Horizontal	5.13 dB
(Above 1 GHz)	Vertical	5.12 dB

## 5. Results of individual test

## 5.1 Conducted disturbance

The EUT is connected to a LISN via travel adapter. If the EUT is connected to the Laptop Computer USB port, the Laptop AC adapter is connected to a LISN.

Both conducted lines are measured in Quasi-Peak and CISPR-Average mode, including the worst-case data points for each tested configuration. The EUT measured in accordance with the methods described in standards.

Frequency range Limits	Resolution Bandwidth	Limits [ dB(µV) ]			
[ MHz ]	[ kHz ]	Quasi-peak	Average		
0,15 to 0,50	9	66 to 56	56 to 46		
0,50 to 5	9	56	46		
5 to 30	9	60	50		
NOTE 1 The lower limit shall a	E 1 The lower limit shall apply at the transition frequency.				
NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 N					

#### Limits for conducted disturbance at the mains ports of Class B ITE

#### 5.1.1 Test instrumentation

					Calibration	
EMC No.	Test Instrument	Model name	Manufacturer	rer Serial No.	Date	Interval (Month)
E5I-043	Two-Line V-Network	ENV216	R&S	101630	2018-08-17	12
E5I-017	EMI Test Receiver	ESU8	R&S	100483	2019-01-16	12
E5I-171	LTE Communicator	CMW500	R&S	154667	2018-08-07	12
-	Test software	EMC32	R&S	Ver 9.26.01	-	-

#### 5.1.2 Temperature and humidity condition

Test date	2019-07-25	Test engineer	Ji-Yeon Lee	
	Ambient temperature	(22.8 ~ 23.1) °C	Limit (15.0 to 35.0) ℃	
Climate condition	Relative humidity	(54.1 ~ 54.6) % R.H.	Limit (25.0 to 75.0) % R.H.	
	Atmospheric pressure	(100.3 ~ 100.5) kPa	Limit (86.0 to 106.0) kPa	
Test place	Shield Room (SR8)			

## 5.1.3 Test results

#### □ Operating Mode 1: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

Frequency (MHz)	QP (dBµV)	CAV (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.152	53.3		65.9	12.6	L1	10.1
0.152		34.1	55.9	21.8	L1	10.1
0.202	48.7		63.5	14.8	L1	10.1
0.202		29.9	53.5	23.6	L1	10.1
0.256	43.7		61.6	17.9	L1	10.1
0.256		25.0	51.6	26.6	L1	10.1
0.420	34.3		57.5	23.2	L1	10.4
0.420		23.8	47.5	23.7	L1	10.4
1.876	22.8		56.0	33.2	Ν	9.7
1.876		21.2	46.0	24.8	Ν	9.7
23.516	23.5		60.0	36.5	L1	10.9
23.516		12.8	50.0	37.2	L1	10.9

$\cap P$		final	maggurament	roculte table.
QP	/ UAV	IIIIai	measurement	results table.

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss) Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

-12/22-



#### □ Operating Mode 2: AC Mains

Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

Frequency (MHz)	QP (dBµV)	CAV (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.154		25.5	55.8	30.3	L1	10.1
0.154	47.1		65.8	18.7	L1	10.1
0.213		22.1	53.1	31.0	L1	10.1
0.213	42.9		63.1	20.2	L1	10.1
0.406		19.6	47.7	28.1	L1	10.4
0.406	33.1		57.7	24.6	L1	10.4
0.723		21.8	46.0	24.2	L1	10.3
0.723	27.5		56.0	28.5	L1	10.3
1.013		21.9	46.0	24.1	L1	10.1
1.013	26.6		56.0	29.4	L1	10.1
13.370		19.0	50.0	31.0	L1	10.5
13.370	25.6		60.0	34.4	L1	10.5

QP / CAV final measurement results	s table:
------------------------------------	----------

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss) Margin (QP and/or CAV) = Limit – Level (QP and/or CAV) QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor



#### □ Operating Mode 3: AC Mains

Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

Frequency (MHz)	QP (dBµV)	CAV (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.152	49.7		65.9	16.2	N	9.9
0.152		34.6	55.9	21.3	N	9.9
0.501	37.2		56.0	18.8	L1	10.2
0.501		27.5	46.0	18.5	L1	10.2
4.002	32.4		56.0	23.6	L1	9.8
4.002		21.9	46.0	24.1	L1	9.8
4.205		21.8	46.0	24.2	L1	9.8
4.205	29.8		56.0	26.2	L1	9.8
9.940	29.2		60.0	30.8	L1	9.9
9.940		24.4	50.0	25.6	L1	9.9
26.624		24.6	50.0	25.4	N	10.0
26.624	25.2		60.0	34.8	N	10.0

QP / CAV final measurement results	s table:
------------------------------------	----------

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss) Margin (QP and/or CAV) = Limit – Level (QP and/or CAV) QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

#### 5.2 Radiated disturbance

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin.

Peak measurements were made over the changeable frequency range 30 MHz to 1 GHz at a measurement distance of 10 m for the following antenna and turntable arrangements:

Antenna Height [ cm ]	Antenna Polarisation	Resolution Bandwidth [ kHz ]	Video Bandwidth [ kHz ]	Turntable position [ degrees ]
100 ~ 400	Horizontal, Vertical	120	300	Continuous

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using quasi-peak detector.

Peak/CISPR-Average measurements were made over the changeable frequency range 1 GHz to 40 GHz or 5th harmonics of the highest frequency generated or used in the device or on which the device operate or tunes at a measurement distance of 3 m for the following antenna and turntable arrangements. The measurements above 1 GHz were performed with the bore-sighting antenna aimed at the EUT.

Antenna Height [ cm ]	Antenna Polarisation	Resolution Bandwidth [ MHz ]	Video Bandwidth [ MHz ]	Turntable position
100 ~ 400	Horizontal, Vertical	1	3	Continuous

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using peak and CISPR-average detectors.

#### Limits for radiated disturbance of Class B ITE at a measuring distance of 3 m and 10 m

Frequency range Limits	Field Strength				
[ MHz ]	3 m [ µV/m ]	3 m [ dB(µV/m) ]	10 m [ dB(µV/m) ]		
30 to 88	100	40.0	29.5		
88 to 216	150	43.5	33.0		
216 to 960	200	46.0	35.5		
Above 960	500	54.0	43.5		

Results checked manually; and points close to the limit line were re-measured.

-15/22-

## 5.2.1 Test instrumentation

				Calibra		
EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Date	Interval (Month)
E5I-016	EMI Test Receiver	ESU8	R&S	100482	2019-05-29	12
E5I-021	EMI Test Receiver	ESU40	R&S	100376	2019-01-30	12
E5I-149	Horn Antenna	HF907	R&S	102525	2018-06-15	24
E5I-039	Signal Conditioning Unit	SCU-18	R&S	10211	2019-01-23	12
E5I-120	BiLog Antenna	CBL6112D	TESEQ	36997	2018-04-23	24
E5I-072	BiLog Antenna	CBL6112D	TESEQ	36009	2018-04-23	24
E5I-073	Preamplifier	310N	SONOMA	332016	2019-05-09	12
E5I-074	Preamplifier	310N	SONOMA	332017	2019-05-09	12
-	Test software	EP7RE	ΤΟΥΟ	Ver 5.8.2	-	-
-	Test software	EMC32	R&S	Ver 9.25.00	-	-

## 5.2.2 Temperature and humidity condition

Test date	2019-07-10 ~ 2019-07-11	Test engineer	Ji-Yeon Lee				
Climate condition	Ambient temperature	(23.1 ~ 23.7) °C	Limit (15.0 to 35.0) °C				
	Relative humidity	(49.8 ~ 50.7) % R.H.	Limit (25.0 to 75.0) % R.H.				
	Atmospheric pressure	(100.4 ~ 100.7) kPa	Limit (86.0 to 106.0) kPa				
Test place	Semi-Anechoic Chamber (SAC4)						

#### 5.2.3 Test results

#### □ Operating Mode 1

#### - Frequencies below 1 GHz



Note1) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 10 m, Antenna Height : 1 to 4 meters Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain) Margin (QP) = Limit – Level (QP) QP = Quasi-Peak, c.f = Correction Factor



#### - Frequencies above 1 GHz

Note 1) Receiving antenna polarization : Horizontal, Vertical Test Distance : 3 m, Antenna Height : 1 to 4 meters Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain) Margin (PK and/or CAV) = Limit – Level (PK and/or CAV) PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

#### □ Operating Mode 2

#### - Frequencies below 1 GHz



Note1) Receiving antenna polarization : Horizontal, Vertical Test Distance : 10 m, Antenna Height : 1 to 4 meters Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain) Margin (QP) = Limit – Level (QP) QP = Quasi-Peak, c.f = Correction Factor



#### - Frequencies above 1 GHz

Note 1) Receiving antenna polarization : Horizontal, Vertical Test Distance : 3 m, Antenna Height : 1 to 4 meters Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain) Margin (PK and/or CAV) = Limit – Level (PK and/or CAV) PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

#### □ Operating Mode 3

#### - Frequencies below 1 GHz



Note1) Receiving antenna polarization : Horizontal, Vertical Test Distance : 10 m, Antenna Height : 1 to 4 meters Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain) Margin (QP) = Limit – Level (QP) QP = Quasi-Peak, c.f = Correction Factor

#### Project No. : LBE20190879

#### Smart Wearable : SM-R835U



#### - Frequencies above 1 GHz

Frequency (MHz)	PK (dBµV/m)	CAV (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1 004.800		25.6	54.0	28.4	125.0	V	105.0	7.0
1 102.800	42.0		74.0	32.0	250.0	Н	41.0	6.5
1 327.200	43.8		74.0	30.2	130.0	V	10.0	7.8
1 327.200		26.4	54.0	27.6	100.0	V	10.0	7.8
1 661.200	41.3		74.0	32.7	111.0	V	134.0	10.2
1 665.200		28.6	54.0	25.4	195.0	V	152.0	10.3
2 129.200		31.3	54.0	22.7	173.0	V	32.0	12.9
2 129.200	51.9		74.0	22.1	105.0	V	32.0	12.9
2 660.400		32.7	54.0	21.3	100.0	V	283.0	15.4
2 660.400	49.3		74.0	24.7	158.0	V	283.0	15.4
17 971.500		43.9	54.0	10.1	210.0	Н	221.0	34.9
17 998.000	49.9		74.0	24.1	265.0	Н	0.0	35.3

Note 1) Receiving antenna polarization : Horizontal, Vertical Test Distance : 3 m, Antenna Height : 1 to 4 meters Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain) Margin (PK and/or CAV) = Limit – Level (PK and/or CAV) PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

-22/22-