

TEST REPORT

KCTL KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr		eport No.:)-SRF0307-A ge (1) of (22)	KCTL				
1. Client							
∘ Name	: Samsung Electronics C	o., Ltd.					
∘ Addres	s : 129, Samsung-ro, Yeong Rep. of Korea	tong-gu, Suwon	-si, Gyeonggi-do, 16677,				
 Date of 	Receipt : 2020-10-08						
2. Use of Re	port : Class II Permissive cha	nge					
3. Name of P	roduct / Model : Smart We	arable / SM-R83	5U				
4. Manufactu	irer / Country of Origin : Samsung	Electronics Co	., Ltd. / Vietnam				
5. FCC ID	: A3LSMR8	35					
6. IC Certific	ate No. : 649E-SM	R835					
7. Date of Te	st : 2020-10-21 to 2020-11	-23					
8. Location o 9. Test meth	of Test : ■ Permanent Testing Lab □ od used : FCC Part 15 Subpart 0 RSS-247 Issue 2 Febru RSS-Gen Issue 5 Marc	Dn Site Testing (Add , 15.247 Iary 2017 h 2019	ress: Address of testing location)				
10. Test Res	ult : Refer to the test result	n the test repo	t				
	Tested by	Technical M	anager				
Affirmation	Name : Kwonse Kim (Signature)	Name : Seur	ngyong Kim (agnature)				
2020-12-07							
KCTL Inc.							
As a test result of the sample which was submitted from the client, this report does not guar antee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.							

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (2) of (22)

REPORT REVISION HISTORY

Date	Revision	Page No
2020-11-25	Originally issued	-
2020-12-07	Updated	8, 9, 10, 11, 22

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.

Note. The report No. KR20-SRF0307 is superseded by the report No. KR20-SRF0307-A.

General remarks for test reports

Nothing significant to report.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (3) of (22)

CONTENTS

Ge	eneral information	4
De	evice information	4
	Accessory information	5
2.	Information about derivative model	5
3.	Frequency/channel operations	6
ŀ.	Duty Cycle Correction Factor	7
Su	Immary of tests	8
Me	easurement uncertainty	9
Tes	st results	10
	Maximum peak output power	10
<u>)</u> .	Radiated spurious emissions & band edge	12
Me	easurement equipment	22
	Ge De	General information Device information Accessory information Information about derivative model Frequency/channel operations Duty Cycle Correction Factor Summary of tests Measurement uncertainty Test results Maximum peak output power Radiated spurious emissions & band edge Measurement equipment

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (4) of (22)

1. General information

Client	:	Samsung Electronics Co., Ltd.
Address	:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
Manufacturer	:	Samsung Electronics Co., Ltd.
Address	:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
Factory	:	Samsung Electronics Vietnam Co., Ltd.
Address	:	Yenphong1-I.P Yentrung Commune, Yenphong Dist., Bac Ninh Province, Vietnam
Laboratory	:	KCTL Inc.
Address	:	65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
Accreditations	:	FCC Site Designation No: KR0040, FCC Site Registration No: 687132
		VCCI Registration No. : R-3327, G-198, C-3706, T-1849
		Industry Canada Registration No. : 8035A
		KOLAS No.: KT231

2. Device information

Equipment under test	:	Smart Wearable
Model	:	SM-R835U
Derivative model	:	SM-R835F
Frequency range	:	Bluetooth(BDR/EDR/BLE)_2 402
		WIFI(802.11b/g/n20)_2 412
		LTE Band 12_699.7 Mb ~ 715.3 Mb
		LTE Band 13_779.5 Mb ~ 784.5 Mb
		LTE Band 5_824.7 № ~ 848.3 №
		LTE Band 26_824.7 Mb ~ 848.3 Mb, 814.7 Mb ~ 823.3 Mb
		LTE Band 4_1 710.7 Mz ~1 754.3 Mz
		LTE Band 66_1 710.7 Młz ~1 779.3 Młz
		LTE Band 2_1 850.7 №z ~1 909.3 №z
		LTE Band 25_1 850.7 Mz ~1 914.3 Mz
		WCDMA 850_826.4 Mz ~ 846.6 Mz
		WCDMA 1700_1 712.4 Mz ~ 1 752.6 Mz
		WCDMA 1900_1 852.4 Mz ~ 1 907.6 Mz
Modulation technique	:	Bluetooth(BDR/EDR)_ GFSK, π/4DQPSK, 8DPSK
		Bluetooth(BLE)_GFSK
		WIFI(802.11b/g/n20)_DSSS, OFDM
		LTE_QPSK, 16QAM
		WCDMA_QPSK
Number of channels	:	Bluetooth(BDR/EDR)_79 ch
		Bluetooth(BLE)_40 ch
		WIFI(802.11b/g/n20)_13 ch

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 <u>www.kctl.co.kr</u> Report No.: KR20-SRF0307-A



Page (5) of (22)

Power source	:	DC 3.85 V
Antenna specification	:	LTE/WCDMA_PIFA (Housing metal) Antenna
		WIFI/Bluetooth(BDR/EDR/BLE)_LDS Antenna
Antenna gain	:	WIFI/Bluetooth(BDR/EDR/BLE): -6.4 dBi
Software version	:	R835U.001
Hardware version	:	REV1.0
Test device serial No.	:	Conducted(R3AM8001MVZ)
		Radiated(R3AM9000LLD, R3AM8002AZB, R3AM8002B0R),
Operation temperature	:	-30 °C ~ 50 °C

2.1. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source	FCC ID & IC
Wireless charger	Samsung Electronics Co., Ltd.	EP-OR825	-	DC 5.0 V, 1.0 A	A3LEPOR825 / 649E-EPOR825

2.2. Information about derivative model

The difference between basic model and derivative models is:

Hardware is identical with the basic model and software is as follows.

a. For the model SM-R835U:

- 3G(B2,B4,B5), 4G(B2,B4,B5,B12,B13,B25,B26,B66) are enabled by software.
- b. For the model SM-R835F:
 - 3G(B2,B4), 4G(B2,B4,B12,B13,B25,B26,B66) are disabled by software.
 - 3G(B1,B8), 4G(B1,B3,B7,B8,B20) are enabled by software.

c. In USA, 4G(B7) disabled by MCC code. Because device doesn't support B7 roaming in USA. d. All other protocol part is same and all other features of Volte, SUPL is same.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (6) of (22)

2.3. Frequency/channel operations

This device contains the following capabilities: Bluetooth(BDR/EDR/BLE), WIFI(802.11b/g/n20) LTE Band 12, LTE Band 13, LTE Band 5, LTE Band 26, LTE Band 4, LTE Band 66, LTE Band 2 LTE Band 25, WCDMA 850, WCDMA 1700, WCDMA 1900

Ch.	Frequency (Mz)
00	2 402
39	2 441
•	
78	2 480

Table 2.2.1. Bluetooth(BDR/EDR) mode

15.247 Requirements for Bluetooth transmitter:

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
 - 1) This system is hopping pseudo-randomly.
 - 2) Each frequency is used equally on the average by each transmitter.
 - 3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
 - 4) The receiver shifts frequencies in synchronization with the transmitted signals.
- 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.
- 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (7) of (22)

2.4. Duty Cycle Correction Factor

Test mode	Period (ms)	On time (ms)	Reduced VBW (Hz)
GFSK	3.753	2.881	347.10
8DPSK	3.754	2.888	346.26



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (8) of (22)

5	. Summa	ry of tests			
	FCC Part section(s)	IC Rule Reference	Parameter	Test condition	Test results
	15.247(b)(1),(4)	RSS-247 5.4 (b)	Maximum peak output power	Conducted	Pass
	15 205(a) BSS Con		Spurious emission		Pass
	15.209(a)	a) (8.9), (8.10)	Band-edge, restricted band	Radiated	Pass

Notes:

- 1. All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2. According to exploratory test no any obvious emission were detected from 9 klz to 30 Mlz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
- 3. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that **Y** orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in **Y** orientation.
- 4. The test procedure(s) in this report were performed in accordance as following.
 - ANSI C63.10-2013
 - KDB 558074 D01 v05r02
- 5. All the radiated tests have been performed two modes (with charger and without charger) and the with charger is the worst case mode.
- 6. The test mode and channel set for this C2PC filing test was based on the worst case condition raised in original report, KR19-SRF0093-A.
- 7. The maximum production power and tolerance are not impacted by the change stated in the C2PC letter.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (9) of (22)

4. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of k=2 to indicated a 95 % level of confidence. The measurement data shown herein meets of exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty (±)		
Conducted RF power	1.3 dB		
	9 kHz ~ 30 MHz:	2.3 dB	
Padiated spurious emissions	30 MHz ~ 300 MHz	5.4 dB	
Radiated spurious emissions	300 MHz ~ 1 000 MHz	5.5 dB	
	Above 1 GHz	6.7 dB	

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (10) of (22)

5 Test results 5.1. Maximum peak output power



<u>Limit</u>

FCC

According to \$15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

According to §15.247(b)(1), for frequency hopping systems operating in the 2 400-2 483.5 Mb band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5 725-5 850 Mb band: 1 watt. For all other frequency hopping systems in the 2 400-2 483.5 Mb band: 0.125 watts.

According to \$15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

IC

According to RSS-247 5.4(b), for FHSs operating in the band 2400-2483.5 Mb, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels.

The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

Test procedure

ANSI C63.10-2013 - Section 7.8.5

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Test settings

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

Use the following spectrum analyzer settings:

- 1) Span: Approximately five times the 20 $\,\mathrm{dB}\,$ bandwidth, centered on a hopping channel.
- 2) RBW > 20 dB bandwidth of the emission being measured.
- 3) VBW ≥ RBW.
- 4) Sweep: Auto.
- 5) Detector function: Peak.
- 6) Trace: Max hold.
- 7) Allow trace to stabilize.

Notes:

A peak responding power sensor is used, where the power sensor system video bandwidth is greater than the occupied bandwidth of the EUT.

Frequency (账)	Data rate (Mbps)	Conducted output power (dBm)		Ant. Gain	Max. e.i.r.p. (dB m)	
		Peak	Average	(dBi)	Peak	Average
2 402	1	15.26	13.67	-6.40	8.86	7.27
2 441	1	16.76	15.08	-6.40	10.36	8.68
2 480	1	15.76	14.18	-6.40	9.36	7.78
2 402	3	11.35	7.02	-6.40	4.95	0.62
2 441	3	12.15	7.73	-6.40	5.75	1.33
2 480	3	10.85	6.39	-6.40	4.45	-0.01

Notes:

Measured output power(Average) = reading value of average power + D.C.F e.i.r.p. Calculation: e.i.r.p. (dB m) = Conducted output power (dB m) + Antenna gain (dB i)

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A





5.2. Radiated spurious emissions & band edge

<u>Test setup</u>

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 Mz to 1 Gz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 $\mathbb{G}_{\mathbb{Z}}$ to the tenth harmonic of the highest fundamental frequency or to 40 $\mathbb{G}_{\mathbb{Z}}$ emissions, whichever is lower.



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (13) of (22)

<u>Limit</u>

FCC

According to section 15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (Mb)	Field strength (μ N/m)	Measurement distance (m)
0.009 - 0.490	2 400/F(kHz)	300
0.490 - 1.705	24 000/F(kHz)	30
1.705 - 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 Mz, 76-88 Mz, 174-216 Mz or 470-806 Mz. However, operation within these frequency bands is permitted under other sections of this part, e.g., Section15.231 and 15.241.

According to section 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 – 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 – 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 – 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 – 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 – 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 – 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 – 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 – 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525	2 483.5 – 2 500	17.7 - 21.4
8.376 25 - 8.386 75	25	2 690 – 2 900	22.01 - 23.12
8.414 25 - 8.414 75	156.7 - 156.9	3 260 – 3 267	23.6 - 24.0
12.29 - 12.293	162.012 5 - 167.17	3 332 – 3 339	31.2 - 31.8
12.519 75 - 12.520 25	167.72 - 173.2	3 345.8 – 3 358	36.43 - 36.5
12.576 75 - 12.577 25	240 - 285	3 600 – 4 400	Above 38.6
13.36 - 13.41	322 - 335.4		

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in section 15.209. At frequencies equal to or less than 1 000 Mb, compliance with the limits in section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasipeak detector. Above 1 000 Mb, compliance with the emission limits in section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in section 15.35 apply to these measurements.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (14) of (22)

IC

According to RSS-247(5.5), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

According to RSS-Gen(8.9), Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Frequency(Mz)	Field strength (µV/m at 3 m)
30 to 88	100
88 to 216	150
216 to 960	200
Above 960	500

Table 5- General field strength limits at frequencies above 30 MHz

Table 6- General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) (µ A/m)	Measurement distance(m)
9-490 kHz ¹⁾	6.37/F (F in ktz)	300
490 – 1705 kHz	63.7/F (F in 🗤)	30
1.705 - 30 M±	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

According to RSS-Gen(8.10), Restricted frequency bands, identified in table 7, are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following conditions related to the restricted frequency bands apply:

- (a) The transmit frequency, including fundamental components of modulation, of licence-exempt radio apparatus shall not fall within the restricted frequency bands listed in table 7 except for apparatus compliant with RSS-287, Emergency Position Indicating Radio Beacons (EPIRB), Emergency Locator Transmitters (ELT), Personal Locator Beacons (PLB), and Maritime Survivor Locator Devices (MSLD).
- (b) Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table 5 and table 6.
- (c) Unwanted emissions that do not fall within the restricted frequency bands listed in table 7 shall comply either with the limits specified in the applicable RSS or with those specified in table 5 and table 6.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A

Page (15) of (22)



Table 7- Restricted frequency bands*

MHz
0.090 - 0.110
0.495 - 0.505
2.1735 - 2.1905
3.020 - 3.026
4.125 - 4.128
4.17725 - 4.17775
4.20725 - 4.20775
5.677 - 5.683
6.215 - 6.218
6.26775 - 6.26825
6.31175 - 6.31225
8.291 - 8.294
8.362 - 8.366
8.37625 - 8.38675
8.41425 - 8.41475
12.29 - 12.293
12.51975 - 12.52025
12.57675 - 12.57725
13.36 - 13.41
16.42 - 16.423
16.69475 - 16.69525
16.80425 - 16.80475
25.5 - 25.67
37.5 - 38.25
73 - 74.6
74.8 - 75.2
108 - 138

MHz					
149.9 - 150.05					
156.52475 - 156.52525					
156.7 - 156.9					
162.0125 - 167.17					
167.72 - 173.2					
240 - 285					
322 - 335.4					
399.9 - 410					
608 - 614					
960 - 1427					
1435 - 1626.5					
1645.5 - 1646.5					
1660 - 1710					
1718.8 - 1722.2					
2200 - 2300					
2310 - 2390					
2483.5 - 2500					
2655 - 2900					
3260 - 3267					
3332 - 3339					
3345.8 - 3358					
3500 - 4400					
4500 - 5150					
5350 - 5460					
7250 - 7750					
8025 - 8500					

GHz
9.0 - 9.2
9.3 - 9.5
10.6 - 12.7
13.25 - 13.4
14.47 - 14.5
15.35 - 16.2
17.7 - 21.4
22.01 - 23.12
23.6 - 24.0
31.2 - 31.8
36.43 - 36.5
Above 38.6

* Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licenceexempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (16) of (22)

Test procedure

ANSI C63.10-2013

Test settings

Peak field strength measurements

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = as specified in table
- 3. VBW \geq (3×RBW)
- 4. Detector = peak
- 5. Sweep time = auto
- 6. Trace mode = max hold
- 7. Allow sweeps to continue until the trace stabilizes

Table: RBW as a function of frequency						
Frequency	RBW					
9 kHz to 150 kHz	200 Hz to 300 Hz					
0.15 Mt to 30 Mt	9 kHz to 10 kHz					
30 MHz to 1 000 MHz	100 kHz to 120 kHz					
> 1 000 MHz	1 MHz					

Table. RBW as a function of frequency

Average field strength measurements

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1 Mz
- 3. VBW = 1/T ≥ 1 Hz
- 4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
- 5. Detector = peak
- 6. Sweep time = auto
- 7. Trace mode = max hold
- 8. Trace was allowed to run for at least 50 times(1/duty cycle) traces

Notes:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 Mb for Peak detection and frequency above 1 Gb. The resolution bandwidth of test receiver/spectrum analyzer is 1 Mb and the video bandwidth is 500 Hz(≥1/T) for Average detection (AV) at frequency above 1 Gb.
- f <30 M₂, extrapolation factor of 40 dB/decade of distance. F_d = 40log(D_m/Ds) f ≥30 M₂, extrapolation factor of 20 dB/decade of distance. F_d = 20log(D_m/Ds) Where:

 F_d = Distance factor in dB

D_m= Measurement distance in meters

D_s= Specification distance in meters

- 3. Factors(dB) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB) + or $F_d(dB)$
- 4. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
- 5. Average test would be performed if the peak result were greater than the average limit.
- 6. ¹⁾ means restricted band.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (17) of (22)

Duty cycle correction factor calculation:

According to 7.5 Procedure for determining the average value of pulsed emissions Duty Cycle Correction Factor Calculation

- Worst case : AFH mode

- Channel hop rate = 800 hops/second
- Hopping rate for DH5 mode = 800 hops/second / 5 (6 slots for DH5) = 133.33 hops/second
- Time per channel hop = 1 / 133.33 hops/second = 7.50 ms
- Time to cycle through all channels = 7.50 x 20 channels(AFH mode) = 150 ms
- Number of times transmitter hits on one channel = 100 ms / Time to cycle through all channels (ms)

= 100 ms / 150 ms = 1 time

- Worst case Dwell time = 7.5 ms
- Duty Cycle Correction Factor = 20log(7.5 ms/100 ms) = -22.5 dB

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (18) of (22)

Test results (Above 1 000 M社)

GFSK / Band-edge

Highest Channel

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(µV))	(dB)	(dB)	(dB)	(dB(µV/m))	(dB(µV/m))	(dB)
Peak data								
2 483.53 ¹⁾	V	47.87	31.98	-28.54	-	51.31	74.00	22.69
Average Data								
2 483.53 ¹⁾	V	35.13	31.98	-28.54	-	38.57	54.00	15.43



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (19) of (22)

GFSK / Harmonic

Highest Channel

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(µV))	(dB)	(dB)	(dB)	(dB(µV/m))	(dB(<i>µ</i> V/ m))	(dB)
Peak data								
4 959.97 ¹⁾	V	63.10	34.37	-54.22	-	43.25	74.00	30.75
16 937.42	V	56.04	41.92	-45.48	-	52.48	74.00	21.52
Average Data								
No spurious emissions were detected within 20 dB of the limit.								



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (20) of (22)

8DPSK / Band-edge

Lowest Channel

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(µV))	(dB)	(dB)	(dB)	(dB(<i>µ</i> V/ m))	(dB(<i>µ</i> V/ m))	(dB)
	Peak data							
2 483.52 ¹⁾	Н	48.46	31.98	-28.54	-	51.90	74.00	22.10
Average Data								
2 483.52 ¹⁾	Н	35.06	31.98	-28.54	-	38.50	54.00	15.50



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (21) of (22)

8DPSK / Harmonic

Highest Channel

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(µV))	(dB)	(dB)	(dB)	(dB(µV/m))	(dB(µV/m))	(dB)
Peak data								
4 969.03 ¹⁾	н	62.45	34.38	-54.29	-	42.54	74.00	31.46
17 031.22	V	56.01	41.51	-45.43	-	52.09	74.00	21.91
Average Data								
No spurious emissions were detected within 20 dB of the limit.								



65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr Report No.: KR20-SRF0307-A



Page (22) of (22)

6. Measurement equipment				
Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum Analyzer	R&S	FSV30	100806	21.07.29
Spectrum Analyzer	R&S	FSV40	100989	21.01.03
Attenuator	Weinschel ENGINEERING	56-10	51395	21.01.22
Signal Generator	R&S	SMB100A	176206	21.01.21
Vector Signal Generator	R&S	SMBV100A	257566	21.07.13
Signal Generator	R&S	SMR40	100007	21.04.08
Power Sensor	R&S	NRP-Z81	1137.9009.02- 106224-tg	21.05.25
Bluetooth Tester	TESCOM	TC-3000C	3000C000270	21.07.28
High pass Filter	WT	WT-A1698-HS	WT160411001	21.05.11
Horn antenna	ETS.lindgren	3117	161225	21.05.12
Horn antenna	ETS.lindgren	3116	00086632	21.02.17
Attenuator	API Inmet	40AH2W-10	12	21.05.12
Broadband PreAmplifier	SCHWARZBECK	BBV9718	216	21.07.28
AMPLIFIER	L-3 Narda-MITEQ	AMF-7D-01001800 -22-10P	2031196	21.02.12
AMPLIFIER	L-3 Narda-MITEQ	JS44-18004000-33-8P	2000996	21.01.22
Antenna Mast	Innco Systems	MA4000-EP	303	-
Turn Table	Innco Systems	DT2000	79	-

End of test report