

EMC TEST REPORT



| | | | |
|--|--------------------------------|---|---|
| Project No. | LBE20210315 | Issue No. | 2 |
| Applicant | Name of organization | Samsung Electronics Co., Ltd. | |
| | Address | (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea | |
| | Date of receipt | May 04, 2021 | |
| EUT | Type of device | <input checked="" type="checkbox"/> All other Receivers subject to part15 <input type="checkbox"/> Class B Personal Computers and peripherals <input checked="" type="checkbox"/> Other Class B digital devices and peripherals <input type="checkbox"/> FM Broadcast Receiver | |
| | Equipment authorization | <input checked="" type="checkbox"/> Certification <input type="checkbox"/> Supplier's Declaration of Conformity | |
| | FCC ID | A3LSMR895 | |
| | Kind of product | Smart Wearable | |
| | Model No. | SM-R895U | |
| | Variant Model No. | Refer to clause 4.6 | |
| | Manufacturer | AG TECH Co., Ltd. Lot G3, Que Vo Industrial Park (Expanded Area), Nam Son Ward, Bac Ninh City, Bac Ninh Province, Vietnam | |
| Applied Standards | | 47 CFR Part 15, Subpart B, Class B / ANSI C63.4-2014 | |
| Test Period | | May 04, 2021 ~ May 17, 2021 | |
| Issue date | | June 4, 2021 | |
| Test result : Complied The equipment under test has found to be compliant with the applied standards. (Refer to the attached test result for more detail.) | | | |
| Tested by : Ji-Yeon Lee  | | Reviewed by : Sun-Ho Kim  | |
| The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from Global CS Center. * Not KOLAS report | | | |
| Samsung Electronics Co Ltd, Global CS Center (Maetan dong) 129, Samsung-ro, Yeongtong-Gu, Suwon-Si, Gyeonggi-Do 16677, Korea | | | |

Table of contents

1. Report Information

| | |
|----------------------------|---|
| 1.1 Revision history | 3 |
|----------------------------|---|

2. Summary of test results

| | |
|--------------------|---|
| 2.1 Emission | 3 |
|--------------------|---|

3. General Information

| | |
|-------------------------|---|
| 3.1 Test facility | 3 |
|-------------------------|---|

4. Test Configuration

| | |
|--|----|
| 4.1 Test Peripherals | 4 |
| 4.2 EUT operating mode | 5 |
| 4.3 Details of Sampling | 5 |
| 4.4 Used cable description | 6 |
| 4.5 Test arrangement | 7 |
| 4.6 EUT Description | 9 |
| 4.7 EUT Frequencies | 9 |
| 4.8 Test configuration and condition | 9 |
| 4.9 Measurement uncertainty | 10 |

5. Result of individual tests

| | |
|------------------------------|----|
| 5.1 Conducted emission | 11 |
| 5.2 Radiated emission | 15 |

1. Report Information

1.1 Revision history

| No. | Date of Issue | Revised detailed information |
|---------|---------------|--|
| Issue 0 | 20 May 2021 | There are no revisions and this version is basic test report. |
| Issue 1 | 21 May 2021 | FCC/IC ID of wireless charger(EP-OR825) is added in clause 4.1 |
| Issue 2 | 4 June 2021 | Variant model is added. |

※ Remark

Compliance with Part 15B requirements for the receiver part of the licensed transmitter (equipment code CXX) is covered by other test report.

2. Summary of test results

2.1 Emission

The EUT has been tested according to the following specifications:

| Applied | Test type | Applied standard | Result |
|-------------------------------------|------------------------------------|---|----------|
| <input checked="" type="checkbox"/> | Conducted emission (Mains port) | 47 CFR Part 15 Subpart B / ANSI C63.4-2014 (Class B) | Complied |
| <input checked="" type="checkbox"/> | Radiated emission | | Complied |

3. General Information

3.1 Test facility

The Global CS Center is located on Samsung Electronics Co., Ltd. at (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea.

All testing are performed in Semi-anechoic chambers conforming to the site attenuation characteristics defined by ANSI C63.4, CISPR 32, CISPR 16-1-4 and Shielded rooms. And all antennas are properly calibrated using ANSI C63.5:2017.

The Global CS Center is an ISO/IEC 17025 accredited testing laboratory by the National Radio Research Agency with designation No. KR0004. for EMC testing.

4. Test Setup configuration

4.1 Test Peripherals

The cables used for these peripherals are either permanently attached by the peripheral manufacturer or coupled with an assigned cable as defined below.

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

| Mark | Description | Model No. | Serial No. | Manufacturer / Trademark | FCC ID |
|------|-------------------|--------------|-------------------------------|--------------------------|---------------------------------------|
| A | Smart Wearable | SM-R895U | - | SAMSUNG | A3LSMR895 |
| B | Battery | EB-BR890ABY | - | SDI | - |
| C | Wireless Charger | EP-OR825 | - | SAMSUNG | FCC : A3LEPOR825 IC : 649E-EPOR825 |
| D | Travel Adapter | EP-TA200 | R37NBJA0045DK3 | Dongyang | - |
| E | Laptop Computer | Latitude5580 | 1WYRYM2 | Dell | DoC |
| | | | D3HRYM2 | Dell | DoC |
| F | Laptop AC Adapter | LA65NM130 | 5DEA | Dell | DoC |
| | | | 5B3C | Dell | DoC |
| G | Mouse | AA-SM7PCPB | CN57BA5903634A DV8JJCD4371 | SAMSUNG | DoC |
| | | SNJ-B138 | Z5F8353 | SAMSUNG | DoC |
| H | Router | DIR-806A | RF0F1D8018454 | D-Link | DoC |
| | | | RF0F1D8011504 | D-Link | DoC |

4.2 EUT operating mode

To achieve compliance applied standard specification including CXX and JAB requirement, the following mode(s) were made during compliance testing:

4.2.1 Conducted emission

| No. | Operating mode |
|-----|---|
| 1 | Wireless Charging (w/TA) + Cellular Receiver (LTE FDD B26 Center Frequency) |
| 2 | Audio playback from internal memory data + Wireless Charging (w/TA) |
| 3 | Wireless Charging (w/USB port of Laptop Computer) |

4.2.2 Radiated emission

| No. | Operating mode |
|-----|---|
| 1 | Wireless Charging (w/TA) |
| 2 | Audio playback from internal memory data |
| 3 | Wireless Charging (w/USB port of Laptop Computer) |

4.3 Details of Sampling

Customer selected, single unit.


4.4 Used cable description

The EUT is configured, installed, arranged and operated in a manner consistent with typical applications. Interface cables/loads/devices are connected to at least one of each type of interface port of the EUT, and where practical, each cable shall be terminated in a device typical of actual usage. The type(s) of interconnecting cables to be used and the interface port (of the EUT) to which these were connected:


| No. | Connected cable | Length [m] | Shielded [Y/N] | Note |
|-----|------------------------|------------|----------------|---|
| 1 | Wireless Charger Cable | 0.8 | N | For Wireless Charger |
| 2 | Power | 1.8 | N | From Laptop Computer to Laptop AC Adapter |
| 3 | Power | 1.5 | N | For Laptop AC Adapter |
| 4 | LAN | 1.5 | N | From Laptop Computer to Router |
| 5 | USB | 0.8 | Y | From Laptop Computer to Router for DC Power |
| 6 | USB | 1.8 | Y | From Laptop Computer to Mouse |

4.5 Test arrangement

4.5.1 Conducted emission




[Mode 1 - 2]



[Mode 3]


4.5.2 Radiated emission



[Mode 1]



[Mode 2]



[Mode 3]

4.6 EUT Description

The EUT is a watch type smart wearable which can operate on WCDMA FDD2/4/5, LTE FDD2/4/5/12/13/25/26/66/71 bands and incorporates a Bluetooth, Wi-Fi(802.11 a/b/g/n), GNSS, NFC, Wireless Charging and Audio.

4.6.1 The variant models

- SM-R895F

4.7 EUT Frequencies

| The highest frequencies (Generated and used) | Frequency [MHz] |
|---|-------------------|
| Wi-Fi | 5 825 |

4.8 Test configuration and condition

The system was configured for testing in a typical fashion that a customer would normally use.

Cables were attached to each of the available I/O Ports. Where applicable, peripherals were attached to the I/O cables.

The EUT was investigated in three orientations and the worst case orientation is reported.

RX mode(850MHz) testing was performed with the LTE FDD26 RX Test mode at center frequency. All licensed communication (850MHz) RX mode, GSM/WCDMA/LTE, test results are not significantly different.

The audio(1 kHz sound) were repetitively played.

The EUT was charged with wireless charger connected to travel adapter or USB port of laptop computer.

Power source for the EUT operating was supplied by CVCF made by the Pacific Corp.

- Test Voltage : AC 120 V, 60 Hz

4.9 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus: (According to CISPR 16-4-2 and UKAS M3003)

| Test type | | Measurement uncertainty (C.L. approximately 95 %, $k = 2$) |
|------------------------------------|------------|--|
| Conducted emission | AC Mains | 2.83 dB |
| Radiated emission (Below 1 GHz) | Horizontal | 4.47 dB |
| | Vertical | 5.67 dB |
| Radiated emission (Above 1 GHz) | Horizontal | 5.21 dB |
| | Vertical | 5.21 dB |

* Remark

- 1) The values for uncertainty of conducted and radiated emissions are less than the Corresponding values of U_{CISPR} given in CISPR 16-4-2. Therefore no adjustment of measurement results is necessary when comparing them with the relevant limits.

5. Results of individual test

5.1 Conducted emission

The EUT is connected to a LISN via travel adapter. If the EUT is connected to the Laptop Computer USB port, the Laptop AC adapter is connected to a LISN.

Both conducted lines are measured in Quasi-Peak and CISPR-Average mode, including the worst-case data points for each tested configuration. The EUT measured in accordance with the methods described in standards.

Limits for conducted emission at the mains ports of Class B

| Frequency range Limits [MHz] | Resolution Bandwidth [kHz] | Limits [dB(μV)] | |
|--|---------------------------------|-------------------|----------|
| | | Quasi-peak | Average |
| 0.15 to 0.50 | 9 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 9 | 56 | 46 |
| 5 to 30 | 9 | 60 | 50 |
| NOTE 1 The lower limit shall apply at the transition frequency. | | | |
| NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz. | | | |

5.1.1 Test instrumentation


| EMC No. | Test Instrument | Model name | Manufacturer | Serial No. | Next Calibration | |
|---------|--------------------|------------|--------------|-------------|------------------|------------------|
| | | | | | Date | Interval (Month) |
| E5I-127 | Two-Line V-Network | ENV216 | R&S | 102061 | 2021-07-29 | 12 |
| E5I-015 | EMI Test Receiver | ESU8 | R&S | 100481 | 2021-07-01 | 12 |
| E5I-006 | LTE Communicator | CMW500 | R&S | 132728 | 2022-04-06 | 12 |
| - | Test software | EMC32 | R&S | Ver 9.26.01 | - | - |

5.1.2 Temperature and humidity condition

| | | | |
|-------------------|----------------------|---------------------|-----------------------------|
| Test date | 2021-05-17 | Test engineer | Ji-Yeon Lee |
| Climate condition | Ambient temperature | (21.6 ± 0.5) °C | Limit (15.0 to 35.0) °C |
| | Relative humidity | (39.4 ± 0.5) % R.H. | Limit (25.0 to 75.0) % R.H. |
| | Atmospheric pressure | (100.7 ± 0.5) kPa | Limit (86.0 to 106.0) kPa |
| Test place | Shield Room (SR8) | | |

5.1.3 Test results

☐ Operating Mode 1: AC Mains



QP / CAV final measurement results table:

| Frequency (MHz) | QP (dBμV) | CAV (dBμV) | Limit (dBμV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|-----------|------------|--------------|-------------|------|------------|
| 0.150 | --- | 28.28 | 56.00 | 27.72 | N | 9.9 |
| 0.150 | 47.37 | --- | 66.00 | 18.63 | N | 9.9 |
| 0.220 | 45.78 | --- | 62.83 | 17.05 | L1 | 9.9 |
| 0.220 | --- | 28.09 | 52.83 | 24.73 | L1 | 9.9 |
| 0.427 | 30.27 | --- | 57.32 | 27.05 | N | 10.2 |
| 0.427 | --- | 21.23 | 47.32 | 26.09 | N | 10.2 |
| 0.708 | 28.84 | --- | 56.00 | 27.16 | L1 | 10.1 |
| 0.708 | --- | 22.79 | 46.00 | 23.21 | L1 | 10.1 |
| 1.277 | 29.90 | --- | 56.00 | 26.10 | L1 | 10.0 |
| 1.277 | --- | 26.44 | 46.00 | 19.56 | L1 | 10.0 |
| 2.128 | --- | 25.30 | 46.00 | 20.70 | L1 | 9.9 |
| 2.128 | 29.63 | --- | 56.00 | 26.37 | L1 | 9.9 |
| 15.416 | --- | 25.96 | 50.00 | 24.04 | L1 | 10.3 |
| 15.416 | 32.05 | --- | 60.00 | 27.95 | L1 | 10.3 |


Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)

Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 2: AC Mains



QP / CAV final measurement results table:

| Frequency (MHz) | QP (dBμV) | CAV (dBμV) | Limit (dBμV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|-----------|------------|--------------|-------------|------|------------|
| 0.150 | --- | 28.84 | 56.00 | 27.16 | L1 | 9.9 |
| 0.150 | 45.67 | --- | 66.00 | 20.33 | L1 | 9.9 |
| 0.438 | --- | 24.52 | 47.10 | 22.58 | L1 | 10.2 |
| 0.438 | 29.77 | --- | 57.10 | 27.32 | L1 | 10.2 |
| 0.731 | --- | 26.93 | 46.00 | 19.07 | L1 | 10.1 |
| 0.731 | 30.62 | --- | 56.00 | 25.38 | L1 | 10.1 |
| 1.610 | --- | 25.51 | 46.00 | 20.49 | L1 | 9.9 |
| 1.610 | 29.05 | --- | 56.00 | 26.95 | L1 | 9.9 |
| 1.903 | --- | 26.52 | 46.00 | 19.48 | L1 | 9.9 |
| 1.903 | 30.23 | --- | 56.00 | 25.77 | L1 | 9.9 |
| 13.331 | --- | 26.09 | 50.00 | 23.91 | L1 | 10.3 |
| 13.331 | 31.93 | --- | 60.00 | 28.07 | L1 | 10.3 |


Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)

Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 3: AC Mains



QP / CAV final measurement results table:

| Frequency (MHz) | QP (dBμV) | CAV (dBμV) | Limit (dBμV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|-----------|------------|--------------|-------------|------|------------|
| 0.150 | 52.01 | --- | 66.00 | 13.99 | N | 9.9 |
| 0.150 | --- | 31.85 | 56.00 | 24.15 | N | 9.9 |
| 0.168 | 49.35 | --- | 65.06 | 15.71 | L1 | 10.3 |
| 0.168 | --- | 35.18 | 55.06 | 19.88 | L1 | 10.3 |
| 0.195 | 45.69 | --- | 63.82 | 18.13 | L1 | 10.1 |
| 0.195 | --- | 32.91 | 53.82 | 20.91 | L1 | 10.1 |
| 0.497 | 39.07 | --- | 56.06 | 16.99 | L1 | 10.2 |
| 0.497 | --- | 28.68 | 46.06 | 17.38 | L1 | 10.2 |
| 3.757 | --- | 22.15 | 46.00 | 23.85 | L1 | 10.0 |
| 3.757 | 32.24 | --- | 56.00 | 23.76 | L1 | 10.0 |
| 9.994 | --- | 25.92 | 50.00 | 24.08 | L1 | 10.1 |
| 9.994 | 31.39 | --- | 60.00 | 28.61 | L1 | 10.1 |
| 29.983 | --- | 9.98 | 50.00 | 40.02 | N | 10.8 |
| 29.983 | 36.40 | --- | 60.00 | 23.60 | N | 10.8 |

Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)

Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

5.2 Radiated emission

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin.

Peak measurements were made over the changeable frequency range 30 MHz to 1 GHz at a measurement distance of 3 m for the following antenna and turntable arrangements:

| Antenna Height [cm] | Antenna Polarisation | Resolution Bandwidth [kHz] | Video Bandwidth [kHz] | Turntable position [degrees] |
|--------------------------|----------------------|------------------------------------|-------------------------------|-----------------------------------|
| 100 ~ 400 | Horizontal, Vertical | 120 | 300 | Continuous |

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using quasi-peak detector.

Peak/CISPR-Average measurements were made over the changeable frequency range 1 GHz to 40 GHz or 5th harmonics of the highest frequency generated or used in the device or on which the device operates or tunes at a measurement distance of 3 m for the following antenna and turntable arrangements. The measurements above 1 GHz were performed with the bore-sighting antenna aimed at the EUT.

| Antenna Height [cm] | Antenna Polarisation | Resolution Bandwidth [MHz] | Video Bandwidth [MHz] | Turntable position |
|--------------------------|----------------------|------------------------------------|-------------------------------|--------------------|
| 100 ~ 400 | Horizontal, Vertical | 1 | 3 | Continuous |

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using peak and CISPR-average detectors.

Limits for radiated emission of Class B at a measuring distance of 3 m and 10 m

| Frequency range Limits [MHz] | Field Strength | | |
|-----------------------------------|-------------------------|-------------------------------|--------------------------------|
| | 3 m [$\mu\text{V/m}$] | 3 m [dB($\mu\text{V/m}$)] | 10 m [dB($\mu\text{V/m}$)] |
| 30 to 88 | 100 | 40.0 | 29.5 |
| 88 to 216 | 150 | 43.5 | 33.0 |
| 216 to 960 | 200 | 46.0 | 35.5 |
| Above 960 | 500 | 54.0 | 43.5 |

Note) Distance correction formula from $D_1(3\text{m})$ to $D_2(10\text{m})$
: Limit at D_2 = Limit at D_1 + $20\text{Log}(D_1 / D_2)$

Results checked manually; and points close to the limit line were re-measured.

5.2.1 Test instrumentation

| EMC No. | Test Instrument | Model name | Manufacturer | Serial No. | Next Calibration | |
|---------|--------------------------|------------|--------------|-------------|------------------|------------------|
| | | | | | Date | Interval (Month) |
| E5I-021 | EMI Test Receiver | ESU40 | R&S | 100376 | 2022-02-04 | 12 |
| E5I-072 | BiLog Antenna | CBL6112D | TESEQ | 36009 | 2022-05-15 | 24 |
| E5I-223 | 6 dB Fixed Attenuator | 8491B-006 | Agilent | 58359 | 2022-05-15 | 24 |
| E5I-093 | Preamplifier | 310N | SONOMA | 273122 | 2022-01-21 | 12 |
| E5I-035 | Horn Antenna | HF907 | R&S | 100506 | 2021-08-30 | 24 |
| E5I-040 | Signal Conditioning Unit | SCU-18 | R&S | 10210 | 2022-04-06 | 12 |
| E5I-037 | WideBand Horn Antenna | WBH 18-40K | R&S | 11201 | 2023-02-15 | 24 |
| E5I-042 | Signal Conditioning Unit | SCU-40A | R&S | 10004 | 2021-09-09 | 12 |
| - | Test software | EP7RE | TOYO | Ver 5.8.2 | - | - |
| - | Test software | EMC32 | R&S | Ver 9.25.00 | - | - |


5.2.2 Temperature and humidity condition

| | | | |
|--------------------------|------------------------------|----------------------|-----------------------------|
| Test date | 2021-05-04, 2021-05-06 | Test engineer | Ji-Yeon Lee |
| Climate condition | Ambient temperature | (23.2 ± 0.5) °C | Limit (15.0 to 35.0) °C |
| | Relative humidity | (41.1 ± 0.5) % R.H. | Limit (25.0 to 75.0) % R.H. |
| | Atmospheric pressure | (100.9 ± 0.5) kPa | Limit (86.0 to 106.0) kPa |
| Test place | Semi-Anechoic Chamber (SAC5) | | |

5.2.3 Test results

☐ Operating Mode 1

- Frequencies below 1 GHz




Note1) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions.


Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 2**- Frequencies below 1 GHz**

Note1) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 3 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions.


Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 3**- Frequencies below 1 GHz**


Note1) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz

| Frequency (MHz) | PK (dBμV/) | CAV (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|------------|--------------|----------------|-------------|-------------|-----|---------------|------------|
| 1 331.500 | --- | 29.00 | 54.00 | 25.00 | 102.3 | V | 12.0 | 7.1 |
| 1 331.500 | 45.01 | --- | 74.00 | 28.99 | 103.4 | V | 12.0 | 7.1 |
| 1 991.000 | --- | 29.70 | 54.00 | 24.30 | 109.1 | V | 0.0 | 11.7 |
| 1 996.000 | 46.43 | --- | 74.00 | 27.57 | 108.8 | V | 18.0 | 11.8 |
| 2 401.500 | 85.73 | --- | 74.00 | -11.73 | 100.2 | V | 230.0 | 12.8 |
| 2 401.500 | --- | 76.67 | 54.00 | -22.67 | 101.5 | V | 230.0 | 12.8 |
| 2 480.000 | 83.53 | --- | 74.00 | -9.53 | 103.6 | V | 320.0 | 13.0 |
| 2 480.000 | --- | 78.07 | 54.00 | -24.07 | 105.4 | V | 320.0 | 13.0 |
| 2 658.000 | 48.19 | --- | 74.00 | 25.81 | 100.0 | V | 284.0 | 13.8 |
| 2 658.000 | --- | 32.80 | 54.00 | 21.20 | 101.5 | V | 284.0 | 13.8 |
| 17 890.500 | 50.16 | --- | 74.00 | 23.84 | 106.0 | H | 1.0 | 38.5 |
| 17 907.500 | --- | 45.06 | 54.00 | 8.94 | 108.1 | H | 175.0 | 38.5 |

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions.

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

Note 3) Radiated emissions (Tx / Rx frequency) from the transceiver shall be ignored.

- Data transmission in the 2.4 GHz ISM band (Bluetooth/Wi-Fi 802.11b/g/n)

: Operating frequencies (2 400 ~ 2 483.5) MHz