



Plot 7-105. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ax (UNII Band 2C) – Ch. 122)




Plot 7-106. Power Spectral Density Plot MIMO ANT1 (160MHz BW 802.11ac (UNII Band 2C) – Ch. 114)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 82 of 151




Plot 7-107. Power Spectral Density Plot MIMO ANT1 (160MHz BW 802.11ax (UNII Band 2C) – Ch. 114)




Plot 7-108. Power Spectral Density Plot MIMO ANT1 (802.11a (UNII Band 3) – Ch. 157)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 83 of 151




Plot 7-109. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11n (UNII Band 3) – Ch. 157)




Plot 7-110. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11ax (UNII Band 3) – Ch. 157)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 84 of 151




Plot 7-111. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11n (UNII Band 3) – Ch. 151)




Plot 7-112. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11ax (UNII Band 3) – Ch. 151)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 85 of 151




Plot 7-113. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ac (UNII Band 3) – Ch. 155)




Plot 7-114. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ax (UNII Band 3) – Ch. 155)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 86 of 151




Plot 7-115. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11a (UNII Band 4) – Ch. 173)




Plot 7-116. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11n (UNII Band 4) – Ch. 173)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 87 of 151




Plot 7-117. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11ax (UNII Band 4) – Ch. 173)




Plot 7-118. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11n (UNII Band 3/4) – Ch. 167)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 88 of 151




Plot 7-119. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11ax (UNII Band 3/4) – Ch. 167)



Plot 7-120. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ac (UNII Band 3/4) – Ch. 171)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 89 of 151




Plot 7-121. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11ax (UNII Band 3/4) – Ch. 171)



Plot 7-122. Power Spectral Density Plot MIMO ANT1 (160MHz BW 802.11ac (UNII Band 3/4) – Ch. 163)


FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 90 of 151




Plot 7-123. Power Spectral Density Plot MIMO ANT1 (160MHz BW 802.11ax (UNII Band 3/4) – Ch. 163)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 91 of 151

7.5.3 MIMO Antenna-2 Power Spectral Density Measurements




Plot 7-124. Power Spectral Density Plot MIMO ANT2 (802.11a (UNII Band 1) – Ch. 40)




Plot 7-125. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11n (UNII Band 1) – Ch. 40)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 92 of 151




Plot 7-126. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax (UNII Band 1) – Ch. 40)




Plot 7-127. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11n (UNII Band 1) – Ch. 38)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 93 of 151




Plot 7-128. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax (UNII Band 1) – Ch. 38)




Plot 7-129. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 94 of 151




Plot 7-130. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax (UNII Band 1) – Ch. 42)




Plot 7-131. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11ac (UNII Band 1/2A) – Ch. 50)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 95 of 151




Plot 7-132. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11ax (UNII Band 1/2A) – Ch. 50)




Plot 7-133. Power Spectral Density Plot MIMO ANT2 (802.11a (UNII Band 2A) – Ch. 56)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 96 of 151




Plot 7-134. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11n (UNII Band 2A) – Ch. 56)




Plot 7-135. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax (UNII Band 2A) – Ch. 56)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 97 of 151




Plot 7-136. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11n (UNII Band 2A) – Ch. 54)




Plot 7-137. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax (UNII Band 2A) – Ch. 54)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 98 of 151




Plot 7-138. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ac (UNII Band 2A) – Ch. 58)




Plot 7-139. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax (UNII Band 2A) – Ch. 58)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 99 of 151




Plot 7-140. Power Spectral Density Plot MIMO ANT2 (802.11a (UNII Band 2C) – Ch. 120)




Plot 7-141. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11n (UNII Band 2C) – Ch. 120)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 100 of 151




Plot 7-142. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax (UNII Band 2C) – Ch. 120)




Plot 7-143. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11n (UNII Band 2C) – Ch. 118)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 101 of 151




Plot 7-144. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax (UNII Band 2C) – Ch. 118)




Plot 7-145. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ac (UNII Band 2C) – Ch. 122)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 102 of 151




Plot 7-146. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax (UNII Band 2C) – Ch. 122)




Plot 7-147. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11ac (UNII Band 2C) – Ch. 114)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 103 of 151




Plot 7-150. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11n (UNII Band 3) – Ch. 157)




Plot 7-151. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax (UNII Band 3) – Ch. 157)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 105 of 151




Plot 7-152. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11n (UNII Band 3) – Ch. 151)




Plot 7-153. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax (UNII Band 3) – Ch. 151)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 106 of 151




Plot 7-154. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ac (UNII Band 3) – Ch. 155)




Plot 7-155. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax (UNII Band 3) – Ch. 155)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 107 of 151




Plot 7-156. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11a (UNII Band 4) – Ch. 173)




Plot 7-157. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11n (UNII Band 4) – Ch. 173)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 108 of 151




Plot 7-158. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax (UNII Band 4) – Ch. 173)




Plot 7-159. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11n (UNII Band 3/4) – Ch. 167)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 109 of 151




Plot 7-160. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax (UNII Band 3/4) – Ch. 167)




Plot 7-161. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ac (UNII Band 3/4) – Ch. 171)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 110 of 151




Plot 7-162. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax (UNII Band 3/4) – Ch. 171)



Plot 7-163. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11ac (UNII Band 3/4) – Ch. 163)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 111 of 151



Plot 7-164. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11ax (UNII Band 3/4) – Ch. 163)

Note:

Per ANSI C63.10-2013 Section 14.3.2.2 and KDB 662911 v02r01 Section E2), the power spectral density at Antenna-1 and Antenna-2 were first measured separately as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Sample MIMO Calculation:

At 5845MHz in 802.11n (20MHz BW) mode, the average conducted power spectral density was measured to be 4.45 dBm for Antenna 1 and 5.01 dBm for Antenna 2.

$$\text{Antenna 1} + \text{Antenna 2} = \text{MIMO}$$

$$(4.45 \text{ dBm} + 5.18 \text{ dBm}) = (2.79 \text{ mW} + 3.17 \text{ mW}) = 5.96 \text{ mW} = 7.74 \text{ dBm}$$

Sample e.i.r.p Power Spectral Density Calculation:

At 5845MHz in 802.11n (20MHz BW) mode, the average MIMO power density was calculated to be 7.74 dBm with directional gain of -0.46 dBi.

$$\text{e.i.r.p. Power Spectral Density(dBm)} = \text{Power Spectral Density (dBm)} + \text{Ant gain (dBi)}$$

$$7.74 \text{ dBm} + -0.46 \text{ dBi} = 6.28 \text{ dBm}$$

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 112 of 151

7.6 Radiated Emission Measurements

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies. All channels, modes, and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

For transmitters operating in the 5.15-5.25 GHz and 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

For transmitters operating in the 5.850 – 5.895 GHz band: all emissions at or above 5.895GHz shall not exceed an e.i.r.p. of -5dBm/MHz and shall decrease linearly up to an e.i.r.p. of -27dBm/MHz at or above 5.925GHz, and all emissions below 5.725 GHz shall not exceed an e.i.r.p. of -27dBm/MHz at 5.65 GHz increasing linearly to 10dBm/MHz at 5.7GHz and from 5.7GHz increasing linearly to a level of 15.6dBm/MHz at 5.72GHz, and from 5.72GHz increasing linearly to a level of 27dBm/MHz at 5.725GHz.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in the table below per FCC §15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400\F (kHz)	300
0.490 – 1.705 MHz	24000\F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-22. Radiated Limits

Test Procedures Used

ANSI C63.10-2013 – Sections 12.7.7.2, 12.7.6, 12.7.5 (Radiated Spurious Emissions)

ANSI C63.10-2013 – Section 12.7.4.4 (Band Edge Measurements)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 113 of 151



Test Settings – Above 1GHz

Average Field Strength Measurements (Method AD – Average Detection)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span} \backslash \backslash \text{RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces.

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize.

Test Settings – Below 1GHz

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 114 of 151




Figure 7-5. Radiated Test Setup < 30MHz




Figure 7-6. Radiated Test Setup < 1GHz

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 115 of 151




Figure 7-7. Radiated Test Setup > 1GHz

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 116 of 151

Test Notes

1. All spurious emissions lying in restricted bands specified in §15.205 are below the limits shown in §15.209. All spurious emissions that do not lie in a restricted band are subject to an average limit of -27dBm/MHz. At 3 meters, the field strength limit in dB μ V/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB μ V/m.
2. All spurious emissions that do not lie in a restricted band are subject to a peak limit not to exceed 20dB of the average limit [68.2dB μ V/m]. If a peak measurement passes the average limit, it was determined no further investigation is necessary.
3. The antenna is manipulated through typical positions, polarity, and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported, however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
9. In the case where a peak-detector measurement passed the given RMS limit it was determined sufficient to demonstrate compliance.
10. The results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level [dB μ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- Margin [dB] = Field Strength Level [dB μ V/m] – Limit [dB μ V/m]

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 117 of 151




Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots was calculated using the formula:


$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 118 of 151


7.6.1 MIMO Radiated Spurious Emission Measurements



Plot 7-165. Radiated Spurious Plot below 1GHz MIMO (802.11a)




Plot 7-166. Radiated Spurious Plot above 1GHz MIMO (802.11a – UNII Band 1 Ch. 40)




Plot 7-167. Radiated Spurious Plot above 1GHz MIMO (802.11a – UNII Band 2A Ch. 56)


FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 119 of 151



Plot 7-168. Radiated Spurious Plot above 1GHz MIMO (802.11a – UNII Band 2C Ch. 120)




Plot 7-169. Radiated Spurious Plot above 1GHz MIMO (802.11a – UNII Band 3 Ch. 157)




Plot 7-170. Radiated Spurious Plot above 1GHz MIMO (802.11a – UNII Band 4 Ch. 173)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 120 of 151



Plot 7-171. Radiated Spurious Plot 18GHz – 26.5GHz MIMO (802.11a)



Plot 7-172. Radiated Spurious Plot 26.5GHz – 40GHz MIMO (802.11a)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 121 of 151



MIMO Radiated Spurious Emission Measurements – UNII Band 1

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
6906.50	Peak	H	113	326	-61.90	13.73	0.00	58.83	68.20	-9.37
10360.00	Peak	H	207	66	-62.01	11.65	0.00	56.64	68.20	-11.56
* 15540.00	Average	H	221	43	-79.75	14.50	0.00	41.75	53.98	-12.23
* 15540.00	Peak	H	221	43	-68.33	14.50	0.00	53.17	73.98	-20.81
* 20720.00	Average	H	150	35	-63.17	3.50	-9.54	37.80	53.98	-16.18
* 20720.00	Peak	H	150	35	-55.15	3.50	-9.54	45.81	73.98	-28.17
25900.00	Peak	H	-	-	-56.31	4.57	-9.54	45.72	68.20	-22.48

Table 7-23. Radiated Measurements MIMO

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
6933.00	Peak	H	146	324	-62.76	13.81	0.00	58.05	68.20	-10.15
10400.00	Peak	H	114	49	-62.17	11.68	0.00	56.51	68.20	-11.69
* 15600.00	Average	H	-	-	-80.20	14.41	0.00	41.21	53.98	-12.77
* 15600.00	Peak	H	-	-	-68.65	14.41	0.00	52.76	73.98	-21.22
* 20800.00	Average	H	150	35	-63.31	3.60	-9.54	37.75	53.98	-16.23
* 20800.00	Peak	H	150	35	-56.23	3.60	-9.54	44.83	73.98	-29.15
26000.00	Peak	H	-	-	-56.22	4.60	-9.54	45.84	68.20	-22.36

Table 7-24. Radiated Measurements MIMO

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 122 of 151

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
6986.50	Peak	H	138	323	-63.93	14.17	0.00	57.24	68.20	-10.96
10480.00	Peak	H	239	51	-60.29	12.23	0.00	58.94	68.20	-9.26
* 15720.00	Average	H	182	66	-80.03	14.54	0.00	41.51	53.98	-12.47
* 15720.00	Peak	H	182	66	-68.24	14.54	0.00	53.30	73.98	-20.68
* 20960.00	Average	H	150	35	-63.42	3.61	-9.54	37.64	53.98	-16.34
* 20960.00	Peak	H	150	35	-55.67	3.61	-9.54	45.40	73.98	-28.58
26200.00	Peak	H	-	-	-56.64	4.72	-9.54	45.54	68.20	-22.66

Table 7-25. Radiated Measurements MIMO

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 123 of 151



MIMO Radiated Spurious Emission Measurements – UNII Band 2A

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
7013.50	Peak	H	135	323	-65.47	14.78	0.00	56.31	68.20	-11.89
10520.00	Peak	H	116	312	-59.68	12.69	0.00	60.01	68.20	-8.19
* 15780.00	Average	H	116	40	-80.15	14.92	0.00	41.77	53.98	-12.21
* 15780.00	Peak	H	116	40	-67.66	14.92	0.00	54.26	73.98	-19.72
* 21040.00	Average	H	150	37	-63.57	3.71	-9.54	37.60	53.98	-16.38
* 21040.00	Peak	H	150	37	-55.19	3.71	-9.54	45.98	73.98	-28.00
26300.00	Peak	H	-	-	-55.99	4.64	-9.54	46.11	68.20	-22.09

Table 7-26. Radiated Measurements MIMO

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5280MHz
 Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
7040.00	Peak	H	124	328	-65.52	14.98	0.00	56.46	68.20	-11.74
10560.00	Peak	H	151	314	-58.86	12.25	0.00	60.39	68.20	-7.81
* 15840.00	Average	H	115	29	-79.22	14.51	0.00	42.29	53.98	-11.69
* 15840.00	Peak	H	115	29	-66.99	14.51	0.00	54.52	73.98	-19.46
* 21120.00	Average	H	150	38	-63.90	3.83	-9.54	37.39	53.98	-16.59
* 21120.00	Peak	H	150	38	-55.78	3.83	-9.54	45.51	73.98	-28.47
26400.00	Peak	H	-	-	-56.22	4.68	-9.54	45.91	68.20	-22.29

Table 7-27. Radiated Measurements MIMO

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 124 of 151



Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
7093.00	Peak	H	128	322	-66.55	14.03	0.00	54.48	68.20	-13.72
* 10640.00	Average	H	234	310	-70.87	12.01	0.00	48.14	53.98	-5.84
* 10640.00	Peak	H	234	310	-56.84	12.01	0.00	62.17	73.98	-11.81
* 15960.00	Average	H	169	37	-80.35	15.87	0.00	42.52	53.98	-11.46
* 15960.00	Peak	H	169	37	-68.49	15.87	0.00	54.38	73.98	-19.60
* 21280.00	Average	H	150	38	-63.75	3.95	-9.54	37.66	53.98	-16.32
* 21280.00	Peak	H	150	38	-55.06	3.95	-9.54	46.35	73.98	-27.63
26600.00	Peak	H	-	-	-56.09	4.51	-9.54	45.88	68.20	-22.32

Table 7-28. Radiated Measurements MIMO

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 125 of 151

MIMO Radiated Spurious Emission Measurements – UNII Band 2C

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	Average	H	210	338	-68.18	12.13	0.00	50.95	53.98	-3.03
* 11000.00	Peak	H	210	338	-55.71	12.13	0.00	63.42	73.98	-10.56
16500.00	Peak	H	-	-	-68.29	16.13	0.00	54.84	68.20	-13.36
22000.00	Peak	H	150	41	-54.02	3.86	-9.54	47.29	68.20	-20.91
27500.00	Peak	H	-	-	-56.79	4.54	-9.54	45.20	68.20	-23.00

Table 7-29. Radiated Measurements MIMO

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5600MHz
 Channel: 120

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11200.00	Average	H	219	297	-68.32	12.24	0.00	50.92	53.98	-3.06
* 11200.00	Peak	H	219	297	-56.01	12.24	0.00	63.23	73.98	-10.75
16800.00	Peak	H	-	-	-68.65	16.46	0.00	54.81	68.20	-13.39
* 22320.00	Average	H	150	38	-61.35	3.86	-9.54	39.96	53.98	-14.02
* 22320.00	Peak	H	150	38	-54.06	3.86	-9.54	47.26	73.98	-26.72
27920.00	Peak	H	-	-	-56.98	4.90	-9.54	45.38	68.20	-22.82

Table 7-30. Radiated Measurements MIMO

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 126 of 151

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5720MHz
 Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11440.00	Average	H	325	301	-72.47	12.95	0.00	47.48	53.98	-6.50
* 11440.00	Peak	H	325	301	-60.42	12.95	0.00	59.53	73.98	-14.45
17160.00	Peak	H	168	88	-68.28	16.76	0.00	55.48	68.20	-12.72
* 22880.00	Average	H	150	320	-63.58	4.09	-9.54	37.97	53.98	-16.01
* 22880.00	Peak	H	150	320	-55.48	4.09	-9.54	46.07	73.98	-27.91
28600.00	Peak	H	-	-	-56.60	5.30	-9.54	46.16	68.20	-22.04

Table 7-31. Radiated Measurements MIMO

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	Average	H	149	359	-68.60	12.13	0.00	50.53	53.98	-3.45
* 11000.00	Peak	H	149	359	-56.32	12.13	0.00	62.81	73.98	-11.17
16500.00	Peak	H	-	-	-68.55	16.13	0.00	54.58	68.20	-13.62
22000.00	Peak	H	150	82	-56.07	3.86	-9.54	45.25	68.20	-22.95
27500.00	Peak	H	-	-	-56.85	4.54	-9.54	45.15	68.20	-23.05

Table 7-32. Radiated Measurements MIMO with WCP

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 127 of 151



MIMO Radiated Spurious Emission Measurements – UNII Band 3

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11490.00	Average	H	272	298	-71.88	12.89	0.00	48.01	53.98	-5.97
* 11490.00	Peak	H	272	298	-59.64	12.89	0.00	60.25	73.98	-13.73
17235.00	Peak	H	-	-	-68.88	16.94	0.00	55.06	68.20	-13.14
* 22980.00	Average	H	150	320	-62.92	4.00	-9.54	38.54	53.98	-15.44
* 22980.00	Peak	H	150	320	-55.05	4.00	-9.54	46.41	73.98	-27.56
28725.00	Peak	H	-	-	-56.83	5.36	-9.54	45.99	69.20	-23.21

Table 7-33. Radiated Measurements MIMO

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5785MHz
 Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11570.00	Average	H	282	304	-70.25	12.68	0.00	49.43	53.98	-4.55
* 11570.00	Peak	H	282	304	-58.51	12.68	0.00	61.17	73.98	-12.81
17355.00	Peak	H	-	-	-69.10	17.64	0.00	55.54	68.20	-12.66
23140.00	Peak	H	150	322	-54.95	3.94	-9.54	46.45	68.20	-21.75
28925.00	Peak	H	-	-	-56.28	5.33	-9.54	46.51	68.20	-21.69

Table 7-34. Radiated Measurements MIMO

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 128 of 151

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
7766.50	Peak	H	150	303	-66.67	16.04	0.00	56.37	68.20	-11.83
* 11650.00	Average	H	232	312	-71.74	13.21	0.00	48.47	53.98	-5.51
* 11650.00	Peak	H	232	312	-59.96	13.21	0.00	60.25	73.98	-13.73
17475.00	Peak	H	-	-	-68.90	17.12	0.00	55.22	68.20	-12.98
23300.00	Peak	H	150	28	-55.84	4.04	-9.54	45.65	68.20	-22.55
29125.00	Peak	H	-	-	-56.41	5.36	-9.54	46.41	68.20	-21.79

Table 7-35. Radiated Measurements MIMO

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 129 of 151

MIMO Radiated Spurious Emission Measurements – UNII Band 4

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5845MHz
 Channel: 169

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
7793.50	Average	H	126	303	-66.50	15.94	0.00	56.44	68.20	-11.76
* 11690.00	Average	H	228	329	-71.65	13.23	0.00	48.58	53.98	-5.40
* 11690.00	Peak	H	228	329	-58.70	13.23	0.00	61.53	73.98	-12.45
17535.00	Peak	H	-	-	-68.12	17.25	0.00	56.13	68.20	-12.07
23380.00	Peak	H	150	359	-55.96	3.89	-9.54	45.40	68.20	-22.80
29225.00	Peak	H	-	-	-56.26	5.50	-9.54	46.70	68.20	-21.50

Table 7-36. Radiated Measurements MIMO

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5865MHz
 Channel: 173

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
7820.00	Peak	H	144	306	-65.52	15.62	0.00	57.10	68.20	-11.10
* 11730.00	Average	H	222	330	-72.95	13.85	0.00	47.90	53.98	-6.08
* 11730.00	Peak	H	222	330	-61.33	13.85	0.00	59.52	73.98	-14.46
17595.00	Peak	H	-	-	-68.99	17.42	0.00	55.43	68.20	-12.77
23460.00	Peak	H	150	317	-56.32	4.00	-9.54	45.14	68.20	-23.06
29325.00	Peak	H	-	-	-56.75	5.64	-9.54	46.35	68.20	-21.85

Table 7-37. Radiated Measurements MIMO

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 130 of 151



Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5885MHz
 Channel: 177


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
7846.50	Peak	H	141	308	-66.79	15.58	0.00	55.79	68.20	-12.41
* 11770.00	Average	H	233	312	-72.48	13.84	0.00	48.36	53.98	-5.62
* 11770.00	Peak	H	233	312	-60.12	13.84	0.00	60.72	73.98	-13.26
17655.00	Peak	H	-	-	-68.87	17.06	0.00	55.19	68.20	-13.01
23540.00	Peak	H	150	319	-55.48	4.00	-9.54	45.99	68.20	-22.21
29425.00	Peak	H	-	-	-57.42	5.71	-9.54	45.74	68.20	-22.46

Table 7-38. Radiated Measurements MIMO


FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 131 of 151

7.6.2 MIMO Radiated Band Edge Measurements (20MHz BW)

Worst Case Mode: 802.11ac
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36




Plot 7-173. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)




Plot 7-174. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64



Plot 7-175. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)




Plot 7-176. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)


FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15-A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 132 of 151



Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100




Plot 7-177. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)



Plot 7-178. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)

Worst Case Mode: 802.11ac
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165




Plot 7-179. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 133 of 151




Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5845MHz
 Channel: 169




Plot 7-180. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 4)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5885MHz
 Channel: 177



Plot 7-181. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 4)




Plot 7-182. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 4)


FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 134 of 151

7.6.3 MIMO Radiated Band Edge Measurements (40MHz BW)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5190MHz
 Channel: 38




Plot 7-183. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)




Plot 7-184. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5310MHz
 Channel: 62




Plot 7-185. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)




Plot 7-186. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15-A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 135 of 151

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5510MHz
 Channel: 102




Plot 7-187. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)



Plot 7-188. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)

Worst Case Mode: 802.11ac
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5795MHz
 Channel: 159




Plot 7-189. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 136 of 151




Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5835MHz
 Channel: 167




Plot 7-190. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 4)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5875MHz
 Channel: 175



Plot 7-191. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 4)




Plot 7-192. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 4)


FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 137 of 151

7.6.4 MIMO Radiated Band Edge Measurements (80MHz BW)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5210MHz
 Channel: 42




Plot 7-193. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)




Plot 7-194. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5290MHz
 Channel: 58



Plot 7-195. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)




Plot 7-196. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)


FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15-A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 138 of 151



Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5530MHz
 Channel: 106




Plot 7-197. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C)



Plot 7-198. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C)


Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5775MHz
 Channel: 155



Plot 7-199. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3)


FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 139 of 151

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5855MHz
 Channel: 171




Plot 7-200. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 4)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5855MHz
 Channel: 171



Plot 7-201. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 4)




Plot 7-202. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 4)


FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15.A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 140 of 151

MIMO Radiated Band Edge Measurements (160MHz BW)

Worst Case Mode: 802.11ac
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5250MHz
 Channel: 50




Plot 7-203. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)




Plot 7-204. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5250MHz
 Channel: 50



Plot 7-205. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A)



Plot 7-206. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A)

FCC ID: A3LSMS711B	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2304260063-15-A3L	Test Dates: 5/30 - 8/8/2023	EUT Type: Portable Handset	Page 141 of 151