

TEST REPORT

FCC LTE B7 Test for SM-S721U
Certification

APPLICANT

SAMSUNG Electronics Co., Ltd.

REPORT NO.

HCT-RF-2407-FC020

DATE OF ISSUE

July 19, 2024

Tested by
Jae Ryang Do



Technical Manager
Jong Seok Lee



HCT CO., LTD.
Bongjai Huh
BongJai Huh / CEO



HCT CO.,LTD.

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.
HCT-RF-2407-FC020

DATE OF ISSUE
July 19, 2024

Additional Model
SM-S721U1

Applicant	SAMSUNG Electronics Co., Ltd. 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
Product Name	Mobile Phone
Model Name	SM-S721U
Date of Test	May 16, 2024 ~ July 19, 2024
FCC ID	A3LSMS721U
Location of Test	<input checked="" type="checkbox"/> Permanent Testing Lab <input type="checkbox"/> On Site Testing (Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 Republic of Korea)
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
Test Standard Used	FCC Rule Part: § 27
Test Results	PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	July 19, 2024	Initial Release

Notice

Content

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

CONTENTS

1. GENERAL INFORMATION	5
1.1. MAXIMUM OUTPUT POWER	6
2. INTRODUCTION	7
2.1. DESCRIPTION OF EUT.....	7
2.2. MEASURING INSTRUMENT CALIBRATION	7
2.3. TEST FACILITY	7
3. DESCRIPTION OF TESTS	8
3.1 TEST PROCEDURE	8
3.2 RADIATED POWER.....	9
3.3 RADIATED SPURIOUS EMISSIONS.....	10
3.4 PEAK- TO- AVERAGE RATIO	11
3.5 OCCUPIED BANDWIDTH.....	13
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	14
3.7 CHANNEL EDGE	15
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	17
3.9 WORST CASE(RADIATED TEST)	18
3.10 WORST CASE(CONDUCTED TEST).....	19
4. LIST OF TEST EQUIPMENT.....	20
5. MEASUREMENT UNCERTAINTY.....	21
6. SUMMARY OF TEST RESULTS	22
7. SAMPLE CALCULATION	23
8. TEST DATA(Main 2 Ant).....	25
8.1 EQUIVALENT ISOTROPIC RADIATED POWER.....	25
8.2 RADIATED SPURIOUS EMISSIONS.....	27
8.3 PEAK-TO-AVERAGE RATIO	31
8.4 OCCUPIED BANDWIDTH.....	32
8.5 CONDUCTED SPURIOUS EMISSIONS	33
8.6 CHANNEL EDGE	34
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	35
9. TEST DATA(Sub 5 Ant)	47
9.1 EQUIVALENT ISOTROPIC RADIATED POWER.....	47
9.2 RADIATED SPURIOUS EMISSIONS.....	49
9.3 PEAK-TO-AVERAGE RATIO	53
9.4 OCCUPIED BANDWIDTH.....	54
9.5 CONDUCTED SPURIOUS EMISSIONS	55
9.6 CHANNEL EDGE	56
9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	57
10. TEST PLOTS(Main 2 Ant).....	69
11. TEST PLOTS(Sub 5 Ant)	150
12. ANNEX A_ TEST SETUP PHOTO	231

MEASUREMENT REPORT**1. GENERAL INFORMATION**

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMS721U
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s):	§ 27
EUT Type:	Mobile phone
Model(s):	SM-S721U
Additional Model(s)	SM-S721U1
Tx Frequency:	2502.5 – 2567.5 : 5 MHz 2505.0 – 2565.0 : 10 MHz 2507.5 – 2562.5 : 15 MHz 2510.0 – 2560.0 : 20 MHz
Date(s) of Tests:	May 16, 2024 ~ July 19, 2024
Serial number:	Radiated : R3CX506M1WK(ANT B), 67d50ecc63197ece(ANT F) Conducted : R3CX40SWJDA

1.1. MAXIMUM OUTPUT POWER

Main 2 Ant (Antenna B)

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band 7 (5)	2502.5 – 2567.5	4M52G7D	QPSK	0.125	20.97
		4M52W7D	16QAM	0.104	20.17
		4M54W7D	64QAM	0.083	19.20
		4M52W7D	256QAM	0.041	16.13
LTE – Band 7 (10)	2505.0 – 2565.0	9M03G7D	QPSK	0.132	21.21
		9M01W7D	16QAM	0.109	20.37
		9M04W7D	64QAM	0.085	19.31
		9M02W7D	256QAM	0.044	16.39
LTE – Band 7 (15)	2507.5 – 2562.5	13M5G7D	QPSK	0.136	21.32
		13M5W7D	16QAM	0.111	20.47
		13M5W7D	64QAM	0.088	19.45
		13M4W7D	256QAM	0.045	16.50
LTE – Band 7 (20)	2510.0 – 2560.0	17M9G7D	QPSK	0.138	21.39
		17M9W7D	16QAM	0.115	20.59
		17M9W7D	64QAM	0.090	19.56
		17M9W7D	256QAM	0.047	16.68

Sub 5 Ant Main 2 Ant (Antenna F)

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band 7 (5)	2502.5 – 2567.5	4M54G7D	QPSK	0.075	18.76
		4M52W7D	16QAM	0.062	17.91
		4M53W7D	64QAM	0.049	16.94
		4M53W7D	256QAM	0.023	13.70
LTE – Band 7 (10)	2505.0 – 2565.0	9M04G7D	QPSK	0.080	19.03
		9M01W7D	16QAM	0.065	18.13
		9M02W7D	64QAM	0.052	17.17
		9M01W7D	256QAM	0.025	14.01
LTE – Band 7 (15)	2507.5 – 2562.5	13M5G7D	QPSK	0.081	19.10
		13M5W7D	16QAM	0.068	18.35
		13M5W7D	64QAM	0.054	17.31
		13M5W7D	256QAM	0.026	14.13
LTE – Band 7 (20)	2510.0 – 2560.0	17M9G7D	QPSK	0.082	19.15
		17M9W7D	16QAM	0.068	18.31
		17M9W7D	64QAM	0.054	17.31
		18M0W7D	256QAM	0.026	14.11

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS and LTE, Sub 6, mmWave. It also supports IEEE 802.11 a/b/g/n/ac/ax (20/40/80/160 MHz), Bluetooth(iPA, ePA), BT LE(iPA, ePA), NFC, WPT, WIFI 6E.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d \text{ (dBm)} = P_g \text{ (dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz
2. VBW \geq 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points > 2 x span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
 3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.
- The spurious emissions is calculated by the following formula;


$$\text{Result } (\text{dBm}) = P_g (\text{dBm}) - \text{cable loss } (\text{dB}) + \text{antenna gain } (\text{dBi})$$

Where: P_g is the generator output power into the substitution antenna.

If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP } (\text{dBm}) = \text{ERP } (\text{dBm}) + 2.15$$

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - .- for continuous transmissions, set to 1 ms,
 - .- or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R \text{ (dB)} = P_{Pk \text{ (dBm)}} - P_{Avg \text{ (dBm)}} \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)


The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.

1. Set the RBW \geq OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times (\text{number of points in sweep}) \times (\text{transmission symbol period})$.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW \geq OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times \text{span} / \text{RBW}$.
5. Sweep time:
Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep (automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to “free run.”
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6 \text{ dB}$ if the duty cycle is a constant 25 %.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.


The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.

Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5 % of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99 % occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW \geq 3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time = auto
6. Number of points in sweep \geq 2 x Span / RBW

3.7 CHANNEL EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum power and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings


1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. Within 1MHz of the channel edge the RBW should be 2% of EBW, then 1 MHz after that.
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span}/\text{RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes

1. The attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge,
2. $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge.
3. $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge.
4. The attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz.
5. $55 + 10 \log(P)$ dB at or below 2490.5 MHz.
6. X is the greater of 6MHz or the actual emission bandwidth
7. The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer

Where Margin < 1 dB the emission level is either corrected by $10 \log(1 \text{ MHz} / \text{RB})$ or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.

2. Primary Supply Voltage:

- .- Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.
- .- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).

2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter.

Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.

3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.

- All modes of operation were investigated and the worst case configuration results are reported.

Mode : Stand alone, Stand alone + External accessories (Earphone, AC adapter, etc)

Worst case : Stand alone

- All simultaneous transmission scenarios of operation were investigated, and the test results showed no additional significant emissions relative to the least restrictive limit were observed.

Therefore, only the worst case(stand-alone) results were reported.

- The worst case is reported with the EUT positioning, modulations, and paging service configurations shown in the test data

- Please refer to the table below.

- SM-S721U & additional models were tested and the worst case results are reported.

(Worst case : SM-S721U)

[Main 2 Ant Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	See Section 8.1		X
Radiated Spurious and Harmonic Emissions	QPSK	See Section 8.2		Y

[Sub 5 Ant Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	See Section 9.1		X
Radiated Spurious and Harmonic Emissions	QPSK	See Section 9.2		Z

3.10 WORST CASE(CONDUCTED TEST)

- All modes of operation were investigated and the worst case configuration results are reported.

- SM-F741U & additional models were tested and the worst case results are reported.

(Worst case : SM-F741U)

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM, 256QAM	5, 10, 15, 20	Mid	Full RB	0
Peak-To-Average Ratio	QPSK, 16QAM, 64QAM, 256QAM	5, 10, 15, 20	Mid	Full RB	0
Band Edge	QPSK	5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		15	Low	1	0
			High	1	74
		20	Low	1	0
			High	1	99
		5, 10, 15, 20	Low, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	QPSK	5, 10, 15, 20	Low, Mid, High	1	0

4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
RF Switching System	FBSR-02B(1.2G HPF+LNA)	T&M SYSTEM	F1L1	12/11/2024	Annual
RF Switching System	FBSR-02B(3.3G HPF+LNA)	T&M SYSTEM	F1L2	12/11/2024	Annual
Power Splitter(DC ~ 26.5 GHz)	11667B	Hewlett Packard	5001	04/17/2025	Annual
DC Power Supply	E3632A	Agilent	KR01009150	04/18/2025	Annual
Dipole Antenna	UHAP	Schwarzbeck	557	03/09/2025	Biennial
Dipole Antenna	UHAP	Schwarzbeck	558	03/09/2025	Biennial
Chamber	SU-642	ESPEC	93008124	02/19/2025	Annual
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	147	08/17/2025	Biennial
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	9120D-1298	09/11/2025	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170342	09/29/2024	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170124	03/28/2025	Biennial
Signal Analyzer(10 Hz ~ 26.5 GHz)	N9020A	Agilent	MY52090906	04/19/2025	Annual
ATTENUATOR(20 dB)	8493C	Hewlett Packard	17280	04/17/2025	Annual
Spectrum Analyzer(10 Hz ~ 40 GHz)	FSV40	REOHDE & SCHWARZ	100931	08/17/2024	Annual
Base Station	8960 (E5515C)	Agilent	MY48360800	08/10/2024	Annual
Loop Antenna(9 kHz ~ 30 MHz)	FMZB1513	Schwarzbeck	1513-333	03/07/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	895	09/16/2024	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	1135	09/16/2024	Biennial
Wideband Radio Communication Tester	MT8821C	Anritsu Corp.	6262094331	11/17/2024	Annual
Wideband Radio Communication Tester	MT8820C	Anritsu Corp.	6201026545	12/11/2024	Annual
SIGNAL GENERATOR (100 kHz ~ 40 GHz)	SMW200A	REOHDE & SCHWARZ	100988	02/26/2025	Annual
Signal Analyzer(5 Hz ~ 40.0 GHz)	N9030B	KEYSIGHT	MY55480167	05/17/2025	Annual
FCC LTE Mobile Conducted RF Automation Test Software	-	HCT CO., LTD.,	-	-	-

Note:

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
2. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (\pm dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.98 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.36 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.70 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.52 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.66 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (Above 40 GHz)	5.58 (Confidence level about 95 %, $k=2$)

6. SUMMARY OF TEST RESULTS

6.1 Test Condition: Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§ 2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§ 2.1051, § 27.53(m)(4)	<ul style="list-style-type: none">■ $< 40 + 10\log_{10} (P[\text{Watts}])$ at Channel edges■ $< 43 + 10\log_{10} (P[\text{Watts}])$ between 5 and X MHz from Channel edges■ $< 55 + 10\log_{10} (P[\text{Watts}])$ beyond X MHz beyond from Channel edges■ $< 43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz	PASS
Conducted Output Power	§ 2.1046	N/A	<u>See Note1</u>
Frequency stability / variation of ambient temperature	§ 2.1055, § 27.54	Emission must remain in band	PASS

Note:

1. See SAR Report

6.2 Test Condition: Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§ 27.50(h)(2)	< 2 Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§ 2.1053, § 27.53(m)(4)	$< 55 + 10\log_{10} (P[\text{Watts}])$	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA(Main 2 Ant)

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured	Substitute	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
			Level (dBm)	Level (dBm)				W	W	dBm	Size	Offset
2502.5		QPSK	-23.87	12.95	10.51	2.57	H	< 2.00	0.123	20.89	1	24
		16-QAM	-24.63	12.19	10.51	2.57	H		0.103	20.13		
		64-QAM	-25.62	11.20	10.51	2.57	H		0.082	19.14		
		256-QAM	-28.66	8.16	10.51	2.57	H		0.041	16.10		
2535.0	LTE B7/ 5 MHz	QPSK	-24.01	12.93	10.67	2.63	H	< 2.00	0.125	20.97	1	0
		16-QAM	-24.81	12.13	10.67	2.63	H		0.104	20.17		
		64-QAM	-25.78	11.16	10.67	2.63	H		0.083	19.20		
		256-QAM	-28.85	8.09	10.67	2.63	H		0.041	16.13		
2567.5		QPSK	-24.04	12.65	10.65	2.72	H	< 2.00	0.114	20.58	1	0
		16-QAM	-24.86	11.83	10.65	2.72	H		0.095	19.76		
		64-QAM	-25.88	10.81	10.65	2.72	H		0.075	18.74		
		256-QAM	-28.88	7.81	10.65	2.72	H		0.038	15.74		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured	Substitute	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
			Level (dBm)	Level (dBm)				W	W	dBm	Size	Offset
2505.0		QPSK	-23.87	12.99	10.55	2.57	H	< 2.00	0.125	20.97	1	49
		16-QAM	-24.61	12.25	10.55	2.57	H		0.105	20.23		
		64-QAM	-25.66	11.20	10.55	2.57	H		0.083	19.18		
		256-QAM	-28.63	8.23	10.55	2.57	H		0.042	16.21		
2535.0	LTE B7/ 10 MHz	QPSK	-23.77	13.17	10.67	2.63	H	< 2.00	0.132	21.21	1	0
		16-QAM	-24.61	12.33	10.67	2.63	H		0.109	20.37		
		64-QAM	-25.67	11.27	10.67	2.63	H		0.085	19.31		
		256-QAM	-28.59	8.35	10.67	2.63	H		0.044	16.39		
2565.0		QPSK	-23.93	13.00	10.66	2.70	H	< 2.00	0.124	20.95	1	0
		16-QAM	-24.79	12.14	10.66	2.70	H		0.102	20.09		
		64-QAM	-25.80	11.13	10.66	2.70	H		0.081	19.08		
		256-QAM	-28.71	8.22	10.66	2.70	H		0.041	16.17		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured	Substitute	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
			Level (dBm)	Level (dBm)				W	W	dBm	Size	Offset
2507.5		QPSK	-23.73	13.16	10.59	2.57	H	< 2.00	0.131	21.18	1	74
		16-QAM	-24.54	12.35	10.59	2.57	H		0.109	20.37		
		64-QAM	-25.55	11.34	10.59	2.57	H		0.086	19.36		
		256-QAM	-28.49	8.40	10.59	2.57	H		0.044	16.42		
2535.0	LTE B7/ 15 MHz	QPSK	-23.66	13.28	10.67	2.63	H	< 2.00	0.136	21.32	1	0
		16-QAM	-24.51	12.43	10.67	2.63	H		0.111	20.47		
		64-QAM	-25.53	11.41	10.67	2.63	H		0.088	19.45		
		256-QAM	-28.48	8.46	10.67	2.63	H		0.045	16.50		
2562.5		QPSK	-23.97	13.20	10.66	2.68	H	< 2.00	0.131	21.18	1	0
		16-QAM	-24.72	12.45	10.66	2.68	H		0.110	20.43		
		64-QAM	-25.77	11.40	10.66	2.68	H		0.087	19.38		
		256-QAM	-28.81	8.36	10.66	2.68	H		0.043	16.34		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured	Substitute	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
			Level (dBm)	Level (dBm)				W	W	dBm	Size	Offset
2510.0		QPSK	-23.79	13.10	10.59	2.57	H	< 2.00	0.129	21.12	1	99
		16-QAM	-24.54	12.35	10.59	2.57	H		0.109	20.37		
		64-QAM	-25.62	11.27	10.59	2.57	H		0.085	19.29		
		256-QAM	-28.53	8.36	10.59	2.57	H		0.043	16.38		
2535.0	LTE B7/ 20 MHz	QPSK	-23.79	13.15	10.67	2.63	H	< 2.00	0.132	21.19	1	0
		16-QAM	-24.68	12.26	10.67	2.63	H		0.107	20.30		
		64-QAM	-25.65	11.29	10.67	2.63	H		0.086	19.33		
		256-QAM	-28.56	8.38	10.67	2.63	H		0.044	16.42		
2560.0		QPSK	-23.76	13.41	10.66	2.68	H	< 2.00	0.138	21.39	1	0
		16-QAM	-24.56	12.61	10.66	2.68	H		0.115	20.59		
		64-QAM	-25.59	11.58	10.66	2.68	H		0.090	19.56		
		256-QAM	-28.47	8.70	10.66	2.68	H		0.047	16.68		

8.2 RADIATED SPURIOUS EMISSIONS

- OPERATING FREQUENCY: 2535.0 MHz
- MEASURED OUTPUT POWER: 20.97 dBm = 0.125 W
- MODE: LTE B7
- MODULATION SIGNAL: 5 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10} (W) =$ 45.97 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitut e Level (dBm)	C.L	Pol	Result (dBm)	dBc	RB	
									Size	Offset
20775 (2502.5)	5 005.00	-52.14	12.56	-62.06	3.85	H	-53.35	74.32	1	24
	7 507.50	-56.85	10.78	-57.26	4.71	V	-51.19	72.17		
	10 010.00	-54.62	11.23	-50.44	5.52	V	-44.73	65.71		
21100 (2535.0)	5 070.00	-49.07	12.31	-56.69	3.73	V	-48.11	69.08	1	0
	7 605.00	-53.53	11.10	-54.38	4.78	V	-48.06	69.03		
	10 140.00	-54.75	11.59	-50.96	5.55	V	-44.92	65.89		
21425 (2567.5)	5 135.00	-41.10	12.33	-48.97	3.94	H	-40.58	61.55	1	0
	7 702.50	-50.62	11.35	-51.72	4.77	V	-45.14	66.11		
	10 270.00	-57.49	11.57	-51.96	5.55	V	-45.94	66.91		

OPERATING FREQUENCY: 2535.0 MHz
 MEASURED OUTPUT POWER: 21.21 dBm = 0.132 W
 MODE: LTE B7
 MODULATION SIGNAL: 10 MHz QPSK
 DISTANCE: 1 meters
 LIMIT: $55 + 10 \log_{10} (W) =$ 46.21 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitut e Level (dBm)	C.L	Pol	Result (dBm)	dBc	RB	
									Size	Offset
20800 (2505.0)	5 010.00	-53.18	12.55	-63.20	3.88	H	-54.53	75.74	1	49
	7 515.00	-53.04	10.80	-53.60	4.71	V	-47.51	68.72		
	10 020.00	-56.05	11.27	-51.76	5.54	V	-46.03	67.24		
21100 (2535.0)	5 070.00	-48.64	12.31	-56.26	3.73	V	-47.68	68.89	1	0
	7 605.00	-55.00	11.10	-55.85	4.78	V	-49.53	70.74		
	10 140.00	-54.94	11.59	-51.15	5.55	V	-45.11	66.32		
21400 (2565.0)	5 130.00	-45.18	12.31	-53.00	3.96	H	-44.65	65.86	1	0
	7 695.00	-49.54	11.35	-50.58	4.76	V	-44.00	65.21		
	10 260.00	-54.13	11.58	-48.52	5.54	V	-42.48	63.70		

OPERATING FREQUENCY: 2535.0 MHz
 MEASURED OUTPUT POWER: 21.32 dBm = 0.136 W
 MODE: LTE B7
 MODULATION SIGNAL: 15 MHz QPSK
 DISTANCE: 1 meters
 LIMIT: $55 + 10 \log_{10} (W) =$ 46.32 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitut e Level (dBm)	C.L	Pol	Result (dBm)	dBc	RB	
									Size	Offset
20825 (2507.5)	5 015.00	-52.80	12.54	-62.93	3.90	H	-54.29	75.61	1	79
	7 522.50	-56.13	10.82	-56.83	4.71	V	-50.72	72.05		
	10 030.00	-54.91	11.31	-50.76	5.53	V	-44.98	66.30		
21100 (2535.0)	5 070.00	-47.49	12.31	-55.11	3.73	H	-46.53	67.85	1	0
	7 605.00	-55.58	11.10	-56.43	4.78	V	-50.11	71.43		
	10 140.00	-56.17	11.59	-52.38	5.55	V	-46.34	67.66		
21375 (2562.5)	5 125.00	-44.71	12.29	-52.66	3.97	H	-44.34	65.66	1	0
	7 687.50	-54.80	11.34	-55.78	4.75	V	-49.19	70.52		
	10 250.00	-57.50	11.59	-52.07	5.54	V	-46.02	67.34		

OPERATING FREQUENCY: 2560.0 MHz
 MEASURED OUTPUT POWER: 21.39 dBm = 0.138 W
 MODE: LTE B7
 MODULATION SIGNAL: 20 MHz QPSK
 DISTANCE: 1 meters
 LIMIT: $55 + 10 \log_{10} (W) =$ 46.39 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitut e Level (dBm)	C.L	Pol	Result (dBm)	dBc	RB	
									Size	Offse t
20850 (2510.0)	5 020.00	-50.06	12.52	-60.29	3.91	H	-51.68	73.07	1	99
	7 530.00	-58.07	10.85	-58.65	4.72	H	-52.52	73.91		
	10 040.00	-55.48	11.34	-51.82	5.51	V	-45.99	67.38		
21100 (2535.0)	5 070.00	-47.85	12.31	-55.47	3.73	H	-46.89	68.27	1	0
	7 605.00	-56.42	11.10	-57.27	4.78	V	-50.95	72.34		
	10 140.00	-56.36	11.59	-52.57	5.55	H	-46.53	67.92		
21350 (2560.0)	5 120.00	-44.54	12.26	-52.62	3.97	H	-44.33	65.72	1	0
	7 680.00	-53.41	11.33	-54.00	4.75	H	-47.42	68.81		
	10 240.00	-58.65	11.59	-53.74	5.53	V	-47.68	69.07		

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)		
7	5 MHz	2535.0	QPSK	25	0	5.08		
			16-QAM			5.71		
			64-QAM			5.85		
			256-QAM			6.30		
	10 MHz		QPSK	50		5.17		
			16-QAM			5.70		
			64-QAM			5.90		
			256-QAM			6.31		
	15 MHz		QPSK	75		5.11		
			16-QAM			5.69		
			64-QAM			5.86		
			256-QAM			6.33		
	20 MHz		QPSK	100		5.09		
			16-QAM			5.74		
			64-QAM			5.91		
			256-QAM			6.34		

Note:

- Plots of the EUT's Peak- to- Average Ratio are shown Page 70 ~ 85.

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)		
7	5 MHz	2535.0	QPSK	25	0	4.5228		
			16-QAM			4.5241		
			64-QAM			4.5381		
			256-QAM			4.5149		
	10 MHz		QPSK	50		9.0304		
			16-QAM			9.0128		
			64-QAM			9.0368		
			256-QAM			9.0165		
	15 MHz		QPSK	75		13.461		
			16-QAM			13.450		
			64-QAM			13.468		
			256-QAM			13.427		
	20 MHz		QPSK	100		17.918		
			16-QAM			17.892		
			64-QAM			17.890		
			256-QAM			17.900		

Note:

- Plots of the EUT's Occupied Bandwidth are shown Page 86 ~ 101.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
7	5	2502.5	26.1236	30.131	-76.897	-46.766	-25.00
		2535.0	25.8423	30.131	-76.790	-46.659	
		2567.5	26.1513	30.131	-76.740	-46.609	
	10	2505.0	26.1593	30.131	-76.352	-46.221	
		2535.0	26.1589	30.131	-76.781	-46.650	
		2565.0	26.1967	30.131	-76.725	-46.594	
	15	2507.5	26.4084	30.131	-76.960	-46.829	
		2535.0	26.4305	30.131	-76.710	-46.579	
		2562.5	25.8027	30.131	-76.862	-46.731	
	20	2510.0	26.1211	30.131	-76.717	-46.586	
		2535.0	26.1534	30.131	-76.702	-46.571	
		2560.0	26.0977	30.131	-76.726	-46.595	

Note:

- Plots of the EUT's Conducted Spurious Emissions are shown Page 102 ~ 125.
- Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
- Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
- Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131

8.6 CHANNEL EDGE

Band Width (Modulation)	Frequency (MHz)	RB Size / Offset	C.E ~ (C.E ± 1 MHz)		2 496 MHz ~ 2 499 MHz	(C.E + 1 MHz) ~ (C.E + 5 MHz)	2 490.5 MHz ~ 2 496 MHz	(C.E + 5 MHz) ~ (C.E + X MHz)	Below 2 490.5 MHz	Above (C.E + X MHz)
			Lower	Upper	Lower	Upper	Lower	Upper	Lower	Upper
5 MHz (QPSK)	2502.5	25 / 0	-21.41	-21.02	-24.51	-24.92	-30.27	-33.41	-44.40	-36.94
10 MHz (QPSK)	2505.0	50 / 0	-25.16	-24.42	-26.85	-27.59	-30.72	-31.73	-37.51	-38.55
15 MHz (QPSK)	2507.5	75 / 0	-27.42	-27.51	-29.85	-31.24	-33.20	-34.43	-35.76	-40.11
20 MHz (QPSK)	2510.0	100 / 0	-29.81	-30.13	-31.96	-33.41	-34.84	-34.16	-37.88	-39.88
Limit(dBm)			-10.0		-10.0		-13.0		-25.0	

Band Width (Modulation)	Frequency (MHz)	RB Size / Offset	C.E ~ (C.E ± 1 MHz)		(C.E ± 1 MHz) ~ (C.E ± 5 MHz)	
			Lower	Upper	Lower	Upper
5 MHz (QPSK)	2535.0	25 / 0	-20.31	-19.90	-17.35	-16.74
	2567.5	25 / 0	-20.07	-21.88	-21.95	-23.49
10 MHz (QPSK)	2535.0	50 / 0	-22.73	-21.78	-19.78	-18.81
	2565.0	50 / 0	-24.23	-24.81	-24.13	-24.76
15 MHz (QPSK)	2535.0	75 / 0	-25.50	-24.03	-23.57	-22.22
	2562.5	75 / 0	-27.27	-27.61	-28.30	-28.49
20 MHz (QPSK)	2535.0	100 / 0	-27.33	-25.94	-26.18	-24.49
	2560.0	100 / 0	-29.89	-30.61	-30.88	-32.15
Limit(dBm)			-10.0		-10.0	

Band Width (Modulation)	Frequency (MHz)	Resource Block Size	(C.E ± 5 MHz) ~ (C.E ± X MHz)		Above (C.E ± X MHz)	
			Lower	Upper	Lower	Upper
5 MHz (QPSK)	2535.0	25 / 0	-31.27	-31.08	-34.88	-35.09
	2567.5	25 / 0	-31.86	-37.53	-35.47	-41.50
10 MHz (QPSK)	2535.0	50 / 0	-24.92	-23.00	-35.35	-35.10
	2565.0	50 / 0	-28.21	-30.83	-34.79	-44.72
15 MHz (QPSK)	2535.0	75 / 0	-26.50	-24.37	-37.44	-37.51
	2562.5	75 / 0	-30.02	-32.51	-37.53	-50.27
20 MHz (QPSK)	2535.0	100 / 0	-28.35	-26.37	-38.99	-39.42
	2560.0	100 / 0	-31.77	-35.00	-41.22	-51.77
Limit(dBm)			-13.0		-25.0	


Note:

1. C.E = Channel Edge
2. X = X is the greater of 6 MHz or the actual emission bandwidth.
3. X = 6 MHz(5 MHz Bandwidth), 10 MHz(10 MHz Bandwidth), 15 MHz(15 MHz Bandwidth), 20 MHz(20 MHz Bandwidth)
4. Plots of the EUT's Channel Edge are shown Page 126 ~ 149.

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


- MODE: LTE 7
 OPERATING FREQUENCY: 2,502,500,000 Hz
 CHANNEL: 20775 (5 MHz)
 REFERENCE VOLTAGE: 3.880 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	2502 500 005	0.0	0.000 000	0.000
100 %		-30	2502 500 008	3.5	0.000 000	0.001
100 %		-20	2502 500 008	3.5	0.000 000	0.001
100 %		-10	2502 500 008	3.3	0.000 000	0.001
100 %		0	2502 500 010	5.6	0.000 000	0.002
100 %		+10	2502 500 008	3.2	0.000 000	0.001
100 %		+30	2502 500 009	3.9	0.000 000	0.002
100 %		+40	2502 500 009	4.6	0.000 000	0.002
100 %		+50	2502 500 008	3.3	0.000 000	0.001
Batt. Endpoint	3.300	+20	2502 500 009	4.1	0.000 000	0.002




MODE: LTE 7
 OPERATING FREQUENCY: 2,505,000,000 Hz
 CHANNEL: 20800 (10 MHz)
 REFERENCE VOLTAGE: 3.880 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2505 000 005	0.0	0.000 000	0.000
100 %		-30	2505 000 009	4.0	0.000 000	0.002
100 %		-20	2505 000 013	7.5	0.000 000	0.003
100 %		-10	2505 000 009	3.9	0.000 000	0.002
100 %		0	2505 000 009	3.4	0.000 000	0.001
100 %		+10	2505 000 010	5.2	0.000 000	0.002
100 %		+30	2505 000 009	3.4	0.000 000	0.001
100 %		+40	2505 000 010	5.0	0.000 000	0.002
100 %		+50	2505 000 011	5.6	0.000 000	0.002
Batt. Endpoint	3.300	+20	2505 000 010	4.3	0.000 000	0.002




- MODE: LTE 7
- OPERATING FREQUENCY: 2,507,500,000 Hz
- CHANNEL: 20825 (15 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2507 500 005	0.0	0.000 000	0.000
100 %		-30	2507 500 008	3.0	0.000 000	0.001
100 %		-20	2507 500 008	3.4	0.000 000	0.001
100 %		-10	2507 500 009	4.3	0.000 000	0.002
100 %		0	2507 500 007	2.0	0.000 000	0.001
100 %		+10	2507 500 008	2.8	0.000 000	0.001
100 %		+30	2507 500 010	4.8	0.000 000	0.002
100 %		+40	2507 500 009	3.8	0.000 000	0.002
100 %		+50	2507 500 010	4.7	0.000 000	0.002
Batt. Endpoint	3.300	+20	2507 500 008	3.5	0.000 000	0.001




- MODE: LTE 7
- OPERATING FREQUENCY: 2,510,000,000 Hz
- CHANNEL: 20850 (20 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2510 000 004	0.0	0.000 000	0.000
100 %		-30	2510 000 010	5.5	0.000 000	0.002
100 %		-20	2510 000 009	4.8	0.000 000	0.002
100 %		-10	2510 000 010	5.9	0.000 000	0.002
100 %		0	2510 000 009	5.4	0.000 000	0.002
100 %		+10	2510 000 008	3.5	0.000 000	0.001
100 %		+30	2510 000 009	5.1	0.000 000	0.002
100 %		+40	2510 000 008	3.9	0.000 000	0.002
100 %		+50	2510 000 009	4.6	0.000 000	0.002
Batt. Endpoint	3.300	+20	2510 000 010	5.6	0.000 000	0.002




- MODE: LTE 7
- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (5 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2535 000 005	0.0	0.000 000	0.000
100 %		-30	2535 000 009	4.0	0.000 000	0.002
100 %		-20	2535 000 011	6.4	0.000 000	0.003
100 %		-10	2535 000 009	4.5	0.000 000	0.002
100 %		0	2535 000 010	4.8	0.000 000	0.002
100 %		+10	2535 000 008	3.4	0.000 000	0.001
100 %		+30	2535 000 009	4.1	0.000 000	0.002
100 %		+40	2535 000 009	4.6	0.000 000	0.002
100 %		+50	2535 000 010	5.0	0.000 000	0.002
Batt. Endpoint	3.300	+20	2535 000 009	4.3	0.000 000	0.002




MODE: LTE 7
 OPERATING FREQUENCY: 2,535,000,000 Hz
 CHANNEL: 21100 (10 MHz)
 REFERENCE VOLTAGE: 3.880 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2535 000 003	0.0	0.000 000	0.000
100 %		-30	2535 000 008	4.7	0.000 000	0.002
100 %		-20	2535 000 008	4.9	0.000 000	0.002
100 %		-10	2535 000 006	2.7	0.000 000	0.001
100 %		0	2535 000 007	3.7	0.000 000	0.001
100 %		+10	2535 000 008	4.8	0.000 000	0.002
100 %		+30	2535 000 007	4.0	0.000 000	0.002
100 %		+40	2535 000 008	4.7	0.000 000	0.002
100 %		+50	2535 000 009	5.6	0.000 000	0.002
Batt. Endpoint	3.300	+20	2535 000 006	3.0	0.000 000	0.001




- MODE: LTE 7
- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (15 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2534 999 997	0.0	0.000 000	0.000
100 %		-30	2535 000 000	3.6	0.000 000	0.001
100 %		-20	2535 000 001	4.9	0.000 000	0.002
100 %		-10	2534 999 999	2.5	0.000 000	0.001
100 %		0	2535 000 002	5.4	0.000 000	0.002
100 %		+10	2535 000 001	4.8	0.000 000	0.002
100 %		+30	2535 000 000	3.8	0.000 000	0.001
100 %		+40	2534 999 999	2.8	0.000 000	0.001
100 %		+50	2535 000 000	3.3	0.000 000	0.001
Batt. Endpoint	3.300	+20	2534 999 999	2.8	0.000 000	0.001




MODE: LTE 7
 OPERATING FREQUENCY: 2,535,000,000 Hz
 CHANNEL: 21100 (20 MHz)
 REFERENCE VOLTAGE: 3.880 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2535 000 004	0.0	0.000 000	0.000
100 %		-30	2535 000 008	4.6	0.000 000	0.002
100 %		-20	2535 000 008	4.4	0.000 000	0.002
100 %		-10	2535 000 009	5.3	0.000 000	0.002
100 %		0	2535 000 007	3.9	0.000 000	0.002
100 %		+10	2535 000 008	4.7	0.000 000	0.002
100 %		+30	2535 000 008	4.9	0.000 000	0.002
100 %		+40	2535 000 006	2.2	0.000 000	0.001
100 %		+50	2535 000 009	5.7	0.000 000	0.002
Batt. Endpoint	3.300	+20	2535 000 008	4.7	0.000 000	0.002




- MODE: LTE 7
- OPERATING FREQUENCY: 2,567,500,000 Hz
- CHANNEL: 21425 (5 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2567 500 004	0.0	0.000 000	0.000
100 %		-30	2567 500 008	3.7	0.000 000	0.001
100 %		-20	2567 500 009	4.5	0.000 000	0.002
100 %		-10	2567 500 011	6.7	0.000 000	0.003
100 %		0	2567 500 012	7.2	0.000 000	0.003
100 %		+10	2567 500 008	3.9	0.000 000	0.002
100 %		+30	2567 500 010	5.5	0.000 000	0.002
100 %		+40	2567 500 010	5.5	0.000 000	0.002
100 %		+50	2567 500 008	3.3	0.000 000	0.001
Batt. Endpoint	3.300	+20	2567 500 009	4.2	0.000 000	0.002




- MODE: LTE 7
- OPERATING FREQUENCY: 2,565,000,000 Hz
- CHANNEL: 21400 (10 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2565 000 005	0.0	0.000 000	0.000
100 %		-30	2565 000 009	3.1	0.000 000	0.001
100 %		-20	2565 000 011	5.4	0.000 000	0.002
100 %		-10	2565 000 008	2.8	0.000 000	0.001
100 %		0	2565 000 009	3.2	0.000 000	0.001
100 %		+10	2565 000 011	5.4	0.000 000	0.002
100 %		+30	2565 000 009	3.6	0.000 000	0.001
100 %		+40	2565 000 008	2.9	0.000 000	0.001
100 %		+50	2565 000 008	3.0	0.000 000	0.001
Batt. Endpoint	3.300	+20	2565 000 010	4.3	0.000 000	0.002




- MODE: LTE 7
- OPERATING FREQUENCY: 2,562,500,000 Hz
- CHANNEL: 21375 (15 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2562 500 002	0.0	0.000 000	0.000
100 %		-30	2562 500 006	4.2	0.000 000	0.002
100 %		-20	2562 500 005	2.6	0.000 000	0.001
100 %		-10	2562 500 006	4.5	0.000 000	0.002
100 %		0	2562 500 007	4.7	0.000 000	0.002
100 %		+10	2562 500 006	4.2	0.000 000	0.002
100 %		+30	2562 500 006	3.8	0.000 000	0.001
100 %		+40	2562 500 007	4.8	0.000 000	0.002
100 %		+50	2562 500 006	4.3	0.000 000	0.002
Batt. Endpoint	3.300	+20	2562 500 007	5.0	0.000 000	0.002



- MODE: LTE 7
- OPERATING FREQUENCY: 2,560,000,000 Hz
- CHANNEL: 21350 (20 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2560 000 003	0.0	0.000 000	0.000
100 %		-30	2560 000 007	4.1	0.000 000	0.002
100 %		-20	2560 000 006	2.9	0.000 000	0.001
100 %		-10	2560 000 006	3.2	0.000 000	0.001
100 %		0	2560 000 007	3.6	0.000 000	0.001
100 %		+10	2560 000 006	2.8	0.000 000	0.001
100 %		+30	2560 000 007	3.5	0.000 000	0.001
100 %		+40	2560 000 007	3.9	0.000 000	0.002
100 %		+50	2560 000 006	3.2	0.000 000	0.001
Batt. Endpoint	3.300	+20	2560 000 008	4.5	0.000 000	0.002



9. TEST DATA(Sub 5 Ant)

9.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured	Substitute	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
			Level (dBm)	Level (dBm)				W	W	dBm	Size	Offset
2502.5		QPSK	-26.08	10.74	10.51	2.57	H	< 2.00	0.074	18.68	1	0
		16-QAM	-26.86	9.96	10.51	2.57	H		0.062	17.90		
		64-QAM	-27.91	8.91	10.51	2.57	H		0.048	16.85		
		256-QAM	-31.12	5.70	10.51	2.57	H		0.023	13.64		
2535.0	LTE B7/ 5 MHz	QPSK	-26.22	10.72	10.67	2.63	H		0.075	18.76	1	0
		16-QAM	-27.07	9.87	10.67	2.63	H		0.062	17.91		
		64-QAM	-28.04	8.90	10.67	2.63	H		0.049	16.94		
		256-QAM	-31.28	5.66	10.67	2.63	H		0.023	13.70		
2567.5		QPSK	-27.23	9.46	10.65	2.72	H	< 2.00	0.055	17.39	1	0
		16-QAM	-27.79	8.90	10.65	2.72	H		0.048	16.83		
		64-QAM	-28.42	8.27	10.65	2.72	H		0.042	16.20		
		256-QAM	-31.15	5.54	10.65	2.72	H		0.022	13.47		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured	Substitute	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
			Level (dBm)	Level (dBm)				W	W	dBm	Size	Offset
2505.0		QPSK	-26.14	10.72	10.55	2.57	H	< 2.00	0.074	18.70	1	0
		16-QAM	-26.97	9.89	10.55	2.57	H		0.061	17.87		
		64-QAM	-27.97	8.89	10.55	2.57	H		0.049	16.87		
		256-QAM	-31.11	5.75	10.55	2.57	H		0.024	13.73		
2535.0	LTE B7/ 10 MHz	QPSK	-25.95	10.99	10.67	2.63	H		0.080	19.03	1	0
		16-QAM	-26.85	10.09	10.67	2.63	H		0.065	18.13		
		64-QAM	-27.81	9.13	10.67	2.63	H		0.052	17.17		
		256-QAM	-30.97	5.97	10.67	2.63	H		0.025	14.01		
2565.0		QPSK	-26.26	10.67	10.66	2.70	H	< 2.00	0.073	18.62	1	0
		16-QAM	-26.97	9.96	10.66	2.70	H		0.062	17.91		
		64-QAM	-27.96	8.97	10.66	2.70	H		0.049	16.92		
		256-QAM	-31.08	5.85	10.66	2.70	H		0.024	13.80		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured	Substitute	Ant. Gain (dBi)	C.L.	Pol	Limit	EIRP		RB	
			Level (dBm)	Level (dBm)				W	W	dBm	Size	Offset
2507.5		QPSK	-26.06	10.83	10.59	2.57	H	< 2.00	0.077	18.85	1	0
		16-QAM	-26.95	9.94	10.59	2.57	H		0.063	17.96		
		64-QAM	-27.93	8.96	10.59	2.57	H		0.050	16.98		
		256-QAM	-31.17	5.72	10.59	2.57	H		0.024	13.74		
2535.0	LTE B7/ 15 MHz	QPSK	-25.88	11.06	10.67	2.63	H	< 2.00	0.081	19.10	1	0
		16-QAM	-26.63	10.31	10.67	2.63	H		0.068	18.35		
		64-QAM	-27.67	9.27	10.67	2.63	H		0.054	17.31		
		256-QAM	-30.85	6.09	10.67	2.63	H		0.026	14.13		
2562.5		QPSK	-26.23	10.94	10.66	2.68	H	< 2.00	0.078	18.92	1	0
		16-QAM	-27.03	10.14	10.66	2.68	H		0.065	18.12		
		64-QAM	-28.02	9.15	10.66	2.68	H		0.052	17.13		
		256-QAM	-31.26	5.91	10.66	2.68	H		0.024	13.89		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured	Substitute	Ant. Gain (dBi)	C.L.	Pol	Limit	EIRP		RB	
			Level (dBm)	Level (dBm)				W	W	dBm	Size	Offset
2510.0		QPSK	-26.06	10.83	10.59	2.57	H	< 2.00	0.077	18.85	1	0
		16-QAM	-26.87	10.02	10.59	2.57	H		0.064	18.04		
		64-QAM	-27.89	9.00	10.59	2.57	H		0.050	17.02		
		256-QAM	-31.09	5.80	10.59	2.57	H		0.024	13.82		
2535.0	LTE B7/ 20 MHz	QPSK	-25.94	11.00	10.67	2.63	H	< 2.00	0.080	19.04	1	0
		16-QAM	-26.79	10.15	10.67	2.63	H		0.066	18.19		
		64-QAM	-27.80	9.14	10.67	2.63	H		0.052	17.18		
		256-QAM	-30.96	5.98	10.67	2.63	H		0.025	14.02		
2560.0		QPSK	-26.00	11.17	10.66	2.68	H	< 2.00	0.082	19.15	1	0
		16-QAM	-26.84	10.33	10.66	2.68	H		0.068	18.31		
		64-QAM	-27.84	9.33	10.66	2.68	H		0.054	17.31		
		256-QAM	-31.04	6.13	10.66	2.68	H		0.026	14.11		

9.2 RADIATED SPURIOUS EMISSIONS

- OPERATING FREQUENCY: 2535.0 MHz
- MEASURED OUTPUT POWER: 18.76 dBm = 0.075 W
- MODE: LTE B7
- MODULATION SIGNAL: 5 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10} (W) =$ 43.76 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitut e Level (dBm)	C.L	Pol	Result (dBm)	dBc	RB	
									Size	Offset
20775 (2502.5)	5 005.00	-48.62	12.56	-58.54	3.85	V	-49.83	68.59	1	0
	7 507.50	-49.01	10.78	-49.42	4.71	V	-43.35	62.12		
	10 010.00	-59.44	11.23	-55.26	5.52	V	-49.55	68.32		
21100 (2535.0)	5 070.00	-47.68	12.31	-55.30	3.73	H	-46.72	65.48	1	0
	7 605.00	-44.22	11.10	-45.07	4.78	V	-38.75	57.51		
	10 140.00	-58.47	11.59	-54.68	5.55	H	-48.64	67.40		
21425 (2567.5)	5 135.00	-52.96	12.33	-60.83	3.94	H	-52.44	71.20	1	0
	7 702.50	-49.72	11.35	-50.82	4.77	V	-44.24	63.00		
	10 270.00	-60.40	11.57	-54.87	5.55	V	-48.85	67.61		

OPERATING FREQUENCY: 2535.0 MHz
 MEASURED OUTPUT POWER: 19.03 dBm = 0.080 W
 MODE: LTE B7
 MODULATION SIGNAL: 10 MHz QPSK
 DISTANCE: 1 meters
 LIMIT: $55 + 10 \log_{10} (W) =$ 44.03 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitut e Level (dBm)	C.L	Pol	Result (dBm)	dBc	RB	
									Size	Offset
20800 (2505.0)	5 010.00	-46.41	12.55	-56.43	3.88	H	-47.76	66.79	1	0
	7 515.00	-46.85	10.80	-47.41	4.71	H	-41.32	60.35		
	10 020.00	-56.45	11.27	-52.16	5.54	H	-46.43	65.46		
21100 (2535.0)	5 070.00	-47.71	12.31	-55.33	3.73	H	-46.75	65.78	1	0
	7 605.00	-42.62	11.10	-43.47	4.78	H	-37.15	56.18		
	10 140.00	-60.04	11.59	-56.25	5.55	H	-50.21	69.24		
21400 (2565.0)	5 130.00	-51.17	12.31	-58.99	3.96	H	-50.64	69.67	1	0
	7 695.00	-40.16	11.35	-41.20	4.76	H	-34.62	53.65		
	10 260.00	-60.46	11.58	-54.85	5.54	V	-48.81	67.85		

OPERATING FREQUENCY: 2535.0 MHz
 MEASURED OUTPUT POWER: 19.10 dBm = 0.081 W
 MODE: LTE B7
 MODULATION SIGNAL: 15 MHz QPSK
 DISTANCE: 1 meters
 LIMIT: $55 + 10 \log_{10} (W) =$ 44.10 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitut e Level (dBm)	C.L	Pol	Result (dBm)	dBc	RB	
									Size	Offset
20825 (2507.5)	5 015.00	-49.53	12.54	-59.66	3.90	H	-51.02	70.12	1	0
	7 522.50	-48.09	10.82	-48.79	4.71	H	-42.68	61.79		
	10 030.00	-57.32	11.31	-53.17	5.53	V	-47.39	66.49		
21100 (2535.0)	5 070.00	-46.81	12.31	-54.43	3.73	H	-45.85	64.95	1	0
	7 605.00	-44.26	11.10	-45.11	4.78	V	-38.79	57.89		
	10 140.00	-58.82	11.59	-55.03	5.55	H	-48.99	68.09		
21375 (2562.5)	5 125.00	-51.24	12.29	-59.19	3.97	H	-50.87	69.97	1	0
	7 687.50	-41.93	11.34	-42.91	4.75	V	-36.32	55.43		
	10 250.00	-59.86	11.59	-54.43	5.54	H	-48.38	67.48		

OPERATING FREQUENCY: 2560.0 MHz
 MEASURED OUTPUT POWER: 19.15 dBm = 0.082 W
 MODE: LTE B7
 MODULATION SIGNAL: 20 MHz QPSK
 DISTANCE: 1 meters
 LIMIT: $55 + 10 \log_{10} (W) =$ 44.15 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitut e Level (dBm)	C.L	Pol	Result (dBm)	dBc	RB	
									Size	Offset
20850 (2510.0)	5 020.00	-48.72	12.52	-58.95	3.91	H	-50.34	69.49	1	0
	7 530.00	-48.86	10.85	-49.44	4.72	V	-43.31	62.46		
	10 040.00	-58.08	11.34	-54.42	5.51	V	-48.59	67.74		
21100 (2535.0)	5 070.00	-46.73	12.31	-54.35	3.73	V	-45.77	64.91	1	0
	7 605.00	-46.32	11.10	-47.17	4.78	H	-40.85	60.00		
	10 140.00	-60.24	11.59	-56.45	5.55	V	-50.41	69.56		
21350 (2560.0)	5 120.00	-48.90	12.26	-56.98	3.97	V	-48.69	67.84	1	0
	7 680.00	-43.49	11.33	-44.08	4.75	V	-37.50	56.65		
	10 240.00	-58.98	11.59	-54.07	5.53	V	-48.01	67.16		

9.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)		
7	5 MHz	2535.0	QPSK	25	0	5.85		
			16-QAM			6.46		
			64-QAM			6.49		
			256-QAM			6.11		
	10 MHz		QPSK	50		5.91		
			16-QAM			6.41		
			64-QAM			6.48		
			256-QAM			6.14		
	15 MHz		QPSK	75		5.69		
			16-QAM			6.34		
			64-QAM			6.44		
			256-QAM			6.11		
	20 MHz		QPSK	100		5.64		
			16-QAM			6.33		
			64-QAM			6.42		
			256-QAM			6.09		

Note:

- Plots of the EUT's Peak- to- Average Ratio are shown Page 151 ~ 166.

9.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)		
7	5 MHz	2535.0	QPSK	25	0	4.5384		
			16-QAM			4.5198		
			64-QAM			4.5341		
			256-QAM			4.5297		
	10 MHz		QPSK	50		9.0403		
			16-QAM			9.0137		
			64-QAM			9.0193		
			256-QAM			9.0142		
	15 MHz		QPSK	75		13.489		
			16-QAM			13.501		
			64-QAM			13.458		
			256-QAM			13.445		
	20 MHz		QPSK	100		17.924		
			16-QAM			17.925		
			64-QAM			17.875		
			256-QAM			17.949		

Note:

- Plots of the EUT's Occupied Bandwidth are shown Page 167 ~ 182.

9.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
7	5	2502.5	26.1772	30.131	-76.758	-46.627	-25.00
		2535.0	26.1309	30.131	-76.895	-46.764	
		2567.5	26.1377	30.131	-76.772	-46.641	
	10	2505.0	26.1275	30.131	-76.769	-46.638	
		2535.0	3.7059	27.976	-76.889	-48.913	
		2565.0	26.1547	30.131	-76.682	-46.551	
	15	2507.5	26.1262	30.131	-76.898	-46.767	
		2535.0	26.1066	30.131	-76.850	-46.719	
		2562.5	26.0726	30.131	-76.938	-46.807	
	20	2510.0	26.1462	30.131	-76.945	-46.814	
		2535.0	26.1185	30.131	-76.731	-46.600	
		2560.0	26.1326	30.131	-76.648	-46.517	

Note:

- Plots of the EUT's Conducted Spurious Emissions are shown Page 183 ~ 206.
- Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
- Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
- Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131

9.6 CHANNEL EDGE

Band Width (Modulation)	Frequency (MHz)	RB Size / Offset	C.E ~ (C.E ± 1 MHz)		2 496 MHz ~ 2 499 MHz	(C.E + 1 MHz) ~ (C.E + 5 MHz)	2 490.5 MHz ~ 2 496 MHz	(C.E + 5 MHz) ~ (C.E + X MHz)	Below 2 490.5 MHz	Above (C.E + X MHz)
			Lower	Upper	Lower	Upper	Lower	Upper	Lower	Upper
5 MHz (QPSK)	2502.5	25 / 0	-22.39	-21.99	-24.14	-22.97	-30.48	-35.69	-44.43	-36.31
10 MHz (QPSK)	2505.0	50 / 0	-26.68	-25.54	-27.53	-24.36	-30.98	-27.62	-40.16	-37.61
15 MHz (QPSK)	2507.5	75 / 0	-28.81	-26.93	-30.06	-25.33	-32.24	-27.04	-35.26	-37.11
20 MHz (QPSK)	2510.0	100 / 0	-31.92	-28.94	-33.14	-26.77	-34.31	-28.00	-36.71	-38.78
Limit(dBm)			-10.0		-10.0		-13.0		-25.0	

Band Width (Modulation)	Frequency (MHz)	RB Size / Offset	C.E ~ (C.E ± 1 MHz)		(C.E ± 1 MHz) ~ (C.E ± 5 MHz)	
			Lower	Upper	Lower	Upper
5 MHz (QPSK)	2535.0	25 / 0	-23.21	-22.90	-27.98	-25.68
	2567.5	25 / 0	-23.17	-22.77	-24.51	-23.56
10 MHz (QPSK)	2535.0	50 / 0	-27.05	-25.54	-29.56	-26.12
	2565.0	50 / 0	-26.21	-25.01	-26.40	-23.23
15 MHz (QPSK)	2535.0	75 / 0	-29.52	-27.60	-30.61	-26.63
	2562.5	75 / 0	-28.08	-26.45	-28.39	-23.71
20 MHz (QPSK)	2535.0	100 / 0	-31.45	-29.43	-31.60	-28.08
	2560.0	100 / 0	-29.60	-26.84	-28.34	-24.74
Limit(dBm)			-10.0		-10.0	

Band Width (Modulation)	Frequency (MHz)	Resource Block Size	(C.E ± 5 MHz) ~ (C.E ± X MHz)		Above (C.E ± X MHz)	
			Lower	Upper	Lower	Upper
5 MHz (QPSK)	2535.0	25 / 0	-34.59	-37.30	-35.69	-38.15
	2567.5	25 / 0	-29.95	-31.08	-31.31	-32.60
10 MHz (QPSK)	2535.0	50 / 0	-30.35	-28.93	-38.48	-41.54
	2565.0	50 / 0	-27.26	-26.64	-32.19	-34.60
15 MHz (QPSK)	2535.0	75 / 0	-32.93	-28.45	-41.47	-42.79
	2562.5	75 / 0	-28.22	-25.71	-34.42	-37.14
20 MHz (QPSK)	2535.0	100 / 0	-33.32	-29.43	-43.11	-43.48
	2560.0	100 / 0	-28.07	-25.95	-37.61	-40.66
Limit(dBm)			-13.0		-25.0	


Note:

1. C.E = Channel Edge
2. X = X is the greater of 6 MHz or the actual emission bandwidth.
3. X = 6 MHz(5 MHz Bandwidth), 10 MHz(10 MHz Bandwidth), 15 MHz(15 MHz Bandwidth), 20 MHz(20 MHz Bandwidth)
4. Plots of the EUT's Channel Edge are shown Page 207 ~ 230.

9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


- MODE: LTE 7
 OPERATING FREQUENCY: 2,502,500,000 Hz
 CHANNEL: 20775 (5 MHz)
 REFERENCE VOLTAGE: 3.880 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	2502 499 992	0.0	0.000 000	0.000
100 %		-30	2502 500 002	9.4	0.000 000	0.004
100 %		-20	2502 499 985	-7.7	0.000 000	-0.003
100 %		-10	2502 499 987	-4.9	0.000 000	-0.002
100 %		0	2502 499 996	4.1	0.000 000	0.002
100 %		+10	2502 499 997	5.1	0.000 000	0.002
100 %		+30	2502 499 997	4.8	0.000 000	0.002
100 %		+40	2502 499 985	-7.5	0.000 000	-0.003
100 %		+50	2502 499 997	4.3	0.000 000	0.002
Batt. Endpoint	3.300	+20	2502 499 986	-6.2	0.000 000	-0.002




MODE: LTE 7
 OPERATING FREQUENCY: 2,505,000,000 Hz
 CHANNEL: 20800 (10 MHz)
 REFERENCE VOLTAGE: 3.880 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2504 999 993	0.0	0.000 000	0.000
100 %		-30	2505 000 002	8.5	0.000 000	0.003
100 %		-20	2504 999 999	5.7	0.000 000	0.002
100 %		-10	2504 999 984	-8.7	0.000 000	-0.003
100 %		0	2504 999 984	-9.3	0.000 000	-0.004
100 %		+10	2504 999 985	-8.4	0.000 000	-0.003
100 %		+30	2504 999 985	-7.7	0.000 000	-0.003
100 %		+40	2505 000 000	7.4	0.000 000	0.003
100 %		+50	2504 999 998	4.7	0.000 000	0.002
Batt. Endpoint	3.300	+20	2505 000 001	7.5	0.000 000	0.003




- MODE: LTE 7
- OPERATING FREQUENCY: 2,507,500,000 Hz
- CHANNEL: 20825 (15 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2507 500 007	0.0	0.000 000	0.000
100 %		-30	2507 500 015	7.4	0.000 000	0.003
100 %		-20	2507 499 999	-8.3	0.000 000	-0.003
100 %		-10	2507 499 999	-8.2	0.000 000	-0.003
100 %		0	2507 500 013	5.8	0.000 000	0.002
100 %		+10	2507 499 998	-9.0	0.000 000	-0.004
100 %		+30	2507 500 015	7.9	0.000 000	0.003
100 %		+40	2507 500 015	7.9	0.000 000	0.003
100 %		+50	2507 500 012	4.8	0.000 000	0.002
Batt. Endpoint	3.300	+20	2507 499 999	-8.2	0.000 000	-0.003




- MODE: LTE 7
- OPERATING FREQUENCY: 2,510,000,000 Hz
- CHANNEL: 20850 (20 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2510 000 007	0.0	0.000 000	0.000
100 %		-30	2509 999 999	-8.6	0.000 000	-0.003
100 %		-20	2510 000 016	8.5	0.000 000	0.003
100 %		-10	2510 000 015	7.3	0.000 000	0.003
100 %		0	2510 000 015	7.3	0.000 000	0.003
100 %		+10	2510 000 012	5.0	0.000 000	0.002
100 %		+30	2510 000 018	11.0	0.000 000	0.004
100 %		+40	2510 000 015	7.8	0.000 000	0.003
100 %		+50	2509 999 991	-16.1	-0.000 001	-0.006
Batt. Endpoint	3.300	+20	2510 000 013	5.7	0.000 000	0.002




- MODE: LTE 7
- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (5 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2535 000 007	0.0	0.000 000	0.000
100 %		-30	2535 000 002	-5.2	0.000 000	-0.002
100 %		-20	2535 000 014	6.9	0.000 000	0.003
100 %		-10	2535 000 013	5.8	0.000 000	0.002
100 %		0	2535 000 014	6.1	0.000 000	0.002
100 %		+10	2535 000 014	6.6	0.000 000	0.003
100 %		+30	2535 000 001	-6.6	0.000 000	-0.003
100 %		+40	2535 000 012	4.6	0.000 000	0.002
100 %		+50	2535 000 015	7.9	0.000 000	0.003
Batt. Endpoint	3.300	+20	2535 000 014	6.8	0.000 000	0.003




- MODE: LTE 7
- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (10 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2534 999 996	0.0	0.000 000	0.000
100 %		-30	2534 999 999	3.7	0.000 000	0.001
100 %		-20	2535 000 001	5.4	0.000 000	0.002
100 %		-10	2534 999 990	-5.5	0.000 000	-0.002
100 %		0	2534 999 992	-3.8	0.000 000	-0.001
100 %		+10	2534 999 992	-3.6	0.000 000	-0.001
100 %		+30	2534 999 998	2.6	0.000 000	0.001
100 %		+40	2534 999 985	-11.0	0.000 000	-0.004
100 %		+50	2535 000 000	3.9	0.000 000	0.002
Batt. Endpoint	3.300	+20	2535 000 002	6.4	0.000 000	0.003




- MODE: LTE 7
- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (15 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2534 999 987	0.0	0.000 000	0.000
100 %		-30	2534 999 990	2.9	0.000 000	0.001
100 %		-20	2534 999 991	3.6	0.000 000	0.001
100 %		-10	2534 999 982	-4.7	0.000 000	-0.002
100 %		0	2534 999 983	-3.8	0.000 000	-0.001
100 %		+10	2534 999 993	6.5	0.000 000	0.003
100 %		+30	2534 999 994	6.8	0.000 000	0.003
100 %		+40	2534 999 995	8.0	0.000 000	0.003
100 %		+50	2534 999 994	7.0	0.000 000	0.003
Batt. Endpoint	3.300	+20	2534 999 994	6.6	0.000 000	0.003




- MODE: LTE 7
- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (20 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2535 000 006	0.0	0.000 000	0.000
100 %		-30	2535 000 013	6.8	0.000 000	0.003
100 %		-20	2535 000 001	-4.5	0.000 000	-0.002
100 %		-10	2535 000 011	4.7	0.000 000	0.002
100 %		0	2535 000 009	3.0	0.000 000	0.001
100 %		+10	2535 000 012	6.0	0.000 000	0.002
100 %		+30	2535 000 002	-3.9	0.000 000	-0.002
100 %		+40	2535 000 001	-4.4	0.000 000	-0.002
100 %		+50	2535 000 010	4.2	0.000 000	0.002
Batt. Endpoint	3.300	+20	2535 000 013	7.5	0.000 000	0.003




- MODE: LTE 7
- OPERATING FREQUENCY: 2,567,500,000 Hz
- CHANNEL: 21425 (5 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2567 499 995	0.0	0.000 000	0.000
100 %		-30	2567 499 997	2.5	0.000 000	0.001
100 %		-20	2567 500 003	7.8	0.000 000	0.003
100 %		-10	2567 499 999	4.4	0.000 000	0.002
100 %		0	2567 500 002	7.4	0.000 000	0.003
100 %		+10	2567 499 991	-4.2	0.000 000	-0.002
100 %		+30	2567 500 003	8.2	0.000 000	0.003
100 %		+40	2567 499 999	4.0	0.000 000	0.002
100 %		+50	2567 500 002	7.2	0.000 000	0.003
Batt. Endpoint	3.300	+20	2567 500 002	6.7	0.000 000	0.003




MODE: LTE 7
 OPERATING FREQUENCY: 2,565,000,000 Hz
 CHANNEL: 21400 (10 MHz)
 REFERENCE VOLTAGE: 3.880 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2565 000 006	0.0	0.000 000	0.000
100 %		-30	2565 000 001	-5.2	0.000 000	-0.002
100 %		-20	2565 000 011	4.3	0.000 000	0.002
100 %		-10	2565 000 011	4.6	0.000 000	0.002
100 %		0	2565 000 009	2.5	0.000 000	0.001
100 %		+10	2565 000 012	5.8	0.000 000	0.002
100 %		+30	2565 000 012	5.5	0.000 000	0.002
100 %		+40	2565 000 011	4.3	0.000 000	0.002
100 %		+50	2565 000 013	6.3	0.000 000	0.002
Batt. Endpoint	3.300	+20	2565 000 011	4.5	0.000 000	0.002




- MODE: LTE 7
- OPERATING FREQUENCY: 2,562,500,000 Hz
- CHANNEL: 21375 (15 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2562 500 004	0.0	0.000 000	0.000
100 %		-30	2562 500 009	4.5	0.000 000	0.002
100 %		-20	2562 500 009	4.4	0.000 000	0.002
100 %		-10	2562 500 008	3.4	0.000 000	0.001
100 %		0	2562 500 009	5.0	0.000 000	0.002
100 %		+10	2562 500 011	7.0	0.000 000	0.003
100 %		+30	2562 500 011	6.5	0.000 000	0.003
100 %		+40	2562 500 010	5.2	0.000 000	0.002
100 %		+50	2562 500 010	5.3	0.000 000	0.002
Batt. Endpoint	3.300	+20	2562 500 009	4.5	0.000 000	0.002



- MODE: LTE 7
- OPERATING FREQUENCY: 2,560,000,000 Hz
- CHANNEL: 21350 (20 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	2560 000 007	0.0	0.000 000	0.000
100 %		-30	2560 000 010	3.3	0.000 000	0.001
100 %		-20	2560 000 012	4.9	0.000 000	0.002
100 %		-10	2560 000 014	7.1	0.000 000	0.003
100 %		0	2560 000 012	4.5	0.000 000	0.002
100 %		+10	2560 000 013	5.8	0.000 000	0.002
100 %		+30	2560 000 010	3.3	0.000 000	0.001
100 %		+40	2560 000 012	5.2	0.000 000	0.002
100 %		+50	2560 000 014	6.5	0.000 000	0.003
Batt. Endpoint	3.300	+20	2560 000 016	8.5	0.000 000	0.003




10. TEST PLOTS(Main 2 Ant)





LTE B7_5 M_PAR_Mid_16QAM_FullRB












































LTE B7_5 M_OBW_Mid_QPSK_FullRB




LTE B7_5 M_OBW_Mid_16QAM_FullRB




LTE B7_5 M_OBW_Mid_64QAM_FullRB




LTE B7_5 M_OBW_Mid_256QAM_FullRB




LTE B7_10 M_OBW_Mid_QPSK_FullRB




LTE B7_10 M_OBW_Mid_16QAM_FullRB




LTE B7_10 M_OBW_Mid_64QAM_FullRB




LTE B7_10 M_OBW_Mid_256QAM_FullRB




LTE B7_15 M_OBW_Mid_QPSK_FullRB




LTE B7_15 M_OBW_Mid_16QAM_FullRB




LTE B7_15 M_OBW_Mid_64QAM_FullRB




LTE B7_15 M_OBW_Mid_256QAM_FullRB




LTE B7_20 M_OBW_Mid_QPSK_FullRB




LTE B7_20 M_OBW_Mid_16QAM_FullRB




LTE B7_20 M_OBW_Mid_64QAM_FullRB




LTE B7_20 M_OBW_Mid_256QAM_FullRB




LTE B7_5 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB




LTE B7_5 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB





LTE B7_5 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB







LTE B7_10 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB










LTE B7_15 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB








LTE B7_20 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB







LTE B7_5 M_Conducted Spurious(10 G-26.5 G)_Mid_QPSK_1RB



LTE B7_5 M_Conducted Spurious(10 G-26.5 G)_High_QPSK_1RB





LTE B7_10 M_Conducted Spurious(10 G-26.5 G)_Mid_QPSK_1RB





LTE B7_15 M_Conducted Spurious(10 G-26.5 G)_Low_QPSK_1RB

