



**PART 22 & 90 MEASUREMENT REPORT**

**Applicant Name:**

Samsung Electronics Co., Ltd.  
129, Samsung-ro,  
Yeongtong-gu, Suwon-si  
Gyeonggi-do, 16677, Korea

**Date of Testing:**

10/14/2021 - 11/10/2021

**Test Report Issue Date:**

12/17/2021

**Test Site/Location:**

PCTEST Lab. Yongin-Si, Gyeonggi-do, South Korea

**Test Report Serial No.:**

1M2109290114-06.A3L

**FCC ID:**

**A3LSMS901E**

**APPLICANT:**

**Samsung Electronics Co., Ltd.**

**Application Type:**

Certification

**Model:**

SM-S901E/DS

**Additional Model(s):**

SM-S901E

**EUT Type:**

Portable Handset

**FCC Classification:**

PCS Licensed Transmitter Held to Ear (PCE)

**FCC Rule Part:**

§2.1049, §22(H), §90(S), §90(R)

**Test Procedure(s):**

ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168  
D01 v03r01, KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.



I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Prepared by






Reviewed by

FCC ID: A3LSMS901E	 <b>PART 22 &amp; 90 MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 1 of 34

## TABLE OF CONTENTS


1.0	INTRODUCTION .....	4
1.1	Scope .....	4
1.2	PCTEST Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description .....	5
2.2	Device Capabilities.....	5
2.3	Test Configuration .....	5
2.4	EMI Suppression Device(s)/Modifications .....	5
3.0	DESCRIPTION OF TESTS .....	6
3.1	Evaluation Procedure .....	6
3.2	Radiated Power and Radiated Spurious Emissions .....	6
4.0	MEASUREMENT UNCERTAINTY .....	7
5.0	TEST EQUIPMENT CALIBRATION DATA .....	8
6.0	SAMPLE CALCULATIONS .....	9
7.0	TEST RESULTS .....	10
7.1	Summary .....	10
7.2	Occupied Bandwidth .....	11
7.3	Spurious and Harmonic Emissions at Antenna Terminal .....	17
7.4	Band Edge Emissions at Antenna Terminal .....	20
7.5	Conducted Power Output Data .....	25
7.6	Radiated Power (ERP).....	26
7.7	Radiated Spurious Emissions Measurements.....	29
7.8	Frequency Stability / Temperature Variation .....	32
8.0	CONCLUSION.....	34

<b>FCC ID:</b> A3LSMS901E		<b>PART 22 &amp; 90 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2109290114-06.A3L	<b>Test Dates:</b> 10/14/2021 - 11/10/2021	<b>EUT Type:</b> Portable Handset		Page 2 of 34





# MEASUREMENT REPORT

## FCC Part 22 & 90



Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	Measurement	Max. Power [W]	Max. Power [dBm]	Emission Designator
LTE Band 26	15 MHz	QPSK	821.5	ERP	0.072	18.57	13M6G7D
		16QAM	821.5	ERP	0.059	17.70	13M5W7D
	15 MHz	QPSK	821.5	Conducted	0.230	23.62	13M6G7D
		16QAM	821.5	Conducted	0.194	22.88	13M5W7D
	10 MHz	QPSK	819.0	Conducted	0.232	23.65	9M04G7D
		16QAM	819.0	Conducted	0.202	23.05	9M03W7D
	5 MHz	QPSK	816.5 - 821.5	Conducted	0.231	23.64	4M54G7D
		16QAM	816.5 - 821.5	Conducted	0.206	23.14	4M57W7D
	3 MHz	QPSK	815.5 - 822.5	Conducted	0.236	23.73	2M73G7D
		16QAM	815.5 - 822.5	Conducted	0.205	23.12	2M73W7D
	1.4 MHz	QPSK	814.7 - 823.3	Conducted	0.246	23.91	1M11G7D
		16QAM	814.7 - 823.3	Conducted	0.205	23.13	1M12W7D

### EUT Overview

FCC ID: A3LSMS901E	 PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 3 of 34

# 1.0 INTRODUCTION

## 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.



## 1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, 16954, South Korea. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

## 1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Yongin-si, Gyeonggi-do, 16954, South Korea.

- PCTEST is an ISO 17025-2017 accredited test facility under the National Voluntary Laboratory Accreditation Program (NVLAP) with Certificate number 600143-0 for Specific Absorption Rate (SAR), where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (26168) test laboratory with the site description on file with ISED.

FCC ID: A3LSMS901E	 PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 4 of 34

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMS901E**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part.

**Test Device Serial No.: 0403M, 0419M, 0842M**

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 5G NR (FR1), 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII (5GHz), Bluetooth (1x, EDR, LE), NFC, Wireless Power Transfer

This device uses a tuner circuit that dynamically updates the antenna impedance parameters to optimize antenna performance for certain bands and modes of operation. The tuner for this device was set to simulate a "free space" condition where the transmit antenna is matched to the medium into which it is transmitting and, thus, the power is at its maximum level.



### 2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad\_WCP Model: EP-N5100 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMS901E		PART 22 & 90 MEASUREMENT REPORT	 <b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2109290114-06.A3L	<b>Test Dates:</b> 10/14/2021 - 11/10/2021	<b>EUT Type:</b> Portable Handset	Page 5 of 34

## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

### 3.2 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer “Channel Power” function with the integration band set to the emissions’ occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03r01.



Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where,  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g \text{ [dBm]} - \text{cable loss [dB]}$ .

For fundamental radiated power measurements, the guidance of KDB 971168 D01 v03r01 is used to record the EUT power level that is subsequently matched via the aforementioned substitution method given in ANSI/TIA-603-E-2016.



All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01.

FCC ID: A3LSMS901E		PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 6 of 34	

## 4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.20
Radiated Disturbance (<1GHz)	3.01
Radiated Disturbance (>1GHz)	5.56
Radiated Disturbance (>18GHz)	3.16

FCC ID: A3LSMS901E	 PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 7 of 34

## 5.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E5515C	WIRELESS COMMUNICATION TEST SET	2/19/2021	Annual	2/18/2022	MY50262130
Agilent	N9030A	PXA Signal Analyzer	7/6/2021	Annual	7/5/2022	MY49432391
Anritsu	S820E	Cable and Antenna Analyzer	7/7/2021	Annual	7/6/2022	6201300731
Anritsu	MA24106A	USB Power Sensor	7/7/2021	Annual	7/6/2022	1244512
Espec	SH-242	Environmental Chamber	9/15/2021	Annual	9/14/2022	93011064
ETS Lindgren	3110C	Biconical Antenna	7/9/2020	Biennial	7/8/2022	00211248
ETS Lindgren	3110C	Biconical Antenna	7/9/2020	Biennial	7/8/2022	00211250
Fairview Microwave	FM2CP1122-10	Coupler	7/7/2021	Annual	7/6/2022	1946
Keysight Technologies	N9030B	MXA Signal Analyzer	5/11/2021	Annual	5/10/2022	MY57142018
Mini Circuits	ZUDC10-83-S+	Coupler	9/15/2021	Annual	9/14/2022	2111
Mini-Circuits	BW-N10W5+	Attenuator	7/6/2021	Annual	7/5/2022	1607
Mini-Circuits	BW-N10W5+	Attenuator	7/6/2021	Annual	7/5/2022	1607
Rohde & Schwarz	TS-PR18	Preamplifier	7/8/2021	Annual	7/7/2022	102141
Rohde & Schwarz	SMBV100B	Signal Generator	11/4/2021	Annual	11/3/2022	101568
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	7/6/2021	Annual	7/5/2022	116851
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	2/19/2021	Annual	2/18/2022	131453
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	2/19/2021	Annual	2/18/2022	131454
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	2/19/2021	Annual	2/18/2022	150117
Rohde & Schwarz	ESW	EMI Test Receiver	7/6/2021	Annual	7/5/2022	101761
Rohde & Schwarz	FSW43	Signal & Spectrum Analyzer	9/15/2021	Annual	9/14/2022	101250
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	2/19/2021	Annual	2/18/2022	102131
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	3/29/2021	Annual	3/28/2022	102151
Schwarzbeck	UHA9105	Dipole Antenna	7/9/2020	Biennial	7/8/2022	91052522
Sunol	DRH-118	Horn Antenna	7/14/2021	Biennial	7/13/2023	A102416-1
Sunol	DRH-118	Horn Antenna	1/12/2021	Biennial	1/11/2023	A060215

**Table 5-1. Test Equipment**

**Notes:**

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMS901E	 PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 8 of 34



## 6.0 SAMPLE CALCULATIONS

### Emission Designator

#### QPSK Modulation

**Emission Designator = 8M62G7D**

- LTE BW = 8.62 MHz
- G = Phase Modulation
- 7 = Quantized/Digital Info
- D = Data transmission, telemetry, telecommand

#### QAM Modulation



**Emission Designator = 8M45W7D**

- LTE BW = 8.45 MHz
- W = Amplitude/Angle Modulated
- 7 = Quantized/Digital Info
- D = Data transmission, telemetry, telecommand

### Spurious Radiated Emission – LTE Band

#### **Example: Middle Channel LTE Mode 2<sup>nd</sup> Harmonic (1564 MHz)**

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80).

FCC ID: A3LSMS901E		PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset		Page 9 of 34

## 7.0 TEST RESULTS

### 7.1 Summary



Company Name: Samsung Electronics Co., Ltd.  
 FCC ID: A3LSMS901E  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): LTE

Test Condition	Test Description	FCC Part Section(s)	Test Limit	Test Result	Reference
<b>CONDUCTED</b>	Occupied Bandwidth	2.1049	N/A	<b>PASS</b>	Section 7.2
	Conducted Band Edge / Spurious Emissions (LTE Band 26)	2.1051, 90.691(a)	> 43 + 10 log <sub>10</sub> (P[Watts]) for all out-of-band emissions except emissions beyond 37.5kHz from the block edge > 50 + 10 log <sub>10</sub> (P[Watts]) at Band Edge and for all out-	<b>PASS</b>	Sections 7.3, 7.4
	Frequency Stability	2.1055, 90.213	< 2.5 ppm	<b>PASS</b>	Section 7.8
	Conducted Power	2.1046, 90.635	< 100 Watts	<b>PASS</b>	Section 7.5
<b>RADIATED</b>	Effective Radiated Power (LTE Band 26)	22.913(a)(2)	< 7 Watts max. ERP	<b>PASS</b>	Section 7.6
	Radiated Spurious Emissions (LTE Band 26)	2.1053, 90.691(a)	> 43 + 10 log <sub>10</sub> (P[Watts]) for all out-of-band emissions except emissions beyond 37.5kHz from the block edge > 50 + 10 log <sub>10</sub> (P[Watts]) at Band Edge and for all out-of-band emissions within 37.5kHz of Block Edge	<b>PASS</b>	Section 7.7

**Table 7-1. Summary of Test Results**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST EMC Software Tool v1.0.

FCC ID: A3LSMS901E		PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset		Page 10 of 34

## 7.2 Occupied Bandwidth

### Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

### Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

### Test Settings

1. The signal analyzer’s automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### Test Setup



The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-1. Test Instrument & Measurement Setup**

### Test Notes

None.

FCC ID: A3LSMS901E	 PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 11 of 34

# LTE Band 26



Plot 7-1. Occupied Bandwidth Plot (LTE Band 26 - 15MHz QPSK - Full RB)



Plot 7-2. Occupied Bandwidth Plot (LTE Band 26 - 15MHz 16-QAM - Full RB)

FCC ID: A3LSMS901E	PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 12 of 34




Plot 7-3. Occupied Bandwidth Plot (LTE Band 26 - 10MHz QPSK - Full RB)



Plot 7-4. Occupied Bandwidth Plot (LTE Band 26 - 10MHz 16-QAM - Full RB)

FCC ID: A3LSMS901E	<b>PCTEST</b> Proud to be part of	<b>PART 22 &amp; 90 MEASUREMENT REPORT</b>	<b>Approved by:</b> Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 13 of 34




Plot 7-5. Occupied Bandwidth Plot (LTE Band 26 - 5MHz QPSK - Full RB)



Plot 7-6. Occupied Bandwidth Plot (LTE Band 26 - 5MHz 16-QAM - Full RB)

FCC ID: A3LSMS901E	<b>PCTEST</b> Proud to be part of	<b>PART 22 &amp; 90 MEASUREMENT REPORT</b>	<b>Approved by:</b> Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 14 of 34



Plot 7-7. Occupied Bandwidth Plot (LTE Band 26 - 3MHz QPSK - Full RB)



Plot 7-8. Occupied Bandwidth Plot (LTE Band 26 - 3MHz 16-QAM - Full RB)

FCC ID: A3LSMS901E	<b>PCTEST</b> Proud to be part of	<b>PART 22 &amp; 90 MEASUREMENT REPORT</b>	<b>Approved by:</b> Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 15 of 34



Plot 7-9. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz QPSK - Full RB)



Plot 7-10. Occupied Bandwidth Plot (LTE Band 26 - 1.4MHz 16-QAM - Full RB)

FCC ID: A3LSMS901E	<b>PCTEST</b> Proud to be part of	<b>PART 22 &amp; 90 MEASUREMENT REPORT</b>	<b>Approved by:</b> Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 16 of 34



### 7.3 Spurious and Harmonic Emissions at Antenna Terminal

#### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

**The minimum permissible attenuation level of any spurious emission is  $43 + 10 \log_{10}(P_{\text{Watts}})$ , where P is the transmitter power in Watts.**

#### Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

#### Test Settings



1. Start frequency was set to 30MHz and stop frequency was set to 10GHz (separated into at least two plots per channel)
2. RBW  $\geq$  100kHz
3. VBW  $\geq$  3 x RBW
4. Detector = RMS
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

#### Test Setup


The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-2. Test Instrument & Measurement Setup

FCC ID: A3LSMS901E	 PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 17 of 34

# LTE Band 26



Plot 7-11. Conducted Spurious Plot (LTE Band 26 - 15MHz QPSK - RB Size 1, RB Offset 0)



Plot 7-12. Conducted Spurious Plot (LTE Band 26 - 15MHz QPSK - RB Size 1, RB Offset 0)

FCC ID: A3LSMS901E		PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset		Page 18 of 34



Plot 7-13. Conducted Spurious Plot (LTE Band 26 - 15MHz QPSK - RB Size 1, RB Offset 0)

FCC ID: A3LSMS901E	PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 19 of 34

## 7.4 Band Edge Emissions at Antenna Terminal

### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

**For LTE B26 operation under Part 90.691, the minimum permissible attenuation level of any spurious emission removed from the EA licensee’s frequency block by greater than 37.5 kHz is  $43 + 10\log_{10}(P_{[Watts]})$ , where  $P$  is the transmitter power in Watts. The minimum permissible attenuation level of any spurious emission removed from the EA licensee’s frequency block by up to and including 37.5 kHz is  $50 + 10\log_{10}(P_{[Watts]})$ , where  $P$  is the transmitter power in Watts.**

### Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

### Test Settings

1. Span was set large enough so as to capture all out of band emissions near the band edge
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Detector = RMS
5. Trace mode = trace average
6. Sweep time = auto couple
7. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-3. Test Instrument & Measurement Setup


### Test Notes

For channel edge emission, the signal analyzer’s “ACP” measurement capability is used.


Per 22.917(b) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMS901E	 PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 20 of 34

## LTE Band 26




Plot 7-14. Channel Edge Plot (LTE Band 26 - 15MHz QPSK - Mid Channel)



Plot 7-15. Channel Edge Plot (LTE Band 26 - 10MHz QPSK - Mid Channel)

FCC ID: A3LSMS901E	<b>PCTEST</b> Proud to be part of	<b>PART 22 &amp; 90 MEASUREMENT REPORT</b>	<b>Approved by:</b> Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 21 of 34



Plot 7-16. Channel Edge Plot (LTE Band 26 - 5MHz QPSK - Low Channel)



Plot 7-17. Channel Edge Plot (LTE Band 26 - 5MHz QPSK - High Channel)

FCC ID: A3LSMS901E	<b>PCTEST</b> Proud to be part of	<b>PART 22 &amp; 90 MEASUREMENT REPORT</b>	<b>Approved by:</b> Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 22 of 34



Plot 7-18. Channel Edge Plot (LTE Band 26 - 3MHz QPSK - Low Channel)



Plot 7-19. Channel Edge Plot (LTE Band 26 - 3MHz QPSK - High Channel)

FCC ID: A3LSMS901E	<b>PCTEST</b> Proud to be part of	<b>PART 22 &amp; 90 MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset		Page 23 of 34



Plot 7-20. Channel Edge Plot (LTE Band 26 - 1.4MHz QPSK - Low Channel)



Plot 7-21. Channel Edge Plot (LTE Band 26 - 1.4MHz QPSK - High Channel)

FCC ID: A3LSMS901E	<b>PCTEST</b> Proud to be part of	<b>PART 22 &amp; 90 MEASUREMENT REPORT</b>	<b>Approved by:</b> Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 24 of 34





## 7.5 Conducted Power Output Data

§2.1046 §90.635

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]	Conducted Power [Watts]	Conducted Power Limit [dBm]	Margin [dB]
15 MHz	QPSK	26765	821.5	1 / 0	23.62	0.230	50.00	-26.38
	16-QAM	26765	821.5	1 / 74	22.88	0.194	50.00	-27.12
	64-QAM	26765	821.5	1 / 0	21.81	0.152	50.00	-28.19
	256-QAM	26765	821.5	1 / 74	18.69	0.074	50.00	-31.31
10 MHz	QPSK	26740	819.0	1 / 25	23.65	0.232	50.00	-26.35
	16-QAM	26740	819.0	1 / 25	23.05	0.202	50.00	-26.95
	64-QAM	26740	819.0	1 / 25	22.22	0.167	50.00	-27.78
	256-QAM	26740	819.0	1 / 25	18.70	0.074	50.00	-31.30
5 MHz	QPSK	26715	816.5	1 / 12	23.62	0.230	50.00	-26.38
		26765	821.5	1 / 12	23.64	0.231	50.00	-26.36
	16-QAM	26715	816.5	1 / 0	22.95	0.197	50.00	-27.05
		26765	821.5	1 / 12	23.14	0.206	50.00	-26.86
	64-QAM	26715	816.5	1 / 12	21.90	0.155	50.00	-28.10
		26765	821.5	1 / 12	22.02	0.159	50.00	-27.98
	256-QAM	26715	816.5	1 / 12	18.82	0.076	50.00	-31.18
		26765	821.5	1 / 12	18.94	0.078	50.00	-31.06
3 MHz	QPSK	26705	815.5	1 / 7	23.73	0.236	50.00	-26.27
		26775	822.5	1 / 14	23.68	0.233	50.00	-26.32
	16-QAM	26705	815.5	1 / 0	23.02	0.201	50.00	-26.98
		26775	822.5	1 / 7	23.12	0.205	50.00	-26.88
	64-QAM	26705	815.5	1 / 7	22.07	0.161	50.00	-27.93
		26775	822.5	1 / 7	22.06	0.161	50.00	-27.94
	256-QAM	26705	815.5	1 / 7	18.90	0.078	50.00	-31.10
		26775	822.5	1 / 7	18.80	0.076	50.00	-31.20
1.4 MHz	QPSK	26697	814.7	1 / 3	23.91	0.246	50.00	-26.09
		26783	823.3	1 / 3	23.66	0.232	50.00	-26.34
	16-QAM	26697	814.7	1 / 3	23.13	0.205	50.00	-26.87
		26783	823.3	1 / 5	22.99	0.199	50.00	-27.01
	64-QAM	26697	814.7	1 / 0	22.04	0.160	50.00	-27.96
		26783	823.3	1 / 3	21.92	0.155	50.00	-28.08
	256-QAM	26697	814.7	1 / 5	18.82	0.076	50.00	-31.18
		26783	823.3	1 / 0	18.71	0.074	50.00	-31.29

Table 7-2. Conducted Power Output Data (LTE Band 26)

FCC ID: A3LSMS901E		PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset		Page 25 of 34

## 7.6 Radiated Power (ERP)

### Test Overview

Effective Radiated Power (ERP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.



### Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17


### Test Settings

1. Radiated power measurements are performed using the signal analyzer’s “channel power” measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq$  3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $\geq$  2 x span / RBW
6. Detector = RMS
7. Trigger is set to “free run” for signals with continuous operation with the sweep times set to “auto”.
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: A3LSMS901E	 PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 26 of 34

**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-4. Radiated Test Setup <1GHz**



**Test Notes**

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

<b>FCC ID:</b> A3LSMS901E		<b>PART 22 &amp; 90 MEASUREMENT REPORT</b>	<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2109290114-06.A3L	<b>Test Dates:</b> 10/14/2021 - 11/10/2021	<b>EUT Type:</b> Portable Handset	Page 27 of 34

Bandwidth	Mod.	Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Ant. Gain [dBi]	RB Size/Offset	Substitute Level [dBm]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
15 MHz	QPSK	821.5	V	141	253	1.24	1 / 37	19.48	18.57	0.072	38.45	-19.88
	16-QAM	821.5	V	141	253	1.24	1 / 37	18.61	17.70	0.059	38.45	-20.75
1.4 MHz	QPSK (WCP)	821.5	V	121	282	1.24	1 / 5	13.67	12.76	0.019	38.45	-25.69

Table 7-3. ERP Data (LTE Band 26)

FCC ID: A3LSMS901E	 PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 28 of 34

## 7.7 Radiated Spurious Emissions Measurements

### Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.



### Test Procedures Used

KDB 971168 D01 v03r01 – Section 5.8

ANSI/TIA-603-E-2016 – Section 2.2.12


### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq$  3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $\geq$  2 x span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: A3LSMS901E	 PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 29 of 34

**Test Setup**



The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-5. Test Instrument & Measurement Setup**

**Test Notes**

1. Field strengths are calculated using the Measurement quantity conversions in KDB 971168 Section 5.8.4.
  - a.  $E \text{ (dB}\mu\text{V/m)} = \text{Measured amplitude level (dBm)} + 107 + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$
  - b.  $\text{EIRP (dBm)} = E \text{ (dB}\mu\text{V/m)} + 20\log D - 104.8$ ; where D is the measurement distance in meters.
2. For LTE mode, the device was tested under all modulations, RB sizes and offsets, and channel bandwidth configurations and the worst case emissions are reported with 1 RB.
3. This unit was tested with its standard battery.
4. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
5. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: A3LSMS901E	 PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 30 of 34

# LTE Band 26





Plot 7-22. Radiated Spurious Plot (LTE Band 26)

Bandwidth (MHz):	15
Frequency (MHz):	821.5
Modulation Signal:	QPSK
RB Config (Size / Offset):	1 / 37

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
1643.00	H	156	9	-74.59	-7.53	24.88	-70.38	-13.00	-57.38
2464.50	H	-	-	-75.58	-4.10	27.32	-67.93	-13.00	-54.93
3286.00	H	-	-	-77.39	-0.85	28.76	-66.50	-13.00	-53.50
4107.50	H	-	-	-77.02	0.74	30.72	-64.54	-13.00	-51.54
4929.00	H	-	-	-78.34	1.42	30.08	-65.18	-13.00	-52.18

Table 7-4. Radiated Spurious Data (LTE Band 26 – Mid Channel)

FCC ID: A3LSMS901E	 PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 31 of 34

## 7.8 Frequency Stability / Temperature Variation

### Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

***The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency.***

### Test Procedure Used

ANSI/TIA-603-E-2016

### Test Settings



1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

### Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

### Test Notes

None


FCC ID: A3LSMS901E	 PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 32 of 34





# LTE Band 26

LTE Band 26					
Operating Frequency (Hz):		819,000,000			
Ref. Voltage (VDC):		4.39			
Deviation Limit:		± 0.00025% or 2.5 ppm			
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.39	- 30	819,000,551	-588	-0.0000717
		- 20	819,000,085	-1,053	-0.0001286
		- 10	819,000,763	-375	-0.0000458
		0	819,001,312	174	0.0000212
		+ 10	819,001,271	133	0.0000162
		+ 20 (Ref)	819,001,138	0	0.0000000
		+ 30	819,000,637	-501	-0.0000612
		+ 40	819,001,489	351	0.0000429
Battery Endpoint	3.85	+ 20	819,001,997	859	0.0001049

Table 7-5. LTE Band 26 Frequency Stability Data





Plot 7-23. LTE Band 26 Frequency Stability Chart

FCC ID: A3LSMS901E	 PART 22 & 90 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109290114-06.A3L	Test Dates: 10/14/2021 - 11/10/2021	EUT Type: Portable Handset	Page 33 of 34

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMS901E** complies with all the requirements of Parts 22(H) and 90 of the FCC rules.

FCC ID: A3LSMS901E		PART 22 & 90 MEASUREMENT REPORT	 <b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2109290114-06.A3L	<b>Test Dates:</b> 10/14/2021 - 11/10/2021	<b>EUT Type:</b> Portable Handset	Page 34 of 34