

MEASUREMENT REPORT FCC PART 15.247 WLAN

Applicant Name:
Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea


Date of Testing:
09/22- 12/22/2021
Test Report Issue Date:
01/07/2022
Test Site/Location:
PCTEST Lab.Columbia, MD, USA
Test Report Serial No.:
1M2112090153-09.A3L

FCC ID:	A3LSMS901JPN
APPLICANT:	Samsung Electronics Co., Ltd.

Application Type:	Certification
Model:	SC-51C
Additional Model(s):	SCG13
EUT Type:	Portable Handset
Frequency Range:	2412 – 2472MHz
Modulation Type:	CCK/DSSS/OFDM
FCC Classification:	Digital Transmission System (DTS)
FCC Rule Part(s):	Part 15 Subpart C (15.247)
Test Procedure(s):	ANSI C63.10-2013, KDB 558074 D01 v05r02, KDB 662911 D01 v02r01, KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and KDB 558074 D01 v05r02. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President




FCC ID: A3LSMS901JPN	 PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset	Page 1 of 118	


TABLE OF CONTENTS

1.0	INTRODUCTION.....	4
1.1	Scope	4
1.2	PCTEST Location.....	4
1.3	Test Facilities / Accreditations	4
2.0	PRODUCT INFORMATION	5
2.1	Equipment Description	5
2.2	Device Capabilities	5
2.3	Test Configuration	7
2.4	Antenna Description	8
2.5	Software and Firmware	8
2.6	EMI Suppression Device(s)/Modifications	8
3.0	DESCRIPTION OF TESTS	9
3.1	Evaluation Procedure	9
3.2	AC Line Conducted Emissions	9
3.3	Radiated Emissions.....	9
3.4	Environmental Conditions.....	10
4.0	ANTENNA REQUIREMENTS	11
5.0	MEASUREMENT UNCERTAINTY	12
6.0	TEST EQUIPMENT CALIBRATION DATA	13
7.0	TEST RESULTS.....	14
7.1	Summary	14
7.2	6dB Bandwidth Measurement	15
7.3	Output Power Measurement.....	30
7.4	Power Spectral Density	34
7.5	Conducted Emissions at the Band Edge	62
7.6	Conducted Spurious Emissions.....	81
7.7	Radiated Spurious Emission Measurements – Above 1 GHz.....	89
7.7.1	SISO Antenna-1 Radiated Spurious Emission Measurements	92
7.7.2	SISO Antenna-2 Radiated Spurious Emission Measurements	96
7.7.3	MIMO/CDD Radiated Spurious Emission Measurements.....	100
7.7.4	SISO Antenna-1 Radiated Restricted Band Edge Measurements	104
7.7.5	SISO Antenna-2 Radiated Restricted Band Edge Measurements	106
7.7.6	MIMO Radiated Restricted Band Edge Measurements	108
7.8	Radiated Spurious Emissions Measurements – Below 1GHz	110
7.9	Line-Conducted Test Data.....	114
8.0	CONCLUSION	118

FCC ID: A3LSMS901JPN	 <small>Proud to be part of  element</small>	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset	Page 2 of 118	



MEASUREMENT REPORT



Mode	Tx Frequency (MHz)	ANT1				ANT2				MIMO			
		Avg Conducted		Peak Conducted		Avg Conducted		Peak Conducted		Avg Conducted		Peak Conducted	
		Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)
802.11b	2412 - 2472	50.003	16.99	134.586	21.29	49.545	16.95	94.189	19.74	99.541	19.98	222.844	23.48
802.11g	2412 - 2472	52.845	17.23	281.190	24.49	53.703	17.30	226.986	23.56	106.414	20.27	506.991	27.05
802.11n	2412 - 2472	62.661	17.97	184.077	22.65	62.951	17.99	180.302	22.56	125.603	20.99	359.749	25.56
802.11ax	2412 - 2472	58.210	17.65	229.087	23.60	62.951	17.99	231.739	23.65	121.060	20.83	461.318	26.64

EUT Overview

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 3 of 118

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Location

These Measurement tests were conducted at the PCTEST facilities located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facilities / Accreditations

- PCTEST is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset	Page 4 of 118	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMS901JPN**. The test data contained in this report pertains only to the emissions due to the EUT's WLAN (DTS) transmitter.

Test Device Serial No.: 1045M, 1013M, 1350M, 1046M

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII (5GHz), Bluetooth (1x, EDR, LE), NFC, Wireless Power Transfer

Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442		

Table 2-1. Frequency/ Channel Operations

Note: The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section 6.0 b) of ANSI C63.10-2013 and KDB 558074 D01 v05r02. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Maximum Achievable Duty Cycles				
802.11 Mode/Band		Duty Cycle [%]		
		ANT1	ANT2	MIMO
2.4GHz	b	98.9	98.9	99.1
	g	93.3	93.3	93.5
	n	92.2	92.2	91.3
	ax	99.7	99.7	99.7

Table 2-2. Measured Duty Cycles

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 5 of 118

Data Rates Supported: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps (b)
 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps (g)
 6.5/7.2Mbps, 13/14.4Mbps, 19.5/21.7Mbps, 26/28.9Mbps, 39/43.3Mbps, 52/57.8Mbps, 58.5/65Mbps, 65/72.2Mbps (n)
 8/8.6Mbps, 16/17.2Mbps, 24/25.8Mbps, 33/34.4Mbps, 49/51.6Mbps, 65/68.8Mbps, 73/77.4Mbps, 81/86Mbps, 98/103.2Mbps, 108/114.7Mbps, 122/129Mbps, 135/143.4Mbps (ax)
 2Mbps, 4Mbps, 11Mbps, 22Mbps (CDD b)
 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 72Mbps, 96Mbps, 108Mbps (CDD g)
 13/14.4Mbps, 26/28.9Mbps, 39/43.3Mbps, 52/57.8Mbps, 78/86.7Mbps, 104/115.6Mbps, 117/130Mbps, 130/144.4Mbps (MIMO n)
 16/17.2Mbps, 32/34.4Mbps, 49/51.6Mbps, 66/68.8Mbps, 98/103.2Mbps, 130/137.6Mbps, 146/154.8Mbps, 162/172Mbps, 196/206.5Mbps, 216/229.4Mbps, 244/258Mbps, 270/286.8Mbps (MIMO ax)

The device employs MIMO technology. Below are the possible configurations.

WiFi Configurations		SISO		SDM		CDD	
		ANT1	ANT2	ANT1	ANT2	ANT1	ANT2
2.4GHz	11b	✘	✓	✘	✘	✓	✓
	11g	✘	✓	✘	✘	✓	✓
	11n	✘	✓	✓	✓	✓	✓
	11ax SU	✘	✓	✓	✓	✓	✓

Table 2-3. Frequency / Channel Operations

✓ = Support ; ✘ = NOT Support
SISO = Single Input Single Output
SDM = Spatial Diversity Multiplexing – MIMO function
CDD = Cyclic Delay Diversity - 2Tx Function

This device supports simultaneous transmission operation, which allows for two SISO channels to operate independent of one another in the 2.4GHz and 5GHz bands simultaneously on each antenna. The following tables show the worst case configurations determined during testing. The data for these configurations is contained in the UNII test report.

Configuration 1: ANT1 and ANT2 both transmitting in 2.4GHz and 5GHz modes simultaneously

Description	2.4 GHz Emission	5 GHz Emission
Antenna	1, 2	1, 2
Channel	11	120
Operating Frequency (MHz)	2462	5600
Data Rate (Mbps)	6	6
Mode	802.11b	802.11a

Table 2-4. Config-1 (ANT1 2.4GHz & ANT2 5GHz)

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 6 of 118

Configuration 2: ANT1 and ANT2 both transmitting in 2.4GHz and 6GHz modes simultaneously

Description	2.4 GHz Emission	6 GHz Emission
Antenna	1, 2	1, 2
Channel	11	1
Operating Frequency (MHz)	2462	5955
Data Rate (Mbps)	6	6
Mode	802.11b	802.11ax

Table 2-5. Config-2 (ANT1 5GHz & ANT2 2.4GHz)

Configuration 3: ANT1 and ANT2 both transmitting in 5GHz modes simultaneously, Antenna 1 is transmitting BT and Antenna 2 is transmitting 2.4GHz additionally

Description	Bluetooth	2.4 GHz Emission	6GHz Emission
Antenna	1	2	1, 2
Channel	0	11	1
Operating Frequency (MHz)	2402	2462	5955
Data Rate (Mbps)	1	6	6
Mode	GFSK	802.11a	802.11ax

Table 2-6. Config-3 (ANT1 MIMO & ANT2 MIMO)

Configuration 3: ANT1 and ANT2 both transmitting in 6GHz modes simultaneously, Antenna 1 is transmitting BT and Antenna 2 is transmitting 2.4GHz additionally

Description	Bluetooth	2.4 GHz Emission	5 GHz Emission
Antenna	1	2	1, 2
Channel	0	11	36
Operating Frequency (MHz)	2402	2462	5180
Data Rate (Mbps)	1	6	6
Mode	GFSK	802.11b	802.11a

Table 2-7. Config-3 (ANT1 MIMO & ANT2 MIMO)

2.3 Test Configuration

The EUT was tested per the guidance of KDB 558074 D01 v05r02. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 7.9 for AC line conducted emissions test setups, for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, and 7.6 for antenna port conducted emissions test setups.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) Model: EP-N5100 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 7 of 118

2.4 Antenna Description

Following antenna was used for the testing.

Frequency [GHz]	Antenna 1 Gain [dBi]	Antenna 2 Gain [dBi]
2.4	-3.3	-6.1

Table 2-8. Maximum Peak Antenna Gain

2.5 Software and Firmware

The test was conducted with firmware version S901USQU0AUJ5 installed on the EUT.

2.6 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset	Page 8 of 118	

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.9. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest

FCC ID: A3LSMS901JPN	 PCTEST <small>Proud to be part of element</small>	MEASUREMENT REPORT (CERTIFICATION)	 Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset	Page 9 of 118

frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset	Page 10 of 118	

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connections to an external antenna.

Conclusion:

The EUT unit complies with the requirement of §15.203.

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset	Page 11 of 118	

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMS901JPN	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 12 of 118

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	WL25-1	Conducted Cable Set (25GHz)	7/2/2020	Annual	8/18/2022	WL25-1
-	WL40-1	Conducted Cable Set (40GHz)	9/10/2021	Annual	9/10/2022	WL40-1
Agilent	N9038A	MXE EMI Receiver	7/17/2019	Annual	12/1/2021	MY51210133
Agilent	N9030A	PXA Signal Analyzer (44GHz)	7/17/2020	Annual	7/21/2022	MY49430494
Anritsu	ML2495A	Power Meter	12/17/2019	Annual	1/18/2022	941001
Anritsu	MA2411B	Pulse Power Sensor	8/14/2019	Annual	9/21/2022	1315051
Com-Power	AL-130R	9kHz - 30MHz Loop Antenna	10/10/2019	Biennial	12/10/2021	121085
Emco	3115	Horn Antenna (1-18GHz)	6/18/2020	Biennial	6/18/2022	9704-5182
Emco	3116C	Horn Antenna (18 - 40GHz)	5/11/2021	Biennial	5/11/2023	218893
ETS-Lindgren	3816/2NM	Line Impedance Stabilization Network	7/9/2020	Biennial	7/9/2022	114451
Keysight Technologies	N9030A	PXA Signal Analyzer (44GHz)	8/17/2020	Annual	12/17/2021	MY52350166
Pasternack	NMLC-2	Line Conducted Emissions Cable (NM)	9/10/2021	Annual	9/10/2022	NMLC-2
Rohde & Schwarz	TS-PR1840	18-40 GHz Pre-Amplifier	9/10/2021	Annual	9/10/2022	100059
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	8/3/2021	Annual	8/3/2022	100342
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44GHz	1/21/2021	Annual	1/21/2022	101716
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	8/25/2021	Annual	8/25/2022	103200
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	9/3/2021	Annual	9/3/2022	102138
Solar Electronics	8012-50-R-24-BNC	Line Impedance Stabilization Network	9/21/2021	Biennial	9/21/2023	310233
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Test Antenna	8/13/2020	Biennial	8/13/2022	101073
Schwarzbeck	VULB9162	Bilog Antenna	4/17/2020	Biennial	4/17/2022	00301

Table 0-1. Annual Test Equipment Calibration Schedule

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 13 of 118

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMS901JPN
 FCC Classification: Digital Transmission System (DTS)

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	RSS-247 [5.2]	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 7.2
15.247(b)(3)	RSS-247 [5.4]	Transmitter Output Power	< 1 Watt		PASS	Sections 7.3
15.247(e)	RSS-247 [5.2]	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 7.4
15.247(d)	RSS-247 [5.5]	Band Edge / Out-of-Band Emissions	≥ 20dBc		PASS	Sections 7.5, 7.6
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Sections 7.7, Error! Reference source not found.
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen[8.8])	LINE CONDUCTED	PASS	Section 7.9

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST “WLAN Automation,” Version 3.5.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST “Chamber Automation,” Version 1.3.1.

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 14 of 118

7.2 6dB Bandwidth Measurement

§15.247(a.2); RSS-247 [5.2]

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated and the worst case configuration results are reported in this section.

The minimum permissible 6dB bandwidth is 500 kHz.

Test Procedure Used

ANSI C63.10-2013 – Section 11.8.2 Option 2
KDB 558074 D01 v05r02 – Section 8.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

None


FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 15 of 118

SISO Antenna-1 6 dB Bandwidth Measurements


Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
2412	1	b	1	7.615	0.500
2437	6	b	1	7.635	0.500
2462	11	b	1	7.669	0.500
2412	1	g	6	14.50	0.500
2437	6	g	6	15.15	0.500
2462	11	g	6	15.74	0.500
2412	1	n	6.5/7.2 (MCS0)	15.10	0.500
2437	6	n	6.5/7.2 (MCS0)	15.12	0.500
2462	11	n	6.5/7.2 (MCS0)	16.36	0.500
2412	1	ax	6.5/7.2 (MCS0)	15.77	0.500
2437	6	ax	6.5/7.2 (MCS0)	17.88	0.500
2462	11	ax	6.5/7.2 (MCS0)	16.87	0.500

Table 7-2. Conducted Bandwidth Measurements SISO ANT1

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 16 of 118




Plot 7-1. 6dB Bandwidth Plot SISO ANT1 (802.11b – Ch. 1)




Plot 7-2. 6dB Bandwidth Plot SISO ANT1 (802.11b – Ch. 6)

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 17 of 118




Plot 7-3. 6dB Bandwidth Plot SISO ANT1 (802.11b – Ch. 11)




Plot 7-4. 6dB Bandwidth Plot SISO ANT1 (802.11g – Ch. 1)


FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 18 of 118




Plot 7-5. 6dB Bandwidth Plot SISO ANT1 (802.11g – Ch. 6)




Plot 7-6. 6dB Bandwidth Plot SISO ANT1 (802.11g – Ch. 11)

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 19 of 118




Plot 7-7. 6dB Bandwidth Plot SISO ANT1 (802.11n (2.4GHz) – Ch. 1)




Plot 7-8. 6dB Bandwidth Plot SISO ANT1 (802.11n (2.4GHz) – Ch. 6)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 20 of 118




Plot 7-9. 6dB Bandwidth Plot SISO ANT1 (802.11n (2.4GHz) – Ch. 11)




Plot 7-10. 6dB Bandwidth Plot SISO ANT1 (802.11ax (2.4GHz) – Ch. 1)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 21 of 118



Plot 7-11. 6dB Bandwidth Plot SISO ANT1 (802.11ax (2.4GHz) – Ch. 6)



Plot 7-12. 6dB Bandwidth Plot SISO ANT1 (802.11ax (2.4GHz) – Ch. 11)


FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 22 of 118

SISO Antenna-2 6 dB Bandwidth Measurements


Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
2412	1	b	1	8.133	0.500
2437	6	b	1	8.102	0.500
2462	11	b	1	7.617	0.500
2412	1	g	6	15.70	0.500
2437	6	g	6	15.17	0.500
2462	11	g	6	15.72	0.500
2412	1	n	6.5/7.2 (MCS0)	15.99	0.500
2437	6	n	6.5/7.2 (MCS0)	15.18	0.500
2462	11	n	6.5/7.2 (MCS0)	16.35	0.500
2412	1	ax	6.5/7.2 (MCS0)	16.98	0.500
2437	6	ax	6.5/7.2 (MCS0)	17.61	0.500
2462	11	ax	6.5/7.2 (MCS0)	15.77	0.500

Table 7-3. Conducted Bandwidth Measurements SISO ANT2

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 23 of 118




Plot 7-13. 6dB Bandwidth Plot SISO ANT2 (802.11b – Ch. 1)




Plot 7-14. 6dB Bandwidth Plot SISO ANT2 (802.11b – Ch. 6)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 24 of 118




Plot 7-15. 6dB Bandwidth Plot SISO ANT2 (802.11b – Ch. 11)




Plot 7-16. 6dB Bandwidth Plot SISO ANT2 (802.11g – Ch. 1)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 25 of 118




Plot 7-17. 6dB Bandwidth Plot SISO ANT2 (802.11g – Ch. 6)




Plot 7-18. 6dB Bandwidth Plot SISO ANT2 (802.11g – Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 26 of 118




Plot 7-19. 6dB Bandwidth Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 1)




Plot 7-20. 6dB Bandwidth Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 6)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 27 of 118




Plot 7-21. 6dB Bandwidth Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 11)




Plot 7-22. 6dB Bandwidth Plot SISO ANT2 (802.11ax (2.4GHz) – Ch. 1)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 28 of 118



Plot 7-23. 6dB Bandwidth Plot SISO ANT2 (802.11ax (2.4GHz) – Ch. 6)



Plot 7-24. 6dB Bandwidth Plot SISO ANT2 (802.11ax (2.4GHz) – Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 29 of 118

7.3 Output Power Measurement

§15.247(b.3); RSS-247 [5.4]

Test Overview and Limits

A transmitter antenna terminal of EUT is connected to the input of an RF power sensor. Measurement is made using a broadband power meter capable of making peak and average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

Test Procedure Used

ANSI C63.10-2013 – Section 11.9.1.3 PKPM1 Peak Power Method
 KDB 558074 D01 v05r02 – Section 8.3.1.3 PKPM1 Peak-reading Power Meter Method
 ANSI C63.10-2013 – Section 11.9.2.3.2 Method AVGPM-G
 KDB 558074 D01 v05r02 – Section 8.3.2.3 Measurement using a Power Meter (PM)
 ANSI C63.10-2013 – Section 14.2 Measure-and-Sum Technique
 KDB 662911 D01 v02r01 – Section E)1) Measure-and-Sum Technique

Test Settings

Method PKPM1 (Peak Power Measurement)

Peak power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The pulse sensor employs a VBW = 50MHz so this method was only used for signals whose DTS bandwidth was less than or equal to 50MHz.

Method AVGPM-G (Average Power Measurement)

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.



Figure 7-2. Test Instrument & Measurement Setup for Power Meter Measurements

Test Notes

None

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 30 of 118

2.4GHZ	Freq [MHz]	Channel	Detector	IEEE Transmission Mode				Conducted Power Limit [dBm]	Conducted Power Margin [dB]
				802.11b	802.11g	802.11n	802.11ax		
	2412	1	AVG	16.79	17.07	17.97	17.62	30.00	-12.03
		PEAK	20.71	24.27	22.65	23.60	30.00	-5.73	
2437	6	AVG	16.98	17.23	17.89	17.55	30.00	-12.11	
		PEAK	21.29	24.49	22.54	22.55	30.00	-5.51	
2457	10	AVG			17.67	17.65	30.00	-12.33	
		PEAK			22.14	22.21	30.00	-7.86	
2462	11	AVG	16.99	17.02	16.12	16.02	30.00	-12.98	
		PEAK	20.14	23.32	22.60	22.66	30.00	-6.68	
2467	12	AVG	5.68	5.68	5.55	5.74	30.00	-24.32	
		PEAK	9.43	12.29	12.34	13.33	30.00	-17.66	
2472	13	AVG	-0.23	-0.48	-0.26	-0.43	30.00	-30.23	
		PEAK	3.50	5.99	7.01	7.09	30.00	-22.99	

Table 7-4. Conducted Output Power Measurements SISO ANT1

2.4GHZ	Freq [MHz]	Channel	Detector	IEEE Transmission Mode				Conducted Power Limit [dBm]	Conducted Power Margin [dB]
				802.11b	802.11g	802.11n	802.11ax		
	2412	1	AVG	16.54	17.16	17.99	17.63	30.00	-12.01
		PEAK	19.64	23.24	22.29	23.65	30.00	-6.76	
2437	6	AVG	16.95	17.28	17.79	17.84	30.00	-12.21	
		PEAK	19.47	23.54	22.56	22.64	30.00	-6.46	
2457	10	AVG			17.72	17.99	30.00	-12.28	
		PEAK			22.10	22.61	30.00	-7.90	
2462	11	AVG	16.68	17.30	16.45	16.25	30.00	-12.70	
		PEAK	19.74	23.56	22.46	22.38	30.00	-6.44	
2467	12	AVG	5.98	5.72	5.55	5.67	30.00	-24.02	
		PEAK	9.83	11.48	12.71	14.06	30.00	-17.29	
2472	13	AVG	-0.14	-0.48	-0.12	-0.46	30.00	-30.12	
		PEAK	3.60	6.29	6.84	7.69	30.00	-23.16	

Table 7-5. Conducted Output Power Measurements SISO ANT2

2.4GHZ	Freq [MHz]	Channel	Detector	Conducted Power [dBm]			Conducted Power Limit [dBm]	Conducted Power Margin [dB]
				ANT1	ANT2	MIMO		
	2412	1	AVG	16.79	16.54	19.68	30.00	-10.32
		PEAK	20.71	19.64	23.22	30.00	-6.78	
2437	6	AVG	16.98	16.95	19.98	30.00	-10.02	
		PEAK	21.29	19.47	23.48	30.00	-6.52	
2462	11	AVG	16.99	16.68	19.85	30.00	-10.15	
		PEAK	20.14	19.74	22.95	30.00	-7.05	
2467	12	AVG	5.68	5.98	8.84	30.00	-21.16	
		PEAK	9.43	9.83	12.64	30.00	-17.36	
2472	13	AVG	-0.23	-0.14	2.83	30.00	-27.17	
		PEAK	3.50	3.60	6.56	30.00	-23.44	

Table 7-6. Conducted Output Power Measurements CDD (802.11b)

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 31 of 118

2.4GHZ	Freq [MHz]	Channel	Detector	Conducted Power [dBm]			Conducted Power Limit [dBm]	Conducted Power Margin [dB]
				ANT1	ANT2	MIMO		
	2412	1	AVG	17.07	17.16	20.13	30.00	-9.87
		PEAK	24.27	23.24	26.80	30.00	-3.20	
2437	6	AVG	17.23	17.28	20.27	30.00	-9.73	
		PEAK	24.49	23.54	27.05	30.00	-2.95	
2462	11	AVG	17.02	17.30	20.17	30.00	-9.83	
		PEAK	23.32	23.56	26.45	30.00	-3.55	
2467	12	AVG	5.68	5.72	8.71	30.00	-21.29	
		PEAK	12.29	11.48	14.91	30.00	-15.09	
2472	13	AVG	-0.48	-0.48	2.53	30.00	-27.47	
		PEAK	5.99	6.29	9.15	30.00	-20.85	

Table 7-7. Conducted Output Power Measurements CDD (802.11g)

2.4GHZ	Freq [MHz]	Channel	Detector	Conducted Power [dBm]			Conducted Power Limit [dBm]	Conducted Power Margin [dB]
				ANT1	ANT2	MIMO		
	2412	1	AVG	17.97	17.99	20.99	30.00	-9.01
		PEAK	22.65	22.29	25.48	30.00	-4.52	
2437	6	AVG	17.89	17.79	20.85	30.00	-9.15	
		PEAK	22.54	22.56	25.56	30.00	-4.44	
2462	11	AVG	16.12	16.45	19.30	30.00	-10.70	
		PEAK	22.60	22.46	25.54	30.00	-4.46	
2467	12	AVG	5.55	5.55	8.56	30.00	-21.44	
		PEAK	12.34	12.71	15.54	30.00	-14.46	
2472	13	AVG	-0.26	-0.12	2.82	30.00	-27.18	
		PEAK	7.01	6.84	9.94	30.00	-20.06	

Table 7-8. Conducted Output Power Measurements MIMO (802.11n)

2.4GHZ	Freq [MHz]	Channel	Detector	Conducted Power [dBm]			Conducted Power Limit [dBm]	Conducted Power Margin [dB]
				ANT1	ANT2	MIMO		
	2412	1	AVG	17.62	17.63	20.64	30.00	-9.36
		PEAK	23.60	23.65	26.64	30.00	-3.36	
2437	6	AVG	17.55	17.84	20.71	30.00	-9.29	
		PEAK	22.55	22.64	25.61	30.00	-4.39	
2457	10	AVG	17.65	17.99	20.83	30.00	-9.17	
		PEAK	22.21	22.61	25.42	30.00	-4.58	
2462	11	AVG	16.02	16.25	19.15	30.00	-10.85	
		PEAK	22.66	22.38	25.53	30.00	-4.47	
2467	12	AVG	5.74	5.67	8.72	30.00	-21.28	
		PEAK	13.33	14.06	16.72	30.00	-13.28	
2472	13	AVG	-0.43	-0.46	2.57	30.00	-27.43	
		PEAK	7.09	7.69	10.41	30.00	-19.59	

Table 7-9. Conducted Output Power Measurements MIMO (802.11ax)

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 32 of 118

Note:

Per ANSI C63.10-2013 and KDB 662911 D01 v02r01 Section E)1), the conducted powers at Antenna 1 and Antenna 2 were first measured separately during MIMO transmission as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Sample MIMO/CDD Calculation:

At 2437MHz in 802.11n mode, the average conducted output power was measured to be 17.89 dBm for Antenna-1 and 17.79 dBm for Antenna-2.

$$\text{Antenna 1} + \text{Antenna 2} = \text{MIMO/CDD}$$

$$(17.89 \text{ dBm} + 17.79 \text{ dBm}) = (61.52 \text{ mW} + 60.12 \text{ mW}) = 121.64 \text{ mW} = 20.85 \text{ dBm}$$

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset	Page 33 of 118	

7.4 Power Spectral Density

§15.247(e); RSS-247 [5.2]

Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated and the worst case configuration results are reported in this section.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

ANSI C63.10-2013 – Section 11.10.2 Method PKPSD
 KDB 558074 D01 v05r02 – Section 8.4 DTS Maximum Power Spectral Density level in the fundamental emission
 ANSI C63.10-2013 – Section 14.3.2.2 Measure-and-Sum Technique
 KDB 662911 D01 v02r01 – Section E)2) Measure-and-Sum Technique

Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 10kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

Test Notes

None

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 34 of 118

SISO Antenna-1 Power Spectral Density Measurements

Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]	Pass / Fail
2412	1	b	1	0.97	8.00	-7.03	Pass
2437	6	b	1	-0.46	8.00	-8.46	Pass
2462	11	b	1	0.41	8.00	-7.59	Pass
2412	1	g	6	-2.11	8.00	-10.11	Pass
2437	6	g	6	-1.07	8.00	-9.07	Pass
2462	11	g	6	-1.52	8.00	-9.52	Pass
2412	1	n	6.5/7.2 (MCS0)	0.00	8.00	-8.00	Pass
2437	6	n	6.5/7.2 (MCS0)	-1.22	8.00	-9.22	Pass
2462	11	n	6.5/7.2 (MCS0)	-0.80	8.00	-8.80	Pass
2412	1	ax	6.5/7.2 (MCS0)	-1.29	8.00	-9.29	Pass
2437	6	ax	6.5/7.2 (MCS0)	-2.91	8.00	-10.91	Pass
2462	11	ax	6.5/7.2 (MCS0)	-2.50	8.00	-10.50	Pass

Table 7-10. Conducted Power Density Measurements SISO ANT1



Plot 7-25. Power Spectral Density Plot SISO ANT1 (802.11b - Ch. 1)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 - 12/22/2021	EUT Type: Portable Handset		Page 35 of 118




Plot 7-26. Power Spectral Density Plot SISO ANT1 (802.11b – Ch. 6)




Plot 7-27. Power Spectral Density Plot SISO ANT1 (802.11b – Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 36 of 118




Plot 7-28. Power Spectral Density Plot SISO ANT1 (802.11g – Ch. 1)




Plot 7-29. Power Spectral Density Plot SISO ANT1 (802.11g – Ch. 6)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 37 of 118




Plot 7-30. Power Spectral Density Plot SISO ANT1 (802.11g – Ch. 11)




Plot 7-31. Power Spectral Density Plot SISO ANT1 (802.11n (2.4GHz) – Ch. 1)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 38 of 118




Plot 7-32. Power Spectral Density Plot SISO ANT1 (802.11n (2.4GHz) – Ch. 6)




Plot 7-33. Power Spectral Density Plot SISO ANT1 (802.11n (2.4GHz) – Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 39 of 118




Plot 7-34. Power Spectral Density Plot SISO ANT1 (802.11ax (2.4GHz) – Ch. 1)



Plot 7-35. Power Spectral Density Plot SISO ANT1 (802.11ax (2.4GHz) – Ch. 6)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 40 of 118



Plot 7-36. Power Spectral Density Plot SISO ANT1 (802.11ax (2.4GHz) – Ch. 11)


FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 41 of 118

SISO Antenna-2 Power Spectral Density Measurements


Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]	Pass / Fail
2412	1	b	1	-0.02	8.00	-8.02	Pass
2437	6	b	1	0.11	8.00	-7.89	Pass
2462	11	b	1	0.85	8.00	-7.15	Pass
2412	1	g	6	-2.06	8.00	-10.06	Pass
2437	6	g	6	-1.43	8.00	-9.43	Pass
2462	11	g	6	-1.79	8.00	-9.79	Pass
2412	1	n	6.5/7.2 (MCS0)	-0.58	8.00	-8.58	Pass
2437	6	n	6.5/7.2 (MCS0)	-1.08	8.00	-9.08	Pass
2462	11	n	6.5/7.2 (MCS0)	-0.93	8.00	-8.93	Pass
2412	1	ax	6.5/7.2 (MCS0)	-2.37	8.00	-10.37	Pass
2437	6	ax	6.5/7.2 (MCS0)	-1.73	8.00	-9.73	Pass
2462	11	ax	6.5/7.2 (MCS0)	-2.46	8.00	-10.46	Pass

Table 7-11. Conducted Power Density Measurements SISO ANT2

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 42 of 118



Plot 7-37. Power Spectral Density Plot SISO ANT2 (802.11b – Ch. 1)




Plot 7-38. Power Spectral Density Plot SISO ANT2 (802.11b – Ch. 6)

FCC ID: A3LSMS901JPN	 PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 43 of 118




Plot 7-39. Power Spectral Density Plot SISO ANT2 (802.11b – Ch. 11)




Plot 7-40. Power Spectral Density Plot SISO ANT2 (802.11g – Ch. 1)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 44 of 118




Plot 7-41. Power Spectral Density Plot SISO ANT2 (802.11g – Ch. 6)




Plot 7-42. Power Spectral Density Plot SISO ANT2 (802.11g – Ch. 11)

FCC ID: A3LSMS901JPN	Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 45 of 118




Plot 7-43. Power Spectral Density Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 1)




Plot 7-44. Power Spectral Density Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 6)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 46 of 118




Plot 7-45. Power Spectral Density Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 11)




Plot 7-46. Power Spectral Density Plot SISO ANT2 (802.11ax (2.4GHz) – Ch. 1)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 47 of 118



Plot 7-47. Power Spectral Density Plot SISO ANT2 (802.11ax (2.4GHz) – Ch. 6)



Plot 7-48. Power Spectral Density Plot SISO ANT2 (802.11ax (2.4GHz) – Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 48 of 118

MIMO Power Spectral Density Measurements

Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	ANT 1 Power Spectral Density [dBm]	ANT 2 Power Spectral Density [dBm]	Summed MIMO Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]	Pass / Fail
2412	1	b	1	0.22	0.15	3.20	8.00	-4.80	Pass
2437	6	b	1	4.79	1.94	6.61	8.00	-1.39	Pass
2462	11	b	1	1.95	0.12	4.14	8.00	-3.86	Pass
2412	1	g	6	-0.14	-0.84	2.53	8.00	-5.47	Pass
2437	6	g	6	-1.62	-1.78	1.31	8.00	-6.69	Pass
2462	11	g	6	-0.81	-0.74	2.24	8.00	-5.76	Pass
2412	1	n	6.5/7.2 (MCS0)	0.40	0.77	3.60	8.00	-4.40	Pass
2437	6	n	6.5/7.2 (MCS0)	-1.13	0.22	2.61	8.00	-5.39	Pass
2462	11	n	6.5/7.2 (MCS0)	-0.38	1.83	3.87	8.00	-4.13	Pass
2412	1	ax	6.5/7.2 (MCS0)	-1.00	-0.27	2.39	8.00	-5.61	Pass
2437	6	ax	6.5/7.2 (MCS0)	-2.05	-0.96	1.54	8.00	-6.46	Pass
2462	11	ax	6.5/7.2 (MCS0)	-1.42	-0.26	2.21	8.00	-5.79	Pass

Table 7-12. MIMO Conducted Power Density Measurements

Note:

Per ANSI C63.10-2013 Section 14.3.2.2 and KDB 662911 D01 v02r01 Section E)2), the power spectral density at Antenna 1 and Antenna 2 were first measured separately as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.


Sample MIMO Calculation:

At 2412MHz the average conducted power spectral density was measured to be -0.14 dBm for Antenna-1 and -0.84 dBm for Antenna-2.


$$\text{Antenna 1} + \text{Antenna 2} = \text{MIMO}$$

$$(-0.14 \text{ dBm} + -0.84 \text{ dBm}) = (0.97 \text{ mW} + 0.82 \text{ mW}) = 1.79 \text{ mW} = 2.53 \text{ dBm}$$

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 49 of 118




Plot 7-49. Power Spectral Density Plot MIMO ANT1 (802.11b (2.4GHz) – Ch. 1)




Plot 7-50. Power Spectral Density Plot MIMO ANT1 (802.11b (2.4GHz) – Ch. 6)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 50 of 118




Plot 7-51. Power Spectral Density Plot MIMO ANT1 (802.11b (2.4GHz) – Ch. 11)




Plot 7-52. Power Spectral Density Plot MIMO ANT1 (802.11g (2.4GHz) – Ch. 1)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 51 of 118




Plot 7-53. Power Spectral Density Plot MIMO ANT1 (802.11g) (2.4GHz) – Ch. 6)




Plot 7-54. Power Spectral Density Plot MIMO ANT1 (802.11g) (2.4GHz) – Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 52 of 118




Plot 7-55. Power Spectral Density Plot MIMO ANT1 (802.11n (2.4GHz) – Ch. 1)




Plot 7-56. Power Spectral Density Plot MIMO ANT1 (802.11n (2.4GHz) – Ch. 6)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 53 of 118




Plot 7-57. Power Spectral Density Plot MIMO ANT1 (802.11n (2.4GHz) – Ch. 11)




Plot 7-58. Power Spectral Density Plot MIMO ANT1 (802.11ax (2.4GHz) – Ch. 1)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 54 of 118




Plot 7-59. Power Spectral Density Plot MIMO ANT1 (802.11ax (2.4GHz) – Ch. 6)



Plot 7-60. Power Spectral Density Plot MIMO ANT1 (802.11ax (2.4GHz) – Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 55 of 118




Plot 7-61. Power Spectral Density Plot MIMO ANT2 (802.11b (2.4GHz) – Ch. 1)




Plot 7-62. Power Spectral Density Plot MIMO ANT2 (802.11b (2.4GHz) – Ch. 6)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 56 of 118




Plot 7-63. Power Spectral Density Plot MIMO ANT2 (802.11b (2.4GHz) – Ch. 11)




Plot 7-64. Power Spectral Density Plot MIMO ANT2 (802.11g (2.4GHz) – Ch. 1)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 57 of 118




Plot 7-65. Power Spectral Density Plot MIMO ANT2 (802.11g) (2.4GHz) – Ch. 6)




Plot 7-66. Power Spectral Density Plot MIMO ANT2 (802.11g) (2.4GHz) – Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 58 of 118




Plot 7-67. Power Spectral Density Plot MIMO ANT2 (802.11n (2.4GHz) – Ch. 1)




Plot 7-68. Power Spectral Density Plot MIMO ANT2 (802.11n (2.4GHz) – Ch. 6)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 59 of 118




Plot 7-69. Power Spectral Density Plot MIMO ANT2 (802.11n (2.4GHz) – Ch. 11)




Plot 7-70. Power Spectral Density Plot MIMO ANT2 (802.11ax (2.4GHz) – Ch. 1)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 60 of 118



Plot 7-71. Power Spectral Density Plot MIMO ANT2 (802.11ax (2.4GHz) – Ch. 6)



Plot 7-72. Power Spectral Density Plot MIMO ANT2 (802.11ax (2.4GHz) – Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 61 of 118

7.5 Conducted Emissions at the Band Edge

§15.247(d); RSS-247 [5.5]

Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. For the following out of band conducted spurious emissions plots at the band edge, the EUT was set at a data rate of 1Mbps for “b” mode, 6 Mbps for “g” mode, 6.5/7.2Mbps for “n” mode, and 8.6Mbps for “ax” mode as these settings produced the worst-case emissions.

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure (Section 7.4).

Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3
KDB 558074 D01 v05r02 – Section 8.7.2

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 1MHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 62 of 118

SISO Antenna-1 Conducted Emissions at the Band Edge




Plot 7-73. Band Edge Plot SISO ANT1 (802.11b – Ch. 1)




Plot 7-74. Band Edge Plot SISO ANT1 (802.11b – Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 63 of 118




Plot 7-75. Band Edge Plot SISO ANT1 (802.11b – Ch. 12)




Plot 7-76. Band Edge Plot SISO ANT1 (802.11b – Ch. 13)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 64 of 118




Plot 7-77. Band Edge Plot SISO ANT1 (802.11g- Ch. 1)




Plot 7-78. Band Edge Plot SISO ANT1 (802.11g - Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 - 12/22/2021	EUT Type: Portable Handset		Page 65 of 118




Plot 7-79. Band Edge Plot SISO ANT1 (802.11g – Ch. 12)




Plot 7-80. Band Edge Plot SISO ANT1 (802.11g – Ch. 13)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 66 of 118




Plot 7-81. Band Edge Plot SISO ANT1 (802.11n (2.4GHz) – Ch. 1)




Plot 7-82. Band Edge Plot SISO ANT1 (802.11n (2.4GHz) – Ch. 10)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 67 of 118




Plot 7-83. Band Edge Plot SISO ANT1 (802.11n (2.4GHz) – Ch. 11)




Plot 7-84. Band Edge Plot SISO ANT1 (802.11n (2.4GHz) – Ch. 12)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 68 of 118



Plot 7-85. Band Edge Plot SISO ANT1 (802.11n (2.4GHz) – Ch. 13)




Plot 7-86. Band Edge Plot SISO ANT1 (802.11ax (2.4GHz) – Ch. 1)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 69 of 118




Plot 7-87. Band Edge Plot SISO ANT1 (802.11ax (2.4GHz) – Ch. 10)




Plot 7-88. Band Edge Plot SISO ANT1 (802.11ax (2.4GHz) – Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 70 of 118




Plot 7-89. Band Edge Plot SISO ANT1 (802.11ax (2.4GHz) – Ch. 12)




Plot 7-90. Band Edge Plot SISO ANT1 (802.11ax (2.4GHz) – Ch. 13)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 71 of 118

SISO Antenna-2 Conducted Emissions at the Band Edge




Plot 7-91. Band Edge Plot SISO ANT2 (802.11b – Ch. 1)




Plot 7-92. Band Edge Plot SISO ANT2 (802.11b – Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 72 of 118




Plot 7-93. Band Edge Plot SISO ANT2 (802.11b – Ch. 12)




Plot 7-94. Band Edge Plot SISO ANT2 (802.11b – Ch. 13)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 73 of 118




Plot 7-95. Band Edge Plot SISO ANT2 (802.11g- Ch. 1)




Plot 7-96. Band Edge Plot SISO ANT2 (802.11g - Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 - 12/22/2021	EUT Type: Portable Handset		Page 74 of 118




Plot 7-97. Band Edge Plot SISO ANT2 (802.11g – Ch. 12)




Plot 7-98. Band Edge Plot SISO ANT2 (802.11g – Ch. 13)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 75 of 118





Plot 7-99. Band Edge Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 1)




Plot 7-100. Band Edge Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 10)


FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 76 of 118



FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 77 of 118



Plot 7-103. Band Edge Plot SISO ANT2 (802.11n (2.4GHz) – Ch. 13)




Plot 7-104. Band Edge Plot SISO ANT2 (802.11ax (2.4GHz) – Ch. 1)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 78 of 118




Plot 7-105. Band Edge Plot SISO ANT2 (802.11ax (2.4GHz) – Ch. 10)




Plot 7-106. Band Edge Plot SISO ANT2 (802.11ax (2.4GHz) – Ch. 11)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 79 of 118



Plot 7-107. Band Edge Plot SISO ANT2 (802.11ax (2.4GHz) – Ch. 12)



Plot 7-108. Band Edge Plot SISO ANT2 (802.11ax (2.4GHz) – Ch. 13)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 80 of 118

7.6 Conducted Spurious Emissions

§15.247(d); RSS-247 [5.5]

Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. For the following out of band conducted spurious emissions plots at the band edge, the EUT was set at a data rate of 1 Mbps for “b” mode, 6Mbps for “g” mode, 6.5/7.2Mbps for “n” mode, and 8.6Mbps for “ax” mode as these settings produce the worst-case emissions.

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 11.1 of ANSI C63.10-2013 and KDB 558074 D01 v05r02.

Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3
KDB 558074 D01 v05r02 – Section 8.5
ANSI C63.10-2013 – Section 14.3.3
KDB 662911 D01 v02r01 – Section E)3)b)

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-5. Test Instrument & Measurement Setup


FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 81 of 118

Test Notes


1. RBW was set to 1MHz rather than 100kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at N/AdB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be N/AdB below the level of the fundamental in a 1MHz bandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.
4. The conducted spurious emissions were measured to relative limits. Therefore, in accordance with ANSI C63.10-2013 and KDB 662911 D01 v02r01 Section E)3)b), it was unnecessary to show compliance through the summation of test results of the individual outputs.

FCC ID: A3LSMS901JPN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 82 of 118

SISO Antenna-1 Conducted Spurious Emission



Plot 7-109. Conducted Spurious Plot SISO ANT1 (802.11b – Ch. 1)



Plot 7-110. Conducted Spurious Plot SISO ANT1 (802.11b – Ch. 1)

FCC ID: A3LSMS901JPN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2112090153-09.A3L	Test Dates: 9/22 – 12/22/2021	EUT Type: Portable Handset		Page 83 of 118