

## APPENDIX G: POWER REDUCTION VERIFICATION

Per the May 2017 TCBC Workshop Notes, demonstration of proper functioning of the power reduction mechanisms is required to support the corresponding SAR configurations. The verification process was divided into two parts: (1) evaluation of output power levels for individual or multiple triggering mechanisms and (2) evaluation of the triggering distances for proximity-based sensors.

### G.1 Power Verification Procedure




The power verification was performed according to the following procedure:

1. A base station simulator was used to establish a conducted RF connection and the output power was monitored. The power measurements were confirmed to be within expected tolerances for all states before and after a power reduction mechanism was triggered.
2. Step 1 was repeated for all relevant modes and frequency bands for the mechanism being investigated.
3. Steps 1 and 2 were repeated for all individual power reduction mechanisms and combinations thereof. For the combination cases, one mechanism was switched to a 'triggered' state at a time; powers were confirmed to be within tolerances after each additional mechanism was activated.

### G.2 Distance Verification Procedure

The distance verification procedure was performed according to the following procedure:

1. A base station simulator was used to establish an RF connection and to monitor the power levels. The device being tested was placed below the relevant section of the phantom with the relevant side or edge of the device facing toward the phantom.
2. The device was moved toward and away from the phantom to determine the distance at which the mechanism triggers and the output power is reduced, per KDB Publication 616217 D04v01r02 and FCC Guidance. Each applicable test position was evaluated. The distances were confirmed to be the same or larger (more conservative) than the minimum distances provided by the manufacturer.
3. Steps 1 and 2 were repeated for low, mid, and high bands, as appropriate (see note below Table G-2 for more details).
4. Steps 1 through 3 were repeated for all distance-based power reduction mechanisms.

FCC ID A3LSMS901JPN	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 12/20/21 - 02/02/22	DUT Type: Portable Handset			APPENDIX G: Page 1 of 4

### G.3 Main Antenna Verification Summary



**Table G-1  
Power Measurement Verification for Main Antenna**

Mechanism(s)		Mode/Band	Device State Index (DSI)		
1st	2nd		Un-triggered (Max)	Mechanism #1 (Reduced)	Mechanism #2 (Reduced)
Hotspot On		GPRS 1900 1 Tx Slot	0	3	
Grip		GPRS 1900 1 Tx Slot	0	1	
Hotspot On	Grip	GPRS 1900 1 Tx Slot	0	3	3
Grip	Hotspot On	GPRS 1900 1 Tx Slot	0	1	3
Hotspot On		LTE Band 4	0	3	
Grip		LTE Band 4	0	1	
Hotspot On	Grip	LTE Band 4	0	3	3
Grip	Hotspot On	LTE Band 4	0	1	3
Hotspot On		LTE Band 41	0	3	
Grip		LTE Band 41	0	1	
Hotspot On	Grip	LTE Band 41	0	3	3
Grip	Hotspot On	LTE Band 41	0	1	3

**Table G-2  
Distance Measurement Verification for Main Antenna**

Mechanism(s)	Test Condition	Band	Distance Measurements (mm)		Minimum Distance per Manufacturer (mm)
			Moving Toward	Moving Away	
Grip	Body - Back Side	Mid	10	13	9
Grip	Body - Back Side	High	10	13	9
Grip	Body - Front Side	Mid	8	11	7
Grip	Body - Front Side	High	8	11	7
Grip	Body - Bottom Edge	Mid	12	15	12
Grip	Body - Bottom Edge	High	12	15	12

\*Note: Mid band refers to: GSM1900, LTE B4; High band refers to: LTE B41

FCC ID A3LSMS901JPN	 PCTEST <small>Provided to be part of Samsung</small>	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 12/20/21 - 02/02/22	DUT Type: Portable Handset			APPENDIX G: Page 2 of 4

## G.4 WIFI Verification Summary

**Table G-3  
Power Measurement Verification WIFI Ant 1**



Mechanism(s)	Mode/Band	Conducted Power (dBm)	
		Un-triggered (Max)	Mechanism #1 (Reduced)
1st			
Held-to-Ear	802.11b	16.17	14.33
Held-to-Ear	802.11g	16.56	14.22
Held-to-Ear	802.11n (2.4GHz)	17.03	14.35
Held-to-Ear	802.11a	17.12	10.24
Held-to-Ear	802.11n (5GHz, 20MHz BW)	17.21	10.45
Held-to-Ear	802.11ac (20MHz BW)	17.36	10.50
Held-to-Ear	802.11n (5GHz, 40MHz BW)	17.20	10.47
Held-to-Ear	802.11ac (40MHz BW)	17.11	10.00
Held-to-Ear	802.11ac (80MHz BW)	17.04	10.00

\*Note: MIMO and 802.11ax WIFI modes were not evaluated due to equipment limitations.

**Table G-4  
Power Measurement Verification WIFI Ant 2**

Mechanism(s)	Mode/Band	Conducted Power (dBm)	
		Un-triggered (Max)	Mechanism #1 (Reduced)
1st			
Held-to-Ear	802.11b	15.92	14.04
Held-to-Ear	802.11g	16.03	13.80
Held-to-Ear	802.11n (2.4GHz)	16.34	13.71
Held-to-Ear	802.11a	17.99	10.59
Held-to-Ear	802.11n (5GHz, 20MHz BW)	17.72	10.21
Held-to-Ear	802.11ac (20MHz BW)	17.97	10.32
Held-to-Ear	802.11n (5GHz, 40MHz BW)	17.52	10.40
Held-to-Ear	802.11ac (40MHz BW)	17.82	9.65
Held-to-Ear	802.11ac (80MHz BW)	16.36	9.34



\*Note: MIMO and 802.11ax WIFI modes were not evaluated due to equipment limitations.

FCC ID A3LSMS901JPN	 PCTEST <small>Providing the best part of the solution</small>	SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 12/20/21 - 02/02/22	DUT Type: Portable Handset			APPENDIX G: Page 3 of 4

## G.5 Bluetooth Verification Summary

**Table G-5  
Power Measurement Verification Bluetooth**

Mode/Band	Conducted Power (dBm)			
	Un-triggered (Max)	Mechanism #1 RCV Active (Reduced)	Mechanism #2 5 GHz WLAN Active (Reduced)	Mechanism #3 RCV & 5 GHz WLAN Active (Reduced)
Bluetooth	15.10	11.80	12.00	12.00

FCC ID A3LSMS901JPN		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 12/20/21 - 02/02/22	DUT Type: Portable Handset		APPENDIX G: Page 4 of 4	