



CERTIFICATION TEST REPORT

Report Number. : 4790089631-E8V1

Applicant : SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Model : SM-S908B/DS

FCC ID : A3LSMS908B

EUT Description : GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax,
NFC, WPT and UWB

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C

Date Of Issue:

2021-10-29

Prepared by:

UL Korea, Ltd.

26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL Korea, Ltd. Suwon Laboratory

218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea

TEL: (031) 337-9902

FAX: (031) 213-5433



ACCREDITED

Testing Laboratory

TL-637

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	2021-10-29	Initial issue	Hyunsik Yun

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	6
4.1. <i>MEASURING INSTRUMENT CALIBRATION.....</i>	6
4.2. <i>SAMPLE CALCULATION.....</i>	6
4.3. <i>MEASUREMENT UNCERTAINTY</i>	6
4.4. <i>DECISION RULE</i>	6
5. EQUIPMENT UNDER TEST.....	7
5.1. <i>DESCRIPTION OF EUT.....</i>	7
5.2. <i>MAXIMUM E-FIELD STRENGTH.....</i>	7
5.3. <i>WORST-CASE CONFIGURATION AND MODE</i>	7
5.4. <i>DESCRIPTION OF TEST SETUP</i>	8
6. TEST AND MEASUREMENT EQUIPMENT	9
7. 20dB BANDWIDTH	10
8. RADIATED EMISSION TEST RESULTS.....	11
8.1. <i>LIMITS AND PROCEDURE</i>	11
8.1.1. <i>FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 – 30 MHz)</i>	13
8.1.2. <i>SPURIOUS EMISSION 0.009 TO 30 MHz.....</i>	14
8.1.3. <i>TX SPURIOUS EMISSION 30 TO 1000 MHz</i>	15
8.1.4. <i>FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 – 30 MHz) [EUT with passive TAG mode]</i>	16
8.1.5. <i>SPURIOUS EMISSION 0.09 TO 30 MHz [EUT with passive TAG mode].....</i>	17
8.1.6. <i>TX SPURIOUS EMISSION 30 TO 1000 MHz [EUT with passive TAG mode]</i>	18
9. AC MAINS LINE CONDUCTED EMISSIONS.....	19
10. FREQUENCY STABILITY	22

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax, NFC, WPT and UWB
MODEL NUMBER: SM-S908B/DS
SERIAL NUMBER: R3CR80AB9PK (RADIATED);
DATE TESTED: 2021-09-28 ~ 2021-10-29

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Complies

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Dexter(Hyunsik) Yun
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. ANSI C63.10-2013.
4. 414788 D01 Radiated Test Site v01r01

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
<input checked="" type="checkbox"/>	Chamber 1
<input checked="" type="checkbox"/>	Chamber 2
<input type="checkbox"/>	Chamber 3

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <https://www.iasonline.org/wp-content/uploads/2017/05/TL-637-cert-New.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.02 dB
Radiated Disturbance, 9 kHz to 30 MHz	1.72 dB
Radiated Disturbance, 30 MHz to 1 GHz	4.05 dB

Uncertainty figures are valid to a confidence level of 95%.

4.4. DECISION RULE

Decision rule for statement(s) of conformity is based on Procedure 2, Clause 4.4.3 in IEC Guide 115:2007.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax, NFC, WPT and UWB. This test report addresses the DXX (NFC) operational mode.

5.2. MAXIMUM E-FIELD STRENGTH

The testing was performed at 3 meter. The transmitter maximum E-field at 30m distance is 22.28 dBuV/m which convert from 3 meter data.

5.3. WORST-CASE CONFIGURATION AND MODE

The NFC function was tested at its' fundamental and only operational frequency of 13.56 MHz.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that the Z orientation was the worst-case orientation; therefore all final radiated testing was performed with the EUT in the Z orientation while generating continuous emissions.

The fundamental level of the EUT was investigated each type and bitrate.
All test was performed worst case condition(type A and bit rate 106 kbps).

Radiated(fundamental level and spurious emissions) tests were performed both without reading a passive tag condition[test mode] and with reading a passive tag condition.

5.4. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA800	R37N9BV0382HM3	N/A
Data Cable	SAMSUNG	EP-DN980BBE	N/A	N/A


I/O CABLE

I/O Cable List						
Cable No.	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	C Type	Shielded	1.0 m	N/A

The EUT is a stand-alone device configured and tested in a worst-case setup.

Note: Worst case is using worst case orientation with AC charger attached to the EUT with NFC signal continuously transmitting.

SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	845	2022-08-13
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	2022-08-13
Preamplifier, 1000 MHz	Sonoma	310N	341282	2022-08-02
Preamplifier, 1000 MHz	Sonoma	310N	351741	2022-08-02
Spectrum Analyzer, 7 GHz	Agilent / HP	N9010A	MY542200580	2022-08-02
EMI Test Receive, 3 GHz	R&S	ESR3	101832	2022-08-02
DC Power Supply	Agilent / HP	E3640A	MY54226395	2022-08-02
Temperature Chamber	ESPEC	SH-642	93001109	2022-08-02
LISN	R&S	ENV216	101837	2022-08-05
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	2023-10-06
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	

7. 20dB BANDWIDTH

LIMITS

§15.215

(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated

§15.225

Operation within the band 13.110 – 14.010MHz

TEST PROCEDURE

The spectrum analyzer connected receive antenna and the EUT placed on near the receive antenna. The RBW is set to 10kHz. The VBW is set to 3 times the RBW. The sweep time is coupled.

RESULTS

Frequency [MHz]	20 dB Bandwidth [kHz]
13.56	438.35

20dB Bandwidth Plot



8. RADIATED EMISSION TEST RESULTS

8.1. LIMITS AND PROCEDURE

LIMIT

§15.225

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/ meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110– 14.010 MHz and shall not exceed the general radiated emission limits in § 15.209 as follows:

§15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

Formula for converting the filed strength from uV/m to dBuV/m is:

Limit (dBuV/m) = 20 log limit (uV/m)

In addition:

§15.209 (d) The emission limits shown the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

§15.209 (d) The provisions in §§ 15.225, measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

TEST PROCEDURE

ANSI C63.10-2013


The EUT is an intentional radiator that incorporates a digital device. The highest fundamental frequency generated or used in the device is 13.56 MHz. The frequency range was investigated from 0.15 MHz to the 10th harmonic of the highest fundamental frequency, or 1000 MHz, whichever is greater (1000MHz)

RESULTS

No non-compliance noted:

8.1.1. FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 – 30 MHz)

[EUT without passive TAG mode]



Trace Markers

[Face On]

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	HFH2-Z2_Loop Antenna	Dist Corr 30m	Cable Loss	Corrected Reading dB(uVolts/meter)	FCC 15.225 Limit	Margin (dB)	Azimuth (Degs)
1	12.88413	21.09	Pk	20	-40	.5	1.59	29.54	-27.95	0-360
2	13.34713	25.41	Pk	20	-40	.5	5.91	40.51	-34.6	0-360
3	13.46013	28.39	Pk	20	-40	.5	8.89	50.5	-41.61	0-360
**4	13.5685	34.71	Pk	20	-40	.5	15.21	50.5	-35.29	0-360
5	13.66725	27.52	Pk	20	-40	.6	8.12	50.5	-42.38	0-360
6	13.7715	25.61	Pk	20	-40	.6	6.21	40.51	-34.3	0-360
7	14.22113	20.62	Pk	20	-40	.6	1.22	29.54	-28.32	0-360

[Face Off]

8	13.09375	19.19	Pk	20	-40	.5	-.31	29.54	-29.85	0-360
9	13.35475	21.57	Pk	20	-40	.5	2.07	40.51	-38.44	0-360
10	13.464	23.74	Pk	20	-40	.5	4.24	50.5	-46.26	0-360
**11	13.55925	36.25	Pk	20	-40	.5	16.75	84	-67.25	0-360
12	13.66163	23.06	Pk	20	-40	.6	3.66	50.5	-46.84	0-360
13	13.83613	19.85	Pk	20	-40	.6	.45	40.51	-40.06	0-360
14	14.15638	19.38	Pk	20	-40	.6	-.02	29.54	-29.56	0-360

Pk - Peak detector

**Fundamental


Note 1 : Although these tests were performed other than open filed test site, adequate comparison measurements were confirmed against 30 m open are test site.

Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Note 2: Radiated test were investigated with three receiving antenna axes: Face-on, Face-off and horizontal (parallel to the ground plane) and the worse orientations of Face-on and Face-off were set for final test.

8.1.2. SPURIOUS EMISSION 0.009 TO 30 MHz

[EUT without passive TAG mode]



Trace Markers

Face on

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	HFH2-Z2_Loop Antenna	Cable Loss	Dist Corr 30m	Corrected Reading dBuV/m	QP Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
1	.54628	27.36	Pk	19.7	.1	-40	7.16	32.86	-25.7	0-360
2	.70892	31.68	Pk	19.7	.1	-40	11.48	30.6	-19.12	0-360
3	.87942	26.17	Pk	19.8	.2	-40	6.17	28.73	-22.56	0-360
4	1.12711	29.15	Pk	19.8	.2	-40	9.15	26.59	-17.44	0-360
5	2.84543	31.52	Pk	19.9	.3	-40	11.72	29.5	-17.78	0-360
6	4.7587	32.15	Pk	19.8	.3	-40	12.25	29.5	-17.25	0-360
**7	13.56165	39.7	Pk	20	.5	-40	20.2	29.5	-9.3	0-360

Face off

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	HFH2-Z2_Loop Antenna	Cable Loss	Dist Corr 30m	Corrected Reading dBuV/m	QP Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
8	.50417	32.71	Pk	19.7	.1	-40	12.51	33.55	-21.04	0-360
9	.7134	29.25	Pk	19.7	.1	-40	9.05	30.55	-21.5	0-360
10	.91469	25.18	Pk	19.8	.2	-40	5.18	28.39	-23.21	0-360
11	1.13858	29.1	Pk	19.8	.2	-40	9.1	26.5	-17.4	0-360
12	2.84543	30.93	Pk	19.9	.3	-40	11.13	29.5	-18.37	0-360
13	4.3817	32.1	Pk	19.8	.3	-40	12.2	29.5	-17.3	0-360
**14	13.56165	35.54	Pk	20	.5	-40	16.04	29.5	-13.46	0-360

Pk - Peak detector

**Fundamental

Note 1: The data for marker number 7 and 14 are the fundamental signal.


Please refer to section 8.1.1 about the fundamental level.

Frequency range 0.009MHz ~ 0.490MHz, only noise floor level and more than 20dB margin.


Note 2: Radiated test were investigated with three receiving antenna axes: Face-on, Face-off and horizontal (parallel to the ground plane) and the worse orientations of Face-on and Face-off were set for final test.

8.1.3. TX SPURIOUS EMISSION 30 TO 1000 MHz [EUT without passive TAG mode]

HORIZONTAL



VERTICAL




Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163_749	Below 1G[dB]	Corrected Reading (dBuV/m)	QPK Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	48.624	30.72	Pk	19.9	-31.7	18.92	40	-21.08	0-360	100	H
2	* 108.279	30.3	Pk	17.3	-31.3	16.3	43.52	-27.22	0-360	200	H
3	* 330.506	30.9	Pk	19.9	-30.2	20.6	46.02	-25.42	0-360	100	H
4	43.968	39.1	Pk	19.5	-31.8	26.8	40	-13.2	0-360	100	V
5	105.854	30.25	Pk	17.5	-31.3	16.45	43.52	-27.07	0-360	100	V
6	* 330.603	29.26	Pk	19.9	-30.2	18.96	46.02	-27.06	0-360	300	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
 Pk - Peak detector

8.1.4. FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 – 30 MHz) [EUT with passive TAG mode]



Trace Markers [Face On]

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	HFH2-Z2_Loop Antenna	Dist Corr 30m	Cable Loss	Corrected Reading dB(uVolts/meter)	FCC 15.225 Limit	Margin (dB)	Azimuth (Degs)
1	12.95838	20.27	Pk	20	-40	.5	.77	29.54	-28.77	0-360
2	13.35063	22.61	Pk	20	-40	.5	3.11	40.51	-37.4	0-360
3	13.46313	21.99	Pk	20	-40	.5	2.49	50.5	-48.01	0-360
**4	13.5615	41.78	Pk	20	-40	.5	22.28	84	-61.72	0-360
5	13.629	21.66	Pk	20	-40	.6	2.26	50.5	-48.24	0-360
6	13.85563	19.01	Pk	20	-40	.6	-.39	40.51	-40.9	0-360
7	14.14325	18.86	Pk	20	-40	.6	-.54	29.54	-30.08	0-360

[Face Off]

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	HFH2-Z2_Loop Antenna	Dist Corr 30m	Cable Loss	Corrected Reading dB(uVolts/meter)	FCC 15.225 Limit	Margin (dB)	Azimuth (Degs)
8	12.57688	21.1	Pk	20	-40	.5	1.6	29.54	-27.94	0-360
9	13.38288	19.98	Pk	20	-40	.5	.48	40.51	-40.03	0-360
10	13.45388	19.38	Pk	20	-40	.5	-.12	50.5	-50.62	0-360
**11	13.56063	37.17	Pk	20	-40	.5	17.67	84	-66.33	0-360
12	13.6045	18.94	Pk	20	-40	.6	-.46	50.5	-50.96	0-360
13	13.82338	19.01	Pk	20	-40	.6	-.39	40.51	-40.9	0-360
14	14.3175	19.69	Pk	20	-40	.6	.29	29.54	-29.25	0-360

Pk - Peak detector


**Fundamental

Note 1: Although these tests were performed other than open filed test site, adequate comparison measurements were confirmed against 30 m open are test site.

Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Note 2: Radiated test were investigated with three receiving antenna axes: Face-on, Face-off and horizontal (parallel to the ground plane) and the worse orientations of Face-on and Face-off were set for final test.

8.1.5. SPURIOUS EMISSION 0.09 TO 30 MHz [EUT with passive TAG mode]



Trace Markers

Face on

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	HFH2-Z2_Loop Antenna	Cable Loss	Dist Corr 30m	Corrected Reading dBuV/m	QP Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
1	.7074	30.15	Pk	19.7	.1	-40	9.95	30.62	-20.67	0-360
2	.81517	27.19	Pk	19.8	.2	-40	7.19	29.39	-22.2	0-360
3	1.10336	29.87	Pk	19.8	.2	-40	9.87	26.77	-16.9	0-360
4	2.88313	31.96	Pk	19.9	.3	-40	12.16	29.5	-17.34	0-360
5	4.66445	30.45	Pk	19.8	.3	-40	10.55	29.5	-18.95	0-360
6	7.80298	28.75	Pk	19.9	.4	-40	9.05	29.5	-20.45	0-360
**7	13.56165	41	Pk	20	.5	-40	21.5	29.5	-10.53	0-360

Face off

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	HFH2-Z2_Loop Antenna	Cable Loss	Dist Corr 30m	Corrected Reading dBuV/m	QP Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
8	.70611	30.32	Pk	19.7	.1	-40	10.12	30.64	-20.52	0-360
9	.81076	27.6	Pk	19.8	.2	-40	7.6	29.44	-21.84	0-360
10	1.0793	30.78	Pk	19.8	.2	-40	10.78	26.96	-16.18	0-360
11	2.92083	31.39	Pk	19.9	.3	-40	11.59	29.5	-17.91	0-360
12	4.2686	31.61	Pk	19.8	.3	-40	11.71	29.5	-17.79	0-360
13	7.65218	28.68	Pk	19.9	.4	-40	8.98	29.5	-20.52	0-360
**14	13.56165	36.65	Pk	20	.5	-40	17.15	29.5	-12.35	0-360

Pk - Peak detector

**Fundamental

Note 1: The data for marker number 7 and 14 are the fundamental signal.


Please refer to section 8.1.4 about the fundamental level.

Frequency range 0.009MHz ~ 0.490MHz, only noise floor level and more than 20dB margin.


Note 2: Radiated test were investigated with three receiving antenna axes: Face-on, Face-off and horizontal (parallel to the ground plane) and the worse orientations of Face-on and Face-off were set for final test.

8.1.6. TX SPURIOUS EMISSION 30 TO 1000 MHz [EUT with passive TAG mode]

HORIZONTAL



VERTICAL



Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163_749	Below 1G[dB]	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	40.67	41.31	Pk	18.8	-31.8	28.31	40	-11.69	0-360	300	H
2	94.893	43.11	Pk	16.5	-31.3	28.31	43.52	-15.21	0-360	200	H
3	176.276	37.24	Pk	14.9	-30.9	21.24	43.52	-22.28	0-360	100	H
4	40.67	48.46	Pk	18.8	-31.8	35.46	40	-4.54	0-360	100	V
5	67.733	39.4	Pk	16.2	-31.6	24	40	-16	0-360	100	V
6	94.893	42	Pk	16.5	-31.3	27.2	43.52	-16.32	0-360	100	V

Pk - Peak detector

Radiated Emissions

Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163_749	Below 1G[dB]	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
40.67	48.24	Qp	18.8	-31.8	35.24	40	-4.76	79	100	V

Qp - Quasi-Peak detector

9. AC MAINS LINE CONDUCTED EMISSIONS

LIMITS

§15.207

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Notes:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.

The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.


Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

No non-compliance noted:

WORST EMISSIONS

LINE 1 PLOT




LINE 1 RESULTS

Range 1: Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_Wit h EX_L1[dB]	CABLELOS S(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
1	.423	34.18	Pk	9.8	.2	44.18	57.39	-13.21	-	-
2	.411	19.17	Av	9.8	.2	29.17	-	-	47.63	-18.46
3	1.02	34.61	Pk	9.7	.3	44.61	56	-11.39	-	-
4	1.074	19.69	Av	9.7	.3	29.69	-	-	46	-16.31
5	1.374	35.79	Pk	9.7	.3	45.79	56	-10.21	-	-
6	1.314	19.87	Av	9.7	.3	29.87	-	-	46	-16.13
7	4.059	35.12	Pk	9.7	.3	45.12	56	-10.88	-	-
8	4.056	21.74	Av	9.7	.3	31.74	-	-	46	-14.26
9	12.729	38.86	Pk	9.9	.3	49.06	60	-10.94	-	-
10	12.75	25.23	Av	9.9	.3	35.43	-	-	50	-14.57
11	14.667	38.67	Pk	10	.4	49.07	60	-10.93	-	-
12	14.667	25.45	Av	10	.4	35.85	-	-	50	-14.15

Pk - Peak detector
 Av - Average detection

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Range 2: Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_Wit h EX_N[dB]	CABLELOS S(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
13	.288	32.69	Pk	9.7	.2	42.59	60.58	-17.99	-	-
14	.234	20.92	Av	9.7	.2	30.82	-	-	52.31	-21.49
15	2.364	31.51	Pk	9.7	.3	41.51	56	-14.49	-	-
16	2.292	15.14	Av	9.7	.3	25.14	-	-	46	-20.86
17	2.946	31.97	Pk	9.7	.3	41.97	56	-14.03	-	-
18	2.919	18.84	Av	9.7	.3	28.84	-	-	46	-17.16
19	5.73	33.43	Pk	9.7	.3	43.43	60	-16.57	-	-
20	5.727	22.82	Av	9.7	.3	32.82	-	-	50	-17.18
21	7.824	35.02	Pk	9.8	.3	45.12	60	-14.88	-	-
22	7.893	22.27	Av	9.8	.3	32.37	-	-	50	-17.63
23	14.646	36.36	Pk	10.1	.4	46.86	60	-13.14	-	-
24	14.658	25.75	Av	10.1	.4	36.25	-	-	50	-13.75

Pk - Peak detector

10. FREQUENCY STABILITY

LIMIT

§15.225 (e) The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency, over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

TEST PROCEDURE

ANSI C63.10 §6.8

RESULTS

Reference Frequency: EUT Channel 13.56 MHz @ 20°C Limit: ± 100 ppm = 1.356 kHz										
Power Supply (Vdc)	Envir. Temp (°C)	Frequency Deviation Measured with Time Elapse								
		Start up (MHz)	Delta (ppm)	@ 2mins (MHz)	Delta (ppm)	@ 5mins (MHz)	Delta (ppm)	@ 10 mins (MHz)	Delta (ppm)	Limit (ppm)
3.88	50	13.559968299	6.541	13.559963171	6.919	13.559958618	7.255	13.559956052	7.444	100
3.88	40	13.559991997	4.793	13.559984930	5.315	13.559976265	5.954	13.559973114	6.186	100
3.88	30	13.559995363	4.545	13.559995310	4.549	13.559994812	4.586	13.559995043	4.569	100
3.88	20	13.560056996	0	13.560047558	0.696	13.560038106	1.393	13.560032874	1.779	100
3.88	10	13.560069144	-0.896	13.560066056	-0.668	13.560063921	-0.511	13.560061592	-0.339	100
3.88	0	13.560085686	-2.116	13.560084648	-2.039	13.560083239	-1.935	13.560081623	-1.816	100
3.88	-10	13.560069813	-0.945	13.560077881	-1.540	13.560082009	-1.845	13.560083509	-1.955	100
3.88	-20	13.560016628	2.977	13.560037787	1.417	13.560051626	0.396	13.560059993	-0.221	100
3.88	-30	13.560048242	0.646	13.560032080	1.837	13.560020293	2.707	13.560007227	3.670	100

Reference Frequency: EUT Channel 13.56 MHz @ 20°C Limit: ± 100 ppm = 1.356 kHz										
Power Supply (Vdc)	Envir. Temp (°C)	Frequency Deviation Measured with Time Elapse								
		Start up (MHz)	Delta (ppm)	@ 2mins (MHz)	Delta (ppm)	@ 5mins (MHz)	Delta (ppm)	@ 10 mins (MHz)	Delta (ppm)	Limit (ppm)
3.88	20	13.560056996	0	13.560047558	0.696	13.560038106	1.393	13.560032874	1.779	100
4.42	20	13.560056491	0.037	13.560047162	0.725	13.560038004	1.401	13.560032762	1.787	100
3.65	20	13.560056085	0.067	13.560046733	0.757	13.560037948	1.405	13.560032693	1.792	100

No non-compliance noted.

END OF TEST REPORT