

Appendix H SPLSR criteria plots

Figure (1)




Figure (1-a)




Figure (2)




Figure (2-a)




Figure (3)




Figure (3-a)




Figure (4)




Figure (4-a)




Figure (5)




Figure (5-a)




Figure (6)




Figure (6-a)




Figure (7)




Figure (7-a)




Figure (8)




Figure (9)




Figure (10)




Figure (10-a)




Figure (11)




Figure (11-a)




Figure (12)




Figure (12-a)




Figure (13)




Figure (13-a)




Figure (14)




Figure (14-a)




Figure (15)




Figure (15-a)





Figure (16)




Mode		SAR	X	Y	Z	d: Calculated distance (mm)	
		W/kg	m	m	m		
LTE B5	1	0.341	-0.0259	-0.0705	0.0000	1 + 2	24.7
NR Bn66	2	0.627	-0.0055	-0.0845	0.0000	1 + 3	149.4
UNII MIMO + BT Ant.1	3	1.110	0.0220	0.0710	0.0000	2 + 3	157.9

The Peak Location Separation Distance is computed by using the formula below:

$$\text{SQRT}((X1-X2)^2+(Y1-Y2)^2+(Z1-Z2)^2)$$

Figure (17)



Mode		SAR	X	Y	Z	d: Calculated distance (mm)	
		W/kg	m	m	m		
LTE B5	1	0.341	-0.0259	-0.0705	0.0000	1 + 2	24.7
NR Bn66	2	0.627	-0.0055	-0.0845	0.0000	1 + 3	149.4
UNII MIMO + BT Ant.2	3	1.120	0.0220	0.0710	0.0000	2 + 3	157.9

The Peak Location Separation Distance is computed by using the formula below:

$$\text{SQRT}((X1-X2)^2+(Y1-Y2)^2+(Z1-Z2)^2)$$

Figure (18)




Figure (19)




Figure (20)




Figure (21)




Figure (22)




Figure (23)






Figure (24)



Mode	SAR W/kg	X m	Y m	Z m	d: Calculated distance (mm)		
LTE B5	1	0.68	-0.0259	-0.0705	0.0000	1 + 2	24.7
NR Bn66	2	0.341	-0.0055	-0.0845	0.0000	1 + 3	147.7
UNII MIMO + DTS MIMO	3	1.300	0.0208	0.0696	0.0000	2 + 3	156.3

The Peak Location Separation Distance is computed by using the formula below:
 $SQRT((X1-X2)^2+(Y1-Y2)^2+(Z1-Z2)^2)$

Figure (25)



Mode	SAR W/kg	X m	Y m	Z m	d: Calculated distance (mm)		
LTE B12	1	0.181	-0.0230	-0.0689	0.0000	1 + 2	23.4
NR Bn66	2	0.627	-0.0055	-0.0845	0.0000	1 + 3	147.0
UNII MIMO + BT Ant.1	3	1.110	0.0220	0.0710	0.0000	2 + 3	157.9

The Peak Location Separation Distance is computed by using the formula below:
 $SQRT((X1-X2)^2+(Y1-Y2)^2+(Z1-Z2)^2)$

Figure (26)




Figure (27)




Figure (28)




Figure (29)




Figure (30)




Figure (31)




Figure (32)




Figure (33)




Figure (34)




Figure (35)




Figure (36)




Figure (37)





Figure (38)




Mode		SAR	X	Y	Z	d: Calculated distance (mm)	
		W/kg	m	m	m		
LTE B13	1	0.576	-0.0214	-0.0705	0.0000	1 + 2	21.2
NR Bn66	2	0.341	-0.0055	-0.0845	0.0000	1 + 3	146.3
UNII MIMO + BT Ant.2	3	1.300	0.0208	0.0696	0.0000	2 + 3	156.3

The Peak Location Separation Distance is computed by using the formula below:

$$\text{SQRT}((X1-X2)^2+(Y1-Y2)^2+(Z1-Z2)^2)$$

Figure (39)




Mode		SAR	X	Y	Z	d: Calculated distance (mm)	
		W/kg	m	m	m		
LTE B13	1	0.576	-0.0214	-0.0705	0.0000	1 + 2	21.2
NR Bn66	2	0.341	-0.0055	-0.0845	0.0000	1 + 3	146.3
UNII MIMO + BT MIMO	3	1.250	0.0208	0.0696	0.0000	2 + 3	156.3

The Peak Location Separation Distance is computed by using the formula below:

$$\text{SQRT}((X1-X2)^2+(Y1-Y2)^2+(Z1-Z2)^2)$$


Figure (40)



Mode		SAR W/kg	X m	Y m	Z m	d: Calculated distance (mm)	
LTE B13	1	0.576	-0.0214	-0.0705	0.0000	1 + 2	21.2
NR Bn66	2	0.341	-0.0055	-0.0845	0.0000	1 + 3	146.3
UNII MIMO + DTS Ant.1	3	1.270	0.0208	0.0696	0.0000	2 + 3	156.3

The Peak Location Separation Distance is computed by using the formula below :
 $SQRT((X1-X2)^2+(Y1-Y2)^2+(Z1-Z2)^2)$


Figure (41)



Mode		SAR W/kg	X m	Y m	Z m	d: Calculated distance (mm)	
LTE B13	1	0.576	-0.0214	-0.0705	0.0000	1 + 2	21.2
NR Bn66	2	0.341	-0.0055	-0.0845	0.0000	1 + 3	146.3
UNII MIMO + DTS Ant.2	3	1.310	0.0208	0.0696	0.0000	2 + 3	156.3

The Peak Location Separation Distance is computed by using the formula below :
 $SQRT((X1-X2)^2+(Y1-Y2)^2+(Z1-Z2)^2)$

Figure (42)



Mode	SAR W/kg	X m	Y m	Z m	d: Calculated distance (mm)	
					1+2	1+3
LTE B13	1	0.576	-0.0214	-0.0705	0.0000	21.2
NR Bn66	2	0.341	-0.0055	-0.0845	0.0000	146.3
UNII MIMO + DTS MIMO	3	1.300	0.0208	0.0696	0.0000	156.3

The Peak Location Separation Distance is computed by using the formula below :

$$\text{SQRT}((X1-X2)^2+(Y1-Y2)^2+(Z1-Z2)^2)$$