

PART 24 MEASUREMENT REPORT

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

10/8/2021 - 11/10/2021

Test Report Issue Date:

12/17/2021

Test Site/Location:

PCTEST Lab. Yongin-Si, Gyeonggi-do, South Korea

Test Report Serial No.:

1M2109220110-03.A3L

FCC ID:

A3LSMS908E

Applicant Name:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SM-S908E/DS

Additional Model(s):

SM-S908E

EUT Type:

Portable Handset

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part:

24

Test Procedure(s):

ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168
D01 v03r01, KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Prepared by



Reviewed by






FCC ID: A3LSMS908E	 PART 24 MEASUREMENT REPORT 	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset
		Page 1 of 84


TABLE OF CONTENTS

1.0	INTRODUCTION	4
1.1	Scope	4
1.2	PCTEST Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description	5
2.2	Device Capabilities.....	5
2.3	Test Configuration	5
2.4	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Radiated Power and Radiated Spurious Emissions	6
4.0	MEASUREMENT UNCERTAINTY	7
5.0	TEST EQUIPMENT CALIBRATION DATA	8
6.0	SAMPLE CALCULATIONS	9
7.0	TEST RESULTS	11
7.1	Summary	11
7.2	Occupied Bandwidth	12
7.3	Spurious and Harmonic Emissions at Antenna Terminal	21
7.4	Band Edge Emissions at Antenna Terminal	37
7.5	Peak-Average Ratio	59
7.6	Radiated Power (ERP/EIRP).....	68
7.7	Radiated Spurious Emissions Measurements.....	71
7.8	Frequency Stability / Temperature Variation	80
8.0	CONCLUSION.....	84

FCC ID: A3LSMS908E	 PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset	Page 2 of 84





PART 24 MEASUREMENT REPORT



Mode	Modulation	Tx Frequency Range [MHz]	EIRP		Emission Designator
			Max. Power [W]	Max. Power [dBm]	
GSM/GPRS	GMSK	1850.2 - 1909.8	0.971	29.87	242KGXW
EDGE	8-PSK	1850.2 - 1909.8	0.303	24.81	241KG7W
WCDMA	Spread Spectrum	1852.4 - 1907.6	0.192	22.83	4M17F9W

Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	EIRP		Emission Designator
				Max. Power [W]	Max. Power [dBm]	
LTE Band 25/2	20 MHz	QPSK	1860 - 1905	0.174	22.41	18M1G7D
		16QAM	1860 - 1905	0.131	21.17	18M0W7D
	15 MHz	QPSK	1857.5 - 1907.5	0.175	22.42	13M5G7D
		16QAM	1857.5 - 1907.5	0.126	21.02	13M5W7D
	10 MHz	QPSK	1855 - 1910	0.190	22.78	9M04G7D
		16QAM	1855 - 1910	0.140	21.45	9M06W7D
	5 MHz	QPSK	1852.5 - 1912.5	0.173	22.37	4M53G7D
		16QAM	1852.5 - 1912.5	0.128	21.07	4M54W7D
	3 MHz	QPSK	1851.5 - 1913.5	0.147	21.67	2M73G7D
		16QAM	1851.5 - 1913.5	0.117	20.69	2M73W7D
	1.4 MHz	QPSK	1850.7 - 1914.3	0.150	21.76	1M11G7D
		16QAM	1850.7 - 1914.3	0.123	20.90	1M10W7D

EUT Overview

FCC ID: A3LSMS908E	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 3 of 84

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.



1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, 16954, South Korea. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Yongin-si, Gyeonggi-do, 16954, South Korea.

- PCTEST is an ISO 17025-2017 accredited test facility under the National Voluntary Laboratory Accreditation Program (NVLAP) with Certificate number 600143-0 for Specific Absorption Rate (SAR), where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (26168) test laboratory with the site description on file with ISED.

FCC ID: A3LSMS908E	 PART 24 MEASUREMENT REPORT 	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset
Page 4 of 84		

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMS908E**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 24.

Test Device Serial No.: 1643M, 0722M

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 5G NR (FR1), 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII (5GHz), Bluetooth (1x, EDR, LE), NFC, Wireless Power Transfer, Ultra Wideband



2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) Model: EP-N5100 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMS908E	 PART 24 MEASUREMENT REPORT 	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset
		Page 5 of 84

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Measurement Guidance for Certification of Licensed Digital Transmitters” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

3.2 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

For radiated power measurements, substitution method is used per the guidance of ANSI/TIA-603-E-2016. A half-wave dipole is substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d [dBm] = P_g [dBm] - \text{cable loss} [dB] + \text{antenna gain} [dBd/dBi];$$

where P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g [dBm] - \text{cable loss} [dB]$.

For radiated spurious emissions measurements and calculations, conversion method is used per the formulas in KDB 971168 Section 5.8.4. Field Strength (EIRP) is calculated using the following formulas:



$$E_{[dB\mu V/m]} = \text{Measured amplitude level}_{[dBm]} + 107 + \text{Cable Loss}_{[dB]} + \text{Antenna Factor}_{[dB/m]}$$

And

$$\text{EIRP}_{[dBm]} = E_{[dB\mu V/m]} + 20\log D - 104.8; \text{ where } D \text{ is the measurement distance in meters.}$$

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.



Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/TIA-603-E-2016.

FCC ID: A3LSMS908E		PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset	Page 6 of 84	

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.20
Radiated Disturbance (<1GHz)	3.01
Radiated Disturbance (>1GHz)	5.56
Radiated Disturbance (>18GHz)	3.16

FCC ID: A3LSMS908E	 PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset	Page 7 of 84

5.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E5515C	WIRELESS COMMUNICATION TEST SET	2/19/2021	Annual	2/18/2022	MY50262130
Agilent	N9030A	PXA Signal Analyzer	7/6/2021	Annual	7/5/2022	MY49432391
Anritsu	S820E	Cable and Antenna Analyzer	7/7/2021	Annual	7/6/2022	6201300731
Anritsu	MA24106A	USB Power Sensor	7/7/2021	Annual	7/6/2022	1244512
Anritsu	MA24106A	USB Power Sensor	2/19/2021	Annual	2/18/2022	1344557
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	10/29/2020	Biennial	10/28/2022	10160045
Com-Power	PAM-118A	Preamplifier	7/7/2021	Annual	7/6/2022	551042
Espec	SH-242	Environmental Chamber	9/15/2021	Annual	9/14/2022	93011064
ETS Lindgren	3110C	Biconical Antenna	7/9/2020	Biennial	7/8/2022	00211248
ETS Lindgren	3110C	Biconical Antenna	7/9/2020	Biennial	7/8/2022	00211250
Fairview Microwave	FM2CP1122-10	Coupler	7/7/2021	Annual	7/6/2022	1946
Keysight Technologies	N9030B	MXA Signal Analyzer	5/11/2021	Annual	5/10/2022	MY57142018
Mini Circuits	ZUDC10-83-S+	Coupler	9/15/2021	Annual	9/14/2022	2111
Mini-Circuits	BW-N10W5+	Attenuator	7/6/2021	Annual	7/5/2022	1607
Mini-Circuits	BW-N10W5+	Attenuator	7/6/2021	Annual	7/5/2022	1607
Rohde & Schwarz	TS-PR18	Preamplifier	7/8/2021	Annual	7/7/2022	102141
Rohde & Schwarz	SMBV100B	Signal Generator	11/4/2021	Annual	11/3/2022	101568
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	7/6/2021	Annual	7/5/2022	116851
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	2/19/2021	Annual	2/18/2022	131453
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	2/19/2021	Annual	2/18/2022	131454
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	2/19/2021	Annual	2/18/2022	150117
Rohde & Schwarz	ESW	EMI Test Receiver	7/6/2021	Annual	7/5/2022	101761
Rohde & Schwarz	FSW43	Signal & Spectrum Analyzer	9/15/2021	Annual	9/14/2022	101250
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	2/19/2021	Annual	2/18/2022	102131
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	3/29/2021	Annual	3/28/2022	102151
Schwarzbeck	UHA9105	Dipole Antenna	7/9/2020	Biennial	7/8/2022	91052522
Sunol	DRH-118	Horn Antenna	7/14/2021	Biennial	7/13/2023	A102416-1
Sunol	DRH-118	Horn Antenna	1/12/2021	Biennial	1/11/2023	A060215

Table 5-1. Test Equipment

Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMS908E	 PART 24 MEASUREMENT REPORT 	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset
		Page 8 of 84

6.0 SAMPLE CALCULATIONS

GSM Emission Designator

Emission Designator = 250KGXW

GSM BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 250KG7W

EDGE BW = 250 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M16F9W

WCDMA BW = 4.16 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

QAM Modulation



Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info



D = Data transmission, telemetry, telecommand

FCC ID: A3LSMS908E	 PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 9 of 84

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm $- (-24.80) = 50.3$ dBc.

FCC ID: A3LSMS908E	 PART 24 MEASUREMENT REPORT 		Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset	Page 10 of 84

7.0 TEST RESULTS

7.1 Summary



Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMS908E
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): GSM/GPRS/EDGE/WCDMA/LTE

Test Condition	Test Description	FCC Part Section(s)	RSS Section(s)	Test Limit	Test Result	Reference
CONDUCTED	Occupied Bandwidth	2.1049	RSS-Gen(6.7)	N/A	PASS	Section 7.2
	Conducted Band Edge / Spurious Emissions	2.1051, 24.238(b)	RSS-133(6.5)	> 43 + 10log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions	PASS	Sections 7.3, 7.4
	Transmitter Conducted Output Power	2.1046	RSS-133(4.1)	N/A	PASS	See RF Exposure Report
	Frequency Stability	2.1055, 24.235	RSS-133(6.3)	Fundamental emissions stay within authorized frequency block	PASS	Section 7.8
RADIATED	Equivalent Isotropic Radiated Power	24.232(c)	RSS-132(5.4)	< 2 Watts max. EIRP	PASS	Section 7.6
	Radiated Spurious Emissions	2.1053, 24.238(b)	RSS-133(6.5)	> 43 + 10 log ₁₀ (P[Watts]) for all out-of-band emissions	PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) All conducted emissions measurements are performed with automated test software to capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST EMC Software Tool v1.0.

FCC ID: A3LSMS908E	 PART 24 MEASUREMENT REPORT 	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset
Page 11 of 84		

7.2 Occupied Bandwidth

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup

Test Notes


None.

FCC ID: A3LSMS908E	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 12 of 84


LTE Band 25/2



FCC ID: A3LSMS908E	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 13 of 84




Plot 7-3. Occupied Bandwidth Plot (LTE Band 25/2 - 15MHz QPSK - Full RB)




Plot 7-4. Occupied Bandwidth Plot (LTE Band 25/2 - 15MHz 16-QAM - Full RB)

FCC ID: A3LSMS908E	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 14 of 84




Plot 7-5. Occupied Bandwidth Plot (LTE Band 25/2 - 10MHz QPSK - Full RB)




Plot 7-6. Occupied Bandwidth Plot (LTE Band 25/2 - 10MHz 16-QAM - Full RB)

FCC ID: A3LSMS908E	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 15 of 84




Plot 7-7. Occupied Bandwidth Plot (LTE Band 25/2 - 5MHz QPSK - Full RB)




Plot 7-8. Occupied Bandwidth Plot (LTE Band 25/2 - 5MHz 16-QAM - Full RB)

FCC ID: A3LSMS908E	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 16 of 84




Plot 7-9. Occupied Bandwidth Plot (LTE Band 25/2 - 3MHz QPSK - Full RB)




Plot 7-10. Occupied Bandwidth Plot (LTE Band 25/2 - 3MHz 16-QAM - Full RB)

FCC ID: A3LSMS908E	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 17 of 84



Plot 7-11. Occupied Bandwidth Plot (LTE Band 25/2 - 1.4MHz QPSK - Full RB)



Plot 7-12. Occupied Bandwidth Plot (LTE Band 25/2 - 1.4MHz 16-QAM - Full RB)

FCC ID: A3LSMS908E	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 18 of 84

GSM/GPRS PCS



Plot 7-13. Occupied Bandwidth Plot (GPRS, Ch. 661)



Plot 7-14. Occupied Bandwidth Plot (EDGE, Ch. 661)

FCC ID: A3LSMS908E	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 19 of 84

WCDMA PCS



Plot 7-15. Occupied Bandwidth Plot (WCDMA, Ch. 9400)

FCC ID: A3LSMS908E		PART 24 MEASUREMENT REPORT	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset	Page 20 of 84

7.3 Spurious and Harmonic Emissions at Antenna Terminal

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + 10 \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 20GHz (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 7-2. Test Instrument & Measurement Setup

Test Notes


Per Part 24 and RSS-133, compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth 100 kHz or greater for measurements below 1GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMS908E	 PART 24 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset	Page 21 of 84

LTE Band 25/2




Plot 7-16. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - 1RB - Low Channel)



Plot 7-17. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - 1RB - Low Channel)

FCC ID: A3LSMS908E	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 22 of 84




Plot 7-18. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - 1RB - Low Channel)




Plot 7-19. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - 1RB - Mid Channel)

FCC ID: A3LSMS908E	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 23 of 84




Plot 7-20. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - 1RB - Mid Channel)




Plot 7-21. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - 1RB - Mid Channel)

FCC ID: A3LSMS908E	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 24 of 84




Plot 7-22. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - 1RB - High Channel)



Plot 7-23. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - 1RB - High Channel)

FCC ID: A3LSMS908E	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 25 of 84



Plot 7-24. Conducted Spurious Plot (LTE Band 25/2 - 20MHz QPSK - 1RB - High Channel)

FCC ID: A3LSMS908E	PCTEST Proud to be part of element	PART 24 MEASUREMENT REPORT	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2109220110-03.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 26 of 84