

## PART 27 MEASUREMENT REPORT

**Applicant Name:**

Samsung Electronics Co., Ltd.  
129, Samsung-ro,  
Yeongtong-gu, Suwon-si  
Gyeonggi-do, 16677, Korea

**Date of Testing:**

10/8/2021 - 11/10/2021

**Test Report Issue Date:**

12/17/2021

**Test Site/Location:**

PCTEST Lab. Yongin-Si, Gyeonggi-do, South Korea

**Test Report Serial No.:**

1M2109220110-29.A3L

**FCC ID:**

**A3LSMS908E**

**APPLICANT:**

**Samsung Electronics Co., Ltd.**

**Application Type:**

Certification

**Model:**

SM-S908E/DS

**Additional Model(s):**

SM-S908E

**EUT Type:**

Portable Handset

**FCC Classification:**

PCS Licensed Transmitter Held to Ear (PCE)

**FCC Rule Part:**

27

**Test Procedure(s):**

ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01,  
KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.



I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Prepared by






Reviewed by

FCC ID: A3LSMS908E	 <b>PCTEST</b> Proud to be part of element	<b>PART 27 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2109220110-29.A3L	<b>Test Dates:</b> 10/8/2021 - 11/10/2021	<b>EUT Type:</b> Portable Handset		Page 1 of 101

## TABLE OF CONTENTS


1.0	INTRODUCTION .....	4
1.1	Scope .....	4
1.2	PCTEST Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description .....	5
2.2	Device Capabilities.....	5
2.3	Test Configuration .....	5
2.4	EMI Suppression Device(s)/Modifications .....	5
3.0	DESCRIPTION OF TESTS .....	6
3.1	Evaluation Procedure .....	6
3.2	Radiated Power and Radiated Spurious Emissions .....	6
4.0	MEASUREMENT UNCERTAINTY .....	7
5.0	TEST EQUIPMENT CALIBRATION DATA .....	8
6.0	SAMPLE CALCULATIONS .....	9
7.0	TEST RESULTS .....	10
7.1	Summary .....	10
7.2	Occupied Bandwidth .....	12
7.3	Spurious and Harmonic Emissions at Antenna Terminal .....	26
7.4	Band Edge Emissions at Antenna Terminal .....	44
7.5	Peak-Average Ratio .....	75
7.6	Radiated Power (ERP/EIRP).....	83
7.7	Radiated Spurious Emissions Measurements.....	87
7.8	Frequency Stability / Temperature Variation .....	96
8.0	CONCLUSION.....	101

<b>FCC ID:</b> A3LSMS908E	 Proud to be part of element	<b>PART 27 MEASUREMENT REPORT</b>	 <b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2109220110-29.A3L	<b>Test Dates:</b> 10/8/2021 - 11/10/2021	<b>EUT Type:</b> Portable Handset	Page 2 of 101



# MEASUREMENT REPORT

## FCC Part 27





Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	ERP		EIRP		Emission Designator
				Max. Power [W]	Max. Power [dBm]	Max. Power [W]	Max. Power [dBm]	
LTE Band 12/17	10 MHz	QPSK	704.0 - 711.0	0.035	15.45	0.057	17.60	9M01G7D
		16QAM	704.0 - 711.0	0.025	13.92	0.040	16.07	9M02W7D
	5 MHz	QPSK	701.5 - 713.5	0.032	15.00	0.052	17.15	4M53G7D
		16QAM	701.5 - 713.5	0.025	13.95	0.041	16.10	4M56W7D
	3 MHz	QPSK	700.5 - 714.5	0.026	14.23	0.043	16.38	2M73G7D
		16QAM	700.5 - 714.5	0.021	13.29	0.035	15.44	2M73W7D
1.4 MHz	QPSK	699.7 - 715.3	0.026	14.17	0.043	16.32	1M11G7D	
	16QAM	699.7 - 715.3	0.020	13.06	0.033	15.21	1M11W7D	
LTE Band 13	10 MHz	QPSK	782.0	0.066	18.21	0.109	20.36	9M04G7D
		16QAM	782.0	0.051	17.05	0.083	19.20	9M00W7D
	5 MHz	QPSK	779.5 - 784.5	0.062	17.90	0.101	20.05	4M56G7D
		16QAM	779.5 - 784.5	0.046	16.67	0.076	18.82	4M53W7D

Overview Table (<1GHz Bands)

Mode	Modulation	Tx Frequency Range [MHz]	EIRP		Emission Designator
			Max. Power [W]	Max. Power [dBm]	
WCDMA1700	Spread Spectrum	1712.4 - 1752.6	0.193	22.87	4M16F9W

Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	EIRP		Emission Designator
				Max. Power [W]	Max. Power [dBm]	
LTE Band 66/4	20 MHz	QPSK	1720.0 - 1770.0	0.177	22.49	18M0G7D
		16QAM	1720.0 - 1770.0	0.133	21.23	18M0W7D
	15 MHz	QPSK	1717.5 - 1772.5	0.181	22.57	13M5G7D
		16QAM	1717.5 - 1772.5	0.132	21.21	13M5W7D
	10 MHz	QPSK	1715.0 - 1775.0	0.192	22.84	9M04G7D
		16QAM	1715.0 - 1775.0	0.139	21.43	9M06W7D
	5 MHz	QPSK	1712.5 - 1777.5	0.168	22.26	4M54G7D
		16QAM	1712.5 - 1777.5	0.133	21.25	4M53W7D
	3 MHz	QPSK	1711.5 - 1778.5	0.150	21.76	2M73G7D
		16QAM	1711.5 - 1778.5	0.120	20.78	2M72W7D
	1.4 MHz	QPSK	1710.7 - 1779.3	0.144	21.60	1M11G7D
		16QAM	1710.7 - 1779.3	0.115	20.60	1M10W7D

Overview Table (>1GHz Bands)

FCC ID: A3LSMS908E	 PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 3 of 101

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.



### 1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, 16954, South Korea. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

### 1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Yongin-si, Gyeonggi-do, 16954, South Korea.

- PCTEST is an ISO 17025-2017 accredited test facility under the National Voluntary Laboratory Accreditation Program (NVLAP) with Certificate number 600143-0 for Specific Absorption Rate (SAR), where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (26168) test laboratory with the site description on file with ISED.

FCC ID: A3LSMS908E	 PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 4 of 101

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMS908E**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 27.

**Test Device Serial No.:** 1643M, 0722M

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 5G NR (FR1), 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII (5GHz), Bluetooth (1x, EDR, LE), NFC, Wireless Power Transfer, Ultra Wideband



### 2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) Model: EP-N5100 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMS908E	 PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 5 of 101

## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedures described in the document titled “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

### 3.2 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer “Channel Power” function with the integration band set to the emissions’ occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03r01.



Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where,  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g \text{ [dBm]} - \text{cable loss [dB]}$ .

For fundamental radiated power measurements, the guidance of KDB 971168 D01 v03r01 is used to record the EUT power level that is subsequently matched via the aforementioned substitution method given in ANSI/TIA-603-E-2016.



All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

FCC ID: A3LSMS908E	 PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 6 of 101

## 4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.20
Radiated Disturbance (<1GHz)	3.01
Radiated Disturbance (>1GHz)	5.56
Radiated Disturbance (>18GHz)	3.16

FCC ID: A3LSMS908E	 PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 7 of 101



## 5.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E5515C	WIRELESS COMMUNICATION TEST SET	2/19/2021	Annual	2/18/2022	MY50262130
Agilent	N9030A	PXA Signal Analyzer	7/6/2021	Annual	7/5/2022	MY49432391
Anritsu	S820E	Cable and Antenna Analyzer	7/7/2021	Annual	7/6/2022	6201300731
Anritsu	MA24106A	USB Power Sensor	7/7/2021	Annual	7/6/2022	1244512
Anritsu	MA24106A	USB Power Sensor	2/19/2021	Annual	2/18/2022	1344557
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	10/29/2020	Biennial	10/28/2022	10160045
Com-Power	PAM-118A	Preamplifier	7/7/2021	Annual	7/6/2022	551042
Espec	SH-242	Environmental Chamber	9/15/2021	Annual	9/14/2022	93011064
ETS Lindgren	3110C	Biconical Antenna	7/9/2020	Biennial	7/8/2022	00211248
ETS Lindgren	3110C	Biconical Antenna	7/9/2020	Biennial	7/8/2022	00211250
Fairview Microwave	FM2CP1122-10	Coupler	7/7/2021	Annual	7/6/2022	1946
Keysight Technologies	N9030B	MXA Signal Analyzer	5/11/2021	Annual	5/10/2022	MY57142018
Mini Circuits	ZUDC10-83-S+	Coupler	9/15/2021	Annual	9/14/2022	2111
Mini-Circuits	BW-N10W5+	Attenuator	7/6/2021	Annual	7/5/2022	1607
Mini-Circuits	BW-N10W5+	Attenuator	7/6/2021	Annual	7/5/2022	1607
Rohde & Schwarz	TS-PR18	Preamplifier	7/8/2021	Annual	7/7/2022	102141
Rohde & Schwarz	SMBV100B	Signal Generator	11/4/2021	Annual	11/3/2022	101568
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	7/6/2021	Annual	7/5/2022	116851
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	2/19/2021	Annual	2/18/2022	131453
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	2/19/2021	Annual	2/18/2022	131454
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	2/19/2021	Annual	2/18/2022	150117
Rohde & Schwarz	ESW	EMI Test Receiver	7/6/2021	Annual	7/5/2022	101761
Rohde & Schwarz	FSW43	Signal & Spectrum Analyzer	9/15/2021	Annual	9/14/2022	101250
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	2/19/2021	Annual	2/18/2022	102131
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	3/29/2021	Annual	3/28/2022	102151
Schwarzbeck	UHA9105	Dipole Antenna	7/9/2020	Biennial	7/8/2022	91052522
Sunol	DRH-118	Horn Antenna	7/14/2021	Biennial	7/13/2023	A102416-1
Sunol	DRH-118	Horn Antenna	1/12/2021	Biennial	1/11/2023	A060215

Table 5-1. Test Equipment

### Notes:

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMS908E	 PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 8 of 101



## 6.0 SAMPLE CALCULATIONS

### Emission Designator

#### QPSK Modulation

**Emission Designator = 8M62G7D**

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

#### QAM Modulation

**Emission Designator = 8M45W7D**

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated



7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

### Spurious Radiated Emission – LTE Band

#### **Example: Middle Channel LTE Mode 2<sup>nd</sup> Harmonic (1564 MHz)**

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was  $-81.0$  dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of  $-81.0$  dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of  $-30.9$  dBm yielding  $-24.80$  dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – ( $-24.80$ ).

FCC ID: A3LSMS908E	 PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 9 of 101



## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: Samsung Electronics Co., Ltd.  
 FCC ID: A3LSMS908E  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): WCDMA/LTE



Test Condition	Test Description	FCC Part Section(s)	Test Limit	Test Result	Reference
Conducted	Occupied Bandwidth	2.1049(h)	N/A	PASS	Section 7.2
	Conducted Band Edge / Spurious Emissions (LTE Band 13)	2.1051, 27.53(c), 27.53(f)	Undesirable emissions must meet the limits detailed in sections 27.53(c) and 27.53(f)	PASS	Sections 7.3, 7.4
	Conducted Band Edge / Spurious Emissions (LTE Band 12, 17)	2.1051, 27.53(g)	$\geq 43 + 10 \log (P[\text{Watts}])$ dB of attenuation below transmitter power	PASS	Sections 7.3, 7.4
	Conducted Band Edge / Spurious Emissions (WCDMA AWS; LTE Band 4, 66)	2.1051, 27.53(h)	$\geq 43 + 10 \log (P[\text{Watts}])$ dB of attenuation below transmitter power	PASS	Sections 7.3, 7.4
	Peak-to-Average Ratio (WCDMA AWS; LTE Band 4, 66)	27.50(d)(5)	$\leq 13$ dB	PASS	Section 7.5
	Frequency Stability	2.1055, 27.54	Fundamental emissions stay within authorized frequency block	PASS	Section 7.8
RADIATED	Effective Radiated Power (LTE Band 13)	27.50(b)(10)	$\leq 3$ Watts max. ERP	PASS	Section 7.6
	Effective Radiated Power (LTE Band 12, 17)	27.50(c)(10)	$\leq 3$ Watts max. ERP	PASS	Section 7.6
	Equivalent Isotropic Radiated Power (WCDMA AWS; LTE Band 4, 66)	27.50(d)(10)	$\leq 1$ Watt max. EIRP	PASS	Section 7.6
	Radiated Spurious Emissions (LTE Band 13)	2.1053, 27.53(c), 27.53(f)	Undesirable emissions must meet the limits detailed in sections 27.53(c) and 27.53(f)	PASS	Section 7.7
	Radiated Spurious Emissions (LTE Band 12, 17)	2.1053, 27.53(g)	$\geq 43 + 10 \log (P[\text{Watts}])$ dB of attenuation below transmitter power	PASS	Section 7.7
	Radiated Spurious Emissions (WCDMA AWS; LTE Band 4, 66)	2.1053, 27.53(h)	$\geq 43 + 10 \log (P[\text{Watts}])$ dB of attenuation below transmitter power	PASS	Section 7.7

Table 7-1. Summary of Test Results

FCC ID: A3LSMS908E	 PCTEST Proud to be part of element	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 10 of 101

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST EMC Software Tool v1.0.

<b>FCC ID:</b> A3LSMS908E		<b>PART 27 MEASUREMENT REPORT</b> 	<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2109220110-29.A3L	<b>Test Dates:</b> 10/8/2021 - 11/10/2021	<b>EUT Type:</b> Portable Handset	Page 11 of 101

## 7.2 Occupied Bandwidth

### Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

### Test Procedure Used


KDB 971168 D01 v03r01 – Section 4.2

### Test Settings

1. The signal analyzer’s automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### Test Setup



The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-1. Test Instrument & Measurement Setup**

### Test Notes

None.

FCC ID: A3LSMS908E	 <b>PCTEST</b> Proud to be part of element	<b>PART 27 MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 12 of 101

## LTE Band 12/17




Plot 7-1. Occupied Bandwidth Plot (LTE Band 12/17 - 10MHz QPSK - Full RB)




Plot 7-2. Occupied Bandwidth Plot (LTE Band 12/17 - 10MHz 16-QAM - Full RB)

FCC ID: A3LSMS908E	<b>PCTEST</b> Proud to be part of element	PART 27 MEASUREMENT REPORT	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 13 of 101




Plot 7-3. Occupied Bandwidth Plot (LTE Band 12/17 - 5MHz QPSK - Full RB)




Plot 7-4. Occupied Bandwidth Plot (LTE Band 12/17 - 5MHz 16-QAM - Full RB)

FCC ID: A3LSMS908E	<b>PCTEST</b> Proud to be part of element	PART 27 MEASUREMENT REPORT	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 14 of 101






Plot 7-5. Occupied Bandwidth Plot (LTE Band 12 - 3MHz QPSK - Full RB)




Plot 7-6. Occupied Bandwidth Plot (LTE Band 12 - 3MHz 16-QAM - Full RB)

FCC ID: A3LSMS908E	<b>PCTEST</b> Proud to be part of element	PART 27 MEASUREMENT REPORT	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 15 of 101





Plot 7-7. Occupied Bandwidth Plot (LTE Band 12 – 1.4MHz QPSK - Full RB)




Plot 7-8. Occupied Bandwidth Plot (LTE Band 12 – 1.4MHz 16-QAM - Full RB)

FCC ID: A3LSMS908E	<b>PCTEST</b> Proud to be part of element	<b>PART 27 MEASUREMENT REPORT</b>	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 16 of 101


## LTE Band 13



FCC ID: A3LSMS908E	<b>PCTEST</b> Proud to be part of element	<b>PART 27 MEASUREMENT REPORT</b>	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 17 of 101




Plot 7-11. Occupied Bandwidth Plot (LTE Band 13 - 5MHz QPSK - Full RB)



Plot 7-12. Occupied Bandwidth Plot (LTE Band 13 - 5MHz 16-QAM - Full RB)

FCC ID: A3LSMS908E	<b>PCTEST</b> Proud to be part of element	<b>PART 27 MEASUREMENT REPORT</b>	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 18 of 101



# WCDMA AWS



Plot 7-13. Occupied Bandwidth Plot (WCDMA, Ch. 1413)


FCC ID: A3LSMS908E	<b>PCTEST</b> Proud to be part of element	<b>PART 27 MEASUREMENT REPORT</b>	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 19 of 101

## LTE Band 66/4




FCC ID: A3LSMS908E	<b>PCTEST</b> Proud to be part of element	<b>PART 27 MEASUREMENT REPORT</b>	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 20 of 101






Plot 7-16. Occupied Bandwidth Plot (LTE Band 66/4 - 15MHz QPSK - Full RB)




Plot 7-17. Occupied Bandwidth Plot (LTE Band 66/4 - 15MHz 16-QAM - Full RB)

FCC ID: A3LSMS908E	<b>PCTEST</b> Proud to be part of element	PART 27 MEASUREMENT REPORT	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 21 of 101




Plot 7-18. Occupied Bandwidth Plot (LTE Band 66/4 - 10MHz QPSK - Full RB)



Plot 7-19. Occupied Bandwidth Plot (LTE Band 66/4 - 10MHz 16-QAM - Full RB)

FCC ID: A3LSMS908E	<b>PCTEST</b> Proud to be part of  element	<b>PART 27 MEASUREMENT REPORT</b>	<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2109220110-29.A3L	<b>Test Dates:</b> 10/8/2021 - 11/10/2021	<b>EUT Type:</b> Portable Handset	Page 22 of 101




Plot 7-20. Occupied Bandwidth Plot (LTE Band 66/4 - 5MHz QPSK - Full RB)




Plot 7-21. Occupied Bandwidth Plot (LTE Band 66/4 - 5MHz 16-QAM - Full RB)

FCC ID: A3LSMS908E	<b>PCTEST</b> Proud to be part of  element	<b>PART 27 MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 23 of 101



Plot 7-22. Occupied Bandwidth Plot (LTE Band 66/4 - 3MHz QPSK - Full RB)



Plot 7-23. Occupied Bandwidth Plot (LTE Band 66/4 - 3MHz 16-QAM - Full RB)

FCC ID: A3LSMS908E	<b>PCTEST</b> Proud to be part of element	PART 27 MEASUREMENT REPORT	<b>SAMSUNG</b>	Approved by: Technical Manager
Test Report S/N: 1M2109220110-29.A3L	Test Dates: 10/8/2021 - 11/10/2021	EUT Type: Portable Handset		Page 24 of 101