

FCC LTE REPORT

Certification

Applicant Name:

SAMSUNG Electronics Co., Ltd.

Date of Issue:

October 21, 2022

Address:

129, Samsung-ro, Yeongtong-gu,
 Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Location:

HCT CO., LTD.,
 74, Seoicheon-ro 578beon-gil, Majang-myeon,
 Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Report No.: HCT-RF-2210-FC017

FCC ID: A3LSMS911B

APPLICANT: SAMSUNG Electronics Co., Ltd.

Model(s): SM-S911B/DS
 Additional Model(s): SM-S911B
 EUT Type: Mobile phone
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 FCC Rule Part(s): §90, §22, §2

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	Conducted Output Power	
				Max. Power (W)	Max. Power (dBm)
LTE – Band26 (1.4)	814.7 – 824.0	1M10G7D	QPSK	0.223	23.49
		1M10W7D	16QAM	0.191	22.82
		1M10W7D	64QAM	0.146	21.64
		1M09W7D	256QAM	0.072	18.59
LTE – Band26 (3)	815.5 – 824.0	2M70G7D	QPSK	0.220	23.43
		2M72W7D	16QAM	0.194	22.88
		2M71W7D	64QAM	0.146	21.64
		2M71W7D	256QAM	0.072	18.60
LTE – Band26 (5)	816.5 – 824.0	4M52G7D	QPSK	0.243	23.86
		4M52W7D	16QAM	0.211	23.24
		4M53W7D	64QAM	0.157	21.96
		4M51W7D	256QAM	0.080	19.01
LTE – Band26 (10)	819.0 – 824.0	8M98G7D	QPSK	0.242	23.83
		8M98W7D	16QAM	0.199	22.99
		8M98W7D	64QAM	0.161	22.06
		9M97W7D	256QAM	0.078	18.94
LTE – Band26 (15)	821.5	13M5G7D	QPSK	0.225	23.52
		13M5W7D	16QAM	0.193	22.86
		13M5W7D	64QAM	0.144	21.57
		13M4W7D	256QAM	0.074	18.70

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.
 HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

Report No.: HCT-RF-2210-FC017

REVIEWED BY



Report prepared by : Jae Mun Do
Engineer of Telecommunication Testing Center

Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked *.

The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

* The report shall not be reproduced except in full(only partly) without approval of the laboratory.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2210-FC017	October 21, 2022	- First Approval Report

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

Table of Contents

REVIEWED BY	2
1. GENERAL INFORMATION	5
2. INTRODUCTION	6
2.1. DESCRIPTION OF EUT.....	6
2.2. MEASURING INSTRUMENT CALIBRATION	6
2.3. TEST FACILITY	6
3. DESCRIPTION OF TESTS.....	7
3.1 TEST PROCEDURE	7
3.2 CONDUCTED OUTPUT POWER.....	8
3.3 RADIATED POWER.....	9
3.4 RADIATED SPURIOUS EMISSIONS	10
3.5 OCCUPIED BANDWIDTH.	11
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	12
3.7 CHANNEL EDGE.....	13
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	14
3.9 WORST CASE(RADIATED TEST)	15
3.10 WORST CASE(CONDUCTED TEST)	16
4. LIST OF TEST EQUIPMENT	17
5. MEASUREMENT UNCERTAINTY	18
6. SUMMARY OF TEST RESULTS	19
7. SAMPLE CALCULATION	20
8. TEST DATA	22
8.1 CONDUCTED OUTPUT POWER.....	22
8.2 EFFECTIVE RADIATED POWER.....	27
8.3 RADIATED SPURIOUS EMISSIONS	29
8.4 OCCUPIED BANDWIDTH	30
8.5 CONDUCTED SPURIOUS EMISSIONS	31
8.6 CHANNEL EDGE.....	31
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	32
8.8 STADDLE CHANNEL	37
8.8.1 CONDUCTED OUTPUT POWER.....	37
8.8.2 EFFECTIVE RADIATED POWER	41
8.8.3 RADIATED SPURIOUS EMISSIONS	42
8.8.4 CONDUCTED SPURIOUS EMISSIONS	43
8.8.5 CHANNEL EDGE(Part90)	43
8.8.6 BAND EDGE(Part22)	43
9. TEST PLOTS.....	44
10. TEST PLOTS (STRADDLE CHANNEL).....	93
11 ANNEX A_ TEST SETUP PHOTO	118

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMS911B
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s):	§90, §22, §2
EUT Type:	Mobile phone
Model(s):	SM-S911B/DS
Additional Model(s):	SM-S911B
Tx Frequency:	814.7 MHz – 823.3 MHz (LTE – Band 26 (1.4 MHz)) 815.5 MHz – 822.5 MHz (LTE – Band 26 (3 MHz)) 816.5 MHz – 821.5 MHz (LTE – Band 26 (5 MHz)) 819.0 MHz (LTE – Band 26 (10 MHz)) 821.5 MHz (LTE – Band 26 (15 MHz))
Date(s) of Tests:	August 31, 2022~ October 11, 2022
Serial number:	Radiated: R3CT706PCND Conducted: 64208a01b13f7ece

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS and LTE, Sub6.

It also supports IEEE 802.11 a/b/g/n/ac/ax (20/40/80/160 MHz), Bluetooth, BT LE, NFC, AIT, WPT.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Channel Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- KDB 971168 D01 v03r01 - Section 5.2.4 - ANSI C63.26-2015 - Section 5.2.1 & 5.2.4.2
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

3.2 CONDUCTED OUTPUT POWER

Test Overview


According to ANSI C63.26-2015 Section 5.2.1 when measuring the maximum RF output power from such devices, control over the EUT must be provided either through special test software (provided by manufacturer specifically for compliance testing, but not accessible by an end user) or through use of a base station emulator, communications test set, call box, or similar instrumentation that is capable of establishing a communications link with the EUT to enable control over variable parameters (e.g., output power, OBW, etc.).

In some cases, these instruments also include basic digital spectrum analyzer and/or power meter capabilities that can be utilized to measure the RF output power if the specified detectors and requirements can be realized and the measurement functions have been calibrated.

Test Procedure

1. The RF port of the EUT was connected to the Communication Tester via an RF cable.
2. Conducted average power was measured using a calibrated Radio Communication Tester.

Test setup



3.3 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $>$ 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d \text{ (dBm)} = P_g \text{ (dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference

between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.4 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $> 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_g_{(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5 % of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99 % occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic.

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW \geq 3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time = auto
6. Number of points in sweep \geq 2 x Span / RBW

3.7 CHANNEL EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings


1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW :
 - .- EA licensee's frequency block by up to and including 37.5 kHz : 300 Hz
 - .- EA licensee's frequency block greater than 37.5 kHz : 100 kHz
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes

For 90.691(a), RBW=300 Hz for offset less than 37.5 kHz from channel edge and RBW=100 kHz for offsets greater than 37.5 kHz is allowed.

Where Margin < 1 dB the emission level is either corrected by $10 \log(1 \text{ MHz/ RB})$ or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.

2. Primary Supply Voltage:

- Unless otherwise specified, vary primary supply voltage from 85 % to 115% of the nominal value for other than hand carried battery equipment.
- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
 Mode : Stand alone, Stand alone + External accessories (Earphone, AC adapter, etc)
 Worst case : Stand alone
- We were performed the RSE test in condition of co-location.
 Mode : Stand alone, Simultaneous transmission scenarios
 Worst case : Stand alone
- In the case of radiated spurious emissions, all bandwidth of operation were investigated and the worst case bandwidth results are reported. (Worst case : 5 MHz)
- The worst case is reported with the EUT positioning, modulations, and paging service configurations shown in the test data.
- All modes of operation were tested and the worst case results are reported.
- Please refer to the table below.
- SM-S911B/DS & additional models were tested and the worst case results are reported.
 (Worst case : SM-S911B/DS)

[Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	1	0	Y
Radiated Spurious and Harmonic Emissions	QPSK	1	0	Z

3.10 WORST CASE(CONDUCTED TEST)

-Worst case : Of all modulation, We have tested modulation of the high Conducted Output Power.

- SM-S911B/DS & additional models were tested and the worst case results are reported.

(Worst case : SM-S911B/DS)

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM, 256QAM	1.4, 3, 5	High	Full RB	0
	QPSK, 16QAM, 64QAM, 256QAM	10, 15	Mid	Full RB	0
Channel Edge	QPSK	1.4	Low	1	0
			High	1	5
		3	Low	1	0
			High	1	14
		5	Low	1	0
			High	1	24
		10	Mid	1	0
				1	49
		15	Mid	1	0
				1	74
1.4, 3, 5	Low, High	Full RB	0		
10, 15	Mid	Full RB	0		
Band Edge (Staddle Channel)	QPSK	1.4	Mid	1	5
		3	Mid	1	14
		5	Mid	1	24
		10	Mid	1	49
		1.4, 3, 5 10	Mid	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	QPSK	1.4, 3, 5	Low, High	1	0
		10, 15	Mid	1	0

4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
H.P.F	FBSR-02B(WHK1.2/15 G-10EF)	T&M SYSTEM	-	02/18/2023	Annual
H.P.F	FBSR-02B(WHK3.3/18 G-10EF)	T&M SYSTEM	-	02/18/2023	Annual
Power Splitter(DC ~ 26.5 GHz)	11667B	Hewlett Packard	11275	03/11/2023	Annual
DC Power Supply	E3632A	Agilent	MY40010147	06/21/2023	Annual
Dipole Antenna	UHAP	Schwarzbeck	557	04/05/2023	Biennial
Dipole Antenna	UHAP	Schwarzbeck	558	04/05/2023	Biennial
Chamber	SU-642	ESPEC	93008124	03/04/2023	Annual
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	147	08/30/2023	Biennial
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	9120D-1298	09/15/2023	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170342	09/29/2024	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170124	04/12/2023	Biennial
Signal Analyzer(10 Hz ~ 26.5 GHz)	N9020A	Agilent	MY52090906	05/02/2023	Annual
ATTENUATOR(20 dB)	8493C	Hewlett Packard	17280	05/18/2023	Annual
Spectrum Analyzer(10 Hz ~ 40 GHz)	FSV40	REOHDE & SCHWARZ	100931	08/29/2023	Annual
Base Station	8960 (E5515C)	Agilent	MY48360800	08/18/2023	Annual
Loop Antenna(9 kHz ~ 30 MHz)	FMZB1513	Schwarzbeck	1513-333	03/17/2024	Biennial
Bilog Antenna	VULB9160	Schwarzbeck	3150	03/03/2023	Biennial
Hybrid Antenna	VULB9168	Schwarzbeck	760	02/22/2023	Biennial
Wideband Radio Communication Tester	MT8821C	Anritsu Corp.	6262116770	07/05/2023	Annual
Wideband Radio Communication Tester	MT8820C	Anritsu Corp.	6200863156	12/29/2022	Annual
SIGNAL GENERATOR (100 kHz ~ 40 GHz)	SMB100A	REOHDE & SCHWARZ	177633	07/05/2023	Annual
Signal Analyzer(5 Hz ~ 40.0 GHz)	N9030B	KEYSIGHT	MY55480167	05/30/2023	Annual
FCC LTE Mobile Conducted RF Automation Test Software	-	HCT CO., LTD.,	-	-	-

Note:

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
2. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (\pm dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	2.00 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.40 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.74 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.51 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.92 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (Above 40 GHz)	5.48 (Confidence level about 95 %, $k=2$)

6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Channel Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §90.691	< 50 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions within 37.5 kHz of Block Edge	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §22.917(a)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§2.1046 §90.635	< 100 Watts	PASS
Frequency stability / variation of ambient temperature	§2.1055, §90.213 §22.355	< 2.5 ppm	PASS

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Effective Radiated Power	§22.913(a)(5)	< 7 Watts max. ERP (Only 15 MHz B.W)	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §90.691 §22.917(a)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$ERP = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$EIRP = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 CONDUCTED OUTPUT POWER

Band Width	Modulation	RB Size	RB Offset	Max. output power(dBm)				Limit (W)
				814.7 MHz		823.3 MHz		
				dBm	W	dBm	W	
1.4	QPSK	1	0	23.49	0.223	23.35	0.216	100
		1	3	23.36	0.217	23.28	0.213	100
		1	5	23.31	0.214	23.22	0.210	100
		3	0	23.48	0.223	23.34	0.216	100
		3	1	23.42	0.220	23.36	0.217	100
		3	3	23.35	0.216	23.25	0.211	100
		6	0	22.38	0.173	22.28	0.169	100
	16QAM	1	0	22.67	0.185	22.52	0.178	100
		1	3	22.82	0.191	22.70	0.186	100
		1	5	22.51	0.178	22.43	0.175	100
		3	0	22.57	0.181	22.43	0.175	100
		3	1	22.54	0.179	22.44	0.175	100
		3	3	22.51	0.178	22.38	0.173	100
		6	0	21.46	0.140	21.36	0.137	100
	64QAM	1	0	21.45	0.140	21.39	0.138	100
		1	3	21.56	0.143	21.43	0.139	100
		1	5	21.64	0.146	21.49	0.141	100
		3	0	21.48	0.141	21.39	0.138	100
		3	1	21.48	0.141	21.40	0.138	100
		3	3	21.52	0.142	21.39	0.138	100
		6	0	20.43	0.110	20.32	0.108	100
	256QAM	1	0	18.52	0.071	18.41	0.069	100
		1	3	18.59	0.072	18.40	0.069	100
		1	5	18.50	0.071	18.35	0.068	100
		3	0	18.54	0.071	18.38	0.069	100
		3	1	18.48	0.070	18.34	0.068	100
		3	3	18.47	0.070	18.34	0.068	100
		6	0	18.43	0.070	18.31	0.068	100

Band Width	Modulation	RB Size	RB Offset	Max. output power(dBm)				Limit (W)
				815.5 MHz		822.5 MHz		
				dBm	W	dBm	W	
3	QPSK	1	0	23.43	0.220	23.32	0.215	100
		1	7	23.38	0.218	23.31	0.215	100
		1	14	23.33	0.215	23.21	0.209	100
		8	0	22.47	0.177	22.36	0.172	100
		8	3	22.49	0.177	22.35	0.172	100
		8	7	22.41	0.174	22.30	0.170	100
		15	0	22.46	0.176	22.36	0.172	100
	16QAM	1	0	22.67	0.185	22.61	0.182	100
		1	7	22.88	0.194	22.72	0.187	100
		1	14	22.66	0.185	22.54	0.179	100
		8	0	21.45	0.140	21.35	0.136	100
		8	3	21.41	0.138	21.36	0.137	100
		8	7	21.54	0.143	21.39	0.138	100
		15	0	21.49	0.141	21.38	0.137	100
	64QAM	1	0	21.53	0.142	21.40	0.138	100
		1	7	21.45	0.140	21.36	0.137	100
		1	14	21.64	0.146	21.44	0.139	100
		8	0	20.48	0.112	20.35	0.108	100
		8	3	20.52	0.113	20.36	0.109	100
		8	7	20.41	0.110	20.31	0.108	100
		15	0	20.40	0.110	20.33	0.108	100
	256QAM	1	0	18.50	0.071	18.43	0.070	100
		1	7	18.60	0.072	18.49	0.071	100
		1	14	18.38	0.069	18.32	0.068	100
		8	0	18.44	0.070	18.35	0.068	100
		8	3	18.41	0.069	18.35	0.068	100
		8	7	18.37	0.069	18.27	0.067	100
		15	0	18.41	0.069	18.31	0.068	100

Band Width	Modulation	RB Size	RB Offset	Max. output power(dBm)				Limit (W)
				816.5 MHz		821.5 MHz		
				dBm	W	dBm	W	
5	QPSK	1	0	23.77	0.238	23.67	0.233	100
		1	12	23.86	0.243	23.74	0.237	100
		1	24	23.70	0.234	23.64	0.231	100
		12	0	22.80	0.191	22.68	0.185	100
		12	6	22.83	0.192	22.70	0.186	100
		12	11	22.78	0.190	22.68	0.185	100
		25	0	22.79	0.190	22.64	0.184	100
	16QAM	1	0	23.08	0.203	22.89	0.195	100
		1	12	23.24	0.211	23.00	0.200	100
		1	24	23.04	0.201	22.95	0.197	100
		12	0	21.94	0.156	21.85	0.153	100
		12	6	21.77	0.150	21.69	0.148	100
		12	11	21.81	0.152	21.71	0.148	100
		25	0	21.76	0.150	21.63	0.146	100
	64QAM	1	0	21.95	0.157	21.82	0.152	100
		1	12	21.96	0.157	21.88	0.154	100
		1	24	21.85	0.153	21.75	0.150	100
		12	0	20.92	0.124	20.71	0.118	100
		12	6	20.80	0.120	20.64	0.116	100
		12	11	20.73	0.118	20.59	0.115	100
		25	0	20.69	0.117	20.61	0.115	100
	256QAM	1	0	18.97	0.079	18.77	0.075	100
		1	12	19.01	0.080	18.82	0.076	100
		1	24	18.67	0.074	18.64	0.073	100
		12	0	18.87	0.077	18.74	0.075	100
		12	6	18.83	0.076	18.65	0.073	100
		12	11	18.76	0.075	18.61	0.073	100
		25	0	18.72	0.074	18.68	0.074	100

Band Width	Modulation	RB Size	RB Offset	Max. output power(dBm)		Limit (W)
				819 MHz		
				dBm	W	
10	QPSK	1	0	23.83	0.242	100
		1	24	23.75	0.237	100
		1	49	23.59	0.229	100
		25	0	22.83	0.192	100
		25	12	22.77	0.189	100
		25	24	22.73	0.187	100
		50	0	22.70	0.186	100
	16QAM	1	0	22.99	0.199	100
		1	24	22.95	0.197	100
		1	49	22.83	0.192	100
		25	0	21.82	0.152	100
		25	12	21.76	0.150	100
		25	24	21.74	0.149	100
		50	0	21.67	0.147	100
	64QAM	1	0	22.06	0.161	100
		1	24	21.97	0.157	100
		1	49	21.70	0.148	100
		25	0	20.85	0.122	100
		25	12	20.79	0.120	100
		25	24	20.73	0.118	100
		50	0	20.72	0.118	100
	256QAM	1	0	18.86	0.077	100
		1	24	18.94	0.078	100
		1	49	18.60	0.072	100
		25	0	18.83	0.076	100
		25	12	18.72	0.074	100
		25	24	18.66	0.073	100
		50	0	18.69	0.074	100

Band Width	Modulation	RB Size	RB Offset	Max. output power(dBm)		Limit (W)
				821.5 MHz		
				dBm	W	
15	QPSK	1	0	23.47	0.222	100
		1	36	23.30	0.214	100
		1	74	23.52	0.225	100
		36	0	22.50	0.178	100
		36	18	22.41	0.174	100
		36	39	22.47	0.177	100
		75	0	22.52	0.179	100
	16QAM	1	0	22.86	0.193	100
		1	36	22.69	0.186	100
		1	74	22.61	0.182	100
		36	0	21.52	0.142	100
		36	18	21.45	0.140	100
		36	39	21.51	0.142	100
		75	0	21.46	0.140	100
	64QAM	1	0	21.53	0.142	100
		1	36	21.41	0.138	100
		1	74	21.50	0.141	100
		36	0	20.46	0.111	100
		36	18	21.57	0.144	100
		36	39	20.33	0.108	100
		75	0	20.47	0.111	100
	256QAM	1	0	18.70	0.074	100
		1	36	18.45	0.070	100
		1	74	18.68	0.074	100
		36	0	18.49	0.071	100
		36	18	18.48	0.070	100
		36	39	18.44	0.070	100
		75	0	18.52	0.071	100

8.2 EFFECTIVE RADIATED POWER

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol	Limit	ERP	
									W	W
814.7	LTE B26/ 1.4 MHz	QPSK	-30.27	30.57	-10.29	1.40	V	< 100	0.077	18.88
		16QAM	-30.93	29.91	-10.29	1.40	V		0.066	18.22
		64QAM	-32.04	28.80	-10.29	1.40	V		0.051	17.11
		256QAM	-35.14	25.70	-10.29	1.40	V		0.025	14.01
823.3		QPSK	-30.32	30.73	-10.25	1.41	V		0.081	19.07
		16QAM	-31.04	30.01	-10.25	1.41	V		0.069	18.35
		64QAM	-32.12	28.93	-10.25	1.41	V		0.053	17.27
		256QAM	-35.18	25.87	-10.25	1.41	V		0.026	14.21

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol	Limit	ERP	
									W	W
815.5	LTE B26/ 3 MHz	QPSK	-30.29	30.54	-10.29	1.41	V	< 100	0.077	18.85
		16QAM	-31.01	29.82	-10.29	1.41	V		0.065	18.13
		64QAM	-32.08	28.75	-10.29	1.41	V		0.051	17.06
		256QAM	-35.21	25.62	-10.29	1.41	V		0.025	13.93
822.5		QPSK	-30.26	30.76	-10.26	1.41	V		0.081	19.09
		16QAM	-30.98	30.04	-10.26	1.41	V		0.069	18.37
		64QAM	-32.04	28.98	-10.26	1.41	V		0.054	17.31
		256QAM	-35.18	25.84	-10.26	1.41	V		0.026	14.17

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol	Limit	ERP	
									W	W
816.5	LTE B26/ 5 MHz	QPSK	-30.31	30.48	-10.28	1.41	V	< 100	0.076	18.79
		16QAM	-31.02	29.77	-10.28	1.41	V		0.064	18.08
		64QAM	-32.07	28.72	-10.28	1.41	V		0.050	17.03
		256QAM	-35.20	25.59	-10.28	1.41	V		0.025	13.90
821.5		QPSK	-30.18	30.78	-10.26	1.41	V		0.082	19.11
		16QAM	-30.90	30.06	-10.26	1.41	V		0.069	18.39
		64QAM	-31.97	28.99	-10.26	1.41	V		0.054	17.32
		256QAM	-35.10	25.86	-10.26	1.41	V		0.026	14.19

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol	Limit	ERP	
									W	W
819.0	LTE B26/ 10 MHz	QPSK	-30.24	30.57	-10.27	1.41	V	< 100	0.077	18.89
		16QAM	-30.97	29.84	-10.27	1.41	V		0.065	18.16
		64QAM	-32.06	28.75	-10.27	1.41	V		0.051	17.07
		256QAM	-35.19	25.62	-10.27	1.41	V		0.025	13.94

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol	Limit	ERP	
									W	W
821.5	LTE B26/ 15 MHz	QPSK	-30.41	30.55	-10.26	1.41	V	< 7.00	0.077	18.88
		16QAM	-31.26	29.70	-10.26	1.41	V		0.064	18.03
		64QAM	-32.30	28.66	-10.26	1.41	V		0.050	16.99
		256QAM	-35.37	25.59	-10.26	1.41	V		0.025	13.92

Note

1. Limit: None (for reporting purposes only)

8.3 RADIATED SPURIOUS EMISSIONS

- ▣ MODE: LTE B26
- ▣ MODULATION SIGNAL: 5 MHz QPSK
- ▣ DISTANCE: 3 meters

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit
26715 (816.5)	1 633.00	-53.11	9.50	-63.46	1.96	V	-55.92	-13.00
	2 449.50	-56.12	10.30	-60.45	2.56	H	-52.71	-13.00
	3 266.00	-57.56	10.89	-57.51	2.92	H	-49.54	-13.00
26765 (821.5)	1 643.00	-53.50	9.60	-64.14	1.99	V	-56.53	-13.00
	2 464.50	-55.41	10.42	-60.37	2.55	H	-52.50	-13.00
	3 286.00	-57.32	12.01	-58.62	2.92	H	-49.54	-13.00

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
Band 26	1.4 MHz	823.3	QPSK	6	0	1.1000
			16QAM			1.1035
			64QAM			1.1003
			256QAM			1.0937
	3 MHz	822.5	QPSK	15		2.6970
			16QAM			2.7209
			64QAM			2.7109
			256QAM			2.7056
	5 MHz	821.5	QPSK	25		4.5220
			16QAM			4.5177
			64QAM			4.5282
			256QAM			4.5058
	10 MHz	819.0	QPSK	50		8.9814
			16QAM			8.9833
			64QAM			8.9843
			256QAM			8.9698
	15 MHz	821.5	QPSK	75		13.456
			16QAM			13.470
			64QAM			13.480
			256QAM			13.441

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 45 ~ 64.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
26	1.4	814.7	3.7269	27.976	-67.539	-39.563	-13.00
		823.3	3.7089	27.976	-67.193	-39.217	
	3	815.5	3.6850	27.976	-67.209	-39.233	
		822.5	3.7089	27.976	-67.279	-39.303	
	5	816.5	3.6860	27.976	-67.441	-39.465	
		821.5	3.7383	27.976	-67.387	-39.411	
	10	819.0	3.7010	27.976	-67.360	-39.384	
	15	821.5	3.1910	27.976	-67.312	-39.336	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 85 ~ 92.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor (dB) = Cable Loss + Ext. Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131


8.6 CHANNEL EDGE

- Plots of the EUT's Band Edge are shown Page 65 ~ 84.

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


- ▣ MODE: LTE 26
- ▣ OPERATING FREQUENCY: 814,700,000 Hz
- ▣ CHANNEL: 26697(1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	814 700 002	0.0	0.000 000	0.000
100 %		-30	814 700 005	3.1	0.000 000	0.004
100 %		-20	814 700 006	4.0	0.000 000	0.005
100 %		-10	814 700 000	-2.5	0.000 000	-0.003
100 %		0	814 700 004	2.1	0.000 000	0.003
100 %		+10	814 700 005	3.3	0.000 000	0.004
100 %		+30	814 700 004	2.0	0.000 000	0.002
100 %		+40	814 700 007	5.4	0.000 001	0.007
100 %		+50	814 700 006	4.2	0.000 001	0.005
Batt. Endpoint	3.300	+20	814 700 007	4.5	0.000 001	0.006




- ▣ MODE: LTE 26
- ▣ OPERATING FREQUENCY: 815,500,000 Hz
- ▣ CHANNEL: 26705(3 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	815 500 008	0.0	0.000 000	0.000
100 %		-30	815 500 004	-4.5	-0.000 001	-0.006
100 %		-20	815 500 004	-3.9	0.000 000	-0.005
100 %		-10	815 500 002	-5.6	-0.000 001	-0.007
100 %		0	815 499 999	-8.7	-0.000 001	-0.011
100 %		+10	815 499 996	-12.4	-0.000 002	-0.015
100 %		+30	815 499 997	-10.6	-0.000 001	-0.013
100 %		+40	815 500 001	-6.6	-0.000 001	-0.008
100 %		+50	815 499 997	-11.0	-0.000 001	-0.013
Batt. Endpoint		3.300	+20	815 499 998	-10.2	-0.000 001




- ▣ MODE: LTE 26
- ▣ OPERATING FREQUENCY: 816,500,000 Hz
- ▣ CHANNEL: 26715(5 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	816 499 995	0.0	0.000 000	0.000
100 %		-30	816 499 989	-5.5	-0.000 001	-0.007
100 %		-20	816 499 991	-4.1	-0.000 001	-0.005
100 %		-10	816 499 990	-5.2	-0.000 001	-0.006
100 %		0	816 499 988	-6.4	-0.000 001	-0.008
100 %		+10	816 499 988	-6.8	-0.000 001	-0.008
100 %		+30	816 499 989	-5.7	-0.000 001	-0.007
100 %		+40	816 499 991	-4.3	-0.000 001	-0.005
100 %		+50	816 499 992	-3.2	0.000 000	-0.004
Batt. Endpoint		3.300	+20	816 499 988	-6.5	-0.000 001




- ▣ MODE: LTE 26
- ▣ OPERATING FREQUENCY: 819,000,000 Hz
- ▣ CHANNEL: 26740(10 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	818 999 996	0.0	0.000 000	0.000
100 %		-30	818 999 992	-4.6	-0.000 001	-0.006
100 %		-20	818 999 990	-5.8	-0.000 001	-0.007
100 %		-10	818 999 990	-6.2	-0.000 001	-0.008
100 %		0	818 999 991	-4.9	-0.000 001	-0.006
100 %		+10	818 999 992	-4.6	-0.000 001	-0.006
100 %		+30	818 999 990	-6.0	-0.000 001	-0.007
100 %		+40	818 999 991	-5.1	-0.000 001	-0.006
100 %		+50	818 999 990	-5.8	-0.000 001	-0.007
Batt. Endpoint		3.300	+20	818 999 991	-5.4	-0.000 001



- ▣ MODE: LTE 26
- ▣ OPERATING FREQUENCY: 821,500,000 Hz
- ▣ CHANNEL: 26765(15 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	821 499 995	0.0	0.000 000	0.000
100 %		-30	821 499 987	-8.2	-0.000 001	-0.010
100 %		-20	821 499 988	-6.9	-0.000 001	-0.008
100 %		-10	821 499 990	-4.6	-0.000 001	-0.006
100 %		0	821 499 988	-6.9	-0.000 001	-0.008
100 %		+10	821 499 988	-6.3	-0.000 001	-0.008
100 %		+30	821 499 989	-6.0	-0.000 001	-0.007
100 %		+40	821 499 990	-4.4	-0.000 001	-0.005
100 %		+50	821 499 990	-4.4	-0.000 001	-0.005
Batt. Endpoint		3.300	+20	821 499 987	-8.2	-0.000 001



8.8 STADDLE CHANNEL

8.8.1 CONDUCTED OUTPUT POWER

Band Width	Modulation	RB Size	RB Offset	Max. output power(dBm)		Limit (W)
				824 MHz		
				dBm	W	
1.4	QPSK	1	0	23.22	0.210	100
		1	3	23.24	0.211	100
		1	5	23.18	0.208	100
		3	0	23.25	0.211	100
		3	1	23.26	0.212	100
		3	3	23.22	0.210	100
		6	0	22.24	0.168	100
	16QAM	1	0	22.45	0.176	100
		1	3	22.54	0.179	100
		1	5	22.47	0.177	100
		3	0	22.33	0.171	100
		3	1	22.32	0.171	100
		3	3	22.26	0.168	100
		6	0	21.34	0.136	100
	64QAM	1	0	21.34	0.136	100
		1	3	21.38	0.137	100
		1	5	21.34	0.136	100
		3	0	21.34	0.136	100
		3	1	21.34	0.136	100
		3	3	21.26	0.134	100
		6	0	20.26	0.106	100
	256QAM	1	0	18.25	0.067	100
		1	3	18.27	0.067	100
		1	5	18.20	0.066	100
		3	0	18.22	0.066	100
		3	1	18.25	0.067	100
		3	3	18.25	0.067	100
		6	0	18.20	0.066	100

Band Width	Modulation	RB Size	RB Offset	Max. output power(dBm)		Limit (W)
				824 MHz		
				dBm	W	
3	QPSK	1	0	23.20	0.209	100
		1	7	23.26	0.212	100
		1	14	23.14	0.206	100
		8	0	22.23	0.167	100
		8	3	22.21	0.167	100
		8	7	22.23	0.167	100
		15	0	22.20	0.166	100
	16QAM	1	0	22.47	0.177	100
		1	7	22.54	0.179	100
		1	14	22.35	0.172	100
		8	0	21.26	0.134	100
		8	3	21.26	0.134	100
		8	7	21.24	0.133	100
		15	0	21.24	0.133	100
	64QAM	1	0	21.32	0.136	100
		1	7	21.35	0.136	100
		1	14	21.28	0.134	100
		8	0	20.22	0.105	100
		8	3	20.23	0.105	100
		8	7	20.25	0.106	100
		15	0	20.22	0.105	100
	256QAM	1	0	18.27	0.067	100
		1	7	18.33	0.068	100
		1	14	18.28	0.067	100
		8	0	18.23	0.067	100
		8	3	18.27	0.067	100
		8	7	18.20	0.066	100
		15	0	18.20	0.066	100

Band Width	Modulation	RB Size	RB Offset	Max. output power(dBm)		Limit (W)
				824 MHz		
				dBm	W	
5	QPSK	1	0	23.55	0.226	100
		1	12	23.68	0.233	100
		1	24	23.56	0.227	100
		12	0	22.58	0.181	100
		12	6	22.61	0.182	100
		12	11	22.59	0.182	100
		25	0	22.58	0.181	100
	16QAM	1	0	22.76	0.189	100
		1	12	22.85	0.193	100
		1	24	22.88	0.194	100
		12	0	21.64	0.146	100
		12	6	21.60	0.145	100
		12	11	21.56	0.143	100
		25	0	21.58	0.144	100
	64QAM	1	0	21.67	0.147	100
		1	12	21.60	0.145	100
		1	24	21.69	0.148	100
		12	0	20.56	0.114	100
		12	6	20.59	0.115	100
		12	11	20.52	0.113	100
		25	0	20.56	0.114	100
	256QAM	1	0	18.62	0.073	100
		1	12	18.55	0.072	100
		1	24	18.60	0.072	100
		12	0	18.59	0.072	100
		12	6	18.53	0.071	100
		12	11	18.54	0.071	100
		25	0	18.51	0.071	100

Band Width	Modulation	RB Size	RB Offset	Max. output power(dBm)		Limit (W)
				824 MHz		
				dBm	W	
10	QPSK	1	0	23.58	0.228	100
		1	24	23.54	0.226	100
		1	49	23.56	0.227	100
		25	0	22.60	0.182	100
		25	12	22.63	0.183	100
		25	24	22.64	0.184	100
		50	0	22.65	0.184	100
	16QAM	1	0	22.85	0.193	100
		1	24	22.76	0.189	100
		1	49	22.81	0.191	100
		25	0	21.62	0.145	100
		25	12	21.58	0.144	100
		25	24	21.60	0.145	100
		50	0	21.60	0.145	100
	64QAM	1	0	21.73	0.149	100
		1	24	21.59	0.144	100
		1	49	21.68	0.147	100
		25	0	20.56	0.114	100
		25	12	20.63	0.116	100
		25	24	20.52	0.113	100
		50	0	20.59	0.115	100
	256QAM	1	0	18.70	0.074	100
		1	24	18.61	0.073	100
		1	49	18.73	0.075	100
		25	0	18.58	0.072	100
		25	12	18.65	0.073	100
		25	24	18.45	0.070	100
		50	0	18.57	0.072	100

8.8.2 EFFECTIVE RADIATED POWER

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
824.0	LTE B26/ 1.4 MHz	QPSK	-30.28	30.86	-10.25	1.41	V	< 7.00	0.083	19.20
		16QAM	-31.03	30.11	-10.25	1.41	V		0.070	18.45
		64QAM	-32.09	29.05	-10.25	1.41	V		0.055	17.39
		256QAM	-35.15	25.99	-10.25	1.41	V		0.027	14.33

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
824.0	LTE B26/ 3 MHz	QPSK	-30.26	30.88	-10.25	1.41	V	< 7.00	0.084	19.22
		16QAM	-30.98	30.16	-10.25	1.41	V		0.071	18.50
		64QAM	-32.06	29.08	-10.25	1.41	V		0.055	17.42
		256QAM	-35.18	25.96	-10.25	1.41	V		0.027	14.30

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
824.0	LTE B26/ 5 MHz	QPSK	-30.21	30.93	-10.25	1.41	V	< 7.00	0.085	19.27
		16QAM	-30.99	30.15	-10.25	1.41	V		0.071	18.49
		64QAM	-32.02	29.12	-10.25	1.41	V		0.056	17.46
		256QAM	-35.21	25.93	-10.25	1.41	V		0.027	14.27

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
824.0	LTE B26/ 10 MHz	QPSK	-30.18	30.96	-10.25	1.41	V	< 7.00	0.085	19.30
		16QAM	-30.95	30.19	-10.25	1.41	V		0.071	18.53
		64QAM	-32.01	29.13	-10.25	1.41	V		0.056	17.47
		256QAM	-35.08	26.06	-10.25	1.41	V		0.028	14.40

8.8.3 RADIATED SPURIOUS EMISSIONS

- ▣ MODE: LTE B26
- ▣ MODULATION SIGNAL: 10 MHz QPSK
- ▣ DISTANCE: 3 meters

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit
26790 (824.0)	1 648.00	-52.95	9.70	-63.54	2.04	H	-55.88	-13.00
	2 472.00	-55.60	10.46	-60.62	2.54	H	-52.70	-13.00
	3 296.00	-57.27	12.07	-58.32	2.95	H	-49.20	-13.00

8.8.4 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
26	1.4	824.0	3.7219	27.976	-67.441	-39.465	-13.00
	3		3.6820	27.976	-67.314	-39.338	
	5		3.7139	27.976	-67.618	-39.642	
	10		3.6930	27.976	-67.340	-39.364	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 94 ~ 97.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor (dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131

8.8.5 CHANNEL EDGE(Part90)

- Test Channel : 26790(824.0MHz)

Plots of the EUT's Band Edge are shown Page 98 ~ 109.


8.8.6 BAND EDGE(Part22)

- Test Channel : 26790(824.0 MHz)


- Plots of the EUT's Band Edge are shown Page 110 ~ 117.

9. TEST PLOTS


BAND 26. Occupied Bandwidth Plot (1.4 M BW Ch.26783 QPSK RB 6_0)




BAND 26. Occupied Bandwidth Plot (1.4 M BW Ch.26783 16QAM RB 6_0)




BAND 26. Occupied Bandwidth Plot (1.4 M BW Ch.26783 64QAM RB 6_0)




BAND 26. Occupied Bandwidth Plot (1.4 M BW Ch.26783 256QAM RB 6_0)




BAND 26. Occupied Bandwidth Plot (3 M BW Ch.26775 QPSK RB 15_0)




BAND 26. Occupied Bandwidth Plot (3 M BW Ch.26775 16QAM RB 15_0)




BAND 26. Occupied Bandwidth Plot (3 M BW Ch.26775 64QAM RB 15_0)




BAND 26. Occupied Bandwidth Plot (3 M BW Ch.26775 256QAM RB 15_0)




BAND 26. Occupied Bandwidth Plot (5 M BW Ch.26765 QPSK RB 25_0)




BAND 26. Occupied Bandwidth Plot (5 M BW Ch.26765 16QAM RB 25_0)




BAND 26. Occupied Bandwidth Plot (5 M BW Ch.26765 64QAM RB 25_0)




BAND 26. Occupied Bandwidth Plot (5 M BW Ch.26765 256QAM RB 25_0)




BAND 26. Occupied Bandwidth Plot (10 M BW Ch.26740 QPSK RB 50_0)




BAND 26. Occupied Bandwidth Plot (10 M BW Ch.26740 16QAM RB 50_0)




BAND 26. Occupied Bandwidth Plot (10 M BW Ch.26740 64QAM RB 50_0)




BAND 26. Occupied Bandwidth Plot (10 M BW Ch.26740 256QAM RB 50_0)




BAND 26. Occupied Bandwidth Plot (15 M BW Ch.26765 QPSK RB 75_0)




BAND 26. Occupied Bandwidth Plot (15 M BW Ch.26765 16QAM RB 75_0)




BAND 26. Occupied Bandwidth Plot (15 M BW Ch.26765 64QAM RB 75_0)




BAND 26. Occupied Bandwidth Plot (15 M BW Ch.26765 256QAM RB 75_0)




BAND 26. Lower Channel Edge Plot (1.4 M BW Ch.26697 QPSK RB 1, Offset 0)




BAND 26. Lower Channel Edge Plot (1.4 M BW Ch.26697 QPSK_RB6_Offset 0)




BAND 26. Lower Channel Edge Plot (3 M BW Ch.26705 QPSK RB 1, Offset 0)




BAND 26. Lower Channel Edge Plot (3 M BW Ch.26705 QPSK_RB15_Offset 0)




BAND 26. Lower Channel Edge Plot (5 M BW Ch.26715 QPSK RB 1, Offset 0)




BAND 26. Lower Channel Edge Plot (5 M BW Ch.26715 QPSK_RB25_Offset 0)




BAND 26. Low Channel Edge Plot (10 M BW Ch.26740 QPSK RB 1, Offset 0)




BAND 26. Low Channel Edge Plot (10 M BW Ch.26740 QPSK_RB50_Offset 0)




BAND 26. Mid Channel Edge Plot (10 M BW Ch. 26740 QPSK_RB1_Offset 49)




BAND 26. Low Channel Edge Plot (15 M BW Ch.26765 QPSK RB 1, Offset 0)




BAND 26. Low Channel Edge Plot (15 M BW Ch.26765 QPSK RB 75, Offset0)



BAND 26. Mid Channel Edge Plot (15 M BW Ch.26765 QPSK_RB1_Offset 74)




BAND 26. Mid Band Edge Plot (15 M BW Ch.26765 QPSK RB 1, Offset74)




BAND 26. Mid Band Edge Plot (15 M BW Ch.26765 QPSK_RB75_Offset 0)




BAND 26. Upper Channel Edge Plot (1.4 M BW Ch.26783 QPSK_RB1_Offset 5)




BAND 26. Upper Channel Edge Plot (1.4 M BW Ch.26783 QPSK_RB6_Offset 0)




BAND 26. Upper Channel Edge Plot (3 M BW Ch.26775 QPSK_RB1_Offset 14)




BAND 26. Upper Channel Edge Plot (3 M BW Ch.26775 QPSK_RB15_Offset 0)




BAND 26. Upper Channel Edge Plot (5 M BW Ch.26765 QPSK_RB1_Offset 24)




BAND 26. Upper Channel Edge Plot (5 M BW Ch.26765 QPSK_RB25_Offset 0)




BAND 26. Conducted Spurious (26697 ch_1.4 MHz_QPSK_RB 1_0)




BAND 26. Conducted Spurious (26783 ch_1.4 MHz_QPSK_RB 1_0)




BAND 26. Conducted Spurious (26705 ch_3 MHz_QPSK_RB 1_0)




BAND 26. Conducted Spurious (26775 ch_3 MHz_QPSK_RB 1_0)




BAND 26. Conducted Spurious (26715 ch_5 MHz_QPSK_RB 1_0)




BAND 26. Conducted Spurious (26765 ch_5 MHz_QPSK_RB 1_0)



BAND 26. Conducted Spurious (26740 ch_10 MHz_QPSK_RB 1_0)




BAND 26. Conducted Spurious (26765 ch_15 MHz_QPSK_RB 1_0)




10. TEST PLOTS (STRADDLE CHANNEL)


BAND 26. Conducted Spurious (1.4 MHz_QPSK_RB 1_0)




BAND 26. Conducted Spurious (3 MHz_QPSK_RB 1_0)




BAND 26. Conducted Spurious (5 MHz_QPSK_RB 1_0)




BAND 26. Conducted Spurious (10 MHz_QPSK_RB 1_0)




BAND 26. Channel Edge (1.4 MHz_QPSK_RB 1_0)




BAND 26. Channel Edge (1.4 MHz_QPSK_RB 1_5)




BAND 26. Channel Edge (1.4 MHz_QPSK_Full RB)




BAND 26. Channel Edge (3 MHz_QPSK_RB 1_0)




BAND 26. Channel Edge (3 MHz_QPSK_RB 1_14)




BAND 26. Channel Edge (3 MHz_QPSK_Full RB)




BAND 26. Channel Edge (5 MHz_QPSK_RB 1_0)




BAND 26. Channel Edge (5 MHz_QPSK_RB 1_24)




BAND 26. Channel Edge (5 MHz_QPSK_Full RB)




BAND 26. Channel Edge (10 MHz_QPSK_RB 1_0)




BAND 26. Channel Edge (10 MHz_QPSK_RB 1_49)




BAND 26. Channel Edge (10 MHz_QPSK_Full RB)




BAND 26. Band Edge (1.4 MHz_QPSK_RB 1_5)



BAND 26. Band Edge (1.4 MHz_QPSK_FullIRB)



BAND 26. Band Edge (3 MHz_QPSK_RB 1_14)



BAND 26. Band Edge (3 MHz_QPSK_ Full RB)




BAND 26. Band Edge (5 MHz_QPSK_RB 1_24)



BAND 26. Band Edge (5 MHz_QPSK_ Full RB)



BAND 26. Band Edge (10 MHz_QPSK_RB 1_49)



BAND 26. Band Edge (10 MHz_QPSK_ Full RB)



11 ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2210-FC017-P