



Plot 7-116. Conducted Spurious Plot (802.11b – Ch. 11) SISO ANT 2




Plot 7-117. Conducted Spurious Plot (802.11b – Ch. 11) SISO ANT 2

FCC ID: A3LSMS911U	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 84 of 116




Plot 7-118. Conducted Spurious Plot (802.11b – Ch. 1) MIMO ANT 1




Plot 7-119. Conducted Spurious Plot (802.11b – Ch. 1) MIMO ANT 1

FCC ID: A3LSMS911U	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 85 of 116




Plot 7-120. Conducted Spurious Plot (802.11b – Ch. 6) MIMO ANT 1




Plot 7-121. Conducted Spurious Plot (802.11b – Ch. 6) MIMO ANT 1

FCC ID: A3LSMS911U	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 86 of 116




Plot 7-122. Conducted Spurious Plot (802.11b – Ch. 11) MIMO ANT 1




Plot 7-123. Conducted Spurious Plot (802.11b – Ch. 11) MIMO ANT 1

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 87 of 116




Plot 7-124. Conducted Spurious Plot (802.11b – Ch. 1) MIMO ANT 2




Plot 7-125. Conducted Spurious Plot (802.11b – Ch. 1) MIMO ANT 2

FCC ID: A3LSMS911U	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 88 of 116




Plot 7-126. Conducted Spurious Plot (802.11b – Ch. 6) MIMO ANT 2




Plot 7-127. Conducted Spurious Plot (802.11b – Ch. 6) MIMO ANT 2

FCC ID: A3LSMS911U	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 89 of 116



Plot 7-128. Conducted Spurious Plot (802.11b – Ch. 11) MIMO ANT 2



Plot 7-129. Conducted Spurious Plot (802.11b – Ch. 11) MIMO ANT 2

FCC ID: A3LSMS911U	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 90 of 116

## 7.7 Radiated Spurious Emission Measurements – Above 1 GHz

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

***All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-11 per Section 15.209 and RSS-Gen (8.9).***

Frequency	Field Strength [ $\mu\text{V/m}$ ]	Measured Distance [Meters]
Above 960.0 MHz	500	3

**Table 7-11. Radiated Limits**

### Test Procedures Used

ANSI C63.10-2013 – Section 6.6.4.3  
KDB 558074 D01 v05r02 – Sections 8.6, 8.7

### Test Settings

#### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be  $\geq 2 \times \text{span/RBW}$ )
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces

#### Peak Field Strength Measurements


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 91 of 116



### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-6. Test Instrument & Measurement Setup**

### Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 D01 v05r02 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in Section 15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-11.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. Radiated spurious emissions were investigated while operating in MIMO mode, however, it was determined that single antenna operation produced the worst case emissions. Since the emissions

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 92 of 116



produced from MIMO operation were found to be more than 20dB below the limit, the MIMO emissions are not reported.

8. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
9. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

**Sample Calculations**

**Determining Spurious Emissions Levels**

- o Field Strength Level  $_{[dB_{\mu V/m}]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- o  $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- o  $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB_{\mu V/m}]} - \text{Limit }_{[dB_{\mu V/m}]}$


**Radiated Band Edge Measurement Offset**

- o The amplitude offset shown in the radiated restricted band edge plots in Section 7.7 was calculated using the formula:  
 $\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$


FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 93 of 116

### 7.7.1 SISO ANT 2 Radiated Spurious Emission Measurements


§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]



**Plot 7-130. Radiated Spurious Plot above 1GHz (802.11b – Ch. 1) SISO ANT 2**




**Plot 7-131. Radiated Spurious Plot above 1GHz (802.11b – Ch. 6) SISO ANT 2**



**Plot 7-132. Radiated Spurious Plot above 1GHz (802.11b – Ch. 11) SISO ANT 2**

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 94 of 116

**Radiated Spurious Emissions Measurements (Above 18GHz)**  
**§15.209; RSS-Gen [8.9]**



**Plot 7-133. Radiated Spurious Plot above 18GHz SISO ANT 2**

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 95 of 116



## Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11b  
 Worst Case Transfer Rate: 1 Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2412MHz  
 Channel: 01

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4824.00	Avg	H	212	305	-74.72	4.29	36.57	53.98	-17.41
4824.00	Peak	H	212	305	-70.42	4.29	40.87	73.98	-33.11
12060.00	Avg	H	-	-	-75.96	12.99	44.03	53.98	-9.95
12060.00	Peak	H	-	-	-71.12	12.99	48.87	73.98	-25.11

**Table 7-12. Radiated Measurements SISO ANT2**

Worst Case Mode: 802.11b  
 Worst Case Transfer Rate: 1 Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2437MHz  
 Channel: 06

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4874.00	Avg	H	288	81	-75.10	4.30	36.20	53.98	-17.78
4874.00	Peak	H	288	81	-71.21	4.30	40.09	73.98	-33.89
7311.00	Avg	H	-	-	-75.75	7.45	38.70	53.98	-15.28
7311.00	Peak	H	-	-	-71.52	7.45	42.93	73.98	-31.05
12185.00	Avg	H	-	-	-76.51	13.41	43.90	53.98	-10.08
12185.00	Peak	H	-	-	-72.07	13.41	48.34	73.98	-25.64

**Table 7-13. Radiated Measurements SISO ANT2**

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 96 of 116

Worst Case Mode: 802.11b  
Worst Case Transfer Rate: 1 Mbps  
Distance of Measurements: 3 Meters  
Operating Frequency: 2462MHz  
Channel: 11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4924.00	Avg	H	227	28	-71.97	4.25	39.28	53.98	-14.70
4924.00	Peak	H	227	28	-70.08	4.25	41.17	73.98	-32.81
7386.00	Avg	H	-	-	-75.46	7.35	38.89	53.98	-15.09
7386.00	Peak	H	-	-	-71.10	7.35	43.25	73.98	-30.73
12310.00	Avg	H	-	-	-76.54	13.56	44.02	53.98	-9.96
12310.00	Peak	H	-	-	-72.00	13.56	48.56	73.98	-25.42

**Table 7-14. Radiated Measurements SISO ANT2**

Worst Case Mode: 802.11b  
Worst Case Transfer Rate: 1 Mbps  
Distance of Measurements: 3 Meters  
Operating Frequency: 2462MHz  
Channel: 11


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4924.00	Avg	H	-	-	-78.52	4.25	32.73	53.98	-21.25
4924.00	Peak	H	-	-	-66.85	4.25	44.40	73.98	-29.58
7386.00	Avg	H	-	-	-79.26	7.35	35.09	53.98	-18.89
7386.00	Peak	H	-	-	-68.76	7.35	45.59	73.98	-28.39
12310.00	Avg	H	-	-	-81.26	13.56	39.30	53.98	-14.68
12310.00	Peak	H	-	-	-70.25	13.56	50.31	73.98	-23.67

**Table 7-15. Radiated Measurements SISO ANT 2 With WCP**


FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 97 of 116

## 7.7.2 MIMO Radiated Spurious Emission Measurements


§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]



**Plot 7-134. Radiated Spurious Plot above 1GHz (802.11b – Ch. 1) MIMO**




**Plot 7-135. Radiated Spurious Plot above 1GHz (802.11b – Ch. 6) MIMO**



**Plot 7-136. Radiated Spurious Plot above 1GHz (802.11b – Ch. 11) MIMO**

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 98 of 116

**Radiated Spurious Emissions Measurements (Above 18GHz)**  
§15.209; RSS-Gen [8.9]



**Plot 7-137. Radiated Spurious Plot above 18GHz MIMO**

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 99 of 116





## Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11b  
 Worst Case Transfer Rate: 6 Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2412MHz  
 Channel: 01

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4824.00	Avg	H	124	33	-72.32	4.29	38.97	53.98	-15.01
4824.00	Peak	H	124	33	-67.61	4.29	43.68	73.98	-30.30
12060.00	Avg	H	-	-	-80.44	12.99	39.55	53.98	-14.43
12060.00	Peak	H	-	-	-74.00	12.99	45.99	73.98	-27.99

Table 7-16. Radiated Measurements MIMO

Worst Case Mode: 802.11b  
 Worst Case Transfer Rate: 6 Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2437MHz  
 Channel: 06

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4874.00	Avg	H	175	345	-73.55	4.30	37.75	53.98	-16.23
4874.00	Peak	H	175	345	-69.49	4.30	41.81	73.98	-32.17
7311.00	Avg	H	-	-	-78.07	7.45	36.38	53.98	-17.60
7311.00	Peak	H	-	-	-72.21	7.45	42.24	73.98	-31.74
12185.00	Avg	H	-	-	-80.29	13.41	40.12	53.98	-13.86
12185.00	Peak	H	-	-	-73.64	13.41	46.77	73.98	-27.21

Table 7-17. Radiated Measurements MIMO

FCC ID: A3LSMS911U	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 100 of 116

Worst Case Mode: 802.11b  
Worst Case Transfer Rate: 6 Mbps  
Distance of Measurements: 3 Meters  
Operating Frequency: 2462MHz  
Channel: 11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4924.00	Avg	H	156	32	-73.64	4.25	37.61	53.98	-16.37
4924.00	Peak	H	156	32	-69.05	4.25	42.20	73.98	-31.78
7386.00	Avg	H	-	-	-78.54	7.35	35.81	53.98	-18.17
7386.00	Peak	H	-	-	-72.18	7.35	42.17	73.98	-31.81
12310.00	Avg	H	-	-	-80.55	13.56	40.01	53.98	-13.97
12310.00	Peak	H	-	-	-74.44	13.56	46.12	73.98	-27.86

**Table 7-18. Radiated Measurements MIMO**

Worst Case Mode: 802.11b  
Worst Case Transfer Rate: 6 Mbps  
Distance of Measurements: 3 Meters  
Operating Frequency: 2412MHz  
Channel: 01

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4824.00	Avg	H	154	309	-75.62	4.29	35.67	53.98	-18.31
4824.00	Peak	H	154	309	-66.37	4.29	44.92	73.98	-29.06
12060.00	Avg	H	-	-	-80.74	12.99	39.25	53.98	-14.73
12060.00	Peak	H	-	-	-69.16	12.99	50.83	73.98	-23.15

**Table 7-19. Radiated Measurements MIMO with WCP**


FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 101 of 116

### 7.7.3 SISO ANT 2 Radiated Restricted Band Edge Measurements


§15.205 §15.209; RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1




**Plot 7-138. Radiated Restricted Lower Band Edge Measurement SISO ANT2 (Average)**




**Plot 7-139. Radiated Restricted Lower Band Edge Measurement SISO ANT2 (Peak)**

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2417MHz
Channel:	2



**Plot 7-140. Radiated Restricted Lower Band Edge Measurement SISO ANT2 (Average)**




**Plot 7-141. Radiated Restricted Lower Band Edge Measurement SISO ANT2 (Peak)**


FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 102 of 116



Worst Case Mode: 802.11ax  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2452MHz  
 Channel: 9




**Plot 7-142. Radiated Restricted Upper Band Edge Measurement SISO ANT2 (Average)**




**Plot 7-143. Radiated Restricted Upper Band Edge Measurement SISO ANT2 (Peak)**

Worst Case Mode: 802.11ax  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2457MHz  
 Channel: 10




**Plot 7-144. Radiated Restricted Upper Band Edge Measurement SISO ANT2 (Average)**




**Plot 7-145. Radiated Restricted Upper Band Edge Measurement SISO ANT2 (Peak)**

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 103 of 116

Worst Case Mode: 802.11ax  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2462MHz  
 Channel: 11



**Plot 7-146. Radiated Restricted Upper Band Edge Measurement SISO ANT2 (Average)**



**Plot 7-147. Radiated Restricted Upper Band Edge Measurement SISO ANT2 (Peak)**


FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 104 of 116

### 7.7.4 MIMO Radiated Restricted Band Edge Measurements


§15.205 §15.209; RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode:	802.11n
Worst Case Transfer Rate:	MCS8
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	1




**Plot 7-148. Radiated Restricted Lower Band Edge Measurement MIMO (Average)**




**Plot 7-149. Radiated Restricted Lower Band Edge Measurement MIMO (Peak)**

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	2417MHz
Channel:	2




**Plot 7-150. Radiated Restricted Lower Band Edge Measurement MIMO (Average)**




**Plot 7-151. Radiated Restricted Lower Band Edge Measurement MIMO (Peak)**

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 105 of 116

Worst Case Mode: 802.11ax  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2452MHz  
 Channel: 9




**Plot 7-152. Radiated Restricted Lower Band Edge Measurement MIMO (Average)**




**Plot 7-153. Radiated Restricted Lower Band Edge Measurement MIMO (Peak)**

Worst Case Mode: 802.11ax  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2457MHz  
 Channel: 10




**Plot 7-154. Radiated Restricted Lower Band Edge Measurement MIMO (Average)**




**Plot 7-155. Radiated Restricted Lower Band Edge Measurement MIMO (Peak)**

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 106 of 116

Worst Case Mode: 802.11g  
 Worst Case Transfer Rate: 12Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2462MHz  
 Channel: 11




**Plot 7-156. Radiated Restricted Upper Band Edge Measurement MIMO (Average)**




**Plot 7-157. Radiated Restricted Upper Band Edge Measurement MIMO (Peak)**

Worst Case Mode: 802.11n  
 Worst Case Transfer Rate: MCS8  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2412MHz  
 Channel: 1



**Plot 7-158. Radiated Restricted Upper Band Edge Measurement MIMO (Average) with WCP**



**Plot 7-159. Radiated Restricted Upper Band Edge Measurement MIMO (Peak) with WCP**

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 107 of 116



## 7.8 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

**All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-20 per Section 15.209 and RSS-Gen (8.9).**

Frequency	Field Strength [ $\mu\text{V/m}$ ]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

**Table 7-20. Radiated Limits**

### Test Procedures Used

ANSI C63.10-2013

### Test Settings


#### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize


FCC ID: A3LSMS911U	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 108 of 116

**Test Setup**

The EUT and measurement equipment were set up as shown in the diagrams below.



**Figure 7-7. Radiated Test Setup < 30Mhz**



**Figure 7-8. Radiated Test Setup < 1GHz**

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 109 of 116


**Test Notes**

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen(8.10) are below the limit shown in Table 7-20.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2209010096-11.A3L	<b>Test Dates:</b> 09/02/2022 - 11/08/2022	<b>EUT Type:</b> Portable Handset	Page 110 of 116

## Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-160. Radiated Spurious Plot below 1GHz MIMO

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
94.75	Quasi-Peak	H	-	-	-96.85	15.89	26.04	43.52	-17.48

Table 7-21. Radiated Spurious Emissions below 1GHz MIMO

FCC ID: A3LSMS911U	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 111 of 116

## 7.9 Line-Conducted Test Data

§15.207; RSS-Gen [8.8]

### Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

**All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).**

Frequency of emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

**Table 7-22. Conducted Limits**

\*Decreases with the logarithm of the frequency.

### Test Procedures Used

ANSI C63.10-2013, Section 6.2

### Test Settings

#### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

#### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMS911U	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 112 of 116

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-9. Test Instrument & Measurement Setup


### Test Notes

1. All modes of operation were investigated, and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz is specified in Part 15.207 and RSS-Gen(8.8).
3.  $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4.  $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5.  $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.
8. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 113 of 116




Plot 7-161. Line Conducted Plot with 802.11b (L1)




Plot 7-162. Line Conducted Plot with 802.11b (N)

FCC ID: A3LSMS911U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset	Page 114 of 116	



Plot 7-163. Line Conducted Plot with 802.11b (L1) with WCP



Plot 7-164. Line Conducted Plot with 802.11b (N) with WCP

FCC ID: A3LSMS911U		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2209010096-11.A3L	Test Dates: 09/02/2022 - 11/08/2022	EUT Type: Portable Handset		Page 115 of 116



## 8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMS911U** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules.

FCC ID: A3LSMS911U	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2209010096-11.A3L	<b>Test Dates:</b> 09/02/2022 - 11/08/2022	<b>EUT Type:</b> Portable Handset	Page 116 of 116