



**FCC 47 CFR § 2.1091**

**RF EVALUATION REPORT (MPE)**

**FOR**

**GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac, NFC, WPT and UWB**

**MODEL NUMBER: SM-S916B/DS, SM-S916B**

**FCC ID: A3LSMS916B**

**REPORT NUMBER: 4790541040-S3V1**

**ISSUE DATE: 10/24/2022**

*Prepared for*

**SAMSUNG ELECTRONICS CO., LTD.  
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,  
GYEONGGI-DO, 16677, KOREA**

*Prepared by*

**UL Korea, Ltd.**

**26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea**

**Suwon Test Site: UL Korea, Ltd. Suwon Laboratory  
218 Maeyeong-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16675, Korea**

**TEL: (031) 337-9902**

**FAX: (031) 213-5433**



**Testing Laboratory**

**TL-637**

**Revision History**

Rev.	Date	Revisions	Revised By
V1	10/24/2022	Initial Issue	-

**Table of Contents**

1. **Attestation of SAR Characterization** ..... 4

2. **Test Methodology**..... 5

3. **Facilities and Accreditation** ..... 5

4. **Equipment Under Test** ..... 5

4.1. **Description of EUT** ..... 5

4.2. **Worst-case configuration** ..... 5

4.3. **KDB 680106 D01 SECTION 5.b) EQUIPMENT APPROVAL CONSIDERATIONS**..... 6

4.4. **Description of Test setup** ..... 7

5. **Test and Measurement equipment**..... 10

6. **Maximum Permissive RF exposure**..... 10

6.1. **FCC Limits and Summary** ..... 10

6.1.1. **FCC Limits** ..... 10

6.2. **Test Results**..... 11

6.2.1. **FCC RF Exposure**..... 11

6.2.2. **FCC SUMMARY OF RESULTS** ..... 13

**Appendixes** ..... 14



*4790541040-S3 FCC Report MPE\_App A\_Test setup photos* ..... 14

# 1. Attestation of SAR Characterization

Applicant Name	SAMSUNG ELECTRONICS CO.,LTD.
FCC ID	A3LSMS916B
Model Number	SM-S916B/DS< SM-S916B
Applicable Standards	FCC 47 CFR § 2.1091 KDB 680106 D01 RF Exposure Wireless Charging Apps
Date Tested	10/5/2022
Test Results	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government

Approved & Released By: 	Prepared By: 
Justin Park Operations Leader UL Korea, Ltd. Suwon Laboratory	Eunji Choi Laboratory Test Engineer UL Korea, Ltd. Suwon Laboratory

## 2. Test Methodology

All calculations were made in accordance with FCC OET Bulletin 65 Edition 97-01.

## 3. Facilities and Accreditation

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro
<input checked="" type="checkbox"/> Shield Room 1

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <https://www.iasonline.org/wp-content/uploads/2017/05/TL-637-cert-New.pdf>.

## 4. Equipment Under Test

### 4.1. Description of EUT

The EUT has WPT (Wireless Power Transfer) feature which has inductive charging coil to charge phone or watch. The charging frequency is between 110 kHz to 148 kHz, and the maximum power consumption is 9.0 W in charging status.

### 4.2. Worst-case configuration

Test configuration	Description
DUT to Phone test configuration 1	Charging from Phone to DUT
DUT to Phone test configuration 2	Charging from Phone to DUT (TA Charging from DUT)
DUT to Phone test configuration 3 (Cross position)	Charging from Phone to DUT
DUT to Phone test configuration 4 (Cross position)	Charging from Phone to DUT (TA Charging from DUT)
DUT to Watch test configuration 5	Charging from Watch to DUT
DUT to Watch test configuration 6	Charging from Watch to DUT (TA Charging from DUT)

#### Note:

Configuration 2, 4 and 6 were tested with the worst case of configuration 1, 3 and 5.

**4.3. KDB 680106 D01 SECTION 5.b) EQUIPMENT APPROVAL CONSIDERATIONS**

Requirement	Device informations
(1) Power transfer frequency is less than 1 MHz.	Yes. Operating Frequency is between 110kHz to 148 kHz.
(2) Output power from each primary coil is less than or equal to 15 watts.	Yes. Maximum power is 9.0 Watts.
(3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.	Yes.
(4) Client device is placed directly in contact with the transmitter.	Yes.
(5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes.
(6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Yes. The aggregate field at 15 cm or 20cm from the device are 10.06 % of the FCC H field limit.

## 4.4. Description of Test setup

### SUPPORT EQUIPMENT & PERIPHERALS

SUPPROT EQUIPMENT & PERIPHERALS LIST				
Description	Manufacturer	Model	Serial Numver	FCC ID
Phone	Samsung Electronics Co., Ltd.	SM-G986B/DS	R3CMB0C70XN	A3LSMG986B
Watch	Samsung Electronics Co., Ltd.	SM-R835F	RFAM90ZXFTF	A3LSMR835
Traver Adapter	Samsung Electronics Co., Ltd.	EP-TA800	R37N9BV0382HM3	DoC
USB Data Cable	Samsung Electronics Co., Ltd.	EP-DN980BBE	N/A	-

### TEST SETUP


The following three modes are tested in test configurations

Mode
Operating (SUPPORT Equipment, <10% Power Charging)
Operating (SUPPORT Equipment, 50~55% Power Charging)
Operating (SUPPORT Equipment, 90~95% Power Charging)


**MEASUREMENT TEST SETUP**

The measurement was taken using a probe placed 15 cm surrounding the device and 20 cm above the top surface of the EUT. Measurements were taken the top (charger below/above client) and all sides of the EUT per KDB680106 D01.

**DUT to phone test Configuration 1 & 2**




**DUT to phone test Configuration 3 & 4**





DUT to Watch test Configuration 5 & 6



### 5. Test and Measurement equipment

The following test and measurement equipment was used for the tests documented in this report;

Test equipment (Measurement probe)				
Description	Manufacturer	Model	S/N	Cal due.
E-H Field Analyzer	Narda	EHP-200AC	170WX91008	8/23/2023

### 6. Maximum Permissible RF exposure

#### 6.1. FCC Limits and Summary

##### 6.1.1. FCC Limits

§ 1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in § 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of § 2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

## 6.2. Test Results

### 6.2.1. FCC RF Exposure

#### H-FIELD MEASUREMENTS

Note: Peak measurement were performed. Additional test was performed in each Test mode by moving the probe surrounding the device to find the maximum exposure.

#### TEST results of DUT to phone test Configuration 1 & 2

#### FCC RF Exposure Result

Test Configuration	Test mode	Test distance	Test Position	H-Field Limit (A/m)	H-Field meas. data (A/m)			
Configuration 1	Operating Real Product (Power <10% charging)	15 cm probe to edges of EUT and 20 cm probe to top surface of the EUT	Top - charger above client	1.63	0.0377			
			Top - charger below client		0.0389			
			Edge 1		0.0381			
			Edge 2		0.0377			
			Edge 3		0.0374			
			Edge 4		0.0366			
			Max		0.0389			
	Operating Real Product (Power 50~55% charging)		Top - charger above client		0.0385			
			Top - charger below client		0.0357			
			Edge 1		0.0389			
			Edge 2		0.0354			
			Edge 3		0.0374			
			Edge 4		0.0374			
			Max		0.0389			
	Operating Real Product (Power 90~95% charging)		Top - charger above client		0.0389			
			Top - charger below client		<b>0.0397</b>			
			Edge 1		0.0385			
			Edge 2		0.0381			
			Edge 3		0.0348			
			Edge 4		0.0381			
			Max		0.0397			
	Configuration 2		Operating Real Product (Power 90~95% charging)			Top - charger below client		0.0385

**TEST results of DUT to phone test Configuration 3 & 4**

**FCC RF Exposure Result**

Test Configuration	Test mode	Test distance	Test Position	H-Field Limit (A/m)	H-Field meas. data (A/m)
Configuration 3	Operating Real Product (Power <10% charging)	15 cm probe to edges of EUT and 20 cm probe to top surface of the EUT	Top - charger above client	1.63	0.0381
			Top - charger below client		0.0389
			Edge 1		0.0315
			Edge 2		0.1534
			Edge 3		0.0308
			Edge 4		0.0743
			Max		0.1534
	Operating Real Product (Power 50~55% charging)		Top - charger above client		0.0377
			Top - charger below client		0.0366
			Edge 1		0.0308
			Edge 2		0.1555
			Edge 3		0.0305
			Edge 4		0.0656
			Max		0.1555
	Operating Real Product (Power 90~95% charging)		Top - charger above client		0.0368
			Top - charger below client		0.0379
			Edge 1		0.0317
			Edge 2		<b>0.1640</b>
			Edge 3		0.0329
			Edge 4		0.0672
			Max		0.1640
Configuration 4	Operating Real Product (Power 90~95% charging)		Edge 2		0.1710

**TEST results of DUT to phone test Configuration 5 & 6**

**FCC RF Exposure Result**

Test Configuration	Test mode	Test distance	Test Position	H-Field Limit (A/m)	H-Field meas. data (A/m)
Configuration 5	Operating Real Product (Power <10% charging)	15 cm probe to edges of EUT and 20 cm probe to top surface of the EUT	Top - charger below client	1.63	0.0381
			Edge 1		0.0527
			Edge 2		0.0575
			Edge 3		0.0973
			Edge 4		0.0557
			Max		0.0973
	Operating Real Product (Power 50~55% charging)		Top - charger below client		0.0389
			Edge 1		0.0545
			Edge 2		0.0565
			Edge 3		0.0990
			Edge 4		0.0606
			Max		0.0990
	Operating Real Product (Power 90~95% charging)		Top - charger below client		0.0385
			Edge 1		0.0508
			Edge 2		0.0554
			Edge 3		<b>0.1019</b>
			Edge 4		0.0668
			Max		0.1019
Configuration 6	Operating Real Product (Power 90~95% charging)		Edge 3		0.0951

**6.2.2. FCC SUMMARY OF RESULTS**

H-Field Limit		
FCC RF Exposure	Maximum meas data (A/m)	Percentage (%)
1.63	0.1640	<b>10.06</b>

**Conclusion:**

H-Field result is less than 50% of the MPE limit.

## **Appendixes**

**Refer to separated files for the following appendixes.**

**4790541040-S3 FCC Report MPE\_App A\_Test setup photos**

**END OF REPORT**