

## APPENDIX F: POWER REDUCTION VERIFICATION

Per the May 2017 TCBC Workshop Notes, demonstration of proper functioning of the power reduction mechanisms is required to support the corresponding SAR configurations. The verification process was divided into two parts: (1) evaluation of output power levels for individual or multiple triggering mechanisms and (2) evaluation of the triggering distances for proximity-based sensors.

## F.1 Power Verification Procedure

The power verification was performed according to the following procedure:

- A base station simulator was used to establish a conducted RF connection and the output power was
  monitored. The power measurements were confirmed to be within expected tolerances for all states
  before and after a power reduction mechanism was triggered. For licensed modes, the device state index
  as displayed on the device UI was recorded before and after the mechanism was triggered.
- 2. Step 1 was repeated for all relevant modes and frequency bands for the mechanism being investigated.
- 3. Steps 1 and 2 were repeated for all individual power reduction mechanisms and combinations thereof. For the combination cases, one mechanism was switched to a 'triggered' state at a time; powers were confirmed to be within tolerances after each additional mechanism was activated.

FCC ID A3LSMS918JPN	SAR EVALUATION REPORT	Approved by: Technical Manager
<b>DUT Type:</b> Portable Handset		APPENDIX F: Page 1 of 3



## F.2 Main Antenna Verification Summary

Table F-1
Power Measurement Verification for Main Antenna

Mechanism(s)	Mode/Band	Conducted F	Power (dBm)
1st		Free Space	Mechanism #1
Held-to-Ear	GSM1900	0	2
Held-to-Ear	LTE Band 66	0	2
Held-to-Ear	LTE Band 4	0	2
Held-to-Ear	LTE Band 2	0	2
Held-to-Ear	LTE Band 41	0	2
Held-to-Ear	NR TDD Band n41	0	2

<sup>\*</sup>Note: This device uses different Device State Indices (DSI) to configure different time averaged power levels based on certain exposure scenarios. For this device, DSI = 2 represents the case where the device is held to ear, and DSI = 0 is configured when the device cannot detect the use condition.

## F.3 WIFI Verification Summary

Table F-2
Power Measurement Verification WIFI – Antenna 1

Fower Measurement Vermication WiFi - Antenna i				
	Conducted Power (dBm)			
Mode/Band	Un-triggered (Max)	Mechanism #1 NR Active (Reduced)	Mechanism #2 RCV Active (Reduced)	
802.11b	19.65	13.73	12.98	
802.11g	17.61	13.58	13.66	
802.11n (2.4GHz)	17.71	13.74	13.11	
802.11a	16.5	11.42	11.81	
802.11n (5GHz, 20MHz BW)	16.61	11.48	11.18	
802.11ac (20MHz BW)	16.63	11.47	11.65	
802.11n (5GHz, 40MHz BW)	16.33	11.48	9.55	
802.11ac (40MHz BW)	16.42	11.51	12.29	
802.11ac (80MHz BW)	15.57	11.05	12.60	
802.11ac (160MHz BW)	15.87	11.26	12.94	

<sup>\*</sup>Note: MIMO WIFI modes were not evaluated due to equipment limitations. All SISO powers were taken during MIMO Conditions.

FCC ID A3LSMS918JPN	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX F: Page 2 of 3



Table F-3
Power Measurement Verification WIFI – Antenna 2

	Conducted Power (dBm)			
Mode/Band	Un-triggered (Max)	Mechanism #1 NR Active (Reduced)	Mechanism #2 RCV and NR Active (Reduced)	
802.11b	19.2	13.3	13.95	
802.11g	17.25	13.13	13.12	
802.11n (2.4GHz)	17.28	13.24	13.85	
802.11a	17.34	11.75	12.28	
802.11n (5GHz, 20MHz BW)	17.35	11.78	11.94	
802.11ac (20MHz BW)	17.35	11.47	11.38	
802.11n (5GHz, 40MHz BW)	16.93	11.48	9.71	
802.11ac (40MHz BW)	16.81	11.95	12.15	
802.11ac (80MHz BW)	15.9	11.95	12.18	
802.11ac (160MHz BW)	15.77	11.73	12.53	

<sup>\*</sup>Note: MIMO WIFI modes were not evaluated due to equipment limitations. All SISO powers were taken during MIMO Conditions.

Table F-4
Power Measurement Verification Bluetooth – Antenna 1

Mechanism(s)	Mode/Band	Conducted Power (dBm)	
		Un-triggered	Mechanism #1
1st			RCV Active
		(Max)	(Reduced)
Held-to-Ear	Bluetooth	15.82	11.7

Table F-5
Power Measurement Verification Bluetooth – Antenna 2

Mechanism(s)	Mode/Band	Conducted Power (dBm)	
		Un-triggered	Mechanism #1
1st			RCV Active
		(Max)	(Reduced)
Held-to-Ear	Bluetooth	16.83	12.02

FCC ID A3LSMS918JPN	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX F: Page 3 of 3