

FCC LTE REPORT

Certification

Applicant Name:

SAMSUNG Electronics Co., Ltd.

Date of Issue:

October 16, 2023

Location:

HCT CO., LTD.,
 74, Seoicheon-ro 578beon-gil, Majang-myeon,
 Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Address:

129, Samsung-ro, Yeongtong-gu,
 Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Report No.: HCT-RF-2310-FC027

FCC ID: A3LSMS926U

APPLICANT: SAMSUNG Electronics Co., Ltd.

Model(s): SM-S926U
 Additional Model(s): SM-S926U1
 EUT Type: Mobile phone
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 FCC Rule Part(s): §27

Main 2 Ant

| Mode (MHz) | Tx Frequency (MHz) | Emission Designator | Modulation | EIRP | |
|--------------------|--------------------|---------------------|------------|----------------|------------------|
| | | | | Max. Power (W) | Max. Power (dBm) |
| LTE – Band 38 (5) | 2572.5 – 2617.5 | 4M52G7D | QPSK | 0.186 | 22.70 |
| | | 4M51W7D | 16QAM | 0.150 | 21.76 |
| | | 4M51W7D | 64QAM | 0.119 | 20.75 |
| | | 4M50W7D | 256QAM | 0.058 | 17.62 |
| LTE – Band 38 (10) | 2575.0 – 2615.0 | 8M97G7D | QPSK | 0.178 | 22.50 |
| | | 9M03W7D | 16QAM | 0.141 | 21.50 |
| | | 9M00W7D | 64QAM | 0.113 | 20.52 |
| | | 8M97W7D | 256QAM | 0.055 | 17.42 |
| LTE – Band 38 (15) | 2577.5 – 2612.5 | 13M5G7D | QPSK | 0.180 | 22.56 |
| | | 13M5W7D | 16QAM | 0.149 | 21.74 |
| | | 13M5W7D | 64QAM | 0.118 | 20.71 |
| | | 13M5W7D | 256QAM | 0.059 | 17.69 |
| LTE – Band 38 (20) | 2580.0 – 2610.0 | 18M0G7D | QPSK | 0.188 | 22.74 |
| | | 18M0W7D | 16QAM | 0.156 | 21.92 |
| | | 18M0W7D | 64QAM | 0.124 | 20.94 |
| | | 18M0W7D | 256QAM | 0.060 | 17.76 |

Sub 2 Ant

| Mode (MHz) | Tx Frequency (MHz) | Emission Designator | Modulation | EIRP | |
|--------------------|--------------------|---------------------|------------|----------------|------------------|
| | | | | Max. Power (W) | Max. Power (dBm) |
| LTE – Band 38 (5) | 2572.5 – 2617.5 | 4M52G7D | QPSK | 0.166 | 22.21 |
| | | 4M52W7D | 16QAM | 0.133 | 21.24 |
| | | 4M52W7D | 64QAM | 0.106 | 20.24 |
| | | 4M51W7D | 256QAM | 0.052 | 17.14 |
| LTE – Band 38 (10) | 2575.0 – 2615.0 | 8M99G7D | QPSK | 0.163 | 22.13 |
| | | 8M99W7D | 16QAM | 0.131 | 21.16 |
| | | 9M00W7D | 64QAM | 0.105 | 20.21 |
| | | 8M98W7D | 256QAM | 0.051 | 17.04 |
| LTE – Band 38 (15) | 2577.5 – 2612.5 | 13M5G7D | QPSK | 0.160 | 22.04 |
| | | 13M5W7D | 16QAM | 0.132 | 21.20 |
| | | 13M5W7D | 64QAM | 0.106 | 20.26 |
| | | 13M5W7D | 256QAM | 0.051 | 17.07 |
| LTE – Band 38 (20) | 2580.0 – 2610.0 | 18M0G7D | QPSK | 0.169 | 22.28 |
| | | 18M0W7D | 16QAM | 0.142 | 21.51 |
| | | 18M0W7D | 64QAM | 0.113 | 20.52 |
| | | 18M0W7D | 256QAM | 0.053 | 17.28 |

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

Report No.: HCT-RF-2310-FC027

REVIEWED BY



Report prepared by : Jae Mun Do
Engineer of Telecommunication Testing Center

Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.
This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked *.
The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

The report shall not be reproduced except in full(only partly) without approval of the laboratory.

Version

| TEST REPORT NO. | DATE | DESCRIPTION |
|-------------------|------------------|-------------------------|
| HCT-RF-2310-FC027 | October 16, 2023 | - First Approval Report |

Table of Contents

| | |
|---|-----|
| REVIEWED BY | 3 |
| 1. GENERAL INFORMATION | 6 |
| 2. INTRODUCTION..... | 7 |
| 2.1. DESCRIPTION OF EUT | 7 |
| 2.2. MEASURING INSTRUMENT CALIBRATION..... | 7 |
| 2.3. TEST FACILITY..... | 7 |
| 3. DESCRIPTION OF TESTS | 8 |
| 3.1 TEST PROCEDURE..... | 8 |
| 3.2 RADIATED POWER | 9 |
| 3.3 RADIATED SPURIOUS EMISSIONS..... | 10 |
| 3.4 PEAK- TO- AVERAGE RATIO | 11 |
| 3.5 OCCUPIED BANDWIDTH..... | 13 |
| 3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL | 14 |
| 3.7 CHANNEL EDGE | 15 |
| 3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE..... | 17 |
| 3.9 WORST CASE(RADIATED TEST)..... | 18 |
| 3.10 WORST CASE(CONDUCTED TEST)..... | 21 |
| 4. LIST OF TEST EQUIPMENT..... | 22 |
| 5. MEASUREMENT UNCERTAINTY | 23 |
| 6. SUMMARY OF TEST RESULTS | 24 |
| 7. SAMPLE CALCULATION | 25 |
| 8. TEST DATA(Main 2 Ant) | 27 |
| 8.1 EQUIVALENT ISOTROPIC RADIATED POWER | 27 |
| 8.2 RADIATED SPURIOUS EMISSIONS..... | 29 |
| 8.3 PEAK-TO-AVERAGE RATIO | 33 |
| 8.4 OCCUPIED BANDWIDTH..... | 34 |
| 8.5 CONDUCTED SPURIOUS EMISSIONS | 35 |
| 8.6 CHANNEL EDGE | 36 |
| 8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE..... | 37 |
| 9. TEST DATA(Sub 2 Ant) | 49 |
| 9.1 EQUIVALENT ISOTROPIC RADIATED POWER | 49 |
| 9.2 RADIATED SPURIOUS EMISSIONS..... | 51 |
| 9.3 PEAK-TO-AVERAGE RATIO | 55 |
| 9.4 OCCUPIED BANDWIDTH..... | 56 |
| 9.5 CONDUCTED SPURIOUS EMISSIONS | 57 |
| 9.6 CHANNEL EDGE | 58 |
| 9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE..... | 59 |
| 10. TEST PLOTS(Main 2 Ant) | 71 |
| 11. TEST PLOTS(Sub 2 Ant) | 148 |
| 12. ANNEX A_ TEST SETUP PHOTO | 225 |

MEASUREMENT REPORT

1. GENERAL INFORMATION

| | |
|-----------------------------|---|
| Applicant Name: | SAMSUNG Electronics Co., Ltd. |
| Address: | 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea |
| FCC ID: | A3LSMS926U |
| Application Type: | Certification |
| FCC Classification: | PCS Licensed Transmitter Held to Ear (PCE) |
| FCC Rule Part(s): | §27 |
| EUT Type: | Mobile phone |
| Model(s): | SM-S926U |
| Additional Model(s): | SM-S926U1 |
| Tx Frequency: | 2572.5 – 2617.5 : 5 MHz 2575.0 – 2615.0 : 10 MHz 2577.5 – 2612.5 : 15 MHz 2580.0 – 2610.0 : 20 MHz |
| Date(s) of Tests: | September 05, 2023 ~ October 11, 2023 |
| Serial number: | Radiated: R3CW90B4EEV Conducted: R3CW808LYGJ(Main2 Ant), 741c314dee0f7ece(Sub2 Ant) |

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS and LTE, Sub6, mmWave.

It also supports IEEE 802.11 a/b/g/n/ac/ax (20/40/80/160 MHz), WIFI 6E, Bluetooth, BT LE, NFC, UWB, WPT.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

| Test Description | Test Procedure Used |
|---|---|
| Occupied Bandwidth | - KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4 |
| Channel Edge | - KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7 |
| Spurious and Harmonic Emissions at Antenna Terminal | - KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7 |
| Conducted Output Power | - N/A (See SAR Report) |
| Peak- to- Average Ratio | - KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4 |
| Frequency stability | - ANSI C63.26-2015 – Section 5.6 |
| Effective Radiated Power/ Effective Isotropic Radiated Power | - KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17 |
| Radiated Spurious and Harmonic Emissions | - KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12 |

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed Normal Hz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $>$ 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d \text{ (dBm)} = P_g \text{ (dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.
These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration
4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and Normal Hz for emissions above 1 GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $> 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_g_{(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15 \text{ dB}$$

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - for continuous transmissions, set to 1 ms,
 - or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R. (dB) = P_{Pk} (dBm) - P_{Avg} (dBm) \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)

The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.


1. Set the RBW \geq OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times$ (number of points in sweep) \times (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW \geq OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:

Set $\geq [10 \times$ (number of points in sweep) \times (transmission period)] for single sweep
(automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6 \text{ dB}$ if the duty cycle is a constant 25 %.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5 % of the expected OBW
3. VBW \geq 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99 % occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW \geq 3 MHz
3. Detector = RMS
4. Trace Mode = Average
5. Sweep time = auto
6. Number of points in sweep \geq 2 x Span / RBW

3.7 CHANNEL EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings


1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. Within 1MHz of the channel edge the RBW should be 2 % of EBW, then 1 MHz after that.
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes

1. The attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge,
2. $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge.
3. $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge.
4. The attenuation factor shall not be less that $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz.
5. $55 + 10 \log (P)$ dB at or below 2490.5 MHz.
6. X is the greater of 6MHz or the actual emission bandwidth
7. The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer

Where Margin < 1 dB the emission level is either corrected by $10 \log(1 \text{ MHz/ RB})$ or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.

2. Primary Supply Voltage:

- Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.
- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
Mode : Stand alone, Stand alone + External accessories (Earphone, AC adapter, etc)
Worst case : Stand alone
- We were performed the RSE test in condition of co-location.
Mode : Stand alone, Simultaneous transmission scenarios
Worst case : Stand alone
- The worst case is reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data.
- Please refer to the table below.
- SM-S926U & additional models were tested and the worst case results are reported.
(Worst case : SM-S926U)

[Main 2 Ant Worst case]

| Test Description | Modulation | Bandwidth (MHz) | Frequency | RB size | RB offset | Axis |
|--|-------------------------------------|-----------------|-----------|---------|-----------|------|
| Effective Isotropic Radiated Power | QPSK, 16QAM, 64QAM, 256QAM | 5 | Low | 1 | 13 | X |
| | | | Mid | 1 | 0 | |
| | | | High | 1 | 24 | |
| | | 10 | Low | 1 | 25 | |
| | | | Mid | 1 | 0 | |
| | | | High | 1 | 49 | |
| | | 15 | Low | 1 | 38 | |
| | | | Mid | 1 | 0 | |
| | | | High | 1 | 74 | |
| | | 20 | Low | 1 | 50 | |
| | | | Mid | 1 | 0 | |
| | | | High | 1 | 99 | |
| Radiated Spurious and Harmonic Emissions | QPSK | 5 | Low | 1 | 13 | X |
| | | | Mid | 1 | 0 | |
| | | | High | 1 | 24 | |
| | | 10 | Low | 1 | 25 | |
| | | | Mid | 1 | 0 | |
| | | | High | 1 | 49 | |
| | | 15 | Low | 1 | 38 | |
| | | | Mid | 1 | 0 | |
| | | | High | 1 | 74 | |
| | | 20 | Low | 1 | 50 | |
| | | | Mid | 1 | 0 | |
| | | | High | 1 | 99 | |

[Sub 2 Ant Worst case]

| Test Description | Modulation | Bandwidth (MHz) | Frequency | RB size | RB offset | Axis |
|--|-------------------------------------|-----------------|-------------------|-------------------|-----------|------|
| Effective Isotropic Radiated Power | QPSK, 16QAM, 64QAM, 256QAM | 5 | Low, High | 1 | 24 | X |
| | | | Mid | 1 | 0 | |
| | | 10 | Low, Mid, High | 1 | 49 | |
| | | | 15 | Low, Mid, High | 1 | |
| | | 20 | | Low, High | 1 | |
| | | | Mid | 1 | 0 | |
| Radiated Spurious and Harmonic Emissions | QPSK | 5 | Low, High | 1 | 24 | Z |
| | | | Mid | 1 | 0 | |
| | | 10 | Low, Mid, High | 1 | 49 | |
| | | | 15 | Low, Mid, High | 1 | |
| | | 20 | | Low, High | 1 | |
| | | | Mid | 1 | 0 | |

3.10 WORST CASE(CONDUCTED TEST)

- All modes of operation were investigated and the worst case configuration results are reported.
- SM-S926U & additional models were tested and the worst case results are reported.
(Worst case : SM-S926U)

[Worst case]

| Test Description | Modulation | Bandwidth (MHz) | Frequency | RB size | RB offset |
|--|-------------------------------------|-----------------|----------------------|---------|-----------|
| Occupied Bandwidth | QPSK, 16QAM, 64QAM, 256QAM | 5, 10, 15, 20 | Mid | Full RB | 0 |
| Peak-To-Average Ratio | QPSK, 16QAM, 64QAM, 256QAM | 5, 10, 15, 20 | Mid | Full RB | 0 |
| Channel Edge | QPSK | 5 | Low | 1 | 0 |
| | | | High | 1 | 24 |
| | | 10 | Low | 1 | 0 |
| | | | High | 1 | 49 |
| | | 15 | Low | 1 | 0 |
| | | | High | 1 | 74 |
| | | 20 | Low | 1 | 0 |
| | | | High | 1 | 99 |
| | | 5, 10, 15, 20 | Low, Mid, High | Full RB | 0 |
| | | | | | |
| Spurious and Harmonic Emissions at Antenna Terminal | QPSK | 5, 10, 15, 20 | Low, Mid, High | 1 | 0 |

4. LIST OF TEST EQUIPMENT

| Equipment | Model | Manufacturer | Serial No. | Due to Calibration | Calibration Interval |
|--|------------------------|------------------|-------------|--------------------|----------------------|
| RF Switching System | FBSR-02B(1.2G HPF+LNA) | T&M SYSTEM | F1L1 | 01/19/2024 | Annual |
| RF Switching System | FBSR-02B(3.3G HPF+LNA) | T&M SYSTEM | F1L2 | 01/19/2024 | Annual |
| Power Splitter(DC ~ 26.5 GHz) | 11667B | Hewlett Packard | 5001 | 04/19/2024 | Annual |
| DC Power Supply | E3632A | Agilent | MY40010147 | 06/23/2024 | Annual |
| Dipole Antenna | UHAP | Schwarzbeck | 557 | 03/09/2025 | Biennial |
| Dipole Antenna | UHAP | Schwarzbeck | 558 | 03/09/2025 | Biennial |
| Chamber | SU-642 | ESPEC | 93008124 | 02/22/2024 | Annual |
| Horn Antenna(1 ~ 18 GHz) | BBHA 9120D | Schwarzbeck | 147 | 08/17/2025 | Biennial |
| Horn Antenna(1 ~ 18 GHz) | BBHA 9120D | Schwarzbeck | 9120D-1298 | 09/11/2025 | Biennial |
| Horn Antenna(15 ~ 40 GHz) | BBHA 9170 | Schwarzbeck | BBHA9170342 | 09/29/2024 | Biennial |
| Horn Antenna(15 ~ 40 GHz) | BBHA 9170 | Schwarzbeck | BBHA9170124 | 03/28/2025 | Biennial |
| Signal Analyzer(10 Hz ~ 26.5 GHz) | N9020A | Agilent | MY52090906 | 04/20/2024 | Annual |
| ATTENUATOR(20 dB) | 8493C | Hewlett Packard | 17280 | 04/19/2024 | Annual |
| Spectrum Analyzer(10 Hz ~ 40 GHz) | FSV40 | REOHDE & SCHWARZ | 100931 | 08/17/2024 | Annual |
| Base Station | 8960 (E5515C) | Agilent | MY48360800 | 08/10/2024 | Annual |
| Loop Antenna(9 kHz ~ 30 MHz) | FMZB1513 | Schwarzbeck | 1513-333 | 03/17/2024 | Biennial |
| Trilog Broadband Antenna | VULB9168 | Schwarzbeck | 895 | 08/16/2024 | Biennial |
| Trilog Broadband Antenna | VULB9168 | Schwarzbeck | 1135 | 03/21/2024 | Biennial |
| Wideband Radio Communication Tester | MT8821C | Anritsu Corp. | 6262094331 | 12/01/2023 | Annual |
| Wideband Radio Communication Tester | MT8820C | Anritsu Corp. | 6201026545 | 01/05/2024 | Annual |
| SIGNAL GENERATOR (100 kHz ~ 40 GHz) | SMB100A | REOHDE & SCHWARZ | 177633 | 06/22/2024 | Annual |
| Signal Analyzer(5 Hz ~ 40.0 GHz) | N9030B | KEYSIGHT | MY55480167 | 05/24/2024 | Annual |
| FCC LTE Mobile Conducted RF Automation Test Software | - | HCT CO., LTD., | - | - | - |

Note:

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
2. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Parameter | Expanded Uncertainty (\pm dB) |
|--|--|
| Conducted Disturbance (150 kHz ~ 30 MHz) | 1.90 (Confidence level about 95 %, $k=2$) |
| Radiated Disturbance (9 kHz ~ 30 MHz) | 4.14 (Confidence level about 95 %, $k=2$) |
| Radiated Disturbance (30 MHz ~ 1 GHz) | 5.16 (Confidence level about 95 %, $k=2$) |
| Radiated Disturbance (1 GHz ~ 18 GHz) | 5.57 (Confidence level about 95 %, $k=2$) |
| Radiated Disturbance (18 GHz ~ 40 GHz) | 5.76 (Confidence level about 95 %, $k=2$) |
| Radiated Disturbance (Above 40 GHz) | 5.52 (Confidence level about 95 %, $k=2$) |

6. SUMMARY OF TEST RESULTS

6.1 Test Condition: Conducted Test

| Test Description | FCC Part Section(s) | Test Limit | Test Result |
|--|--------------------------|---|------------------|
| Occupied Bandwidth | §2.1049 | N/A | PASS |
| Band Edge / Spurious and Harmonic Emissions at Antenna Terminal. | §2.1051, §27.53(m)(4) | <ul style="list-style-type: none"> ■ $< 40 + 10\log_{10} (P[\text{Watts}])$ at Channel edges ■ $< 43 + 10\log_{10} (P[\text{Watts}])$ between 5 and X MHz from Channel edges ■ $< 55 + 10\log_{10} (P[\text{Watts}])$ beyond X MHz beyond from Channel edges ■ $< 43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz | PASS |
| Conducted Output Power | §2.1046 | N/A | <u>See Note1</u> |
| Frequency stability / variation of ambient temperature | §2.1055, §27.54 | Emission must remain in band | PASS |

Note:

1. See SAR Report

6.2 Test Condition: Radiated Test

| Test Description | FCC Part Section(s) | Test Limit | Test Result |
|--|--------------------------|--|-------------|
| Equivalent Isotropic Radiated Power | §27.50(h)(2) | < 2 Watts max. EIRP | PASS |
| Radiated Spurious and Harmonic Emissions | §2.1053, §27.53(m)(4) | $< 55 + 10\log_{10} (P[\text{Watts}])$ | PASS |

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

| Ch./ Freq. | | Measured Level (dBm) | Substitute Level (dBm) | Ant. Gain (dBd) | C.L | Pol. | ERP | |
|------------|------------|----------------------|------------------------|-----------------|------|------|-------|-------|
| channel | Freq.(MHz) | | | | | | W | dBm |
| 128 | 824.20 | -21.37 | 38.40 | -10.61 | 0.95 | H | 0.483 | 26.84 |

ERP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter’s level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter’s level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

| Ch./ Freq. | | Measured Level (dBm) | Substitute Level (dBm) | Ant. Gain (dBi) | C.L | Pol. | EIRP | |
|------------|------------|----------------------|------------------------|-----------------|------|------|-------|-------|
| channel | Freq.(MHz) | | | | | | W | dBm |
| 38000 | 2595.0 | -15.75 | 18.45 | 9.90 | 1.76 | H | 0.456 | 26.59 |

EIRP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter’s level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter’s level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA(Main 2 Ant)

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

| Freq (MHz) | Bandwidth | Modulation | Measured Level (dBm) | Substitute Level (dBm) | Ant. Gain(dBi) | C.L | Pol | Limit | EIRP | |
|------------|-------------------|------------|----------------------|------------------------|----------------|------|-----|--------|-------|-------|
| | | | | | | | | W | W | dBm |
| 2572.5 | LTE B38/ 5 MHz | QPSK | -22.56 | 14.13 | 10.65 | 2.72 | H | < 2.00 | 0.161 | 22.06 |
| | | 16-QAM | -23.50 | 13.19 | 10.65 | 2.72 | H | | 0.129 | 21.12 |
| | | 64-QAM | -24.47 | 12.22 | 10.65 | 2.72 | H | | 0.103 | 20.15 |
| | | 256-QAM | -27.50 | 9.19 | 10.65 | 2.72 | H | | 0.052 | 17.12 |
| 2595.0 | | QPSK | -22.37 | 14.74 | 10.64 | 2.68 | H | | 0.186 | 22.70 |
| | | 16-QAM | -23.31 | 13.80 | 10.64 | 2.68 | H | | 0.150 | 21.76 |
| | | 64-QAM | -24.32 | 12.79 | 10.64 | 2.68 | H | | 0.119 | 20.75 |
| | | 256-QAM | -27.45 | 9.66 | 10.64 | 2.68 | H | | 0.058 | 17.62 |
| 2617.5 | | QPSK | -22.52 | 14.62 | 10.65 | 2.72 | H | | 0.180 | 22.55 |
| | | 16-QAM | -23.52 | 13.62 | 10.65 | 2.72 | H | | 0.143 | 21.55 |
| | | 64-QAM | -24.49 | 12.65 | 10.65 | 2.72 | H | | 0.114 | 20.58 |
| | | 256-QAM | -27.60 | 9.54 | 10.65 | 2.72 | H | | 0.056 | 17.47 |

| Freq (MHz) | Bandwidth | Modulation | Measured Level (dBm) | Substitute Level (dBm) | Ant. Gain(dBi) | C.L | Pol | Limit | EIRP | |
|------------|--------------------|------------|----------------------|------------------------|----------------|------|-----|--------|-------|-------|
| | | | | | | | | W | W | dBm |
| 2575.0 | LTE B38/ 10 MHz | QPSK | -22.58 | 14.14 | 10.65 | 2.73 | H | < 2.00 | 0.161 | 22.06 |
| | | 16-QAM | -23.53 | 13.19 | 10.65 | 2.73 | H | | 0.129 | 21.11 |
| | | 64-QAM | -24.54 | 12.18 | 10.65 | 2.73 | H | | 0.102 | 20.10 |
| | | 256-QAM | -27.56 | 9.16 | 10.65 | 2.73 | H | | 0.051 | 17.08 |
| 2595.0 | | QPSK | -22.94 | 14.17 | 10.64 | 2.68 | H | | 0.163 | 22.13 |
| | | 16-QAM | -23.74 | 13.37 | 10.64 | 2.68 | H | | 0.136 | 21.33 |
| | | 64-QAM | -24.71 | 12.40 | 10.64 | 2.68 | H | | 0.109 | 20.36 |
| | | 256-QAM | -27.85 | 9.26 | 10.64 | 2.68 | H | | 0.053 | 17.22 |
| 2615.0 | | QPSK | -22.64 | 14.51 | 10.65 | 2.66 | H | | 0.178 | 22.50 |
| | | 16-QAM | -23.64 | 13.51 | 10.65 | 2.66 | H | | 0.141 | 21.50 |
| | | 64-QAM | -24.62 | 12.53 | 10.65 | 2.66 | H | | 0.113 | 20.52 |
| | | 256-QAM | -27.72 | 9.43 | 10.65 | 2.66 | H | | 0.055 | 17.42 |

| Freq (MHz) | Bandwidth | Modulation | Measured Level (dBm) | Substitute Level (dBm) | Ant. Gain(dBi) | C.L | Pol | Limit | | EIRP | |
|------------|--------------------|------------|----------------------|------------------------|----------------|------|-----|--------|-------|-------|-----|
| | | | | | | | | W | W | dBm | dBm |
| 2577.5 | LTE B38/ 15 MHz | QPSK | -22.86 | 13.88 | 10.65 | 2.74 | H | < 2.00 | 0.151 | 21.79 | |
| | | 16-QAM | -23.67 | 13.07 | 10.65 | 2.74 | H | | 0.125 | 20.98 | |
| | | 64-QAM | -24.63 | 12.11 | 10.65 | 2.74 | H | | 0.101 | 20.02 | |
| | | 256-QAM | -27.65 | 9.09 | 10.65 | 2.74 | H | | 0.050 | 17.00 | |
| 2595.0 | | QPSK | -22.88 | 14.23 | 10.64 | 2.68 | H | | 0.165 | 22.19 | |
| | | 16-QAM | -23.75 | 13.36 | 10.64 | 2.68 | H | | 0.135 | 21.32 | |
| | | 64-QAM | -24.73 | 12.38 | 10.64 | 2.68 | H | | 0.108 | 20.34 | |
| | | 256-QAM | -27.85 | 9.26 | 10.64 | 2.68 | H | | 0.053 | 17.22 | |
| 2612.5 | | QPSK | -22.59 | 14.58 | 10.66 | 2.68 | H | | 0.180 | 22.56 | |
| | | 16-QAM | -23.41 | 13.76 | 10.66 | 2.68 | H | | 0.149 | 21.74 | |
| | | 64-QAM | -24.44 | 12.73 | 10.66 | 2.68 | H | | 0.118 | 20.71 | |
| | | 256-QAM | -27.46 | 9.71 | 10.66 | 2.68 | H | | 0.059 | 17.69 | |

| Freq (MHz) | Bandwidth | Modulation | Measured Level (dBm) | Substitute Level (dBm) | Ant. Gain(dBi) | C.L | Pol | Limit | | EIRP | |
|------------|--------------------|------------|----------------------|------------------------|----------------|------|-----|--------|-------|-------|-----|
| | | | | | | | | W | W | dBm | dBm |
| 2580.0 | LTE B38/ 20 MHz | QPSK | -22.77 | 13.97 | 10.65 | 2.74 | H | < 2.00 | 0.154 | 21.88 | |
| | | 16-QAM | -23.59 | 13.15 | 10.65 | 2.74 | H | | 0.128 | 21.06 | |
| | | 64-QAM | -24.56 | 12.18 | 10.65 | 2.74 | H | | 0.102 | 20.09 | |
| | | 256-QAM | -27.64 | 9.10 | 10.65 | 2.74 | H | | 0.050 | 17.01 | |
| 2595.0 | | QPSK | -22.64 | 14.47 | 10.64 | 2.68 | H | | 0.175 | 22.43 | |
| | | 16-QAM | -23.33 | 13.78 | 10.64 | 2.68 | H | | 0.149 | 21.74 | |
| | | 64-QAM | -24.33 | 12.78 | 10.64 | 2.68 | H | | 0.118 | 20.74 | |
| | | 256-QAM | -27.50 | 9.61 | 10.64 | 2.68 | H | | 0.057 | 17.57 | |
| 2610.0 | | QPSK | -22.70 | 14.73 | 10.64 | 2.63 | H | | 0.188 | 22.74 | |
| | | 16-QAM | -23.52 | 13.91 | 10.64 | 2.63 | H | | 0.156 | 21.92 | |
| | | 64-QAM | -24.50 | 12.93 | 10.64 | 2.63 | H | | 0.124 | 20.94 | |
| | | 256-QAM | -27.68 | 9.75 | 10.64 | 2.63 | H | | 0.060 | 17.76 | |

8.2 RADIATED SPURIOUS EMISSIONS

- ▣ OPERATING FREQUENCY : 2595.0 MHz
- ▣ MEASURED OUTPUT POWER: 22.70 dBm = 0.186 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 5 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 47.70 dBc

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | dBc |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------|
| 37775 (2572.5) | 5 145.00 | -57.83 | 12.37 | -65.82 | 3.88 | V | -57.33 | 80.02 |
| | 7 717.50 | -57.15 | 11.37 | -57.63 | 4.78 | H | -51.04 | 73.73 |
| | 10 290.00 | -59.55 | 11.54 | -54.43 | 5.58 | V | -48.47 | 71.16 |
| 38000 (2595.0) | 5 190.00 | -53.71 | 12.57 | -62.82 | 3.83 | V | -54.08 | 76.77 |
| | 7 785.00 | -51.13 | 11.41 | -51.46 | 4.79 | V | -44.84 | 67.53 |
| | 10 380.00 | -59.65 | 11.41 | -54.54 | 5.62 | V | -48.75 | 71.45 |
| 38225 (2617.5) | 5 235.00 | -55.68 | 12.84 | -65.17 | 3.95 | H | -56.28 | 78.97 |
| | 7 852.50 | -48.48 | 11.35 | -47.87 | 4.81 | H | -41.33 | 64.02 |
| | 10 470.00 | -59.66 | 11.27 | -54.37 | 5.59 | V | -48.69 | 71.38 |

- ▣ OPERATING FREQUENCY : 2615.0 MHz
- ▣ MEASURED OUTPUT POWER: 22.50 dBm = 0.178 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 10 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 47.50 dBc

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | dBc |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------|
| 37800 (2575.0) | 5 150.00 | -56.92 | 12.39 | -64.98 | 3.84 | H | -56.43 | 78.93 |
| | 7 725.00 | -56.32 | 11.38 | -56.64 | 4.78 | V | -50.05 | 72.55 |
| | 10 300.00 | -59.34 | 11.53 | -54.16 | 5.62 | H | -48.25 | 70.75 |
| 38000 (2595.0) | 5 190.00 | -58.09 | 12.57 | -67.20 | 3.83 | H | -58.46 | 80.96 |
| | 7 785.00 | -53.19 | 11.41 | -53.52 | 4.79 | H | -46.90 | 69.40 |
| | 10 380.00 | -60.15 | 11.41 | -55.04 | 5.62 | V | -49.25 | 71.75 |
| 38200 (2615.0) | 5 230.00 | -53.94 | 12.81 | -63.54 | 3.95 | V | -54.68 | 77.18 |
| | 7 845.00 | -54.50 | 11.36 | -53.88 | 4.82 | H | -47.34 | 69.84 |
| | 10 460.00 | -59.91 | 11.28 | -54.93 | 5.57 | V | -49.22 | 71.72 |

- ▣ OPERATING FREQUENCY : 2612.5 MHz
- ▣ MEASURED OUTPUT POWER: 22.56 dBm = 0.180 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 15 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10} (W) =$ 47.56 dBc

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | dBc |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------|
| 37825 (2577.5) | 5 155.00 | -57.60 | 12.42 | -65.64 | 3.81 | V | -57.03 | 79.59 |
| | 7 732.50 | -55.74 | 11.38 | -55.91 | 4.78 | V | -49.31 | 71.87 |
| | 10 310.00 | -59.88 | 11.52 | -54.70 | 5.65 | H | -48.83 | 71.39 |
| 38000 (2595.0) | 5 190.00 | -57.07 | 12.57 | -66.18 | 3.83 | V | -57.44 | 80.00 |
| | 7 785.00 | -56.65 | 11.41 | -56.98 | 4.79 | V | -50.36 | 72.91 |
| | 10 380.00 | -59.28 | 11.41 | -54.17 | 5.62 | H | -48.38 | 70.94 |
| 38175 (2612.5) | 5 225.00 | -57.59 | 12.78 | -67.42 | 3.95 | V | -58.59 | 81.14 |
| | 7 837.50 | -47.02 | 11.36 | -46.40 | 4.82 | V | -39.86 | 62.42 |
| | 10 450.00 | -59.27 | 11.29 | -54.59 | 5.60 | H | -48.90 | 71.46 |

- ▣ OPERATING FREQUENCY : 2610.0 MHz
- ▣ MEASURED OUTPUT POWER: 22.74 dBm = 0.188 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 20 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10} (W) =$ 47.74 dBc

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | dBc |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------|
| 37850 (2580.0) | 5 160.00 | -57.77 | 12.44 | -65.78 | 3.78 | V | -57.12 | 79.86 |
| | 7 740.00 | -54.80 | 11.40 | -54.87 | 4.76 | H | -48.23 | 70.97 |
| | 10 320.00 | -60.35 | 11.51 | -55.24 | 5.66 | V | -49.39 | 72.13 |
| 38000 (2595.0) | 5 190.00 | -57.00 | 12.57 | -66.11 | 3.83 | H | -57.37 | 80.10 |
| | 7 785.00 | -55.32 | 11.41 | -55.65 | 4.79 | H | -49.03 | 71.76 |
| | 10 380.00 | -59.46 | 11.41 | -54.35 | 5.62 | V | -48.56 | 71.30 |
| 38150 (2610.0) | 5 220.00 | -57.64 | 12.75 | -67.69 | 3.95 | V | -58.89 | 81.63 |
| | 7 830.00 | -54.85 | 11.37 | -54.28 | 4.81 | H | -47.72 | 70.46 |
| | 10 440.00 | -59.65 | 11.30 | -55.05 | 5.65 | V | -49.40 | 72.14 |

8.3 PEAK-TO-AVERAGE RATIO

| Band | Band Width | Frequency (MHz) | Modulation | Resource Block Size | Resource Block Offset | Data (dB) |
|------|------------|-----------------|------------|---------------------|-----------------------|-----------|
| 38 | 5 MHz | 2595.0 | QPSK | 25 | 0 | 4.67 |
| | | | 16-QAM | | | 5.94 |
| | | | 64-QAM | | | 6.79 |
| | | | 256-QAM | | | 7.27 |
| | 10 MHz | | QPSK | 50 | | 4.63 |
| | | | 16-QAM | | | 5.64 |
| | | | 64-QAM | | | 6.74 |
| | | | 256-QAM | | | 7.05 |
| | 15 MHz | | QPSK | 75 | | 4.60 |
| | | | 16-QAM | | | 5.60 |
| | | | 64-QAM | | | 6.54 |
| | | | 256-QAM | | | 7.10 |
| | 20 MHz | | QPSK | 100 | | 4.74 |
| | | | 16-QAM | | | 5.70 |
| | | | 64-QAM | | | 6.40 |
| | | | 256-QAM | | | 6.91 |

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 108 ~ 123.

8.4 OCCUPIED BANDWIDTH

| Band | Band Width | Frequency (MHz) | Modulation | Resource Block Size | Resource Block Offset | Data (MHz) |
|------|------------|-----------------|------------|---------------------|-----------------------|------------|
| 38 | 5 MHz | 2595.0 | QPSK | 25 | 0 | 4.5180 |
| | | | 16-QAM | | | 4.5138 |
| | | | 64-QAM | | | 4.5099 |
| | | | 256-QAM | | | 4.5024 |
| | 10 MHz | | QPSK | 50 | | 8.9693 |
| | | | 16-QAM | | | 9.0276 |
| | | | 64-QAM | | | 9.0017 |
| | | | 256-QAM | | | 8.9688 |
| | 15 MHz | | QPSK | 75 | | 13.488 |
| | | | 16-QAM | | | 13.504 |
| | | | 64-QAM | | | 13.519 |
| | | | 256-QAM | | | 13.477 |
| | 20 MHz | | QPSK | 100 | | 18.014 |
| | | | 16-QAM | | | 17.949 |
| | | | 64-QAM | | | 17.994 |
| | | | 256-QAM | | | 17.982 |

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 92 ~ 107.

8.5 CONDUCTED SPURIOUS EMISSIONS

| Band | Band Width (MHz) | Frequency (MHz) | Frequency of Maximum Harmonic (GHz) | Factor (dB) | Measurement Maximum Data (dBm) | Result (dBm) | Limit (dBm) |
|------|------------------|-----------------|-------------------------------------|-------------|--------------------------------|--------------|-------------|
| 38 | 5 | 2572.5 | 26.1721 | 34.110 | -76.401 | -42.291 | -25.00 |
| | | 2595.0 | 26.1249 | 34.110 | -76.504 | -42.394 | |
| | | 2617.5 | 26.1436 | 34.110 | -76.752 | -42.642 | |
| | 10 | 2575.0 | 26.1598 | 34.110 | -76.743 | -42.633 | |
| | | 2595.0 | 26.1593 | 34.110 | -76.845 | -42.735 | |
| | | 2615.0 | 26.1279 | 34.110 | -76.707 | -42.597 | |
| | 15 | 2577.5 | 26.1521 | 34.110 | -76.387 | -42.277 | |
| | | 2595.0 | 26.1028 | 34.110 | -76.854 | -42.744 | |
| | | 2612.5 | 26.2010 | 34.110 | -76.242 | -42.132 | |
| | 20 | 2580.0 | 25.8316 | 34.110 | -76.384 | -42.274 | |
| | | 2595.0 | 26.4152 | 34.110 | -76.816 | -42.706 | |
| | | 2610.0 | 26.1466 | 34.110 | -76.790 | -42.680 | |

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 124 ~ 147.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Duty Cycle factor already applied on the factor.
 - Duty Cycle factor(dB) = 3.979
 - Factor(dB) = Duty Cycle factor + Cable Loss + Ext. Attenuator + Power Splitter
 - Result(dBm) = Reading + Factor

| Frequency Range (GHz) | Factor [dB] |
|-----------------------|-------------|
| 0.03 – 1 | 29.249 |
| 1 – 5 | 31.955 |
| 5 – 10 | 32.570 |
| 10 – 15 | 33.095 |
| 15 – 20 | 33.468 |
| Above 20 | 34.110 |

8.6 CHANNEL EDGE

| Band Width (Modulation) | Frequency (MHz) | Modulation | RB Size / Offset | C.E ~ (C.E ± 1 MHz) | | (C.E ± 1 MHz) ~ (C.E ± 5 MHz) | |
|-------------------------|-----------------|------------|------------------|---------------------|--------|-------------------------------|--------|
| | | | | Lower | Upper | Lower | Upper |
| 5 MHz | 2572.5 | QPSK | 25 / 0 | -21.78 | -21.18 | -19.25 | -17.71 |
| | 2595.0 | QPSK | 25 / 0 | -22.00 | -21.58 | -21.61 | -20.64 |
| | 2617.5 | QPSK | 25 / 0 | -22.14 | -22.05 | -22.29 | -22.14 |
| 10 MHz | 2575.0 | QPSK | 50 / 0 | -23.43 | -23.47 | -18.66 | -20.10 |
| | 2595.0 | QPSK | 50 / 0 | -24.07 | -24.24 | -21.79 | -21.60 |
| | 2615.0 | QPSK | 50 / 0 | -24.81 | -25.02 | -23.07 | -22.52 |
| 15 MHz | 2577.5 | QPSK | 75 / 0 | -23.79 | -23.90 | -19.96 | -21.25 |
| | 2595.0 | QPSK | 75 / 0 | -24.95 | -24.47 | -22.59 | -22.43 |
| | 2612.5 | QPSK | 75 / 0 | -25.38 | -25.62 | -23.90 | -23.27 |
| 20 MHz | 2580.0 | QPSK | 100 / 0 | -24.41 | -24.50 | -22.06 | -21.74 |
| | 2595.0 | QPSK | 100 / 0 | -25.42 | -25.16 | -23.59 | -23.13 |
| | 2610.0 | QPSK | 100 / 0 | -26.14 | -25.78 | -25.03 | -24.38 |
| Limit(dBm) | | | | -10.0 | | -10.0 | |

| Band Width (Modulation) | Frequency (MHz) | Modulation | Resource Block Size | (C.E ± 5 MHz) ~ (C.E ± X MHz) | | Above (C.E ± X MHz) | |
|-------------------------|-----------------|------------|---------------------|-------------------------------|--------|---------------------|--------|
| | | | | Lower | Upper | Lower | Upper |
| 5 MHz | 2572.5 | QPSK | 25 / 0 | -28.37 | -28.31 | -29.81 | -29.12 |
| | 2595.0 | QPSK | 25 / 0 | -29.61 | -28.80 | -29.75 | -28.86 |
| | 2617.5 | QPSK | 25 / 0 | -28.88 | -28.03 | -29.49 | -28.49 |
| 10 MHz | 2575.0 | QPSK | 50 / 0 | -24.23 | -24.52 | -33.18 | -31.83 |
| | 2595.0 | QPSK | 50 / 0 | -29.25 | -29.00 | -32.04 | -31.36 |
| | 2615.0 | QPSK | 50 / 0 | -28.74 | -29.73 | -31.34 | -30.95 |
| 15 MHz | 2577.5 | QPSK | 75 / 0 | -26.30 | -26.12 | -34.55 | -33.45 |
| | 2595.0 | QPSK | 75 / 0 | -29.41 | -28.45 | -33.56 | -32.97 |
| | 2612.5 | QPSK | 75 / 0 | -30.11 | -29.83 | -32.36 | -33.08 |
| 20 MHz | 2580.0 | QPSK | 100 / 0 | -25.84 | -25.75 | -34.84 | -33.64 |
| | 2595.0 | QPSK | 100 / 0 | -27.69 | -26.84 | -34.42 | -33.74 |
| | 2610.0 | QPSK | 100 / 0 | -29.27 | -28.23 | -32.60 | -33.38 |
| Limit(dBm) | | | | -13.0 | | -25.0 | |


Note:

1. C.E = Channel Edge
2. X = X is the greater of 6 MHz or the actual emission bandwidth.
3. X = 6 MHz(5 MHz Bandwidth), 10 MHz(10 MHz Bandwidth), 15 MHz(15 MHz Bandwidth), 20 MHz(20 MHz Bandwidth)
4. RB = Resource Block
5. Duty Cycle factor already applied on the factor.
 - Factor(dB) = Duty Cycle factor + Cable Loss + Ext. Attenuator + Power Splitter
 - Result(dBm) = Reading + Factor
 - Duty Cycle Factor(dB) = 3.979
6. Plots of the EUT's Channel Edge are shown Page 72 ~ 91. (1RB & Full RB)

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2572,500,000 Hz
- ▣ BANDWIDTH: 37775 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|-----------|
| 100 % | 3.880 | +20(Ref) | 2572 500 002 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2572 499 997 | -4.7 | 0.000 000 | -0.002 |
| 100 % | | -20 | 2572 499 999 | -3.2 | 0.000 000 | -0.001 |
| 100 % | | -10 | 2572 499 998 | -4.3 | 0.000 000 | -0.002 |
| 100 % | | 0 | 2572 500 008 | 5.4 | 0.000 000 | 0.002 |
| 100 % | | +10 | 2572 500 005 | 2.6 | 0.000 000 | 0.001 |
| 100 % | | +30 | 2572 500 008 | 6.1 | 0.000 000 | 0.002 |
| 100 % | | +40 | 2572 499 999 | -2.8 | 0.000 000 | -0.001 |
| 100 % | | +50 | 2572 500 000 | -2.1 | 0.000 000 | -0.001 |
| Batt. Endpoint | | 3.300 | +20 | 2572 500 008 | 6.1 | 0.000 000 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2575,000,000 Hz
- ▣ BANDWIDTH: 37800 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2575 000 004 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2575 000 007 | 3.1 | 0.000 000 | 0.001 |
| 100 % | | -20 | 2574 999 999 | -4.3 | 0.000 000 | -0.002 |
| 100 % | | -10 | 2575 000 002 | -2.1 | 0.000 000 | -0.001 |
| 100 % | | 0 | 2575 000 008 | 4.3 | 0.000 000 | 0.002 |
| 100 % | | +10 | 2575 000 006 | 2.7 | 0.000 000 | 0.001 |
| 100 % | | +30 | 2575 000 008 | 4.7 | 0.000 000 | 0.002 |
| 100 % | | +40 | 2575 000 002 | -1.7 | 0.000 000 | -0.001 |
| 100 % | | +50 | 2575 000 008 | 3.9 | 0.000 000 | 0.002 |
| Batt. Endpoint | 3.300 | +20 | 2575 000 002 | -1.8 | 0.000 000 | -0.001 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2577,500,000 Hz
- ▣ BANDWIDTH: 37825 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2577 499 992 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2577 499 987 | -4.5 | 0.000 000 | -0.002 |
| 100 % | | -20 | 2577 499 985 | -7.2 | 0.000 000 | -0.003 |
| 100 % | | -10 | 2577 499 985 | -6.3 | 0.000 000 | -0.002 |
| 100 % | | 0 | 2577 499 984 | -7.7 | 0.000 000 | -0.003 |
| 100 % | | +10 | 2577 499 983 | -8.3 | 0.000 000 | -0.003 |
| 100 % | | +30 | 2577 499 985 | -6.8 | 0.000 000 | -0.003 |
| 100 % | | +40 | 2577 499 986 | -5.9 | 0.000 000 | -0.002 |
| 100 % | | +50 | 2577 499 987 | -4.8 | 0.000 000 | -0.002 |
| Batt. Endpoint | 3.300 | +20 | 2577 499 988 | -3.8 | 0.000 000 | -0.001 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2580,000,000 Hz
- ▣ BANDWIDTH: 37850 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|-----------|
| 100 % | 3.880 | +20(Ref) | 2580 000 003 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2580 000 000 | -3.4 | 0.000 000 | -0.001 |
| 100 % | | -20 | 2580 000 001 | -1.9 | 0.000 000 | -0.001 |
| 100 % | | -10 | 2579 999 999 | -4.3 | 0.000 000 | -0.002 |
| 100 % | | 0 | 2580 000 005 | 2.2 | 0.000 000 | 0.001 |
| 100 % | | +10 | 2580 000 001 | -1.7 | 0.000 000 | -0.001 |
| 100 % | | +30 | 2579 999 999 | -4.0 | 0.000 000 | -0.002 |
| 100 % | | +40 | 2580 000 001 | -2.3 | 0.000 000 | -0.001 |
| 100 % | | +50 | 2580 000 001 | -2.4 | 0.000 000 | -0.001 |
| Batt. Endpoint | | 3.300 | +20 | 2580 000 001 | -2.5 | 0.000 000 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2594 999 997 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2594 999 993 | -4.0 | 0.000 000 | -0.002 |
| 100 % | | -20 | 2594 999 993 | -3.6 | 0.000 000 | -0.001 |
| 100 % | | -10 | 2594 999 993 | -4.0 | 0.000 000 | -0.002 |
| 100 % | | 0 | 2594 999 993 | -3.5 | 0.000 000 | -0.001 |
| 100 % | | +10 | 2594 999 992 | -4.6 | 0.000 000 | -0.002 |
| 100 % | | +30 | 2594 999 994 | -3.1 | 0.000 000 | -0.001 |
| 100 % | | +40 | 2594 999 995 | -1.7 | 0.000 000 | -0.001 |
| 100 % | | +50 | 2594 999 993 | -3.6 | 0.000 000 | -0.001 |
| Batt. Endpoint | 3.300 | +20 | 2594 999 993 | -3.6 | 0.000 000 | -0.001 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2595 000 003 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2595 000 001 | -2.3 | 0.000 000 | -0.001 |
| 100 % | | -20 | 2595 000 007 | 4.4 | 0.000 000 | 0.002 |
| 100 % | | -10 | 2595 000 006 | 2.7 | 0.000 000 | 0.001 |
| 100 % | | 0 | 2595 000 000 | -2.8 | 0.000 000 | -0.001 |
| 100 % | | +10 | 2595 000 006 | 3.3 | 0.000 000 | 0.001 |
| 100 % | | +30 | 2595 000 006 | 2.5 | 0.000 000 | 0.001 |
| 100 % | | +40 | 2595 000 006 | 2.9 | 0.000 000 | 0.001 |
| 100 % | | +50 | 2594 999 999 | -4.1 | 0.000 000 | -0.002 |
| Batt. Endpoint | 3.300 | +20 | 2595 000 006 | 3.3 | 0.000 000 | 0.001 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2594 999 997 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2594 999 994 | -2.9 | 0.000 000 | -0.001 |
| 100 % | | -20 | 2594 999 994 | -3.2 | 0.000 000 | -0.001 |
| 100 % | | -10 | 2594 999 995 | -2.4 | 0.000 000 | -0.001 |
| 100 % | | 0 | 2594 999 995 | -2.8 | 0.000 000 | -0.001 |
| 100 % | | +10 | 2595 000 000 | 2.6 | 0.000 000 | 0.001 |
| 100 % | | +30 | 2594 999 994 | -3.5 | 0.000 000 | -0.001 |
| 100 % | | +40 | 2594 999 992 | -5.8 | 0.000 000 | -0.002 |
| 100 % | | +50 | 2594 999 992 | -5.1 | 0.000 000 | -0.002 |
| Batt. Endpoint | 3.300 | +20 | 2594 999 994 | -3.3 | 0.000 000 | -0.001 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2594 999 996 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2594 999 991 | -5.5 | 0.000 000 | -0.002 |
| 100 % | | -20 | 2594 999 992 | -4.5 | 0.000 000 | -0.002 |
| 100 % | | -10 | 2594 999 999 | 2.5 | 0.000 000 | 0.001 |
| 100 % | | 0 | 2594 999 992 | -4.3 | 0.000 000 | -0.002 |
| 100 % | | +10 | 2594 999 998 | 1.4 | 0.000 000 | 0.001 |
| 100 % | | +30 | 2594 999 993 | -3.7 | 0.000 000 | -0.001 |
| 100 % | | +40 | 2594 999 993 | -2.9 | 0.000 000 | -0.001 |
| 100 % | | +50 | 2594 999 993 | -2.8 | 0.000 000 | -0.001 |
| Batt. Endpoint | 3.300 | +20 | 2594 999 991 | -4.9 | 0.000 000 | -0.002 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2617,500,000 Hz
- ▣ BANDWIDTH: 38225 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|-----------|
| 100 % | 3.880 | +20(Ref) | 2617 499 997 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2617 499 995 | -1.7 | 0.000 000 | -0.001 |
| 100 % | | -20 | 2617 499 992 | -4.7 | 0.000 000 | -0.002 |
| 100 % | | -10 | 2617 500 000 | 2.7 | 0.000 000 | 0.001 |
| 100 % | | 0 | 2617 499 994 | -3.1 | 0.000 000 | -0.001 |
| 100 % | | +10 | 2617 499 991 | -5.6 | 0.000 000 | -0.002 |
| 100 % | | +30 | 2617 500 001 | 4.2 | 0.000 000 | 0.002 |
| 100 % | | +40 | 2617 499 993 | -4.4 | 0.000 000 | -0.002 |
| 100 % | | +50 | 2617 500 001 | 4.2 | 0.000 000 | 0.002 |
| Batt. Endpoint | | 3.300 | +20 | 2617 499 994 | -3.2 | 0.000 000 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2615,000,000 Hz
- ▣ BANDWIDTH: 38200 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2614 999 993 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2614 999 991 | -2.0 | 0.000 000 | -0.001 |
| 100 % | | -20 | 2614 999 987 | -6.2 | 0.000 000 | -0.002 |
| 100 % | | -10 | 2614 999 985 | -7.5 | 0.000 000 | -0.003 |
| 100 % | | 0 | 2614 999 989 | -4.1 | 0.000 000 | -0.002 |
| 100 % | | +10 | 2614 999 987 | -5.8 | 0.000 000 | -0.002 |
| 100 % | | +30 | 2614 999 984 | -9.2 | 0.000 000 | -0.004 |
| 100 % | | +40 | 2614 999 985 | -7.5 | 0.000 000 | -0.003 |
| 100 % | | +50 | 2614 999 987 | -5.6 | 0.000 000 | -0.002 |
| Batt. Endpoint | 3.300 | +20 | 2614 999 985 | -7.8 | 0.000 000 | -0.003 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2612,500,000 Hz
- ▣ BANDWIDTH: 38175 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2612 499 996 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2612 499 993 | -3.2 | 0.000 000 | -0.001 |
| 100 % | | -20 | 2612 499 992 | -4.6 | 0.000 000 | -0.002 |
| 100 % | | -10 | 2612 499 993 | -3.4 | 0.000 000 | -0.001 |
| 100 % | | 0 | 2612 499 992 | -3.9 | 0.000 000 | -0.001 |
| 100 % | | +10 | 2612 499 993 | -3.2 | 0.000 000 | -0.001 |
| 100 % | | +30 | 2612 499 992 | -3.9 | 0.000 000 | -0.001 |
| 100 % | | +40 | 2612 499 991 | -5.3 | 0.000 000 | -0.002 |
| 100 % | | +50 | 2612 499 999 | 2.6 | 0.000 000 | 0.001 |
| Batt. Endpoint | 3.300 | +20 | 2612 499 991 | -4.7 | 0.000 000 | -0.002 |



- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2610,000,000 Hz
- ▣ BANDWIDTH: 38150 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2609 999 995 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2609 999 989 | -5.5 | 0.000 000 | -0.002 |
| 100 % | | -20 | 2609 999 990 | -4.9 | 0.000 000 | -0.002 |
| 100 % | | -10 | 2609 999 990 | -4.3 | 0.000 000 | -0.002 |
| 100 % | | 0 | 2609 999 987 | -7.5 | 0.000 000 | -0.003 |
| 100 % | | +10 | 2609 999 984 | -10.5 | 0.000 000 | -0.004 |
| 100 % | | +30 | 2609 999 992 | -2.9 | 0.000 000 | -0.001 |
| 100 % | | +40 | 2609 999 989 | -5.4 | 0.000 000 | -0.002 |
| 100 % | | +50 | 2609 999 985 | -9.2 | 0.000 000 | -0.004 |
| Batt. Endpoint | 3.300 | +20 | 2609 999 991 | -4.1 | 0.000 000 | -0.002 |



9. TEST DATA(Sub 2 Ant)

9.1 EQUIVALENT ISOTROPIC RADIATED POWER

| Freq (MHz) | Bandwidth | Modulation | Measured Level (dBm) | Substitute Level (dBm) | Ant. Gain(dBi) | C.L | Pol | Limit | EIRP | |
|------------|-------------------|------------|----------------------|------------------------|----------------|------|-----|--------|-------|-------|
| | | | | | | | | W | W | dBm |
| 2572.5 | LTE B38/ 5 MHz | QPSK | -23.44 | 13.25 | 10.65 | 2.72 | H | < 2.00 | 0.131 | 21.18 |
| | | 16-QAM | -24.40 | 12.29 | 10.65 | 2.72 | H | | 0.105 | 20.22 |
| | | 64-QAM | -25.37 | 11.32 | 10.65 | 2.72 | H | | 0.084 | 19.25 |
| | | 256-QAM | -28.46 | 8.23 | 10.65 | 2.72 | H | | 0.041 | 16.16 |
| 2595.0 | | QPSK | -22.86 | 14.25 | 10.64 | 2.68 | H | | 0.166 | 22.21 |
| | | 16-QAM | -23.83 | 13.28 | 10.64 | 2.68 | H | | 0.133 | 21.24 |
| | | 64-QAM | -24.83 | 12.28 | 10.64 | 2.68 | H | | 0.106 | 20.24 |
| | | 256-QAM | -27.93 | 9.18 | 10.64 | 2.68 | H | | 0.052 | 17.14 |
| 2617.5 | | QPSK | -22.99 | 14.15 | 10.65 | 2.72 | H | | 0.161 | 22.08 |
| | | 16-QAM | -23.94 | 13.20 | 10.65 | 2.72 | H | | 0.130 | 21.13 |
| | | 64-QAM | -24.99 | 12.15 | 10.65 | 2.72 | H | | 0.102 | 20.08 |
| | | 256-QAM | -28.16 | 8.98 | 10.65 | 2.72 | H | | 0.049 | 16.91 |

| Freq (MHz) | Bandwidth | Modulation | Measured Level (dBm) | Substitute Level (dBm) | Ant. Gain(dBi) | C.L | Pol | Limit | EIRP | |
|------------|--------------------|------------|----------------------|------------------------|----------------|------|-----|--------|-------|-------|
| | | | | | | | | W | W | dBm |
| 2575.0 | LTE B38/ 10 MHz | QPSK | -23.37 | 13.35 | 10.65 | 2.73 | H | < 2.00 | 0.134 | 21.27 |
| | | 16-QAM | -24.33 | 12.39 | 10.65 | 2.73 | H | | 0.107 | 20.31 |
| | | 64-QAM | -25.34 | 11.38 | 10.65 | 2.73 | H | | 0.085 | 19.30 |
| | | 256-QAM | -28.37 | 8.35 | 10.65 | 2.73 | H | | 0.042 | 16.27 |
| 2595.0 | | QPSK | -22.94 | 14.17 | 10.64 | 2.68 | H | | 0.163 | 22.13 |
| | | 16-QAM | -23.91 | 13.20 | 10.64 | 2.68 | H | | 0.131 | 21.16 |
| | | 64-QAM | -24.86 | 12.25 | 10.64 | 2.68 | H | | 0.105 | 20.21 |
| | | 256-QAM | -28.03 | 9.08 | 10.64 | 2.68 | H | | 0.051 | 17.04 |
| 2615.0 | | QPSK | -23.16 | 13.99 | 10.65 | 2.66 | H | | 0.158 | 21.98 |
| | | 16-QAM | -24.00 | 13.15 | 10.65 | 2.66 | H | | 0.130 | 21.14 |
| | | 64-QAM | -24.94 | 12.21 | 10.65 | 2.66 | H | | 0.105 | 20.20 |
| | | 256-QAM | -28.12 | 9.03 | 10.65 | 2.66 | H | | 0.050 | 17.02 |

| Freq (MHz) | Bandwidth | Modulation | Measured Level (dBm) | Substitute Level (dBm) | Ant. Gain(dBi) | C.L | Pol | Limit | | EIRP | |
|------------|--------------------|------------|----------------------|------------------------|----------------|------|-----|--------|-------|-------|-----|
| | | | | | | | | W | W | dBm | dBm |
| 2577.5 | LTE B38/ 15 MHz | QPSK | -23.41 | 13.33 | 10.65 | 2.74 | H | < 2.00 | 0.133 | 21.24 | |
| | | 16-QAM | -24.21 | 12.53 | 10.65 | 2.74 | H | | 0.111 | 20.44 | |
| | | 64-QAM | -25.19 | 11.55 | 10.65 | 2.74 | H | | 0.088 | 19.46 | |
| | | 256-QAM | -28.33 | 8.41 | 10.65 | 2.74 | H | | 0.043 | 16.32 | |
| 2595.0 | | QPSK | -23.20 | 13.91 | 10.64 | 2.68 | H | | 0.154 | 21.87 | |
| | | 16-QAM | -24.03 | 13.08 | 10.64 | 2.68 | H | | 0.127 | 21.04 | |
| | | 64-QAM | -25.03 | 12.08 | 10.64 | 2.68 | H | | 0.101 | 20.04 | |
| | | 256-QAM | -28.00 | 9.11 | 10.64 | 2.68 | H | | 0.051 | 17.07 | |
| 2612.5 | | QPSK | -23.11 | 14.06 | 10.66 | 2.68 | H | | 0.160 | 22.04 | |
| | | 16-QAM | -23.95 | 13.22 | 10.66 | 2.68 | H | | 0.132 | 21.20 | |
| | | 64-QAM | -24.89 | 12.28 | 10.66 | 2.68 | H | | 0.106 | 20.26 | |
| | | 256-QAM | -28.10 | 9.07 | 10.66 | 2.68 | H | | 0.051 | 17.05 | |

| Freq (MHz) | Bandwidth | Modulation | Measured Level (dBm) | Substitute Level (dBm) | Ant. Gain(dBi) | C.L | Pol | Limit | | EIRP | |
|------------|--------------------|------------|----------------------|------------------------|----------------|------|-----|--------|-------|-------|-----|
| | | | | | | | | W | W | dBm | dBm |
| 2580.0 | LTE B38/ 20 MHz | QPSK | -23.40 | 13.34 | 10.65 | 2.74 | H | < 2.00 | 0.133 | 21.25 | |
| | | 16-QAM | -24.20 | 8.56 | 10.65 | 2.74 | H | | 0.111 | 20.45 | |
| | | 64-QAM | -25.20 | 11.54 | 10.65 | 2.74 | H | | 0.088 | 19.45 | |
| | | 256-QAM | -28.29 | 8.45 | 10.65 | 2.74 | H | | 0.043 | 16.36 | |
| 2595.0 | | QPSK | -23.14 | 13.97 | 10.64 | 2.68 | H | | 0.156 | 21.93 | |
| | | 16-QAM | -23.89 | 13.22 | 10.64 | 2.68 | H | | 0.131 | 21.18 | |
| | | 64-QAM | -24.90 | 12.21 | 10.64 | 2.68 | H | | 0.104 | 20.17 | |
| | | 256-QAM | -28.05 | 9.06 | 10.64 | 2.68 | H | | 0.050 | 17.02 | |
| 2610.0 | | QPSK | -23.16 | 14.27 | 10.64 | 2.63 | H | | 0.169 | 22.28 | |
| | | 16-QAM | -23.93 | 13.50 | 10.64 | 2.63 | H | | 0.142 | 21.51 | |
| | | 64-QAM | -24.92 | 12.51 | 10.64 | 2.63 | H | | 0.113 | 20.52 | |
| | | 256-QAM | -28.16 | 9.27 | 10.64 | 2.63 | H | | 0.053 | 17.28 | |

9.2 RADIATED SPURIOUS EMISSIONS

- ▣ OPERATING FREQUENCY : 2595.0 MHz
- ▣ MEASURED OUTPUT POWER: 22.21 dBm = 0.166 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 5 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 47.21 dBc

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | dBc |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------|
| 37775 (2572.5) | 5 145.00 | -60.51 | 12.37 | -68.50 | 3.88 | H | -60.01 | 82.21 |
| | 7 717.50 | -59.51 | 11.37 | -59.99 | 4.78 | H | -53.40 | 75.60 |
| | 10 290.00 | -62.04 | 11.54 | -56.92 | 5.58 | H | -50.96 | 73.16 |
| 38000 (2595.0) | 5 190.00 | -60.46 | 12.57 | -69.57 | 3.83 | V | -60.83 | 83.03 |
| | 7 785.00 | -59.84 | 11.41 | -60.17 | 4.79 | V | -53.55 | 75.75 |
| | 10 380.00 | -59.29 | 11.41 | -54.18 | 5.62 | H | -48.39 | 70.60 |
| 38225 (2617.5) | 5 235.00 | -59.79 | 12.84 | -69.28 | 3.95 | H | -60.39 | 82.59 |
| | 7 852.50 | -60.93 | 11.35 | -60.32 | 4.81 | V | -53.78 | 75.98 |
| | 10 470.00 | -61.70 | 11.27 | -56.41 | 5.59 | V | -50.73 | 72.93 |

- ▣ OPERATING FREQUENCY : 2595.0 MHz
- ▣ MEASURED OUTPUT POWER: 22.13 dBm = 0.163 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 10 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10}(W) =$ 47.13 dBc

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | dBc |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------|
| 37800 (2575.0) | 5 150.00 | -49.78 | 12.39 | -57.84 | 3.84 | H | -49.29 | 71.42 |
| | 7 725.00 | -59.13 | 11.38 | -59.45 | 4.78 | H | -52.86 | 74.98 |
| | 10 300.00 | -61.96 | 11.53 | -56.78 | 5.62 | H | -50.87 | 73.00 |
| 38000 (2595.0) | 5 190.00 | -60.31 | 12.57 | -69.42 | 3.83 | H | -60.68 | 82.80 |
| | 7 785.00 | -61.39 | 11.41 | -61.72 | 4.79 | H | -55.10 | 77.22 |
| | 10 380.00 | -60.86 | 11.41 | -55.75 | 5.62 | H | -49.96 | 72.09 |
| 38200 (2615.0) | 5 230.00 | -53.21 | 12.81 | -62.81 | 3.95 | H | -53.95 | 76.08 |
| | 7 845.00 | -60.70 | 11.36 | -60.08 | 4.82 | H | -53.54 | 75.67 |
| | 10 460.00 | -61.46 | 11.28 | -56.48 | 5.57 | V | -50.77 | 72.90 |

- ▣ OPERATING FREQUENCY : 2612.5 MHz
- ▣ MEASURED OUTPUT POWER: 22.04 dBm = 0.160 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 15 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10} (W) =$ 47.04 dBc

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | dBc |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------|
| 37825 (2577.5) | 5 155.00 | -54.91 | 12.42 | -62.95 | 3.81 | H | -54.34 | 76.38 |
| | 7 732.50 | -57.14 | 11.38 | -57.31 | 4.78 | H | -50.71 | 72.75 |
| | 10 310.00 | -62.28 | 11.52 | -57.10 | 5.65 | V | -51.23 | 73.27 |
| 38000 (2595.0) | 5 190.00 | -60.35 | 12.57 | -69.46 | 3.83 | H | -60.72 | 82.76 |
| | 7 785.00 | -60.57 | 11.41 | -60.90 | 4.79 | V | -54.28 | 76.31 |
| | 10 380.00 | -61.55 | 11.41 | -56.44 | 5.62 | V | -50.65 | 72.69 |
| 38175 (2612.5) | 5 225.00 | -58.10 | 12.78 | -67.93 | 3.95 | H | -59.10 | 81.13 |
| | 7 837.50 | -60.49 | 11.36 | -59.87 | 4.82 | V | -53.33 | 75.37 |
| | 10 450.00 | -61.92 | 11.29 | -57.24 | 5.60 | V | -51.55 | 73.59 |

- ▣ OPERATING FREQUENCY : 2610.0 MHz
- ▣ MEASURED OUTPUT POWER: 22.28 dBm = 0.169 W
- ▣ MODE: LTE B38
- ▣ MODULATION SIGNAL: 20 MHz QPSK
- ▣ DISTANCE: 1 meters
- ▣ LIMIT: $55 + 10 \log_{10} (W) =$ 47.28 dBc

| Ch | Freq (MHz) | Measured Level (dBm) | Ant. Gain (dBi) | Substitute Level (dBm) | C.L | Pol | Result (dBm) | dBc |
|-------------------|------------|----------------------|-----------------|------------------------|------|-----|--------------|-------|
| 37850 (2580.0) | 5 160.00 | -55.91 | 12.44 | -63.92 | 3.78 | H | -55.26 | 77.54 |
| | 7 740.00 | -57.74 | 11.40 | -57.81 | 4.76 | H | -51.17 | 73.45 |
| | 10 320.00 | -60.02 | 11.51 | -54.91 | 5.66 | H | -49.06 | 71.34 |
| 38000 (2595.0) | 5 190.00 | -57.38 | 12.57 | -66.49 | 3.83 | H | -57.75 | 80.02 |
| | 7 785.00 | -56.65 | 11.41 | -56.98 | 4.79 | V | -50.36 | 72.63 |
| | 10 380.00 | -58.97 | 11.41 | -53.86 | 5.62 | V | -48.07 | 70.35 |
| 38150 (2610.0) | 5 220.00 | -57.69 | 12.75 | -67.74 | 3.95 | H | -58.94 | 81.22 |
| | 7 830.00 | -58.43 | 11.37 | -57.86 | 4.81 | V | -51.30 | 73.58 |
| | 10 440.00 | -59.87 | 11.30 | -55.27 | 5.65 | V | -49.62 | 71.90 |

9.3 PEAK-TO-AVERAGE RATIO

| Band | Band Width | Frequency (MHz) | Modulation | Resource Block Size | Resource Block Offset | Data (dB) |
|------|------------|-----------------|------------|---------------------|-----------------------|-----------|
| 38 | 5 MHz | 2595.0 | QPSK | 25 | 0 | 4.51 |
| | | | 16-QAM | | | 5.93 |
| | | | 64-QAM | | | 6.90 |
| | | | 256-QAM | | | 7.32 |
| | 10 MHz | | QPSK | 50 | | 4.53 |
| | | | 16-QAM | | | 5.71 |
| | | | 64-QAM | | | 6.82 |
| | | | 256-QAM | | | 7.31 |
| | 15 MHz | | QPSK | 75 | | 4.51 |
| | | | 16-QAM | | | 5.57 |
| | | | 64-QAM | | | 6.48 |
| | | | 256-QAM | | | 7.40 |
| | 20 MHz | | QPSK | 100 | | 4.60 |
| | | | 16-QAM | | | 5.64 |
| | | | 64-QAM | | | 6.42 |
| | | | 256-QAM | | | 6.95 |

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 185 ~ 200.

9.4 OCCUPIED BANDWIDTH

| Band | Band Width | Frequency (MHz) | Modulation | Resource Block Size | Resource Block Offset | Data (MHz) |
|------|------------|-----------------|------------|---------------------|-----------------------|------------|
| 38 | 5 MHz | 2595.0 | QPSK | 25 | 0 | 4.5169 |
| | | | 16-QAM | | | 4.5176 |
| | | | 64-QAM | | | 4.5146 |
| | | | 256-QAM | | | 4.5057 |
| | 10 MHz | | QPSK | 50 | | 8.9871 |
| | | | 16-QAM | | | 8.9882 |
| | | | 64-QAM | | | 8.9956 |
| | | | 256-QAM | | | 8.9818 |
| | 15 MHz | | QPSK | 75 | | 13.523 |
| | | | 16-QAM | | | 13.481 |
| | | | 64-QAM | | | 13.522 |
| | | | 256-QAM | | | 13.486 |
| | 20 MHz | | QPSK | 100 | | 17.951 |
| | | | 16-QAM | | | 17.997 |
| | | | 64-QAM | | | 17.949 |
| | | | 256-QAM | | | 17.983 |

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 169 ~ 184.

9.5 CONDUCTED SPURIOUS EMISSIONS

| Band | Band Width (MHz) | Frequency (MHz) | Frequency of Maximum Harmonic (GHz) | Factor (dB) | Measurement Maximum Data (dBm) | Result (dBm) | Limit (dBm) |
|------|------------------|-----------------|-------------------------------------|-------------|--------------------------------|--------------|-------------|
| 38 | 5 | 2572.5 | 25.8461 | 34.110 | -76.849 | -42.739 | -25.00 |
| | | 2595.0 | 26.1304 | 34.110 | -76.817 | -42.707 | |
| | | 2617.5 | 3.7099 | 31.955 | -76.890 | -44.935 | |
| | 10 | 2575.0 | 26.1674 | 34.110 | -76.744 | -42.634 | |
| | | 2595.0 | 26.1109 | 34.110 | -76.784 | -42.674 | |
| | | 2615.0 | 25.8979 | 34.110 | -76.874 | -42.764 | |
| | 15 | 2577.5 | 26.1610 | 34.110 | -76.863 | -42.753 | |
| | | 2595.0 | 26.1096 | 34.110 | -76.805 | -42.695 | |
| | | 2612.5 | 26.1751 | 34.110 | -76.713 | -42.603 | |
| | 20 | 2580.0 | 26.1513 | 34.110 | -76.480 | -42.370 | |
| | | 2595.0 | 26.1976 | 34.110 | -77.052 | -42.942 | |
| | | 2610.0 | 25.8006 | 34.110 | -76.713 | -42.603 | |

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 201 ~ 224.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Duty Cycle factor already applied on the factor.
 - Duty Cycle factor(dB) = 3.979
 - Factor(dB) = Duty Cycle factor + Cable Loss + Ext. Attenuator + Power Splitter
 - Result(dBm) = Reading + Factor

| Frequency Range (GHz) | Factor [dB] |
|-----------------------|-------------|
| 0.03 – 1 | 29.249 |
| 1 – 5 | 31.955 |
| 5 – 10 | 32.570 |
| 10 – 15 | 33.095 |
| 15 – 20 | 33.468 |
| Above 20 | 34.110 |

9.6 CHANNEL EDGE

| Band Width (Modulation) | Frequency (MHz) | Modulation | RB Size / Offset | C.E ~ (C.E ± 1 MHz) | | (C.E ± 1 MHz) ~ (C.E ± 5 MHz) | |
|-------------------------|-----------------|------------|------------------|---------------------|--------|-------------------------------|--------|
| | | | | Lower | Upper | Lower | Upper |
| 5 MHz | 2572.5 | QPSK | 25 / 0 | -22.19 | -21.95 | -19.90 | -19.18 |
| | 2595.0 | QPSK | 25 / 0 | -21.46 | -22.00 | -19.32 | -19.38 |
| | 2617.5 | QPSK | 25 / 0 | -21.54 | -21.62 | -19.70 | -19.75 |
| 10 MHz | 2575.0 | QPSK | 50 / 0 | -23.81 | -23.42 | -20.21 | -20.04 |
| | 2595.0 | QPSK | 50 / 0 | -23.75 | -23.66 | -19.57 | -20.14 |
| | 2615.0 | QPSK | 50 / 0 | -23.51 | -23.41 | -19.94 | -20.21 |
| 15 MHz | 2577.5 | QPSK | 75 / 0 | -23.54 | -23.84 | -21.63 | -20.67 |
| | 2595.0 | QPSK | 75 / 0 | -24.03 | -24.37 | -21.29 | -20.98 |
| | 2612.5 | QPSK | 75 / 0 | -23.38 | -23.91 | -21.55 | -21.61 |
| 20 MHz | 2580.0 | QPSK | 100 / 0 | -24.09 | -24.00 | -22.21 | -21.69 |
| | 2595.0 | QPSK | 100 / 0 | -23.57 | -23.87 | -21.98 | -20.79 |
| | 2610.0 | QPSK | 100 / 0 | -24.29 | -24.66 | -20.77 | -22.02 |
| Limit(dBm) | | | | -10.0 | | -10.0 | |

| Band Width (Modulation) | Frequency (MHz) | Modulation | Resource Block Size | (C.E ± 5 MHz) ~ (C.E ± X MHz) | | Above (C.E ± X MHz) | |
|-------------------------|-----------------|------------|---------------------|-------------------------------|--------|---------------------|--------|
| | | | | Lower | Upper | Lower | Upper |
| 5 MHz | 2572.5 | QPSK | 25 / 0 | -28.56 | -28.32 | -30.23 | -29.90 |
| | 2595.0 | QPSK | 25 / 0 | -28.50 | -28.23 | -31.47 | -30.02 |
| | 2617.5 | QPSK | 25 / 0 | -28.39 | -29.37 | -31.59 | -30.98 |
| 10 MHz | 2575.0 | QPSK | 50 / 0 | -23.33 | -23.68 | -32.60 | -32.41 |
| | 2595.0 | QPSK | 50 / 0 | -23.70 | -23.41 | -33.31 | -31.73 |
| | 2615.0 | QPSK | 50 / 0 | -23.55 | -24.35 | -33.65 | -33.29 |
| 15 MHz | 2577.5 | QPSK | 75 / 0 | -25.81 | -25.70 | -34.90 | -34.49 |
| | 2595.0 | QPSK | 75 / 0 | -24.07 | -25.11 | -34.75 | -33.99 |
| | 2612.5 | QPSK | 75 / 0 | -26.06 | -26.38 | -35.75 | -35.10 |
| 20 MHz | 2580.0 | QPSK | 100 / 0 | -25.67 | -25.22 | -35.06 | -35.53 |
| | 2595.0 | QPSK | 100 / 0 | -25.02 | -25.38 | -35.05 | -34.99 |
| | 2610.0 | QPSK | 100 / 0 | -25.68 | -24.21 | -36.08 | -35.68 |
| Limit(dBm) | | | | -13.0 | | -25.0 | |


Note:

1. C.E = Channel Edge
2. X = X is the greater of 6 MHz or the actual emission bandwidth.
3. X = 6 MHz(5 MHz Bandwidth), 10 MHz(10 MHz Bandwidth), 15 MHz(15 MHz Bandwidth), 20 MHz(20 MHz Bandwidth)
4. RB = Resource Block
5. Duty Cycle factor already applied on the factor.
 - Factor(dB) = Duty Cycle factor + Cable Loss + Ext. Attenuator + Power Splitter
 - Result(dBm) = Reading + Factor
 - Duty Cycle Factor(dB) = 3.979
6. Plots of the EUT's Channel Edge are shown Page 149 ~ 168. (1RB & Full RB)

9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2572,500,000 Hz
- ▣ BANDWIDTH: 37775 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|-----------|
| 100 % | 3.880 | +20(Ref) | 2572 500 005 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2572 500 008 | 3.7 | 0.000 000 | 0.001 |
| 100 % | | -20 | 2572 500 011 | 6.5 | 0.000 000 | 0.003 |
| 100 % | | -10 | 2572 500 003 | -1.8 | 0.000 000 | -0.001 |
| 100 % | | 0 | 2572 500 008 | 3.8 | 0.000 000 | 0.001 |
| 100 % | | +10 | 2572 500 008 | 3.6 | 0.000 000 | 0.001 |
| 100 % | | +30 | 2572 500 007 | 2.8 | 0.000 000 | 0.001 |
| 100 % | | +40 | 2572 500 007 | 1.9 | 0.000 000 | 0.001 |
| 100 % | | +50 | 2572 500 010 | 5.6 | 0.000 000 | 0.002 |
| Batt. Endpoint | | 3.300 | +20 | 2572 500 007 | 2.7 | 0.000 000 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2575,000,000 Hz
- ▣ BANDWIDTH: 37800 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2574 999 995 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2574 999 990 | -4.4 | 0.000 000 | -0.002 |
| 100 % | | -20 | 2574 999 992 | -3.0 | 0.000 000 | -0.001 |
| 100 % | | -10 | 2574 999 992 | -3.1 | 0.000 000 | -0.001 |
| 100 % | | 0 | 2574 999 999 | 4.3 | 0.000 000 | 0.002 |
| 100 % | | +10 | 2574 999 998 | 3.5 | 0.000 000 | 0.001 |
| 100 % | | +30 | 2574 999 998 | 2.9 | 0.000 000 | 0.001 |
| 100 % | | +40 | 2574 999 998 | 2.9 | 0.000 000 | 0.001 |
| 100 % | | +50 | 2574 999 992 | -2.2 | 0.000 000 | -0.001 |
| Batt. Endpoint | 3.300 | +20 | 2574 999 992 | -3.0 | 0.000 000 | -0.001 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2577,500,000 Hz
- ▣ BANDWIDTH: 37825 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2577 499 995 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2577 499 992 | -3.2 | 0.000 000 | -0.001 |
| 100 % | | -20 | 2577 499 991 | -3.5 | 0.000 000 | -0.001 |
| 100 % | | -10 | 2577 499 989 | -5.4 | 0.000 000 | -0.002 |
| 100 % | | 0 | 2577 499 990 | -5.0 | 0.000 000 | -0.002 |
| 100 % | | +10 | 2577 499 993 | -2.1 | 0.000 000 | -0.001 |
| 100 % | | +30 | 2577 499 991 | -3.7 | 0.000 000 | -0.001 |
| 100 % | | +40 | 2577 499 991 | -4.2 | 0.000 000 | -0.002 |
| 100 % | | +50 | 2577 499 989 | -5.6 | 0.000 000 | -0.002 |
| Batt. Endpoint | 3.300 | +20 | 2577 499 988 | -6.5 | 0.000 000 | -0.003 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2580,000,000 Hz
- ▣ BANDWIDTH: 37850 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|-----------|
| 100 % | 3.880 | +20(Ref) | 2579 999 995 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2579 999 990 | -5.0 | 0.000 000 | -0.002 |
| 100 % | | -20 | 2579 999 992 | -3.1 | 0.000 000 | -0.001 |
| 100 % | | -10 | 2579 999 993 | -2.5 | 0.000 000 | -0.001 |
| 100 % | | 0 | 2580 000 000 | 4.7 | 0.000 000 | 0.002 |
| 100 % | | +10 | 2580 000 000 | 5.2 | 0.000 000 | 0.002 |
| 100 % | | +30 | 2579 999 999 | 3.8 | 0.000 000 | 0.001 |
| 100 % | | +40 | 2579 999 999 | 4.4 | 0.000 000 | 0.002 |
| 100 % | | +50 | 2579 999 992 | -3.5 | 0.000 000 | -0.001 |
| Batt. Endpoint | | 3.300 | +20 | 2579 999 998 | 2.9 | 0.000 000 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2595 000 004 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2595 000 007 | 3.2 | 0.000 000 | 0.001 |
| 100 % | | -20 | 2595 000 001 | -2.8 | 0.000 000 | -0.001 |
| 100 % | | -10 | 2595 000 008 | 4.0 | 0.000 000 | 0.002 |
| 100 % | | 0 | 2595 000 007 | 3.2 | 0.000 000 | 0.001 |
| 100 % | | +10 | 2595 000 009 | 5.1 | 0.000 000 | 0.002 |
| 100 % | | +30 | 2595 000 007 | 3.3 | 0.000 000 | 0.001 |
| 100 % | | +40 | 2595 000 000 | -3.5 | 0.000 000 | -0.001 |
| 100 % | | +50 | 2595 000 010 | 6.2 | 0.000 000 | 0.002 |
| Batt. Endpoint | 3.300 | +20 | 2595 000 000 | -4.0 | 0.000 000 | -0.002 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2595 000 003 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2595 000 008 | 4.6 | 0.000 000 | 0.002 |
| 100 % | | -20 | 2595 000 006 | 2.4 | 0.000 000 | 0.001 |
| 100 % | | -10 | 2595 000 007 | 3.6 | 0.000 000 | 0.001 |
| 100 % | | 0 | 2595 000 007 | 3.8 | 0.000 000 | 0.001 |
| 100 % | | +10 | 2595 000 001 | -2.7 | 0.000 000 | -0.001 |
| 100 % | | +30 | 2595 000 000 | -3.0 | 0.000 000 | -0.001 |
| 100 % | | +40 | 2595 000 008 | 4.3 | 0.000 000 | 0.002 |
| 100 % | | +50 | 2595 000 008 | 4.6 | 0.000 000 | 0.002 |
| Batt. Endpoint | 3.300 | +20 | 2595 000 007 | 4.2 | 0.000 000 | 0.002 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2594 999 997 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2594 999 995 | -2.4 | 0.000 000 | -0.001 |
| 100 % | | -20 | 2594 999 995 | -2.1 | 0.000 000 | -0.001 |
| 100 % | | -10 | 2594 999 999 | 2.0 | 0.000 000 | 0.001 |
| 100 % | | 0 | 2594 999 995 | -2.7 | 0.000 000 | -0.001 |
| 100 % | | +10 | 2595 000 000 | 2.8 | 0.000 000 | 0.001 |
| 100 % | | +30 | 2594 999 995 | -2.6 | 0.000 000 | -0.001 |
| 100 % | | +40 | 2595 000 000 | 2.2 | 0.000 000 | 0.001 |
| 100 % | | +50 | 2595 000 000 | 2.3 | 0.000 000 | 0.001 |
| Batt. Endpoint | 3.300 | +20 | 2595 000 000 | 2.4 | 0.000 000 | 0.001 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2595,000,000 Hz
- ▣ BANDWIDTH: 38000 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2594 999 997 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2595 000 002 | 5.3 | 0.000 000 | 0.002 |
| 100 % | | -20 | 2595 000 003 | 6.2 | 0.000 000 | 0.002 |
| 100 % | | -10 | 2595 000 002 | 5.1 | 0.000 000 | 0.002 |
| 100 % | | 0 | 2595 000 001 | 3.6 | 0.000 000 | 0.001 |
| 100 % | | +10 | 2594 999 999 | 1.8 | 0.000 000 | 0.001 |
| 100 % | | +30 | 2595 000 002 | 5.3 | 0.000 000 | 0.002 |
| 100 % | | +40 | 2595 000 002 | 5.1 | 0.000 000 | 0.002 |
| 100 % | | +50 | 2595 000 000 | 2.7 | 0.000 000 | 0.001 |
| Batt. Endpoint | 3.300 | +20 | 2594 999 993 | -3.8 | 0.000 000 | -0.001 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2617,500,000 Hz
- ▣ BANDWIDTH: 38225 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|-----------|
| 100 % | 3.880 | +20(Ref) | 2617 499 994 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2617 499 989 | -5.3 | 0.000 000 | -0.002 |
| 100 % | | -20 | 2617 499 989 | -4.7 | 0.000 000 | -0.002 |
| 100 % | | -10 | 2617 499 988 | -6.0 | 0.000 000 | -0.002 |
| 100 % | | 0 | 2617 499 989 | -4.5 | 0.000 000 | -0.002 |
| 100 % | | +10 | 2617 499 986 | -7.7 | 0.000 000 | -0.003 |
| 100 % | | +30 | 2617 499 988 | -6.2 | 0.000 000 | -0.002 |
| 100 % | | +40 | 2617 499 991 | -3.1 | 0.000 000 | -0.001 |
| 100 % | | +50 | 2617 499 990 | -3.6 | 0.000 000 | -0.001 |
| Batt. Endpoint | | 3.300 | +20 | 2617 499 991 | -2.6 | 0.000 000 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2615,000,000 Hz
- ▣ BANDWIDTH: 38200 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2614 999 991 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2614 999 984 | -7.6 | 0.000 000 | -0.003 |
| 100 % | | -20 | 2614 999 983 | -7.9 | 0.000 000 | -0.003 |
| 100 % | | -10 | 2614 999 984 | -7.3 | 0.000 000 | -0.003 |
| 100 % | | 0 | 2614 999 985 | -5.7 | 0.000 000 | -0.002 |
| 100 % | | +10 | 2614 999 985 | -6.1 | 0.000 000 | -0.002 |
| 100 % | | +30 | 2614 999 987 | -4.6 | 0.000 000 | -0.002 |
| 100 % | | +40 | 2614 999 984 | -6.8 | 0.000 000 | -0.003 |
| 100 % | | +50 | 2614 999 982 | -8.9 | 0.000 000 | -0.003 |
| Batt. Endpoint | 3.300 | +20 | 2614 999 987 | -4.0 | 0.000 000 | -0.002 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2612,500,000 Hz
- ▣ BANDWIDTH: 38175 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2612 499 993 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2612 499 989 | -4.6 | 0.000 000 | -0.002 |
| 100 % | | -20 | 2612 499 990 | -3.4 | 0.000 000 | -0.001 |
| 100 % | | -10 | 2612 499 990 | -3.2 | 0.000 000 | -0.001 |
| 100 % | | 0 | 2612 499 998 | 4.6 | 0.000 000 | 0.002 |
| 100 % | | +10 | 2612 499 989 | -4.7 | 0.000 000 | -0.002 |
| 100 % | | +30 | 2612 499 988 | -5.6 | 0.000 000 | -0.002 |
| 100 % | | +40 | 2612 499 990 | -3.0 | 0.000 000 | -0.001 |
| 100 % | | +50 | 2612 499 990 | -3.4 | 0.000 000 | -0.001 |
| Batt. Endpoint | 3.300 | +20 | 2612 499 991 | -2.0 | 0.000 000 | -0.001 |




- ▣ MODE: LTE 38
- ▣ OPERATING FREQUENCY: 2610,000,000 Hz
- ▣ BANDWIDTH: 38150 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.880 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency (Hz) | Frequency Error (Hz) | Deviation (%) | ppm |
|----------------|-------------|------------|----------------|----------------------|---------------|--------|
| 100 % | 3.880 | +20(Ref) | 2609 999 993 | 0.0 | 0.000 000 | 0.000 |
| 100 % | | -30 | 2609 999 989 | -4.5 | 0.000 000 | -0.002 |
| 100 % | | -20 | 2609 999 989 | -3.9 | 0.000 000 | -0.001 |
| 100 % | | -10 | 2609 999 987 | -6.2 | 0.000 000 | -0.002 |
| 100 % | | 0 | 2609 999 989 | -4.2 | 0.000 000 | -0.002 |
| 100 % | | +10 | 2609 999 989 | -4.1 | 0.000 000 | -0.002 |
| 100 % | | +30 | 2609 999 987 | -6.0 | 0.000 000 | -0.002 |
| 100 % | | +40 | 2609 999 989 | -4.1 | 0.000 000 | -0.002 |
| 100 % | | +50 | 2609 999 990 | -3.1 | 0.000 000 | -0.001 |
| Batt. Endpoint | 3.300 | +20 | 2609 999 987 | -6.4 | 0.000 000 | -0.002 |




10. TEST PLOTS(Main 2 Ant)


LTE38_5 M_Channel Edge_Low_2572.5 MHz_QPSK_1RB




LTE38_5 M_Channel Edge_Low_2572.5 MHz_QPSK_Full RB




LTE38_5 M_Channel Edge_Mid_2595.0 MHz_QPSK_Full RB




LTE38_5 M_Channel Edge_High_2617.5 MHz_QPSK_1RB




LTE38_5 M_Channel Edge_High_2617.5 MHz_QPSK_Full RB




LTE38_10 M_Channel Edge_Low_2575 MHz_QPSK_1RB




LTE38_10 M_Channel Edge_Low_2575.0 MHz_QPSK_Full RB




LTE38_10 M_Channel Edge_Mid_2595.0 MHz_QPSK_Full RB




LTE38_10 M_Channel Edge_High_2615.0 MHz_QPSK_1RB




LTE38_10 M_Channel Edge_High_2615.0 MHz_QPSK_Full RB




LTE38_15 M_Channel Edge_Low_2577.5 MHz_QPSK_1RB




LTE38_15 M_Channel Edge_Low_2577.5 MHz_QPSK_Full RB




LTE38_15 M_Channel Edge_Mid_2595.0 MHz_QPSK_Full RB




LTE38_15 M_Channel Edge_High_2612.5 MHz_QPSK_1RB




LTE38_15 M_Channel Edge_High_2612.5 MHz_QPSK_Full RB




LTE38_20 M_Channel Edge_Low_2580.0 MHz_QPSK_1RB




LTE38_20 M_Channel Edge_Low_2580.0 MHz_QPSK_Full RB




LTE38_20 M_Channel Edge_Mid_2595.0 MHz_QPSK_Full RB




LTE38_20 M_Channel Edge_High_2610.0 MHz_QPSK_1RB




LTE38_20 M_Channel Edge_High_2610.0 MHz_QPSK_Full RB




LTE38_5 M_OBW_Mid Channel_QPSK_Full RB




LTE38_5 M_OBW_Mid Channel_16QAM_Full RB




LTE38_5 M_OBW_Mid Channel_64QAM_Full RB




LTE38_5 M_OBW_Mid Channel_256QAM_Full RB




LTE38_10 M_OBW_Mid Channel_QPSK_Full RB




LTE38_10 M_OBW_Mid Channel_16QAM_Full RB




LTE38_10 M_OBW_Mid Channel_64QAM_Full RB




LTE38_10 M_OBW_Mid Channel_256QAM_Full RB




LTE38_15 M_OBW_Mid Channel_QPSK_Full RB




LTE38_15 M_OBW_Mid Channel_16QAM_Full RB




LTE38_15 M_OBW_Mid Channel_64QAM_Full RB




LTE38_15 M_OBW_Mid Channel_256QAM_Full RB




LTE38_20 M_OBW_Mid Channel_QPSK_Full RB




LTE38_20 M_OBW_Mid Channel_16QAM_Full RB




LTE38_20 M_OBW_Mid Channel_64QAM_Full RB




LTE38_20 M_OBW_Mid Channel_256QAM_Full RB




LTE38_5 M_PAR_Mid Channel_QPSK_Full RB




LTE38_5 M_PAR_Mid Channel_16QAM_Full RB




LTE38_5 M_PAR_Mid Channel_64QAM_Full RB




LTE38_5 M_PAR_Mid Channel_256QAM_Full RB




LTE38_10 M_PAR_Mid Channel_QPSK_Full RB




LTE38_10 M_PAR_Mid Channel_16QAM_Full RB




LTE38_10 M_PAR_Mid Channel_64QAM_Full RB




LTE38_10 M_PAR_Mid Channel_256QAM_Full RB




LTE38_15 M_PAR_Mid Channel_QPSK_Full RB




LTE38_15 M_PAR_Mid Channel_16QAM_Full RB




LTE38_15 M_PAR_Mid Channel_64QAM_Full RB




LTE38_15 M_PAR_Mid Channel_256QAM_Full RB




LTE38_20 M_PAR_Mid Channel_QPSK_Full RB




LTE38_20 M_PAR_Mid Channel_16QAM_Full RB




LTE38_20 M_PAR_Mid Channel_64QAM_Full RB




LTE38_20 M_PAR_Mid Channel_256QAM_Full RB




LTE38_5 M_CSE(30 M-10 G)_Lowest Channel




LTE38_5 M_CSE(30 M-10 G)_Mid Channel




LTE38_5 M_CSE(30 M-10 G)_Highest Channel




LTE38_10 M_CSE(30 M-10 G)_Lowest Channel




LTE38_10 M_CSE(30 M-10 G)_Mid Channel




LTE38_10 M_CSE(30 M-10 G)_Highest Channel




LTE38_15 M_CSE(30 M-10 G)_Lowest Channel




LTE38_15 M_CSE(30 M-10 G)_Mid Channel




LTE38_15 M_CSE(30 M-10 G)_Highest Channel




LTE38_20 M_CSE(30 M-10 G)_Lowest Channel



LTE38_20 M_CSE(30 M-10 G)_Mid Channel



LTE38_20 M_CSE(30 M-10 G)_Highest Channel



LTE38_5 M_CSE(Above 10 G)_Lowest Channel



LTE38_5 M_CSE(Above10 G)_Mid Channel



LTE38_5 M_CSE(Above10 G)_Highest Channel



LTE38_10 M_CSE(Above10 G)_Lowest Channel



LTE38_10 M_CSE(Above10 G)_Mid Channel



LTE38_10 M_CSE(Above10 G)_Highest Channel



LTE38_15 M_CSE(Above10 G)_Lowest Channel



LTE38_15 M_CSE(Above10 G)_Mid Channel



LTE38_15 M_CSE(Above10 G)_Highest Channel



LTE38_20 M_CSE(Above10 G)_Lowest Channel



LTE38_20 M_CSE(Above10 G)_Mid Channel




LTE38_20 M_CSE(Above10 G)_Highest Channel




11. TEST PLOTS(Sub 2 Ant)


LTE38_5 M_Channel Edge_Low_2572.5 MHz_QPSK_1RB




LTE38_5 M_Channel Edge_Low_2572.5 MHz_QPSK_Full RB




LTE38_5 M_Channel Edge_Mid_2595.0 MHz_QPSK_Full RB




LTE38_5 M_Channel Edge_High_2617.5 MHz_QPSK_1RB




LTE38_5 M_Channel Edge_High_2617.5 MHz_QPSK_Full RB




LTE38_10 M_Channel Edge_Low_2575 MHz_QPSK_1RB




LTE38_10 M_Channel Edge_Low_2575.0 MHz_QPSK_Full RB




LTE38_10 M_Channel Edge_Mid_2595.0 MHz_QPSK_Full RB




LTE38_10 M_Channel Edge_High_2615.0 MHz_QPSK_1RB




LTE38_10 M_Channel Edge_High_2615.0 MHz_QPSK_Full RB




LTE38_15 M_Channel Edge_Low_2577.5 MHz_QPSK_1RB




LTE38_15 M_Channel Edge_Low_2577.5 MHz_QPSK_Full RB




LTE38_15 M_Channel Edge_Mid_2595.0 MHz_QPSK_Full RB




LTE38_15 M_Channel Edge_High_2612.5 MHz_QPSK_1RB



LTE38_15 M_Channel Edge_High_2612.5 MHz_QPSK_Full RB



LTE38_20 M_Channel Edge_Low_2580.0 MHz_QPSK_1RB



LTE38_20 M_Channel Edge_Low_2580.0 MHz_QPSK_Full RB

