

# FCC Sub6 REPORT

## Certification

<b>Applicant Name:</b> SAMSUNG Electronics Co., Ltd.	<b>Date of Issue:</b> October 16, 2023
<b>Address:</b> 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea	<b>Location:</b> HCT CO., LTD., 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA
<b>Report No.:</b> HCT-RF-2310-FC046	

<b>FCC ID:</b>	<b>A3LSMS926U</b>
<b>APPLICANT:</b>	<b>SAMSUNG Electronics Co., Ltd.</b>

Model(s): SM-S926U  
 Additional Model(s): SM-S926U1  
 EUT Type: Mobile phone  
 FCC Classification: Citizens Band End User Devices (CBE)  
 FCC Rule Part(s): §96

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W/10 MHz)	Max. Power (dBm/10 MHz)
Sub6 n48 (10)	3555.00 – 3694.98	8M68G7D	PI/2 BPSK	0.125	20.97
		8M71G7D	QPSK	0.119	20.76
		8M67W7D	16QAM	0.093	19.69
		8M67W7D	64QAM	0.069	18.36
		8M65W7D	256QAM	0.040	15.97
Sub6 n48 (15)	3557.52 – 3692.49	13M0G7D	PI/2 BPSK	0.122	20.86
		13M0G7D	QPSK	0.119	20.76
		13M0W7D	16QAM	0.091	19.57
		12M9W7D	64QAM	0.068	18.31
		12M9W7D	256QAM	0.040	16.06
Sub6 n48 (20)	3560.01 – 3690.00	17M9G7D	PI/2 BPSK	0.124	20.93
		18M0G7D	QPSK	0.121	20.84
		18M0W7D	16QAM	0.094	19.75
		17M9W7D	64QAM	0.068	18.33
		17M9W7D	256QAM	0.041	16.08
Sub6 n48 (30)	3565.02 – 3684.99	27M0G7D	PI/2 BPSK	0.132	21.22
		27M0G7D	QPSK	0.131	21.16
		26M9W7D	16QAM	0.099	19.95
		27M0W7D	64QAM	0.071	18.50
		26M9W7D	256QAM	0.044	16.40
Sub6 n48 (40)	3570.00 – 3679.98	35M9G7D	PI/2 BPSK	0.131	21.17
		35M9G7D	QPSK	0.128	21.07
		35M9W7D	16QAM	0.097	19.87
		35M9W7D	64QAM	0.073	18.62
		35M9W7D	256QAM	0.042	16.27

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)

Report No.: HCT-RF-2310-FC046

---

REVIEWED BY



---

Report prepared by : Jae Ryang Do  
Engineer of Telecommunication Testing Center

---

Report approved by : Jong Seok Lee  
Manager of Telecommunication Testing Center

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.  
This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked \*.  
The above Test Report is the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

The report shall not be reproduced except in full(only partly) without approval of the laboratory.

## Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-2310-FC046	October 16, 2023	- First Approval Report

## Table of Contents

REVIEWED BY .....	2
1. GENERAL INFORMATION .....	5
2. INTRODUCTION .....	6
2.1. DESCRIPTION OF EUT .....	6
2.2. MEASURING INSTRUMENT CALIBRATION .....	6
2.3. TEST FACILITY .....	6
3. DESCRIPTION OF TESTS.....	7
3.1 TEST PROCEDURE .....	7
3.2 RADIATED POWER.....	8
3.3 RADIATED SPURIOUS EMISSIONS .....	9
3.4 PEAK- TO- AVERAGE RATIO.....	10
3.5 OCCUPIED BANDWIDTH. ....	12
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL .....	13
3.7 CHANNEL EDGE.....	14
3.8 Adjacent Channel Leakage Ratio.....	15
3.9 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE .....	16
3.10 End User Device Additional Requirement (CBSD Protocol).....	17
3.11 WORST CASE(RADIATED TEST) .....	18
3.12 WORST CASE(CONDUCTED TEST) .....	19
4. LIST OF TEST EQUIPMENT .....	20
5. MEASUREMENT UNCERTAINTY .....	21
6. SUMMARY OF TEST RESULTS .....	22
7. SAMPLE CALCULATION .....	23
8. TEST DATA .....	25
8.1 EQUIVALENT ISOTROPIC RADIATED POWER.....	25
8.2 RADIATED SPURIOUS EMISSIONS .....	30
8.3 PEAK-TO-AVERAGE RATIO.....	35
8.4 OCCUPIED BANDWIDTH .....	36
8.5 CONDUCTED SPURIOUS EMISSIONS .....	37
8.6 CHANNEL EDGE.....	38
8.7 Adjacent Channel Leakage Ratio(ACLR) .....	40
8.8 End User Device Additional Requirement (CBSD Protocol).....	41
8.9 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE .....	45
9. TEST PLOTS.....	50
10. ANNEX A_ TEST SETUP PHOTO.....	201

# MEASUREMENT REPORT

## 1. GENERAL INFORMATION

<b>Applicant Name:</b>	SAMSUNG Electronics Co., Ltd.
<b>Address:</b>	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
<b>FCC ID:</b>	A3LSMS926U
<b>Application Type:</b>	Certification
<b>FCC Classification:</b>	Citizens Band End User Devices (CBE)
<b>FCC Rule Part(s):</b>	§96
<b>EUT Type:</b>	Mobile phone
<b>Model(s):</b>	SM-S926U
<b>Additional Model(s):</b>	SM-S926U1
<b>SCS(kHz):</b>	30
<b>Bandwidth(MHz):</b>	10, 15, 20, 30, 40
<b>Waveform:</b>	CP-OFDM, DFT-S-OFDM
<b>Modulation:</b>	DFT-S-OFDM: PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM CP-OFDM: QPSK, 16QAM, 64QAM, 256QAM
<b>Tx Frequency:</b>	3555.00 – 3694.98 : (Sub6 n48(10 MHz)) 3557.52 – 3692.49 : (Sub6 n48(15 MHz)) 3560.01 – 3690.00 : (Sub6 n48(20 MHz)) 3565.02 – 3684.99 : (Sub6 n48(30 MHz)) 3570.00 – 3679.98 : (Sub6 n48(40 MHz))
<b>Date(s) of Tests:</b>	August 31, 2023 ~ October 11, 2023
<b>Serial number:</b>	Radiated: R3CW90B4EDB Conducted: R3CW80MBYBM CBSD Protocol : R3CW90B4FYH

## **2. INTRODUCTION**

### **2.1. DESCRIPTION OF EUT**

The EUT was a Mobile Phone with GSM/GPRS/EGPRS/UMTS and LTE, Sub6, mmWave.

It also supports IEEE 802.11 a/b/g/n/ac/ax (20/40/80/160 MHz), WIFI 6E, Bluetooth, BT LE, NFC, UWB, WPT.

### **2.2. MEASURING INSTRUMENT CALIBRATION**

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

### **2.3. TEST FACILITY**

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

### 3. DESCRIPTION OF TESTS

#### 3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4 - KDB 940660 D01 v01
Channel Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7 - KDB 940660 D01 v01
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7 - KDB 940660 D01 v01
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4 - KDB 940660 D01 v01
Frequency stability	- ANSI C63.26-2015 – Section 5.6 - KDB 940660 D01 v01
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17 - KDB 940660 D01 v01
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12 - KDB 940660 D01 v01
End User Device Additional Requirement (CBSD Protocol)	- KDB 940660 D01 v01 - WINNF-18-IN-00178 v1.0.0.00

## 3.2 RADIATED POWER

### Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

### Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW ≥ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was set equal to 10 MHz.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

### Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(\text{dBm})} = P_{g(\text{dBm})} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where:  $P_d$  is the dipole equivalent power and  $P_g$  is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration
4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.



### 3.3 RADIATED SPURIOUS EMISSIONS

#### Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

#### Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and NormalHz for emissions above 1 GHz
2. VBW  $\geq 3 \times$  RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $> 2 \times$  span / RBW
5. Detector = RMS
6. Trace mode = Average
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10<sup>th</sup> harmonics from 9 kHz.

#### Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin  $> 20$  dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_{g(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where:  $P_g$  is the generator output power into the substitution antenna.

If the fundamental frequency is below 1GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15 \text{ dB}$$

### 3.4 PEAK- TO- AVERAGE RATIO



**Test setup**

① CCDF Procedure for PAPR

**Test Settings**

1. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
  - for continuous transmissions, set to 1 ms,
  - or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as  $P_{Pk}$ .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as  $P_{Avg}$ . Determine the P.A.R. from:

$$P.A.R_{(dB)} = P_{Pk} (dBm) - P_{Avg} (dBm) \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

### **Test Settings(Peak Power)**


The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW  $\geq 3 \times$  RBW.

1. Set the RBW  $\geq$  OBW.
2. Set VBW  $\geq 3 \times$  RBW.
3. Set span  $\geq 2 \times$  OBW.
4. Sweep time  $\geq 10 \times$  (number of points in sweep)  $\times$  (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

### **Test Settings(Average Power)**

1. Set span to  $2 \times$  to  $3 \times$  the OBW.
2. Set RBW  $\geq$  OBW.
3. Set VBW  $\geq 3 \times$  RBW.
4. Set number of measurement points in sweep  $\geq 2 \times$  span / RBW.
5. Sweep time:  
  
Set  $\geq [10 \times$  (number of points in sweep)  $\times$  (transmission period)] for single sweep  
(automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add  $[10 \log (1/\text{duty cycle})]$  to the measured maximum power level to compute the average power during continuous transmission. For example, add  $[10 \log (1/0.25)] = 6$  dB if the duty cycle is a constant 25%.

### 3.5 OCCUPIED BANDWIDTH.



#### Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

#### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5 % of the expected OBW
3. VBW  $\geq$  3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99% occupied bandwidth observed in Step 7

### 3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



**Test setup**


#### **Test Overview**

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

#### **Test Settings**

1. RBW = 1 MHz
2. VBW  $\geq$  3 MHz
3. Detector = RMS
4. Trace Mode = Average
5. Sweep time = auto
6. Number of points in sweep  $\geq$  2 x Span / RBW

### 3.7 CHANNEL EDGE



**Test setup**

#### **Test Settings**

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. Within 1 MHz of the channel edge the RBW should be 2% of EBW, then 1 MHz after that.
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points  $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize


#### **Test Notes**

The conducted power of any emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed  $-13 \text{ dBm/MHz}$  within 0-10 megahertz above the upper SAS-assigned channel edge and within 0-10 megahertz below the lower SAS-assigned channel edge. At all frequencies greater than 10 megahertz above the upper SAS assigned channel edge and less than 10 MHz below the lower SAS assigned channel edge, the conducted power of any emission shall not exceed  $-25 \text{ dBm/MHz}$ .

The conducted power of any emissions below 3530 MHz or above 3720 MHz shall not exceed  $-40 \text{ dBm/MHz}$

Where Margin < 1 dB the emission level is either corrected by  $10 \log(1 \text{ MHz/ RB})$  or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

### 3.8 Adjacent Channel Leakage Ratio



**Test setup**


#### **Test Settings**

1. Use ACP measurement function of Spectrum analyzer to measure adjacent channel leakage ratio
2. Integral BW = Assigned channel bandwidth
5. Detector = RMS
6. Number of sweep points  $\geq 2 \times \text{Span}/\text{RBW}$
7. Trace mode = trace average
8. Sweep time = 1 s
9. The trace was allowed to stabilize

#### **Test Notes**

the Adjacent Channel Leakage Ratio for End User Devices shall be at least 30 dB.

### 3.9 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



**Test setup**

#### **Test Overview**

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.

2. Primary Supply Voltage:


- Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.
- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

#### **Test Settings**

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.



### 3.10 End User Device Additional Requirement (CBSD Protocol)



**Test setup**

#### **Test Overview**

End user device additional requirements (CBSD Protocol) are tested per the test procedures listed below. During testing, the EUT is connected to a certified CBSD (FCC ID: PIDAS2900) as a companion device to show compliance with Part 96.47.

End User Devices may operate only if they can positively receive and decode an authorization signal transmitted by a CBSD, including the frequencies and power limits for their operation.

#### **Test Channel & Power**

1. Setup companion device with 3560 MHz - 3580 MHz(BW 20MHz) and power level 5 dBm
2. Setup companion device with 3640 MHz - 3680 MHz(BW 40MHz) and power level 20 dBm

#### **Test Procedure**

1. Enable AP service from companion device.
2. EUT is connected to a companion device.
3. Check EUT Tx frequency and power.
4. Disable AP service from companion device and check EUT stop transmission within 10 s.

**3.11 WORST CASE(RADIATED TEST)**

- Waveform : All Waveform of operation were investigated and the worst case configuration results are reported.  
(Worst case: DFT-S-OFDM)
- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.  
Mode: SA, SRS  
Worst case : SA  
Mode : Stand alone, Stand alone + External accessories (Earphone, AC adapter, etc)  
Worst case : Stand alone
- We were performed the RSE test in condition of co-location.  
Mode : Stand alone, Simultaneous transmission scenarios  
Worst case : Stand alone
- All RB sizes, offsets of operation were investigated and the worst case configuration results are reported.  
Please refer to the table below.
- SM-S926U & additional models were tested and the worst case results are reported.  
(Worst case : SM-S926U)

[ Worst case ]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM	See Section 8.1		Y
Radiated Spurious and Harmonic Emissions	PI/2 BPSK	See Section 8.2		X

**3.12 WORST CASE(CONDUCTED TEST)**

- Waveform : All Waveform of operation were investigated and the worst case configuration results are reported.

(Worst case: DFT-S-OFDM)

- Modulation : All Modulation of operation were investigated and the worst case configuration results are reported.

(Worst case: PI/2 BPSK)

- All modes of operation were investigated and the worst case configuration results are reported.

Mode: SA, SRS

Worst case : SA

- All RB sizes, offsets of operation were investigated and the worst case configuration results are reported.

Please refer to the table below.

- SM-S926U & additional models were tested and the worst case results are reported.

(Worst case : SM-S926U)

[ Worst case ]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth, Peak-To-Average Ratio	PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM	10, 15, 20, 30, 40	Mid	Full RB	0
Channel Edge	PI/2 BPSK	10	Low	1	0
			High	1	23
		15	Low	1	0
			High	1	37
		20	Low	1	0
			High	1	50
		30	Low	1	0
			High	1	77
		40	Low	1	0
			High	1	105
		10, 15, 20, 30, 40	Low, Mid, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	PI/2 BPSK	10, 15, 20, 30, 40	Low, Mid, High	1	1

#### 4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacture	Serial No.	Due to Calibration	Calibration Interval
Precision Dipole Antenna	UHAP	Schwarzbeck	01273	03/27/2024	Biennial
Precision Dipole Antenna	UHAP	Schwarzbeck	01274	03/27/2024	Biennial
Horn Antenna(1~18 GHz)	BBHA 9120D	Schwarzbeck	02289	03/21/2024	Biennial
Horn Antenna(1~18 GHz)	BBHA 9120D	Schwarzbeck	9120D-1299	04/27/2025	Biennial
Horn Antenna(15~40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170342	09/29/2024	Biennial
Horn Antenna(15~40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170124	03/28/2025	Biennial
Loop Antenna(9 kHz~30 MHz)	FMZB1513	Rohde & Schwarz	1513-175	01/16/2025	Biennial
Bilog Antenna	VULB9160	Schwarzbeck	3150	03/09/2025	Biennial
Hybrid Antenna	VULB9160	Schwarzbeck	760	02/24/2025	Biennial
RF Switching System	FBSR-06B (1G HPF + LNA)	T&M SYSTEM	F3L1	05/22/2024	Annual
RF Switching System	FBSR-06B (3G HPF + LNA)	T&M SYSTEM	F3L2	05/22/2024	Annual
RF Switching System	FBSR-06B (6G HPF + LNA)	T&M SYSTEM	F3L3	05/22/2024	Annual
RF Switching System	FBSR-06B (LNA)	T&M SYSTEM	F3L4	05/22/2024	Annual
Power Amplifier	CBL18265035	CERNEX	22966	12/01/2023	Annual
Power Amplifier	CBL26405040	CERNEX	25956	03/02/2024	Annual
DC Power Supply	E3632A	Hewlett Packard	MY40004427	08/25/2024	Annual
Power Splitter(DC~26.5 GHz)	11667B	Hewlett Packard	11275	03/02/2024	Annual
Chamber	SU-642	ESPEC	93008124	02/22/2024	Annual
Signal Analyzer(10 Hz~26.5 GHz)	N9020A	Agilent	MY51110063	04/11/2024	Annual
ATTENUATOR(20 dB)	8493C	Hewlett Packard	17280	04/19/2024	Annual
Spectrum Analyzer(10 Hz~40 GHz)	FSV40	REOHDE & SCHWARZ	101436	02/22/2024	Annual
Base Station	8960 (E5515C)	Agilent	MY48360800	08/10/2024	Annual
Wideband Radio Communication Tester	MT8821C	Anritsu Corp.	6262287701	05/22/2024	Annual
Wideband Radio Communication Tester	MT8000A	Anritsu Corp.	6262302511	05/23/2024	Annual
SIGNAL GENERATOR (100 kHz~40 GHz)	SMB100A	REOHDE & SCHWARZ	177633	06/22/2024	Annual
Signal Analyzer(5 Hz~40.0 GHz)	N9030B	KEYSIGHT	MY55480167	05/24/2024	Annual
4-Way Divider	ZC4PD-K1844+	Mini-Circuits	942907	09/19/2024	Annual
Companion device (FCC ID: PIDAS2900)	AirSpeed 2900	Airspan Networks inc	F36866015EBC	-	-
FCC LTE Mobile Conducted RF Automation Test Software	-	HCT CO., LTD.,	-	-	-

Note:

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
2. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

## 5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ( $\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.90 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (9 kHz ~ 30 MHz)	4.14 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (30 MHz ~ 1 GHz)	5.16 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (1 GHz ~ 18 GHz)	5.57 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (18 GHz ~ 40 GHz)	5.76 (Confidence level about 95 %, $k=2$ )
Radiated Disturbance (Above 40 GHz)	5.52 (Confidence level about 95 %, $k=2$ )

## 6. SUMMARY OF TEST RESULTS

### 6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §96.41(e)	<ul style="list-style-type: none"> <li>■ -13 dBm/Mhz at frequencies within 0-10 MHz of channel edge</li> <li>■ -25 dBm/MHz at frequencies greater than 10 MHz above and below channel edge</li> <li>■ -40 dBm/MHz at frequencies below 3530 MHz and above 3720 MHz</li> </ul>	PASS
Adjacent Channel Leakage Ratio	§96.41(e)	At least 30 dB.	PASS
Conducted Output Power	§2.1046	N/A	<u>See Note1</u>
Peak- to- Average Ratio	§96.41(g)	< 13 dB	PASS
Frequency stability / variation of ambient temperature	§2.1055,	Emission must remain in band	PASS

**Note:**

1. See SAR Report
2. Conducted tests were tested using 5G Wireless Tester.

### 6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§96.41(b)	23 dBm/10 MHz	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §96.41(e)	-40 dBm/MHz	PASS
End User Device Additional Requirements (CBSD Protocol)	§96.47	End User Devices may operate only if they can positively receive and decode an authorization signal transmitted by a CBSD, including the frequencies and power limits for their operation. An End User Device must discontinue operations, change frequencies, or change its operational power level within 10 seconds of receiving instructions from its associated CBSD.	PASS

**Note:**

1. Radiated tests were tested using 5G Wireless Tester.

## 7. SAMPLE CALCULATION

### 7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$ERP = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

### 7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
55990	2595.0	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$EIRP = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4 M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4 M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4 M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand



## 8. TEST DATA

### 8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	Limit	RB	
								dBm/10 MHz		Size	Size
3555.00	Sub6 n48/ 10 MHz [30 kHz]	PI/2 BPSK	-28.57	9.67	11.40	3.02	H	18.05	23.0	1	22
		QPSK	-28.76	9.48	11.40	3.02	H	17.86			
		16-QAM	-29.90	8.34	11.40	3.02	H	16.72			
		64-QAM	-31.23	7.01	11.40	3.02	H	15.39			
		256-QAM	-33.56	4.68	11.40	3.02	H	13.06			
3624.99		PI/2 BPSK	-26.41	12.25	11.50	3.03	H	20.72		1	1
		QPSK	-26.56	12.10	11.50	3.03	H	20.57			
		16-QAM	-27.81	10.85	11.50	3.03	H	19.32			
		64-QAM	-29.13	9.53	11.50	3.03	H	18.00			
		256-QAM	-31.29	7.37	11.50	3.03	H	15.84			
3694.98	PI/2 BPSK	-25.90	12.58	11.45	3.06	H	20.97	1	22		
	QPSK	-26.11	12.37	11.45	3.06	H	20.76				
	16-QAM	-27.18	11.30	11.45	3.06	H	19.69				
	64-QAM	-28.51	9.97	11.45	3.06	H	18.36				
	256-QAM	-30.90	7.58	11.45	3.06	H	15.97				

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	Limit	RB	
								dBm/10 MHz		Size	Size
3557.52	Sub6 n48/ 15 MHz [30 kHz]	PI/2 BPSK	-28.39	9.85	11.40	3.02	H	18.23	23.0	1	36
		QPSK	-28.51	9.73	11.40	3.02	H	18.11			
		16-QAM	-29.61	8.63	11.40	3.02	H	17.01			
		64-QAM	-31.06	7.18	11.40	3.02	H	15.56			
		256-QAM	-33.33	4.91	11.40	3.02	H	13.29			
3624.99		PI/2 BPSK	-26.40	12.26	11.50	3.03	H	20.73		1	36
		QPSK	-26.51	12.15	11.50	3.03	H	20.62			
		16-QAM	-27.61	11.05	11.50	3.03	H	19.52			
		64-QAM	-28.91	9.75	11.50	3.03	H	18.22			
		256-QAM	-31.14	7.52	11.50	3.03	H	15.99			
3692.49	PI/2 BPSK	-26.01	12.47	11.45	3.06	H	20.86	1	36		
	QPSK	-26.11	12.37	11.45	3.06	H	20.76				
	16-QAM	-27.30	11.18	11.45	3.06	H	19.57				
	64-QAM	-28.56	9.92	11.45	3.06	H	18.31				
	256-QAM	-30.81	7.67	11.45	3.06	H	16.06				

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	Limit	RB	
								dBm/10 MHz		Size	Size
3560.01	Sub6 n48/ 20 MHz [30 kHz]	PI/2 BPSK	-28.46	9.82	11.40	3.01	H	18.21	23.0	1	49
		QPSK	-28.71	9.57	11.40	3.01	H	17.96			
		16-QAM	-29.71	8.57	11.40	3.01	H	16.96			
		64-QAM	-31.01	7.27	11.40	3.01	H	15.66			
		256-QAM	-33.28	5.00	11.40	3.01	H	13.39			
3624.99		PI/2 BPSK	-26.48	12.18	11.50	3.03	H	20.65		1	49
		QPSK	-26.59	12.07	11.50	3.03	H	20.54			
		16-QAM	-27.63	11.03	11.50	3.03	H	19.50			
		64-QAM	-29.01	9.65	11.50	3.03	H	18.12			
		256-QAM	-31.19	7.47	11.50	3.03	H	15.94			
3690.00	PI/2 BPSK	-26.01	12.49	11.50	3.06	H	20.93	1	49		
	QPSK	-26.10	12.40	11.50	3.06	H	20.84				
	16-QAM	-27.19	11.31	11.50	3.06	H	19.75				
	64-QAM	-28.61	9.89	11.50	3.06	H	18.33				
	256-QAM	-30.86	7.64	11.50	3.06	H	16.08				

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	Limit	RB	
								dBm/10 MHz		Size	Size
3565.02	Sub6 n48/ 30 MHz [30 kHz]	PI/2 BPSK	-28.14	10.09	11.40	3.00	H	18.49	23.0	1	76
		QPSK	-28.26	9.97	11.40	3.00	H	18.37			
		16-QAM	-29.41	8.82	11.40	3.00	H	17.22			
		64-QAM	-30.81	7.42	11.40	3.00	H	15.82			
		256-QAM	-32.95	5.28	11.40	3.00	H	13.68			
3624.99		PI/2 BPSK	-26.25	12.41	11.50	3.03	H	20.88		1	76
		QPSK	-26.34	12.32	11.50	3.03	H	20.79			
		16-QAM	-27.46	11.20	11.50	3.03	H	19.67			
		64-QAM	-28.91	9.75	11.50	3.03	H	18.22			
		256-QAM	-31.21	7.45	11.50	3.03	H	15.92			
3684.99	PI/2 BPSK	-25.79	12.78	11.50	3.06	H	21.22	1	76		
	QPSK	-25.85	12.72	11.50	3.06	H	21.16				
	16-QAM	-27.06	11.51	11.50	3.06	H	19.95				
	64-QAM	-28.51	10.06	11.50	3.06	H	18.50				
	256-QAM	-30.61	7.96	11.50	3.06	H	16.40				

Freq (MHz)	Mod/ Bandwidth [SCS (kHz)]	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	EIRP	Limit	RB	
								dBm/10 MHz		Size	Size
3570.00	Sub6 n48/ 40 MHz [30 kHz]	PI/2 BPSK	-28.13	10.05	11.40	2.99	H	18.46	23.0	1	104
		QPSK	-28.21	9.97	11.40	2.99	H	18.38			
		16-QAM	-29.41	8.77	11.40	2.99	H	17.18			
		64-QAM	-30.81	7.37	11.40	2.99	H	15.78			
		256-QAM	-33.01	5.17	11.40	2.99	H	13.58			
3624.99		PI/2 BPSK	-26.41	12.25	11.50	3.03	H	20.72		1	104
		QPSK	-26.46	12.20	11.50	3.03	H	20.67			
		16-QAM	-27.61	11.05	11.50	3.03	H	19.52			
		64-QAM	-29.11	9.55	11.50	3.03	H	18.02			
		256-QAM	-31.21	7.45	11.50	3.03	H	15.92			
3679.98	PI/2 BPSK	-25.91	12.72	11.50	3.05	H	21.17	1	104		
	QPSK	-26.01	12.62	11.50	3.05	H	21.07				
	16-QAM	-27.21	11.42	11.50	3.05	H	19.87				
	64-QAM	-28.46	10.17	11.50	3.05	H	18.62				
	256-QAM	-30.81	7.82	11.50	3.05	H	16.27				

### 8.2 RADIATED SPURIOUS EMISSIONS

- NR Band: N48
- Bandwidth: 10 MHz
- Modulation: PI/2 BPSK
- Distance: 1 meters
- SCS: 30 kHz

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
637000 (3555.00)	7 110.00	-65.16	10.50	-58.09	4.35	V	-51.94	-40.00	1	22
	10 665.00	-65.60	11.00	-54.00	5.48	V	-48.48	-40.00		
	14 220.00	-61.83	12.40	-52.60	6.44	V	-46.64	-40.00		
641666 (3624.99)	7 249.98	-64.24	10.10	-56.32	4.42	H	-50.64	-40.00	1	1
	10 874.97	-64.23	11.20	-52.97	5.53	H	-47.30	-40.00		
	14 499.96	-58.44	12.90	-51.63	6.49	H	-45.22	-40.00		
646332 (3694.98)	7 389.96	-63.97	10.60	-56.39	4.46	V	-50.25	-40.00	1	22
	11 084.94	-64.98	11.30	-53.84	5.59	V	-48.13	-40.00		
	14 779.92	-58.50	13.10	-52.40	6.56	V	-45.86	-40.00		

- NR Band: N48
- Bandwidth: 15 MHz
- Modulation: PI/2 BPSK
- Distance: 1 meters
- SCS: 30 kHz

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
637168 (3557.52)	7 115.04	-63.61	10.50	-56.55	4.37	V	-50.42	-40.00	1	36
	10 672.56	-64.62	11.10	-53.45	5.47	V	-47.82	-40.00		
	14 230.08	-60.54	12.40	-51.74	6.44	V	-45.78	-40.00		
641666 (3624.99)	7 249.98	-64.48	10.10	-56.56	4.42	V	-50.88	-40.00	1	36
	10 874.97	-65.64	11.20	-54.38	5.53	V	-48.71	-40.00		
	14 499.96	-58.93	12.90	-52.12	6.49	V	-45.71	-40.00		
646166 (3692.49)	7 384.98	-64.98	10.60	-57.32	4.45	V	-51.17	-40.00	1	36
	11 077.47	-65.28	11.30	-53.96	5.60	V	-48.26	-40.00		
	14 769.96	-62.29	13.10	-56.19	6.58	V	-49.67	-40.00		

- NR Band: N48
- Bandwidth: 20 MHz
- Modulation: PI/2 BPSK
- Distance: 1 meters
- SCS: 30 kHz

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
637334 (3560.01)	7 120.02	-65.23	10.50	-58.12	4.39	V	-52.01	-40.00	1	49
	10 680.03	-62.45	11.10	-50.98	5.46	V	-45.34	-40.00		
	14 240.04	-61.57	12.40	-52.71	6.44	V	-46.75	-40.00		
641666 (3624.99)	7 249.98	-64.39	10.10	-56.47	4.42	V	-50.79	-40.00	1	49
	10 874.97	-63.99	11.20	-52.73	5.53	V	-47.06	-40.00		
	14 499.96	-57.99	12.90	-51.18	6.49	V	-44.77	-40.00		
646000 (3690.00)	7 380.00	-63.46	10.60	-55.70	4.45	V	-49.55	-40.00	1	49
	11 070.00	-65.10	11.30	-53.38	5.61	V	-47.69	-40.00		
	14 760.00	-60.21	13.10	-54.24	6.58	V	-47.72	-40.00		



- NR Band: N48
- Bandwidth: 30 MHz
- Modulation: PI/2 BPSK
- Distance: 1 meters
- SCS: 30 kHz

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
637668 (3565.02)	7 130.04	-64.91	10.50	-57.41	4.40	V	-51.31	-40.00	1	76
	10 695.06	-63.79	11.10	-52.63	5.48	V	-47.01	-40.00		
	14 260.08	-58.30	12.50	-49.86	6.44	V	-43.80	-40.00		
641666 (3624.99)	7 249.98	-65.03	10.10	-57.11	4.42	V	-51.43	-40.00	1	76
	10 874.97	-65.06	11.20	-53.80	5.53	V	-48.13	-40.00		
	14 499.96	-58.70	12.90	-51.89	6.49	V	-45.48	-40.00		
645666 (3684.99)	7 369.98	-63.70	10.60	-55.82	4.44	V	-49.66	-40.00	1	76
	11 054.97	-65.64	11.30	-53.66	5.61	V	-47.97	-40.00		
	14 739.96	-57.82	13.00	-51.16	6.59	V	-44.75	-40.00		

- NR Band: N48
- Bandwidth: 40 MHz
- Modulation: PI/2 BPSK
- Distance: 1 meters
- SCS: 30 kHz

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
638000 (3570.00)	7 140.00	-63.32	10.50	-55.46	4.41	V	-49.37	-40.00	1	104
	10 710.00	-65.29	11.10	-53.79	5.47	V	-48.16	-40.00		
	14 280.00	-58.39	12.50	-50.11	6.43	V	-44.04	-40.00		
641666 (3624.99)	7 249.98	-64.46	10.10	-56.54	4.42	V	-50.86	-40.00	1	104
	10 874.97	-64.92	11.20	-53.66	5.53	V	-47.99	-40.00		
	14 499.96	-57.79	12.90	-50.98	6.49	V	-44.57	-40.00		
645332 (3679.98)	7 359.96	-65.07	10.60	-57.31	4.44	V	-51.15	-40.00	1	104
	11 039.94	-65.54	11.30	-53.50	5.59	V	-47.79	-40.00		
	14 719.92	-60.90	13.00	-53.78	6.59	V	-47.37	-40.00		

**8.3 PEAK-TO-AVERAGE RATIO**

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB )
Sub6 n48	10 MHz	3624.99	BPSK	24	0	3.96
			QPSK			5.79
			16-QAM			6.57
			64-QAM			6.51
			256-QAM			6.57
	15 MHz		BPSK	36		4.13
			QPSK			5.51
			16-QAM			6.37
			64-QAM			6.64
			256-QAM			6.74
	20 MHz		BPSK	50		4.00
			QPSK			5.74
			16-QAM			6.27
			64-QAM			6.61
			256-QAM			6.69
	30 MHz		BPSK	75		4.13
			QPSK			5.38
			16-QAM			6.36
			64-QAM			6.60
			256-QAM			6.60
40 MHz	BPSK	100	4.03			
	QPSK		5.62			
	16-QAM		6.28			
	64-QAM		6.54			
	256-QAM		6.69			

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 77 ~ 101.

**8.4 OCCUPIED BANDWIDTH**

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data ( MHz )
Sub6 n48	10 MHz	3624.99	BPSK	24	0	8.6812
			QPSK			8.7103
			16-QAM			8.6732
			64-QAM			8.6718
			256-QAM			8.6463
	15 MHz		BPSK	36		12.986
			QPSK			12.964
			16-QAM			12.994
			64-QAM			12.919
			256-QAM			12.944
	20 MHz		BPSK	50		17.921
			QPSK			17.963
			16-QAM			17.953
			64-QAM			17.924
			256-QAM			17.942
	30 MHz		BPSK	75		26.963
			QPSK			26.959
			16-QAM			26.872
			64-QAM			26.946
			256-QAM			26.906
40 MHz	BPSK	100	35.866			
	QPSK		35.868			
	16-QAM		35.857			
	64-QAM		35.932			
	256-QAM		35.835			

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 52 ~ 76.

**8.5 CONDUCTED SPURIOUS EMISSIONS**

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
Sub6 n48	10	3555.00	8.0015	30.815	-77.162	-46.347	-40.00
		3624.99	3.7483	30.200	-76.502	-46.302	
		3694.98	8.8674	30.815	-77.310	-46.495	
	15	3557.52	7.9975	30.815	-76.734	-45.919	
		3624.99	9.7278	30.815	-76.689	-45.874	
		3692.49	4.9083	30.200	-76.995	-46.795	
	20	3560.01	6.0414	30.815	-76.905	-46.090	
		3624.99	8.5858	30.815	-76.031	-45.216	
		3690.00	6.0225	30.815	-77.345	-46.530	
	30	3565.02	5.2144	30.815	-76.268	-45.453	
		3624.99	9.7463	30.815	-76.851	-46.036	
		3684.99	9.7174	30.815	-76.665	-45.850	
	40	3570.00	4.0020	30.200	-77.131	-46.931	
		3624.99	3.7528	30.200	-76.245	-46.045	
		3679.98	8.2862	30.815	-76.265	-45.450	

**Note:**

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 172 ~ 201.
2. Factor(dB) = Cable Loss + Ext. Attenuator + Power Splitter  
 - Result(dBm) = Reading + Factor
3. Factor(dB)

Frequency Range (GHz)	Factor [dB]
0.03 – 1	27.494
1 – 5	30.200
5 – 10	30.815
10 – 15	31.340
15 – 20	31.713
Above 20	32.355

**8.6 CHANNEL EDGE**

BW (MHz)	RB (Size/Offset)	Freq. (MHz)	Outside of the authorized band (dBm)							
			Lower Side(MHz)				Upper Side(MHz)			
			Below 3530 MHz	-[B]MHz ~ 3530 MHz	-1 MHz ~ -[B]MHz	0 MHz ~ -1 MHz	0 MHz ~ +1 MHz	1 MHz ~ +[B]MHz	+ [B]MHz ~ 3720 MHz	Above 3720 MHz
10	24/0	3555.00	-53.46	-46.23	-29.72	-30.36	-28.96	-30.22	-45.82	—
		3624.99	—	-46.26	-29.82	-29.33	-32.05	-33.08	-49.60	—
		3694.98	—	-45.15	-29.06	-29.44	-30.92	-32.51	-46.51	-49.44
15	36/0	3557.52	-51.13	-41.45	-31.32	-28.42	-37.14	-32.66	-47.31	—
		3624.99	—	-49.68	-32.74	-30.15	-39.98	-38.46	-51.32	—
		3692.49	—	-50.31	-32.88	-29.14	-40.85	-37.68	-44.39	-49.36
20	50/0	3560.01	-47.78	-36.79	-31.33	-30.90	-34.65	-30.42	-47.49	—
		3624.99	—	-51.98	-33.12	-30.85	-37.36	-37.95	-51.05	—
		3690.00	—	-50.90	-34.37	-32.11	-37.74	-33.85	-40.39	-49.45
30	75/0	3565.02	-43.46	-37.82	-33.68	-32.47	-40.14	-36.49	-50.67	—
		3624.99	—	-52.89	-36.37	-34.04	-42.56	-39.07	-49.58	—
		3684.99	—	-51.03	-37.17	-34.48	-40.90	-37.85	-40.04	-46.19
40	100/0	3570.00	-41.00	-39.36	-31.44	-29.62	-34.96	-33.14	-50.69	—
		3624.99	—	-52.92	-35.47	-32.04	-38.12	-34.78	-49.51	—
		3679.98	—	-49.99	-36.99	-33.67	-42.12	-37.51	-40.55	-44.61
Limit (dBm)			-40.00	-25.00	-13.00	-13.00	-13.00	-13.00	-25.00	-40.00

Note:

1. C.E = Channel Edge
2. Plots of the EUT's Channel Edge are shown Page 117 ~ 171.
3. Duty Cycle factor already applied on the factor.
  - Duty Cycle Factor(dB) = 6.99
  - Factor(dB) = Duty Cycle factor + Cable Loss + Ext. Attenuator
  - Result(dBm) = Reading + Factor

BW (MHz)	RB (Size/ Offset)	Freq. (MHz)	Outside of the authorized band (dBm)							
			Lower Side(MHz)				Upper Side(MHz)			
			Below 3530 MHz	-[B]MHz ~ 3530 MHz	-1 MHz ~ -[B]MHz -1 MHz	0 MHz ~ -1 MHz	0 MHz ~ +1 MHz	1 MHz ~ +[B]MHz 3720 MHz	+ [B]MHz ~ 3720 MHz	Above 3720 MHz
10	Lower Side: 1/0 Upper Side: 1/23	3555.00	-52.19	-43.82	-25.51	-27.07	-26.73	-26.64	-45.26	—
		3624.99	—	-46.92	-27.08	-26.20	-27.95	-27.38	-47.45	—
		3694.98	—	-45.60	-25.74	-25.94	-28.26	-25.63	-42.53	-49.31
15	Lower Side: 1/0 Upper Side: 1/37	3557.52	-51.52	-43.87	-23.26	-22.58	-24.53	-25.16	-49.10	—
		3624.99	—	-48.83	-24.96	-23.34	-28.65	-26.71	-50.47	—
		3692.49	—	-49.70	-25.77	-25.09	-24.54	-23.60	-49.60	-49.46
20	Lower Side: 1/0 Upper Side: 1/50	3560.01	-50.93	-43.30	-25.83	-27.38	-27.76	-27.04	-49.71	—
		3624.99	—	-52.75	-30.37	-29.79	-29.82	-27.96	-51.09	—
		3690.00	—	-50.51	-26.85	-29.27	-28.89	-27.86	-43.29	-48.87
30	Lower Side: 1/0 Upper Side: 1/77	3565.02	-52.46	-46.09	-29.94	-32.23	-32.55	-29.49	-51.02	—
		3624.99	—	-53.05	-29.84	-31.62	-32.47	-30.31	-49.76	—
		3684.99	—	-51.05	-28.50	-31.14	-32.38	-27.50	-42.59	-48.91
40	Lower Side: 1/0 Upper Side: 1/105	3570.00	-50.91	-43.95	-28.37	-31.30	-32.68	-29.21	-51.38	—
		3624.99	—	-53.34	-28.73	-30.47	-31.35	-28.75	-49.55	—
		3679.98	—	-50.12	-28.77	-31.35	-30.54	-25.99	-42.18	-48.78
Limit (dBm)			-40.00	-25.00	-13.00	-13.00	-13.00	-13.00	-25.00	-40.00

**Note:**

1. C.E = Channel Edge
2. Plots of the EUT's Channel Edge are shown Page 117 ~ 171.
3. Duty Cycle factor already applied on the factor.
  - Duty Cycle Factor(dB) = 6.99
  - Factor(dB) = Duty Cycle factor + Cable Loss + Ext. Attenuator
  - Result(dBm) = Reading + Factor

**8.7 Adjacent Channel Leakage Ratio(ACLR)**

Band Width	RB (Size/ Offset)	Frequency (MHz)	Adjacent Channel Leakage Ratio(dB)	
			Lower Side	Upper Side
10 MHz	24/0	3555.00	44.61	44.07
		3624.99	44.87	47.11
		3694.98	44.56	46.66
15 MHz	36/0	3557.52	44.26	46.69
		3624.99	46.20	51.50
		3692.49	46.00	51.76
20 MHz	50/0	3560.01	44.65	45.25
		3624.99	46.49	50.87
		3690.00	47.84	50.00
30 MHz	75/0	3565.02	45.08	47.45
		3624.99	45.91	51.16
		3684.99	46.53	50.46
40 MHz	100/0	3570.00	38.28	45.55
		3624.99	38.67	48.96
		3679.98	38.78	50.42
Limit (dB)			ACLR > 30dB	ACLR > 30dB

Note:

1. Duty Cycle factor already applied on the factor.


- Factor(dB) = Duty Cycle factor + Cable Loss + Ext. Attenuator + Power Splitter
- Result(dBm) = Reading + Factor
- Duty Cycle Factor(dB) = 6.990

2. Plots of the EUT's Adjacent Channel Leakage Ratio(ACLR) are shown Page 102 ~ 116.



**8.8 End User Device Additional Requirement (CBSD Protocol)**

**Test#1: 3570 MHz(BW: 20 MHz)**



**Stop Operation Within 10 s**




**Note:**

Marker 2: CBSD sends instructions to discontinue NR n48 operations.


Marker 1Δ2: EUT discontinues operation. (0.30 s)

Marker 3Δ4: 10 seconds elapsed time from CBSD sending instructions to EUT.(10.0 s)

**Test#2: 3660 MHz(BW: 40 MHz)**



**Stop Operation Within 10 s**



**Note:**

Marker 2: CBSD sends instructions to discontinue NR n48 operations.

Marker 1Δ2: EUT discontinues operation. (0.3600 s)

Marker 3Δ4: 10 seconds elapsed time from CBSD sending instructions to EUT(10.0 s).

**8.9 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE**

- ▣ BandWidth: 10 MHz
- ▣ Voltage(100 %): 3.880 VDC
- ▣ Batt. Endpoint: 3.300 VDC
- ▣ LIMIT: Emission must remain in band

Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
3555.000	100 %	+20(Ref)	3554 999 997	0.0	0.000 000	0.000
	100 %	-30	3554 999 990	-7.4	0.000 000	-0.002
	100 %	-20	3554 999 997	-0.2	0.000 000	0.000
	100 %	-10	3554 999 996	-0.8	0.000 000	0.000
	100 %	0	3554 999 998	0.8	0.000 000	0.000
	100 %	+10	3554 999 995	-2.2	0.000 000	-0.001
	100 %	+30	3554 999 995	-1.5	0.000 000	0.000
	100 %	+40	3554 999 998	1.2	0.000 000	0.000
	100 %	+50	3554 999 992	-5.0	0.000 000	-0.001
	Batt. Endpoint	+20	3554 999 995	-1.7	0.000 000	0.000
3694.980	100 %	+20(Ref)	3694 979 993	0.0	0.000 000	0.000
	100 %	-30	3694 979 988	-4.5	0.000 000	-0.001
	100 %	-20	3694 979 984	-9.1	0.000 000	-0.002
	100 %	-10	3694 979 988	-4.6	0.000 000	-0.001
	100 %	0	3694 979 991	-1.2	0.000 000	0.000
	100 %	+10	3694 979 994	0.9	0.000 000	0.000
	100 %	+30	3694 979 987	-5.4	0.000 000	-0.001
	100 %	+40	3694 979 988	-4.9	0.000 000	-0.001
	100 %	+50	3694 979 989	-3.3	0.000 000	-0.001
	Batt. Endpoint	+20	3694 979 990	-2.4	0.000 000	-0.001

- ▣ BandWidth: 15 MHz
- ▣ Voltage(100 %): 3.880 VDC
- ▣ Batt. Endpoint: 3.300 VDC
- ▣ LIMIT: Emission must remain in band

Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
3557.520	100 %	+20(Ref)	3557 520 004	0.0	0.000 000	0.000
	100 %	-30	3557 520 000	-3.3	0.000 000	-0.001
	100 %	-20	3557 520 003	-0.7	0.000 000	0.000
	100 %	-10	3557 520 000	-4.0	0.000 000	-0.001
	100 %	0	3557 520 009	4.9	0.000 000	0.001
	100 %	+10	3557 520 005	1.0	0.000 000	0.000
	100 %	+30	3557 520 006	2.2	0.000 000	0.001
	100 %	+40	3557 520 007	3.3	0.000 000	0.001
	100 %	+50	3557 520 006	2.8	0.000 000	0.001
	Batt. Endpoint	+20	3557 519 998	-5.7	0.000 000	-0.002
3692.490	100 %	+20(Ref)	3692 489 999	0.0	0.000 000	0.000
	100 %	-30	3692 489 995	-3.5	0.000 000	-0.001
	100 %	-20	3692 489 997	-1.9	0.000 000	-0.001
	100 %	-10	3692 489 992	-6.7	0.000 000	-0.002
	100 %	0	3692 489 999	0.3	0.000 000	0.000
	100 %	+10	3692 489 999	0.5	0.000 000	0.000
	100 %	+30	3692 489 993	-5.8	0.000 000	-0.002
	100 %	+40	3692 490 000	1.1	0.000 000	0.000
	100 %	+50	3692 490 002	3.3	0.000 000	0.001
	Batt. Endpoint	+20	3692 489 998	-0.9	0.000 000	0.000

- ▣ BandWidth: 20 MHz
- ▣ Voltage(100 %): 3.880 VDC
- ▣ Batt. Endpoint: 3.300 VDC
- ▣ LIMIT: Emission must remain in band

Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
3560.010	100 %	+20(Ref)	3560 009 996	0.0	0.000 000	0.000
	100 %	-30	3560 009 996	0.7	0.000 000	0.000
	100 %	-20	3560 009 995	-1.0	0.000 000	0.000
	100 %	-10	3560 009 996	0.1	0.000 000	0.000
	100 %	0	3560 009 994	-1.8	0.000 000	0.000
	100 %	+10	3560 009 998	2.4	0.000 000	0.001
	100 %	+30	3560 009 997	1.5	0.000 000	0.000
	100 %	+40	3560 009 994	-1.2	0.000 000	0.000
	100 %	+50	3560 009 995	-0.6	0.000 000	0.000
	Batt. Endpoint	+20	3560 009 991	-4.6	0.000 000	-0.001
3690.000	100 %	+20(Ref)	3689 999 998	0.0	0.000 000	0.000
	100 %	-30	3689 999 994	-4.3	0.000 000	-0.001
	100 %	-20	3689 999 997	-0.9	0.000 000	0.000
	100 %	-10	3689 999 994	-3.6	0.000 000	-0.001
	100 %	0	3689 999 992	-5.4	0.000 000	-0.001
	100 %	+10	3689 999 997	-0.5	0.000 000	0.000
	100 %	+30	3689 999 993	-4.5	0.000 000	-0.001
	100 %	+40	3689 999 997	-1.0	0.000 000	0.000
	100 %	+50	3689 999 996	-1.7	0.000 000	0.000
	Batt. Endpoint	+20	3689 999 994	-3.5	0.000 000	-0.001

- ▣ BandWidth: 30 MHz
- ▣ Voltage(100 %): 3.880 VDC
- ▣ Batt. Endpoint: 3.300 VDC
- ▣ LIMIT: Emission must remain in band

Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
3565.020	100 %	+20(Ref)	3565 019 994	0.0	0.000 000	0.000
	100 %	-30	3565 019 995	1.0	0.000 000	0.000
	100 %	-20	3565 019 993	-0.4	0.000 000	0.000
	100 %	-10	3565 019 993	-0.5	0.000 000	0.000
	100 %	0	3565 019 991	-3.4	0.000 000	-0.001
	100 %	+10	3565 019 990	-3.7	0.000 000	-0.001
	100 %	+30	3565 019 988	-5.9	0.000 000	-0.002
	100 %	+40	3565 019 990	-3.9	0.000 000	-0.001
	100 %	+50	3565 019 992	-1.7	0.000 000	0.000
	Batt. Endpoint	+20	3565 019 995	0.6	0.000 000	0.000
3684.990	100 %	+20(Ref)	3684 989 995	0.0	0.000 000	0.000
	100 %	-30	3684 989 993	-2.0	0.000 000	-0.001
	100 %	-20	3684 989 990	-5.3	0.000 000	-0.001
	100 %	-10	3684 989 993	-2.3	0.000 000	-0.001
	100 %	0	3684 989 991	-4.0	0.000 000	-0.001
	100 %	+10	3684 989 998	2.4	0.000 000	0.001
	100 %	+30	3684 989 993	-2.0	0.000 000	-0.001
	100 %	+40	3684 989 995	-0.2	0.000 000	0.000
	100 %	+50	3684 989 984	-11.5	0.000 000	-0.003
	Batt. Endpoint	+20	3684 989 987	-8.0	0.000 000	-0.002




- ▣ BandWidth: 40 MHz
- ▣ Voltage(100 %): 3.880 VDC
- ▣ Batt. Endpoint: 3.300 VDC
- ▣ LIMIT: Emission must remain in band


Test. Frequency (MHz)	Voltage (%)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
3570.000	100 %	+20(Ref)	3569 999 996	0.0	0.000 000	0.000
	100 %	-30	3569 999 995	-1.2	0.000 000	0.000
	100 %	-20	3569 999 993	-2.9	0.000 000	-0.001
	100 %	-10	3569 999 997	1.1	0.000 000	0.000
	100 %	0	3569 999 994	-2.3	0.000 000	-0.001
	100 %	+10	3569 999 996	-0.6	0.000 000	0.000
	100 %	+30	3569 999 993	-3.1	0.000 000	-0.001
	100 %	+40	3569 999 997	0.3	0.000 000	0.000
	100 %	+50	3569 999 994	-2.5	0.000 000	-0.001
	Batt. Endpoint	+20	3569 999 993	-3.1	0.000 000	-0.001
3679.980	100 %	+20(Ref)	3679 979 995	0.0	0.000 000	0.000
	100 %	-30	3679 979 990	-4.9	0.000 000	-0.001
	100 %	-20	3679 979 993	-2.0	0.000 000	-0.001
	100 %	-10	3679 979 993	-2.1	0.000 000	-0.001
	100 %	0	3679 979 991	-4.0	0.000 000	-0.001
	100 %	+10	3679 979 992	-3.2	0.000 000	-0.001
	100 %	+30	3679 979 991	-4.2	0.000 000	-0.001
	100 %	+40	3679 979 998	2.7	0.000 000	0.001
	100 %	+50	3679 979 991	-4.1	0.000 000	-0.001
	Batt. Endpoint	+20	3679 979 993	-1.9	0.000 000	-0.001

## 9. TEST PLOTS


Sub6 n48. Occupied Bandwidth Plot (10 MHz Ch. 641666 BPSK RB 24)



Sub6 n48. Occupied Bandwidth Plot (10 MHz Ch. 641666 QPSK RB 24)




Sub6 n48. Occupied Bandwidth Plot (10 MHz Ch.641666 16-QAM RB 24)




Sub6 n48. Occupied Bandwidth Plot (10 MHz Ch.641666 64-QAM RB 24)



Sub6 n48. Occupied Bandwidth Plot (10 MHz Ch.641666 256-QAM RB 24)



Sub6 n48. Occupied Bandwidth Plot (15 MHz Ch. 641666 BPSK RB 36)







Sub6 n48. Occupied Bandwidth Plot (15 MHz Ch. 641666 QPSK RB 36)



Sub6 n48. Occupied Bandwidth Plot (15 MHz Ch.641666 16-QAM RB 36)




Sub6 n48. Occupied Bandwidth Plot (15 MHz Ch.641666 64-QAM RB 36)



Sub6 n48. Occupied Bandwidth Plot (15 MHz Ch.641666 256-QAM RB 36)



Sub6 n48. Occupied Bandwidth Plot (20 MHz Ch. 641666 BPSK RB 50)




Sub6 n48. Occupied Bandwidth Plot (20 MHz Ch. 641666 QPSK RB 50)



Sub6 n48. Occupied Bandwidth Plot (20 MHz Ch.641666 16-QAM RB 50)



Sub6 n48. Occupied Bandwidth Plot (20 MHz Ch.641666 64-QAM RB 50)






Sub6 n48. Occupied Bandwidth Plot (20 MHz Ch.641666 256-QAM RB 50)




Sub6 n48. Occupied Bandwidth Plot (30 MHz Ch. 641666 BPSK RB 75)




Sub6 n48. Occupied Bandwidth Plot (30 MHz Ch. 641666 QPSK RB 75)



Sub6 n48. Occupied Bandwidth Plot (30 MHz Ch.641666 16-QAM RB 75)




Sub6 n48. Occupied Bandwidth Plot (30 MHz Ch.641666 64-QAM RB 75)




Sub6 n48. Occupied Bandwidth Plot (30 MHz Ch.641666 256-QAM RB 75)



Sub6 n48. Occupied Bandwidth Plot (40 MHz Ch. 641666 BPSK RB 100)




Sub6 n48. Occupied Bandwidth Plot (40 MHz Ch. 641666 QPSK RB 100)






Sub6 n48. Occupied Bandwidth Plot (40 MHz Ch.641666 16-QAM RB 100)



Sub6 n48. Occupied Bandwidth Plot (40 MHz Ch.641666 64-QAM RB 100)



Sub6 n48. Occupied Bandwidth Plot (40 MHz Ch.641666 256-QAM RB 100)



Sub6 n48. PAR Plot (10 MHz Ch. 641666 BPSK RB 24)




Sub6 n48. PAR Plot (10 MHz Ch. 641666 QPSK RB 24)



Sub6 n48. PAR Plot (10 MHz Ch.641666 16-QAM RB 24)



Sub6 n48. PAR Plot (10 MHz Ch.641666 64-QAM RB 24)




Sub6 n48. PAR Plot (10 MHz Ch.641666 256-QAM RB 24)





Sub6 n48. PAR Plot (15 MHz Ch. 641666 BPSK RB 36)



Sub6 n48. PAR Plot (15 MHz Ch. 641666 QPSK RB 36)



Sub6 n48. PAR Plot (15 MHz Ch.641666 16-QAM RB 36)




Sub6 n48. PAR Plot (15 MHz Ch.641666 64-QAM RB 36)




Sub6 n48. PAR Plot (15 MHz Ch.641666 256-QAM RB 36)



Sub6 n48. PAR Plot (20 MHz Ch. 641666 BPSK RB 50)



Sub6 n48. PAR Plot (20 MHz Ch. 641666 QPSK RB 50)



Sub6 n48. PAR Plot (20 MHz Ch.641666 16-QAM RB 50)






Sub6 n48. PAR Plot (20 MHz Ch.641666 64-QAM RB 50)




Sub6 n48. PAR Plot (20 MHz Ch.641666 256-QAM RB 50)




Sub6 n48. PAR Plot (30 MHz Ch. 641666 BPSK RB 75)



Sub6 n48. PAR Plot (30 MHz Ch. 641666 QPSK RB 75)



Sub6 n48. PAR Plot (30 MHz Ch.641666 16-QAM RB 75)




Sub6 n48. PAR Plot (30 MHz Ch.641666 64-QAM RB 75)



Sub6 n48. PAR Plot (30 MHz Ch.641666 256-QAM RB 75)



Sub6 n48. PAR Plot (40 MHz Ch. 641666 BPSK RB 100)






Sub6 n48. PAR Plot (40 MHz Ch. 641666 QPSK RB 100)



Sub6 n48. PAR Plot (40 MHz Ch.641666 16-QAM RB 100)




Sub6 n48. PAR Plot (40 MHz Ch.641666 64-QAM RB 100)




Sub6 n48. PAR Plot (40 MHz Ch.641666 256-QAM RB 100)




Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (10 MHz Ch.637000 BPSK RB 24, Offset 0)




Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (10 MHz Ch.641666 BPSK RB 24, Offset 0)



Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (10 MHz Ch.646332 BPSK RB 24, Offset 0)




Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (15 MHz Ch.637168 BPSK RB 36, Offset 0)







Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (15 MHz Ch.641666 BPSK RB 36, Offset 0)




Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (15 MHz Ch.646166 BPSK RB 36, Offset 0)




Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (20 MHz Ch.637334 BPSK RB 50, Offset 0)




Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (20 MHz Ch.641666 BPSK RB 50, Offset 0)




Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (20 MHz Ch.646000 BPSK RB 50, Offset 0)




Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (30 MHz Ch.638000 BPSK RB 75, Offset 0)



Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (30 MHz Ch.641666 BPSK RB 75, Offset 0)




Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (30 MHz Ch.645332 BPSK RB 75, Offset 0)







Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (40 MHz Ch.638000 BPSK RB 100, Offset 0)




Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (40 MHz Ch.641666 BPSK RB 100, Offset 0)




Sub6 n48. Adjacent Channel Leakage Ratio(ACLR) Plot (40 MHz Ch.645332 BPSK RB 100, Offset 0)




Sub6 n48. 10 M BandEdge(Lower)\_Low\_3555.00 MHz\_BPSK\_FullIRB




Sub6 n48. 10 M\_BandEdge(Upper)\_Low\_ 3555.00 MHz\_BPSK\_FullIRB




Sub6 n48. 10 M\_BandEdge(Lower)\_Low\_ 3555.00 MHz\_BPSK\_1RB



Sub6 n48. 10 M\_BandEdge(Upper)\_Low\_ 3555.00 MHz\_BPSK\_1RB




Sub6 n48. 10 M\_BandEdge(Center)\_Mid\_3624.99 MHz\_BPSK\_FullIRB







Sub6 n48. 10 M\_BandEdge(Lower)\_Mid\_3624.99 MHz\_BPSK\_1RB



Sub6 n48. 10 M\_BandEdge(Upper)\_Mid\_3624.99 MHz\_BPSK\_1RB




Sub6 n48. 10 M\_BandEdge(Lower)\_High\_ 3694.98 MHz\_BPSK\_FullRB




Sub6 n48. 10 M\_BandEdge(Upper)\_High\_ 3694.98 MHz\_BPSK\_FullIRB




Sub6 n48. 10 M\_BandEdge(Lower)\_High\_ 3694.98 MHz\_BPSK\_1RB




Sub6 n48. 10 M\_BandEdge(Upper)\_High\_ 3694.98 MHz\_BPSK\_1RB



Sub6 n48. 15 M BandEdge(Lower)\_Low\_ 3557.52 MHz\_BPSK\_FullRB




Sub6 n48. 15 M\_BandEdge(Upper)\_Low\_ 3557.52 MHz\_BPSK\_FullIRB







Sub6 n48. 15 M\_BandEdge(Lower)\_Low\_ 3557.52 MHz\_BPSK\_1RB




Sub6 n48. 15 M\_BandEdge(Upper)\_Low\_ 3557.52 MHz\_BPSK\_1RB




Sub6 n48. 15 M\_BandEdge(Center)\_Mid\_3624.99 MHz\_BPSK\_FullIRB



Sub6 n48. 15 M\_BandEdge(Lower)\_Mid\_3624.99 MHz\_BPSK\_1RB




Sub6 n48. 15 M\_BandEdge(Upper)\_Mid\_3624.99 MHz\_BPSK\_1RB




Sub6 n48. 15 M\_BandEdge(Lower)\_High\_ 3692.49 MHz\_BPSK\_FullIRB



Sub6 n48. 15 M\_BandEdge(Upper)\_High\_ 3692.49 MHz\_BPSK\_FullRB




Sub6 n48. 15 M\_BandEdge(Lower)\_High\_ 3692.49 MHz\_BPSK\_1RB






Sub6 n48. 15 M\_BandEdge(Upper)\_High\_ 3692.49 MHz\_BPSK\_1RB



Sub6 n48. 20 M BandEdge(Lower)\_Low\_ 3560.01 MHz\_BPSK\_FullIRB



Sub6 n48. 20 M\_BandEdge(Upper)\_Low\_ 3560.01 MHz\_BPSK\_FullIRB

