


Date: 1.NOV.2023 08:30:31


**Plot 7-201. Contention Based Protocol Timing Plot (20MHz (UNII Band 7) – Ch. 149)**



Date: 1.NOV.2023 08:57:27


**Plot 7-202. Contention Based Protocol Timing Plot (320MHz (UNII Band 7) – Ch. 159 Low)**

FCC ID: A3LSMS928U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 154 of 185



Date: 1.NOV.2023 08:58:22


**Plot 7-203. Contention Based Protocol Timing Plot (320MHz (UNII Band 7) – Ch. 159 Mid)**



Date: 1.NOV.2023 08:59:09


**Plot 7-204. Contention Based Protocol Timing Plot (320MHz (UNII Band 7) – Ch. 159 High)**

FCC ID: A3LSMS928U	<b>MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 155 of 185



Date: 1.NOV.2023 09:09:17


**Plot 7-205. Contention Based Protocol Timing Plot (20MHz (UNII Band 8) – Ch. 197)**




Date: 1.NOV.2023 09:04:50

**Plot 7-206. Contention Based Protocol Timing Plot (320MHz (UNII Band 8) – Ch. 191 Low)**

FCC ID: A3LSMS928U	<b>MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 156 of 185



**Plot 7-207. Contention Based Protocol Timing Plot (320MHz (UNII Band 8) – Ch. 191 Mid)**




**Plot 7-208. Contention Based Protocol Timing Plot (320MHz (UNII Band 8) – Ch. 191 High)**

FCC ID: A3LSMS928U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 157 of 185

### 7.6.3 Channel Move Plots

This section demonstrates the effect of injecting the AWGN signal at various locations throughout the 320MHz signal. The blue trace shows the full 320MHz signal prior to AWGN injection while the black trace shows the spectrum following AWGN injection. The following items were observed as demonstrated in the three plots shown below:


- When a 10 MHz AWGN signal centered at 6110 MHz (lower edge of channel) is injected, the channel completely stops transmitting.
- When a 10 MHz AWGN signal centered at 6265 MHz (middle of channel) is injected, the channel completely stops transmitting.
- When a 10 MHz AWGN signal centered at 6420 MHz (upper edge of channel) is injected, the channel completely stops transmitting.



Date: 1.NOV.2023 08:03:18


**Plot 7-209. CBP 320MHz Channel - Injection Lower Edge – [6110 MHz]**

FCC ID: A3LSMS928U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 158 of 185



Date: 1.NOV.2023 08:02:16

**Plot 7-210. CBP 320MHz Channel - Injection Center – [6265 MHz]**



Date: 1.NOV.2023 08:07:03

**Plot 7-211. CBP 320MHz Channel - Injection Upper Edge – [6420 MHz]**

FCC ID: A3LSMS928U	<b>MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 159 of 185

## 7.7 Radiated Emission Measurements

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11ax (20/40/80/160MHz), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

***For transmitters operating in the 5.925-7.125 GHz band: All emissions outside of the 5.925-7.125 GHz band shall not exceed an EIRP of -27dBm/MHz (68.2dBuV/m at a 3m distance). Emissions found in a restricted band are subject to the limits of 15.209 as shown in the table below.***

Frequency	Field Strength [ $\mu$ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400\F (kHz)	300
0.490 – 1.705 MHz	24000\F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

**Table 7-82. Radiated Limits**

### Test Procedures Used

ANSI C63.10-2013 – Sections 12.7.7.2, 12.7.6, 12.7.5

### Test Settings – Above 1GHz

#### Average Field Strength Measurements (Method AD – Average Detection)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be  $\geq 2 \times \text{span} \backslash \backslash \text{RBW}$ )
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces.

FCC ID: A3LSMS928U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 160 of 185

### Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize.


### Test Settings – Below 1GHz

#### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.

### Test Setup


The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-6. Radiated Test Setup < 30MHz**

<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 161 of 185





**Figure 7-7. Radiated Test Setup < 1GHz**



**Figure 7-8. Radiated Test Setup > 1GHz**

<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 162 of 185

**Test Notes**

1. All spurious emissions lying in restricted bands specified in §15.205 are below the limits specified in §15.209. All spurious emissions that do not lie in a restricted band are subject to an average limit of -27dBm/MHz. At 3 meters, the field strength limit in dBμV/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
2. All spurious emissions that do not lie in a restricted band are subject to a peak limit not to exceed 20dB of the average limit [68.2dBμV/m]. If a peak measurement passes the average limit, it was determined no further investigation is necessary.
3. The antenna is manipulated through typical positions, polarity, and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported, however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
8. In the case where a peak-detector measurement passed the given RMS limit it was determined sufficient to demonstrate compliance.
9. The results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.

**Sample Calculations**

**Determining Spurious Emissions Levels**

- Field Strength Level [dBμV/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- Margin [dB] = Field Strength Level [dBμV/m] – Limit [dBμV/m]


**Radiated Band Edge Measurement Offset**

The amplitude offset shown in the radiated restricted band edge plots was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$


<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 163 of 185

### 7.7.1 MIMO Radiated Spurious Emission Measurements



**Plot 7-212. Radiated Spurious Plot below 1GHz MIMO (802.11ax)**

<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 164 of 185




**Plot 7-213. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11ax – UNII Band 5 Ch. 45 – LPI)**

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
802.11a	MIMO	5	2	5935	*	11870.00	Average	V	-	-	-78.45	9.32	0.00	37.87	53.98	-16.11
					*	11870.00	Peak	V	-	-	-66.09	9.32	0.00	50.23	73.98	-23.75
					*	17805.00	Average	V	-	-	-77.12	15.72	0.00	45.60	53.98	-8.38
					*	17805.00	Peak	V	-	-	-65.28	15.72	0.00	57.44	73.98	-16.54
					*	23740.00	Average	V	-	-	-66.42	3.96	-9.54	34.99	53.98	-18.99
					*	23740.00	Peak	V	-	-	-55.33	3.96	-9.54	46.09	73.98	-27.89
				29675.00	Peak	V	-	-	-55.33	5.90	-9.54	48.03	68.20	-20.17		
				12350.00	Average	V	-	-	-78.27	9.60	0.00	38.33	53.98	-15.65		
			*	12350.00	Peak	V	-	-	-65.86	9.60	0.00	50.74	73.98	-23.24		
			*	18525.00	Average	V	-	-	-65.06	1.55	-9.54	33.95	53.98	-20.03		
			*	18525.00	Peak	V	-	-	-54.14	1.55	-9.54	44.87	73.98	-29.11		
				24700.00	Peak	V	-	-	-55.75	4.20	-9.54	45.91	68.20	-22.29		
				30875.00	Peak	V	-	-	-56.21	6.77	-9.54	48.02	68.20	-20.18		
				12830.00	Peak	V	-	-	-66.73	9.64	0.00	49.91	68.20	-18.29		
			*	19245.00	Average	V	-	-	-65.23	2.35	-9.54	34.58	53.98	-19.40		
			*	19245.00	Peak	V	-	-	-54.00	2.35	-9.54	45.81	73.98	-28.17		
				25660.00	Peak	V	-	-	-54.94	4.41	-9.54	46.93	68.20	-21.27		
				32075.00	Peak	V	-	-	-56.36	7.43	-9.54	48.54	68.20	-19.66		

**Table 7-83. Radiated Measurements MIMO – LPI**

<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 165 of 185




**Plot 7-214. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11ax – UNII Band 5 Ch. 45 – SP)**

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]					
802.11a	MIMO	5	2	5935	*	11870.00	Average	V	-	-	-78.32	9.32	0.00	38.00	53.98	-15.98					
					*	11870.00	Peak	V	-	-	-66.05	9.32	0.00	50.27	73.98	-23.71					
					*	17805.00	Average	V	-	-	-77.03	15.72	0.00	45.69	53.98	-8.29					
					*	17805.00	Peak	V	-	-	-64.33	15.72	0.00	58.39	73.98	-15.59					
					*	23740.00	Average	V	-	-	-66.49	3.96	-9.54	34.92	53.98	-19.06					
					*	23740.00	Peak	V	-	-	-55.17	3.96	-9.54	46.24	73.98	-27.74					
									29675.00	Peak	V	-	-	-55.73	5.90	-9.54	47.64	68.20	-20.56		
						45	6175	*	12350.00	Average	V	-	-	-78.25	9.60	0.00	38.35	53.98	-15.63		
			*	12350.00	Peak			V	-	-	-66.32	9.60	0.00	50.28	73.98	-23.70					
			*	18525.00	Average			V	-	-	-65.17	1.55	-9.54	33.84	53.98	-20.14					
			*	18525.00	Peak			V	-	-	-54.50	1.55	-9.54	44.50	73.98	-29.48					
											24700.00	Peak	V	-	-	-54.71	4.20	-9.54	46.95	68.20	-21.25
											30875.00	Peak	V	-	-	-55.63	6.77	-9.54	48.60	68.20	-19.60
						93	6415		12830.00	Peak	V	-	-	-67.08	9.64	0.00	49.56	68.20	-18.64		
			*	19245.00	Average			V	-	-	-65.32	2.35	-9.54	34.49	53.98	-19.49					
			*	19245.00	Peak			V	-	-	-53.83	2.35	-9.54	45.98	73.98	-28.00					
											25660.00	Peak	V	-	-	-54.13	4.41	-9.54	47.74	68.20	-20.46
											32075.00	Peak	V	-	-	-56.33	7.43	-9.54	48.56	68.20	-19.64

**Table 7-84. Radiated Measurements MIMO - SP**

<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 166 of 185




**Plot 7-215. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11ax – UNII Band 6 Ch. 105 – LPI)**

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
802.11a	MIMO	6	97	6435		12870.00	Peak	V	-	-	-67.38	10.05	0.00	49.67	68.20	-18.53
					*	19305.00	Average	V	-	-	-66.50	2.13	-9.54	33.09	53.98	-20.89
					*	19305.00	Peak	V	-	-	-55.81	2.13	-9.54	43.78	73.98	-30.20
						25740.00	Peak	V	-	-	-57.31	4.51	-9.54	44.66	68.20	-23.54
						32175.00	Peak	V	-	-	-57.51	7.53	-9.54	47.48	68.20	-20.72
			105	6475		12950.00	Peak	V	-	-	-66.09	10.12	0.00	51.03	68.20	-17.17
					*	19425.00	Average	V	-	-	-66.31	2.22	-9.54	33.37	53.98	-20.61
					*	19425.00	Peak	V	-	-	-56.78	2.22	-9.54	42.90	73.98	-31.08
						25900.00	Peak	V	-	-	-56.45	4.57	-9.54	45.58	68.20	-22.62
						32375.00	Peak	V	-	-	-58.17	7.29	-9.54	46.59	68.20	-21.61
			113	6515		13030.00	Peak	V	-	-	-66.34	10.12	0.00	50.78	68.20	-17.42
					*	19545.00	Average	V	-	-	-66.13	2.37	-9.54	33.70	53.98	-20.28
					*	19545.00	Peak	V	-	-	-56.49	2.37	-9.54	43.34	73.98	-30.64
						26060.00	Peak	V	-	-	-57.00	4.80	-9.54	45.26	68.20	-22.94
						32575.00	Peak	V	-	-	-57.04	6.85	-9.54	47.27	68.20	-20.93

**Table 7-85. Radiated Measurements MIMO – LPI**

<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 167 of 185




**Plot 7-216. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11ax – UNII Band 7 Ch. 149 – LPI)**

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
802.11a	MIMO	7	117	6535		13070.00	Peak	V	-	-	-66.17	10.15	0.00	50.98	68.20	-17.22
					*	19605.00	Average	V	-	-	-65.11	2.64	-9.54	34.99	53.98	-18.99
					*	19605.00	Peak	V	-	-	-54.06	2.64	-9.54	46.04	73.98	-27.94
						26140.00	Peak	V	-	-	-55.67	4.56	-9.54	46.34	68.20	-21.86
						32675.00	Peak	V	-	-	-55.22	7.03	-9.54	49.27	68.20	-18.93
			149	6695	*	13390.00	Average	V	-	-	-78.40	10.35	0.00	38.95	53.98	-15.03
					*	13390.00	Peak	V	-	-	-66.01	10.35	0.00	51.34	73.98	-22.64
					*	20085.00	Peak	V	-	-	-65.61	3.01	-9.54	34.86	53.98	-19.12
					*	20085.00	Average	V	-	-	-54.64	3.01	-9.54	45.83	73.98	-28.15
						26780.00	Peak	V	-	-	-56.33	4.57	-9.54	45.70	68.20	-22.50
			185	6875		33475.00	Peak	V	-	-	-56.46	7.57	-9.54	48.57	68.20	-19.63
						13750.00	Peak	V	-	-	-66.40	11.07	0.00	51.67	68.20	-16.53
					*	20625.00	Average	V	-	-	-67.04	3.42	-9.54	33.84	53.98	-20.14
					*	20625.00	Peak	V	-	-	-58.24	3.42	-9.54	42.65	73.98	-31.33
						27500.00	Peak	V	-	-	-56.13	4.54	-9.54	45.87	68.20	-22.33
	34375.00	Peak	V	-	-	-57.19	8.08	-9.54	48.35	68.20	-19.85					

**Table 7-86. Radiated Measurements MIMO – LPI**

<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 168 of 185




**Plot 7-217. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11ax – UNII Band 7 Ch. 149 – SP)**

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
802.11a	MIMO	7	117	6535		13070.00	Peak	V	-	-	-66.89	10.15	0.00	50.26	68.20	-17.94
					*	19605.00	Average	V	-	-	-65.14	2.64	-9.54	34.97	53.98	-19.01
					*	19605.00	Peak	V	-	-	-53.43	2.64	-9.54	46.67	73.98	-27.31
						26140.00	Peak	V	-	-	-55.76	4.56	-9.54	46.26	68.20	-21.94
						32675.00	Peak	V	-	-	-55.48	7.03	-9.54	49.01	68.20	-19.19
			149	6695	*	13390.00	Average	V	-	-	-78.43	10.35	0.00	38.92	53.98	-15.06
					*	13390.00	Peak	V	-	-	-66.20	10.35	0.00	51.15	73.98	-22.83
					*	20085.00	Peak	V	100	328	-63.19	3.01	-9.54	37.28	53.98	-16.70
					*	20085.00	Average	V	100	328	-51.76	3.01	-9.54	48.71	73.98	-25.27
						26780.00	Peak	V	-	-	-55.33	4.57	-9.54	46.71	68.20	-21.49
			185	6875		33475.00	Peak	V	-	-	-56.04	7.57	-9.54	48.99	68.20	-19.21
						13750.00	Peak	V	-	-	-66.31	11.07	0.00	51.76	68.20	-16.44
					*	20625.00	Average	V	100	35	-62.73	3.42	-9.54	38.15	53.98	-15.83
					*	20625.00	Peak	V	100	35	-53.57	3.42	-9.54	47.31	73.98	-26.67
						27500.00	Peak	V	-	-	-56.47	4.54	-9.54	45.53	68.20	-22.67
	34375.00	Peak	V	-	-	-56.62	8.08	-9.54	48.92	68.20	-19.28					

**Table 7-87. Radiated Measurements MIMO – SP**

<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 169 of 185






**Plot 7-218. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11ax – U Band 8 Ch. 209 – LPI)**


Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
802.11a	MIMO	8	189	6895		13790.00	Peak	V	-	-	-65.80	11.00	0.00	52.20	68.20	-16.00
					*	20685.00	Average	V	-	-	-66.78	3.67	-9.54	34.35	53.98	-19.63
					*	20685.00	Peak	V	-	-	-57.66	3.67	-9.54	43.47	73.98	-30.51
						27580.00	Peak	V	-	-	-57.32	4.68	-9.54	44.83	68.20	-23.37
						34475.00	Peak	V	-	-	-57.73	7.83	-9.54	47.56	68.20	-20.64
			209	6995		13990.00	Peak	V	-	-	-65.76	11.26	0.00	52.50	68.20	-15.70
					*	20985.00	Average	V	-	-	-67.82	3.59	-9.54	33.23	53.98	-20.75
					*	20985.00	Peak	V	-	-	-56.82	3.59	-9.54	44.23	73.98	-29.75
						27980.00	Peak	V	-	-	-57.76	5.05	-9.54	44.76	68.20	-23.44
						34975.00	Peak	V	-	-	-57.83	8.24	-9.54	47.87	68.20	-20.33
			233	7115		14230.00	Peak	V	-	-	-66.01	12.13	0.00	53.12	68.20	-15.08
					*	21345.00	Average	V	-	-	-67.38	4.08	-9.54	34.16	53.98	-19.82
					*	21345.00	Peak	V	-	-	-56.79	4.08	-9.54	44.75	73.98	-29.23
						28460.00	Peak	V	-	-	-57.66	5.14	-9.54	44.94	68.20	-23.26
						35575.00	Peak	V	-	-	-57.53	8.16	-9.54	48.09	68.20	-20.11

**Table 7-88. Radiated Measurements MIMO – LPI**

<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 170 of 185



**Plot 7-219. Radiated Spurious Plot 18GHz - 26.5GHz (802.11ax)**




**Plot 7-220. Radiated Spurious Plot 26.5GHz - 40GHz (802.11ax)**


<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 171 of 185

## 7.7.2 MIMO Radiated Band Edge Measurements (20MHz BW)

Worst Case Mode: 802.11be  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5935MHz  
 Channel: 2




**Plot 7-221. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 5)**




**Plot 7-222. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 5)**

Worst Case Mode: 802.11be  
 Worst Case Transfer Rate: MSC0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 7115MHz  
 Channel: 233




**Plot 7-223. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 8)**




**Plot 7-224. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 8)**

<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 172 of 185

Worst Case Mode: 802.11be  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 7115MHz  
 Channel: 233



**Plot 7-225. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 8) with WCP**




**Plot 7-226. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 8) with WCP**


<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 173 of 185

### 7.7.3 MIMO Radiated Band Edge Measurements (40MHz BW)

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5965MHz
Channel:	3




**Plot 7-227. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 5)**




**Plot 7-228. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 5)**

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	7085MHz
Channel:	227



**Plot 7-229. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 8)**




**Plot 7-230. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 8)**


FCC ID: A3LSMS928U	<b>MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 174 of 185

### 7.7.4 MIMO Radiated Band Edge Measurements (80MHz BW)

Worst Case Mode: 802.11be  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5985MHz  
 Channel: 7




**Plot 7-231. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 5)**




**Plot 7-232. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 5)**

Worst Case Mode: 802.11be  
 Worst Case Transfer Rate: MCS0  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 7025MHz  
 Channel: 215



**Plot 7-233. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 8)**




**Plot 7-234. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 8)**


FCC ID: A3LSMS928U	<b>MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 175 of 185

## 7.7.5 MIMO Radiated Band Edge Measurements (160MHz BW)

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6025MHz
Channel:	15




**Plot 7-235. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 5)**




**Plot 7-236. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 5)**

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6985MHz
Channel:	207



**Plot 7-237. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 8)**




**Plot 7-238. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 8)**


<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 176 of 185

## 7.7.6 MIMO Radiated Band Edge Measurements (320MHz BW)

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6105MHz
Channel:	31




**Plot 7-239. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 5)**




**Plot 7-240. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 5)**

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6905MHz
Channel:	191



**Plot 7-241. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 8)**



**Plot 7-242. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 8)**

<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 177 of 185



## 7.8 Line Conducted Test Data

### Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst-case emissions are reported in this section.

**All conducted emissions must not exceed the limits shown in the table below, per Section 15.207.**

Frequency of emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

**Table 7-89. Conducted Limits**

\*Decreases with the logarithm of the frequency.

### Test Procedures Used

ANSI C63.10-2013, Section 6.2

### Test Settings

#### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest.
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.


#### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest.
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.

FCC ID: A3LSMS928U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 178 of 185

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-9. Test Instrument & Measurement Setup**


### Test Notes

1. All modes of operation were investigated, and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz is specified in 15.207.
3.  $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4.  $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5.  $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 179 of 185




Plot 7-243. Line Conducted Plot with 802.11a UNII Band 5 (L1)




Plot 7-244. Line Conducted Plot with 802.11a UNII Band 5 (N)

FCC ID: A3LSMS928U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 180 of 185




Plot 7-245. Line Conducted Plot with 802.11a UNII Band 6 (L1)




Plot 7-246. Line Conducted Plot with 802.11a UNII Band 6 (N)

FCC ID: A3LSMS928U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 181 of 185




Plot 7-247. Line Conducted Plot with 802.11a UNII Band 7 (L1)




Plot 7-248. Line Conducted Plot with 802.11a UNII Band 7 (N)

FCC ID: A3LSMS928U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 182 of 185




Plot 7-249. Line Conducted Plot with 802.11a UNII Band 8 (L1)




Plot 7-250. Line Conducted Plot with 802.11a UNII Band 8 (N)

FCC ID: A3LSMS928U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 183 of 185



Plot 7-251. Line Conducted Plot with 802.11a UNII Band 5 (L1) with WCP



Plot 7-252. Line Conducted Plot with 802.11a UNII Band 5 (N) with WCP

FCC ID: A3LSMS928U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2308210092-17-R1.A3L	Test Dates: 9/6/2023 – 11/2/2023	EUT Type: Portable Handset	Page 184 of 185

## 8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMS928U** is in compliance with FCC Part Subpart E (15.407) of the FCC rules for operation as a client device.

<b>FCC ID:</b> A3LSMS928U	<b>MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2308210092-17-R1.A3L	<b>Test Dates:</b> 9/6/2023 – 11/2/2023	<b>EUT Type:</b> Portable Handset	Page 185 of 185