


Plot 7-83. Radiated Spurious Plot – 18GHz - 26.5GHz (ULCA LB48 – Mid Channel)



Plot 7-84. Radiated Spurious Plot – 26GHz - 40GHz (ULCA LB48 – Mid Channel)

| | |
|----------------------|--------|
| PCC Bandwidth (MHz): | 20 |
| PCC Frequency (MHz): | 3560.0 |
| PCC RB / Offset: | 1 / 99 |
| SCC Bandwidth (MHz): | 20 |
| SCC Frequency (MHz): | 3579.8 |
| SCC RB / Offset: | 1 / 0 |
| Modulation Signal: | QPSK |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7139.80 | V | 112 | 230 | -75.13 | 9.62 | 41.49 | -53.77 | -40.00 | -13.77 |
| 10709.70 | V | - | - | -77.81 | 12.33 | 41.52 | -53.74 | -40.00 | -13.74 |
| 14279.60 | V | - | - | -78.10 | 15.61 | 44.51 | -50.75 | -40.00 | -10.75 |
| 17849.50 | V | - | - | -78.37 | 17.62 | 46.25 | -49.00 | -40.00 | -9.00 |
| 21419.40 | V | - | - | -58.50 | 3.98 | 52.48 | -52.32 | -40.00 | -12.32 |

Table 7-36. Radiated Spurious Data (ULCA LB48 – Low Channel)

| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 84 of 110 |



| | |
|----------------------|--------|
| PCC Bandwidth (MHz): | 20 |
| PCC Frequency (MHz): | 3625.0 |
| PCC RB / Offset: | 1 / 99 |
| SCC Bandwidth (MHz): | 20 |
| SCC Frequency (MHz): | 3644.8 |
| SCC RB / Offset: | 1 / 0 |
| Modulation Signal: | QPSK |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7269.80 | V | 117 | 224 | -74.08 | 8.84 | 41.76 | -53.50 | -40.00 | -13.50 |
| 10904.70 | V | - | - | -77.46 | 12.51 | 42.05 | -53.21 | -40.00 | -13.21 |
| 14539.60 | V | - | - | -78.83 | 15.63 | 43.80 | -51.46 | -40.00 | -11.46 |
| 18174.50 | V | - | - | -57.77 | 1.56 | 50.78 | -54.02 | -40.00 | -14.02 |

Table 7-37. Radiated Spurious Data (ULCA LB48 – Mid Channel)

| | |
|----------------------|--------|
| PCC Bandwidth (MHz): | 20 |
| PCC Frequency (MHz): | 3690.0 |
| PCC RB / Offset: | 1 / 0 |
| SCC Bandwidth (MHz): | 20 |
| SCC Frequency (MHz): | 3670.2 |
| SCC RB / Offset: | 1 / 99 |
| Modulation Signal: | QPSK |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7360.20 | V | - | - | -76.16 | 9.61 | 40.45 | -54.81 | -40.00 | -14.81 |
| 11040.30 | V | - | - | -77.22 | 12.05 | 41.83 | -53.42 | -40.00 | -13.42 |
| 14720.40 | V | - | - | -78.80 | 15.48 | 43.68 | -51.58 | -40.00 | -11.58 |
| 18400.50 | V | - | - | -58.62 | 1.46 | 49.84 | -54.96 | -40.00 | -14.96 |

Table 7-38. Radiated Spurious Data (ULCA LB48 – High Channel)


| | |
|----------------------|--------------------------|
| Case: | w/ Wireless Charging Pad |
| PCC Bandwidth (MHz): | 20 |
| PCC Frequency (MHz): | 3625.0 |
| PCC RB / Offset: | 1 / 99 |
| SCC Bandwidth (MHz): | 20 |
| SCC Frequency (MHz): | 3644.8 |
| SCC RB / Offset: | 1 / 0 |
| Modulation Signal: | QPSK |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7269.80 | V | - | - | -75.33 | 8.84 | 40.51 | -54.75 | -40.00 | -14.75 |
| 10904.70 | V | - | - | -77.42 | 12.51 | 42.09 | -53.17 | -40.00 | -13.17 |
| 14539.60 | V | - | - | -78.70 | 15.63 | 43.93 | -51.33 | -40.00 | -11.33 |

Table 7-39. Radiated Spurious Data with WCP (ULCA LB48)

| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 85 of 110 |

NR Band n48 Ant F




Plot 7-85. Radiated Spurious Plot (NR Band n48 – Below 1GHz)

| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3625.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |


| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | ERP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|-----------------------------------|-------------|-------------|
| 103.38 | V | 128 | 64 | -98.92 | 18.06 | 26.14 | -71.27 | -40.00 | -31.27 |
| 886.20 | V | - | - | -97.32 | 31.01 | 40.69 | -56.72 | -40.00 | -16.72 |

Table 7-40. Radiated Spurious Data (NR Band n48 – Mid Channel)


| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 86 of 110 |



Plot 7-86. Radiated Spurious Plot (NR Band n48 – 1GHz - 18GHz)



Plot 7-87. Radiated Spurious Plot (NR Band n48 – 18GHz - 26.5GHz)



Plot 7-88. Radiated Spurious Plot (NR Band n48 – 26GHz - 40GHz)

| | | | |
|--|---|--------------------------------------|--|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 87 of 110 |



| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3570.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBµV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7140.00 | V | - | - | -76.93 | 9.62 | 39.69 | -55.57 | -40.00 | -15.57 |
| 10710.00 | V | - | - | -77.75 | 12.33 | 41.58 | -53.67 | -40.00 | -13.67 |
| 14280.00 | V | - | - | -78.57 | 15.60 | 44.03 | -51.23 | -40.00 | -11.23 |
| 17850.00 | V | - | - | -78.51 | 17.64 | 46.13 | -49.13 | -40.00 | -9.13 |

Table 7-41. Radiated Spurious Data (NR Band n48 – Low Channel)

| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3625.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBµV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7250.00 | V | - | - | -75.74 | 9.18 | 40.44 | -54.82 | -40.00 | -14.82 |
| 10875.00 | V | - | - | -77.63 | 11.95 | 41.32 | -53.94 | -40.00 | -13.94 |
| 14500.00 | V | - | - | -78.59 | 15.94 | 44.35 | -50.90 | -40.00 | -10.90 |

Table 7-42. Radiated Spurious Data (NR Band n48 – Mid Channel)

| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3680.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBµV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7360.00 | V | - | - | -76.24 | 9.60 | 40.36 | -54.90 | -40.00 | -14.90 |
| 11040.00 | V | - | - | -77.30 | 12.06 | 41.76 | -53.50 | -40.00 | -13.50 |
| 14720.00 | V | - | - | -78.36 | 15.48 | 44.12 | -51.13 | -40.00 | -11.13 |

Table 7-43. Radiated Spurious Data (NR Band n48 – High Channel)


| | |
|----------------------------|--------------------------|
| Case: | w/ Wireless Charging Pad |
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3625.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBµV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7250.00 | V | - | - | -75.90 | 9.18 | 40.28 | -54.98 | -40.00 | -14.98 |
| 10875.00 | V | - | - | -77.61 | 11.95 | 41.34 | -53.92 | -40.00 | -13.92 |
| 14500.00 | V | - | - | -78.63 | 15.94 | 44.31 | -50.94 | -40.00 | -10.94 |

Table 7-44. Radiated Spurious Data with WCP (NR Band n48 Ant F)

| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 88 of 110 |

NR Band n48 - Ant C




Plot 7-89. Radiated Spurious Plot (NR Band n48 – Below 1GHz)

| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3680.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |


| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | ERP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|-----------------------------------|-------------|-------------|
| 54.80 | V | - | - | -99.66 | 16.86 | 24.20 | -73.21 | -40.00 | -33.21 |
| 99.20 | V | 183 | 203 | -96.87 | 16.86 | 26.99 | -70.42 | -40.00 | -30.42 |

Table 7-45. Radiated Spurious Data (NR Band n48 – Mid Channel - Ant C)


| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 89 of 110 |



Plot 7-90. Radiated Spurious Plot (NR Band n48 – 1GHz - 18GHz)



Plot 7-91. Radiated Spurious Plot (NR Band n48 – 18GHz - 26.5GHz)



Plot 7-92. Radiated Spurious Plot (NR Band n48 – 26GHz - 40GHz)

| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 90 of 110 |



| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3570.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBµV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7140.00 | V | 215 | 2 | -75.61 | 9.62 | 41.01 | -54.25 | -40.00 | -14.25 |
| 10710.00 | V | - | - | -77.87 | 12.33 | 41.46 | -53.79 | -40.00 | -13.79 |
| 14280.00 | V | - | - | -78.27 | 15.60 | 44.33 | -50.93 | -40.00 | -10.93 |
| 17850.00 | V | - | - | -78.63 | 17.64 | 46.01 | -49.25 | -40.00 | -9.25 |

Table 7-46. Radiated Spurious Data (NR Band n48 – Low Channel - Ant C)

| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3625.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBµV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7250.00 | V | 268 | 38 | -73.29 | 9.18 | 42.89 | -52.37 | -40.00 | -12.37 |
| 10875.00 | V | - | - | -77.63 | 11.95 | 41.32 | -53.94 | -40.00 | -13.94 |
| 14500.00 | V | - | - | -78.22 | 15.94 | 44.72 | -50.53 | -40.00 | -10.53 |
| 18125.00 | V | - | - | -56.02 | 1.60 | 52.58 | -52.22 | -40.00 | -12.22 |

Table 7-47. Radiated Spurious Data (NR Band n48 – Mid Channel - Ant C)

| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3680.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBµV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7360.00 | V | 249 | 33 | -72.76 | 9.60 | 43.84 | -51.42 | -40.00 | -11.42 |
| 11040.00 | V | - | - | -76.99 | 12.06 | 42.07 | -53.19 | -40.00 | -13.19 |
| 14720.00 | V | - | - | -79.02 | 15.48 | 43.46 | -51.79 | -40.00 | -11.79 |
| 18400.00 | V | - | - | -57.23 | 1.45 | 51.23 | -53.57 | -40.00 | -13.57 |

Table 7-48. Radiated Spurious Data (NR Band n48 – High Channel - Ant C)

| | |
|----------------------------|--------------------------|
| Case: | w/ Wireless Charging Pad |
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3680.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |


| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBµV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7360.00 | V | 238.00 | 341.00 | -74.02 | 9.60 | 42.58 | -52.68 | -40.00 | -12.68 |
| 11040.00 | V | - | - | -77.52 | 12.06 | 41.54 | -53.72 | -40.00 | -13.72 |
| 14720.00 | V | - | - | -78.34 | 15.48 | 44.14 | -51.11 | -40.00 | -11.11 |
| 18400.00 | V | - | - | -57.23 | 1.45 | 51.23 | -53.57 | -40.00 | -13.57 |

Table 7-49. Radiated Spurious Data with WCP (NR Band n48 - Ant C)

| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 91 of 110 |



NR Band n48 – Ant I




Plot 7-93. Radiated Spurious Plot – Below 1GHz (NR Band n48 Ant I)

| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3625.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |


| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | ERP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|-----------------------------------|-------------|-------------|
| 836.00 | H | - | - | -97.43 | 30.68 | 40.25 | -57.16 | -40.00 | -17.16 |

Table 7-50. Radiated Spurious Data (NR Band n48 – Mid Channel - Ant I)


| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 92 of 110 |



Plot 7-94. Radiated Spurious Plot - 1GHz - 18GHz (NR Band n48 - Ant I)



Plot 7-95. Radiated Spurious Plot 18GHz - 26.5GHz (NR Band n48 - Ant I)



Plot 7-96. Radiated Spurious Plot 26GHz - 40GHz (NR Band n48 - Ant I)

| | | | |
|--|---|--------------------------------------|--|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 93 of 110 |



| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3570.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7140.00 | H | - | - | -76.79 | 9.62 | 39.83 | -55.43 | -40.00 | -15.43 |
| 10710.00 | H | - | - | -78.11 | 12.33 | 41.22 | -54.03 | -40.00 | -14.03 |
| 14280.00 | H | - | - | -78.41 | 15.60 | 44.19 | -51.07 | -40.00 | -11.07 |
| 17850.00 | H | - | - | -78.63 | 17.64 | 46.01 | -49.25 | -40.00 | -9.25 |

Table 7-51. Radiated Spurious Data (NR Band n48 – Low Channel - Ant I)

| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3625.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7250.00 | H | - | - | -75.93 | 9.18 | 40.25 | -55.01 | -40.00 | -15.01 |
| 10875.00 | H | - | - | -77.85 | 11.95 | 41.10 | -54.16 | -40.00 | -14.16 |
| 14500.00 | H | - | - | -78.27 | 15.94 | 44.67 | -50.58 | -40.00 | -10.58 |

Table 7-52. Radiated Spurious Data (NR Band n48 – Mid Channel - Ant I)


| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3680.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7360.00 | H | - | - | -76.47 | 9.60 | 40.13 | -55.13 | -40.00 | -15.13 |
| 11040.00 | H | - | - | -77.29 | 12.06 | 41.77 | -53.49 | -40.00 | -13.49 |
| 14720.00 | H | - | - | -78.88 | 15.48 | 43.60 | -51.65 | -40.00 | -11.65 |

Table 7-53. Radiated Spurious Data (NR Band n48 – High Channel - Ant I)

| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 94 of 110 |

NR Band n48 – Ant D




Plot 7-97. Radiated Spurious Plot – Below 1GHz (NR Band n48 Ant D)

| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3680.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |


| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | ERP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|-----------------------------------|-------------|-------------|
| 99.10 | V | 371 | 98 | -95.57 | 16.81 | 28.24 | -69.17 | -40.00 | -29.17 |

Table 7-54. Radiated Spurious Data (NR Band n48 – Mid Channel - Ant D)


| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 95 of 110 |



Plot 7-98. Radiated Spurious Plot – 1GHz - 18GHz (NR Band n48 – Ant D)



Plot 7-99. Radiated Spurious Plot 18GHz – 26.5GHz (NR Band n48 – Ant D)



Plot 7-100. Radiated Spurious Plot 26GHz – 40GHz (NR Band n48 – Ant D)

| | | | |
|--|---|--------------------------------------|--|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 96 of 110 |



| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3570.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7140.00 | V | - | - | -77.00 | 9.62 | 39.62 | -55.64 | -40.00 | -15.64 |
| 10710.00 | V | - | - | -77.89 | 12.33 | 41.44 | -53.81 | -40.00 | -13.81 |
| 14280.00 | V | - | - | -78.49 | 15.60 | 44.11 | -51.15 | -40.00 | -11.15 |
| 17850.00 | V | - | - | -78.53 | 17.64 | 46.11 | -49.15 | -40.00 | -9.15 |

Table 7-55. Radiated Spurious Data (NR Band n48 – Low Channel - Ant D)

| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3625.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7250.00 | V | 133 | 2 | -73.26 | 9.18 | 42.92 | -52.34 | -40.00 | -12.34 |
| 10875.00 | V | - | - | -77.77 | 11.95 | 41.18 | -54.08 | -40.00 | -14.08 |
| 14500.00 | V | - | - | -78.17 | 15.94 | 44.77 | -50.48 | -40.00 | -10.48 |
| 18125.00 | V | - | - | -56.60 | 1.60 | 52.00 | -52.80 | -40.00 | -12.80 |

Table 7-56. Radiated Spurious Data (NR Band n48 – Mid Channel - Ant D)

| | |
|----------------------------|--------|
| Bandwidth (MHz): | 40 |
| Frequency (MHz): | 3680.0 |
| Modulation Signal: | QPSK |
| RB Config (Size / Offset): | 1 / 53 |

| Frequency [MHz] | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | EIRP Spurious Emission Level [dBm] | Limit [dBm] | Margin [dB] |
|-----------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|------------------------------------|-------------|-------------|
| 7360.00 | V | 149 | 0 | -74.32 | 9.60 | 42.28 | -52.98 | -40.00 | -12.98 |
| 11040.00 | V | - | - | -77.01 | 12.06 | 42.05 | -53.21 | -40.00 | -13.21 |
| 14720.00 | V | - | - | -78.83 | 15.48 | 43.65 | -51.60 | -40.00 | -11.60 |
| 18400.00 | V | - | - | -57.31 | 1.45 | 51.14 | -53.66 | -40.00 | -13.66 |

Table 7-57. Radiated Spurious Data (NR Band n48 – High Channel - Ant D)

| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 97 of 110 |



7.8 Frequency Stability / Temperature Variation

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 96, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI C63.26-2015 – Section 5.6

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes


None

| | | | |
|--|---|--------------------------------------|--|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 98 of 110 |

Frequency Stability / Temperature Variation

| LTE Band 48 | | | | | |
|---------------------------|-------------|---------------|----------------|-----------------|---------------|
| Operating Frequency (Hz): | | 3,625,000,000 | | | |
| Ref. Voltage (VDC): | | 4.27 | | | |
| Voltage (%) | Power (VDC) | Temp (°C) | Frequency (Hz) | Freq. Dev. (Hz) | Deviation (%) |
| 100 % | 4.27 | - 30 | 3,625,000,388 | 676 | 0.0000187 |
| | | - 20 | 3,624,999,632 | -80 | -0.0000022 |
| | | - 10 | 3,624,998,090 | -1,621 | -0.0000447 |
| | | 0 | 3,624,998,815 | -896 | -0.0000247 |
| | | + 10 | 3,624,997,439 | -2,272 | -0.0000627 |
| | | + 20 (Ref) | 3,624,999,712 | 0 | 0.0000000 |
| | | + 30 | 3,624,999,194 | -518 | -0.0000143 |
| | | + 40 | 3,624,998,520 | -1,192 | -0.0000329 |
| Battery Endpoint | 3.68 | + 20 | 3,624,998,922 | -790 | -0.0000218 |

Table 7-58. LTE Band 48 Frequency Stability Data




Plot 7-101. LTE Band 48 Frequency Stability Chart

| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 99 of 110 |

| NR Band n48 | | | | | |
|---------------------------|-------------|---------------|----------------|-----------------|---------------|
| Operating Frequency (Hz): | | 3,625,000,000 | | | |
| Ref. Voltage (VDC): | | 4.27 | | | |
| Voltage (%) | Power (VDC) | Temp (°C) | Frequency (Hz) | Freq. Dev. (Hz) | Deviation (%) |
| 100 % | 4.27 | - 30 | 3,625,154,000 | 811 | 0.0000224 |
| | | - 20 | 3,625,151,927 | -1,262 | -0.0000348 |
| | | - 10 | 3,625,156,039 | 2,850 | 0.0000786 |
| | | 0 | 3,625,152,208 | -980 | -0.0000270 |
| | | + 10 | 3,625,152,725 | -463 | -0.0000128 |
| | | + 20 (Ref) | 3,625,153,189 | 0 | 0.0000000 |
| | | + 30 | 3,625,153,803 | 614 | 0.0000169 |
| | | + 40 | 3,625,154,714 | 1,525 | 0.0000421 |
| | | + 50 | 3,625,152,083 | -1,106 | -0.0000305 |
| Battery Endpoint | 3.68 | + 20 | 3,625,152,398 | -791 | -0.0000218 |

Table 7-59. LTE Band 48 Frequency Stability Data



Plot 7-102. LTE Band 48 Frequency Stability Chart

| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 100 of 110 |



7.9 End User Device Additional Requirement (CBSD Protocol)

Test Overview and Limit

End user device additional requirements (CBSD Protocol) are tested per the test procedures listed below. During testing, the EUT is connected to a certified LTE CBSD (Ruckus FCC ID: S9GQ910US00) or to a certified NR CBSD (FCC ID: PIDAV2700) as a companion device to show compliance with Part 96.47.

End User Devices may operate only if they can positively receive and decode an authorization signal transmitted by a CBSD, including the frequencies and power limits for their operation.

An End User Device must discontinue operations, change frequencies, or change its operational power level within 10 seconds of receiving instructions from its associated CBSD.

Test Procedure Used

KDB 940660 D01 v03, WINNF-18-IN-00178 v1.0.0.00

Test Setup/Method

The EUT was connected via an RF cable to a certified CBSD and spectrum analyzer. The following procedure is performed by applying WINNF-TS-0122 CBRS CBSD Test Specification.


1. Run#1:
 - a. Setup WINNF.PT.C.HBT.1 with 3615MHz – 3635MHz.
 - b. Enable AP service from Ruckus Cloud management.
 - c. Check EUT Tx frequency.
 - d. Disable AP service from Ruckus Cloud management and check EUT stop transmission within 10s.
2. Run#2:
 - a. Setup WINNF.PT.C.HBT.1 with 3660MHz – 3680MHz.
 - b. Enable AP service from Ruckus Cloud management.
 - c. Check EUT Tx frequency.
 - d. Disable AP service from Ruckus Cloud management and check EUT stop transmission within 10s.

Test Notes

The EUT is an End User Device.


| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 101 of 110 |

Run#1: LTE Band 48



Plot 7-103. Run#1 End User Device Frequency of Operations

| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 102 of 110 |




Plot 7-104. Run#1 End User Device Discontinues Operations within 10s

Note:

- Marker 1: CBSD sends instructions to discontinue LTE operations.
- Marker 2: EUT discontinues operation.
- Marker 3: 10 seconds elapsed time from CBSD sending instructions to EUT.


| | | | |
|--|---|--------------------------------------|--|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 103 of 110 |

Run#2:



Plot 7-105. Run#2 End User Device Frequency of Operations

| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 104 of 110 |




Plot 7-106. Run#2 End User Device Discontinues Operations within 10s

Note:

- Marker 1: CBSD sends instructions to discontinue LTE operations.
- Marker 2: EUT discontinues operation.
- Marker 3: 10 seconds elapsed time from CBSD sending instructions to EUT.


| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 105 of 110 |

Run#1: NR Band n48



Plot 7-107. Run#1 End User Device Frequency of Operations

| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 106 of 110 |




Plot 7-108. Run#1 End User Device Discontinues Operations within 10s

Note:

- Marker 1: CBSD sends instructions to discontinue LTE operations.
- Marker 2: EUT discontinues operation.
- Marker 3: 10 seconds elapsed time from CBSD sending instructions to EUT.


| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 107 of 110 |

Run#2:



Plot 7-109. Run#2 End User Device Frequency of Operations

| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 108 of 110 |



Plot 7-110. Run#2 End User Device Discontinues Operations within 10s

Note:

- Marker 1: CBSD sends instructions to discontinue LTE operations.
- Marker 2: EUT discontinues operation.
- Marker 3: 10 seconds elapsed time from CBSD sending instructions to EUT.

| | | | |
|---|--------------------------------------|-------------------------------|-----------------------------------|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 109 of 110 |

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset** **FCC ID: A3LSMS928U** complies with all of the End User Device requirements of Part 96 of the FCC Rules for LTE operation only.

| | | | |
|--|---|--------------------------------------|--|
| FCC ID: A3LSMS928U | PART 96 MEASUREMENT REPORT | | Approved by: Technical Manager |
| Test Report S/N: 1M2308210092-08.A3L | Test Dates: 9/6/2023 - 10/22/2023 | EUT Type: Portable Handset | Page 110 of 110 |