




Radiated Spurious Emission Measurements – Ant 1 §15.205 §15.209 §15.247(d)



Plot 7-159. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 0) – Ant 1



Plot 7-160. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 19) – Ant 1



Plot 7-161. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 39) – Ant 1

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 111 of 132

Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 37

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4808.00	Avg	H	162	336	-75.46	6.89	0.00	38.43	53.98	-15.55
4808.00	Peak	H	162	336	-66.94	6.89	0.00	46.95	73.98	-27.03
12020.00	Avg	H	-	-	-83.03	18.55	0.00	42.52	53.98	-11.46
12020.00	Peak	H	-	-	-74.09	18.55	0.00	51.46	73.98	-22.52

Table 7-17. Radiated Measurements @ 3 meters – Ant 1

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2440MHz
 Channel: 17

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4880.00	Avg	H	153	338	-70.43	7.16	0.00	43.73	53.98	-10.25
4880.00	Peak	H	153	338	-60.44	7.16	0.00	53.72	73.98	-20.26
7320.00	Avg	H	176	341	-77.79	12.37	0.00	41.58	53.98	-12.39
7320.00	Peak	H	176	341	-68.37	12.37	0.00	51.00	73.98	-22.97
12200.00	Avg	H	-	-	-82.69	19.15	0.00	43.46	53.98	-10.52
12200.00	Peak	H	-	-	-73.67	19.15	0.00	52.48	73.98	-21.50

Table 7-18. Radiated Measurements @ 3 meters – Ant 1

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 112 of 132

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4960.00	Avg	H	150	327	-72.55	6.83	0.00	41.28	53.98	-12.70
4960.00	Peak	H	150	327	-64.46	6.83	0.00	49.37	73.98	-24.61
7440.00	Avg	H	150	343	-79.47	12.35	0.00	39.88	53.98	-14.10
7440.00	Peak	H	150	343	-70.28	12.35	0.00	49.07	73.98	-24.91
12400.00	Avg	H	-	-	-82.77	18.97	0.00	43.20	53.98	-10.78
12400.00	Peak	H	-	-	-74.23	18.97	0.00	51.74	73.98	-22.24


Table 7-19. Radiated Measurements @ 3 meters – Ant 1

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 113 of 132




Radiated Spurious Emission Measurements – Ant 2


§15.205 §15.209 §15.247(d)



Plot 7-162. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 0) – Ant 2



Plot 7-163. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 19) – Ant 2



Plot 7-164. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 39) – Ant 2

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 114 of 132

© 2022 ELEMENT

V11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Bluetooth Mode: LE
Distance of Measurements: 3 Meters
Operating Frequency: 2402MHz
Channel: 17

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4808.00	Avg	V	-	-	-79.94	6.89	0.00	33.95	53.98	-20.03
4808.00	Peak	V	-	-	-72.27	6.89	0.00	41.62	73.98	-32.36
12020.00	Avg	V	-	-	-83.52	18.55	0.00	42.03	53.98	-11.95
12020.00	Peak	V	-	-	-74.77	18.55	0.00	50.78	73.98	-23.20

Table 7-20. Radiated Measurements @ 3 meters – Ant 2

Bluetooth Mode: LE
Distance of Measurements: 3 Meters
Operating Frequency: 2440MHz
Channel: 37

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4880.00	Avg	V	143	178	-75.26	7.16	0.00	38.90	53.98	-15.08
4880.00	Peak	V	143	178	-71.63	7.16	0.00	42.53	73.98	-31.45
7320.00	Avg	V	-	-	-81.07	12.37	0.00	38.30	53.98	-15.67
7320.00	Peak	V	-	-	-74.27	12.37	0.00	45.10	73.98	-28.87
12200.00	Avg	V	-	-	-82.70	19.15	0.00	43.45	53.98	-10.53
12200.00	Peak	V	-	-	-74.76	19.15	0.00	51.39	73.98	-22.59

Table 7-21. Radiated Measurements @ 3 meters – Ant 2

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 115 of 132

© 2022 ELEMENT

V11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Bluetooth Mode: LE
Distance of Measurements: 3 Meters
Operating Frequency: 2480MHz
Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4960.00	Avg	V	-	-	-79.80	6.83	0.00	34.03	53.98	-19.95
4960.00	Peak	V	-	-	-71.84	6.83	0.00	41.99	73.98	-31.99
7440.00	Avg	V	-	-	-81.27	12.35	0.00	38.08	53.98	-15.90
7440.00	Peak	V	-	-	-73.08	12.35	0.00	46.27	73.98	-27.71
12400.00	Avg	V	-	-	-82.48	18.97	0.00	43.49	53.98	-10.49
12400.00	Peak	V	-	-	-74.12	18.97	0.00	51.85	73.98	-22.13


Table 7-22. Radiated Measurements @ 3 meters – Ant 2

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 116 of 132




Radiated Spurious Emission Measurements – Dual Ant


§15.205 §15.209 §15.247(d)



Plot 7-165. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 0) – Dual Ant



Plot 7-166. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 19) – Dual Ant



Plot 7-167. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 39) – Dual Ant

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 117 of 132

© 2022 ELEMENT

V11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 37

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4808.00	Avg	H	146	333	-76.87	6.89	0.00	37.02	53.98	-16.96
4808.00	Peak	H	146	333	-67.74	6.89	0.00	46.15	73.98	-27.83
12020.00	Avg	H	-	-	-82.82	18.55	0.00	42.73	53.98	-11.25
12020.00	Peak	H	-	-	-75.96	18.55	0.00	49.59	73.98	-24.39

Table 7-23. Radiated Measurements @ 3 meters – Dual Ant

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2440MHz
 Channel: 17

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4880.00	Avg	H	148	341	-72.21	7.16	0.00	41.95	53.98	-12.03
4880.00	Peak	H	148	341	-63.28	7.16	0.00	50.88	73.98	-23.10
7320.00	Avg	H	133	341	-79.95	12.37	0.00	39.42	53.98	-14.55
7320.00	Peak	H	133	341	-70.60	12.37	0.00	48.77	73.98	-25.20
12200.00	Avg	H	-	-	-81.99	19.15	0.00	44.16	53.98	-9.82
12200.00	Peak	H	-	-	-73.77	19.15	0.00	52.38	73.98	-21.60

Table 7-24. Radiated Measurements @ 3 meters – Dual Ant

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 118 of 132



Bluetooth Mode: LE
Distance of Measurements: 3 Meters
Operating Frequency: 2478MHz
Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4956.00	Avg	H	143	354	-74.60	6.83	0.00	39.23	53.98	-14.75
4956.00	Peak	H	143	354	-65.20	6.83	0.00	48.63	73.98	-25.35
7434.00	Avg	H	176	347	-80.16	12.35	0.00	39.19	53.98	-14.79
7434.00	Peak	H	176	347	-69.79	12.35	0.00	49.56	73.98	-24.42
12390.00	Avg	H	-	-	-82.69	18.97	0.00	43.28	53.98	-10.70
12390.00	Peak	H	-	-	-74.51	18.97	0.00	51.46	73.98	-22.52

Table 7-25. Radiated Measurements @ 3 meters – Dual Ant

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 119 of 132



7.8 Radiated Restricted Band Edge Measurements


§15.205 §15.209; RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.


The amplitude offset shown in the following plots for average measurements was calculated using the formula:

Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

Bluetooth Mode:	LE
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	39



Plot 7-168. Radiated Restricted Upper Band Edge Measurement (Average) – Ant 1



Plot 7-169. Radiated Restricted Upper Band Edge Measurement (Peak) – Ant 1

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 120 of 132


© 2022 ELEMENT

V11.1 08/28/2023


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Bluetooth Mode: LE
Measurement Distance: 3 Meters
Operating Frequency: 2480MHz
Channel: 39




Plot 7-170. Radiated Restricted Upper Band Edge Measurement (Average) – Ant 2




Plot 7-171. Radiated Restricted Upper Band Edge Measurement (Peak) – Ant 2

Bluetooth Mode: LE
Measurement Distance: 3 Meters
Operating Frequency: 2478MHz
Channel: 36



Plot 7-172. Radiated Restricted Upper Band Edge Measurement (Average) – Dual Ant



Plot 7-173. Radiated Restricted Upper Band Edge Measurement (Peak) – Dual Ant

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 121 of 132

© 2022 ELEMENT

V11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.9 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-23 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-26. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 122 of 132

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-7. Radiated Test Setup < 30Mhz




Figure 7-8. Radiated Test Setup < 1GHz

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 123 of 132


Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen(8.10) are below the limit shown in Table 7-23.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 124 of 132

Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]




Plot 7-174. Radiated Spurious Plot below 1GHz – Ant 1

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
53.70	Quasi-Peak	H	-	-	-102.76	14.38	18.62	40.00	-21.38
120.00	Quasi-Peak	H	-	-	-103.87	20.64	23.77	43.52	-19.75
200.00	Quasi-Peak	H	-	-	-103.58	19.98	23.40	43.52	-20.12
304.00	Quasi-Peak	H	-	-	-103.69	21.30	24.61	46.02	-21.41

Table 7-27. Radiated Spurious Emissions below 1GHz – Ant 1

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 125 of 132




Plot 7-175. Radiated Spurious Plot below 1GHz – Ant 2

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
53.70	Quasi-Peak	V	202	114	-99.64	14.38	21.74	40.00	-18.26
116.00	Quasi-Peak	V	-	-	-103.92	20.06	23.14	43.52	-20.39
190.00	Quasi-Peak	V	-	-	-103.20	18.73	22.53	43.52	-20.99
318.00	Quasi-Peak	V	-	-	-103.58	21.35	24.77	46.02	-21.25

Table 7-28. Radiated Spurious Emissions below 1GHz – Ant 2

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 126 of 132



Plot 7-176. Radiated Spurious Plot below 1GHz –Dual Ant

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
53.00	Quasi-Peak	H	-	-	-103.87	14.58	17.71	40.00	-22.29
133.00	Quasi-Peak	H	-	-	-103.84	20.35	23.51	43.52	-20.01
200.00	Quasi-Peak	H	-	-	-103.64	19.98	23.34	43.52	-20.18
292.00	Quasi-Peak	H	-	-	-103.61	21.03	24.42	46.02	-21.60

Table 7-29. Radiated Spurious Emissions below 1GHz – Dual Ant

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 127 of 132

7.10 Line-Conducted Test Data

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-30. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 128 of 132

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-9. Test Instrument & Measurement Setup


Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen (8.8).
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 129 of 132




Plot 7-177. Line Conducted Plot with Bluetooth LE (L1)




Plot 7-178. Line Conducted Plot with Bluetooth LE (N)

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 130 of 132



Plot 7-179. Line Conducted Plot with Bluetooth LE (L1) - WCP



Plot 7-180. Line Conducted Plot with Bluetooth LE (N) - WCP

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 131 of 132

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMS938B** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules.

FCC ID: A3LSMS938B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2408260069-12.A3L	Test Dates: 09/03/2024 - 10/25/2024	EUT Type: Portable Handset	Page 132 of 132