

APPENDIX H: LTE AND NR LOWER BANDWIDTH RF CONDUCTED POWERS

Note: Some bands do not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 1 of 155

H.1 LTE Lower Bandwidth RF Conducted Powers

H.1.1 LTE Band 12

Table H-1
LTE Band 12 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 12							
5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.86	24.04	24.14	0	0
	1	12	24.12	24.13	24.25		0
	1	24	23.97	23.89	24.16		0
	12	0	22.94	22.94	23.10	0-1	1
	12	6	22.95	23.00	23.10		1
	12	13	23.05	23.05	23.11		1
	25	0	22.93	22.94	23.07		1
16QAM	1	0	23.19	23.17	23.31	0-1	1
	1	12	23.19	23.31	23.40		1
	1	24	23.26	23.30	23.39		1
	12	0	22.06	21.99	22.08	0-2	2
	12	6	21.99	22.06	22.20		2
	12	13	22.02	22.06	22.13		2
	25	0	21.88	21.95	22.07		2
64QAM	1	0	22.14	22.22	22.38	0-2	2
	1	12	22.28	22.22	22.46		2
	1	24	22.05	22.08	22.35		2
	12	0	20.97	21.05	21.16	0-3	3
	12	6	21.04	21.01	21.17		3
	12	13	21.07	21.10	21.16		3
	25	0	21.00	20.92	21.05		3
256QAM	1	0	18.99	18.99	19.11	0-5	5
	1	12	19.25	19.19	19.29		5
	1	24	19.13	18.96	19.09		5
	12	0	19.02	19.05	19.01		5
	12	6	19.02	19.00	19.10		5
	12	13	19.05	19.04	19.17		5
	25	0	18.91	18.97	18.96		5

Table H-2
LTE Band 12 Ant A Measured P_{Max} for all DSI - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.73	23.89	24.18	0	0
	1	7	23.96	24.35	24.23		0
	1	14	23.85	23.91	24.06		0
	8	0	22.87	22.97	23.09	0-1	1
	8	4	22.90	23.05	23.25		1
	8	7	22.95	23.02	23.18		1
	15	0	22.91	22.90	23.07		1
16QAM	1	0	23.00	23.12	23.31	0-1	1
	1	7	23.34	23.31	23.57		1
	1	14	23.11	23.21	23.29		1
	8	0	21.96	22.00	22.15	0-2	2
	8	4	22.02	22.05	22.26		2
	8	7	22.04	22.05	22.29		2
	15	0	21.99	22.00	22.07		2
64QAM	1	0	21.96	22.10	22.26	0-2	2
	1	7	22.23	22.25	22.55		2
	1	14	22.04	22.05	22.35		2
	8	0	20.85	21.05	21.07	0-3	3
	8	4	21.00	21.15	21.28		3
	8	7	20.96	21.02	21.17		3
	15	0	20.95	20.88	21.13		3
256QAM	1	0	18.86	19.06	19.20	0-5	5
	1	7	19.20	19.20	19.30		5
	1	14	18.84	19.00	19.12		5
	8	0	18.96	18.85	19.08		5
	8	4	19.00	19.05	19.25		5
	8	7	18.90	19.02	19.15		5
	15	0	18.88	18.90	19.04		5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 2 of 155

Table H-3
LTE Band 12 Ant A Measured P_{Max} for all DSI - 1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.74	24.06	24.08	0	0
	1	2	23.83	24.10	24.14		0
	1	5	23.87	23.99	24.05		0
	3	0	23.83	23.89	24.11		0
	3	2	23.79	23.94	24.24		0
	3	3	23.81	23.93	24.04		0
	6	0	22.78	22.84	22.98		0-1
16QAM	1	0	23.06	23.10	23.54	0-1	1
	1	2	23.29	23.16	23.44		1
	1	5	23.03	23.23	23.32		1
	3	0	22.89	23.40	23.19		1
	3	2	22.87	23.09	23.47		1
	3	3	22.96	23.06	23.29		1
	6	0	21.93	22.08	22.29		0-2
64QAM	1	0	21.85	22.45	22.23	0-2	2
	1	2	21.93	22.19	22.35		2
	1	5	22.07	22.16	22.57		2
	3	0	22.02	22.18	22.28		2
	3	2	21.98	22.14	22.31		2
	3	3	22.08	22.10	22.30		2
	6	0	21.02	21.11	21.19		0-3
256QAM	1	0	18.99	18.84	19.25	0-5	5
	1	2	18.72	19.12	19.22		5
	1	5	18.98	19.08	19.14		5
	3	0	18.92	19.04	19.16		5
	3	2	19.01	19.08	19.27		5
	3	3	18.92	19.13	19.21		5
	6	0	18.90	18.97	19.10		5

Table H-4
LTE Band 12 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.08	24.15	24.25	0	0
	1	12	24.22	24.25	24.34		0
	1	24	24.07	24.10	24.31		0
	12	0	23.02	23.07	23.16	0-1	1
	12	6	23.15	23.09	23.20		1
	12	13	23.06	23.09	23.25		1
	25	0	23.09	23.05	23.17		1
16QAM	1	0	23.38	23.38	23.63	0-1	1
	1	12	23.67	23.52	23.71		1
	1	24	23.37	23.48	23.58		1
	12	0	22.08	22.07	22.22	0-2	2
	12	6	22.22	22.10	22.26		2
	12	13	22.16	22.12	22.29		2
	25	0	22.14	22.06	22.17		2
64QAM	1	0	22.26	22.24	22.34	0-2	2
	1	12	22.52	22.29	22.47		2
	1	24	22.26	22.22	22.44		2
	12	0	21.07	21.09	21.20	0-3	3
	12	6	21.13	21.13	21.25		3
	12	13	21.09	21.13	21.31		3
	25	0	21.08	21.07	21.18		3
256QAM	1	0	19.22	19.17	19.16	0-5	5
	1	12	19.46	19.16	19.31		5
	1	24	19.14	19.19	19.36		5
	12	0	19.00	19.07	19.17		5
	12	6	19.13	19.10	19.25		5
	12	13	19.09	19.12	19.20		5
	25	0	19.07	19.03	19.13		5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 3 of 155

Table H-5
LTE Band 12 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.18	24.02	24.22	0	0
	1	7	24.28	24.22	24.35		0
	1	14	24.07	24.06	24.25		0
	8	0	23.07	23.11	23.18	0-1	1
	8	4	23.11	23.23	23.28		1
	8	7	23.06	23.18	23.24		1
	15	0	23.08	23.07	23.18		1
16QAM	1	0	23.34	23.39	23.37	0-1	1
	1	7	23.38	23.42	23.56		1
	1	14	23.21	23.40	23.41		1
	8	0	22.18	22.12	22.29	0-2	2
	8	4	22.17	22.23	22.32		2
	8	7	22.12	22.21	22.28		2
	15	0	22.13	22.09	22.24		2
64QAM	1	0	22.20	22.11	22.37	0-2	2
	1	7	22.33	22.39	22.56		2
	1	14	22.42	22.31	22.55		2
	8	0	21.16	21.12	21.26	0-3	3
	8	4	21.14	21.18	21.33		3
	8	7	21.13	21.20	21.30		3
	15	0	21.11	21.10	21.20		3
256QAM	1	0	19.04	19.02	19.27	0-5	5
	1	7	19.19	19.33	19.45		5
	1	14	19.07	19.05	19.37		5
	8	0	19.08	19.05	19.17		5
	8	4	19.09	19.23	19.29		5
	8	7	19.08	19.14	19.29		5
	15	0	19.06	19.06	19.16		5

Table H-6
LTE Band 12 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.05	24.19	24.24	0	0
	1	2	24.04	24.25	24.23		0
	1	5	24.00	24.27	24.19		0
	3	0	23.98	23.99	24.18		0
	3	2	23.93	24.07	24.19		0
	3	3	23.95	24.04	24.19		0
	6	0	23.01	23.11	23.19		0-1
16QAM	1	0	23.25	23.29	23.65	0-1	1
	1	2	23.32	23.37	23.61		1
	1	5	23.26	23.38	23.63		1
	3	0	23.26	23.32	23.38		1
	3	2	23.30	23.24	23.38		1
	3	3	23.22	23.22	23.31		1
	6	0	22.17	22.18	22.37		0-2
64QAM	1	0	22.26	22.25	22.44	0-2	2
	1	2	22.23	22.12	22.35		2
	1	5	22.39	22.02	22.53		2
	3	0	22.16	22.21	22.46		2
	3	2	22.25	22.22	22.37		2
	3	3	22.25	22.24	22.55		2
	6	0	21.07	21.12	21.25		0-3
256QAM	1	0	19.08	19.15	19.33	0-5	5
	1	2	19.09	19.21	19.24		5
	1	5	19.19	19.22	19.23		5
	3	0	19.18	19.12	19.37		5
	3	2	19.14	19.07	19.25		5
	3	3	19.11	19.19	19.30		5
	6	0	19.03	19.10	19.26		5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 4 of 155

Table H-7
LTE Band 12 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.36	21.31	21.46	0	0
	1	12	21.53	21.48	21.57		0
	1	24	21.27	21.27	21.48		0
	12	0	21.26	21.36	21.40	0-1	0
	12	6	21.39	21.36	21.44		0
	12	13	21.31	21.39	21.45		0
	25	0	21.30	21.32	21.42		0
16QAM	1	0	21.64	21.79	21.85	0-1	0
	1	12	21.67	21.80	21.85		0
	1	24	21.59	21.62	21.80		0
	12	0	21.36	21.39	21.43	0-2	0
	12	6	21.44	21.41	21.48		0
	12	13	21.37	21.45	21.50		0
	25	0	21.33	21.32	21.45		0
64QAM	1	0	21.55	21.58	21.61	0-2	0
	1	12	21.48	21.64	21.76		0
	1	24	21.46	21.46	21.59		0
	12	0	21.03	21.11	21.20	0-3	0.2
	12	6	21.16	21.17	21.20		0.2
	12	13	21.15	21.15	21.23		0.2
	25	0	21.10	21.06	21.16		0.2
256QAM	1	0	19.10	19.27	19.30	0-5	2.2
	1	12	19.27	19.30	19.38		2.2
	1	24	19.08	19.22	19.21		2.2
	12	0	19.01	19.10	19.19		2.2
	12	6	19.13	19.07	19.23		2.2
	12	13	19.08	19.14	19.23		2.2
	25	0	19.06	19.10	19.14		2.2

Table H-8
LTE Band 12 Ant E Measured P_{Limit} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.23	21.28	21.43	0	0
	1	7	21.40	21.39	21.59		0
	1	14	21.21	21.20	21.42		0
	8	0	21.31	21.30	21.45	0-1	0
	8	4	21.37	21.37	21.52		0
	8	7	21.33	21.38	21.50		0
	15	0	21.33	21.31	21.43		0
16QAM	1	0	21.45	21.56	21.61	0-1	0
	1	7	21.63	21.78	21.71		0
	1	14	21.53	21.47	21.72		0
	8	0	21.38	21.44	21.45	0-2	0
	8	4	21.46	21.45	21.61		0
	8	7	21.37	21.41	21.56		0
	15	0	21.39	21.32	21.48		0
64QAM	1	0	21.27	21.45	21.70	0-2	0
	1	7	21.69	21.81	21.78		0
	1	14	21.29	21.41	21.52		0
	8	0	21.11	21.08	21.19	0-3	0.2
	8	4	21.14	21.17	21.33		0.2
	8	7	21.06	21.12	21.25		0.2
	15	0	21.07	21.05	21.22		0.2
256QAM	1	0	19.04	19.05	19.10	0-5	2.2
	1	7	19.24	19.24	19.43		2.2
	1	14	19.14	19.18	19.35		2.2
	8	0	19.06	19.05	19.21		2.2
	8	4	19.10	19.19	19.26		2.2
	8	7	19.07	19.13	19.26		2.2
	15	0	19.00	19.02	19.17		2.2

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 5 of 155

Table H-9
LTE Band 12 Ant E Measured P_{Limit} for DSI = 1 (Head) - 1.4 MHz Bandwidth

LTE Band 12							
1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.21	21.12	21.22	0	0
	1	2	21.28	21.34	21.26		0
	1	5	21.21	21.30	21.26		0
	3	0	21.19	21.28	21.22		0
	3	2	21.22	21.31	21.16		0
	3	3	21.21	21.26	21.27		0
	6	0	21.21	21.30	21.24		0
16QAM	1	0	21.58	21.52	21.35	0-1	0
	1	2	21.52	21.69	21.36		0
	1	5	21.48	21.67	21.35		0
	3	0	21.47	21.42	21.23		0
	3	2	21.45	21.35	21.27		0
	3	3	21.40	21.50	21.23		0
	6	0	21.39	21.45	21.24		0
64QAM	1	0	21.67	21.55	21.33	0-2	0
	1	2	21.49	21.64	21.28		0
	1	5	21.48	21.60	21.23		0
	3	0	21.53	21.50	21.31		0
	3	2	21.39	21.58	21.18		0
	3	3	21.40	21.63	21.32		0
	6	0	21.12	21.08	21.26		0.2
256QAM	1	0	19.24	19.19	19.46	0-5	2.2
	1	2	19.09	19.22	19.41		2.2
	1	5	19.18	19.20	19.55		2.2
	3	0	19.14	19.13	19.31		2.2
	3	2	19.15	19.20	19.31		2.2
	3	3	19.19	19.14	19.32		2.2
	6	0	19.02	19.05	19.19		2.2

H.1.2 LTE Band 13

Table H-10
LTE Band 13 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.35	0	0
	1	12	24.30		0
	1	24	24.38		0
	12	0	23.26		1
	12	6	23.35		1
	12	13	23.28		1
	25	0	23.30		1
16QAM	1	0	23.64	0-1	1
	1	12	23.53		1
	1	24	23.65		1
	12	0	22.31	0-2	2
	12	6	22.39		2
	12	13	22.28		2
	25	0	22.30		2
64QAM	1	0	22.59	0-2	2
	1	12	22.66		2
	1	24	22.48		2
	12	0	21.32	0-3	3
	12	6	21.39		3
	12	13	21.33		3
	25	0	21.33		3
256QAM	1	0	19.39	0-5	5
	1	12	19.54		5
	1	24	19.26		5
	12	0	19.42		5
	12	6	19.41		5
	12	13	19.27		5
	25	0	19.30		5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 6 of 155

Table H-11
LTE Band 13 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.42	0	0
	1	12	24.50		0
	1	24	24.35		0
	12	0	23.37	0-1	1
	12	6	23.41		1
	12	13	23.38		1
	25	0	23.36		1
	25	0	23.36		1
16QAM	1	0	23.86	0-1	1
	1	12	23.87		1
	1	24	23.71		1
	12	0	22.44	0-2	2
	12	6	22.42		2
	12	13	22.45		2
	25	0	22.34		2
	25	0	22.34		2
64QAM	1	0	22.68	0-2	2
	1	12	22.71		2
	1	24	22.55		2
	12	0	21.39	0-3	3
	12	6	21.46		3
	12	13	21.39		3
	25	0	21.37		3
	25	0	21.37		3
256QAM	1	0	19.49	0-5	5
	1	12	19.62		5
	1	24	19.45		5
	12	0	19.40		5
	12	6	19.41		5
	12	13	19.38		5
	25	0	19.31		5
	25	0	19.31		5

Table H-12
LTE Band 13 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	21.77	0	0
	1	12	21.80		0
	1	24	21.79		0
	12	0	21.66	0-1	0
	12	6	21.67		0
	12	13	21.72		0
	25	0	21.58		0
	25	0	21.58		0
16QAM	1	0	22.02	0-1	0
	1	12	22.10		0
	1	24	22.00		0
	12	0	21.67	0-2	0
	12	6	21.74		0
	12	13	21.70		0
	25	0	21.67		0
	25	0	21.67		0
64QAM	1	0	22.00	0-2	0
	1	12	21.91		0
	1	24	22.05		0
	12	0	21.42	0-3	0.5
	12	6	21.45		0.5
	12	13	21.39		0.5
	25	0	21.37		0.5
	25	0	21.37		0.5
256QAM	1	0	19.54	0-5	2.5
	1	12	19.67		2.5
	1	24	19.50		2.5
	12	0	19.39		2.5
	12	6	19.41		2.5
	12	13	19.39		2.5
	25	0	19.36		2.5
	25	0	19.36		2.5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 7 of 155

H.1.3 LTE Band 26

Table H-13
LTE Band 26 Ant A Measured P_{Max} for all DSI - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.02	24.05	24.26	0	0
	1	25	24.20	24.18	24.26		0
	1	49	24.02	24.16	24.08		0
	25	0	23.01	23.10	23.12	0-1	1
	25	12	23.11	23.10	23.25		1
	25	25	23.14	23.18	23.14		1
	50	0	23.08	23.10	23.22		1
16QAM	1	0	22.93	23.42	23.23	0-1	1
	1	25	23.26	23.45	23.31		1
	1	49	23.26	23.22	23.13		1
	25	0	21.97	22.18	22.12	0-2	2
	25	12	22.24	22.15	22.23		2
	25	25	22.18	22.19	22.21		2
	50	0	22.14	22.18	22.18		2
64QAM	1	0	22.05	22.23	22.50	0-2	2
	1	25	21.93	22.28	22.28		2
	1	49	22.20	22.36	22.53		2
	25	0	21.09	21.12	21.15	0-3	3
	25	12	21.15	21.11	21.19		3
	25	25	21.11	21.18	21.13		3
	50	0	21.11	21.10	21.23		3
256QAM	1	0	19.06	19.22	19.20	0-5	5
	1	25	19.24	19.33	19.28		5
	1	49	19.18	19.45	19.05		5
	25	0	19.05	19.12	19.17		5
	25	12	19.12	19.05	19.17		5
	25	25	19.15	19.18	19.18		5
	50	0	19.15	19.12	19.18		5

Table H-14
LTE Band 26 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.07	24.19	24.10	0	0
	1	12	24.11	24.17	24.18		0
	1	24	24.10	24.10	24.00		0
	12	0	23.05	23.15	23.15	0-1	1
	12	6	23.16	23.20	23.20		1
	12	13	23.13	23.21	23.15		1
	25	0	23.07	23.06	23.17		1
16QAM	1	0	23.41	23.47	23.24	0-1	1
	1	12	23.46	23.56	23.69		1
	1	24	23.12	23.66	23.23		1
	12	0	22.09	22.13	22.15	0-2	2
	12	6	22.12	22.19	22.22		2
	12	13	22.13	22.20	22.21		2
	25	0	22.14	22.17	22.21		2
64QAM	1	0	22.24	22.30	22.34	0-2	2
	1	12	22.35	22.32	22.70		2
	1	24	22.10	22.39	22.42		2
	12	0	21.07	21.19	21.11	0-3	3
	12	6	21.11	21.25	21.21		3
	12	13	21.11	21.25	21.12		3
	25	0	21.15	21.14	21.19		3
256QAM	1	0	19.19	19.09	19.10	0-5	5
	1	12	19.02	19.36	19.29		5
	1	24	19.10	19.20	19.17		5
	12	0	19.06	19.11	19.09		5
	12	6	19.15	19.16	19.23		5
	12	13	19.10	19.21	19.19		5
	25	0	19.10	19.12	19.12		5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 8 of 155

Table H-15
LTE Band 26 Ant A Measured P_{Max} for all DSI - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.03	24.23	24.17	0	0
	1	7	23.96	24.11	24.05		0
	1	14	23.82	24.21	24.18		0
	8	0	23.10	23.10	23.12	0-1	1
	8	4	23.08	23.06	23.07		1
	8	7	23.13	23.17	23.12		1
	15	0	23.09	23.14	23.07		1
16QAM	1	0	23.40	23.37	23.43	0-1	1
	1	7	23.42	23.38	23.40		1
	1	14	23.16	23.48	23.34		1
	8	0	22.13	22.20	22.10	0-2	2
	8	4	22.18	22.15	22.21		2
	8	7	22.17	22.25	22.21		2
	15	0	22.05	22.09	22.43		2
64QAM	1	0	22.55	22.31	22.11	0-2	2
	1	7	22.24	22.54	22.42		2
	1	14	22.33	22.62	22.11		2
	8	0	21.07	21.11	21.14	0-3	3
	8	4	21.14	21.13	21.22		3
	8	7	21.12	21.30	21.09		3
	15	0	21.12	21.15	21.11		3
256QAM	1	0	19.11	19.14	19.25	0-5	5
	1	7	19.19	19.28	19.20		5
	1	14	19.16	19.26	19.13		5
	8	0	19.09	19.06	19.05		5
	8	4	19.11	19.09	19.07		5
	8	7	19.07	19.16	19.10		5
	15	0	19.14	19.14	19.06		5

Table H-16
LTE Band 26 Ant A Measured P_{Max} for all DSI - 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.25	24.16	24.03	0	0
	1	2	24.09	24.17	24.20		0
	1	5	23.99	24.20	23.85		0
	3	0	24.07	24.07	24.13		0
	3	2	24.01	24.09	24.11		0
	3	3	24.07	24.20	24.07		0
	6	0	22.58	22.63	22.58	0-1	1
16QAM	1	0	23.29	23.47	23.39	0-1	1
	1	2	23.38	23.44	23.40		1
	1	5	23.19	23.54	23.21		1
	3	0	23.21	23.24	23.30		1
	3	2	23.32	23.32	23.39		1
	3	3	23.16	23.46	23.07		1
	6	0	22.15	22.08	22.18	0-2	2
64QAM	1	0	22.21	22.29	22.19	0-2	2
	1	2	22.33	22.46	22.21		2
	1	5	22.16	22.11	22.50		2
	3	0	22.04	22.19	22.34		2
	3	2	22.21	22.34	22.21		2
	3	3	22.01	22.39	22.34		2
	6	0	21.12	21.15	21.10	0-3	3
256QAM	1	0	19.08	19.47	19.26	0-5	5
	1	2	19.11	19.37	19.31		5
	1	5	19.09	19.07	19.38		5
	3	0	19.11	19.16	19.07		5
	3	2	19.11	19.16	19.24		5
	3	3	19.19	19.22	19.08		5
	6	0	19.07	19.11	19.12	5	

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 9 of 155

Table H-17

LTE Band 26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.35	24.08	24.27	0	0
	1	25	24.22	24.13	24.14		0
	1	49	24.26	24.05	24.10		0
	25	0	23.16	23.14	23.16	0-1	1
	25	12	23.26	23.18	23.24		1
	25	25	23.22	23.21	23.25		1
	50	0	23.20	23.23	23.22		1
16QAM	1	0	23.38	23.54	23.46	0-1	1
	1	25	23.52	23.39	23.51		1
	1	49	23.34	23.40	23.38		1
	25	0	22.19	22.15	22.16	0-2	2
	25	12	22.32	22.16	22.32		2
	25	25	22.26	22.26	22.22		2
	50	0	22.23	22.21	22.24		2
64QAM	1	0	22.42	22.51	22.35	0-2	2
	1	25	22.54	22.33	22.41		2
	1	49	22.44	22.42	22.28		2
	25	0	21.22	21.19	21.18	0-3	3
	25	12	21.28	21.18	21.24		3
	25	25	21.23	21.21	21.21		3
	50	0	21.28	21.19	21.27		3
256QAM	1	0	19.15	19.28	19.22	0-5	5
	1	25	19.36	19.33	19.40		5
	1	49	19.20	19.27	19.25		5
	25	0	19.15	19.14	19.13		5
	25	12	19.22	19.13	19.22		5
	25	25	19.18	19.22	19.14		5
	50	0	19.21	19.15	19.20		5

Table H-18

LTE Band 26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.32	24.15	24.40	0	0
	1	12	24.32	24.15	24.23		0
	1	24	24.18	24.13	24.23		0
	12	0	23.24	23.12	23.12	0-1	1
	12	6	23.24	23.24	23.18		1
	12	13	23.18	23.13	23.19		1
	25	0	23.26	23.17	23.13		1
16QAM	1	0	23.57	23.45	23.56	0-1	1
	1	12	23.62	23.54	23.57		1
	1	24	23.60	23.37	23.61		1
	12	0	22.29	22.18	22.21	0-2	2
	12	6	22.30	22.26	22.19		2
	12	13	22.25	22.17	22.22		2
	25	0	22.23	22.23	22.14		2
64QAM	1	0	22.39	22.38	22.35	0-2	2
	1	12	22.47	22.53	22.47		2
	1	24	22.25	22.33	22.39		2
	12	0	21.27	21.18	21.16	0-3	3
	12	6	21.33	21.28	21.21		3
	12	13	21.20	21.21	21.24		3
	25	0	21.21	21.20	21.13		3
256QAM	1	0	19.24	19.18	19.27	0-5	5
	1	12	19.45	19.26	19.38		5
	1	24	19.21	19.23	19.07		5
	12	0	19.22	19.11	19.15		5
	12	6	19.27	19.21	19.15		5
	12	13	19.19	19.18	19.19		5
	25	0	19.22	19.19	19.11		5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 10 of 155

Table H-19

LTE Band 26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.28	24.13	24.21	0	0
	1	7	24.28	24.21	24.28		0
	1	14	24.23	24.22	24.18		0
	8	0	23.21	23.15	23.11	0-1	1
	8	4	23.20	23.21	23.07		1
	8	7	23.21	23.19	23.18		1
	15	0	23.23	23.19	23.11		1
16QAM	1	0	23.46	23.41	23.46	0-1	1
	1	7	23.61	23.55	23.51		1
	1	14	23.33	23.51	23.47		1
	8	0	22.27	22.20	22.19	0-2	2
	8	4	22.28	22.24	22.18		2
	8	7	22.23	22.22	22.26		2
	15	0	22.25	22.25	22.14		2
64QAM	1	0	22.49	22.37	22.24	0-2	2
	1	7	22.54	22.58	22.45		2
	1	14	22.32	22.31	22.24		2
	8	0	21.28	21.12	21.15	0-3	3
	8	4	21.29	21.21	21.19		3
	8	7	21.16	21.21	21.21		3
	15	0	21.28	21.21	21.10		3
256QAM	1	0	19.38	19.15	19.20	0-5	5
	1	7	19.29	19.25	19.38		5
	1	14	19.25	19.26	19.12		5
	8	0	19.20	19.07	19.12		5
	8	4	19.24	19.16	19.12		5
	8	7	19.16	19.16	19.15		5
	15	0	19.22	19.16	19.07		5

Table H-20

LTE Band 26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.35	24.29	24.23	0	0
	1	2	24.33	24.26	24.20		0
	1	5	24.29	24.32	24.13		0
	3	0	24.20	24.16	24.20		0
	3	2	24.25	24.18	24.17		0
	3	3	24.19	24.13	24.12		0
	6	0	23.16	23.13	23.09	0-1	1
16QAM	1	0	23.51	23.52	23.47	0-1	1
	1	2	23.46	23.62	23.40		1
	1	5	23.54	23.54	23.33		1
	3	0	23.50	23.36	23.37		1
	3	2	23.40	23.34	23.30		1
	3	3	23.36	23.38	23.33		1
	6	0	22.29	22.26	22.23	0-2	2
64QAM	1	0	22.47	22.36	22.36	0-2	2
	1	2	22.67	22.29	22.43		2
	1	5	22.40	22.54	22.24		2
	3	0	22.39	22.32	22.25		2
	3	2	22.34	22.29	22.33		2
	3	3	22.42	22.28	22.29		2
	6	0	21.19	21.19	21.20	0-3	3
256QAM	1	0	19.40	19.34	19.38	0-5	5
	1	2	19.44	19.45	19.24		5
	1	5	19.33	19.46	19.34		5
	3	0	19.22	19.27	19.27		5
	3	2	19.21	19.28	19.22		5
	3	3	19.22	19.23	19.21		5
	6	0	19.21	19.14	19.11	5	

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 11 of 155

Table H-21
LTE Band 26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.97	21.01	20.99	0	0
	1	25	20.90	20.98	20.98		0
	1	49	20.80	20.96	20.99		0
	25	0	20.92	20.97	20.98	0-1	0
	25	12	20.99	20.99	21.01		0
	25	25	20.92	20.98	21.02		0
	50	0	20.95	20.98	21.02		0
16QAM	1	0	21.20	20.98	20.99	0-1	0
	1	25	21.17	21.00	20.96		0
	1	49	21.00	21.00	20.99		0
	25	0	20.96	20.96	20.98	0-2	0
	25	12	21.03	20.99	21.06		0
	25	25	20.97	20.99	21.01		0
	50	0	20.99	20.97	20.99		0
64QAM	1	0	21.15	20.99	21.02	0-2	0
	1	25	21.11	20.96	20.98		0
	1	49	21.12	20.99	21.00		0
	25	0	20.94	20.97	20.98	0-3	0
	25	12	21.05	20.97	21.04		0
	25	25	21.00	20.98	20.99		0
	50	0	20.97	21.01	21.01		0
256QAM	1	0	19.21	19.26	19.29	0-5	2
	1	25	19.35	19.25	19.19		2
	1	49	19.24	19.34	19.31		2
	25	0	19.15	19.12	19.13		2
	25	12	19.24	19.11	19.23		2
	25	25	19.23	19.18	19.18		2
	50	0	19.21	19.20	19.19		2

Table H-22
LTE Band 26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.02	20.98	20.89	0	0
	1	12	21.03	21.02	20.93		0
	1	24	20.89	20.98	20.92		0
	12	0	20.98	20.98	20.90	0-1	0
	12	6	20.98	21.02	20.90		0
	12	13	20.92	21.01	20.90		0
	25	0	20.92	21.01	20.87		0
16QAM	1	0	21.23	20.99	20.90	0-1	0
	1	12	21.25	21.02	20.91		0
	1	24	21.34	21.00	20.94		0
	12	0	21.00	20.99	20.90	0-2	0
	12	6	20.97	20.98	20.90		0
	12	13	21.00	21.00	20.85		0
	25	0	20.94	20.98	20.91		0
64QAM	1	0	21.14	20.98	20.86	0-2	0
	1	12	21.23	21.02	20.93		0
	1	24	21.10	21.04	20.91		0
	12	0	21.08	21.02	20.91	0-3	0
	12	6	21.08	21.02	20.89		0
	12	13	20.96	21.01	20.92		0
	25	0	21.01	21.03	20.93		0
256QAM	1	0	19.32	19.39	19.22	0-5	2
	1	12	19.28	19.33	19.35		2
	1	24	19.28	19.26	19.14		2
	12	0	19.24	19.14	19.14		2
	12	6	19.27	19.26	19.14		2
	12	13	19.20	19.17	19.15		2
	25	0	19.20	19.18	19.13		2

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 12 of 155

Table H-23
LTE Band 26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.97	20.99	20.90	0	0
	1	7	21.02	20.97	20.88		0
	1	14	20.93	21.02	20.91		0
	8	0	21.00	20.96	20.90	0-1	0
	8	4	20.98	20.98	20.90		0
	8	7	20.96	20.97	20.92		0
	15	0	20.99	20.95	20.89		0
16QAM	1	0	21.28	20.98	20.95	0-1	0
	1	7	21.39	20.98	20.93		0
	1	14	21.12	20.98	20.86		0
	8	0	21.07	20.99	20.92	0-2	0
	8	4	21.06	20.98	20.94		0
	8	7	21.01	20.96	20.88		0
	15	0	21.09	20.95	20.90		0
64QAM	1	0	21.16	20.96	20.87	0-2	0
	1	7	21.36	20.99	20.91		0
	1	14	21.17	21.01	20.90		0
	8	0	21.01	20.96	20.93	0-3	0
	8	4	21.04	21.00	20.89		0
	8	7	21.05	20.98	20.96		0
	15	0	21.03	21.02	20.93		0
256QAM	1	0	19.34	19.26	19.14	0-5	2
	1	7	19.42	19.28	19.25		2
	1	14	19.30	19.21	19.19		2
	8	0	19.28	19.13	19.06		2
	8	4	19.22	19.19	19.10		2
	8	7	19.22	19.16	19.17		2
	15	0	19.23	19.21	19.10		2

Table H-24
LTE Band 26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.97	20.99	20.98	0	0
	1	2	20.98	20.89	21.04		0
	1	5	20.93	20.90	20.93		0
	3	0	20.90	20.97	20.97		0
	3	2	20.92	20.95	20.96		0
	3	3	20.91	20.93	21.06		0
	6	0	20.89	21.00	20.99	0-1	0
16QAM	1	0	21.15	20.96	21.07	0-1	0
	1	2	21.20	20.93	21.01		0
	1	5	21.19	20.99	21.00		0
	3	0	21.06	20.89	21.00		0
	3	2	21.03	20.96	21.02		0
	3	3	21.19	20.97	21.04		0
	6	0	21.03	20.91	21.02	0-2	0
64QAM	1	0	21.16	20.96	20.96	0-2	0
	1	2	21.17	20.97	21.01		0
	1	5	21.12	20.89	20.95		0
	3	0	21.11	20.97	20.99		0
	3	2	21.08	20.88	21.02		0
	3	3	21.06	20.91	20.98		0
	6	0	21.03	21.01	21.06	0-3	0
256QAM	1	0	19.47	19.28	19.42	0-5	2
	1	2	19.50	19.19	19.36		2
	1	5	19.31	19.23	19.30		2
	3	0	19.27	19.29	19.22		2
	3	2	19.26	19.19	19.18		2
	3	3	19.25	19.27	19.16		2
	6	0	19.20	19.12	19.15		2

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 13 of 155

H.1.4 LTE Band 66

Table H-25
LTE Band 66 Ant A Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.39	23.39	23.45	0	0
	1	36	23.47	23.36	23.43		0
	1	74	23.28	23.26	23.41		0
	36	0	22.26	22.33	22.31	0-1	1
	36	18	22.36	22.34	22.31		1
	36	37	22.33	22.38	22.35		1
	75	0	22.36	22.36	22.26		1
16QAM	1	0	22.62	22.57	22.48	0-1	1
	1	36	22.61	22.51	22.56		1
	1	74	22.47	22.48	22.51		1
	36	0	21.31	21.36	21.35	0-2	2
	36	18	21.39	21.32	21.34		2
	36	37	21.35	21.40	21.36		2
	75	0	21.38	21.34	21.30		2
64QAM	1	0	21.69	21.62	21.53	0-2	2
	1	36	21.50	21.60	21.55		2
	1	74	21.44	21.48	21.57		2
	36	0	20.24	20.36	20.31	0-3	3
	36	18	20.38	20.31	20.32		3
	36	37	20.32	20.32	20.35		3
	75	0	20.31	20.40	20.31		3
256QAM	1	0	18.36	18.48	18.46	0-5	5
	1	36	18.51	18.61	18.48		5
	1	74	18.31	18.40	18.38		5
	36	0	18.24	18.30	18.29		5
	36	18	18.33	18.30	18.27		5
	36	37	18.30	18.32	18.36		5
	75	0	18.32	18.36	18.29		5

Table H-26
LTE Band 66 Ant A Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.40	23.58	23.30	0	0
	1	25	23.45	23.63	23.35		0
	1	49	23.42	23.45	23.18		0
	25	0	22.31	22.38	22.36	0-1	1
	25	12	22.36	22.38	22.35		1
	25	25	22.38	22.41	22.43		1
	50	0	22.33	22.43	22.35		1
16QAM	1	0	22.53	22.64	22.57	0-1	1
	1	25	22.42	22.77	22.60		1
	1	49	22.51	22.59	22.38		1
	25	0	21.31	21.35	21.35	0-2	2
	25	12	21.39	21.37	21.40		2
	25	25	21.37	21.41	21.43		2
	50	0	21.40	21.42	21.33		2
64QAM	1	0	21.52	21.62	21.55	0-2	2
	1	25	21.64	21.63	21.66		2
	1	49	21.49	21.43	21.64		2
	25	0	20.23	20.35	20.34	0-3	3
	25	12	20.37	20.37	20.33		3
	25	25	20.33	20.38	20.44		3
	50	0	20.33	20.42	20.29		3
256QAM	1	0	18.31	18.46	18.36	0-5	5
	1	25	18.44	18.56	18.56		5
	1	49	18.42	18.32	18.39		5
	25	0	18.21	18.32	18.29		5
	25	12	18.34	18.32	18.34		5
	25	25	18.34	18.36	18.38		5
	50	0	18.30	18.37	18.31		5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 14 of 155

Table H-27
LTE Band 66 Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.35	23.49	23.45	0	0
	1	12	23.53	23.56	23.55		0
	1	24	23.36	23.48	23.45		0
	12	0	22.36	22.34	22.36	0-1	1
	12	6	22.43	22.39	22.41		1
	12	13	22.38	22.40	22.42		1
	25	0	22.37	22.43	22.36		1
16QAM	1	0	22.61	22.65	22.73	0-1	1
	1	12	22.94	22.80	22.95		1
	1	24	22.58	22.61	22.72		1
	12	0	21.35	21.37	21.37	0-2	2
	12	6	21.51	21.44	21.43		2
	12	13	21.37	21.39	21.47		2
	25	0	21.42	21.39	21.33		2
64QAM	1	0	21.50	21.48	21.55	0-2	2
	1	12	21.60	21.75	21.54		2
	1	24	21.50	21.39	21.60		2
	12	0	20.38	20.38	20.36	0-3	3
	12	6	20.38	20.40	20.41		3
	12	13	20.37	20.40	20.40		3
	25	0	20.32	20.44	20.33		3
256QAM	1	0	18.42	18.36	18.45	0-5	5
	1	12	18.54	18.48	18.56		5
	1	24	18.34	18.41	18.56		5
	12	0	18.34	18.34	18.37		5
	12	6	18.37	18.35	18.39		5
	12	13	18.33	18.37	18.38		5
	25	0	18.30	18.39	18.32		5

Table H-28
LTE Band 66 Ant A Measured P_{Max} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.35	23.33	23.42	0	0
	1	7	23.43	23.47	23.58		0
	1	14	23.36	23.32	23.40		0
	8	0	22.34	22.33	22.40	0-1	1
	8	4	22.40	22.42	22.38		1
	8	7	22.33	22.39	22.43		1
	15	0	22.36	22.40	22.36		1
16QAM	1	0	22.58	22.60	22.62	0-1	1
	1	7	22.66	22.89	22.77		1
	1	14	22.47	22.54	22.52		1
	8	0	21.46	21.46	21.41	0-2	2
	8	4	21.46	21.53	21.46		2
	8	7	21.43	21.46	21.51		2
	15	0	21.36	21.43	21.36		2
64QAM	1	0	21.51	21.40	21.48	0-2	2
	1	7	21.70	21.64	21.87		2
	1	14	21.43	21.52	21.70		2
	8	0	20.33	20.32	20.39	0-3	3
	8	4	20.38	20.47	20.44		3
	8	7	20.35	20.43	20.43		3
	15	0	20.37	20.44	20.38		3
256QAM	1	0	18.39	18.27	18.35	0-5	5
	1	7	18.45	18.54	18.66		5
	1	14	18.15	18.35	18.46		5
	8	0	18.34	18.32	18.34		5
	8	4	18.39	18.43	18.37		5
	8	7	18.26	18.41	18.41		5
	15	0	18.31	18.42	18.32		5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 15 of 155

Table H-29
LTE Band 66 Ant A Measured P_{Max} for DSI = 1 (Head) – 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.38	23.36	23.35	0	0
	1	2	23.38	23.31	23.29		0
	1	5	23.43	23.32	23.33		0
	3	0	23.30	23.37	23.37		0
	3	2	23.25	23.31	23.37		0
	3	3	23.33	23.26	23.39		0
	6	0	22.26	22.32	22.34		0-1
16QAM	1	0	22.43	22.47	22.78	0-1	1
	1	2	22.36	22.55	22.78		1
	1	5	22.51	22.50	22.68		1
	3	0	22.45	22.59	22.52		1
	3	2	22.54	22.53	22.58		1
	3	3	22.54	22.54	22.53		1
	6	0	21.36	21.44	21.42		0-2
64QAM	1	0	21.67	21.56	21.62	0-2	2
	1	2	21.46	21.46	21.57		2
	1	5	21.55	21.47	21.67		2
	3	0	21.53	21.53	21.49		2
	3	2	21.51	21.49	21.48		2
	3	3	21.38	21.44	21.56		2
	6	0	20.34	20.43	20.41		0-3
256QAM	1	0	18.29	18.59	18.52	0-5	5
	1	2	18.36	18.57	18.43		5
	1	5	18.52	18.57	18.46		5
	3	0	18.34	18.37	18.48		5
	3	2	18.39	18.35	18.46		5
	3	3	18.44	18.41	18.48		5
	6	0	18.24	18.32	18.35		5

Table H-30
LTE Band 66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.30	19.25	19.20	0	0
	1	36	19.24	19.14	19.39		0
	1	74	19.27	19.04	19.11		0
	36	0	19.26	19.10	19.07	0-1	0
	36	18	19.35	19.19	19.14		0
	36	37	19.29	19.18	19.16		0
	75	0	19.25	19.15	19.18		0
16QAM	1	0	19.58	19.35	19.31	0-1	0
	1	36	19.51	19.34	19.38		0
	1	74	19.27	19.39	19.35		0
	36	0	19.21	19.18	19.07	0-2	0
	36	18	19.26	19.22	19.21		0
	36	37	19.31	19.26	19.18		0
	75	0	19.30	19.19	19.23		0
64QAM	1	0	19.20	19.38	19.33	0-2	0
	1	36	19.47	19.44	19.28		0
	1	74	19.60	19.36	19.31		0
	36	0	19.23	19.17	19.09	0-3	0
	36	18	19.26	19.17	19.17		0
	36	37	19.21	19.10	19.17		0
	75	0	19.33	19.22	19.18		0
256QAM	1	0	18.31	18.44	18.35	0-5	0.5
	1	36	18.59	18.38	18.39		0.5
	1	74	18.41	18.24	18.31		0.5
	36	0	18.30	18.29	18.21		0.5
	36	18	18.45	18.30	18.19		0.5
	36	37	18.44	18.16	18.30		0.5
	75	0	18.37	18.31	18.29		0.5

Table H-31

LTE Band 66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.23	19.16	19.14	0	0
	1	25	19.14	19.17	19.06		0
	1	49	19.29	19.08	19.03		0
	25	0	19.29	19.17	19.18	0-1	0
	25	12	19.31	19.21	19.22		0
	25	25	19.37	19.12	19.19		0
	50	0	19.30	19.17	19.22		0
16QAM	1	0	19.52	19.33	19.18	0-1	0
	1	25	19.50	19.48	19.35		0
	1	49	19.58	19.42	19.35		0
	25	0	19.25	19.13	19.23	0-2	0
	25	12	19.43	19.26	19.29		0
	25	25	19.35	19.30	19.26		0
	50	0	19.35	19.25	19.26		0
64QAM	1	0	19.22	19.14	19.18	0-2	0
	1	25	19.57	19.25	19.35		0
	1	49	19.34	19.09	19.41		0
	25	0	19.17	19.14	19.16	0-3	0
	25	12	19.32	19.26	19.24		0
	25	25	19.36	19.21	19.28		0
	50	0	19.35	19.23	19.20		0
256QAM	1	0	18.34	18.20	18.23	0-5	0.5
	1	25	18.49	18.38	18.43		0.5
	1	49	18.28	18.28	18.47		0.5
	25	0	18.32	18.33	18.18		0.5
	25	12	18.51	18.43	18.35		0.5
	25	25	18.42	18.28	18.31		0.5
	50	0	18.41	18.36	18.26	0.5	

Table H-32

LTE Band 66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.18	19.11	19.12	0	0
	1	12	19.32	19.18	19.14		0
	1	24	19.21	19.07	19.12		0
	12	0	19.35	19.15	19.14	0-1	0
	12	6	19.45	19.28	19.16		0
	12	13	19.34	19.25	19.20		0
16QAM	25	0	19.30	19.25	19.10	0-1	0
	1	0	19.42	19.34	19.23		0
	1	12	19.54	19.48	19.51		0
	1	24	19.45	19.16	19.35	0-2	0
	12	0	19.43	19.24	19.19		0
	12	6	19.41	19.32	19.21		0
64QAM	12	13	19.41	19.29	19.18	0-2	0
	25	0	19.34	19.25	19.16		0
	1	0	19.28	19.44	19.08		0
	1	12	19.57	19.31	19.39	0-2	0
	1	24	19.33	19.24	19.25		0
	12	0	19.29	19.16	19.17	0-3	0
12	6	19.41	19.30	19.19	0		
12	13	19.32	19.21	19.20	0		
256QAM	25	0	19.34	19.24	19.12	0-5	0
	1	0	18.36	18.27	18.23		0.5
	1	12	18.54	18.42	18.33		0.5
	1	24	18.41	18.22	18.39		0.5
	12	0	18.53	18.22	18.15		0.5
	12	6	18.48	18.31	18.32		0.5
	12	13	18.36	18.28	18.36	0.5	
	25	0	18.44	18.29	18.26	0.5	

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 17 of 155

Table H-33

LTE Band 66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.15	19.06	19.03	0	0
	1	7	19.25	19.19	19.09		0
	1	14	19.35	19.02	19.10		0
	8	0	19.33	19.16	19.14	0-1	0
	8	4	19.58	19.24	19.23		0
	8	7	19.29	19.25	19.18		0
	15	0	19.36	19.24	19.17		0
16QAM	1	0	19.35	19.28	19.22	0-1	0
	1	7	19.73	19.49	19.42		0
	1	14	19.42	19.21	19.25		0
	8	0	19.46	19.20	19.17	0-2	0
	8	4	19.49	19.33	19.23		0
	8	7	19.41	19.24	19.24		0
	15	0	19.46	19.22	19.15		0
64QAM	1	0	19.25	19.20	19.13	0-2	0
	1	7	19.57	19.41	19.49		0
	1	14	19.30	19.23	19.34		0
	8	0	19.40	19.18	19.12	0-3	0
	8	4	19.38	19.21	19.17		0
	8	7	19.38	19.30	19.15		0
	15	0	19.36	19.27	19.10		0
256QAM	1	0	18.33	18.42	18.26	0-5	0.5
	1	7	18.52	18.49	18.39		0.5
	1	14	18.50	18.32	18.25		0.5
	8	0	18.44	18.23	18.33		0.5
	8	4	18.43	18.39	18.20		0.5
	8	7	18.48	18.38	18.31		0.5
	15	0	18.41	18.34	18.20		0.5

Table H-34

LTE Band 66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.25	19.39	19.16	0	0
	1	2	19.25	19.03	19.06		0
	1	5	19.34	19.11	19.23		0
	3	0	19.23	19.12	19.09		0
	3	2	19.20	18.99	19.00		0
	3	3	19.26	19.16	18.99		0
	6	0	19.29	19.04	19.10	0-1	0
16QAM	1	0	19.44	19.61	19.31	0-1	0
	1	2	19.74	19.38	19.26		0
	1	5	19.61	19.45	19.09		0
	3	0	19.29	19.15	19.26		0
	3	2	19.37	19.51	19.07		0
	3	3	19.60	19.31	19.12		0
	6	0	19.45	19.06	19.26	0-2	0
64QAM	1	0	19.32	19.43	19.26	0-2	0
	1	2	19.33	19.32	19.20		0
	1	5	19.59	19.38	19.22		0
	3	0	19.38	19.24	19.26		0
	3	2	19.33	19.20	19.34		0
	3	3	19.60	19.26	19.11		0
	6	0	19.50	19.21	19.35	0-3	0
256QAM	1	0	18.51	18.37	18.30	0-5	0.5
	1	2	18.46	18.32	18.37		0.5
	1	5	18.42	18.58	18.29		0.5
	3	0	18.69	18.31	18.22		0.5
	3	2	18.54	18.24	18.24		0.5
	3	3	18.45	18.16	18.36		0.5
	6	0	18.40	18.25	18.06	0.5	

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 18 of 155

Table H-35

LTE Band 66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.97	20.78	20.74	0	0
	1	36	21.05	20.77	21.01		0
	1	74	20.75	20.73	20.76		0
	36	0	20.73	20.82	20.82	0-1	0
	36	18	20.80	20.78	20.80		0
	36	37	20.80	20.83	20.86		0
	75	0	20.79	20.83	20.80		0
16QAM	1	0	21.00	20.90	20.90	0-1	0
	1	36	21.00	20.92	20.99		0
	1	74	20.85	20.83	21.00		0
	36	0	20.74	20.74	20.82	0-2	0
	36	18	20.78	20.77	20.80		0
	36	37	20.78	20.82	20.87		0
	75	0	20.78	20.85	20.80		0
64QAM	1	0	21.07	20.82	20.89	0-2	0
	1	36	21.07	20.83	20.71		0
	1	74	21.08	20.81	20.81		0
	36	0	20.42	20.52	20.50	0-3	0.5
	36	18	20.51	20.52	20.46		0.5
	36	37	20.43	20.55	20.51		0.5
	75	0	20.49	20.52	20.49		0.5
256QAM	1	0	18.54	18.66	18.68	0-5	2.5
	1	36	18.61	18.61	18.60		2.5
	1	74	18.52	18.60	18.67		2.5
	36	0	18.40	18.50	18.52		2.5
	36	18	18.47	18.47	18.51		2.5
	36	37	18.45	18.51	18.57		2.5
	75	0	18.49	18.51	18.50		2.5

Table H-36

LTE Band 66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.81	21.02	20.79	0	0
	1	25	20.76	20.92	20.81		0
	1	49	20.73	20.87	20.75		0
	25	0	20.81	20.83	20.84	0-1	0
	25	12	20.86	20.89	20.89		0
	25	25	20.80	20.87	20.87		0
	50	0	20.79	20.88	20.85		0
16QAM	1	0	20.92	21.07	21.04	0-1	0
	1	25	21.00	21.18	21.04		0
	1	49	20.82	21.11	20.98		0
	25	0	20.79	20.81	20.86	0-2	0
	25	12	20.82	20.87	20.87		0
	25	25	20.78	20.87	20.96		0
	50	0	20.84	20.86	20.82		0
64QAM	1	0	20.99	20.85	20.86	0-2	0
	1	25	21.06	20.84	20.82		0
	1	49	20.92	20.83	20.85		0
	25	0	20.55	20.34	20.35	0-3	0.5
	25	12	20.53	20.36	20.34		0.5
	25	25	20.53	20.35	20.36		0.5
	50	0	20.51	20.22	20.32		0.5
256QAM	1	0	18.59	18.54	18.68	0-5	2.5
	1	25	18.61	18.67	18.64		2.5
	1	49	18.61	18.55	18.74		2.5
	25	0	18.52	18.49	18.34		2.5
	25	12	18.51	18.62	18.54		2.5
	25	25	18.45	18.53	18.59		2.5
	50	0	18.49	18.51	18.53		2.5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 19 of 155

Table H-37

LTE Band 66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.80	20.87	20.93	0	0
	1	12	20.78	20.91	21.00		0
	1	24	20.71	20.87	20.99		0
	12	0	20.82	20.79	20.86	0-1	0
	12	6	20.89	20.92	20.92		0
	12	13	20.83	20.82	20.95		0
	25	0	20.84	20.84	20.86		0
16QAM	1	0	21.04	20.99	21.20	0-1	0
	1	12	21.03	21.07	21.23		0
	1	24	21.02	21.01	21.16		0
	12	0	20.87	20.76	20.92	0-2	0
	12	6	20.85	20.90	20.96		0
	12	13	20.82	20.87	20.96		0
	25	0	20.81	20.81	20.85		0
64QAM	1	0	20.89	20.87	20.67	0-2	0
	1	12	21.05	20.81	20.87		0
	1	24	20.88	20.86	20.65		0
	12	0	20.51	20.33	20.36	0-3	0.5
	12	6	20.56	20.57	20.57		0.5
	12	13	20.56	20.54	20.56		0.5
	25	0	20.49	20.56	20.59		0.5
256QAM	1	0	18.65	18.61	18.57	0-5	2.5
	1	12	18.67	18.69	18.50		2.5
	1	24	18.66	18.71	18.60		2.5
	12	0	18.53	18.48	18.45		2.5
	12	6	18.59	18.60	18.59		2.5
	12	13	18.51	18.54	18.61		2.5
	25	0	18.49	18.54	18.55		2.5

Table H-38

LTE Band 66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.71	20.81	20.76	0	0
	1	7	20.86	21.00	20.99		0
	1	14	20.73	20.83	20.77		0
	8	0	20.83	20.88	20.88	0-1	0
	8	4	20.86	20.87	20.95		0
	8	7	20.81	20.89	20.97		0
	15	0	20.82	20.89	20.87		0
16QAM	1	0	20.89	21.05	20.97	0-1	0
	1	7	20.99	21.24	21.17		0
	1	14	20.84	21.07	20.97		0
	8	0	20.91	20.93	20.91	0-2	0
	8	4	20.90	20.97	21.06		0
	8	7	20.93	20.95	21.00		0
	15	0	20.84	20.89	20.86		0
64QAM	1	0	20.89	20.88	20.87	0-2	0
	1	7	21.17	20.86	20.85		0
	1	14	20.92	20.55	20.60		0
	8	0	20.54	20.35	20.30	0-3	0.5
	8	4	20.59	20.36	20.33		0.5
	8	7	20.53	20.37	20.59		0.5
	15	0	20.55	20.40	20.36		0.5
256QAM	1	0	18.55	18.42	18.59	0-5	2.5
	1	7	18.55	18.49	18.45		2.5
	1	14	18.52	18.47	18.58		2.5
	8	0	18.56	18.46	18.53		2.5
	8	4	18.54	18.52	18.58		2.5
	8	7	18.54	18.49	18.53		2.5
	15	0	18.48	18.53	18.52		2.5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 20 of 155

Table H-39

LTE Band 66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.68	20.84	20.93	0	0
	1	2	20.70	20.86	20.89		0
	1	5	20.69	20.83	20.93		0
	3	0	20.71	20.79	20.85		0
	3	2	20.66	20.80	20.82		0
	3	3	20.68	20.78	20.82		0
	6	0	20.73	20.80	20.93		0
16QAM	1	0	20.98	21.07	20.97	0-1	0
	1	2	20.92	21.08	20.96		0
	1	5	20.89	21.10	21.01		0
	3	0	20.89	21.03	21.15		0
	3	2	20.90	20.95	21.07		0
	3	3	20.93	20.92	21.10		0
	6	0	20.80	20.94	20.98		0
64QAM	1	0	21.06	20.95	20.75	0-2	0
	1	2	20.92	20.93	20.77		0
	1	5	21.00	20.53	20.63		0
	3	0	20.98	20.57	20.60		0
	3	2	20.86	20.62	20.58		0
	3	3	20.99	20.58	20.60		0
	6	0	20.23	20.22	20.25		0.5
256QAM	1	0	18.62	18.21	18.32	0-3	2.5
	1	2	18.47	18.50	18.49		2.5
	1	5	18.59	18.51	18.48		2.5
	3	0	18.62	18.46	18.43		2.5
	3	2	18.49	18.47	18.45		2.5
	3	3	18.53	18.53	18.40		2.5
	6	0	18.52	18.43	18.47		2.5

Table H-40

LTE Band 66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.24	18.31	18.25	0	0
	1	36	18.25	18.33	18.24		0
	1	74	18.15	18.28	18.23		0
	36	0	18.13	18.28	18.26		0
	36	18	18.26	18.33	18.23		0
	36	37	18.23	18.30	18.23		0
	75	0	18.22	18.30	18.26		0
16QAM	1	0	18.45	18.33	18.27	0-1	0
	1	36	18.51	18.31	18.24		0
	1	74	18.42	18.29	18.23		0
	36	0	18.18	18.29	18.29		0
	36	18	18.23	18.31	18.26		0
	36	37	18.25	18.30	18.23		0
	75	0	18.24	18.31	18.27		0
64QAM	1	0	18.29	18.16	18.10	0-2	0
	1	36	18.35	18.16	18.10		0
	1	74	18.25	18.13	18.11		0
	36	0	18.03	18.15	18.13		0
	36	18	18.11	18.14	18.09		0
	36	37	18.08	18.18	18.15		0
	75	0	18.10	18.16	18.14		0
256QAM	1	0	18.19	18.30	18.23	0-5	0
	1	36	18.23	18.26	18.38		0
	1	74	18.14	18.20	18.33		0
	36	0	18.03	18.11	18.12		0
	36	18	18.11	18.15	18.17		0
	36	37	18.08	18.18	18.20		0
	75	0	18.11	18.18	18.16		0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 21 of 155

Table H-41
LTE Band 66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.20	18.26	18.32	0	0
	1	25	18.17	18.32	18.31		0
	1	49	18.16	18.29	18.30		0
	25	0	18.22	18.31	18.30	0-1	0
	25	12	18.27	18.33	18.31		0
	25	25	18.22	18.31	18.32		0
	50	0	18.20	18.33	18.29		0
16QAM	1	0	18.41	18.30	18.27	0-1	0
	1	25	18.40	18.28	18.31		0
	1	49	18.33	18.30	18.30		0
	25	0	18.27	18.30	18.31	0-2	0
	25	12	18.33	18.29	18.29		0
	25	25	18.27	18.33	18.30		0
	50	0	18.25	18.31	18.29		0
64QAM	1	0	18.20	18.13	18.16	0-2	0
	1	25	18.31	18.14	18.11		0
	1	49	18.05	18.16	18.13		0
	25	0	18.06	18.15	18.15	0-3	0
	25	12	18.14	18.12	18.09		0
	25	25	18.03	18.10	18.15		0
	50	0	18.05	18.10	18.12		0
256QAM	1	0	18.10	18.06	18.17	0-5	0
	1	25	18.27	18.30	18.38		0
	1	49	18.07	18.21	18.25		0
	25	0	18.10	18.11	18.15		0
	25	12	18.12	18.21	18.24		0
	25	25	18.07	18.17	18.20		0
	50	0	18.11	18.15	18.15		0

Table H-42
LTE Band 66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.16	18.34	18.29	0	0
	1	12	18.21	18.32	18.32		0
	1	24	18.12	18.28	18.32		0
	12	0	18.23	18.28	18.30	0-1	0
	12	6	18.31	18.32	18.32		0
	12	13	18.25	18.31	18.31		0
	25	0	18.26	18.34	18.29		0
16QAM	1	0	18.56	18.33	18.28	0-1	0
	1	12	18.60	18.33	18.27		0
	1	24	18.62	18.34	18.29		0
	12	0	18.30	18.35	18.27	0-2	0
	12	6	18.33	18.32	18.31		0
	12	13	18.26	18.28	18.27		0
	25	0	18.29	18.34	18.29		0
64QAM	1	0	18.19	18.14	18.18	0-2	0
	1	12	18.35	18.13	18.18		0
	1	24	18.19	18.10	18.22		0
	12	0	18.08	18.10	18.17	0-3	0
	12	6	18.14	18.13	18.16		0
	12	13	18.04	18.07	18.15		0
	25	0	18.06	18.11	18.17		0
256QAM	1	0	18.19	18.18	18.19	0-5	0
	1	12	18.16	18.22	18.42		0
	1	24	18.17	18.28	18.22		0
	12	0	18.11	18.12	18.23		0
	12	6	18.17	18.27	18.22		0
	12	13	18.07	18.13	18.26		0
	25	0	18.09	18.15	18.18		0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 22 of 155

Table H-43
LTE Band 66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.23	18.32	18.33	0	0
	1	7	18.22	18.31	18.33		0
	1	14	18.14	18.30	18.37		0
	8	0	18.24	18.28	18.32	0-1	0
	8	4	18.29	18.28	18.34		0
	8	7	18.26	18.30	18.32		0
	15	0	18.22	18.31	18.34		0
16QAM	1	0	18.30	18.30	18.32	0-1	0
	1	7	18.47	18.30	18.31		0
	1	14	18.33	18.28	18.34		0
	8	0	18.34	18.30	18.33	0-2	0
	8	4	18.36	18.31	18.37		0
	8	7	18.28	18.30	18.35		0
	15	0	18.27	18.30	18.33		0
64QAM	1	0	18.07	18.13	18.21	0-2	0
	1	7	18.24	18.11	18.16		0
	1	14	18.15	18.14	18.19		0
	8	0	18.09	18.12	18.19	0-3	0
	8	4	18.06	18.11	18.19		0
	8	7	18.04	18.13	18.15		0
	15	0	18.03	18.09	18.18		0
256QAM	1	0	18.09	18.13	18.12	0-5	0
	1	7	18.30	18.29	18.33		0
	1	14	18.03	18.16	18.20		0
	8	0	18.11	18.13	18.18		0
	8	4	18.11	18.23	18.24		0
	8	7	18.05	18.19	18.28		0
	15	0	18.09	18.16	18.14		0

Table H-44
LTE Band 66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.20	18.36	18.34	0	0
	1	2	18.15	18.24	18.37		0
	1	5	18.14	18.36	18.34		0
	3	0	18.15	18.28	18.37		0
	3	2	18.09	18.32	18.36		0
	3	3	18.11	18.35	18.34		0
	6	0	18.17	18.36	18.37		0-1
16QAM	1	0	18.36	18.30	18.32	0-1	0
	1	2	18.40	18.24	18.42		0
	1	5	18.31	18.28	18.36		0
	3	0	18.38	18.32	18.36		0
	3	2	18.28	18.28	18.34		0
	3	3	18.31	18.31	18.38		0
	6	0	18.32	18.25	18.36		0-2
64QAM	1	0	18.24	18.09	18.25	0-2	0
	1	2	18.12	18.11	18.22		0
	1	5	18.11	18.00	18.21		0
	3	0	18.15	18.09	18.22		0
	3	2	18.14	18.11	18.21		0
	3	3	18.06	18.09	18.25		0
	6	0	18.01	18.05	18.20		0-3
256QAM	1	0	18.17	18.18	18.29	0-5	0
	1	2	18.13	17.97	18.32		0
	1	5	18.18	18.06	18.26		0
	3	0	18.12	18.05	18.23		0
	3	2	18.05	18.20	18.19		0
	3	3	17.97	18.17	18.20		0
	6	0	18.06	18.08	18.16		0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 23 of 155

H.1.5 LTE Band 25

Table H-45
LTE Band 25 Ant A Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.33	23.39	23.42	0	0
	1	36	23.37	23.52	23.46		0
	1	74	23.39	23.44	23.50		0
	36	0	22.15	22.26	22.24	0-1	1
	36	18	22.25	22.32	22.30		1
	36	37	22.22	22.36	22.31		1
	75	0	22.25	22.25	22.24		1
16QAM	1	0	22.34	22.44	22.42	0-1	1
	1	36	22.47	22.50	22.69		1
	1	74	22.35	22.47	22.50		1
	36	0	21.20	21.34	21.29	0-2	2
	36	18	21.24	21.35	21.30		2
	36	37	21.26	21.38	21.35		2
	75	0	21.26	21.29	21.27		2
64QAM	1	0	21.40	21.45	21.50	0-2	2
	1	36	21.45	21.55	21.49		2
	1	74	21.32	21.42	21.49		2
	36	0	20.12	20.29	20.25	0-3	3
	36	18	20.21	20.31	20.24		3
	36	37	20.16	20.31	20.26		3
	75	0	20.19	20.23	20.22		3
256QAM	1	0	18.26	18.37	18.23	0-5	5
	1	36	18.45	18.50	18.43		5
	1	74	18.31	18.34	18.38		5
	36	0	18.12	18.24	18.19		5
	36	18	18.20	18.27	18.26		5
	36	37	18.21	18.33	18.28		5
	75	0	18.20	18.24	18.19		5

Table H-46
LTE Band 25 Ant A Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.34	23.66	23.22	0	0
	1	25	23.39	23.59	23.27		0
	1	49	23.33	23.55	23.17		0
	25	0	22.25	22.32	22.36	0-1	1
	25	12	22.24	22.33	22.40		1
	25	25	22.27	22.37	22.36		1
16QAM	50	0	22.22	22.33	22.36	0-1	1
	1	0	22.44	22.67	22.44		1
	1	25	22.49	22.75	22.55		1
	1	49	22.40	22.64	22.34	0-2	1
	25	0	21.25	21.37	21.36		2
	25	12	21.32	21.40	21.43		2
64QAM	25	25	21.29	21.45	21.35	0-2	2
	50	0	21.27	21.34	21.32		2
	1	0	21.43	21.51	21.44		2
	1	25	21.38	21.56	21.52	0-2	2
	1	49	21.38	21.42	21.51		2
	25	0	20.19	20.27	20.26	0-3	3
25	12	20.26	20.30	20.33	3		
25	25	20.21	20.34	20.26	3		
50	0	20.22	20.23	20.28	3		
256QAM	1	0	18.31	18.40	18.41	0-5	5
	1	25	18.34	18.55	18.31		5
	1	49	18.31	18.31	18.29		5
	25	0	18.20	18.27	18.29		5
	25	12	18.20	18.29	18.30		5
	25	25	18.22	18.33	18.28		5
	50	0	18.20	18.26	18.26		5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 24 of 155

Table H-47
LTE Band 25 Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	23.18	23.49	23.47	0	0	
	1	12	23.29	23.62	23.60		0	
	1	24	23.24	23.56	23.60		0	
	12	0	22.29	22.30	22.28	0-1	1	
	12	6	22.33	22.35	22.40		1	
	12	13	22.28	22.43	22.40		1	
16QAM	25	0	22.28	22.32	22.29	0-1	1	
	1	0	22.49	22.71	22.73		0-2	1
	1	12	22.57	22.74	22.90			1
	1	24	22.52	22.74	22.94	0-2		1
	12	0	21.29	21.33	21.31		2	
	12	6	21.36	21.38	21.45		2	
64QAM	12	13	21.31	21.44	21.43	0-2	2	
	25	0	21.29	21.33	21.29		0-3	2
	1	0	21.32	21.56	21.48			2
	1	12	21.44	21.63	21.61	0-3		2
	1	24	21.40	21.55	21.50		0-3	2
	12	0	20.20	20.24	20.23			3
256QAM	12	6	20.28	20.35	20.38	0-3		3
	12	13	20.24	20.43	20.33		0-5	3
	25	0	20.19	20.28	20.22			3
	1	0	18.37	18.28	18.29	0-5		5
	1	12	18.40	18.55	18.48		5	
	1	24	18.28	18.33	18.43		5	
12	0	18.20	18.21	18.18	5			
12	6	18.30	18.32	18.30	5			
12	13	18.26	18.37	18.28	5			
256QAM	25	0	18.21	18.28	18.17	0-5	5	

Table H-48
LTE Band 25 Ant A Measured P_{Max} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	23.30	23.29	23.29	0	0	
	1	7	23.41	23.51	23.45		0	
	1	14	23.27	23.32	23.38		0	
	8	0	22.28	22.28	22.34	0-1	1	
	8	4	22.33	22.31	22.39		1	
	8	7	22.29	22.39	22.39		1	
16QAM	15	0	22.30	22.31	22.36	0-1	1	
	1	0	22.40	22.65	22.68		0-2	1
	1	7	22.54	22.82	22.62			1
	1	14	22.48	22.65	22.58	1		
	8	0	21.31	21.37	21.39	2		
	8	4	21.37	21.41	21.38	2		
64QAM	8	7	21.36	21.47	21.40	0-2	2	
	15	0	21.32	21.31	21.39		2	
	1	0	21.38	21.38	21.49		0-2	2
	1	7	21.65	21.59	21.73	2		
	1	14	21.36	21.43	21.57	0-3		2
	8	0	20.31	20.32	20.32		3	
256QAM	8	4	20.32	20.32	20.36		0-3	3
	8	7	20.28	20.37	20.33	3		
	15	0	20.28	20.30	20.29	0-5		3
	1	0	18.29	18.27	18.20		0-5	5
	1	7	18.33	18.52	18.51			5
	1	14	18.26	18.45	18.32	5		
256QAM	8	0	18.18	18.24	18.29	0-5	5	
	8	4	18.28	18.30	18.31		5	
	8	7	18.25	18.34	18.31		5	
	15	0	18.21	18.29	18.32		5	

Table H-49
LTE Band 25 Ant A Measured P_{Max} for DSI = 1 (Head) - 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.24	23.30	23.39	0	0
	1	2	23.23	23.30	23.49		0
	1	5	23.21	23.36	23.36		0
	3	0	23.17	23.25	23.32		0
	3	2	23.15	23.24	23.25		0
	3	3	23.15	23.28	23.42		0
	6	0	22.16	22.20	22.22	0-1	1
16QAM	1	0	22.40	22.50	22.76	0-1	1
	1	2	22.42	22.52	22.78		1
	1	5	22.27	22.41	22.75		1
	3	0	22.49	22.41	22.43		1
	3	2	22.39	22.47	22.38		1
	3	3	22.48	22.46	22.53		1
	6	0	21.29	21.33	21.38	0-2	2
64QAM	1	0	21.45	21.41	21.64	0-2	2
	1	2	21.38	21.52	21.67		2
	1	5	21.46	21.55	21.69		2
	3	0	21.30	21.45	21.37		2
	3	2	21.29	21.43	21.40		2
	3	3	21.33	21.39	21.47		2
	6	0	20.22	20.28	20.23	0-3	3
256QAM	1	0	18.48	18.42	18.27	0-5	5
	1	2	18.32	18.46	18.20		5
	1	5	18.30	18.49	18.41		5
	3	0	18.24	18.35	18.36		5
	3	2	18.27	18.37	18.31		5
	3	3	18.20	18.35	18.39		5
	6	0	18.19	18.21	18.21	5	

Table H-50
LTE Band 25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.18	18.14	18.28	0	0
	1	36	18.24	18.20	18.31		0
	1	74	18.18	18.14	18.21		0
	36	0	18.05	18.17	18.11	0-1	0
	36	18	18.12	18.19	18.17		0
	36	37	18.12	18.22	18.22		0
16QAM	75	0	18.09	18.18	18.12	0	
	1	0	18.24	18.37	18.32	0-1	0
	1	36	18.23	18.47	18.36		0
	1	74	18.16	18.41	18.25		0
	36	0	18.05	18.20	18.13	0-2	0
	36	18	18.15	18.23	18.20		0
64QAM	36	37	18.12	18.24	18.22		0
	75	0	18.12	18.19	18.16	0	
	1	0	18.33	18.20	18.14	0-2	0
	1	36	18.32	18.19	18.13		0
	1	74	18.18	18.21	18.13		0
	36	0	18.02	18.20	18.13	0-3	0
36	18	18.12	18.19	18.14	0		
36	37	18.07	18.21	18.14	0		
256QAM	75	0	18.09	18.19	18.14	0	
	1	0	18.15	18.28	18.17	0-5	0
	1	36	18.26	18.46	18.17		0
	1	74	18.18	18.31	18.23		0
	36	0	18.07	18.14	18.13		0
	36	18	18.11	18.21	18.12		0
36	37	18.10	18.23	18.14	0		
	75	0	18.09	18.15	18.12	0	

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 26 of 155

Table H-51

LTE Band 25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.08	18.41	18.11	0	0
	1	25	18.05	18.39	18.08		0
	1	49	18.04	18.27	18.13		0
	25	0	18.14	18.21	18.20	0-1	0
	25	12	18.16	18.24	18.21		0
	25	25	18.13	18.24	18.19		0
	50	0	18.12	18.17	18.22		0
16QAM	1	0	18.31	18.60	18.35	0-1	0
	1	25	18.36	18.67	18.53		0
	1	49	18.32	18.52	18.28		0
	25	0	18.16	18.21	18.25	0-2	0
	25	12	18.18	18.20	18.27		0
	25	25	18.17	18.28	18.20		0
	50	0	18.17	18.18	18.24		0
64QAM	1	0	18.46	18.20	18.21	0-2	0
	1	25	18.34	18.22	18.24		0
	1	49	18.31	18.22	18.20		0
	25	0	18.13	18.21	18.21	0-3	0
	25	12	18.16	18.20	18.23		0
	25	25	18.12	18.20	18.19		0
	50	0	18.09	18.21	18.19		0
256QAM	1	0	18.25	18.23	18.27	0-5	0
	1	25	18.30	18.42	18.43		0
	1	49	18.19	18.29	18.29		0
	25	0	18.14	18.17	18.20		0
	25	12	18.17	18.20	18.23		0
	25	25	18.11	18.24	18.16		0
	50	0	18.11	18.15	18.18		0

Table H-52

LTE Band 25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.05	18.23	18.17	0	0
	1	12	18.13	18.21	18.17		0
	1	24	18.02	18.22	18.18		0
	12	0	18.14	18.20	18.17	0-1	0
	12	6	18.21	18.21	18.15		0
	12	13	18.13	18.19	18.16		0
	25	0	18.15	18.22	18.15		0
16QAM	1	0	18.38	18.20	18.13	0-1	0
	1	12	18.47	18.24	18.16		0
	1	24	18.34	18.20	18.13		0
	12	0	18.18	18.20	18.17	0-2	0
	12	6	18.23	18.18	18.18		0
	12	13	18.19	18.21	18.17		0
	25	0	18.15	18.20	18.16		0
64QAM	1	0	18.26	18.19	18.15	0-2	0
	1	12	18.28	18.19	18.19		0
	1	24	18.26	18.20	18.18		0
	12	0	18.16	18.22	18.16	0-3	0
	12	6	18.21	18.23	18.20		0
	12	13	18.18	18.18	18.16		0
	25	0	18.11	18.19	18.19		0
256QAM	1	0	18.30	18.32	18.34	0-5	0
	1	12	18.38	18.50	18.47		0
	1	24	18.30	18.34	18.39		0
	12	0	18.13	18.19	18.13		0
	12	6	18.18	18.24	18.25		0
	12	13	18.19	18.30	18.24		0
	25	0	18.17	18.18	18.14		0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 27 of 155

Table H-53

LTE Band 25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	18.10	18.14	18.04	0	0	
	1	7	18.23	18.29	18.20		0	
	1	14	18.07	18.19	18.04		0	
	8	0	18.18	18.15	18.16	0-1	0	
	8	4	18.19	18.24	18.24		0	
	8	7	18.19	18.26	18.21		0	
16QAM	15	0	18.18	18.18	18.21	0	0	
	1	0	18.19	18.49	18.27		0-1	0
	1	7	18.34	18.73	18.39			0
	1	14	18.30	18.45	18.41	0-2		0
	8	0	18.24	18.29	18.25		0	
	8	4	18.31	18.31	18.30		0	
64QAM	8	7	18.21	18.37	18.28	0-2	0	
	15	0	18.23	18.19	18.20		0	
	1	0	18.29	18.23	18.24		0-2	0
	1	7	18.46	18.25	18.25	0		
	1	14	18.26	18.25	18.25	0-3		0
	8	0	18.18	18.23	18.26		0	
256QAM	8	4	18.23	18.21	18.26		0-3	0
	8	7	18.21	18.25	18.27	0		
	15	0	18.19	18.23	18.23	0		
	1	0	18.12	18.16	18.28	0-5	0	
	1	7	18.25	18.46	18.36		0	
	1	14	18.25	18.29	18.22		0	
8	0	18.22	18.19	18.26	0			
8	4	18.25	18.27	18.21	0			
256QAM	8	7	18.23	18.30	18.23	0		
	15	0	18.16	18.22	18.20	0		

Table H-54

LTE Band 25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.17	18.15	18.09	0	0
	1	2	18.08	18.17	17.98		0
	1	5	18.15	18.13	18.02		0
	3	0	18.06	18.13	18.13		0
	3	2	18.08	18.13	18.11		0
	3	3	18.09	18.18	18.14		0
	6	0	18.08	18.12	18.10	0-1	0
16QAM	1	0	18.21	18.39	18.51	0-1	0
	1	2	18.22	18.43	18.44		0
	1	5	18.23	18.53	18.50		0
	3	0	18.33	18.27	18.35		0
	3	2	18.28	18.28	18.34		0
	3	3	18.32	18.34	18.34		0
	6	0	18.25	18.28	18.26	0-2	0
64QAM	1	0	18.34	18.24	18.29	0-2	0
	1	2	18.30	18.21	18.24		0
	1	5	18.16	18.25	18.25		0
	3	0	18.29	18.26	18.20		0
	3	2	18.25	18.19	18.21		0
	3	3	18.20	18.22	18.22		0
	6	0	18.18	18.21	18.19	0-3	0
256QAM	1	0	18.26	18.17	18.25	0-5	0
	1	2	18.26	18.29	18.21		0
	1	5	18.34	18.33	18.22		0
	3	0	18.24	18.27	18.24		0
	3	2	18.24	18.31	18.17		0
	3	3	18.21	18.31	18.19		0
	6	0	18.08	18.16	18.12	0	

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 28 of 155

Table H-55

LTE Band 25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.73	19.91	19.95	0	0
	1	36	19.88	19.90	20.00		0
	1	74	19.76	19.89	19.96		0
	36	0	19.82	19.91	20.02	0-1	0
	36	18	19.87	19.89	20.01		0
	36	37	19.83	19.90	20.00		0
	75	0	19.81	19.89	20.02		0
16QAM	1	0	19.94	19.90	19.96	0-1	0
	1	36	19.99	19.91	19.98		0
	1	74	19.94	19.91	20.00		0
	36	0	19.88	19.89	20.00	0-2	0
	36	18	19.92	19.90	19.99		0
	36	37	19.87	19.89	20.01		0
	75	0	19.84	19.92	20.00		0
64QAM	1	0	20.06	19.89	20.00	0-2	0
	1	36	20.05	19.88	20.01		0
	1	74	20.09	19.90	19.98		0
	36	0	19.85	19.90	19.99	0-3	0
	36	18	19.90	19.91	20.02		0
	36	37	19.83	19.88	20.00		0
	75	0	19.84	19.92	19.99		0
256QAM	1	0	18.07	18.17	18.20	0-5	2
	1	36	18.31	18.36	18.25		2
	1	74	18.21	18.35	18.28		2
	36	0	18.10	18.11	18.17		2
	36	18	18.08	18.19	18.25		2
	36	37	18.08	18.23	18.18		2
	75	0	18.05	18.15	18.23		2

Table H-56

LTE Band 25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.89	19.92	20.00	0	0
	1	25	19.82	19.91	19.97		0
	1	49	19.85	19.92	19.97		0
	25	0	19.82	19.93	19.95	0-1	0
	25	12	19.90	19.92	19.94		0
	25	25	19.84	19.93	19.96		0
	50	0	19.85	19.92	19.99		0
16QAM	1	0	20.08	19.92	19.97	0-1	0
	1	25	20.03	19.92	19.98		0
	1	49	20.05	19.92	19.97		0
	25	0	19.92	19.91	20.00	0-2	0
	25	12	19.94	19.92	19.98		0
	25	25	19.89	19.94	20.01		0
	50	0	19.86	19.89	19.97		0
64QAM	1	0	20.12	19.91	20.00	0-2	0
	1	25	20.23	19.92	19.98		0
	1	49	20.08	19.93	19.99		0
	25	0	19.87	19.91	19.95	0-3	0
	25	12	19.92	19.90	20.00		0
	25	25	19.90	19.93	19.98		0
	50	0	19.88	19.93	20.02		0
256QAM	1	0	18.17	18.38	18.40	0-5	2
	1	25	18.29	18.34	18.43		2
	1	49	18.15	18.27	18.29		2
	25	0	18.13	18.10	18.21		2
	25	12	18.12	18.16	18.23		2
	25	25	18.14	18.22	18.22		2
	50	0	18.08	18.15	18.23		2

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 29 of 155

Table H-57

LTE Band 25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	19.71	19.95	19.98	0	0	
	1	12	19.83	19.94	20.01		0	
	1	24	19.76	19.95	19.98		0	
	12	0	19.82	19.92	20.00	0-1	0	
	12	6	19.88	19.92	19.99		0	
	12	13	19.88	19.95	20.00		0	
16QAM	25	0	19.86	19.97	20.03	0-1	0	
	1	0	19.98	19.96	20.01		0	
	1	12	20.15	19.91	20.02		0	
	1	24	20.10	19.95	20.02	0-2	0	
	12	0	19.87	19.90	20.03		0	
	12	6	19.99	19.93	20.03		0	
64QAM	12	13	19.95	19.93	20.01	0-2	0	
	25	0	19.91	19.96	20.02		0	
	1	0	19.91	19.92	20.04	0-2	0	
	1	12	20.02	19.92	20.02		0	
	1	24	19.88	19.93	19.99		0	
	12	0	19.85	19.92	20.01	0-3	0	
12	6	19.94	19.91	20.00	0			
12	13	19.90	19.92	20.04	0			
256QAM	25	0	19.87	19.93	20.01	0-3	0	
	1	0	18.34	18.23	18.29		0-5	2
	1	12	18.43	18.35	18.44			2
	1	24	18.20	18.39	18.39	2		
	12	0	18.08	18.15	18.21	2		
	12	6	18.16	18.21	18.30	2		
	12	13	18.11	18.21	18.27	2		
	25	0	18.06	18.13	18.23	2		

Table H-58

LTE Band 25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.85	19.99	20.01	0	0
	1	7	19.96	19.95	19.99		0
	1	14	19.84	19.95	20.01		0
	8	0	19.83	19.94	20.00	0-1	0
	8	4	19.91	19.94	19.97		0
	8	7	19.89	19.94	20.00		0
	15	0	19.82	19.94	20.00		0
16QAM	1	0	19.93	19.97	20.04	0-1	0
	1	7	20.20	19.96	20.06		0
	1	14	20.07	19.98	19.98		0
	8	0	19.91	19.97	20.08	0-2	0
	8	4	19.99	19.89	20.02		0
	8	7	19.94	20.00	20.04		0
	15	0	19.86	19.95	20.04		0
64QAM	1	0	19.96	19.98	20.04	0-2	0
	1	7	20.19	19.93	20.03		0
	1	14	20.07	19.91	20.05		0
	8	0	19.86	19.96	20.02	0-3	0
	8	4	19.95	19.95	20.07		0
	8	7	19.95	19.96	20.01		0
	15	0	19.87	19.96	20.05		0
256QAM	1	0	18.08	18.17	18.19	0-5	2
	1	7	18.27	18.54	18.36		2
	1	14	18.21	18.33	18.15		2
	8	0	18.11	18.14	18.24	0-5	2
	8	4	18.12	18.18	18.29		2
	8	7	18.12	18.30	18.25		2
	15	0	18.10	18.16	18.19		2

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 30 of 155

Table H-59

LTE Band 25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.80	20.02	20.02	0	0
	1	2	19.74	20.01	19.99		0
	1	5	19.73	20.05	19.99		0
	3	0	19.78	20.05	20.07		0
	3	2	19.73	20.03	20.02		0
	3	3	19.79	20.06	19.95		0
	6	0	19.79	20.09	19.94		0-1
16QAM	1	0	19.95	20.02	19.98	0-1	0
	1	2	19.86	20.05	19.94		0
	1	5	20.03	20.06	19.99		0
	3	0	20.01	20.03	19.97		0
	3	2	20.00	20.04	19.97		0
	3	3	19.93	20.09	19.97		0
	6	0	19.90	20.00	19.93		0-2
64QAM	1	0	20.10	20.09	19.97	0-2	0
	1	2	19.94	19.97	19.89		0
	1	5	20.12	20.04	19.99		0
	3	0	19.98	20.01	20.03		0
	3	2	20.05	20.11	19.99		0
	3	3	20.04	20.10	19.97		0
	6	0	19.92	19.99	20.05		0-3
256QAM	1	0	18.14	18.43	18.29	0-5	2
	1	2	18.21	18.36	18.37		2
	1	5	18.16	18.41	18.34		2
	3	0	18.12	18.32	18.32		2
	3	2	18.15	18.18	18.21		2
	3	3	18.10	18.22	18.27		2
	6	0	18.08	18.20	18.22		2

Table H-60

LTE Band 25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.88	18.93	18.95	0	0
	1	36	19.02	18.94	18.98		0
	1	74	18.76	18.89	18.97		0
	36	0	18.84	18.89	18.99	0-1	0
	36	18	18.88	18.89	18.97		0
	36	37	18.81	18.90	18.96		0
	75	0	18.82	18.94	18.99		0
16QAM	1	0	18.95	18.92	18.99	0-1	0
	1	36	19.06	18.90	18.99		0
	1	74	18.92	18.91	18.98		0
	36	0	18.80	18.90	18.97	0-2	0
	36	18	18.85	18.95	19.00		0
	36	37	18.81	18.89	19.00		0
	75	0	18.86	18.92	18.97		0
64QAM	1	0	18.82	18.83	18.90	0-2	0
	1	36	19.01	18.85	18.90		0
	1	74	18.96	18.85	18.90		0
	36	0	18.75	18.83	18.90	0-3	0
	36	18	18.76	18.85	18.87		0
	36	37	18.76	18.83	18.90		0
	75	0	18.74	18.86	18.91		0
256QAM	1	0	17.92	17.99	18.15	0-5	1
	1	36	18.01	18.25	18.20		1
	1	74	18.02	18.29	18.05		1
	36	0	17.97	18.03	18.05		1
	36	18	18.00	18.10	18.14		1
	36	37	17.95	18.13	18.08		1
	75	0	17.96	18.03	18.13		1

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 31 of 155

Table H-61
LTE Band 25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.79	18.90	18.98	0	0
	1	25	18.85	18.92	18.93		0
	1	49	18.73	18.90	18.97		0
	25	0	18.83	18.91	18.97	0-1	0
	25	12	18.89	18.93	18.98		0
	25	25	18.84	18.92	18.97		0
	50	0	18.85	18.91	18.94		0
16QAM	1	0	18.97	18.90	18.93	0-1	0
	1	25	19.12	18.89	18.97		0
	1	49	19.00	18.88	18.96		0
	25	0	18.85	18.90	18.96	0-2	0
	25	12	18.89	18.90	18.95		0
	25	25	18.85	18.88	18.95		0
	50	0	18.83	18.90	18.95		0
64QAM	1	0	18.96	18.85	18.89	0-2	0
	1	25	19.04	18.86	18.90		0
	1	49	18.97	18.80	18.86		0
	25	0	18.77	18.84	18.88	0-3	0
	25	12	18.81	18.83	18.88		0
	25	25	18.81	18.81	18.89		0
	50	0	18.75	18.81	18.85		0
256QAM	1	0	18.10	18.05	18.11	0-5	1
	1	25	18.23	18.23	18.33		1
	1	49	18.11	18.17	18.09		1
	25	0	17.95	17.98	18.07		1
	25	12	17.99	18.07	18.14		1
	25	25	17.99	18.11	18.09		1
	50	0	17.98	18.05	18.07		1

Table H-62
LTE Band 25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.73	18.93	18.95	0	0
	1	12	18.82	18.90	18.95		0
	1	24	18.76	18.92	18.98		0
	12	0	18.84	18.89	18.98	0-1	0
	12	6	18.89	18.90	18.97		0
	12	13	18.90	18.92	18.96		0
	25	0	18.87	18.91	18.98		0
16QAM	1	0	19.03	18.88	19.01	0-1	0
	1	12	19.21	18.92	18.97		0
	1	24	19.14	18.91	18.97		0
	12	0	18.87	18.93	18.96	0-2	0
	12	6	18.92	18.94	18.91		0
	12	13	18.86	18.93	18.97		0
	25	0	18.86	18.90	18.97		0
64QAM	1	0	18.84	18.83	18.86	0-2	0
	1	12	18.94	18.88	18.91		0
	1	24	18.77	18.85	18.85		0
	12	0	18.75	18.85	18.88	0-3	0
	12	6	18.82	18.82	18.90		0
	12	13	18.74	18.83	18.88		0
	25	0	18.73	18.83	18.85		0
256QAM	1	0	18.02	18.07	18.13	0-5	1
	1	12	18.14	18.37	18.26		1
	1	24	18.02	18.34	18.16		1
	12	0	17.99	18.04	18.07		1
	12	6	18.05	18.09	18.14		1
	12	13	18.02	18.15	18.09		1
	25	0	17.95	18.04	18.08		1

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 32 of 155

Table H-63
LTE Band 25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.80	18.92	18.95	0	0
	1	7	19.01	18.99	18.98		0
	1	14	18.73	18.92	19.01		0
	8	0	18.87	18.94	19.00	0-1	0
	8	4	18.90	18.89	18.96		0
	8	7	18.89	19.00	19.07		0
	15	0	18.88	18.94	19.02		0
16QAM	1	0	18.87	18.95	18.99	0-1	0
	1	7	18.95	18.99	19.02		0
	1	14	18.99	18.94	19.00		0
	8	0	18.89	18.93	18.97	0-2	0
	8	4	18.94	18.96	18.98		0
	8	7	18.94	18.93	18.98		0
	15	0	18.87	18.94	18.97		0
64QAM	1	0	18.88	18.78	18.92	0-2	0
	1	7	18.94	18.91	18.97		0
	1	14	18.92	18.84	18.90		0
	8	0	18.77	18.84	18.92	0-3	0
	8	4	18.82	18.80	18.87		0
	8	7	18.83	18.81	18.88		0
	15	0	18.77	18.80	18.90		0
256QAM	1	0	17.84	17.99	18.15	0-5	1
	1	7	18.17	18.21	18.32		1
	1	14	18.06	18.18	18.11		1
	8	0	17.99	18.03	18.10		1
	8	4	18.02	18.07	18.15		1
	8	7	18.00	18.17	18.07		1
	15	0	17.95	18.06	18.06		1

Table H-64
LTE Band 25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.78	18.98	18.90	0	0
	1	2	18.72	19.02	18.93		0
	1	5	18.78	19.00	18.95		0
	3	0	18.78	19.00	18.94		0
	3	2	18.72	18.99	18.95		0
	3	3	18.77	19.02	18.91		0
	6	0	18.79	19.01	18.94	0-1	0
16QAM	1	0	19.03	19.02	18.96	0-1	0
	1	2	18.98	19.00	18.98		0
	1	5	18.97	19.01	18.95		0
	3	0	18.97	19.00	18.97		0
	3	2	18.88	19.00	18.95		0
	3	3	18.91	18.96	19.01		0
	6	0	18.83	19.00	18.99	0-2	0
64QAM	1	0	19.05	18.87	18.92	0-2	0
	1	2	18.71	18.93	18.94		0
	1	5	18.85	18.87	18.84		0
	3	0	18.84	18.88	18.87		0
	3	2	18.80	18.91	18.89		0
	3	3	18.86	18.85	18.85		0
	6	0	18.72	18.87	18.89	0-3	0
256QAM	1	0	18.23	18.24	18.18	0-5	1
	1	2	18.14	18.15	18.22		1
	1	5	18.13	18.18	18.20		1
	3	0	17.92	18.20	18.19		1
	3	2	18.02	18.15	18.21		1
	3	3	17.97	18.17	18.06		1
	6	0	17.90	18.04	18.04		1

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 33 of 155

H.1.6 LTE Band 41

Table H-65
LTE Band 41 Ant B Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	24.46	24.08	24.15	24.18	24.29	0	0	
	1	36	24.46	24.12	24.29	24.33	24.37		0	
	1	74	24.34	24.10	24.22	24.20	24.27		0	
	36	0	23.47	23.23	23.24	23.32	23.38	0-1	1	
	36	18	23.37	23.15	23.24	23.34	23.42		1	
	36	37	23.35	23.15	23.28	23.31	23.40		1	
16QAM	75	0	23.36	23.14	23.25	23.31	23.39	0-1	1	
	1	0	23.51	23.09	22.92	23.21	23.28		1	
	1	36	23.57	23.26	23.14	23.38	23.27		1	
	1	74	23.36	23.03	23.10	23.24	23.24	0-2	1	
	36	0	22.46	22.23	22.21	22.32	22.39		2	
	36	18	22.40	22.18	22.27	22.39	22.46		2	
64QAM	36	37	22.41	22.14	22.22	22.32	22.42	0-2	2	
	75	0	22.34	22.14	22.25	22.34	22.40		2	
	1	0	22.50	22.09	21.96	22.23	22.29		0-2	2
	1	36	22.47	22.14	22.19	22.32	22.41	2		
	1	74	22.38	22.00	22.04	22.17	22.30	2		
	36	0	21.49	21.21	21.23	21.28	21.42	0-3	3	
36	18	21.37	21.14	21.26	21.30	21.47	3			
36	37	21.40	21.15	21.28	21.38	21.44	3			
256QAM	75	0	21.34	21.15	21.24	21.33	21.48	0-3	3	
	1	0	19.24	19.07	19.03	19.29	19.30		0-5	5
	1	36	19.40	19.19	19.15	19.23	19.42			5
	1	74	19.18	18.95	19.09	19.10	19.19	5		
	36	0	19.39	19.14	19.18	19.25	19.35	5		
	36	18	19.37	19.13	19.22	19.26	19.41	5		
36	37	19.35	19.07	19.19	19.30	19.39	5			
75	0	19.33	19.05	19.19	19.29	19.44	5			

Table H-66
LTE Band 41 Ant B Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.39	24.11	24.20	24.25	24.24	0	0
	1	25	24.44	24.16	24.29	24.34	24.35		0
	1	49	24.37	24.05	24.19	24.23	24.23		0
	25	0	23.49	23.25	23.27	23.33	23.43	0-1	1
	25	12	23.40	23.21	23.26	23.35	23.47		1
	25	25	23.37	23.18	23.26	23.38	23.44		1
16QAM	50	0	23.40	23.17	23.29	23.33	23.47	0-1	1
	1	0	23.56	23.07	23.14	23.19	23.34		1
	1	25	23.48	23.05	23.09	23.31	23.43		0-2
	1	49	23.42	23.17	23.06	23.21	23.29	1	
	25	0	22.49	22.21	22.26	22.29	22.39	2	
	25	12	22.41	22.17	22.31	22.35	22.46	2	
64QAM	25	25	22.38	22.14	22.27	22.30	22.43	0-2	2
	50	0	22.38	22.10	22.25	22.32	22.41		2
	1	0	22.46	22.05	22.12	22.18	22.35		0-2
	1	25	22.58	22.16	22.23	22.39	22.55	2	
	1	49	22.43	22.04	22.11	22.19	22.24	0-3	
	25	0	21.43	21.20	21.24	21.25	21.42		3
256QAM	25	12	21.43	21.17	21.32	21.34	21.52		0-3
	25	25	21.36	21.13	21.30	21.35	21.48	3	
	50	0	21.39	21.15	21.27	21.34	21.48	3	
	1	0	19.20	19.03	19.10	19.19	19.31	0-5	5
	1	25	19.41	18.94	19.20	19.42	19.34		5
	1	49	19.18	19.05	19.27	19.11	19.28		5
25	0	19.45	19.17	19.22	19.28	19.37	5		
25	12	19.40	19.14	19.28	19.31	19.41	5		
25	25	19.36	19.16	19.28	19.33	19.40	5		
	50	0	19.36	19.14	19.21	19.29	19.40	5	

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 34 of 155

Table H-67
LTE Band 41 Ant B Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.35	24.11	24.16	24.30	24.27	0	0
	1	12	24.49	24.20	24.24	24.37	24.39		0
	1	24	24.41	24.05	24.10	24.23	24.22		0
	12	0	23.47	23.25	23.32	23.37	23.46	0-1	1
	12	6	23.42	23.18	23.29	23.35	23.45		1
	12	13	23.36	23.15	23.27	23.35	23.42		1
	25	0	23.35	23.15	23.29	23.35	23.45		1
16QAM	1	0	23.39	23.05	23.10	23.31	23.41	0-1	1
	1	12	23.57	23.13	23.20	23.37	23.35		1
	1	24	23.35	23.01	23.13	23.31	23.29		1
	12	0	22.45	22.25	22.33	22.38	22.44	0-2	2
	12	6	22.40	22.15	22.29	22.38	22.45		2
	12	13	22.42	22.13	22.24	22.38	22.44		2
	25	0	22.38	22.16	22.30	22.35	22.44		2
64QAM	1	0	22.32	22.11	22.28	22.25	22.39	0-2	2
	1	12	22.43	22.16	22.29	22.44	22.29		2
	1	24	22.25	22.05	22.20	22.19	22.16		2
	12	0	21.42	21.29	21.27	21.34	21.49	0-3	3
	12	6	21.39	21.19	21.34	21.38	21.45		3
	12	13	21.41	21.15	21.27	21.28	21.43		3
	25	0	21.32	21.14	21.31	21.30	21.44		3
256QAM	1	0	19.42	19.12	19.17	19.27	19.33	0-5	5
	1	12	19.37	19.28	19.33	19.24	19.43		5
	1	24	19.13	19.01	19.12	19.14	19.34		5
	12	0	19.47	19.22	19.23	19.33	19.44		5
	12	6	19.38	19.15	19.27	19.31	19.43		5
	12	13	19.34	19.07	19.24	19.31	19.40		5
	25	0	19.34	19.15	19.26	19.34	19.39		5

Table H-68
LTE Band 41 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.51	21.27	21.35	21.32	21.52	0	0
	1	36	21.57	21.28	21.37	21.43	21.54		0
	1	74	21.43	21.22	21.36	21.33	21.49		0
	36	0	21.64	21.35	21.34	21.47	21.58	0-1	0
	36	18	21.53	21.30	21.42	21.47	21.62		0
	36	37	21.49	21.26	21.39	21.48	21.59		0
	75	0	21.50	21.24	21.34	21.47	21.61	0	
16QAM	1	0	21.76	21.22	21.01	21.45	21.44	0-1	0
	1	36	21.64	21.25	21.29	21.53	21.54		0
	1	74	21.58	21.26	21.23	21.48	21.43		0
	36	0	21.62	21.35	21.39	21.46	21.59	0-2	0
	36	18	21.56	21.29	21.41	21.51	21.62		0
	36	37	21.53	21.28	21.42	21.48	21.59		0
	75	0	21.52	21.29	21.39	21.47	21.60	0	
64QAM	1	0	21.64	21.29	21.22	21.33	21.50	0-2	0
	1	36	21.60	21.31	21.19	21.58	21.64		0
	1	74	21.50	21.28	21.27	21.45	21.57		0
	36	0	21.46	21.19	21.17	21.30	21.42	0-3	0
	36	18	21.38	21.13	21.25	21.36	21.47		0
	36	37	21.36	21.10	21.21	21.34	21.45		0
	75	0	21.33	21.09	21.22	21.30	21.44	0	
256QAM	1	0	19.24	19.03	18.97	19.11	19.23	0-5	2
	1	36	19.34	19.21	19.11	19.23	19.40		2
	1	74	19.19	18.95	19.07	19.12	19.21		2
	36	0	19.40	19.15	19.18	19.26	19.39		2
	36	18	19.34	19.12	19.21	19.31	19.44		2
	36	37	19.32	19.06	19.21	19.26	19.37		2
	75	0	19.30	19.08	19.19	19.26	19.39		2

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 35 of 155

Table H-69

LTE Band 41 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.64	21.27	21.35	21.40	21.48	0	0
	1	25	21.64	21.34	21.41	21.51	21.56		0
	1	49	21.51	21.25	21.36	21.39	21.43		0
	25	0	21.66	21.40	21.38	21.47	21.60	0-1	0
	25	12	21.60	21.34	21.44	21.49	21.64		0
	25	25	21.53	21.36	21.41	21.52	21.61		0
	50	0	21.57	21.31	21.40	21.46	21.62	0	
16QAM	1	0	21.64	21.29	21.14	21.26	21.41	0-1	0
	1	25	21.60	21.32	21.32	21.45	21.50		0
	1	49	21.59	21.19	21.13	21.38	21.41		0
	25	0	21.66	21.42	21.35	21.48	21.57	0-2	0
	25	12	21.58	21.35	21.41	21.47	21.57		0
	25	25	21.55	21.36	21.36	21.48	21.61		0
	50	0	21.55	21.34	21.37	21.49	21.64	0	
64QAM	1	0	21.66	21.29	21.14	21.49	21.60	0-2	0
	1	25	21.82	21.44	21.31	21.40	21.59		0
	1	49	21.58	21.26	21.07	21.50	21.48		0
	25	0	21.49	21.24	21.20	21.28	21.42	0-3	0
	25	12	21.43	21.19	21.25	21.29	21.46		0
	25	25	21.39	21.18	21.26	21.28	21.43		0
	50	0	21.38	21.13	21.22	21.27	21.41	0	
256QAM	1	0	19.30	19.16	19.02	19.15	19.27	0-5	2
	1	25	19.41	19.00	19.18	19.23	19.35		2
	1	49	19.24	18.99	19.10	19.08	19.24		2
	25	0	19.40	19.16	19.18	19.23	19.37	0-5	2
	25	12	19.38	19.12	19.21	19.25	19.40		2
	25	25	19.34	19.06	19.21	19.27	19.36		2
	50	0	19.34	19.08	19.17	19.26	19.39	2	

Table H-70

LTE Band 41 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.61	21.25	21.32	21.45	21.46	0	0
	1	12	21.68	21.34	21.38	21.55	21.53		0
	1	24	21.60	21.20	21.26	21.42	21.42		0
	12	0	21.65	21.42	21.43	21.48	21.59	0-1	0
	12	6	21.57	21.35	21.46	21.50	21.62		0
	12	13	21.55	21.33	21.41	21.48	21.61		0
16QAM	25	0	21.55	21.32	21.41	21.50	21.59	0	
	1	0	21.70	21.32	21.26	21.45	21.44	0-1	0
	1	12	21.67	21.34	21.33	21.58	21.57		0
	1	24	21.42	21.15	21.21	21.46	21.50		0
	12	0	21.64	21.43	21.42	21.56	21.62	0-2	0
	12	6	21.56	21.34	21.45	21.54	21.64		0
64QAM	12	13	21.59	21.30	21.43	21.51	21.58		0
	25	0	21.57	21.32	21.46	21.52	21.62	0	
	1	0	21.69	21.26	21.29	21.29	21.43	0-2	0
	1	12	21.64	21.38	21.45	21.53	21.63		0
	1	24	21.40	21.17	21.30	21.31	21.42		0
	12	0	21.48	21.23	21.25	21.36	21.47	0-3	0
12	6	21.40	21.17	21.30	21.36	21.44	0		
12	13	21.35	21.14	21.24	21.33	21.42	0		
256QAM	25	0	21.39	21.14	21.24	21.36	21.43	0-5	0
	1	0	19.44	19.17	19.17	19.31	19.40		2
	1	12	19.40	19.12	19.19	19.42	19.31		2
	1	24	19.22	18.97	19.02	19.19	19.24	2	
	12	0	19.43	19.21	19.25	19.30	19.42	2	
	12	6	19.33	19.15	19.25	19.31	19.43	2	
	12	13	19.35	19.09	19.21	19.28	19.38	2	
	25	0	19.34	19.14	19.21	19.33	19.45	2	

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 36 of 155

Table H-71

LTE Band 41 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.30	21.08	21.23	21.00	21.03	0	0
	1	36	21.31	21.11	21.23	21.07	21.05		0
	1	74	21.19	21.06	21.22	20.94	20.97		0
	36	0	21.37	21.16	21.19	21.13	21.15	0-1	0
	36	18	21.33	21.18	21.18	21.15	21.14		0
	36	37	21.33	21.14	21.17	21.13	21.13		0
16QAM	75	0	21.33	21.15	21.18	21.12	21.09	0-1	0
	1	0	21.35	21.07	21.04	21.17	20.95		0
	1	36	21.33	21.06	21.09	21.11	21.03		0
	1	74	21.29	21.05	21.00	21.08	21.08	0-2	0
	36	0	21.38	21.16	21.20	21.19	21.12		0
	36	18	21.41	21.20	21.18	21.16	21.13		0
64QAM	36	37	21.36	21.18	21.16	21.12	21.12	0-2	0
	75	0	21.32	21.18	21.24	21.14	21.11		0
	1	0	21.34	21.03	21.10	21.14	20.92	0-2	0
	1	36	21.41	21.09	21.12	21.12	20.97		0
	1	74	21.13	21.13	21.07	21.05	20.91	0-3	0
	36	0	21.33	21.14	21.16	21.14	21.10		0
256QAM	36	18	21.32	21.17	21.14	21.16	21.13		0-3
	36	37	21.32	21.13	21.14	21.10	21.08	0	
	75	0	21.33	21.15	21.14	21.08	21.07	0-5	0
	1	0	19.15	19.10	18.95	18.81	18.90		2
	1	36	19.27	19.06	19.16	19.12	19.10		2
	1	74	19.20	18.93	19.09	18.91	18.86	0-5	2
36	0	19.36	19.13	19.17	19.11	19.10	2		
36	18	19.32	19.15	19.19	19.12	19.13	2		
256QAM	36	37	19.32	19.12	19.14	19.11	19.08	0-5	2
	75	0	19.29	19.11	19.16	19.12	19.10		2

Table H-72

LTE Band 41 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	21.35	21.02	21.23	21.09	20.97	0	0	
	1	25	21.33	21.10	21.28	21.18	21.05		0	
	1	49	21.28	20.96	21.22	21.10	20.99		0	
	25	0	21.36	21.14	21.23	21.14	21.13	0-1	0	
	25	12	21.34	21.17	21.21	21.18	21.14		0	
	25	25	21.31	21.17	21.20	21.11	21.11		0	
16QAM	50	0	21.34	21.15	21.19	21.12	21.10	0-1	0	
	1	0	21.22	21.00	20.98	21.09	21.02		0	
	1	25	21.19	21.08	21.18	21.05	21.08		0	
	1	49	21.27	20.89	20.95	21.00	21.04	0-2	0	
	25	0	21.33	21.18	21.22	21.14	21.09		0	
	25	12	21.38	21.20	21.19	21.13	21.11		0	
64QAM	25	25	21.30	21.15	21.20	21.16	21.08	0-2	0	
	50	0	21.36	21.14	21.20	21.15	21.09		0	
	1	0	21.26	21.00	21.07	21.10	21.05		0-2	0
	1	25	21.58	21.11	21.25	21.06	21.14	0		
	1	49	21.34	21.04	20.98	21.01	21.14	0		
	25	0	21.33	21.13	21.17	21.10	21.08	0-3	0	
25	12	21.34	21.20	21.17	21.16	21.09	0			
25	25	21.32	21.19	21.20	21.16	21.08	0			
256QAM	50	0	21.31	21.16	21.16	21.13	21.07	0-3	0	
	1	0	19.12	19.16	19.09	18.97	18.98		0-5	2
	1	25	19.17	19.15	19.19	19.03	19.08			2
	1	49	19.16	18.96	19.15	19.04	18.92	2		
	25	0	19.30	19.16	19.16	19.11	19.08	2		
	25	12	19.33	19.21	19.21	19.15	19.11	2		
25	25	19.30	19.16	19.22	19.13	19.09	2			
50	0	19.31	19.13	19.19	19.11	19.08	2			

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 37 of 155

Table H-73

LTE Band 41 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	21.28	20.96	21.07	21.02	20.98	0	0	
	1	12	21.32	21.06	21.15	21.15	21.04		0	0
	1	24	21.16	20.90	21.02	20.94	20.84			0
	12	0	21.29	21.11	21.20	21.13	21.08	0-1		0
	12	6	21.31	21.15	21.19	21.13	21.11		0	
	12	13	21.28	21.06	21.10	21.09	21.05		0	
16QAM	25	0	21.26	21.11	21.12	21.09	21.04	0-1	0	
	1	0	21.28	21.10	21.06	21.11	20.87		0	0
	1	12	21.30	20.97	21.16	21.10	20.96			0
	1	24	21.17	20.90	21.05	20.95	20.88	0-2		0
	12	0	21.34	21.17	21.20	21.13	21.05		0	
	12	6	21.25	21.12	21.22	21.17	21.11		0	
64QAM	12	13	21.28	21.11	21.21	21.10	21.06	0-2	0	
	25	0	21.27	21.13	21.21	21.11	21.05		0	0
	1	0	21.32	21.11	21.18	20.87	21.06			0-2
	1	12	21.31	21.19	21.23	20.98	20.96	0		
	1	24	21.07	21.00	21.05	20.82	20.90		0-3	
	12	0	21.22	21.21	21.18	21.09	21.03			0
256QAM	12	6	21.25	21.17	21.25	21.12	21.06	0-3		0
	12	13	21.27	21.12	21.13	21.06	21.02		0	0
	25	0	21.28	21.17	21.15	21.06	21.09			0-5
	1	0	19.15	19.01	19.07	19.11	19.04	2		
	1	12	19.33	19.23	19.26	19.21	19.15		2	
	1	24	19.01	18.84	18.93	19.00	18.93			2
12	0	19.28	19.14	19.19	19.14	19.10	2	2		
12	6	19.28	19.17	19.28	19.14	19.07		2	2	
12	13	19.26	19.09	19.16	19.10	19.09			2	2
25	0	19.22	19.11	19.17	19.14	19.07	2			2

Table H-74

LTE Band 41 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	17.77	17.54	17.69	17.51	17.46	0	0
	1	36	17.76	17.56	17.75	17.55	17.52		0
	1	74	17.67	17.55	17.70	17.44	17.46		0
	36	0	17.83	17.66	17.68	17.62	17.56	0-1	0
	36	18	17.82	17.64	17.69	17.63	17.58		0
	36	37	17.78	17.62	17.65	17.60	17.54		0
	75	0	17.78	17.60	17.63	17.59	17.55		0
16QAM	1	0	17.86	17.56	17.53	17.62	17.44	0-1	0
	1	36	17.86	17.49	17.59	17.61	17.59		0
	1	74	17.69	17.50	17.51	17.56	17.38		0
	36	0	17.84	17.64	17.62	17.59	17.55	0-2	0
	36	18	17.84	17.64	17.65	17.59	17.58		0
	36	37	17.82	17.64	17.65	17.58	17.54		0
	75	0	17.81	17.63	17.63	17.57	17.55		0
64QAM	1	0	17.72	17.58	17.59	17.51	17.49	0-2	0
	1	36	17.73	17.60	17.69	17.60	17.52		0
	1	74	17.66	17.54	17.46	17.37	17.41		0
	36	0	17.84	17.63	17.66	17.59	17.59	0-3	0
	36	18	17.82	17.64	17.70	17.57	17.58		0
	36	37	17.84	17.61	17.65	17.60	17.57		0
	75	0	17.80	17.62	17.63	17.58	17.55		0
256QAM	1	0	17.83	17.42	17.50	17.58	17.45	0-5	0
	1	36	17.80	17.56	17.64	17.54	17.57		0
	1	74	17.56	17.65	17.56	17.36	17.47		0
	36	0	17.85	17.67	17.66	17.62	17.59		0
	36	18	17.88	17.70	17.70	17.66	17.60		0
	36	37	17.83	17.66	17.68	17.61	17.58		0
	75	0	17.84	17.65	17.65	17.61	17.59		0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 38 of 155

Table H-75
LTE Band 41 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	17.85	17.60	17.74	17.55	17.44	0	0
	1	25	17.81	17.67	17.77	17.66	17.52		0
	1	49	17.74	17.51	17.70	17.47	17.43		0
	25	0	17.85	17.64	17.67	17.65	17.55	0-1	0
	25	12	17.84	17.70	17.73	17.65	17.59		0
	25	25	17.80	17.68	17.71	17.64	17.59		0
16QAM	50	0	17.81	17.65	17.67	17.60	17.56	0	
	1	0	17.82	17.51	17.56	17.54	17.47	0-1	0
	1	25	17.77	17.57	17.59	17.59	17.54		0
	1	49	17.68	17.49	17.50	17.48	17.37		0-2
	25	0	17.86	17.71	17.66	17.61	17.54	0	
	25	12	17.82	17.68	17.66	17.63	17.59	0	
64QAM	25	25	17.82	17.67	17.72	17.62	17.55	0-2	0
	50	0	17.81	17.68	17.67	17.57	17.59		0
	1	0	17.86	17.57	17.49	17.63	17.44	0-2	0
	1	25	18.01	17.68	17.67	17.59	17.59		0
	1	49	17.75	17.50	17.52	17.46	17.49	0-3	0
	25	0	17.87	17.68	17.67	17.63	17.57		0
256QAM	25	12	17.84	17.72	17.74	17.68	17.56	0-3	0
	25	25	17.83	17.71	17.69	17.59	17.56		0
	50	0	17.83	17.65	17.69	17.60	17.56	0-5	0
	1	0	17.79	17.59	17.50	17.54	17.44		0
	1	25	17.77	17.79	17.72	17.43	17.56		0
	1	49	17.54	17.36	17.43	17.27	17.51	0	
25	0	17.86	17.66	17.70	17.66	17.56	0		
256QAM	25	12	17.89	17.66	17.79	17.65	17.64	0-5	0
	25	25	17.82	17.73	17.74	17.58	17.61		0
	50	0	17.82	17.66	17.72	17.59	17.64		0
									0

Table H-76
LTE Band 41 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	17.79	17.55	17.62	17.57	17.44	0	0
	1	12	17.85	17.63	17.72	17.66	17.53		0
	1	24	17.72	17.45	17.59	17.50	17.39		0
	12	0	17.79	17.71	17.69	17.60	17.57	0-1	0
	12	6	17.80	17.69	17.77	17.59	17.63		0
	12	13	17.80	17.65	17.64	17.60	17.57		0
16QAM	25	0	17.83	17.64	17.68	17.63	17.57	0-1	0
	1	0	17.80	17.47	17.51	17.53	17.45		0
	1	12	17.86	17.65	17.62	17.64	17.51		0
	1	24	17.70	17.44	17.52	17.45	17.42	0-2	0
	12	0	17.77	17.62	17.69	17.56	17.54		0
	12	6	17.88	17.65	17.78	17.64	17.58		0
64QAM	12	13	17.81	17.64	17.69	17.57	17.57	0-2	0
	25	0	17.78	17.67	17.67	17.61	17.54		0
	1	0	17.73	17.45	17.61	17.61	17.53		0
	1	12	17.63	17.57	17.80	17.58	17.57	0-3	0
	1	24	17.67	17.49	17.62	17.29	17.32		0
	12	0	17.82	17.72	17.68	17.67	17.62		0
256QAM	12	6	17.89	17.73	17.78	17.67	17.63	0-3	0
	12	13	17.79	17.68	17.66	17.66	17.56		0
	25	0	17.82	17.66	17.70	17.63	17.57		0
	1	0	17.84	17.71	17.64	17.56	17.54	0-5	0
	1	12	17.84	17.71	17.87	17.54	17.69		0
	1	24	17.60	17.61	17.60	17.44	17.53		0
256QAM	12	0	17.88	17.68	17.73	17.64	17.64	0-5	0
	12	6	17.82	17.69	17.79	17.70	17.57		0
	12	13	17.80	17.69	17.69	17.60	17.60		0
	25	0	17.90	17.70	17.72	17.67	17.62	0	

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 39 of 155

H.2 NR Lower Bandwidth RF Conducted Powers

H.2.1 NR Band n5

Table H-77
NR Band n5 Ant A Measured P_{Max} for all DSI - 15 MHz Bandwidth

NR Band n5 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.84	0	0.0
	1	40	23.80		0.0
	1	77	23.84		0.0
	36	0	22.89	0-1	1.0
	36	22	23.99	0	0.0
	36	43	22.80	0-1	1.0
	75	0	22.88		1.0
DFT-s-OFDM 16QAM	1	1	23.05	0-1	1.0
CP-OFDM QPSK	1	1	22.57	0-1.5	1.5

Table H-78
NR Band n5 Ant A Measured P_{Max} for all DSI - 10 MHz Bandwidth

NR Band n5 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.85	0	0.0
	1	26	23.83		0.0
	1	50	23.96		0.0
	25	0	22.89	0-1	1.0
	25	14	23.96	0	0.0
	25	27	22.83	0-1	1.0
	50	0	22.85		1.0
DFT-s-OFDM 16QAM	1	1	23.03	0-1	1.0
CP-OFDM QPSK	1	1	22.52	0-1.5	1.5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 40 of 155

Table H-79
NR Band n5 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

NR Band n5 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	165300 (826.5 MHz)	167300 (836.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.88	23.94	23.79	0	0.0
	1	13	23.86	23.86	23.78		0.0
	1	23	23.80	23.90	23.71		0.0
	12	0	22.94	22.91	22.92	0-1	1.0
	12	7	24.03	23.95	23.94	0	0.0
	12	13	22.91	22.88	22.83	0-1	1.0
	25	0	22.93	22.90	22.87		1.0
DFT-s-OFDM 16QAM	1	1	23.00	23.02	23.06	0-1	1.0
CP-OFDM QPSK	1	1	22.53	22.73	22.56	0-1.5	1.5

Table H-80
NR Band n5 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n5 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.18	0	0.0
	1	40	24.06		0.0
	1	77	24.12		0.0
	36	0	23.18	0-1	1.0
	36	22	24.28	0	0.0
	36	43	23.11	0-1	1.0
	75	0	23.14		1.0
DFT-s-OFDM 16QAM	1	1	23.14	0-1	1.0
CP-OFDM QPSK	1	1	22.74	0-1.5	1.5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 41 of 155

Table H-81
NR Band n5 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n5 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.21	0	0.0
	1	26	24.15		0.0
	1	50	24.18		0.0
	25	0	23.14	0-1	1.0
	25	14	24.30	0	0.0
	25	27	23.19	0-1	1.0
	50	0	23.24		1.0
DFT-s-OFDM 16QAM	1	1	23.11	0-1	1.0
CP-OFDM QPSK	1	1	22.79	0-1.5	1.5

Table H-82
NR Band n5 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n5 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	165300 (826.5 MHz)	167300 (836.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.14	24.14	24.08	0	0.0
	1	13	24.21	24.14	24.09		0.0
	1	23	24.16	24.06	24.03		0.0
	12	0	23.17	23.19	23.22	0-1	1.0
	12	7	24.36	24.21	24.27	0	0.0
	12	13	23.26	23.17	23.16	0-1	1.0
	25	0	23.26	23.18	23.22		1.0
DFT-s-OFDM 16QAM	1	1	23.14	23.17	23.18	0-1	1.0
CP-OFDM QPSK	1	1	22.86	22.84	22.96	0-1.5	1.5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 42 of 155

Table H-83
NR Band n5 Ant E Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n5 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.81	0	0.0
	1	40	20.80		0.0
	1	77	20.73		0.0
	36	0	20.75	0-1	0.0
	36	22	20.84	0	0.0
	36	43	20.62	0-1	0.0
	75	0	20.70		0.0
DFT-s-OFDM 16QAM	1	1	20.67	0-1	0.0
CP-OFDM QPSK	1	1	20.92	0-1.5	0.0

Table H-84
NR Band n5 Ant E Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n5 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.79	0	0.0
	1	26	20.71		0.0
	1	50	20.71		0.0
	25	0	20.71	0-1	0.0
	25	14	20.80	0	0.0
	25	27	20.67	0-1	0.0
	50	0	20.69		0.0
DFT-s-OFDM 16QAM	1	1	20.65	0-1	0.0
CP-OFDM QPSK	1	1	20.93	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 43 of 155

Table H-85
NR Band n5 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n5 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	165300 (826.5 MHz)	167300 (836.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.74	20.77	20.62	0	0.0
	1	13	20.81	20.71	20.67		0.0
	1	23	20.71	20.64	20.55		0.0
	12	0	20.77	20.71	20.66	0-1	0.0
	12	7	20.84	20.79	20.66	0	0.0
	12	13	20.72	20.64	20.62	0-1	0.0
	25	0	20.78	20.72	20.57		0.0
DFT-s-OFDM 16QAM	1	1	20.68	20.68	20.67	0-1	0.0
CP-OFDM QPSK	1	1	20.86	20.92	20.76	0-1.5	0.0

H.2.2 NR Band n66

Table H-86
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	22.23	0	0.0
	1	108	22.23		0.0
	1	214	22.28		0.0
	108	0	21.17	0-1	1.0
	108	54	22.30	0	0.0
	108	108	21.10	0-1	1.0
	216	0	21.27		1.0
DFT-s-OFDM 16QAM	1	1	21.15	0-1	1.0
CP-OFDM QPSK	1	1	20.81	0-1.5	1.5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 44 of 155

Table H-87
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	22.82	0	0.0
	1	94	22.87		0.0
	1	186	22.71		0.0
	90	0	21.82	0-1	1.0
	90	49	22.94	0	0.0
	90	98	21.84	0-1	1.0
	180	0	21.83		1.0
DFT-s-OFDM 16QAM	1	1	21.80	0-1	1.0
CP-OFDM QPSK	1	1	21.45	0-1.5	1.5

Table H-88
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	22.96	0	0.0
	1	80	22.91		0.0
	1	158	22.88		0.0
	80	0	21.91	0-1	1.0
	80	40	22.91	0	0.0
	80	80	21.87	0-1	1.0
	160	0	21.80		1.0
DFT-s-OFDM 16QAM	1	1	21.80	0-1	1.0
CP-OFDM QPSK	1	1	21.33	0-1.5	1.5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 45 of 155

Table H-89
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.01	0	0.0
	1	67	22.91		0.0
	1	131	22.89		0.0
	64	0	21.76	0-1	1.0
	64	35	22.90	0	0.0
	64	69	21.82	0-1	1.0
	128	0	21.81		1.0
DFT-s-OFDM 16QAM	1	1	21.81	0-1	1.0
CP-OFDM QPSK	1	1	21.35	0-1.5	1.5

Table H-90
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	22.77	22.75	22.78	0	0.0
	1	53	22.77	22.85	22.78		0.0
	1	104	22.82	22.75	22.72		0.0
	50	0	21.63	21.74	21.61	0-1	1.0
	50	28	22.80	22.87	22.77	0	0.0
	50	56	21.69	21.73	21.69	0-1	1.0
	100	0	21.80	21.89	21.77		1.0
DFT-s-OFDM 16QAM	1	1	22.10	21.81	22.05	0-1	1.0
CP-OFDM QPSK	1	1	21.19	21.27	21.35	0-1.5	1.5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 46 of 155

Table H-91
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	22.82	22.86	22.69	0	0.0
	1	40	22.84	22.86	22.74		0.0
	1	77	22.77	22.81	22.69		0.0
	36	0	21.70	21.76	21.56	0-1	1.0
	36	22	22.83	22.85	22.84	0	0.0
	36	43	21.75	21.79	21.63	0-1	1.0
	75	0	21.63	21.79	21.61		1.0
DFT-s-OFDM 16QAM	1	1	22.21	22.28	22.13	0-1	1.0
CP-OFDM QPSK	1	1	21.27	21.41	21.28	0-1.5	1.5

Table H-92
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	22.70	22.74	22.80	0	0.0
	1	26	22.77	22.73	22.85		0.0
	1	50	22.76	22.85	22.76		0.0
	25	0	21.71	21.85	21.73	0-1	1.0
	25	14	22.90	22.78	22.86	0	0.0
	25	27	21.75	21.77	21.76	0-1	1.0
	50	0	21.77	21.73	21.67		1.0
DFT-s-OFDM 16QAM	1	1	22.26	22.36	22.19	0-1	1.0
CP-OFDM QPSK	1	1	21.31	21.28	21.24	0-1.5	1.5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 47 of 155

Table H-93
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	22.69	22.79	22.75	0	0.0
	1	13	22.78	22.87	22.84		0.0
	1	23	22.73	22.73	22.75		0.0
	12	0	21.62	21.79	21.72	0-1	1.0
	12	7	22.85	22.91	22.84	0	0.0
	12	13	21.76	21.79	21.81	0-1	1.0
	25	0	21.75	21.85	21.73		1.0
DFT-s-OFDM 16QAM	1	1	22.27	22.18	22.20	0-1	1.0
CP-OFDM QPSK	1	1	21.32	21.42	21.32	0-1.5	1.5

Table H-94
NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.64	0	0.0
	1	108	18.57		0.0
	1	214	18.69		0.0
	108	0	18.56	0-1	0.0
	108	54	18.49	0	0.0
	108	108	18.49	0-1	0.0
	216	0	18.50		0.0
DFT-s-OFDM 16QAM	1	1	18.52	0-1	0.0
CP-OFDM QPSK	1	1	18.75	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 48 of 155

Table H-95

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.66	0	0.0
	1	94	18.83		0.0
	1	186	18.65		0.0
	90	0	18.74	0-1	0.0
	90	49	18.82	0	0.0
	90	98	18.65	0-1	0.0
	180	0	18.78		0.0
DFT-s-OFDM 16QAM	1	1	19.18	0-1	0.0
CP-OFDM QPSK	1	1	18.83	0-1.5	0.0

Table H-96

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.89	0	0.0
	1	80	18.79		0.0
	1	158	18.74		0.0
	80	0	18.69	0-1	0.0
	80	40	18.87	0	0.0
	80	80	18.76	0-1	0.0
	160	0	18.74		0.0
DFT-s-OFDM 16QAM	1	1	19.23	0-1	0.0
CP-OFDM QPSK	1	1	18.85	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 49 of 155

Table H-97

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.84	0	0.0
	1	67	18.82		0.0
	1	131	18.79		0.0
	64	0	18.79	0-1	0.0
	64	35	18.78	0	0.0
	64	69	18.80	0-1	0.0
	128	0	18.70		0.0
DFT-s-OFDM 16QAM	1	1	19.18	0-1	0.0
CP-OFDM QPSK	1	1	18.89	0-1.5	0.0

Table H-98

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.53	18.69	18.68	0	0.0
	1	53	18.65	18.60	18.66		0.0
	1	104	18.67	18.70	18.62		0.0
	50	0	18.61	18.67	18.59	0-1	0.0
	50	28	18.73	18.78	18.69	0	0.0
	50	56	18.61	18.64	18.55	0-1	0.0
	100	0	18.73	18.82	18.67		0.0
DFT-s-OFDM 16QAM	1	1	19.12	19.18	19.08	0-1	0.0
CP-OFDM QPSK	1	1	18.68	18.84	18.67	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 50 of 155

Table H-99

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.74	18.78	18.68	0	0.0
	1	40	18.71	18.81	18.58		0.0
	1	77	18.68	18.77	18.73		0.0
	36	0	18.65	18.70	18.55	0-1	0.0
	36	22	18.75	18.80	18.72	0	0.0
	36	43	18.67	18.68	18.52	0-1	0.0
	75	0	18.60	18.70	18.54		0.0
DFT-s-OFDM 16QAM	1	1	19.15	19.24	19.05	0-1	0.0
CP-OFDM QPSK	1	1	18.81	18.93	18.76	0-1.5	0.0

Table H-100

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.72	18.76	18.83	0	0.0
	1	26	18.71	18.76	18.75		0.0
	1	50	18.69	18.78	18.72		0.0
	25	0	18.73	18.72	18.74	0-1	0.0
	25	14	18.82	18.80	18.81	0	0.0
	25	27	18.73	18.72	18.67	0-1	0.0
	50	0	18.75	18.71	18.73		0.0
DFT-s-OFDM 16QAM	1	1	19.04	19.19	19.04	0-1	0.0
CP-OFDM QPSK	1	1	18.72	18.87	18.77	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 51 of 155

Table H-101

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.49	18.62	18.56	0	0.0
	1	13	18.68	18.80	18.63		0.0
	1	23	18.58	18.76	18.63		0.0
	12	0	18.49	18.72	18.65	0-1	0.0
	12	7	18.72	18.88	18.64	0	0.0
	12	13	18.63	18.80	18.70	0-1	0.0
	25	0	18.63	18.70	18.68		0.0
DFT-s-OFDM 16QAM	1	1	19.00	19.14	19.11	0-1	0.0
CP-OFDM QPSK	1	1	18.70	18.80	18.81	0-1.5	0.0

Table H-102

NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.40	0	0.0
	1	108	20.49		0.0
	1	214	20.37		0.0
	108	0	20.41	0-1	0.0
	108	54	20.42	0	0.0
	108	108	20.21	0-1	0.0
	216	0	20.40		0.0
DFT-s-OFDM 16QAM	1	1	20.34	0-1	0.0
CP-OFDM QPSK	1	1	20.55	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 52 of 155

Table H-103

NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.67	0	0.0
	1	94	20.85		0.0
	1	186	20.62		0.0
	90	0	20.72	0-1	0.0
	90	49	20.71	0	0.0
	90	98	20.69	0-1	0.0
	180	0	20.66		0.0
DFT-s-OFDM 16QAM	1	1	21.12	0-1	0.0
CP-OFDM QPSK	1	1	20.81	0-1.5	0.0

Table H-104

NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.73	0	0.0
	1	80	20.77		0.0
	1	158	20.71		0.0
	80	0	20.65	0-1	0.0
	80	40	20.79	0	0.0
	80	80	20.65	0-1	0.0
	160	0	20.53		0.0
DFT-s-OFDM 16QAM	1	1	21.08	0-1	0.0
CP-OFDM QPSK	1	1	20.65	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 53 of 155

Table H-105
NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.84	0	0.0
	1	67	20.73		0.0
	1	131	20.65		0.0
	64	0	20.69	0-1	0.0
	64	35	20.79	0	0.0
	64	69	20.63	0-1	0.0
	128	0	20.69		0.0
DFT-s-OFDM 16QAM	1	1	21.12	0-1	0.0
CP-OFDM QPSK	1	1	20.69	0-1.5	0.0

Table H-106
NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.31	20.48	20.50	0	0.0
	1	53	20.38	20.64	20.57		0.0
	1	104	20.53	20.53	20.48		0.0
	50	0	20.42	20.53	20.52	0-1	0.0
	50	28	20.54	20.67	20.62	0	0.0
	50	56	20.45	20.48	20.53	0-1	0.0
	100	0	20.55	20.66	20.51		0.0
DFT-s-OFDM 16QAM	1	1	20.82	21.01	20.84	0-1	0.0
CP-OFDM QPSK	1	1	20.46	20.61	20.48	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 54 of 155

Table H-107

NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.53	20.65	20.54	0	0.0
	1	40	20.49	20.71	20.55		0.0
	1	77	20.54	20.68	20.54		0.0
	36	0	20.48	20.48	20.51	0-1	0.0
	36	22	20.48	20.64	20.61	0	0.0
	36	43	20.51	20.50	20.39	0-1	0.0
	75	0	20.46	20.57	20.42		0.0
DFT-s-OFDM 16QAM	1	1	20.97	21.04	20.92	0-1	0.0
CP-OFDM QPSK	1	1	20.61	20.69	20.48	0-1.5	0.0

Table H-108

NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.49	20.56	20.51	0	0.0
	1	26	20.55	20.62	20.54		0.0
	1	50	20.41	20.53	20.42		0.0
	25	0	20.40	20.58	20.46	0-1	0.0
	25	14	20.58	20.66	20.55	0	0.0
	25	27	20.48	20.54	20.45	0-1	0.0
	50	0	20.38	20.53	20.48		0.0
DFT-s-OFDM 16QAM	1	1	20.77	21.03	20.92	0-1	0.0
CP-OFDM QPSK	1	1	20.32	20.44	20.56	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 55 of 155

Table H-109

NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.44	20.47	20.45	0	0.0
	1	13	20.40	20.63	20.48		0.0
	1	23	20.34	20.48	20.38		0.0
	12	0	20.46	20.53	20.45	0-1	0.0
	12	7	20.55	20.46	20.53	0	0.0
	12	13	20.46	20.54	20.43	0-1	0.0
	25	0	20.44	20.53	20.43		0.0
DFT-s-OFDM 16QAM	1	1	20.89	21.04	20.91	0-1	0.0
CP-OFDM QPSK	1	1	20.54	20.64	20.45	0-1.5	0.0

Table H-110

NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.96	0	0.0
	1	108	17.97		0.0
	1	214	17.92		0.0
	108	0	17.84	0-1	0.0
	108	54	17.83	0	0.0
	108	108	17.67	0-1	0.0
	216	0	17.80		0.0
DFT-s-OFDM 16QAM	1	1	17.86	0-1	0.0
CP-OFDM QPSK	1	1	17.91	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 56 of 155

Table H-111
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.18	0	0.0
	1	94	18.16		0.0
	1	186	18.04		0.0
	90	0	18.23	0-1	0.0
	90	49	18.20	0	0.0
	90	98	18.16	0-1	0.0
	180	0	18.27		0.0
DFT-s-OFDM 16QAM	1	1	18.46	0-1	0.0
CP-OFDM QPSK	1	1	18.23	0-1.5	0.0

Table H-112
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.25	0	0.0
	1	80	18.15		0.0
	1	158	18.35		0.0
	80	0	18.24	0-1	0.0
	80	40	18.21	0	0.0
	80	80	18.17	0-1	0.0
	160	0	18.20		0.0
DFT-s-OFDM 16QAM	1	1	18.44	0-1	0.0
CP-OFDM QPSK	1	1	18.34	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 57 of 155

Table H-113
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.36	0	0.0
	1	67	18.19		0.0
	1	131	18.14		0.0
	64	0	18.12	0-1	0.0
	64	35	18.24	0	0.0
	64	69	18.19	0-1	0.0
	128	0	18.24		0.0
DFT-s-OFDM 16QAM	1	1	18.46	0-1	0.0
CP-OFDM QPSK	1	1	18.40	0-1.5	0.0

Table H-114
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.95	18.16	17.98	0	0.0
	1	53	18.05	18.02	18.13		0.0
	1	104	18.10	18.12	18.13		0.0
	50	0	17.96	18.13	17.99	0-1	0.0
	50	28	18.16	18.20	18.19	0	0.0
	50	56	18.12	18.06	18.11	0-1	0.0
	100	0	18.09	18.16	18.09		0.0
DFT-s-OFDM 16QAM	1	1	18.39	18.42	18.42	0-1	0.0
CP-OFDM QPSK	1	1	17.99	18.23	17.92	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 58 of 155

Table H-115
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.09	18.15	17.95	0	0.0
	1	40	18.00	18.13	17.93		0.0
	1	77	18.08	17.90	17.91		0.0
	36	0	17.93	17.97	17.89	0-1	0.0
	36	22	18.17	18.11	17.92	0	0.0
	36	43	17.98	17.91	17.90	0-1	0.0
	75	0	17.89	18.00	17.91		0.0
DFT-s-OFDM 16QAM	1	1	18.43	18.30	18.37	0-1	0.0
CP-OFDM QPSK	1	1	18.12	18.18	18.10	0-1.5	0.0

Table H-116
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.12	18.20	18.19	0	0.0
	1	26	18.03	18.11	18.27		0.0
	1	50	17.97	18.27	17.98		0.0
	25	0	18.08	18.22	18.17	0-1	0.0
	25	14	17.99	18.16	18.25	0	0.0
	25	27	18.05	18.14	18.12	0-1	0.0
	50	0	18.15	18.17	18.20		0.0
DFT-s-OFDM 16QAM	1	1	18.65	18.43	18.43	0-1	0.0
CP-OFDM QPSK	1	1	18.25	18.26	18.20	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 59 of 155

Table H-117
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.02	18.18	18.09	0	0.0
	1	13	18.01	18.11	18.19		0.0
	1	23	17.96	18.10	17.99		0.0
	12	0	18.04	18.16	18.11	0-1	0.0
	12	7	18.06	18.20	18.25	0	0.0
	12	13	17.99	18.13	18.06	0-1	0.0
	25	0	18.06	18.19	18.09		0.0
DFT-s-OFDM 16QAM	1	1	18.49	18.42	18.55	0-1	0.0
CP-OFDM QPSK	1	1	18.18	18.31	18.16	0-1.5	0.0

H.2.3 NR Band n25

Table H-118
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	22.68	0	0.0
	1	94	22.56		0.0
	1	186	22.61		0.0
	90	0	21.65	0-1	1.0
	90	49	22.68	0	0.0
	90	98	21.68	0-1	1.0
	180	0	21.54		1.0
DFT-s-OFDM 16QAM	1	1	22.14	0-1	1.0
CP-OFDM QPSK	1	1	21.12	0-1.5	1.5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 60 of 155

Table H-119
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	22.82	0	0.0
	1	80	22.68		0.0
	1	158	22.74		0.0
	80	0	21.64	0-1	1.0
	80	40	22.65	0	0.0
	80	80	21.65	0-1	1.0
	160	0	21.65		1.0
DFT-s-OFDM 16QAM	1	1	22.16	0-1	1.0
CP-OFDM QPSK	1	1	21.23	0-1.5	1.5

Table H-120
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	22.80	0	0.0
	1	67	22.56		0.0
	1	131	22.73		0.0
	64	0	21.55	0-1	1.0
	64	35	22.61	0	0.0
	64	69	21.67	0-1	1.0
	128	0	21.67		1.0
DFT-s-OFDM 16QAM	1	1	22.16	0-1	1.0
CP-OFDM QPSK	1	1	21.26	0-1.5	1.5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 61 of 155

Table H-121
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	22.77	22.68	22.63	0	0.0
	1	53	22.78	22.56	22.63		0.0
	1	104	22.51	22.61	22.63		0.0
	50	0	21.65	21.51	21.54	0-1	1.0
	50	28	22.75	22.63	22.67	0	0.0
	50	56	21.59	21.53	21.54	0-1	1.0
	100	0	21.68	21.60	21.70		1.0
DFT-s-OFDM 16QAM	1	1	22.17	21.94	22.04	0-1	1.0
CP-OFDM QPSK	1	1	21.16	21.12	21.14	0-1.5	1.5

Table H-122
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	22.79	22.70	22.75	0	0.0
	1	40	22.75	22.64	22.69		0.0
	1	77	22.62	22.55	22.66		0.0
	36	0	21.66	21.55	21.55	0-1	1.0
	36	22	22.76	22.66	22.58	0	0.0
	36	43	21.61	21.51	21.56	0-1	1.0
	75	0	21.77	21.56	21.56		1.0
DFT-s-OFDM 16QAM	1	1	22.23	21.97	21.96	0-1	1.0
CP-OFDM QPSK	1	1	21.26	21.17	21.19	0-1.5	1.5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 62 of 155

Table H-123
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	22.85	22.65	22.63	0	0.0
	1	26	22.79	22.61	22.61		0.0
	1	50	22.76	22.65	22.59		0.0
	25	0	21.74	21.50	21.53	0-1	1.0
	25	14	22.82	22.61	22.66	0	0.0
	25	27	21.73	21.50	21.57	0-1	1.0
	50	0	21.73	21.48	21.55		1.0
DFT-s-OFDM 16QAM	1	1	22.15	22.07	22.07	0-1	1.0
CP-OFDM QPSK	1	1	21.29	21.19	21.09	0-1.5	1.5

Table H-124
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	22.76	22.64	22.44	0	0.0
	1	13	22.57	22.51	22.51		0.0
	1	23	22.64	22.61	22.57		0.0
	12	0	21.66	21.53	21.61	0-1	1.0
	12	7	22.64	22.68	22.62	0	0.0
	12	13	21.67	21.45	21.51	0-1	1.0
	25	0	21.65	21.49	21.52		1.0
DFT-s-OFDM 16QAM	1	1	22.17	22.06	22.00	0-1	1.0
CP-OFDM QPSK	1	1	21.31	21.28	21.12	0-1.5	1.5

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 63 of 155

Table H-125

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.07	0	0.0
	1	94	18.01		0.0
	1	186	17.91		0.0
	90	0	18.02	0-1	0.0
	90	49	18.00	0	0.0
	90	98	18.00	0-1	0.0
	180	0	18.08		0.0
DFT-s-OFDM 16QAM	1	1	18.45	0-1	0.0
CP-OFDM QPSK	1	1	18.20	0-1.5	0.0

Table H-126

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.08	0	0.0
	1	80	17.95		0.0
	1	158	18.03		0.0
	80	0	18.02	0-1	0.0
	80	40	18.01	0	0.0
	80	80	17.93	0-1	0.0
	160	0	18.02		0.0
DFT-s-OFDM 16QAM	1	1	18.43	0-1	0.0
CP-OFDM QPSK	1	1	18.25	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 64 of 155

Table H-127

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.07	0	0.0
	1	67	18.07		0.0
	1	131	18.10		0.0
	64	0	18.02	0-1	0.0
	64	35	17.99	0	0.0
	64	69	17.95	0-1	0.0
	128	0	18.01		0.0
DFT-s-OFDM 16QAM	1	1	18.43	0-1	0.0
CP-OFDM QPSK	1	1	18.25	0-1.5	0.0

Table H-128

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.93	17.97	18.05	0	0.0
	1	53	18.10	18.03	18.04		0.0
	1	104	17.93	17.84	17.96		0.0
	50	0	18.00	17.91	17.98	0-1	0.0
	50	28	18.05	17.97	18.13	0	0.0
	50	56	18.01	17.83	17.95	0-1	0.0
	100	0	18.09	17.95	18.08		0.0
DFT-s-OFDM 16QAM	1	1	18.48	18.28	18.40	0-1	0.0
CP-OFDM QPSK	1	1	18.22	17.95	18.00	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 65 of 155

Table H-129

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.36	18.05	18.13	0	0.0
	1	40	17.96	17.93	18.01		0.0
	1	77	17.96	17.89	18.08		0.0
	36	0	18.07	17.91	18.00	0-1	0.0
	36	22	18.11	18.04	18.13	0	0.0
	36	43	18.04	17.85	17.92	0-1	0.0
	75	0	18.00	17.84	18.02		0.0
DFT-s-OFDM 16QAM	1	1	18.56	18.32	18.27	0-1	0.0
CP-OFDM QPSK	1	1	18.26	18.11	18.04	0-1.5	0.0

Table H-130

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.23	18.08	17.97	0	0.0
	1	26	18.17	17.99	17.95		0.0
	1	50	18.13	17.95	18.07		0.0
	25	0	18.05	17.92	17.91	0-1	0.0
	25	14	18.15	17.91	17.91	0	0.0
	25	27	18.14	17.75	17.92	0-1	0.0
	50	0	18.12	17.83	17.93		0.0
DFT-s-OFDM 16QAM	1	1	18.61	18.26	18.33	0-1	0.0
CP-OFDM QPSK	1	1	18.30	18.02	17.93	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 66 of 155

Table H-131

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.07	18.00	17.95	0	0.0
	1	13	18.04	17.96	18.01		0.0
	1	23	18.06	17.91	17.91		0.0
	12	0	18.09	17.94	17.93	0-1	0.0
	12	7	18.09	18.01	17.98	0	0.0
	12	13	18.05	17.90	17.91	0-1	0.0
	25	0	18.04	17.93	17.86		0.0
DFT-s-OFDM 16QAM	1	1	18.58	18.42	18.34	0-1	0.0
CP-OFDM QPSK	1	1	18.31	18.11	18.01	0-1.5	0.0

Table H-132

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.25	0	0.0
	1	94	19.56		0.0
	1	186	19.42		0.0
	90	0	19.35	0-1	0.0
	90	49	19.50	0	0.0
	90	98	19.53	0-1	0.0
	180	0	19.40		0.0
DFT-s-OFDM 16QAM	1	1	19.81	0-1	0.0
CP-OFDM QPSK	1	1	19.41	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 67 of 155

Table H-133

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.45	0	0.0
	1	80	19.58		0.0
	1	158	19.58		0.0
	80	0	19.43	0-1	0.0
	80	40	19.48	0	0.0
	80	80	19.46	0-1	0.0
	160	0	19.36		0.0
DFT-s-OFDM 16QAM	1	1	19.71	0-1	0.0
CP-OFDM QPSK	1	1	19.39	0-1.5	0.0

Table H-134

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.46	0	0.0
	1	67	19.57		0.0
	1	131	19.60		0.0
	64	0	19.39	0-1	0.0
	64	35	19.58	0	0.0
	64	69	19.52	0-1	0.0
	128	0	19.37		0.0
DFT-s-OFDM 16QAM	1	1	19.81	0-1	0.0
CP-OFDM QPSK	1	1	19.39	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 68 of 155

Table H-135

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.24	19.43	19.54	0	0.0
	1	53	19.30	19.44	19.52		0.0
	1	104	19.33	19.46	19.42		0.0
	50	0	19.20	19.39	19.51	0-1	0.0
	50	28	19.30	19.53	19.52	0	0.0
	50	56	19.32	19.41	19.46	0-1	0.0
	100	0	19.33	19.57	19.58		0.0
DFT-s-OFDM 16QAM	1	1	19.68	19.66	19.89	0-1	0.0
CP-OFDM QPSK	1	1	19.34	19.39	19.52	0-1.5	0.0

Table H-136

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.31	19.46	19.49	0	0.0
	1	40	19.31	19.46	19.45		0.0
	1	77	19.34	19.48	19.42		0.0
	36	0	19.28	19.30	19.42	0-1	0.0
	36	22	19.27	19.57	19.60	0	0.0
	36	43	19.19	19.41	19.37	0-1	0.0
	75	0	19.17	19.42	19.45		0.0
DFT-s-OFDM 16QAM	1	1	19.77	19.87	19.85	0-1	0.0
CP-OFDM QPSK	1	1	19.42	19.52	19.58	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 69 of 155

Table H-137

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.34	19.29	19.41	0	0.0
	1	26	19.32	19.47	19.37		0.0
	1	50	19.31	19.46	19.35		0.0
	25	0	19.26	19.40	19.34	0-1	0.0
	25	14	19.39	19.57	19.45	0	0.0
	25	27	19.29	19.37	19.36	0-1	0.0
	50	0	19.26	19.42	19.34		0.0
DFT-s-OFDM 16QAM	1	1	19.73	19.72	19.84	0-1	0.0
CP-OFDM QPSK	1	1	19.32	19.34	19.44	0-1.5	0.0

Table H-138

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.26	19.56	19.21	0	0.0
	1	13	19.08	19.50	19.23		0.0
	1	23	19.08	19.48	19.24		0.0
	12	0	19.10	19.48	19.38	0-1	0.0
	12	7	19.14	19.56	19.42	0	0.0
	12	13	18.97	19.43	19.28	0-1	0.0
	25	0	19.08	19.45	19.35		0.0
DFT-s-OFDM 16QAM	1	1	19.63	19.94	19.87	0-1	0.0
CP-OFDM QPSK	1	1	19.30	19.62	19.43	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 70 of 155

Table H-139
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.21	0	0.0
	1	94	18.48		0.0
	1	186	18.48		0.0
	90	0	18.27	0-1	0.0
	90	49	18.45	0	0.0
	90	98	18.32	0-1	0.0
	180	0	18.27		0.0
DFT-s-OFDM 16QAM	1	1	18.64	0-1	0.0
CP-OFDM QPSK	1	1	18.38	0-1.5	0.0

Table H-140
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.29	0	0.0
	1	80	18.48		0.0
	1	158	18.46		0.0
	80	0	18.25	0-1	0.0
	80	40	18.50	0	0.0
	80	80	18.39	0-1	0.0
	160	0	18.24		0.0
DFT-s-OFDM 16QAM	1	1	18.58	0-1	0.0
CP-OFDM QPSK	1	1	18.39	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 71 of 155

Table H-141
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.31	0	0.0
	1	67	18.43		0.0
	1	131	18.46		0.0
	64	0	18.24	0-1	0.0
	64	35	18.46	0	0.0
	64	69	18.33	0-1	0.0
	128	0	18.35		0.0
DFT-s-OFDM 16QAM	1	1	18.73	0-1	0.0
CP-OFDM QPSK	1	1	18.34	0-1.5	0.0

Table H-142
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.45	18.48	18.69	0	0.0
	1	53	18.43	18.65	18.67		0.0
	1	104	18.46	18.65	18.60		0.0
	50	0	18.32	18.53	18.72	0-1	0.0
	50	28	18.56	18.66	18.77	0	0.0
	50	56	18.45	18.59	18.50	0-1	0.0
	100	0	18.48	18.66	18.75		0.0
DFT-s-OFDM 16QAM	1	1	18.84	18.87	19.03	0-1	0.0
CP-OFDM QPSK	1	1	18.50	18.59	18.75	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 72 of 155

Table H-143
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.51	18.60	18.76	0	0.0
	1	40	18.41	18.67	18.70		0.0
	1	77	18.47	18.60	18.66		0.0
	36	0	18.36	18.54	18.66	0-1	0.0
	36	22	18.37	18.73	18.79	0	0.0
	36	43	18.42	18.53	18.58	0-1	0.0
	75	0	18.33	18.55	18.65		0.0
DFT-s-OFDM 16QAM	1	1	18.84	19.01	19.09	0-1	0.0
CP-OFDM QPSK	1	1	18.55	18.65	18.76	0-1.5	0.0

Table H-144
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.47	18.65	18.73	0	0.0
	1	26	18.49	18.72	18.57		0.0
	1	50	18.56	18.62	18.60		0.0
	25	0	18.37	18.58	18.56	0-1	0.0
	25	14	18.54	18.64	18.61	0	0.0
	25	27	18.49	18.63	18.60	0-1	0.0
	50	0	18.49	18.57	18.58		0.0
DFT-s-OFDM 16QAM	1	1	18.88	19.04	19.02	0-1	0.0
CP-OFDM QPSK	1	1	18.50	18.71	18.61	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 73 of 155

Table H-145
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.28	18.67	18.47	0	0.0
	1	13	18.36	18.65	18.68		0.0
	1	23	18.29	18.61	18.51		0.0
	12	0	18.33	18.58	18.61	0-1	0.0
	12	7	18.42	18.68	18.70	0	0.0
	12	13	18.35	18.65	18.58	0-1	0.0
	25	0	18.33	18.59	18.61		0.0
DFT-s-OFDM 16QAM	1	1	18.88	19.00	19.03	0-1	0.0
CP-OFDM QPSK	1	1	18.45	18.94	18.67	0-1.5	0.0

H.2.4 NR Band n41

Table H-146
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)			
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.36	19.49	0	0.0	
	1	123	19.14	18.95		0.0	
	1	243	19.50	19.25		0.0	
	120	0	19.08	19.15	0-1	0.0	
	120	63	19.13	19.13	0	0.0	
	120	125	19.19	19.11	0-1	0.0	
	243	0	19.21	19.23		0.0	
DFT-s-OFDM 16QAM	1	1	19.24	19.46	0-1	0.0	
CP-OFDM QPSK	1	1	19.34	19.50	0-1.5	0.0	

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 74 of 155

Table H-147
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.28	19.16	0	0.0
	1	109	19.10	18.94		0.0
	1	215	19.38	19.15		0.0
	108	0	19.09	19.10	0-1	0.0
	108	55	19.12	19.01	0	0.0
	108	109	19.16	19.09	0-1	0.0
	216	0	19.23	19.10		0.0
DFT-s-OFDM 16QAM	1	1	19.26	19.20	0-1	0.0
CP-OFDM QPSK	1	1	19.32	19.30	0-1.5	0.0

Table H-148
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.26	19.12	0	0.0
	1	95	19.11	19.05		0.0
	1	187	19.29	19.25		0.0
	90	0	19.21	19.10	0-1	0.0
	90	50	19.19	19.09	0	0.0
	90	99	19.17	19.20	0-1	0.0
	180	0	19.15	19.18		0.0
DFT-s-OFDM 16QAM	1	1	19.27	19.16	0-1	0.0
CP-OFDM OPSK	1	1	19.32	19.42	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 75 of 155

Table H-149
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.48	19.48	19.27	0	0.0
	1	81	19.22	19.41	19.18		0.0
	1	160	19.45	19.31	19.40		0.0
	81	0	19.37	19.45	19.22	0-1	0.0
	81	41	19.30	19.50	19.30	0	0.0
	81	81	19.24	19.38	19.29	0-1	0.0
	162	0	19.36	19.50	19.40		0.0
DFT-s-OFDM 16QAM	1	1	19.36	19.37	19.19	0-1	0.0
CP-OFDM QPSK	1	1	19.48	19.50	19.36	0-1.5	0.0

Table H-150
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.48	19.34	19.15	0	0.0
	1	67	19.28	19.37	19.20		0.0
	1	131	19.45	19.45	19.47		0.0
	64	0	19.24	19.47	19.17	0-1	0.0
	64	35	19.26	19.35	19.35	0	0.0
	64	69	19.25	19.34	19.34	0-1	0.0
	128	0	19.25	19.34	19.18		0.0
DFT-s-OFDM 16QAM	1	1	19.33	19.34	19.11	0-1	0.0
CP-OFDM QPSK	1	1	19.50	19.38	19.24	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 76 of 155

Table H-151
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.43	19.43	19.41	19.30	0	0.0
	1	60	19.39	19.37	19.29	19.33		0.0
	1	117	19.48	19.49	19.37	19.48		0.0
	54	0	19.39	19.36	19.39	19.22	0-1	0.0
	54	27	19.29	19.38	19.32	19.30	0	0.0
	54	54	19.33	19.15	19.26	19.35	0-1	0.0
	108	0	19.35	19.26	19.33	19.31		0.0
DFT-s-OFDM 16QAM	1	1	19.43	19.43	19.40	19.19	0-1	0.0
CP-OFDM QPSK	1	1	19.49	19.49	19.48	19.40	0-1.5	0.0

Table H-152
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.45	19.29	19.30	19.14	0	0.0
	1	53	19.28	19.36	19.15	19.20		0.0
	1	104	19.31	19.43	19.10	19.35		0.0
	50	0	19.29	19.34	19.24	19.22	0-1	0.0
	50	28	19.39	19.41	19.26	19.29	0	0.0
	50	56	19.28	19.38	19.13	19.31	0-1	0.0
	100	0	19.39	19.33	19.31	19.28		0.0
DFT-s-OFDM 16QAM	1	1	19.35	19.19	19.30	19.09	0-1	0.0
CP-OFDM QPSK	1	1	19.43	19.22	19.34	19.18	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 77 of 155

Table H-153
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	19.33	19.20	19.25	19.10	19.10	0	0.0
	1	46	19.34	19.35	19.30	19.11	19.26		0.0
	1	90	19.23	19.35	19.13	19.05	19.24		0.0
	45	0	19.26	19.24	19.23	19.10	19.12	0-1	0.0
	45	22	19.32	19.30	19.28	19.12	19.03	0	0.0
	45	45	19.26	19.33	19.20	19.02	19.18	0-1	0.0
	90	0	19.28	19.21	19.22	19.08	19.13		0.0
DFT-s-OFDM 16QAM	1	1	19.37	19.32	19.28	19.15	19.17	0-1	0.0
CP-OFDM QPSK	1	1	19.40	19.29	19.35	19.22	19.28	0-1.5	0.0

Table H-154
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	19.41	19.35	19.48	19.25	19.33	0	0.0
	1	39	19.38	19.34	19.40	19.21	19.32		0.0
	1	76	19.30	19.46	19.36	19.24	19.40		0.0
	36	0	19.34	19.17	19.33	19.10	19.15	0-1	0.0
	36	21	19.32	19.20	19.32	19.19	19.30	0	0.0
	36	42	19.26	19.27	19.29	19.11	19.28	0-1	0.0
	75	0	19.29	19.26	19.25	19.07	19.22		0.0
DFT-s-OFDM 16QAM	1	1	19.44	19.24	19.37	19.21	19.25	0-1	0.0
CP-OFDM QPSK	1	1	19.49	19.32	19.49	19.34	19.38	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 78 of 155

Table H-155
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	19.49	19.36	19.47	19.26	19.41	0	0.0
	1	33	19.40	19.30	19.36	19.18	19.42		0.0
	1	63	19.32	19.42	19.39	19.25	19.48		0.0
	32	0	19.33	19.16	19.31	19.13	19.29	0-1	0.0
	32	17	19.31	19.29	19.34	19.18	19.41	0	0.0
	32	33	19.24	19.24	19.28	19.12	19.34	0-1	0.0
	64	0	19.25	19.39	19.30	19.04	19.30		0.0
DFT-s-OFDM 16QAM	1	1	19.38	19.49	19.38	19.21	19.37	0-1	0.0
CP-OFDM QPSK	1	1	19.47	19.47	19.45	19.44	19.43	0-1.5	0.0

Table H-156
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	19.41	19.25	19.40	19.23	19.24	0	0.0
	1	26	19.45	19.37	19.44	19.18	19.41		0.0
	1	49	19.40	19.36	19.36	19.16	19.40		0.0
	25	0	19.32	19.23	19.32	19.06	19.23	0-1	0.0
	25	13	19.40	19.40	19.40	19.13	19.35	0	0.0
	25	26	19.31	19.25	19.39	19.05	19.28	0-1	0.0
	50	0	19.42	19.36	19.45	19.20	19.32		0.0
DFT-s-OFDM 16QAM	1	1	19.32	19.18	19.33	19.06	19.18	0-1	0.0
CP-OFDM QPSK	1	1	19.39	19.37	19.44	19.22	19.25	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 79 of 155

Table H-157
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	19.45	19.25	19.40	19.23	19.30	0	0.0
	1	19	19.47	19.37	19.44	19.27	19.31		0.0
	1	36	19.41	19.38	19.38	19.21	19.34		0.0
	18	0	19.30	19.26	19.34	19.16	19.18	0-1	0.0
	18	10	19.48	19.35	19.44	19.34	19.43	0	0.0
	18	20	19.32	19.27	19.41	19.03	19.25	0-1	0.0
	36	0	19.34	19.23	19.36	19.15	19.22		0.0
DFT-s-OFDM 16QAM	1	1	19.36	19.25	19.40	19.19	19.25	0-1	0.0
CP-OFDM QPSK	1	1	19.43	19.43	19.46	19.27	19.30	0-1.5	0.0

Table H-158
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	19.49	19.45	19.49	19.44	19.39	0	0.0
	1	12	19.48	19.38	19.40	19.40	19.44		0.0
	1	22	19.44	19.45	19.44	19.47	19.50		0.0
	12	0	19.33	19.26	19.29	19.33	19.33	0-1	0.0
	12	6	19.42	19.37	19.36	19.46	19.50	0	0.0
	12	12	19.39	19.33	19.34	19.30	19.38	0-1	0.0
	24	0	19.32	19.30	19.36	19.30	19.32		0.0
DFT-s-OFDM 16QAM	1	1	19.40	19.37	19.42	19.43	19.36	0-1	0.0
CP-OFDM QPSK	1	1	19.49	19.42	19.50	19.44	19.46	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 80 of 155

Table H-159
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)			
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.11	17.25	0	0.0	
	1	123	16.81	16.79		0.0	
	1	243	17.22	17.13		0.0	
	120	0	16.77	16.92	0-1	0.0	
	120	63	16.88	16.83	0	0.0	
	120	125	16.99	16.86	0-1	0.0	
	243	0	17.03	16.91		0.0	
DFT-s-OFDM 16QAM	1	1	17.12	17.19	0-1	0.0	
CP-OFDM QPSK	1	1	17.04	17.20	0-1.5	0.0	

Table H-160
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.06	17.06	0	0.0
	1	109	16.82	16.72		0.0
	1	215	17.21	16.97		0.0
	108	0	16.85	16.78	0-1	0.0
	108	55	16.86	16.84	0	0.0
	108	109	16.96	16.75	0-1	0.0
	216	0	16.93	16.94		0.0
DFT-s-OFDM 16QAM	1	1	17.03	17.08	0-1	0.0
CP-OFDM QPSK	1	1	17.11	17.11	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 81 of 155

Table H-161
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.93	16.90	0	0.0
	1	95	16.75	16.87		0.0
	1	187	17.02	16.96		0.0
	90	0	16.89	16.87	0-1	0.0
	90	50	16.87	16.95	0	0.0
	90	99	16.97	16.87	0-1	0.0
	180	0	16.93	16.91		0.0
DFT-s-OFDM 16QAM	1	1	16.96	16.80	0-1	0.0
CP-OFDM QPSK	1	1	17.05	16.90	0-1.5	0.0

Table H-162
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.99	17.08	16.85	0	0.0
	1	81	16.78	17.02	16.70		0.0
	1	160	17.05	16.96	17.08		0.0
	81	0	16.87	17.04	16.72	0-1	0.0
	81	41	16.83	17.09	16.84	0	0.0
	81	81	16.87	17.04	16.84	0-1	0.0
	162	0	16.86	17.10	16.88		0.0
DFT-s-OFDM 16QAM	1	1	17.00	17.03	16.77	0-1	0.0
CP-OFDM QPSK	1	1	17.08	17.14	16.80	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 82 of 155

Table H-163
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.10	17.30	16.90	0	0.0
	1	67	17.00	17.31	16.89		0.0
	1	131	17.24	17.14	17.18		0.0
	64	0	17.06	17.26	16.80	0-1	0.0
	64	35	17.07	17.39	16.94	0	0.0
	64	69	17.06	17.16	16.96	0-1	0.0
	128	0	17.08	17.29	16.97		0.0
DFT-s-OFDM 16QAM	1	1	17.22	17.28	16.85	0-1	0.0
CP-OFDM QPSK	1	1	17.26	17.36	16.92	0-1.5	0.0

Table H-164
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.29	17.17	17.46	17.01	0	0.0
	1	60	17.04	17.23	17.19	16.94		0.0
	1	117	17.25	17.50	17.15	17.27		0.0
	54	0	17.16	17.15	17.24	16.93	0-1	0.0
	54	27	17.14	17.21	17.25	17.01	0	0.0
	54	54	17.12	17.38	17.07	17.06	0-1	0.0
	108	0	17.16	17.29	17.20	17.07		0.0
DFT-s-OFDM 16QAM	1	1	17.25	17.15	17.31	16.95	0-1	0.0
CP-OFDM QPSK	1	1	17.32	17.21	17.38	17.11	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 83 of 155

Table H-165
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.12	16.92	17.23	16.85	0	0.0
	1	53	17.03	17.18	17.04	16.91		0.0
	1	104	16.95	17.39	16.93	17.08		0.0
	50	0	17.02	17.11	17.15	16.85	0-1	0.0
	50	28	17.12	17.28	17.14	16.98	0	0.0
	50	56	17.00	17.25	16.90	16.99	0-1	0.0
	100	0	17.13	17.30	17.17	16.97		0.0
DFT-s-OFDM 16QAM	1	1	17.04	16.95	17.15	16.86	0-1	0.0
CP-OFDM QPSK	1	1	17.19	17.14	17.36	16.89	0-1.5	0.0

Table H-166
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.05	16.96	17.23	17.00	16.86	0	0.0
	1	46	17.13	17.14	17.32	16.94	17.06		0.0
	1	90	16.94	17.22	17.18	16.78	17.08		0.0
	45	0	16.99	17.01	17.19	17.03	16.87	0-1	0.0
	45	22	17.06	17.15	17.31	16.93	16.98	0	0.0
	45	45	17.03	17.06	17.23	16.85	16.94	0-1	0.0
	90	0	17.05	17.02	17.25	16.92	16.90		0.0
DFT-s-OFDM 16QAM	1	1	17.14	17.02	17.22	17.10	16.83	0-1	0.0
CP-OFDM QPSK	1	1	17.18	17.08	17.36	17.14	16.90	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 84 of 155

Table H-167
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.20	17.18	17.42	17.19	16.99	0	0.0
	1	39	17.11	17.13	17.30	16.97	17.10		0.0
	1	76	17.00	17.30	17.32	16.92	17.13		0.0
	36	0	17.01	17.03	17.18	16.94	16.88	0-1	0.0
	36	21	17.07	17.12	17.23	16.94	16.99	0	0.0
	36	42	16.99	17.14	17.21	16.93	16.98	0-1	0.0
	75	0	17.05	17.06	17.24	16.94	16.94		0.0
DFT-s-OFDM 16QAM	1	1	17.22	17.03	17.27	17.07	16.95	0-1	0.0
CP-OFDM QPSK	1	1	17.36	17.12	17.37	17.14	17.12	0-1.5	0.0

Table H-168
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n41									
25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.16	17.02	17.40	17.04	17.11	0	0.0
	1	33	17.09	17.08	17.37	16.96	17.05		0.0
	1	63	17.10	17.21	17.36	17.00	17.12		0.0
	32	0	17.02	16.98	17.26	16.90	16.90	0-1	0.0
	32	17	17.09	17.06	17.31	16.98	17.03	0	0.0
	32	33	17.04	17.08	17.27	16.91	16.99	0-1	0.0
	64	0	17.04	17.02	17.29	16.95	16.99		0.0
DFT-s-OFDM 16QAM	1	1	17.12	17.02	17.41	17.04	17.01	0-1	0.0
CP-OFDM QPSK	1	1	17.34	17.13	17.50	17.11	17.05	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 85 of 155

Table H-169
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.08	17.05	17.24	17.12	16.95	0	0.0
	1	26	17.13	17.08	17.38	17.13	17.00		0.0
	1	49	17.03	17.10	17.23	17.12	17.10		0.0
	25	0	17.01	16.93	17.25	16.98	16.89	0-1	0.0
	25	13	17.09	17.05	17.24	17.03	16.97	0	0.0
	25	26	17.04	17.01	17.17	16.95	16.94	0-1	0.0
	50	0	17.12	17.09	17.24	17.05	17.01		0.0
DFT-s-OFDM 16QAM	1	1	17.03	16.92	17.15	17.01	16.92	0-1	0.0
CP-OFDM QPSK	1	1	17.19	16.99	17.22	17.05	17.00	0-1.5	0.0

Table H-170
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n41									
15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.16	17.10	17.36	17.07	17.07	0	0.0
	1	19	17.17	17.07	17.41	17.13	17.12		0.0
	1	36	17.12	17.16	17.30	17.09	17.13		0.0
	18	0	17.04	16.93	17.17	17.03	16.85	0-1	0.0
	18	10	17.20	17.15	17.27	17.18	17.00	0	0.0
	18	20	17.01	16.97	17.19	17.01	16.94	0-1	0.0
	36	0	17.01	17.00	17.19	17.01	16.90		0.0
DFT-s-OFDM 16QAM	1	1	17.09	17.00	17.23	17.09	16.95	0-1	0.0
CP-OFDM QPSK	1	1	17.24	17.07	17.38	17.15	17.06	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 86 of 155

Table H-171
NR Band n41 PC2 Ant F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.15	17.08	17.31	17.02	17.09	0	0.0
	1	12	17.11	17.02	17.26	17.00	16.98		0.0
	1	22	17.06	17.08	17.36	17.05	17.03		0.0
	12	0	17.03	17.01	17.19	16.88	16.88	0-1	0.0
	12	6	17.16	17.05	17.25	17.00	16.86	0	0.0
	12	12	17.05	17.05	17.15	16.91	16.95	0-1	0.0
	24	0	17.06	17.04	17.17	16.93	16.88		0.0
DFT-s-OFDM 16QAM	1	1	17.02	17.11	17.18	16.95	16.93	0-1	0.0
CP-OFDM QPSK	1	1	17.14	17.23	17.44	17.03	17.06	0-1.5	0.0

Table H-172
NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	19.37	19.61
SRS #3 Ant E	16.17	15.81
SRS #4 Ant D	16.54	16.41

Table H-173
NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	19.27	19.61
SRS #3 Ant E	16.01	15.78
SRS #4 Ant D	16.63	16.52

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 87 of 155

Table H-174

NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	19.12	19.60
SRS #3 Ant E	15.98	15.63
SRS #4 Ant D	16.52	16.48

Table H-175

NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	19.28	19.61	19.74
SRS #3 Ant E	15.98	16.21	15.51
SRS #4 Ant D	16.41	16.61	16.36

Table H-176

NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	19.45	19.77	19.91
SRS #3 Ant E	16.22	16.40	15.92
SRS #4 Ant D	16.36	16.51	16.31

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 88 of 155

Table H-177

NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	19.45	19.70	19.70	19.95
SRS #3 Ant E	16.20	16.42	16.20	15.96
SRS #4 Ant D	16.28	16.59	16.44	16.34

Table H-178

NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
S #2 Ant B	19.40	19.60	19.66	19.92
S #3 Ant E	16.12	16.31	16.10	15.79
S #4 Ant D	16.52	16.78	16.55	16.54

Table H-179

NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.24	19.36	19.59	19.42	19.77
SRS #3 Ant E	15.98	16.10	16.22	15.86	15.68
SRS #4 Ant D	16.16	16.34	16.43	16.13	16.17

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 89 of 155

Table H-180
NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.20	19.38	19.67	19.55	19.84
SRS #3 Ant E	16.05	16.23	16.31	15.93	15.84
SRS #4 Ant D	16.51	16.65	16.75	16.42	16.48

Table H-181
NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.25	19.43	19.63	19.47	19.84
SRS #3 Ant E	16.05	16.16	16.32	15.93	15.76
SRS #4 Ant D	16.29	16.32	16.54	16.22	16.25

Table H-182
NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.20	19.27	19.55	19.40	19.86
SRS #3 Ant E	15.98	16.20	16.25	15.86	15.66
SRS #4 Ant D	16.14	16.34	16.38	16.14	16.18

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 90 of 155

Table H-183

NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.22	19.25	19.52	19.42	19.90
SRS #3 Ant E	16.06	16.18	16.17	15.86	15.67
SRS #4 Ant D	16.21	16.24	16.40	16.05	16.12

Table H-184

NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.25	19.29	19.55	19.41	19.90
SRS #3 Ant E	16.00	16.21	16.28	15.88	15.73
SRS #4 Ant D	16.23	16.25	16.42	16.08	16.26

Table H-185

NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	16.79	17.12
SRS #3 Ant E	13.67	13.14
SRS #4 Ant D	14.12	13.80

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 91 of 155

Table H-186
NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	16.68	17.07
SRS #3 Ant E	13.62	13.11
SRS #4 Ant D	14.12	14.03

Table H-187
NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	16.66	17.03
SRS #3 Ant E	13.47	13.11
SRS #4 Ant D	14.05	13.86

Table H-188
NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	16.72	17.08	17.27
SRS #3 Ant E	13.47	13.68	13.20
SRS #4 Ant D	13.88	14.23	13.80

Table H-189
NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 92 of 155

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	16.84	17.23	17.44
SRS #3 Ant E	13.59	13.89	13.37
SRS #4 Ant D	13.72	14.17	13.70

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 93 of 155

Table H-190
NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	16.90	17.13	17.19	17.46
SRS #3 Ant E	13.64	13.86	13.78	13.27
SRS #4 Ant D	13.75	14.18	13.89	13.83

Table H-191
NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
S #2 Ant B	16.69	17.12	17.15	17.39
S #3 Ant E	13.51	13.78	13.59	13.15
S #4 Ant D	14.00	14.32	13.94	13.86

Table H-192
NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	16.67	16.87	17.04	16.93	17.22
SRS #3 Ant E	13.40	13.61	13.82	13.38	13.16
SRS #4 Ant D	13.63	13.82	13.98	13.56	13.58

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 94 of 155

Table H-193
NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	16.67	16.90	17.09	17.00	17.38
SRS #3 Ant E	13.46	13.75	13.82	13.44	13.28
SRS #4 Ant D	13.98	14.19	14.27	13.94	13.87

Table H-194
NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	16.77	16.86	17.09	17.01	17.24
SRS #3 Ant E	13.53	13.72	13.89	13.34	13.23
SRS #4 Ant D	13.73	13.90	14.12	13.59	13.64

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 95 of 155

Table H-195

NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	16.66	16.77	17.01	16.91	17.28
SRS #3 Ant E	13.43	13.65	13.83	13.37	13.10
SRS #4 Ant D	13.67	13.77	13.91	13.55	13.59

Table H-196

NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	16.74	16.72	17.03	16.87	17.27
SRS #3 Ant E	13.46	13.63	13.83	13.37	13.26
SRS #4 Ant D	13.63	13.74	14.05	13.51	13.58

Table H-197

NR Band n41 PC2 Ant B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	16.83	16.78	17.09	16.92	17.25
SRS #3 Ant E	13.51	13.58	13.83	13.36	13.15
SRS #4 Ant D	13.64	13.69	14.06	13.62	13.66

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 96 of 155

Table H-198
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	21.96	21.98	0	0.0
	1	123	21.58	21.61		0.0
	1	243	21.96	22.00		0.0
	120	0	21.68	21.60	0-1	0.0
	120	63	21.63	21.66	0	0.0
	120	125	21.62	21.68	0-1	0.0
	243	0	21.72	21.70		0.0
DFT-s-OFDM 16QAM	1	1	21.86	21.76	0-1	0.0
CP-OFDM QPSK	1	1	21.49	21.92	0-1.5	0.0

Table H-199
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	21.98	21.85	0	0.0
	1	109	21.53	21.58		0.0
	1	215	21.90	22.00		0.0
	108	0	21.68	21.59	0-1	0.0
	108	55	21.70	21.72	0	0.0
	108	109	21.64	21.71	0-1	0.0
	216	0	21.78	21.81		0.0
DFT-s-OFDM 16QAM	1	1	21.84	21.74	0-1	0.0
CP-OFDM QPSK	1	1	21.52	21.81	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 97 of 155

Table H-200
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	21.89	21.66	0	0.0
	1	95	21.66	21.71		0.0
	1	187	21.70	21.94		0.0
	90	0	21.75	21.64	0-1	0.0
	90	50	21.71	21.83	0	0.0
	90	99	21.62	21.88	0-1	0.0
	180	0	21.68	21.75		0.0
DFT-s-OFDM 16QAM	1	1	21.82	21.73	0-1	0.0
CP-OFDM QPSK	1	1	21.75	21.81	0-1.5	0.0

Table H-201
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	21.80	21.87	21.64	0	0.0
	1	81	21.52	21.82	21.60		0.0
	1	160	21.63	21.84	21.90		0.0
	81	0	21.69	21.79	21.54	0-1	0.0
	81	41	21.68	21.97	21.72	0	0.0
	81	81	21.57	21.76	21.79	0-1	0.0
	162	0	21.74	21.96	21.80		0.0
DFT-s-OFDM 16QAM	1	1	21.83	21.73	21.69	0-1	0.0
CP-OFDM QPSK	1	1	21.47	21.90	21.67	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 98 of 155

Table H-202
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	21.98	21.84	21.81	0	0.0
	1	67	21.76	21.80	21.88		0.0
	1	131	21.81	21.86	22.00		0.0
	64	0	21.80	21.77	21.79	0-1	0.0
	64	35	21.89	21.90	21.98	0	0.0
	64	69	21.74	21.83	21.94	0-1	0.0
	128	0	21.80	21.75	21.92		0.0
DFT-s-OFDM 16QAM	1	1	21.84	21.76	21.74	0-1	0.0
CP-OFDM QPSK	1	1	21.65	21.76	21.81	0-1.5	0.0

Table H-203
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	21.91	21.67	21.95	21.85	0	0.0
	1	60	21.66	21.72	21.68	21.64		0.0
	1	117	21.78	21.98	21.70	21.54		0.0
	54	0	21.78	21.61	21.79	21.66	0-1	0.0
	54	27	21.77	21.66	21.77	21.55	0	0.0
	54	54	21.70	21.84	21.78	21.44	0-1	0.0
	108	0	21.71	21.65	21.81	21.55		0.0
DFT-s-OFDM 16QAM	1	1	21.80	21.65	21.93	21.72	0-1	0.0
CP-OFDM QPSK	1	1	21.45	21.69	21.90	21.77	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 99 of 155

Table H-204

NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	21.79	21.47	21.84	21.73	0	0.0
	1	53	21.61	21.56	21.63	21.76		0.0
	1	104	21.57	21.76	21.59	21.92		0.0
	50	0	21.66	21.50	21.68	21.68	0-1	0.0
	50	28	21.64	21.70	21.65	21.80	0	0.0
	50	56	21.61	21.67	21.53	21.83	0-1	0.0
	100	0	21.69	21.67	21.67	21.81		0.0
DFT-s-OFDM 16QAM	1	1	21.58	21.37	21.63	21.57	0-1	0.0
CP-OFDM QPSK	1	1	21.29	21.43	21.68	21.62	0-1.5	0.0

Table H-205

NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	21.88	21.65	21.79	21.78	21.73	0	0.0
	1	46	21.83	21.69	21.94	21.80	21.96		0.0
	1	90	21.63	21.79	21.87	21.70	21.99		0.0
	45	0	21.78	21.55	21.88	21.70	21.85	0-1	0.0
	45	22	21.77	21.62	21.87	21.74	21.92	0	0.0
	45	45	21.73	21.72	21.82	21.71	22.01	0-1	0.0
	90	0	21.75	21.63	21.81	21.69	21.92		0.0
DFT-s-OFDM 16QAM	1	1	21.73	21.67	21.81	21.77	21.82	0-1	0.0
CP-OFDM QPSK	1	1	21.31	21.74	21.84	21.82	21.92	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 100 of 155

Table H-206

NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	21.92	21.60	21.87	21.84	21.82	0	0.0
	1	39	21.75	21.63	21.84	21.71	21.92		0.0
	1	76	21.78	21.82	21.91	21.81	22.00		0.0
	36	0	21.58	21.53	21.77	21.64	21.81	0-1	0.0
	36	21	21.86	21.53	21.89	21.70	21.91	0	0.0
	36	42	21.77	21.65	21.87	21.68	21.93	0-1	0.0
	75	0	21.68	21.62	21.83	21.65	21.88		0.0
DFT-s-OFDM 16QAM	1	1	21.64	21.57	21.83	21.75	21.80	0-1	0.0
CP-OFDM QPSK	1	1	21.17	21.65	21.99	21.85	21.89	0-1.5	0.0

Table H-207

NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	21.95	21.72	21.92	21.89	21.94	0	0.0
	1	33	21.82	21.69	21.92	21.76	21.93		0.0
	1	63	21.68	21.80	21.90	21.82	21.99		0.0
	32	0	21.72	21.54	21.75	21.69	21.82	0-1	0.0
	32	17	21.86	21.67	21.83	21.72	21.94	0	0.0
	32	33	21.75	21.68	21.82	21.69	21.92	0-1	0.0
	64	0	21.75	21.61	21.82	21.68	21.85		0.0
DFT-s-OFDM 16QAM	1	1	21.89	21.61	21.83	21.82	21.86	0-1	0.0
CP-OFDM QPSK	1	1	21.53	21.78	21.98	21.85	21.82	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 101 of 155

Table H-208
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	21.96	21.54	21.85	21.62	21.87	0	0.0
	1	26	21.86	21.70	21.88	21.71	21.93		0.0
	1	49	21.74	21.72	21.76	21.68	21.99		0.0
	25	0	21.63	21.51	21.69	21.48	21.79	0-1	0.0
	25	13	21.78	21.63	21.78	21.62	21.92	0	0.0
	25	26	21.70	21.49	21.70	21.52	21.89	0-1	0.0
	50	0	21.71	21.68	21.82	21.63	21.96		0.0
DFT-s-OFDM 16QAM	1	1	21.65	21.50	21.68	21.50	21.78	0-1	0.0
CP-OFDM QPSK	1	1	21.31	21.64	21.74	21.57	21.60	0-1.5	0.0

Table H-209
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	21.97	21.67	21.89	21.76	21.92	0	0.0
	1	19	21.83	21.69	21.81	21.67	21.97		0.0
	1	36	21.86	21.70	21.87	21.74	22.00		0.0
	18	0	21.66	21.48	21.76	21.58	21.82	0-1	0.0
	18	10	21.85	21.71	21.83	21.79	22.00	0	0.0
	18	20	21.80	21.57	21.77	21.64	21.94	0-1	0.0
	36	0	21.61	21.51	21.76	21.58	21.89		0.0
DFT-s-OFDM 16QAM	1	1	21.60	21.53	21.86	21.66	21.88	0-1	0.0
CP-OFDM QPSK	1	1	21.30	21.69	21.93	21.71	21.73	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 102 of 155

Table H-210
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	21.98	21.70	21.93	21.77	21.94	0	0.0
	1	12	21.96	21.59	21.81	21.71	22.00		0.0
	1	22	22.00	21.57	21.89	21.70	22.00		0.0
	12	0	21.59	21.44	21.77	21.54	21.82	0-1	0.0
	12	6	21.97	21.49	21.89	21.66	22.00	0	0.0
	12	12	21.61	21.51	21.80	21.61	21.77	0-1	0.0
	24	0	21.58	21.49	21.76	21.56	21.75		0.0
DFT-s-OFDM 16QAM	1	1	21.53	21.53	21.84	21.63	21.77	0-1	0.0
CP-OFDM QPSK	1	1	21.99	21.67	21.97	21.76	21.54	0-1.5	0.0

Table H-211
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.90	20.97	0	0.0
	1	123	20.58	20.59		0.0
	1	243	20.91	20.98		0.0
	120	0	20.63	20.57	0-1	0.0
	120	63	20.57	20.68	0	0.0
	120	125	20.65	20.72	0-1	0.0
	243	0	20.75	20.75		0.0
DFT-s-OFDM 16QAM	1	1	20.80	20.78	0-1	0.0
CP-OFDM QPSK	1	1	20.90	20.91	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 103 of 155

Table H-212
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.91	20.86	0	0.0
	1	109	20.50	20.55		0.0
	1	215	20.83	21.00		0.0
	108	0	20.64	20.57	0-1	0.0
	108	55	20.66	20.70	0	0.0
	108	109	20.57	20.71	0-1	0.0
	216	0	20.69	20.68		0.0
DFT-s-OFDM 16QAM	1	1	20.86	20.78	0-1	0.0
CP-OFDM QPSK	1	1	20.94	20.84	0-1.5	0.0

Table H-213
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.76	20.65	0	0.0
	1	95	20.51	20.71		0.0
	1	187	20.71	20.97		0.0
	90	0	20.71	20.66	0-1	0.0
	90	50	20.63	20.74	0	0.0
	90	99	20.58	20.87	0-1	0.0
	180	0	20.65	20.68		0.0
DFT-s-OFDM 16QAM	1	1	20.71	20.72	0-1	0.0
CP-OFDM QPSK	1	1	20.92	20.88	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 104 of 155

Table H-214
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.82	20.78	20.69	0	0.0
	1	81	20.55	20.71	20.58		0.0
	1	160	20.64	20.78	20.95		0.0
	81	0	20.65	20.71	20.50	0-1	0.0
	81	41	20.66	20.88	20.71	0	0.0
	81	81	20.48	20.83	20.79	0-1	0.0
	162	0	20.67	20.86	20.62		0.0
DFT-s-OFDM 16QAM	1	1	20.72	20.75	20.62	0-1	0.0
CP-OFDM QPSK	1	1	20.82	20.82	20.73	0-1.5	0.0

Table H-215
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.97	20.77	20.83	0	0.0
	1	67	20.68	20.80	20.85		0.0
	1	131	20.87	20.93	20.96		0.0
	64	0	20.90	20.76	20.78	0-1	0.0
	64	35	20.82	20.97	20.99	0	0.0
	64	69	20.70	20.79	20.94	0-1	0.0
	128	0	20.80	20.75	20.95		0.0
DFT-s-OFDM 16QAM	1	1	20.88	20.82	20.75	0-1	0.0
CP-OFDM QPSK	1	1	20.98	20.85	20.84	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 105 of 155

Table H-216
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	20.93	20.68	20.80	20.79	0	0.0
	1	60	20.67	20.72	20.69	20.83		0.0
	1	117	20.82	20.96	20.83	21.00		0.0
	54	0	20.84	20.63	20.86	20.81	0-1	0.0
	54	27	20.74	20.76	20.74	20.80	0	0.0
	54	54	20.73	20.78	20.67	20.88	0-1	0.0
	108	0	20.73	20.68	20.73	20.77		0.0
DFT-s-OFDM 16QAM	1	1	20.89	20.65	20.81	20.76	0-1	0.0
CP-OFDM QPSK	1	1	20.95	20.72	20.86	20.76	0-1.5	0.0

Table H-217
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	20.73	20.48	20.74	20.61	0	0.0
	1	53	20.58	20.61	20.65	20.73		0.0
	1	104	20.53	20.77	20.78	20.87		0.0
	50	0	20.70	20.47	20.51	20.66	0-1	0.0
	50	28	20.70	20.64	20.58	20.87	0	0.0
	50	56	20.51	20.63	20.63	20.74	0-1	0.0
	100	0	20.72	20.67	20.57	20.84		0.0
DFT-s-OFDM 16QAM	1	1	20.68	20.42	20.61	20.59	0-1	0.0
CP-OFDM QPSK	1	1	20.86	20.47	20.60	20.65	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 106 of 155

Table H-218
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.85	20.58	20.79	20.81	20.78	0	0.0
	1	46	20.91	20.67	21.00	20.77	20.96		0.0
	1	90	20.66	20.75	20.83	20.74	20.99		0.0
	45	0	20.75	20.57	20.84	20.71	20.87	0-1	0.0
	45	22	20.85	20.72	20.88	20.74	20.99	0	0.0
	45	45	20.72	20.70	20.87	20.72	20.95	0-1	0.0
	90	0	20.78	20.66	20.84	20.69	20.84		0.0
DFT-s-OFDM 16QAM	1	1	20.89	20.55	20.84	20.73	20.82	0-1	0.0
CP-OFDM QPSK	1	1	20.98	20.72	20.93	20.84	20.90	0-1.5	0.0

Table H-219
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.88	20.69	20.89	20.80	20.88	0	0.0
	1	39	20.83	20.64	20.93	20.71	20.94		0.0
	1	76	20.75	20.68	20.86	20.68	20.98		0.0
	36	0	20.80	20.48	20.74	20.64	20.80	0-1	0.0
	36	21	20.81	20.61	20.78	20.59	20.92	0	0.0
	36	42	20.75	20.65	20.77	20.63	20.84	0-1	0.0
	75	0	20.76	20.59	20.75	20.63	20.79		0.0
DFT-s-OFDM 16QAM	1	1	20.92	20.56	20.78	20.77	20.84	0-1	0.0
CP-OFDM QPSK	1	1	20.93	20.76	20.83	20.91	20.94	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 107 of 155

Table H-220
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.92	20.58	20.89	20.83	20.93	0	0.0
	1	33	20.83	20.71	20.92	20.76	20.95		0.0
	1	63	20.78	20.78	20.92	20.83	21.12		0.0
	32	0	20.76	20.61	20.74	20.67	20.82	0-1	0.0
	32	17	20.86	20.60	20.81	20.74	20.99	0	0.0
	32	33	20.75	20.61	20.78	20.69	20.95	0-1	0.0
	64	0	20.79	20.53	20.79	20.68	20.88		0.0
DFT-s-OFDM 16QAM	1	1	20.97	20.64	20.79	20.76	20.87	0-1	0.0
CP-OFDM QPSK	1	1	20.96	20.75	20.88	20.92	20.93	0-1.5	0.0

Table H-221
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.81	20.56	20.77	20.64	20.85	0	0.0
	1	26	20.85	20.60	20.87	20.67	20.95		0.0
	1	49	20.69	20.63	20.76	20.63	20.92		0.0
	25	0	20.77	20.44	20.72	20.52	20.81	0-1	0.0
	25	13	20.78	20.61	20.82	20.63	20.99	0	0.0
	25	26	20.67	20.53	20.72	20.56	20.83	0-1	0.0
	50	0	20.77	20.60	20.84	20.67	20.90		0.0
DFT-s-OFDM 16QAM	1	1	20.72	20.53	20.74	20.56	20.72	0-1	0.0
CP-OFDM QPSK	1	1	20.79	20.48	20.76	20.70	20.77	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 108 of 155

Table H-222
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.97	20.65	20.97	20.70	20.87	0	0.0
	1	19	20.95	20.73	20.85	20.73	20.99		0.0
	1	36	20.89	20.69	20.92	20.76	20.93		0.0
	18	0	20.77	20.60	20.76	20.60	20.74	0-1	0.0
	18	10	20.94	20.67	20.84	20.74	20.89	0	0.0
	18	20	20.77	20.56	20.75	20.66	20.88	0-1	0.0
	36	0	20.79	20.48	20.74	20.54	20.88		0.0
DFT-s-OFDM 16QAM	1	1	20.82	20.60	20.78	20.74	20.88	0-1	0.0
CP-OFDM QPSK	1	1	20.97	20.70	20.83	20.72	20.95	0-1.5	0.0

Table H-223
NR Band n41 PC2 Ant B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.97	20.65	20.87	20.74	20.97	0	0.0
	1	12	20.95	20.57	20.89	20.66	20.96		0.0
	1	22	21.00	20.64	20.94	20.75	20.99		0.0
	12	0	20.85	20.54	20.67	20.58	20.87	0-1	0.0
	12	6	20.94	20.55	20.79	20.65	21.00	0	0.0
	12	12	20.89	20.52	20.74	20.63	20.95	0-1	0.0
	24	0	20.87	20.46	20.72	20.56	20.93		0.0
DFT-s-OFDM 16QAM	1	1	20.94	20.60	20.75	20.65	20.96	0-1	0.0
CP-OFDM QPSK	1	1	20.88	20.75	20.90	20.80	21.00	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 109 of 155

Table H-224

NR Band n41 PC2 Ant F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	19.17	18.89
SRS #3 Ant D	18.60	18.25
SRS #4 Ant E	16.45	15.66

Table H-225

NR Band n41 PC2 Ant F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	19.17	18.96
SRS #3 Ant D	18.53	18.28
SRS #4 Ant E	16.60	15.50

Table H-226

NR Band n41 PC2 Ant F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	19.13	18.89
SRS #3 Ant D	18.52	18.18
SRS #4 Ant E	16.53	15.49

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 110 of 155

Table H-227

NR Band n41 PC2 Ant F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant F	19.16	19.19	18.89
SRS #3 Ant D	18.57	18.42	18.21
SRS #4 Ant E	15.97	16.32	15.54

Table H-228

NR Band n41 PC2 Ant F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant F	19.48	19.45	19.14
SRS #3 Ant D	18.87	18.47	18.39
SRS #4 Ant E	15.96	16.43	15.71

Table H-229

NR Band n41 PC2 Ant F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	19.45	19.25	19.22	19.16
SRS #3 Ant D	18.72	18.70	18.69	18.55
SRS #4 Ant E	16.05	16.52	16.20	15.61

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 111 of 155

Table H-230

NR Band n41 PC2 Ant F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	19.39	19.29	19.15	19.08
SRS #3 Ant D	18.65	18.67	18.42	18.27
SRS #4 Ant E	16.08	16.64	15.78	15.46

Table H-231

NR Band n41 PC2 Ant F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	19.45	19.10	19.03	19.00	18.88
SRS #3 Ant D	18.56	18.49	18.44	18.53	18.34
SRS #4 Ant E	16.28	16.36	16.15	15.84	15.32

Table H-232

NR Band n41 PC2 Ant F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	19.45	19.20	19.33	19.02	19.04
SRS #3 Ant D	18.71	18.59	18.46	18.27	18.26
SRS #4 Ant E	16.10	16.74	16.47	15.81	15.52

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 112 of 155

Table H-233

NR Band n41 PC2 Ant F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	19.44	19.15	19.24	18.92	19.06
SRS #3 Ant D	18.68	18.58	18.57	18.32	18.23
SRS #4 Ant E	16.01	16.76	16.51	15.78	15.20

Table H-234

NR Band n41 PC2 Ant F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	19.09	19.07	19.18	18.87	18.94
SRS #3 Ant D	18.58	18.48	18.50	18.19	18.16
SRS #4 Ant E	15.98	16.63	16.39	15.73	15.26

Table H-235

NR Band n41 PC2 Ant F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	19.08	19.07	19.21	18.87	18.98
SRS #3 Ant D	18.69	18.53	18.61	18.27	18.15
SRS #4 Ant E	15.95	16.62	16.34	15.72	15.55

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 113 of 155

Table H-236

NR Band n41 PC2 Ant F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	19.14	19.18	19.23	18.90	19.00
SRS #3 Ant D	18.71	18.53	18.63	18.20	18.18
SRS #4 Ant E	15.95	16.64	16.37	15.70	15.68

Table H-237

NR Band n41 PC2 Ant F, D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.32	17.10
SRS #3 Ant D	19.66	19.24

Table H-238

NR Band n41 PC2 Ant F, D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.32	17.21
SRS #3 Ant D	19.62	19.25

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 114 of 155

Table H-239
NR Band n41 PC2 Ant F, D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.22	16.98
SRS #3 Ant D	19.54	19.14

Table H-240
NR Band n41 PC2 Ant F, D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant F	17.30	17.21	17.12
SRS #3 Ant D	19.54	19.56	19.21

Table H-241
NR Band n41 PC2 Ant F, D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant F	17.36	17.34	17.02
SRS #3 Ant D	19.80	19.54	19.45

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 115 of 155

Table H-242
NR Band n41 PC2 Ant F, D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	17.39	17.26	17.22	17.16
SRS #3 Ant D	19.79	19.73	19.68	19.55

Table H-243
NR Band n41 PC2 Ant F, D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	17.45	17.39	17.26	17.21
SRS #3 Ant D	19.65	19.71	19.37	19.27

Table H-244
NR Band n41 PC2 Ant F, D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	17.46	17.15	17.02	17.04	16.88
SRS #3 Ant D	19.58	19.49	19.43	19.52	19.35

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 116 of 155

Table H-245
NR Band n41 PC2 Ant F, D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	17.34	17.32	17.32	17.20	17.14
SRS #3 Ant D	19.71	19.63	19.59	19.33	19.30

Table H-246
NR Band n41 PC2 Ant F, D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	17.44	17.33	17.23	17.13	17.09
SRS #3 Ant D	19.67	19.64	19.55	19.29	19.22

Table H-247
NR Band n41 PC2 Ant F, D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	17.47	17.16	17.31	17.01	16.95
SRS #3 Ant D	19.67	19.51	19.55	19.19	19.13

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 117 of 155

Table H-248
NR Band n41 PC2 Ant F, D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	17.47	17.31	17.30	17.07	16.97
SRS #3 Ant D	19.68	19.55	19.56	19.22	19.19

Table H-249
NR Band n41 PC2 Ant F, D Path 2 Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	17.49	17.23	17.25	16.99	16.87
SRS #3 Ant D	19.74	19.52	19.61	19.23	19.18

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 118 of 155

H.2.5 NR Band n77

Table H-250

NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.16	0	0.0
	1	123	18.97		0.0
	1	243	19.14		0.0
	120	0	18.95	0-1	0.0
	120	63	19.02	0	0.0
	120	125	19.00	0-1	0.0
	243	0	18.99		0.0
DFT-s-OFDM 16QAM	1	1	19.06	0-1	0.0
CP-OFDM QPSK	1	1	19.22	0-1.5	0.0

Table H-251

NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.03	0	0.0
	1	109	18.91		0.0
	1	215	19.34		0.0
	108	0	18.98	0-1	0.0
	108	55	19.04	0	0.0
	108	109	18.94	0-1	0.0
	216	0	18.93		0.0
DFT-s-OFDM 16QAM	1	1	19.00	0-1	0.0
CP-OFDM QPSK	1	1	19.15	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 119 of 155

Table H-252

NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.94	0	0.0
	1	95	18.83		0.0
	1	187	19.06		0.0
	90	0	18.90	0-1	0.0
	90	50	18.98	0	0.0
	90	99	18.97	0-1	0.0
	180	0	18.91		0.0
DFT-s-OFDM 16QAM	1	1	18.96	0-1	0.0
CP-OFDM QPSK	1	1	18.93	0-1.5	0.0

Table H-253

NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.88	0	0.0
	1	81	18.71		0.0
	1	160	18.85		0.0
	81	0	18.72	0-1	0.0
	81	41	18.79	0	0.0
	81	81	18.83	0-1	0.0
	162	0	18.73		0.0
DFT-s-OFDM 16QAM	1	1	18.74	0-1	0.0
CP-OFDM QPSK	1	1	18.89	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 120 of 155

Table H-254

NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.13	0	0.0
	1	67	19.03		0.0
	1	131	19.15		0.0
	64	0	19.06	0-1	0.0
	64	35	19.14	0	0.0
	64	69	19.07	0-1	0.0
	128	0	19.06		0.0
DFT-s-OFDM 16QAM	1	1	19.04	0-1	0.0
CP-OFDM QPSK	1	1	19.10	0-1.5	0.0

Table H-255

NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.95	0	0.0
	1	53	18.90		0.0
	1	104	18.94		0.0
	50	0	18.83	0-1	0.0
	50	28	18.95	0	0.0
	50	56	18.92	0-1	0.0
	100	0	18.95		0.0
DFT-s-OFDM 16QAM	1	1	18.91	0-1	0.0
CP-OFDM QPSK	1	1	18.96	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 121 of 155

Table H-256

NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.01	0	0.0
	1	39	18.98		0.0
	1	76	19.05		0.0
	36	0	18.85	0-1	0.0
	36	21	18.96	0	0.0
	36	42	18.90	0-1	0.0
	75	0	18.87		0.0
DFT-s-OFDM 16QAM	1	1	18.94	0-1	0.0
CP-OFDM QPSK	1	1	18.98	0-1.5	0.0

Table H-257

NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.03	0	0.0
	1	33	19.05		0.0
	1	63	19.11		0.0
	32	0	18.87	0-1	0.0
	32	17	19.02	0	0.0
	32	33	18.91	0-1	0.0
	64	0	18.92		0.0
DFT-s-OFDM 16QAM	1	1	18.93	0-1	0.0
CP-OFDM QPSK	1	1	19.13	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 122 of 155

Table H-258

NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.91	0	0.0
	1	26	18.97		0.0
	1	49	18.92		0.0
	25	0	18.83	0-1	0.0
	25	13	18.93	0	0.0
	25	26	18.84	0-1	0.0
	50	0	18.86		0.0
DFT-s-OFDM 16QAM	1	1	18.85	0-1	0.0
CP-OFDM QPSK	1	1	18.89	0-1.5	0.0

Table H-259

NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.84	0	0.0
	1	19	18.94		0.0
	1	36	18.90		0.0
	18	0	18.77	0-1	0.0
	18	10	19.00	0	0.0
	18	20	18.78	0-1	0.0
	36	0	18.83		0.0
DFT-s-OFDM 16QAM	1	1	18.82	0-1	0.0
CP-OFDM QPSK	1	1	18.87	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 123 of 155

Table H-260

NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.93	0	0.0
	1	12	18.88		0.0
	1	22	18.98		0.0
	12	0	18.83	0-1	0.0
	12	6	18.92	0	0.0
	12	12	18.86	0-1	0.0
	24	0	18.85		0.0
DFT-s-OFDM 16QAM	1	1	18.90	0-1	0.0
CP-OFDM QPSK	1	1	19.04	0-1.5	0.0

Table H-261

NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.15	0	0.0
	1	123	14.96		0.0
	1	243	15.20		0.0
	120	0	15.04	0-1	0.0
	120	63	15.07	0	0.0
	120	125	14.95	0-1	0.0
	243	0	15.00		0.0
DFT-s-OFDM 16QAM	1	1	15.10	0-1	0.0
CP-OFDM QPSK	1	1	15.09	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 124 of 155

Table H-262
NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.10	0	0.0
	1	109	14.87		0.0
	1	215	15.17		0.0
	108	0	15.00	0-1	0.0
	108	55	14.96	0	0.0
	108	109	14.86	0-1	0.0
	216	0	14.92		0.0
DFT-s-OFDM 16QAM	1	1	15.01	0-1	0.0
CP-OFDM QPSK	1	1	15.05	0-1.5	0.0

Table H-263
NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.02	0	0.0
	1	95	14.78		0.0
	1	187	14.98		0.0
	90	0	14.96	0-1	0.0
	90	50	14.94	0	0.0
	90	99	14.91	0-1	0.0
	180	0	14.85		0.0
DFT-s-OFDM 16QAM	1	1	14.96	0-1	0.0
CP-OFDM QPSK	1	1	15.00	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 125 of 155

Table H-264
NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	14.91	0	0.0
	1	81	14.74		0.0
	1	160	14.88		0.0
	81	0	14.81	0-1	0.0
	81	41	14.87	0	0.0
	81	81	14.83	0-1	0.0
	162	0	14.85		0.0
DFT-s-OFDM 16QAM	1	1	14.89	0-1	0.0
CP-OFDM QPSK	1	1	14.91	0-1.5	0.0

Table H-265
NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.07	0	0.0
	1	67	15.02		0.0
	1	131	15.14		0.0
	64	0	15.09	0-1	0.0
	64	35	15.14	0	0.0
	64	69	15.07	0-1	0.0
	128	0	15.08		0.0
DFT-s-OFDM 16QAM	1	1	14.96	0-1	0.0
CP-OFDM QPSK	1	1	15.04	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 126 of 155

Table H-266
NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.00	0	0.0
	1	53	14.85		0.0
	1	104	14.97		0.0
	50	0	14.86	0-1	0.0
	50	28	14.97	0	0.0
	50	56	14.90	0-1	0.0
	100	0	14.86		0.0
DFT-s-OFDM 16QAM	1	1	14.89	0-1	0.0
CP-OFDM QPSK	1	1	14.93	0-1.5	0.0

Table H-267
NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	14.91	0	0.0
	1	39	14.96		0.0
	1	76	14.91		0.0
	36	0	14.89	0-1	0.0
	36	21	14.93	0	0.0
	36	42	14.91	0-1	0.0
	75	0	14.96		0.0
DFT-s-OFDM 16QAM	1	1	15.01	0-1	0.0
CP-OFDM QPSK	1	1	15.03	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 127 of 155

Table H-268
NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	14.97	0	0.0
	1	33	14.87		0.0
	1	63	15.05		0.0
	32	0	14.90	0-1	0.0
	32	17	14.95	0	0.0
	32	33	14.89	0-1	0.0
	64	0	14.95		0.0
DFT-s-OFDM 16QAM	1	1	15.05	0-1	0.0
CP-OFDM QPSK	1	1	15.07	0-1.5	0.0

Table H-269
NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	14.84	0	0.0
	1	26	14.88		0.0
	1	49	14.89		0.0
	25	0	14.83	0-1	0.0
	25	13	14.88	0	0.0
	25	26	14.81	0-1	0.0
	50	0	14.97		0.0
DFT-s-OFDM 16QAM	1	1	14.88	0-1	0.0
CP-OFDM QPSK	1	1	14.98	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 128 of 155

Table H-270
NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	14.83	0	0.0
	1	19	14.86		0.0
	1	36	14.85		0.0
	18	0	14.77	0-1	0.0
	18	10	14.93	0	0.0
	18	20	14.79	0-1	0.0
	36	0	14.83		0.0
DFT-s-OFDM 16QAM	1	1	14.81	0-1	0.0
CP-OFDM QPSK	1	1	14.85	0-1.5	0.0

Table H-271
NR Band n77 DoD Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	14.89	0	0.0
	1	12	14.86		0.0
	1	22	14.94		0.0
	12	0	14.85	0-1	0.0
	12	6	14.81	0	0.0
	12	12	14.88	0-1	0.0
	24	0	14.87		0.0
DFT-s-OFDM 16QAM	1	1	14.82	0-1	0.0
CP-OFDM QPSK	1	1	14.94	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 129 of 155

Table H-272
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	14.49
SRS #3 Ant I	18.46
SRS #4 Ant D	14.62

Table H-273
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	14.53
SRS #3 Ant I	18.39
SRS #4 Ant D	14.66

Table H-274
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	14.35
SRS #3 Ant I	18.18
SRS #4 Ant D	14.52

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 130 of 155

Table H-275
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	14.40
SRS #3 Ant I	18.14
SRS #4 Ant D	14.51

Table H-276
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	14.62
SRS #3 Ant I	18.36
SRS #4 Ant D	14.70

Table H-277
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	14.57
SRS #3 Ant I	18.28
SRS #4 Ant D	14.61

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 131 of 155

Table H-278
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	14.55
SRS #3 Ant I	18.23
SRS #4 Ant D	14.62

Table H-279
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	14.53
SRS #3 Ant I	18.38
SRS #4 Ant D	14.53

Table H-280
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	14.47
SRS #3 Ant I	18.17
SRS #4 Ant D	14.40

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 132 of 155

Table H-281
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	14.46
SRS #3 Ant I	18.20
SRS #4 Ant D	14.41

Table H-282
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	14.50
SRS #3 Ant I	18.31
SRS #4 Ant D	14.60

Table H-283
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.59
SRS #3 Ant I	14.42
SRS #4 Ant D	10.72

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 133 of 155

Table H-284
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.57
SRS #3 Ant I	14.29
SRS #4 Ant D	10.73

Table H-285
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.53
SRS #3 Ant I	14.27
SRS #4 Ant D	10.60

Table H-286
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.45
SRS #3 Ant I	14.18
SRS #4 Ant D	10.54

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 134 of 155

Table H-287
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.66
SRS #3 Ant I	14.42
SRS #4 Ant D	10.72

Table H-288
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.55
SRS #3 Ant I	14.29
SRS #4 Ant D	10.68

Table H-289
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.58
SRS #3 Ant I	14.24
SRS #4 Ant D	10.62

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 135 of 155

Table H-290
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.57
SRS #3 Ant I	14.22
SRS #4 Ant D	10.63

Table H-291
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.52
SRS #3 Ant I	14.18
SRS #4 Ant D	10.42

Table H-292
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.49
SRS #3 Ant I	14.10
SRS #4 Ant D	10.43

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 136 of 155

Table H-293
NR Band n77 DoD Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.52
SRS #3 Ant I	14.22
SRS #4 Ant D	10.47

Table H-294
NR Band n77 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 90 MHz Bandwidth

NR Band n77 90 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)			
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.99	19.33	0	0.0	
	1	123	18.90	19.08		0.0	
	1	243	19.19	19.10		0.0	
	120	0	18.86	19.07	0-1	0.0	
	120	63	18.93	19.20	0	0.0	
	120	125	18.93	19.08	0-1	0.0	
	243	0	19.03	19.15		0.0	
DFT-s-OFDM 16QAM	1	1	19.02	19.44	0-1	0.0	
CP-OFDM QPSK	1	1	19.12	19.46	0-1.5	0.0	

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 137 of 155

Table H-295
NR Band n77 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 80 MHz Bandwidth

NR Band n77 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.13	19.20	0	0.0
	1	109	18.87	19.03		0.0
	1	215	19.26	19.24		0.0
	108	0	18.97	19.04	0-1	0.0
	108	55	19.01	19.04	0	0.0
	108	109	19.04	19.12	0-1	0.0
	216	0	19.02	19.17		0.0
DFT-s-OFDM 16QAM	1	1	19.00	19.21	0-1	0.0
CP-OFDM QPSK	1	1	19.24	19.30	0-1.5	0.0

Table H-296
NR Band n77 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 70 MHz Bandwidth

NR Band n77 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.96	19.06	0	0.0
	1	95	18.95	19.04		0.0
	1	187	19.09	19.07		0.0
	90	0	19.06	19.08	0-1	0.0
	90	50	19.05	19.21	0	0.0
	90	99	19.08	19.11	0-1	0.0
	180	0	19.00	19.08		0.0
DFT-s-OFDM 16QAM	1	1	19.03	19.22	0-1	0.0
CP-OFDM QPSK	1	1	19.17	19.28	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 138 of 155

Table H-297
NR Band n77 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 60 MHz Bandwidth

NR Band n77 60 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.94	19.05	0	0.0
	1	81	18.85	18.98		0.0
	1	160	19.04	19.08		0.0
	81	0	18.83	18.95	0-1	0.0
	81	41	18.87	19.09	0	0.0
	81	81	18.82	18.99	0-1	0.0
	162	0	18.93	19.07		0.0
DFT-s-OFDM 16QAM	1	1	18.81	19.19	0-1	0.0
CP-OFDM QPSK	1	1	18.94	19.15	0-1.5	0.0

Table H-298
NR Band n77 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 50 MHz Bandwidth

NR Band n77 50 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.94	19.24	0	0.0
	1	67	18.86	19.26		0.0
	1	131	19.05	19.34		0.0
	64	0	18.82	19.16	0-1	0.0
	64	35	18.99	19.24	0	0.0
	64	69	18.92	19.19	0-1	0.0
	128	0	18.89	19.20		0.0
DFT-s-OFDM 16QAM	1	1	18.93	19.28	0-1	0.0
CP-OFDM QPSK	1	1	19.07	19.34	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 139 of 155

Table H-299
NR Band n77 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n77 40 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.89	19.00	0	0.0
	1	53	18.91	19.14		0.0
	1	104	18.92	19.17		0.0
	50	0	18.85	19.12	0-1	0.0
	50	28	18.89	19.21	0	0.0
	50	56	18.87	19.13	0-1	0.0
	100	0	18.92	19.22		0.0
DFT-s-OFDM 16QAM	1	1	18.78	19.04	0-1	0.0
CP-OFDM QPSK	1	1	18.92	19.11	0-1.5	0.0

Table H-300
NR Band n77 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n77 30 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.92	19.22	0	0.0
	1	39	18.96	19.20		0.0
	1	76	18.97	19.31		0.0
	36	0	18.90	19.18	0-1	0.0
	36	21	18.86	19.19	0	0.0
	36	42	18.84	19.22	0-1	0.0
	75	0	18.89	19.22		0.0
DFT-s-OFDM 16QAM	1	1	18.72	19.18	0-1	0.0
CP-OFDM QPSK	1	1	18.94	19.35	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 140 of 155

Table H-301
NR Band n77 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n77 25 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.79	19.32	0	0.0
	1	33	18.90	19.26		0.0
	1	63	18.78	19.41		0.0
	32	0	18.69	19.14	0-1	0.0
	32	17	18.77	19.15	0	0.0
	32	33	18.60	19.23	0-1	0.0
	64	0	18.74	19.19		0.0
DFT-s-OFDM 16QAM	1	1	18.82	19.23	0-1	0.0
CP-OFDM QPSK	1	1	18.75	19.38	0-1.5	0.0

Table H-302
NR Band n77 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n77 20 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.59	19.11	0	0.0
	1	26	18.60	19.22		0.0
	1	49	18.70	19.19		0.0
	25	0	18.63	19.15	0-1	0.0
	25	13	18.70	19.12	0	0.0
	25	26	18.67	19.10	0-1	0.0
	50	0	18.75	19.24		0.0
DFT-s-OFDM 16QAM	1	1	18.56	19.04	0-1	0.0
CP-OFDM QPSK	1	1	18.67	19.18	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 141 of 155

Table H-303
NR Band n77 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n77 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.68	19.12	0	0.0
	1	19	18.62	19.18		0.0
	1	36	18.65	19.31		0.0
	18	0	18.51	19.07	0-1	0.0
	18	10	18.74	19.15	0	0.0
	18	20	18.52	19.13	0-1	0.0
	36	0	18.49	19.07		0.0
DFT-s-OFDM 16QAM	1	1	18.60	19.21	0-1	0.0
CP-OFDM QPSK	1	1	18.67	19.27	0-1.5	0.0

Table H-304
NR Band n77 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n77 10 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.68	19.25	0	0.0
	1	12	18.66	19.22		0.0
	1	22	18.77	19.26		0.0
	12	0	18.58	19.14	0-1	0.0
	12	6	18.60	19.25	0	0.0
	12	12	18.67	19.25	0-1	0.0
	24	0	18.65	19.11		0.0
DFT-s-OFDM 16QAM	1	1	18.68	19.13	0-1	0.0
CP-OFDM QPSK	1	1	18.79	19.25	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 142 of 155

Table H-305
NR Band n77 Ant F Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n77 90 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)			
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	14.99	15.40	0	0.0	
	1	123	14.80	15.14		0.0	
	1	243	15.19	15.21		0.0	
	120	0	14.91	15.16	0-1	0.0	
	120	63	14.88	15.14	0	0.0	
	120	125	14.94	15.12	0-1	0.0	
	243	0	15.04	15.10		0.0	
DFT-s-OFDM 16QAM	1	1	15.06	15.22	0-1	0.0	
CP-OFDM QPSK	1	1	15.11	15.44	0-1.5	0.0	

Table H-306
NR Band n77 Ant F Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n77 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	14.98	15.32	0	0.0
	1	109	14.92	14.98		0.0
	1	215	15.08	15.16		0.0
	108	0	14.94	15.05	0-1	0.0
	108	55	14.95	15.08	0	0.0
	108	109	15.00	15.04	0-1	0.0
	216	0	15.08	15.01		0.0
DFT-s-OFDM 16QAM	1	1	14.94	15.16	0-1	0.0
CP-OFDM QPSK	1	1	15.16	15.22	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 143 of 155

Table H-307
NR Band n77 Ant F Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n77 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	15.01	15.10	0	0.0
	1	95	14.89	15.08		0.0
	1	187	15.11	15.09		0.0
	90	0	14.96	15.10	0-1	0.0
	90	50	14.93	15.26	0	0.0
	90	99	15.02	15.11	0-1	0.0
	180	0	14.93	15.08		0.0
DFT-s-OFDM 16QAM	1	1	15.04	15.21	0-1	0.0
CP-OFDM QPSK	1	1	15.19	15.23	0-1.5	0.0

Table H-308
NR Band n77 Ant F Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n77 60 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	14.81	15.13	0	0.0
	1	81	14.87	15.00		0.0
	1	160	14.86	15.14		0.0
	81	0	14.75	14.93	0-1	0.0
	81	41	14.82	15.03	0	0.0
	81	81	14.80	15.00	0-1	0.0
	162	0	14.86	14.98		0.0
DFT-s-OFDM 16QAM	1	1	14.87	15.01	0-1	0.0
CP-OFDM QPSK	1	1	14.94	15.08	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 144 of 155

Table H-309
NR Band n77 Ant F Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n77 50 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	14.77	15.36	0	0.0
	1	67	14.90	15.24		0.0
	1	131	14.87	15.32		0.0
	64	0	14.83	15.18	0-1	0.0
	64	35	14.96	15.32	0	0.0
	64	69	14.93	15.21	0-1	0.0
	128	0	14.82	15.24		0.0
DFT-s-OFDM 16QAM	1	1	14.87	15.21	0-1	0.0
CP-OFDM QPSK	1	1	14.86	15.25	0-1.5	0.0

Table H-310
NR Band n77 Ant F Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n77 40 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	14.71	15.01	0	0.0
	1	53	14.72	15.00		0.0
	1	104	14.78	15.09		0.0
	50	0	14.73	14.97	0-1	0.0
	50	28	14.73	15.13	0	0.0
	50	56	14.68	15.09	0-1	0.0
	100	0	14.83	15.14		0.0
DFT-s-OFDM 16QAM	1	1	14.72	15.13	0-1	0.0
CP-OFDM QPSK	1	1	14.80	15.04	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 145 of 155

Table H-311
NR Band n77 Ant F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n77 30 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	14.90	15.25	0	0.0
	1	39	14.84	15.23		0.0
	1	76	14.79	15.28		0.0
	36	0	14.75	15.15	0-1	0.0
	36	21	14.76	15.23	0	0.0
	36	42	14.79	15.22	0-1	0.0
	75	0	14.69	15.21		0.0
DFT-s-OFDM 16QAM	1	1	14.81	15.21	0-1	0.0
CP-OFDM QPSK	1	1	14.83	15.29	0-1.5	0.0

Table H-312
NR Band n77 Ant F Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n77 25 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	14.56	15.38	0	0.0
	1	33	14.64	15.28		0.0
	1	63	14.55	15.37		0.0
	32	0	14.53	15.17	0-1	0.0
	32	17	14.52	15.22	0	0.0
	32	33	14.56	15.24	0-1	0.0
	64	0	14.56	15.20		0.0
DFT-s-OFDM 16QAM	1	1	14.54	15.20	0-1	0.0
CP-OFDM QPSK	1	1	14.60	15.27	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 146 of 155

Table H-313
NR Band n77 Ant F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n77 20 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	14.61	15.08	0	0.0
	1	26	14.50	15.22		0.0
	1	49	14.62	15.18		0.0
	25	0	14.48	15.08	0-1	0.0
	25	13	14.50	15.11	0	0.0
	25	26	14.51	15.17	0-1	0.0
	50	0	14.56	15.14		0.0
DFT-s-OFDM 16QAM	1	1	14.55	15.07	0-1	0.0
CP-OFDM QPSK	1	1	14.60	15.09	0-1.5	0.0

Table H-314
NR Band n77 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n77 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	14.61	15.21	0	0.0
	1	19	14.62	15.20		0.0
	1	36	14.70	15.19		0.0
	18	0	14.50	15.08	0-1	0.0
	18	10	14.41	15.24	0	0.0
	18	20	14.48	15.06	0-1	0.0
	36	0	14.45	15.04		0.0
DFT-s-OFDM 16QAM	1	1	14.48	15.06	0-1	0.0
CP-OFDM QPSK	1	1	14.55	15.13	0-1.5	0.0

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 147 of 155

Table H-315
NR Band n77 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n77 10 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	14.65	15.26	0	0.0
	1	12	14.72	15.30		0.0
	1	22	14.61	15.37		0.0
	12	0	14.56	15.12	0-1	0.0
	12	6	14.57	15.22	0	0.0
	12	12	14.61	15.20	0-1	0.0
	24	0	14.57	15.12		0.0
DFT-s-OFDM 16QAM	1	1	14.55	15.12	0-1	0.0
CP-OFDM QPSK	1	1	14.58	15.27	0-1.5	0.0

Table H-316
NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 90 MHz Bandwidth

NR Band n77 90 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	13.50	13.51
SRS #3 Ant I	18.60	19.33
SRS #4 Ant D	14.34	13.82

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 148 of 155

Table H-317

NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 80 MHz Bandwidth

NR Band n77 80 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	13.38	13.53
SRS #3 Ant I	18.56	19.36
SRS #4 Ant D	13.24	13.83

Table H-318

NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 70 MHz Bandwidth

NR Band n77 70 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	13.27	13.44
SRS #3 Ant I	18.40	19.33
SRS #4 Ant D	14.21	13.63

Table H-319

NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 60 MHz Bandwidth

NR Band n77 60 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	13.23	13.34
SRS #3 Ant I	18.34	19.32
SRS #4 Ant D	14.11	13.66

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 149 of 155

Table H-320

NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 50 MHz Bandwidth

NR Band n77 50 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	13.45	13.65
SRS #3 Ant I	18.61	19.46
SRS #4 Ant D	14.28	13.86

Table H-321

NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n77 40 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	13.36	13.29
SRS #3 Ant I	18.49	19.30
SRS #4 Ant D	14.22	13.56

Table H-322

NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n77 30 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	13.39	13.52
SRS #3 Ant I	18.48	19.47
SRS #4 Ant D	14.13	13.84

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 150 of 155

Table H-323

NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n77 25 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	13.30	13.53
SRS #3 Ant I	18.40	19.47
SRS #4 Ant D	14.14	13.81

Table H-324

NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n77 20 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	13.22	13.34
SRS #3 Ant I	18.35	19.34
SRS #4 Ant D	14.00	13.68

Table H-325

NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n77 15 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	13.27	13.39
SRS #3 Ant I	18.36	19.42
SRS #4 Ant D	14.05	13.73

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 151 of 155

Table H-326
NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n77 10 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	13.23	13.31
SRS #3 Ant I	18.47	19.47
SRS #4 Ant D	14.04	13.63

Table H-327
NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n77 90 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	9.42	9.55
SRS #3 Ant I	14.55	15.24
SRS #4 Ant D	10.33	9.85

Table H-328
NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n77 80 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	9.34	9.35
SRS #3 Ant I	14.51	15.27
SRS #4 Ant D	10.17	9.57

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 152 of 155

Table H-329
NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n77 70 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	9.35	9.43
SRS #3 Ant I	14.42	15.27
SRS #4 Ant D	10.20	9.67

Table H-330
NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n77 60 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	9.14	9.26
SRS #3 Ant I	14.30	15.27
SRS #4 Ant D	10.02	9.71

Table H-331
NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n77 50 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	9.38	9.40
SRS #3 Ant I	14.45	15.42
SRS #4 Ant D	10.28	9.67

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 153 of 155

Table H-332
NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n77 40 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	9.26	9.22
SRS #3 Ant I	14.43	15.41
SRS #4 Ant D	10.16	9.48

Table H-333
NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n77 30 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	9.22	9.45
SRS #3 Ant I	14.41	15.49
SRS #4 Ant D	9.92	9.89

Table H-334
NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n77 25 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	9.30	9.35
SRS #3 Ant I	14.47	15.42
SRS #4 Ant D	10.09	9.69

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 154 of 155

Table H-335
NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n77 20 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	9.16	9.30
SRS #3 Ant I	14.29	15.41
SRS #4 Ant D	9.91	9.57

Table H-336
NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n77 15 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	9.24	9.22
SRS #3 Ant I	14.34	15.44
SRS #4 Ant D	9.99	9.57

Table H-337
NR Band n77 Ant C, I, D Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n77 10 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	9.23	9.28
SRS #3 Ant I	14.46	15.47
SRS #4 Ant D	9.87	9.69

FCC ID A3LSMS938B	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 155 of 155