

EMC TEST REPORT

| | | | |
|--------------------------|---|---|---|
| Project No. | LBE20156231 | Issue No. | 0 |
| Applicant | Name of organization | Samsung Electronics Co., Ltd. | |
| | Address | (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea | |
| | Date of application | January 7, 2016 | |
| EUT | Type of device | <input checked="" type="checkbox"/> Class B personal computers and peripherals <input type="checkbox"/> All other devices | |
| | Equipment authorization | <input type="checkbox"/> Declaration of Conformity <input checked="" type="checkbox"/> Certification <input type="checkbox"/> Verification | |
| | FCC ID | A3LSMT285 | |
| | Kind of product | Portable Device | |
| | Model No. | SM-T285 | |
| | Variant Model No. | Refer to clause 4.6 | |
| | Manufacturer | SAMSUNG ELECTRONICS CO., LTD. 302, 3 Gongdan 3-ro, Gumi-si, Gyengsangbuk-do, 39388, Republic of Korea SAMSUNG ELECTRONICS VIETNAM CO.,LTD. Yen Phong 1 Industrial Zone, Yen Trung Commune, Yen Phong District Bac Ninh Province, Vietnam | |
| Applied Standards | FCC Part 15, Subpart B, Class B / ANSI C63.4-2009 | | |
| Test Period | January 8, 2016 ~ January 11, 2016 | | |
| Issue date | January 12, 2016 | | |

Test result : Complied

The equipment under test has found to be compliant with the applied standards.
 (Refer to the attached test result for more detail.)

Tested by : Jong-Sup Jeong



Reviewed by : Tae-Young Jang



The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from CS & Environment center.



CS & Environment Center of Samsung Electronics Co., Ltd.

(Maetan dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-so, 16677, Republic of Korea

Table of contents

1. Report Information

| | |
|----------------------------|---|
| 1.1 Revision history | 3 |
|----------------------------|---|

2. Summary of test results

| | |
|--------------------|---|
| 2.1 Emission | 3 |
|--------------------|---|

3. General Information

| | |
|-------------------------|---|
| 3.1 Test facility | 3 |
|-------------------------|---|

4. Test Configuration

| | |
|--|---|
| 4.1 Test Peripherals | 4 |
| 4.2 EUT operating mode | 4 |
| 4.3 Details of Sampling | 5 |
| 4.4 Used cable description | 5 |
| 4.5 Test arrangement | 5 |
| 4.6 EUT Description | 6 |
| 4.7 Clock Frequencies | 6 |
| 4.8 Test configuration and condition | 6 |
| 4.9 Measurement uncertainty | 7 |

5. Result of individual tests

| | |
|---------------------------------|----|
| 5.1 Conducted disturbance | 8 |
| 5.2 Radiated disturbance | 10 |

1. Report Information

1.1 Revision history

| No. | Revised detailed information |
|---------|------------------------------|
| Issue 0 | - LBE20156231 (SAMSUNG) |

2. Summary of test results

2.1 Emission

The EUT has been tested according to the following specifications:

| Applied | Test type | Applied standard | Result |
|-------------------------------------|---------------------------------------|--|----------|
| <input checked="" type="checkbox"/> | Conducted Disturbance (Mains port) | FCC Part 15 Subpart B / ANSI C63.4-2009 (Class B) | Complied |
| <input checked="" type="checkbox"/> | Radiated Disturbance | | Complied |

3. General Information

3.1 Test facility

The CS & Environment center is located on Samsung Electronics Co., Ltd. at (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea.

All testing are performed in Semi-anechoic chambers conforming to the site attenuation characteristics defined by ANSI C63.4, CISPR 22, 16-1 and 16-2. and Shielded rooms.

The CS & Environment center is operated as testing laboratory in accordance with the requirements of ISO/IEC 17025:2005.

4. Test Setup configuration

4.1 Test Peripherals

The cables used for these peripherals are either permanently attached by the peripheral manufacturer or coupled with an assigned cable as defined below.

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

| Mark | Description | Model No. | Serial No. | Manufacturer / Trademark | FCC ID / DoC |
|------|-------------------|-----------------------------|------------------------------|--------------------------|--------------|
| A | Portable Device | SM-T285 | - | SAMSUNG | A3LSMT285 |
| B | Battery | EB-BT280ABE | - | SAMSUNG | - |
| C | Headset | EHS61ASFWE | - | SAMSUNG | - |
| D | Data Cable | ECB-DU68WE | - | SAMSUNG | - |
| E | microSD Card | 32GB | - | SAMSUNG | - |
| F | Travel Adapter | ETA0U83EWE | SC1F8Q4AS/A-E | SAMSUNG | - |
| G | Desk-Top Computer | HP Compaq dx2200 Microtower | CNG7060LW0 | HP | DoC |
| H | LCD Monitor | U2713HMt | CN-0GK0KD-74445 -332-106L | Dell | DoC |
| I | Mouse | M-SBF96 | LZ949BG0D9Y | Logitech | DoC |
| J | Keyboard | SKG-2000PB | CNBA5902830AGP53 Z5A3485 | SAMSUNG | DoC |
| K | Router | H3008 | 10070100009 | EFM Networks | DoC |
| L | Power Supply | HB12B-050200SPA | HBK520201025 | Shen Zhen | DoC |

This tablet device does not contain the minimum number of ports required for personal computer testing per ANSI C63.4, but the EUT is attached to a computer through its only available port, which represents worst case emissions. All other aspects of C63.4 testing requirements were maintained.

4.2 EUT operating mode

To achieve compliance applied standard specification, the following mode(s) were made during compliance testing:

| | |
|-------------------------|-------------------------------|
| Operating Mode 1 | USB Mode (Data Communication) |
|-------------------------|-------------------------------|

4.3 Details of Sampling


Customer selected, single unit.

4.4 Used cable description

The EUT is configured, installed, arranged and operated in a manner consistent with typical applications. Interface cables/loads/devices are connected to at least one of each type of interface port of the EUT, and where practical, each cable shall be terminated in a device typical of actual usage. The type(s) of interconnecting cables to be used and the interface port (of the EUT) to which these were connected:

| No. | Connected cable | Length [m] | Shielded [Y/N] | Note |
|-----|-----------------------------|------------|----------------|--|
| 1 | Data Cable / Travel Adapter | 0.8 | Y | From EUT to Desk-Top Computer / From EUT to Travel Adapter |
| 2 | Headset | 1.6 | N | For EUT |
| 3 | Power | 1.8 | N | For Desk-Top Computer |
| 4 | Power | 1.8 | N | For LCD Monitor |
| 5 | Power | 1.8 | N | From Router to Power Supply |
| 6 | LAN | 1.5 | N | From Desk-Top Computer to Router |
| 7 | LAN | 1.5 | N | From Router to Local Area Network |
| 8 | RGB | 1.8 | Y | From Desk-Top Computer to LCD Monitor |
| 9 | PS/2 | 1.8 | Y | From Desk-Top Computer to Mouse |
| 10 | PS/2 | 1.8 | Y | From Desk-Top Computer to Keyboard |

4.5 Test arrangement



4.6 EUT Description

The EUT is a tablet type Portable Device which can operate on GSM850/900/1800/1900, WCDMA FDD1/2/5/8, LTE FDD1/3/5/7/8/20, LTE TDD40 bands and incorporates a camera, Bluetooth, Wi-Fi, GPS, FM radio and MP3/MP4 player.

4.6.1 The variant models

- None

4.7 Clock Frequencies

| Kind of Clocks | Frequency [MHz] | Kind of Clocks | Frequency [MHz] |
|----------------|-------------------|----------------|-------------------|
| CPU | 1 500 | USB 2.0 | 24 |
| | | | |

4.8 Test configuration and condition

- The EUT exercise program which is the samsung standardized emission test program for windows was used during all EMC measurements were tested. This program was contained on the PC hard disk drive. Once loaded, the program sequentially exercises each system component in turn.
- The EUT was exercised during the testing by data read and write cycles repeated with internal/ external storage devices. At the end of the test, the copied back data was compared with original.
- The EUT was connected to the PC by using USB data cable to charge.
- The system was configured for testing in a typical fashion that a customer would normally use, and was tested while in an automated non-attendant mode.

Power source for the EUT operating was supplied by CVCF made by the Pacific Power Source Corp.

- Test Voltage : AC 120 V, 60 Hz

4.9 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus: (According to CISPR 16-4 and UKAS Lab 34.)

4.9.1 Emission

| Test type | | Measurement uncertainty (C.L. 95 %, $k = 2$) |
|--|------------|--|
| Conducted disturbance | AC Mains | 3.62 dB |
| Radiated Disturbance (30 MHz ~ 1 GHz) | Horizontal | 4.90 dB |
| | Vertical | 4.68 dB |
| Radiated Disturbance (1 GHz ~ 6 GHz) | Horizontal | 5.51 dB |
| | Vertical | 5.50 dB |

5. Results of individual test

5.1 Conducted disturbance

The EUT was connected to the Desk-Top Computer which was powered from one LISN for the measurements. The support equipment power cables were connected to a second LISN.

Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration. The EUT measured in accordance with the methods described in standards.

Limits for conducted disturbance at the mains ports of Class B ITE

| Frequency range Limits [MHz] | Resolution Bandwidth [kHz] | Limits [dB(μV)] | |
|-----------------------------------|---------------------------------|-------------------|----------|
| | | Quasi-peak | Average |
| 0,15 to 0,50 | 9 | 66 to 56 | 56 to 46 |
| 0,50 to 5 | 9 | 56 | 46 |
| 5 to 30 | 9 | 60 | 50 |

NOTE 1 The lower limit shall apply at the transition frequency.
NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

5.1.1 Test instrumentation


| EMC No. | Test Instrument | Model name | Manufacturer | Serial No. | Calibration | |
|---------|------------------------------|------------|--------------|------------|-------------|------------------|
| | | | | | Date | Interval (Month) |
| E3I-165 | EMI Test Receiver | ESI-26 | R&S | 100010 | 2015-10-08 | 12 |
| E3I-238 | Universal Radio Communicator | CMU200 | R&S | 120045-IQ | 2015-10-07 | 12 |
| E3I-259 | LISN | ENV216 | R&S | 101369 | 2015-11-25 | 12 |
| E3I-260 | LISN | ENV216 | R&S | 101366 | 2015-08-04 | 12 |

5.1.2 Temperature and humidity condition

| | | | |
|-------------------|----------------------|----------------------|-----------------------------|
| Test date | 2016-01-11 | Test engineer | Jong-Sup Jeong |
| Climate condition | Ambient temperature | (23.8 ~ 24.5) °C | Limit (15.0 to 35.0) °C |
| | Relative humidity | (46.1 ~ 46.7) % R.H. | Limit (25.0 to 75.0) % R.H. |
| | Atmospheric pressure | (100.9 ~ 101.6) kPa | Limit (86.0 to 106.0) kPa |
| Test place | Shield Room (SR8) | | |

5.1.3 Test results

□ Operating Mode 1: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

Final measurement results table(QP):

| Frequency (MHz) | Level (dBµV) | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|--------------|------|------------|-------------|--------------|
| 0.150 | 49.1 | N | 10.1 | 16.9 | 66.0 |
| 0.528 | 40.5 | N | 10.2 | 15.5 | 56.0 |
| 0.636 | 41.2 | N | 10.2 | 14.8 | 56.0 |
| 0.789 | 44.7 | L1 | 10.0 | 11.3 | 56.0 |
| 1.050 | 42.9 | L1 | 9.9 | 13.1 | 56.0 |
| 1.320 | 40.2 | L1 | 9.9 | 15.8 | 56.0 |

Final measurement results table(CAV):

| Frequency (MHz) | Level (dBµV) | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|--------------|------|------------|-------------|--------------|
| 0.483 | 35.0 | N | 10.2 | 11.3 | 46.3 |
| 0.636 | 38.4 | N | 10.2 | 7.6 | 46.0 |
| 0.789 | 41.2 | L1 | 10.0 | 4.8 | 46.0 |
| 1.050 | 37.4 | L1 | 9.9 | 8.6 | 46.0 |
| 1.338 | 34.7 | N | 10.1 | 11.3 | 46.0 |
| 1.572 | 34.0 | N | 10.0 | 12.0 | 46.0 |

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
 QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

5.2 Radiated disturbance

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin.

Peak measurements were made over the changeable frequency range 30 MHz to 1 GHz at a measurement distance of 10 m for the following antenna and turntable arrangements:

| Antenna Height [cm] | Antenna Polarisation | Resolution Bandwidth [kHz] | Video Bandwidth [kHz] | Turntable position [degrees] |
|--------------------------|----------------------|------------------------------------|-------------------------------|-----------------------------------|
| 100 ~ 400 | Horizontal, Vertical | 120 | 300 | Continuous |

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using quasi-peak detector.

Peak/CISPR-Average measurements were made over the changeable frequency range 1 GHz to 40 GHz or 5th harmonics of the highest frequency in accordance with internal maximum operating frequency at a measurement distance of 3 m for the following antenna and turntable arrangements:

| Antenna Height [cm] | Antenna Polarisation | Resolution Bandwidth [MHz] | Video Bandwidth [MHz] | Turntable position [degrees] |
|--------------------------|----------------------|------------------------------------|-------------------------------|---------------------------------------|
| 100 ~ 400 | Horizontal, Vertical | 1 | 3 | 0 ~ 345 (Step size: 15 degrees) |

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using peak and CISPR-average detectors.

Limits for radiated disturbance of Class B ITE at a measuring distance of 3 m and 10 m

| Frequency range Limits [MHz] | Field Strength | | |
|-----------------------------------|-------------------------|-------------------------------|--------------------------------|
| | 3 m [$\mu\text{V/m}$] | 3 m [dB($\mu\text{V/m}$)] | 10 m [dB($\mu\text{V/m}$)] |
| 30 to 88 | 100 | 40.0 | 29.5 |
| 88 to 216 | 150 | 43.5 | 33.0 |
| 216 to 960 | 200 | 46.0 | 35.5 |
| Above 960 | 500 | 54.0 | 43.5 |

Results checked manually; and points close to the limit line were re-measured.

5.2.1 Test instrumentation

| EMC No. | Test Instrument | Model name | Manufacturer | Serial No. | Calibration | |
|---------|------------------------------|------------|--------------|------------|-------------|------------------|
| | | | | | Date | Interval (Month) |
| E5I-015 | EMI Test Receiver | ESU-08 | R&S | 100481 | 2015-05-13 | 12 |
| E3I-142 | EMI Test Receiver | ESI-26 | R&S | 100019 | 2015-02-25 | 12 |
| E3I-170 | Horn Antenna | HF906 | R&S | 100028 | 2014-10-20 | 24 |
| E3I-190 | BILOG Antenna | CBL6112B | Schaffner | 2804 | 2014-05-14 | 24 |
| E3I-233 | EMI Test Receiver | ESU-26 | R&S | 100364 | 2015-03-31 | 12 |
| E3I-238 | Universal Radio Communicator | CMU200 | R&S | 120045-IQ | 2015-10-07 | 12 |
| E3I-273 | Preamplifier | 317 | SONOMA | 312701 | 2015-03-24 | 12 |
| E3I-274 | Preamplifier | 317 | SONOMA | 312702 | 2015-03-24 | 12 |
| E3I-284 | Preamplifier | ESV-Z3 | R&S | 815111 | 2015-04-16 | 12 |
| E3I-320 | BILOG Antenna | CBL6112D | Schaffner | 22602 | 2015-10-06 | 24 |


5.2.2 Temperature and humidity condition

| | | | |
|--------------------------|------------------------------|----------------------|-----------------------------|
| Test date | 2016-01-08 | Test engineer | Jong-Sup Jeong |
| Climate condition | Ambient temperature | (23.2 ~ 23.8) °C | Limit (15.0 to 35.0) °C |
| | Relative humidity | (39.3 ~ 40.1) % R.H. | Limit (25.0 to 75.0) % R.H. |
| | Atmospheric pressure | (101.1 ~ 101.8) kPa | Limit (86.0 to 106.0) kPa |
| Test place | Semi-Anechoic Chamber (SAC4) | | |

5.2.3 Test results

□ Operating Mode 1

- Frequencies below 1 GHz




Note) Receiving antenna polarization : Horizontal, Vertical
 Test Distance : 10 m, Antenna Height : 1 to 4 meters
 Level (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)
 Margin (QP) = Limit - Level (QP)
 QP = Quasi-Peak, c.f = Correction Factor

5.2.3 Test results

Operating Mode 1

- Frequencies above 1 GHz



Final measurement results table(PK):

| Frequency (MHz) | Level (dBuV/m) | Height (cm) | Polarisation | Azimuth (deg) | Corr. (dB) | Margin (dB) | Limit (dBuV/m) |
|-----------------|----------------|-------------|--------------|---------------|------------|-------------|----------------|
| 1 072.144 | 44.0 | 100 | V | 164 | -12.8 | 30.0 | 74.0 |
| 1 184.369 | 41.5 | 100 | V | 159 | -12.3 | 32.5 | 74.0 |
| 1 621.243 | 43.1 | 100 | V | 166 | -10.0 | 30.9 | 74.0 |
| 1 765.531 | 42.6 | 100 | H | 203 | -9.3 | 31.4 | 74.0 |
| 1 933.868 | 39.1 | 100 | H | 217 | -9.4 | 34.9 | 74.0 |
| 6 993.988 | 50.2 | 100 | H | 63 | 3.7 | 23.8 | 74.0 |

Final measurement results table(CAV):

| Frequency (MHz) | Level (dBuV/m) | Height (cm) | Polarisation | Azimuth (deg) | Corr. (dB) | Margin (dB) | Limit (dBuV/m) |
|-----------------|----------------|-------------|--------------|---------------|------------|-------------|----------------|
| 1 079.579 | 24.0 | 100 | V | 168 | -12.8 | 30.0 | 54.0 |
| 1 175.050 | 21.8 | 100 | V | 156 | -12.4 | 32.2 | 54.0 |
| 1 614.610 | 21.4 | 100 | V | 167 | -10.1 | 32.6 | 54.0 |
| 1 768.838 | 17.4 | 100 | H | 208 | -9.3 | 36.6 | 54.0 |
| 1 934.529 | 19.1 | 100 | H | 213 | -9.4 | 34.9 | 54.0 |
| 6 993.247 | 31.0 | 100 | H | 108 | 3.7 | 23.0 | 54.0 |

Note) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor