






LTE Band 2














10.3 OUT OF BAND EMISSIONS

RULE PART(S)

FCC: §2.1051, §22.901, §22.917, §24.238 and §27.53

LIMITS

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

TEST PROCEDURE

Per KDB 971168 D01 Power Meas License Digital Systems v02r02

The RF output of the transmitter was connected to a spectrum analyzer through a calibrated coaxial cable. Sufficient scans were taken to show the out-of-band Emissions, if any, up to 10th harmonic. Multiple sweeps were recorded in maximum hold mode using a peak detector to ensure that the worst-case emissions were caught.

RESULTS

10.3.1. OUT OF BAND EMISSIONS RESULT

GSM

Band	Mode	f [MHz]	Spurious [dBm]	Limit [dBm]	Margin [dB]
GSM850	GPRS	824.2	-22.72	-13.00	9.72
		836.6	-22.99		9.99
		848.8	-22.42		9.42
	EGPRS	824.2	-22.68		9.68
		836.6	-22.76		9.76
		848.8	-22.73		9.73
GSM1900	GPRS	1850.2	-22.45		9.45
		1880.0	-22.71		9.71
		1909.8	-22.85		9.85
	EGPRS	1850.2	-21.91		8.91
		1880.0	-22.82		9.82
		1909.8	-22.44		9.44

WCDMA

Band	Mode	f [MHz]	Spurious [dBm]	Limit [dBm]	Margin [dB]
Band 5	REL99	826.4	-33.79	-13.00	20.79
		836.6	-31.32		18.32
		846.6	-32.93		19.93
	HSDPA	826.4	-33.00		20
		836.6	-32.89		19.89
		846.6	-31.13		18.13
Band 4	REL99	1712.4	-32.60		19.6
		1732.6	-32.98		19.98
		1752.6	-33.28		20.28
	HSDPA	1712.4	-32.69		19.69
		1732.6	-32.11		19.11
		1752.6	-33.00		20
Band 2	REL99	1852.4	-33.16		20.16
		1880.0	-32.67		19.67
		1907.6	-32.90		19.9
	HSDPA	1852.4	-32.46		19.46
		1880.0	-32.59		19.59
		1907.6	-31.67		18.67

LTE 17

Bandwidth	Mode	f [MHz]	Spurious [dBm]	Limit [dBm]	Margin [dB]
10 MHz	QPSK	709.0	-26.81	-13.00	13.81
		710.0	-27.86		14.86
		711.0	-26.77		13.77
	16QAM	709.0	-27.22		14.22
		710.0	-26.31		13.31
		711.0	-27.79		14.79
5 MHz	QPSK	706.5	-27.16		14.16
		710.0	-26.83		13.83
		713.5	-26.42		13.42
	16QAM	706.5	-26.92		13.92
		710.0	-27.68		14.68
		713.5	-27.17		14.17

LTE 5

Bandwidth	Mode	f [MHz]	Spurious [dBm]	Limit [dBm]	Margin [dB]
10 MHz	QPSK	829.0	-27.43	-13.00	14.43
		836.5	-27.02		14.02
		844.0	-26.92		13.92
	16QAM	829.0	-26.26		13.26
		836.5	-27.91		14.91
		844.0	-27.56		14.56
5 MHz	QPSK	826.5	-26.80		13.8
		836.5	-26.46		13.46
		846.5	-27.46		14.46
	16QAM	826.5	-26.94		13.94
		836.5	-27.19		14.19
		846.5	-27.79		14.79
3 MHz	QPSK	825.5	-26.71		13.71
		836.5	-26.84		13.84
		847.5	-26.94		13.94
	16QAM	825.5	-26.63		13.63
		836.5	-26.98		13.98
		847.5	-27.64		14.64
1.4 MHz	QPSK	824.7	-26.71		13.71
		836.5	-26.85		13.85
		848.3	-26.46		13.46
	16QAM	824.7	-27.02		14.02
		836.5	-27.14		14.14
		848.3	-26.85		13.85

LTE 4


Bandwidth	Mode	f [MHz]	Spurious [dBm]	Limit [dBm]	Margin [dB]
20 MHz	QPSK	1720.0	-26.80	-13.00	13.8
		1732.5	-27.39		14.39
		1745.0	-26.49		13.49
	16QAM	1720.0	-26.42		13.42
		1732.5	-26.71		13.71
		1745.0	-26.21		13.21
15 MHz	QPSK	1717.5	-26.78		13.78
		1732.5	-26.37		13.37
		1747.5	-26.43		13.43
	16QAM	1717.5	-26.67		13.67
		1732.5	-26.56		13.56
		1747.5	-25.43		12.43
10 MHz	QPSK	1715.0	-25.54		12.54
		1732.5	-26.85		13.85
		1750.0	-27.66		14.66
	16QAM	1715.0	-26.50		13.5
		1732.5	-27.06		14.06
		1750.0	-26.35		13.35
5 MHz	QPSK	1712.5	-27.13		14.13
		1732.5	-26.22		13.22
		1752.5	-26.97		13.97
	16QAM	1712.5	-25.92		12.92
		1732.5	-26.87		13.87
		1752.5	-25.10		12.1
3 MHz	QPSK	1711.5	-27.41		14.41
		1732.5	-26.59		13.59
		1753.5	-27.26		14.26
	16QAM	1711.5	-26.65		13.65
		1732.5	-26.33		13.33
		1753.5	-27.66		14.66
1.4 MHz	QPSK	1710.7	-26.50		13.5
		1732.5	-26.53		13.53
		1754.3	-26.71		13.71
	16QAM	1710.7	-26.46		13.46
		1732.5	-27.29		14.29
		1754.3	-26.03		13.03

LTE 2


Bandwidth	Mode	f [MHz]	Spurious [dBm]	Limit [dBm]	Margin [dB]
20 MHz	QPSK	1860.0	-26.92	-13.00	13.92
		1880.0	-25.85		12.85
		1900.0	-27.12		14.12
	16QAM	1860.0	-26.39		13.39
		1880.0	-27.53		14.53
		1900.0	-27.19		14.19
15 MHz	QPSK	1857.5	-26.15		13.15
		1880.0	-26.58		13.58
		1902.5	26.14		-39.14
	16QAM	1857.5	-26.80		13.8
		1880.0	-26.68		13.68
		1902.5	-27.14		14.14
10 MHz	QPSK	1855.0	-26.46		13.46
		1880.0	-26.30		13.3
		1905.0	-27.67		14.67
	16QAM	1855.0	-26.33		13.33
		1880.0	-26.11		13.11
		1905.0	-26.04		13.04
5 MHz	QPSK	1852.5	-26.93		13.93
		1880.0	-26.67		13.67
		1907.5	-25.76		12.76
	16QAM	1852.5	-27.30		14.3
		1880.0	-26.15		13.15
		1907.5	-25.96		12.96
3 MHz	QPSK	1851.5	-26.03		13.03
		1880.0	-26.59		13.59
		1908.5	-26.46		13.46
	16QAM	1851.5	-26.66		13.66
		1880.0	-26.35		13.35
		1908.5	-27.42		14.42
1.4 MHz	QPSK	1850.7	-26.65		13.65
		1880.0	-27.01		14.01
		1909.3	-27.11		14.11
	16QAM	1850.7	-26.39		13.39
		1880.0	-26.56		13.56
		1909.3	-26.59		13.59

10.3.2. OUT OF BAND EMISSIONS PLOTS


GSM 850




GSM 1900




WCDMA Band 5




WCDMA Band 4




WCDMA Band 2





LTE Band 17







LTE Band 5














LTE Band 4



















LTE Band 2














10.4. FREQUENCY STABILITY

RULE PART(S)

FCC: §2.1055, §22.355, §24.235 and §27.54

LIMITS

§22.355 - The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations.

§24.235 - The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

§27.54 - The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

TEST PROCEDURE

Per KDB 971168 D01 Power Meas License Digital Systems v02r02

RESULTS

See the following pages.

10.4.1. FREQUENCY STABILITY RESULTS

LTE Band 17, Channel 23790, Frequency 710.0 MHz

Reference Frequency: LTE Band 17 Mid Channel 710.0 MHz @ 20°C				
Limit: +/- 2.5 ppm = 1775.000 Hz				
Power Supply [Vdc]	Environment Temperature [°C]	Frequency Deviation Measured with Time Elapse		
		[MHz]	Delta [ppm]	Limit [ppm]
3.85	50	710.00000589	-0.001	2.5
3.85	40	710.00000438	0.001	2.5
3.85	30	710.00000435	0.002	2.5
3.85	20	710.00000544	0	2.5
3.85	10	710.00000305	0.003	2.5
3.85	0	710.00000552	0.000	2.5
3.85	-10	710.00000636	-0.001	2.5
3.85	-20	710.00000273	0.004	2.5
3.85	-30	710.00000441	0.001	2.5

Reference Frequency: LTE Band 17 Mid Channel 710.0 MHz @ 20°C				
Limit: +/- 2.5 ppm = 1775.000 Hz				
Power Supply [Vdc]	Environment Temperature [°C]	Frequency Deviation Measured with Time Elapse		
		[MHz]	Delta [ppm]	Limit [ppm]
3.85	20	710.00000544	0	2.5
4.40	20	710.00000872	-0.005	2.5
3.60	20	710.00000459	0.001	2.5

LTE Band 5, Channel 20524, Frequency 836.5 MHz

WCDMA Band 5, Channel 4183, Frequency 836.6 MHz

GSM 850, Channel 190, Frequency 836.6 MHz

Reference Frequency: LTE Band 5 Mid Channel 836.5 MHz @ 20°C				
Limit: +- 2.5 ppm = 2091.250 Hz				
Power Supply [Vdc]	Environment Temperature [°C]	Frequency Deviation Measured with Time Elapse		
		[MHz]	Delta [ppm]	Limit [ppm]
3.85	50	836.50000525	0.001	2.5
3.85	40	836.50000829	-0.002	2.5
3.85	30	836.50000678	0.000	2.5
3.85	20	836.50000641	0	2.5
3.85	10	836.50000707	-0.001	2.5
3.85	0	836.50000588	0.001	2.5
3.85	-10	836.50001222	-0.007	2.5
3.85	-20	836.50000599	0.001	2.5
3.85	-30	836.50000484	0.002	2.5

Reference Frequency: LTE Band 5 Mid Channel 836.5 MHz @ 20°C				
Limit: +- 2.5 ppm = 2091.250 Hz				
Power Supply [Vdc]	Environment Temperature [°C]	Frequency Deviation Measured with Time Elapse		
		[MHz]	Delta [ppm]	Limit [ppm]
3.85	20	836.50000641	0	2.5
4.40	20	836.50000859	-0.003	2.5
3.60	20	836.50000606	0.000	2.5

LTE Band 4, Channel 20174, Frequency 1732.5 MHz

WCDMA Band 4, Channel 1413, Frequency 1732.6 MHz

Reference Frequency: LTE Band 4 Mid Channel 1732.5 MHz @ 20°C				
Limit: +/- 2.5 ppm = 4331.250 Hz				
Power Supply [Vdc]	Environment Temperature [°C]	Frequency Deviation Measured with Time Elapse		
		[MHz]	Delta [ppm]	Limit [ppm]
3.85	50	1732.49998870	0.002	2.5
3.85	40	1732.49999154	0.000	2.5
3.85	30	1732.49999021	0.001	2.5
3.85	20	1732.49999190	0	2.5
3.85	10	1732.49999003	0.001	2.5
3.85	0	1732.49999476	-0.002	2.5
3.85	-10	1732.49999508	-0.002	2.5
3.85	-20	1732.49999260	0.000	2.5
3.85	-30	1732.49999083	0.001	2.5

Reference Frequency: LTE Band 4 Mid Channel 1732.5 MHz @ 20°C				
Limit: +/- 2.5 ppm = 4331.250 Hz				
Power Supply [Vdc]	Environment Temperature [°C]	Frequency Deviation Measured with Time Elapse		
		[MHz]	Delta [ppm]	Limit [ppm]
3.85	20	1732.49999190	0	2.5
4.40	20	1732.49999286	-0.001	2.5
3.60	20	1732.49998907	0.002	2.5

LTE Band 2, Channel 18900, Frequency 1880.0 MHz

WCDMA Band 2, Channel 9400, Frequency 1880.0 MHz

GSM 1900, Channel 661, Frequency 1880.0 MHz

Reference Frequency: LTE Band 2 Mid Channel 1880.0 MHz @ 20°C				
Limit: +- 2.5 ppm = 4700.000 Hz				
Power Supply [Vdc]	Environment Temperature [°C]	Frequency Deviation Measured with Time Elapse		
		[MHz]	Delta [ppm]	Limit [ppm]
3.85	50	1880.00001875	-0.004	2.5
3.85	40	1880.00001763	-0.004	2.5
3.85	30	1880.00001456	-0.002	2.5
3.85	20	1880.00001034	0	2.5
3.85	10	1880.00000851	0.001	2.5
3.85	0	1880.00000921	0.001	2.5
3.85	-10	1880.00000850	0.001	2.5
3.85	-20	1880.00001233	-0.001	2.5
3.85	-30	1880.00001358	-0.002	2.5

Reference Frequency: LTE Band 2 Mid Channel 1880.0 MHz @ 20°C				
Limit: +- 2.5 ppm = 4700.000 Hz				
Power Supply [Vdc]	Environment Temperature [°C]	Frequency Deviation Measured with Time Elapse		
		[MHz]	Delta [ppm]	Limit [ppm]
3.85	20	1880.00001034	0	2.5
4.40	20	1880.00001232	-0.001	2.5
3.60	20	1880.00000859	0.001	2.5

11. RADIATED TEST RESULTS

11.1. RADIATED POWER (ERP & EIRP)

RULE PART(S)

FCC: §2.1046, §22.913, §24.232 and §27.50

LIMITS

22.913(a) - The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

24.232(c) - Mobile/portable stations are limited to 2 watts e.i.r.p. peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications.

27.50(c) - (10) Portable stations (hand-held devices) are limited to 3 watts ERP; (LTE B17)

27.50(d) - (4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.(Band 4)

In addition, when the transmitter power is measured in terms of average value, the peak-to-average ratio of the power shall not exceed 13dB.

TEST PROCEDURE

ANSI / TIA / EIA 603D Clause 2.2.17; MXA setting reference to 971168 D01 v02r02

For peak power measurement with a MXA:

a) Set the RBW $\geq$ OBW; b) Set VBW $\geq 3 \times$ RBW; c) Set span $\geq 2 \times$ RBW; d) Sweep time = auto couple; e) Detector = peak; f) Ensure that the number of measurement points $\geq$ span/RBW; g) Trace mode = max hold;

For average power measurement with a MXA:

a) Set span to at least 1.5 times the OBW; b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz; c) Set VBW $\geq 3 \times$ RBW; d) Set number of points in sweep $\geq 2 \times$ span / RBW; e) Sweep time = auto-couple; f) Detector = RMS (power averaging); g) Use free run trigger If burst duty cycle ≥ 98 ; h) Use trigger to capture bursts If burst duty cycle < 98 ; i) Trace average at least 100 traces in power averaging (*i.e.*, RMS) mode. j) Compute the power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function.

TEST RESULTS

11.1.1. ERP/EIRP Results

GSM

Band	Mode	Channel	f [MHz]	ERP / EIRP	
				[dBm]	[mW]
GSM850	GPRS	512	824.2	28.63	729.46
		661	836.6	27.35	543.25
		810	848.8	26.94	494.31
	EGPRS	512	824.2	23.42	219.79
		661	836.6	22.10	162.18
		810	848.8	20.88	122.46
GSM1900	GPRS	512	1850.2	29.53	897.43
		661	1880.0	29.61	914.11
		810	1909.8	30.00	1000.00
	EGPRS	512	1850.2	26.05	402.72
		661	1880.0	26.35	431.52
		810	1909.8	26.59	456.04

WCDMA

Band	Mode	Channel	f [MHz]	ERP / EIRP	
				[dBm]	[mW]
Band 5	REL99	4132	826.4	16.15	41.21
		4183	836.6	16.15	41.21
		4233	846.6	17.05	50.70
	HSDPA	4132	826.4	17.36	54.45
		4183	836.6	15.41	34.75
		4233	846.6	15.86	38.55
Band 4	REL99	1312	1712.4	21.71	148.25
		1413	1732.6	22.41	174.18
		1513	1752.6	22.45	175.79
	HSDPA	1312	1712.4	22.23	167.11
		1413	1732.6	20.08	101.86
		1513	1752.6	22.99	199.07
Band 2	REL99	9262	1852.4	21.97	157.40
		9400	1880.0	22.23	167.11
		9538	1907.6	23.26	211.84
	HSDPA	9262	1852.4	18.86	76.91
		9400	1880.0	20.56	113.76
		9538	1907.6	21.67	146.89

LTE Band 17

Band	BW [MHz]	Mode	RB/RB Size	f [MHz]	ERP / EIRP	
			Full RB		[dBm]	[mW]
Band 17	10	QPSK	50/0	709.0	11.10	12.88
			50/0	710.0	10.81	12.05
			50/0	711.0	11.22	13.24
		16QAM	50/0	709.0	10.64	11.59
			50/0	710.0	10.43	11.04
			50/0	711.0	10.74	11.86
	5	QPSK	25/0	706.5	11.08	12.82
			25/0	710.0	10.96	12.47
			25/0	713.5	10.64	11.59
		16QAM	25/0	706.5	10.56	11.38
			25/0	710.0	10.70	11.75
			25/0	713.5	10.20	10.47

LTE Band 5

Band	BW [MHz]	Mode	RB/RB Size	f [MHz]	ERP / EIRP	
			Full RB		[dBm]	[mW]
Band 5	10	QPSK	50/0	829.0	14.21	26.36
			50/0	836.5	11.69	14.76
			50/0	844.0	14.49	28.12
		16QAM	50/0	829.0	13.88	24.43
			50/0	836.5	13.38	21.78
			50/0	844.0	14.24	26.55
	5	QPSK	25/0	826.5	14.66	29.24
			25/0	836.5	13.89	24.49
			25/0	846.5	14.18	26.18
		16QAM	25/0	826.5	14.25	26.61
			25/0	836.5	13.41	21.93
			25/0	846.5	14.33	27.10
	3	QPSK	15/0	825.5	14.53	28.38
			15/0	836.5	14.03	25.29
			15/0	847.5	14.59	28.77
		16QAM	15/0	825.5	14.16	26.06
			15/0	836.5	13.62	23.01
			15/0	847.5	14.82	30.34
	1.4	QPSK	6/0	824.7	12.62	18.28
			6/0	836.5	11.83	15.24
			6/0	848.3	11.78	15.07
		16QAM	6/0	824.7	12.30	16.98
			6/0	836.5	11.33	13.58
			6/0	848.3	11.69	14.76

LTE Band 4

Band	BW [MHz]	Mode	RB/RB Size	f [MHz]	ERP / EIRP	
			Full RB		[dBm]	[mW]
Band 4	20	QPSK	100/0	1720.0	19.87	97.05
			100/0	1732.5	19.39	86.90
			100/0	1745.0	19.28	84.72
		16QAM	100/0	1720.0	19.50	89.13
			100/0	1732.5	19.09	81.10
			100/0	1745.0	18.85	76.74
	15	QPSK	75/0	1717.5	19.76	94.62
			75/0	1732.5	19.45	88.10
			75/0	1747.5	19.08	80.91
		16QAM	75/0	1717.5	19.49	88.92
			75/0	1732.5	19.12	81.66
			75/0	1747.5	18.80	75.86
	10	QPSK	50/0	1715.0	19.95	98.86
			50/0	1732.5	19.51	89.33
			50/0	1750.0	19.07	80.72
		16QAM	50/0	1715.0	19.63	91.83
			50/0	1732.5	19.16	82.41
			50/0	1750.0	18.73	74.64
	5	QPSK	25/0	1712.5	20.07	101.62
			25/0	1732.5	19.62	91.62
			25/0	1752.5	18.94	78.34
		16QAM	25/0	1712.5	19.73	93.97
			25/0	1732.5	19.27	84.53
			25/0	1752.5	18.66	73.45
	3	QPSK	15/0	1711.5	20.16	103.75
			15/0	1732.5	19.71	93.54
			15/0	1753.5	19.03	79.98
		16QAM	15/0	1711.5	19.80	95.50
			15/0	1732.5	19.51	89.33
			15/0	1753.5	18.77	75.34
	1.4	QPSK	6/0	1710.7	17.73	59.29
			6/0	1732.5	17.42	55.21
			6/0	1754.3	16.48	44.46
		16QAM	6/0	1710.7	17.38	54.70
			6/0	1732.5	16.95	49.55
			6/0	1754.3	16.25	42.17

LTE Band 2

Band	BW [MHz]	Mode	RB/RB Size	f [MHz]	ERP / EIRP	
			Full RB		[dBm]	[mW]
Band 2	20	QPSK	100/0	1860.0	19.43	87.70
			100/0	1880.0	19.12	81.66
			100/0	1900.0	19.90	97.72
		16QAM	100/0	1860.0	19.53	89.74
			100/0	1880.0	19.15	82.22
			100/0	1900.0	19.90	97.72
	15	QPSK	75/0	1857.5	19.68	92.90
			75/0	1880.0	19.73	93.97
			75/0	1902.5	20.84	121.34
		16QAM	75/0	1857.5	19.79	95.28
			75/0	1880.0	19.74	94.19
			75/0	1902.5	20.91	123.31
	10	QPSK	50/0	1955.0	20.33	107.89
			50/0	1880.0	19.48	88.72
			50/0	1905.0	20.30	107.15
		16QAM	50/0	1955.0	20.29	106.91
			50/0	1880.0	19.54	89.95
			50/0	1905.0	20.42	110.15
	5	QPSK	25/0	1852.5	20.01	100.23
			25/0	1880.0	20.08	101.86
			25/0	1907.5	20.85	121.62
		16QAM	25/0	1852.5	20.04	100.93
			25/0	1880.0	20.03	100.69
			25/0	1907.5	20.95	124.45
	3	QPSK	15/0	1815.5	20.02	100.46
			15/0	1880.0	19.32	85.51
			15/0	1908.5	20.31	107.40
		16QAM	15/0	1815.5	20.06	101.39
			15/0	1880.0	19.44	87.90
			15/0	1908.5	20.59	114.55
	1.4	QPSK	6/0	1850.7	19.59	90.99
			6/0	1880.0	20.07	101.62
			6/0	1909.3	21.62	145.21
		16QAM	6/0	1850.7	19.49	88.92
			6/0	1880.0	19.96	99.08
			6/0	1909.3	21.69	147.57

11.1.2. ERP/EIRP DATA

GSM 850

GSM GSM850 GPRS	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 16K22923 Date: 02-25-16 Test Engineer: Steven Kim Configuration: EUT ONLY, X Position Mode: GPRS 850 MHz Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	824.20	31.25	V	1.1	-1.6	28.63	38.5	-9.8	
	824.20	20.46	H	1.1	-1.6	17.84	38.5	-20.6	
	Mid Ch								
	836.60	29.84	V	1.1	-1.4	27.35	38.5	-11.1	
	836.60	19.45	H	1.1	-1.4	16.96	38.5	-21.5	
	High Ch								
	848.80	29.30	V	1.1	-1.3	26.94	38.5	-11.5	
	848.80	19.06	H	1.1	-1.3	16.70	38.5	-21.8	
	Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm								
GSM GSM850 EGPRS	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 16K22923 Date: 02-25-16 Test Engineer: Steven Kim Configuration: EUT ONLY, X Position Mode: EGPRS 850 MHz Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	824.20	26.04	V	1.1	-1.6	23.42	38.5	-15.0	
	824.20	15.56	H	1.1	-1.6	12.94	38.5	-25.5	
	Mid Ch								
	836.60	24.59	V	1.1	-1.4	22.10	38.5	-16.4	
	836.60	13.91	H	1.1	-1.4	11.42	38.5	-27.0	
	High Ch								
	848.80	23.24	V	1.1	-1.3	20.88	38.5	-17.6	
	848.80	13.09	H	1.1	-1.3	10.73	38.5	-27.7	
	Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm								

GSM 1900

GSM

GSM1900

GPRS

High Frequency Substitution Measurement

UL Korea, Ltd. Suwon Laboratory Chamber 2

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

Samsung

16K22923

02-22-16

Steven Kim

EUT ONLY, X Position

GPRS 1900MHz

Test Equipment:

Receiving: 3117[00168724] and Chamber 1 SMA Cables

Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1850.20	12.3	V	1.60	8.80	19.47	33.0	-13.5	
1850.20	22.3	H	1.60	8.80	29.53	33.0	-3.5	
Mid Ch								
1880.00	7.0	V	1.62	8.62	13.99	33.0	-19.0	
1880.00	22.6	H	1.62	8.62	29.61	33.0	-3.4	
High Ch								
1909.80	7.6	V	1.63	8.44	14.38	33.0	-18.6	
1909.80	23.2	H	1.63	8.44	30.00	33.0	-3.0	

Rev. 3.17.11

GSM

GSM1900

EGPRS

High Frequency Substitution Measurement

UL Korea, Ltd. Suwon Laboratory Chamber 2

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

Samsung

16K22923

02-22-16

Steven Kim

EUT ONLY, X Position

EGPRS 1900MHz

Test Equipment:

Receiving: 3117[00168724] and Chamber 1 SMA Cables

Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1850.20	9.5	V	1.60	8.80	16.67	33.0	-16.3	
1850.20	18.9	H	1.60	8.80	26.05	33.0	-7.0	
Mid Ch								
1880.00	4.1	V	1.62	8.62	11.13	33.0	-21.9	
1880.00	19.4	H	1.62	8.62	26.35	33.0	-6.6	
High Ch								
1909.80	4.1	V	1.63	8.44	10.87	33.0	-22.1	
1909.80	19.8	H	1.63	8.44	26.59	33.0	-6.4	

Rev. 3.17.11

WCDMA Band 4

WCDMA Band 4 REL99	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 16K22923 Date: 02-26-16 Test Engineer: Steven Kim Configuration: EUT ONLY, X Position Mode: Rel 99_1700 MHz Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse <table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBi)</th><th>EIRP (dBm)</th><th>Limit (dBm)</th><th>Margin (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1712.40</td><td>6.62</td><td>V</td><td>1.54</td><td>9.20</td><td>14.28</td><td>30.0</td><td>-15.7</td></tr><tr><td>1712.40</td><td>14.05</td><td>H</td><td>1.54</td><td>9.20</td><td>21.71</td><td>30.0</td><td>-8.3</td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1732.60</td><td>9.44</td><td>V</td><td>1.55</td><td>9.31</td><td>17.20</td><td>30.0</td><td>-12.8</td></tr><tr><td>1732.60</td><td>14.65</td><td>H</td><td>1.55</td><td>9.31</td><td>22.41</td><td>30.0</td><td>-7.6</td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1752.60</td><td>8.88</td><td>V</td><td>1.56</td><td>9.38</td><td>16.70</td><td>30.0</td><td>-13.3</td></tr><tr><td>1752.60</td><td>14.63</td><td>H</td><td>1.56</td><td>9.38</td><td>22.45</td><td>30.0</td><td>-7.6</td></tr></table> Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes	Low Ch								1712.40	6.62	V	1.54	9.20	14.28	30.0	-15.7	1712.40	14.05	H	1.54	9.20	21.71	30.0	-8.3	Mid Ch								1732.60	9.44	V	1.55	9.31	17.20	30.0	-12.8	1732.60	14.65	H	1.55	9.31	22.41	30.0	-7.6	High Ch								1752.60	8.88	V	1.56	9.38	16.70	30.0	-13.3	1752.60	14.63	H	1.56	9.38	22.45	30.0	-7.6
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes																																																																																	
	Low Ch																																																																																									
	1712.40	6.62	V	1.54	9.20	14.28	30.0	-15.7																																																																																		
	1712.40	14.05	H	1.54	9.20	21.71	30.0	-8.3																																																																																		
	Mid Ch																																																																																									
	1732.60	9.44	V	1.55	9.31	17.20	30.0	-12.8																																																																																		
	1732.60	14.65	H	1.55	9.31	22.41	30.0	-7.6																																																																																		
	High Ch																																																																																									
	1752.60	8.88	V	1.56	9.38	16.70	30.0	-13.3																																																																																		
1752.60	14.63	H	1.56	9.38	22.45	30.0	-7.6																																																																																			
WCDMA Band 4 HSDPA	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 16K22923 Date: 02-26-16 Test Engineer: Steven Kim Configuration: EUT ONLY, X Position Mode: HSDPA_1700 MHz Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse <table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBi)</th><th>EIRP (dBm)</th><th>Limit (dBm)</th><th>Margin (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1712.40</td><td>6.73</td><td>V</td><td>1.54</td><td>9.20</td><td>14.39</td><td>30.0</td><td>-15.6</td></tr><tr><td>1712.40</td><td>14.57</td><td>H</td><td>1.54</td><td>9.20</td><td>22.23</td><td>30.0</td><td>-7.8</td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1732.60</td><td>7.89</td><td>V</td><td>1.55</td><td>9.31</td><td>15.65</td><td>30.0</td><td>-14.4</td></tr><tr><td>1732.60</td><td>12.32</td><td>H</td><td>1.55</td><td>9.31</td><td>20.08</td><td>30.0</td><td>-9.9</td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1752.60</td><td>10.52</td><td>V</td><td>1.56</td><td>9.38</td><td>18.34</td><td>30.0</td><td>-11.7</td></tr><tr><td>1752.60</td><td>15.17</td><td>H</td><td>1.56</td><td>9.38</td><td>22.99</td><td>30.0</td><td>-7.0</td></tr></table> Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes	Low Ch								1712.40	6.73	V	1.54	9.20	14.39	30.0	-15.6	1712.40	14.57	H	1.54	9.20	22.23	30.0	-7.8	Mid Ch								1732.60	7.89	V	1.55	9.31	15.65	30.0	-14.4	1732.60	12.32	H	1.55	9.31	20.08	30.0	-9.9	High Ch								1752.60	10.52	V	1.56	9.38	18.34	30.0	-11.7	1752.60	15.17	H	1.56	9.38	22.99	30.0	-7.0
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes																																																																																	
	Low Ch																																																																																									
	1712.40	6.73	V	1.54	9.20	14.39	30.0	-15.6																																																																																		
	1712.40	14.57	H	1.54	9.20	22.23	30.0	-7.8																																																																																		
	Mid Ch																																																																																									
	1732.60	7.89	V	1.55	9.31	15.65	30.0	-14.4																																																																																		
	1732.60	12.32	H	1.55	9.31	20.08	30.0	-9.9																																																																																		
	High Ch																																																																																									
	1752.60	10.52	V	1.56	9.38	18.34	30.0	-11.7																																																																																		
1752.60	15.17	H	1.56	9.38	22.99	30.0	-7.0																																																																																			

WCDMA Band 2

WCDMA Band 2 REL99	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 16K22923 Date: 02-22-16 Test Engineer: Steven.Kim Configuration: EUT ONLY, X Position Mode: REL99_1900 MHz Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse <table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBi)</th><th>EIRP (dBm)</th><th>Limit (dBm)</th><th>Margin (dB)</th><th>Notes</th></tr><tr><td colspan="9">Low Ch</td></tr><tr><td>1852.40</td><td>4.79</td><td>V</td><td>1.60</td><td>8.79</td><td>11.98</td><td>33.0</td><td>-21.0</td><td></td></tr><tr><td>1852.40</td><td>14.78</td><td>H</td><td>1.60</td><td>8.79</td><td>21.97</td><td>33.0</td><td>-11.0</td><td></td></tr><tr><td colspan="9">Mid Ch</td></tr><tr><td>1880.00</td><td>0.65</td><td>V</td><td>1.62</td><td>8.62</td><td>7.65</td><td>33.0</td><td>-25.3</td><td></td></tr><tr><td>1880.00</td><td>15.23</td><td>H</td><td>1.62</td><td>8.62</td><td>22.23</td><td>33.0</td><td>-10.8</td><td></td></tr><tr><td colspan="9">High Ch</td></tr><tr><td>1907.60</td><td>6.04</td><td>V</td><td>1.63</td><td>8.45</td><td>12.86</td><td>33.0</td><td>-20.1</td><td></td></tr><tr><td>1907.60</td><td>16.44</td><td>H</td><td>1.63</td><td>8.45</td><td>23.26</td><td>33.0</td><td>-9.7</td><td></td></tr></table> Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes	Low Ch									1852.40	4.79	V	1.60	8.79	11.98	33.0	-21.0		1852.40	14.78	H	1.60	8.79	21.97	33.0	-11.0		Mid Ch									1880.00	0.65	V	1.62	8.62	7.65	33.0	-25.3		1880.00	15.23	H	1.62	8.62	22.23	33.0	-10.8		High Ch									1907.60	6.04	V	1.63	8.45	12.86	33.0	-20.1		1907.60	16.44	H	1.63	8.45	23.26	33.0	-9.7	
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes																																																																																										
	Low Ch																																																																																																		
	1852.40	4.79	V	1.60	8.79	11.98	33.0	-21.0																																																																																											
	1852.40	14.78	H	1.60	8.79	21.97	33.0	-11.0																																																																																											
	Mid Ch																																																																																																		
	1880.00	0.65	V	1.62	8.62	7.65	33.0	-25.3																																																																																											
	1880.00	15.23	H	1.62	8.62	22.23	33.0	-10.8																																																																																											
	High Ch																																																																																																		
	1907.60	6.04	V	1.63	8.45	12.86	33.0	-20.1																																																																																											
1907.60	16.44	H	1.63	8.45	23.26	33.0	-9.7																																																																																												
WCDMA Band 2 HSDPA	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 16K22923 Date: 02-22-16 Test Engineer: Steven.Kim Configuration: EUT ONLY, X Position Mode: HSDPA_1900 MHz Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse <table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBi)</th><th>EIRP (dBm)</th><th>Limit (dBm)</th><th>Margin (dB)</th><th>Notes</th></tr><tr><td colspan="9">Low Ch</td></tr><tr><td>1852.40</td><td>1.22</td><td>V</td><td>1.60</td><td>8.79</td><td>8.41</td><td>33.0</td><td>-24.6</td><td></td></tr><tr><td>1852.40</td><td>11.67</td><td>H</td><td>1.60</td><td>8.79</td><td>18.86</td><td>33.0</td><td>-14.1</td><td></td></tr><tr><td colspan="9">Mid Ch</td></tr><tr><td>1880.00</td><td>-1.10</td><td>V</td><td>1.62</td><td>8.62</td><td>5.90</td><td>33.0</td><td>-27.1</td><td></td></tr><tr><td>1880.00</td><td>13.56</td><td>H</td><td>1.62</td><td>8.62</td><td>20.56</td><td>33.0</td><td>-12.4</td><td></td></tr><tr><td colspan="9">High Ch</td></tr><tr><td>1907.60</td><td>-0.25</td><td>V</td><td>1.63</td><td>8.45</td><td>6.57</td><td>33.0</td><td>-26.4</td><td></td></tr><tr><td>1907.60</td><td>14.85</td><td>H</td><td>1.63</td><td>8.45</td><td>21.67</td><td>33.0</td><td>-11.3</td><td></td></tr></table> Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes	Low Ch									1852.40	1.22	V	1.60	8.79	8.41	33.0	-24.6		1852.40	11.67	H	1.60	8.79	18.86	33.0	-14.1		Mid Ch									1880.00	-1.10	V	1.62	8.62	5.90	33.0	-27.1		1880.00	13.56	H	1.62	8.62	20.56	33.0	-12.4		High Ch									1907.60	-0.25	V	1.63	8.45	6.57	33.0	-26.4		1907.60	14.85	H	1.63	8.45	21.67	33.0	-11.3	
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes																																																																																										
	Low Ch																																																																																																		
	1852.40	1.22	V	1.60	8.79	8.41	33.0	-24.6																																																																																											
	1852.40	11.67	H	1.60	8.79	18.86	33.0	-14.1																																																																																											
	Mid Ch																																																																																																		
	1880.00	-1.10	V	1.62	8.62	5.90	33.0	-27.1																																																																																											
	1880.00	13.56	H	1.62	8.62	20.56	33.0	-12.4																																																																																											
	High Ch																																																																																																		
	1907.60	-0.25	V	1.63	8.45	6.57	33.0	-26.4																																																																																											
1907.60	14.85	H	1.63	8.45	21.67	33.0	-11.3																																																																																												

LTE Band 17

LTE Band 17 10MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2																																																																																																	
	Company:		Samsung																																																																																															
	Project #:		16K22923																																																																																															
	Date:		02-24-16																																																																																															
	Test Engineer:		Steven Kim																																																																																															
	Configuration:		EUT / X-Position																																																																																															
	Mode:		LTE Band 17, QPSK, 10MHz																																																																																															
	Test Equipment:																																																																																																	
	Receiving: VULB9163-750, and 3m Chamber N-type Cable (Setup this one for testing EUT)																																																																																																	
	Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.																																																																																																	
<table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBd)</th><th>EIRP (dBm)</th><th>Limit (dBm)</th><th>Margin (dB)</th><th>Notes</th></tr><tr><td colspan="9">Low Ch</td></tr><tr><td>709.00</td><td>3.27</td><td>V</td><td>1.0</td><td>-1.6</td><td>0.67</td><td>34.8</td><td>-34.1</td><td></td></tr><tr><td>709.00</td><td>13.70</td><td>H</td><td>1.0</td><td>-1.6</td><td>11.10</td><td>34.8</td><td>-23.7</td><td></td></tr><tr><td colspan="9">Mid Ch</td></tr><tr><td>710.00</td><td>6.12</td><td>V</td><td>1.0</td><td>-1.6</td><td>3.52</td><td>34.8</td><td>-31.3</td><td></td></tr><tr><td>710.00</td><td>13.41</td><td>H</td><td>1.0</td><td>-1.6</td><td>10.81</td><td>34.8</td><td>-24.0</td><td></td></tr><tr><td colspan="9">High Ch</td></tr><tr><td>711.00</td><td>6.55</td><td>V</td><td>1.0</td><td>-1.6</td><td>3.95</td><td>34.8</td><td>-30.8</td><td></td></tr><tr><td>711.00</td><td>13.82</td><td>H</td><td>1.0</td><td>-1.6</td><td>11.22</td><td>34.8</td><td>-23.6</td><td></td></tr></table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes	Low Ch									709.00	3.27	V	1.0	-1.6	0.67	34.8	-34.1		709.00	13.70	H	1.0	-1.6	11.10	34.8	-23.7		Mid Ch									710.00	6.12	V	1.0	-1.6	3.52	34.8	-31.3		710.00	13.41	H	1.0	-1.6	10.81	34.8	-24.0		High Ch									711.00	6.55	V	1.0	-1.6	3.95	34.8	-30.8		711.00	13.82	H	1.0	-1.6	11.22	34.8	-23.6	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes																																																																																										
Low Ch																																																																																																		
709.00	3.27	V	1.0	-1.6	0.67	34.8	-34.1																																																																																											
709.00	13.70	H	1.0	-1.6	11.10	34.8	-23.7																																																																																											
Mid Ch																																																																																																		
710.00	6.12	V	1.0	-1.6	3.52	34.8	-31.3																																																																																											
710.00	13.41	H	1.0	-1.6	10.81	34.8	-24.0																																																																																											
High Ch																																																																																																		
711.00	6.55	V	1.0	-1.6	3.95	34.8	-30.8																																																																																											
711.00	13.82	H	1.0	-1.6	11.22	34.8	-23.6																																																																																											
Rev. 3.17.11																																																																																																		
Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm																																																																																																		

LTE Band 17 10MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2																																																																																																	
	Company:		Samsung																																																																																															
	Project #:		16K22923																																																																																															
	Date:		02-24-16																																																																																															
	Test Engineer:		Steven Kim																																																																																															
	Configuration:		EUT / X-Position																																																																																															
	Mode:		LTE Band 17 16QAM, 10MHz																																																																																															
	Test Equipment:																																																																																																	
	Receiving: VULB9163-750, and 3m Chamber N-type Cable (Setup this one for testing EUT)																																																																																																	
	Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.																																																																																																	
<table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBd)</th><th>EIRP (dBm)</th><th>Limit (dBm)</th><th>Margin (dB)</th><th>Notes</th></tr><tr><td colspan="9">Low Ch</td></tr><tr><td>709.00</td><td>2.85</td><td>V</td><td>1.0</td><td>-1.6</td><td>0.25</td><td>34.8</td><td>-34.5</td><td></td></tr><tr><td>709.00</td><td>13.24</td><td>H</td><td>1.0</td><td>-1.6</td><td>10.64</td><td>34.8</td><td>-24.1</td><td></td></tr><tr><td colspan="9">Mid Ch</td></tr><tr><td>710.00</td><td>5.75</td><td>V</td><td>1.0</td><td>-1.6</td><td>3.15</td><td>34.8</td><td>-31.6</td><td></td></tr><tr><td>710.00</td><td>13.03</td><td>H</td><td>1.0</td><td>-1.6</td><td>10.43</td><td>34.8</td><td>-24.3</td><td></td></tr><tr><td colspan="9">High Ch</td></tr><tr><td>711.00</td><td>6.02</td><td>V</td><td>1.0</td><td>-1.6</td><td>3.42</td><td>34.8</td><td>-31.4</td><td></td></tr><tr><td>711.00</td><td>13.34</td><td>H</td><td>1.0</td><td>-1.6</td><td>10.74</td><td>34.8</td><td>-24.0</td><td></td></tr></table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes	Low Ch									709.00	2.85	V	1.0	-1.6	0.25	34.8	-34.5		709.00	13.24	H	1.0	-1.6	10.64	34.8	-24.1		Mid Ch									710.00	5.75	V	1.0	-1.6	3.15	34.8	-31.6		710.00	13.03	H	1.0	-1.6	10.43	34.8	-24.3		High Ch									711.00	6.02	V	1.0	-1.6	3.42	34.8	-31.4		711.00	13.34	H	1.0	-1.6	10.74	34.8	-24.0	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes																																																																																										
Low Ch																																																																																																		
709.00	2.85	V	1.0	-1.6	0.25	34.8	-34.5																																																																																											
709.00	13.24	H	1.0	-1.6	10.64	34.8	-24.1																																																																																											
Mid Ch																																																																																																		
710.00	5.75	V	1.0	-1.6	3.15	34.8	-31.6																																																																																											
710.00	13.03	H	1.0	-1.6	10.43	34.8	-24.3																																																																																											
High Ch																																																																																																		
711.00	6.02	V	1.0	-1.6	3.42	34.8	-31.4																																																																																											
711.00	13.34	H	1.0	-1.6	10.74	34.8	-24.0																																																																																											
Rev. 3.17.11																																																																																																		
Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm																																																																																																		

LTE Band 17 5MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-24-16 Test Engineer: Steven Kim Configuration: EUT / X-Position Mode: LTE Band 17, QPSK , 5MHz								
	Test Equipment: Receiving: VULB9163-750, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	706.50	6.23	V	1.0	-1.6	3.63	34.8	-31.1	
	706.50	13.68	H	1.0	-1.6	11.08	34.8	-23.7	
	Mid Ch								
	710.00	6.71	V	1.0	-1.6	4.11	34.8	-30.7	
	710.00	13.56	H	1.0	-1.6	10.96	34.8	-23.8	
	High Ch								
	713.50	5.38	V	1.0	-1.6	2.78	34.8	-32.0	
	713.50	13.24	H	1.0	-1.6	10.64	34.8	-24.1	
Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm									
LTE Band 17 5MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-24-16 Test Engineer: Steven Kim Configuration: EUT / X-Position Mode: LTE Band 17 16QAM, 5MHz								
	Test Equipment: Receiving: VULB9163-750, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	706.50	5.75	V	1.0	-1.6	3.15	34.8	-31.6	
	706.50	13.16	H	1.0	-1.6	10.56	34.8	-24.2	
	Mid Ch								
	710.00	6.35	V	1.0	-1.6	3.75	34.8	-31.0	
	710.00	13.30	H	1.0	-1.6	10.70	34.8	-24.1	
	High Ch								
	713.50	4.90	V	1.0	-1.6	2.30	34.8	-32.5	
	713.50	12.80	H	1.0	-1.6	10.20	34.8	-24.6	
Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm									

LTE Band 5

LTE Band 5 10MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-27-16 Test Engineer: Steven Kim Configuration: EUT ONLY, X Position Mode: TX, LTE BAND 5, 10MHz BW, QPSK								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	829.00	11.38	V	1.1	-1.5	8.80	38.5	-29.7	
	829.00	16.79	H	1.1	-1.5	14.21	38.5	-24.2	
	Mid Ch								
	836.50	10.54	V	1.1	-1.4	8.04	38.5	-30.4	
	836.50	14.18	H	1.1	-1.4	11.69	38.5	-26.8	
	High Ch								
	844.00	10.44	V	1.1	-1.3	8.05	38.5	-30.4	
	844.00	16.91	H	1.1	-1.3	14.49	38.5	-24.0	
	Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm								
LTE Band 5 10MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-27-16 Test Engineer: Steven Kim Configuration: EUT ONLY, X Position Mode: LTE5 10MHz FUND 16QAM								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	829.00	10.99	V	1.1	-1.5	8.41	38.5	-30.0	
	829.00	16.46	H	1.1	-1.5	13.88	38.5	-24.6	
	Mid Ch								
	836.50	10.22	V	1.1	-1.4	7.71	38.5	-30.7	
	836.50	15.89	H	1.1	-1.4	13.38	38.5	-25.1	
	High Ch								
	844.00	10.15	V	1.1	-1.3	7.73	38.5	-30.7	
	844.00	16.66	H	1.1	-1.3	14.24	38.5	-24.2	
	Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm								

LTE Band 5 5MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-27-16 Test Engineer: Steven Kim Configuration: EUT ONLY, X Position Mode: LTE5 5MHz FUND QPSK								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	826.50	11.42	V	1.1	-1.5	8.82	38.5	-29.6	
	826.50	17.26	H	1.1	-1.5	14.66	38.5	-23.8	
	Mid Ch								
	836.50	10.75	V	1.1	-1.4	8.26	38.5	-30.2	
	836.50	16.38	H	1.1	-1.4	13.89	38.5	-24.6	
	High Ch								
	846.50	10.56	V	1.6	-1.3	7.68	38.5	-30.8	
	846.50	17.06	H	1.6	-1.3	14.18	38.5	-24.3	
Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm									
LTE Band 5 5MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-27-16 Test Engineer: Steven Kim Configuration: EUT ONLY, X Position Mode: LTE5 5MHz FUND 16QAM								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	826.50	10.99	V	1.1	-1.5	8.39	38.5	-30.1	
	826.50	16.85	H	1.1	-1.5	14.25	38.5	-24.2	
	Mid Ch								
	836.50	10.36	V	1.1	-1.4	7.87	38.5	-30.6	
	836.50	15.90	H	1.1	-1.4	13.41	38.5	-25.0	
	High Ch								
	846.50	10.21	V	1.1	-1.3	7.83	38.5	-30.6	
	846.50	16.71	H	1.1	-1.3	14.33	38.5	-24.1	
Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm									

LTE Band 5 3MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-27-16 Test Engineer: Steven Kim Configuration: EUT ONLY, X Position Mode: LTE5 3MHz FUND QPSK								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	825.50	11.61	V	1.1	-1.5	9.01	38.5	-29.4	
	825.50	17.13	H	1.1	-1.5	14.53	38.5	-23.9	
	Mid Ch								
	836.50	10.90	V	1.1	-1.4	8.40	38.5	-30.0	
	836.50	16.52	H	1.1	-1.4	14.03	38.5	-24.4	
	High Ch								
	847.50	10.12	V	1.6	-1.3	7.24	38.5	-31.2	
	847.50	17.47	H	1.6	-1.3	14.59	38.5	-23.9	
Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm									
LTE Band 5 3MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-27-16 Test Engineer: Steven Kim Configuration: EUT ONLY, X Position Mode: LTE5 3MHz FUND 16QAM								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	825.50	11.26	V	1.1	-1.5	8.66	38.5	-29.8	
	825.50	16.76	H	1.1	-1.5	14.16	38.5	-24.3	
	Mid Ch								
	836.50	10.43	V	1.1	-1.4	7.94	38.5	-30.5	
	836.50	16.11	H	1.1	-1.4	13.62	38.5	-24.8	
	High Ch								
	847.50	9.94	V	1.1	-1.3	7.56	38.5	-30.9	
	847.50	17.20	H	1.1	-1.3	14.82	38.5	-23.6	
Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm									

LTE Band 5 1.4MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-27-16 Test Engineer: Steven Kim Configuration: EUT ONLY, X Position Mode: LTE5 1.4MHz FUND QPSK								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	824.70	8.88	V	1.1	-1.5	6.28	38.5	-32.2	
	824.70	15.22	H	1.1	-1.5	12.62	38.5	-25.8	
	Mid Ch								
	836.50	8.30	V	1.1	-1.4	5.81	38.5	-32.6	
	836.50	14.32	H	1.1	-1.4	11.83	38.5	-26.6	
	High Ch								
	848.30	7.97	V	1.6	-1.3	5.09	38.5	-33.4	
	848.30	14.66	H	1.6	-1.3	11.78	38.5	-26.7	
Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm									
LTE Band 5 1.4MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-27-16 Test Engineer: Steven Kim Configuration: EUT ONLY, X Position Mode: LTE5 1.4MHz FUND 16QAM								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	824.70	8.40	V	1.1	-1.5	5.80	38.5	-32.7	
	824.70	14.90	H	1.1	-1.5	12.30	38.5	-26.2	
	Mid Ch								
	836.50	8.01	V	1.1	-1.4	5.52	38.5	-32.9	
	836.50	13.82	H	1.1	-1.4	11.33	38.5	-27.1	
	High Ch								
	848.30	7.43	V	1.1	-1.3	5.05	38.5	-33.4	
	848.30	14.07	H	1.1	-1.3	11.69	38.5	-26.8	
Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm									

LTE Band 4

LTE Band 4 20MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-28-16 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4, QPSK, 20MHz								
	Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1720.00	7.87	V	1.54	9.12	15.45	30.0	-14.6	
	1720.00	12.29	H	1.54	9.12	19.87	30.0	-10.1	
	Mid Ch								
	1732.50	7.93	V	1.55	9.31	15.69	30.0	-14.3	
	1732.50	11.63	H	1.55	9.31	19.39	30.0	-10.6	
	High Ch								
	1745.00	6.40	V	1.56	9.37	14.21	30.0	-15.8	
	1745.00	11.47	H	1.56	9.37	19.28	30.0	-10.7	
	Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm								
LTE Band 4 20MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-28-16 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4, 16QAM, 20MHz								
	Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1720.00	7.53	V	1.54	9.12	15.11	30.0	-14.9	
	1720.00	11.92	H	1.54	9.12	19.50	30.0	-10.5	
	Mid Ch								
	1732.50	7.64	V	1.55	9.31	15.40	30.0	-14.6	
	1732.50	11.33	H	1.55	9.31	19.09	30.0	-10.9	
	High Ch								
	1745.00	5.94	V	1.56	9.37	13.75	30.0	-16.3	
	1745.00	11.04	H	1.56	9.37	18.85	30.0	-11.2	
	Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm								

LTE Band 4 15MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-28-16 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4, QPSK, 15MHz								
	Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1717.50	7.60	V	1.54	9.12	15.18	30.0	-14.8	
	1717.50	12.18	H	1.54	9.12	19.76	30.0	-10.2	
	Mid Ch								
	1732.50	8.05	V	1.55	9.31	15.81	30.0	-14.2	
	1732.50	11.69	H	1.55	9.31	19.45	30.0	-10.6	
	High Ch								
	1747.50	6.18	V	1.56	9.39	14.01	30.0	-16.0	
	1747.50	11.25	H	1.56	9.39	19.08	30.0	-10.9	
	Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm								
LTE Band 4 15MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-28-16 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4, 16QAM, 15MHz								
	Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1717.50	7.33	V	1.54	9.12	14.91	30.0	-15.1	
	1717.50	11.91	H	1.54	9.12	19.49	30.0	-10.5	
	Mid Ch								
	1732.50	7.77	V	1.55	9.31	15.53	30.0	-14.5	
	1732.50	11.36	H	1.55	9.31	19.12	30.0	-10.9	
	High Ch								
	1747.50	5.79	V	1.56	9.39	13.62	30.0	-16.4	
	1747.50	10.97	H	1.56	9.39	18.80	30.0	-11.2	
	Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm								

LTE Band 4 10MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-28-16 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4, QPSK, 10MHz								
	Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1715.00	7.54	V	1.54	9.12	15.12	30.0	-14.9	
	1715.00	12.37	H	1.54	9.12	19.95	30.0	-10.1	
	Mid Ch								
	1732.50	8.13	V	1.55	9.31	15.89	30.0	-14.1	
	1732.50	11.75	H	1.55	9.31	19.51	30.0	-10.5	
	High Ch								
	1750.00	5.88	V	1.56	9.40	13.72	30.0	-16.3	
	1750.00	11.23	H	1.56	9.40	19.07	30.0	-10.9	
	Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm								
LTE Band 4 10MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-28-16 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4 16QAM, 10MHz								
	Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1715.00	7.19	V	1.54	9.12	14.77	30.0	-15.2	
	1715.00	12.05	H	1.54	9.12	19.63	30.0	-10.4	
	Mid Ch								
	1732.50	7.79	V	1.55	9.31	15.55	30.0	-14.5	
	1732.50	11.40	H	1.55	9.31	19.16	30.0	-10.8	
	High Ch								
	1750.00	5.55	V	1.56	9.40	13.39	30.0	-16.6	
	1750.00	10.89	H	1.56	9.40	18.73	30.0	-11.3	
	Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm								

LTE Band 4 5MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-28-16 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4, QPSK , 5MHz								
	Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1712.50	7.56	V	1.54	9.12	15.14	30.0	-14.9	
	1712.50	12.49	H	1.54	9.12	20.07	30.0	-9.9	
	Mid Ch								
	1732.50	8.13	V	1.55	9.31	15.89	30.0	-14.1	
	1732.50	11.86	H	1.55	9.31	19.62	30.0	-10.4	
	High Ch								
	1752.50	5.69	V	1.56	9.39	13.52	30.0	-16.5	
	1752.50	11.11	H	1.56	9.39	18.94	30.0	-11.1	
	Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm								
LTE Band 4 5MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-28-16 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4 16QAM, 5MHz								
	Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1712.50	7.14	V	1.54	9.12	14.72	30.0	-15.3	
	1712.50	12.15	H	1.54	9.12	19.73	30.0	-10.3	
	Mid Ch								
	1732.50	7.98	V	1.55	9.31	15.74	30.0	-14.3	
	1732.50	11.51	H	1.55	9.31	19.27	30.0	-10.7	
	High Ch								
	1752.50	5.37	V	1.56	9.39	13.20	30.0	-16.8	
	1752.50	10.83	H	1.56	9.39	18.66	30.0	-11.3	
	Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm								

LTE Band 4 3MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-28-16 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4, QPSK , 3MHz								
	Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1711.50	7.55	V	1.54	9.12	15.13	30.0	-14.9	
	1711.50	12.58	H	1.54	9.12	20.16	30.0	-9.8	
	Mid Ch								
	1732.50	8.41	V	1.55	9.31	16.17	30.0	-13.8	
	1732.50	11.95	H	1.55	9.31	19.71	30.0	-10.3	
	High Ch								
	1753.50	5.61	V	1.56	9.38	13.43	30.0	-16.6	
	1753.50	11.21	H	1.56	9.38	19.03	30.0	-11.0	
	Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm								
LTE Band 4 3MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K22923 Date: 02-28-16 Test Engineer: Steven.Kim Configuration: EUT / X-Position Mode: LTE Band 4 16QAM, 3MHz								
	Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	1711.50	7.23	V	1.54	9.12	14.81	30.0	-15.2	
	1711.50	12.22	H	1.54	9.12	19.80	30.0	-10.2	
	Mid Ch								
	1732.50	8.06	V	1.55	9.31	15.82	30.0	-14.2	
	1732.50	11.75	H	1.55	9.31	19.51	30.0	-10.5	
	High Ch								
	1753.50	5.31	V	1.56	9.38	13.13	30.0	-16.9	
	1753.50	10.95	H	1.56	9.38	18.77	30.0	-11.2	
	Rev. 3.17.11 Note: For Band 4 EIRP limit is 30dBm								