

FCC/IC DTS REPORT

Certification

Applicant Name:
SAMSUNG Electronics Co., Ltd.

Address:
129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Date of Issue:
23 December 2019

Test Site/Location:
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA

Report No.: HCT-RF-1911-FI019-R1

FCC ID:	A3LSMT307U
IC:	649E-SMT307U
APPLICANT:	SAMSUNG Electronics Co., Ltd.

Model: SM-T307U

EUT Type: Tablet

Average Output Power: 802.11b: 18.77 dBm / 802.11g: 18.53 dBm / 802.11n(HT20): 16.91 dBm

Frequency Range: 2412 MHz ~ 2462 MHz

Modulation type: CCK/DSSS/OFDM

FCC Classification: Digital Transmission System(DTS)

FCC Rule Part(s): Part 15.247

IC Rule Part(s): RSS-247 Issue 2 (February 2017), RSS-Gen Issue 5_Amendment 1 (March 2019)

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC/IC Rules under normal use and maintenance.



Report prepared by : Jeong Ho Kim
Engineer of Telecommunication testing center



Approved by : Jong Seok Lee
Manager of Telecommunication testing center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-1911-FI019	11 December 2019	- First Approval Report
HCT-RF-1911-FI019-R1	23 December 2019	- RSS-GEN issue Date updated. - Section 9.7(Page 27) Revised. - Section 9.7(Page 67-69) : channel number is revised.

This test results were applied only to the test methods required by the standard.

This laboratory is not accredited for the test results marked *.

The above Test Report is the accredited test result by KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA. (HCT Accreditation No.: KT197)

Table of Contents

1. EUT DESCRIPTION	4
2. TEST METHODOLOGY	5
EUT CONFIGURATION	5
EUT EXERCISE	5
GENERAL TEST PROCEDURES	5
DESCRIPTION OF TEST MODES	5
3. INSTRUMENT CALIBRATION.....	6
4. FACILITIES AND ACCREDITATIONS	6
FACILITIES	6
EQUIPMENT	6
5. ANTENNA REQUIREMENTS	7
6. MEASUREMENT UNCERTAINTY	7
7. DESCRIPTION OF TESTS.....	8
8. SUMMARY TEST OF RESULTS	28
9. TEST RESULT	30
9.1 DUTY CYCLE.....	30
9.2 6dB BANDWIDTH & 99 % BANDWIDTH	33
9.3 OUTPUT POWER	39
9.4 POWER SPECTRAL DENSITY	45
9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS.....	48
9.6 RADIATED SPURIOUS EMISSIONS	59
9.7 RADIATED RESTRICTED BAND EDGES	67
9.8 RECEIVER SPURIOUS EMISSIONS	71
9.9 POWERLINE CONDUCTED EMISSIONS	72
9.10 CONFIRMATION OF GEO-LOCATION MECHANISM	80
10. LIST OF TEST EQUIPMENT	84
11. ANNEX A_ TEST SETUP PHOTO	86

1. EUT DESCRIPTION

Model	SM-T307U
EUT Type	Tablet
Power Supply	DC 3.85 V
Battery Information	Model: EB-BT307ABY Type: Li-ion Battery
Travel Adapter Information	Model : EP-TA50JWE Manufacture: DONGYANG E&P
Data Cable Information	Model : EP-DR140AWZ Manufacture: KSD
Ear-jack Information	Model : EHS64AVFWE Manufacture: ALMUS
Frequency Range	2 412 MHz ~ 2 462 MHz
Max. RF Output Power	Peak Power (For information only) 802.11b : 24.57 dBm 802.11g : 26.33 dBm 802.11n(HT20) : 24.82 dBm Average Power 802.11b : 18.77 dBm 802.11g : 18.53 dBm 802.11n(HT20) : 16.91 dBm
Modulation Type	DSSS/CCK : 802.11b OFDM : 802.11g, 802.11n
Number of Channels	11 Channels
Antenna Specification	Antenna type: LDS Peak Gain : -0.1 dBi
Date(s) of Tests	October 22, 2019 ~ November 29, 2019
PMN (Product Marketing Number)	Galaxy Tab A4S
HVIN (Hardware Version Identification Number)	SM-T307U
FVIN (Firmware Version Identification Number)	N/A
HMN (Host Marketing Name)	N/A

2. TEST METHODOLOGY

FCC KDB 558074 D01 15.247 Meas Guidance v05r02 dated April 02, 2019 entitled “guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices and the measurement procedure described in ANSI C63.10(Version : 2013) ‘the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices’.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C. / RSS-Gen issue 5, RSS-247 issue 2.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3.75 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013)

DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment's, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

4. FACILITIES AND ACCREDITATIONS

FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032).

For ISED, test facility was accepted dated February 14, 2019 (CAB identifier: KR0032).

EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- (1) The antennas of this E.U.T are permanently attached.
- (2) The E.U.T Complies with the requirement of §15.203

6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.


The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (\pm dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05

7. DESCRIPTION OF TESTS

7.1. Duty Cycle

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to the zero-span measurement method.

The largest available value of RBW is 8 MHz and VBW is 50 MHz.

The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.


1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz (\geq RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = T_{on} / T_{total} and Duty Cycle Factor = $10\log(1/\text{Duty Cycle})$

7.2. 6dB Bandwidth & 99 % Bandwidth

Limit

The minimum permissible 6 dB bandwidth is 500 kHz.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Procedure 11.8.1 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW $\geq 3 \times$ RBW
- 3) Detector = Peak
- 4) Trace mode = max hold
- 5) Sweep = auto couple
- 6) Allow the trace to stabilize
- 7) We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.

Test Procedure (99 % Bandwidth for IC)

The transmitter output is connected to the spectrum analyzer.

RBW = 1% ~ 5% of the occupied bandwidth

VBW $\approx 3 \times$ RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple

Allow the trace to stabilize


Note : We tested OBW using the automatic bandwidth measurement capability of a spectrum analyzer.

7.3. Output Power

Limit

The maximum permissible conducted output power is 1 Watt.

Test Configuration



Test Procedure

The transmitter output is connected to the Power Meter.

- Peak Power (Procedure 11.9.1.3 in ANSI 63.10-2013)
: Measure the peak power of the transmitter.

- Average Power (Procedure 11.9.2.3 in ANSI 63.10-2013)
 - 1) Measure the duty cycle.
 - 2) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
 - 3) Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

Sample Calculation


- Conducted Output Power(Peak) = Reading Value + ATT loss + Cable loss
- Conducted Output Power(Average) = Reading Value + ATT loss + Cable loss + Duty Cycle Factor

7.4. Power Spectral Density

Limit

The transmitter power density average over 1-second interval shall not be greater than 8dBm in any 3kHz BW.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to Procedure 8.4 in KDB 558074 v05r02, Procedure 11.10 in ANSI 63.10-2013.

The spectrum analyzer is set to :

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set span to at least 1.5 times the OBW.
- 3) $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$.
- 4) $VBW \geq 3 \times RBW$.
- 5) Sweep = auto couple
- 6) Detector = power averaging (rms) or sample detector (when rms not available).
- 7) Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / RBW]$.
- 8) Employ trace averaging (rms) mode over a minimum of 100 traces
- 9) Use the peak marker function to determine the maximum amplitude level.
- 10) Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Sample Calculation

- Power Spectral Density = Reading Value + ATT loss + Cable loss


7.5. Conducted Band Edge(Out of Band Emissions) & Conducted Spurious Emissions

Limit

The maximum conducted (Average) output power was used to demonstrate compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz.

[Conducted > 30 dBc]

Test Configuration



Test Procedure

The transmitter output is connected to the spectrum analyzer.

(Procedure 11.11 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW $\geq 3 \times$ RBW
- 3) Set span to encompass the spectrum to be examined
- 4) Detector = Peak
- 5) Trace Mode = max hold
- 6) Sweep time = auto couple
- 7) Ensure that the number of measurement points $\geq 2 \times$ Span/RBW
- 8) Allow trace to fully stabilize.
- 9) Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

Factors for frequency

Freq(MHz)	Factor(dB)
30	20.54
100	20.62
200	20.70
300	20.80
400	20.86
500	20.89
600	20.89
700	20.93
800	20.95
900	20.99
1000	21.01
2000	21.28
2400	21.37
2480	21.39
2500	21.39
3000	21.49
4000	21.65
5000	21.84
5150	21.85
5850	21.91
6000	21.91
7000	22.06
8000	22.18
9000	22.30
10000	22.44
11000	22.52
12000	22.68
13000	22.87
14000	22.81
15000	22.91
16000	22.96
17000	23.03
18000	23.15
19000	23.21
20000	23.29
21000	23.58
22000	23.64
23000	23.67
24000	23.75
25000	23.88
26000	23.98

Note : 1. 2400 ~ 2500 MHz is fundamental frequency range.

2. Factor = Attenuator loss(20 dB) + Cable loss(2ea) + EUT Cable(For Conducted)

7.6. Radiated Test

FCC

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30

IC


Frequency (MHz)	Field Strength (uA/m)	Measurement Distance (m)
0.009 – 0.490	6.37/F(kHz)	300
0.490 – 1.705	63.7/F(kHz)	30
1.705 – 30	0.08	30

FCC&IC


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



Test Procedure of Radiated spurious emissions(Below 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the ground plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor(0.009 MHz – 0.490 MHz) = $40\log(3\text{ m}/300\text{ m}) = - 80\text{ dB}$
Measurement Distance : 3 m
7. Distance Correction Factor(0.490 MHz – 30 MHz) = $40\log(3\text{ m}/30\text{ m}) = - 40\text{ dB}$
Measurement Distance : 3 m
8. Spectrum Setting
 - Frequency Range = 9 kHz ~ 30 MHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 9 kHz
 - VBW ≥ 3 x RBW
9. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

KDB 414788 OFS and Chamber Correlation Justification

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

Test Procedure of Radiated spurious emissions(Below 1GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. Spectrum Setting

(1) Measurement Type(Peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 100 kHz
- VBW \geq 3 x RBW

(2) Measurement Type(Quasi-peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Quasi-Peak
- RBW = 120 kHz

In general, (1) is used mainly

6. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L)
7. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

Test Procedure of Radiated spurious emissions (Above 1 GHz)

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor(reference distance : 3 m).
 - ◆ Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance})$ (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting (Method 8.6 in KDB 558074 v05r02, Procedure 11.12 in ANSI 63.10-2013)
 - (1) Measurement Type(Peak):
 - Measured Frequency Range : 1 GHz – 25 GHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 1 MHz
 - VBW $\geq 3 \times$ RBW
 - (2) Measurement Type(Average): Duty cycle $\geq 98\%$
 - Measured Frequency Range : 1 GHz – 25 GHz
 - Detector = RMS
 - Averaging type = power (*i.e.*, RMS)
 - RBW = 1 MHz
 - VBW $\geq 3 \times$ RBW
 - Sweep time = auto.
 - Trace mode = average (at least 100 traces).
 - (3) Measurement Type(Average): Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$
 - Measured Frequency Range : 1 GHz – 25 GHz
 - Detector = RMS
 - Averaging type = power (*i.e.*, RMS)
 - RBW = 1 MHz
 - VBW $\geq 3 \times$ RBW

- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.
- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

11. Total(Measurement Type : Peak)

$$= \text{Reading Value} + \text{Antenna Factor(A.F)} + \text{Cable Loss(C.L)} - \text{Amp Gain(G)} + \text{Distance Factor(D.F)}$$

Total(Measurement Type : Average, Duty cycle \geq 98%)

$$= \text{Reading Value} + \text{Antenna Factor(A.F)} + \text{Cable Loss(C.L)} - \text{Amp Gain(G)} + \text{Distance Factor(D.F)}$$

Total(Measurement Type : Average, Duty cycle < 98%)

$$= \text{Reading Value} + \text{Antenna Factor(A.F)} + \text{Cable Loss(C.L)} - \text{Amp Gain(G)} + \text{Distance Factor(D.F)} \\ + \text{Duty Cycle Factor}$$

Test Procedure of Radiated Restricted Band Edge

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor(reference distance : 3 m).
 - ◆ Distance extrapolation factor = $20\log(\text{test distance} / \text{specific distance})$ (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting
 - (1) Measurement Type(Peak):

- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW

(2) Measurement Type(Average): Duty cycle $\geq 98\%$,

- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).

(3) Measurement Type(Average): Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.
- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

11. Total(Measurement Type : Peak)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F) – AMP Gain (A.G)
+Attenuator(ATT)

Total(Measurement Type : Average, Duty cycle $\geq 98\%$)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F) – AMP Gain (A.G)
+Attenuator(ATT)

Total(Measurement Type : Average, Duty cycle < 98%)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F) – AMP Gain (A.G)
+Attenuator(ATT) + Duty Cycle Factor

7.7. AC Power line Conducted Emissions

Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56 ^(a)	56 to 46 ^(a)
0.50 to 5	56	46
5 to 30	60	50

^(a)Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

7.8. Receiver Spurious Emissions

Limit


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note:

Measurements for compliance with the limits in table may be performed at distances other than 3 metres.

Test Configuration

30 MHz - 1 GHz



Test Procedure of Receiver Spurious Emissions (Below 1GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

5. Spectrum Setting

(1) Measurement Type(Peak):


- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 100 kHz
- VBW \geq 3 x RBW

(2) Measurement Type(Quasi-peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Quasi-Peak
- RBW = 120 kHz

6. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L)

Above 1 GHz

**Test Procedure of Radiated spurious emissions (Above 1 GHz)**

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor(reference distance : 3 m).

◆ Distance extrapolation factor = $20 \log (\text{test distance} / \text{specific distance})$ (dB)

6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting

(1) Measurement Type(Peak):

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = Peak
- Trace = Maxhold

- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW

(2) Measurement Type(Average):

- We performed using a reduced video BW method was done with the analyzer in linear mode
- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW $\geq 1/\tau$ Hz, where τ = pulse width in seconds

The actual setting value of VBW = 1 kHz

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
11. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

7.9. Worst case configuration and mode

Radiated test

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone, Stand alone + External accessories(Earphone, etc)
 - Worstcase : Stand alone
2. EUT Axis
 - Radiated Spurious Emissions : Y
 - Radiated Restricted Band Edge : Y
3. Duty cycle factor applies only 802.11g/n(Duty cycle < 98%).
4. All data rate of operation were investigated and the test results are worst case in lowest datarate of each mode.
 - 802.11b : 1Mbps
 - 802.11g : 6Mbps
 - 802.11n_HT20 : MCS0
5. All position of loop antenna were investigated and the test result is a no critical peak found at all positions.
 - Position : Horizontal, Vertical, Parallel to the ground plane

AC Power line Conducted Emissions

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone + External accessories(Earphone, etc)+Travel Adapter(Normal),
Stand alone + Travel Adapter(Normal),
Stand alone + External accessories(Earphone, etc)+Travel Adapter(Fast charging),
Stand alone + Travel Adapter(Fast charging)
 - Worstcase : Stand alone + Travel Adapter(Normal and FastCharging)

Conducted test

1. The EUT was configured with data rate of highest power.

8. SUMMARY TEST OF RESULTS

FCC Part

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§15.247(a)(2)	> 500 kHz	Conducted	PASS
Conducted Maximum Output Power	§15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge (Out of Band Emissions)	§15.247(d)	Conducted > 30 dBc		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 7.7		PASS
Radiated Spurious Emissions	§15.247(d), 15.205, 15.209	cf. Section 7.6		Radiated
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 7.6	PASS	

IC Part

Test Description	IC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	RSS-247, 5.2	> 500 kHz	Conducted	PASS
99% Bandwidth	RSS-GEN, 6.7	N/A		PASS
Conducted Maximum Peak Output Power And e.i.r.p.	RSS-247, 5.4.	< 1 Watt <4 Watt(e.i.r.p.)		PASS
Power Spectral Density	RSS-247, 5.2	< 8 dBm / 3 kHz Band		PASS
Band Edge(Out of Band Emissions)	RSS-247, 5.5	Conducted > 30 dBc		PASS
AC Power line Conducted Emissions	RSS-GEN, 8.8	cf. Section 7.7		N/A (Note1)
Radiated Spurious Emissions	RSS-GEN, 8.9	cf. Section 7.6		Radiated
Receiver Spurious Emissions	RSS-GEN, 7	cf. Section 7.8	PASS	
Radiated Restricted Band Edge	RSS-GEN, 8.10	cf. Section 7.6	PASS	


9. TEST RESULT

9.1 DUTY CYCLE


Mode	Data Rate (Mbps)	T _{on} (ms)	T _{total} (ms)	Duty Cycle	Duty Cycle Factor (dB)
802.11b	1	8.600	8.720	0.986	0.060
	2	4.305	4.410	0.976	0.105
	5.5	1.635	1.740	0.940	0.270
	11	0.859	0.979	0.877	0.569
802.11g	6	1.425	1.542	0.924	0.343
	9	0.958	1.058	0.906	0.430
	12	0.724	0.840	0.861	0.649
	18	0.491	0.586	0.838	0.769
	24	0.371	0.469	0.791	1.019
	36	0.255	0.371	0.687	1.632
	48	0.196	0.291	0.673	1.719
	54	0.180	0.276	0.653	1.853
802.11n (HT20)	6.5 (MCS0)	1.335	1.453	0.919	0.368
	13 (MCS1)	0.688	0.780	0.882	0.547
	19.5 (MCS2)	0.470	0.588	0.800	0.969
	26 (MCS3)	0.364	0.479	0.760	1.191
	39 (MCS4)	0.257	0.351	0.732	1.353
	52 (MCS5)	0.200	0.315	0.633	1.988
	58.5 (MCS6)	0.183	0.299	0.613	2.128
	65 (MCS7)	0.167	0.283	0.591	2.286

Test Plots


Duty cycle plot (802.11b(1Mbps))



Duty cycle plot (802.11g(6Mbps))



Duty cycle plot (802.11n(MCS0))



Note:

In order to simplify the report, attached plots were only the most lowest data rate.

9.2 6dB BANDWIDTH & 99 % BANDWIDTH

FCC


802.11b Mode		Measured Bandwidth [MHz]	OBW Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.			
2412	1	11.102	15.737	0.5
2437	6	12.044	15.834	0.5
2462	11	10.137	15.670	0.5

802.11g Mode		Measured Bandwidth [MHz]	OBW Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.			
2412	1	15.556	17.731	0.5
2437	6	15.819	17.744	0.5
2462	11	15.870	17.651	0.5


802.11n Mode		Measured Bandwidth [MHz]	OBW Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.			
2412	1	15.722	18.934	0.5
2437	6	15.820	19.011	0.5
2462	11	15.482	18.895	0.5

Test Plots


6dB Bandwidth plot (802.11b-CH 11)



6dB Bandwidth plot (802.11g-CH 1)



6dB Bandwidth plot (802.11n_HT20-CH 11)



Note:

In order to simplify the report, attached plots were only the most narrow 6 dB BW channel.

99% Bandwidth Measurements(IC)


802.11b Mode		OBW Bandwidth [MHz]	Limit [MHz]
Frequency [MHz]	Channel No.		
2412	1	15.737	N/A
2437	6	15.815	N/A
2462	11	15.675	N/A

802.11g Mode		OBW Bandwidth [MHz]	Limit [MHz]
Frequency [MHz]	Channel No.		
2412	1	18.322	N/A
2437	6	18.566	N/A
2462	11	18.306	N/A


802.11n(HT20) Mode		OBW Bandwidth [MHz]	Limit [MHz]
Frequency [MHz]	Channel No.		
2412	1	19.430	N/A
2437	6	19.601	N/A
2462	11	19.538	N/A

■ Test Plots


99% Bandwidth plot (802.11b-CH 6)



99% Bandwidth plot (802.11g-CH 6)



99% Bandwidth plot (802.11n_HT20-CH 6)



Note:

In order to simplify the report, attached plots were only the most wide 99% Bandwidth channel.

9.3 OUTPUT POWER

Peak Power

1. Power Meter offset = Attenuator loss + Cable loss
 2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.
- So, 21.39 dB is offset for 2.4 GHz Band

802.11b Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)	Power Level Setting
Frequency[MHz]	Channel No.				
2412	1	1	20.82	30.00	19
		2	21.50	30.00	
		5.5	22.90	30.00	
		11	24.52	30.00	
2437	6	1	20.89	30.00	19
		2	21.36	30.00	
		5.5	22.87	30.00	
		11	24.57	30.00	
2462	11	1	18.92	30.00	19
		2	19.31	30.00	
		5.5	20.73	30.00	
		11	22.35	30.00	

802.11g Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)	Power Level Setting
Frequency[MHz]	Channel No.				
2412	1	6	23.93	30.00	18
		9	24.24	30.00	
		12	23.83	30.00	
		18	23.95	30.00	
		24	24.72	30.00	16
		36	24.61	30.00	
		48	24.53	30.00	
		54	24.76	30.00	
2437	6	6	25.44	30.00	18
		9	25.97	30.00	
		12	25.55	30.00	
		18	25.67	30.00	
		24	26.29	30.00	16
		36	26.33	30.00	
		48	24.71	30.00	
		54	24.88	30.00	
2462	11	6	22.92	30.00	16
		9	23.13	30.00	
		12	22.61	30.00	
		18	22.65	30.00	
		24	23.46	30.00	
		36	23.37	30.00	
		48	22.02	30.00	
		54	22.22	30.00	

802.11n(HT20) Mode		MCS Index	Measured Power(dBm)	Limit (dBm)	Power Level Setting
Frequency[MHz]	Channel No.				
2412	1	0	23.76	30.00	17
		1	23.53	30.00	
		2	23.65	30.00	
		3	24.06	30.00	
		4	24.15	30.00	14.5
		5	23.01	30.00	
		6	23.21	30.00	
		7	23.13	30.00	
2437	6	0	24.01	30.00	17
		1	24.25	30.00	
		2	24.33	30.00	
		3	24.77	30.00	
		4	24.82	30.00	14.5
		5	22.92	30.00	
		6	23.12	30.00	
		7	23.03	30.00	
2462	11	0	20.96	30.00	15
		1	21.17	30.00	
		2	21.10	30.00	
		3	21.52	30.00	
		4	21.48	30.00	
		5	20.74	30.00	
		6	20.92	30.00	
		7	20.89	30.00	

Average Power

1. Power Meter offset = Attenuator loss + Cable loss
2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.
So, 21.39 dB is offset for 2.4 GHz Band.

802.11b Mode		Rate (Mbps)	Measured Power (dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)	Power Level Setting
Frequency [MHz]	Channel No.						
2412	1	1	18.56	0.060	18.62	30.00	19
		2	18.58	0.105	18.68	30.00	
		5.5	18.42	0.270	18.69	30.00	
		11	18.20	0.569	18.77	30.00	
2437	6	1	18.40	0.060	18.46	30.00	19
		2	18.36	0.105	18.46	30.00	
		5.5	18.31	0.270	18.58	30.00	
		11	18.07	0.569	18.64	30.00	
2462	11	1	16.72	0.060	16.78	30.00	19
		2	16.68	0.105	16.78	30.00	
		5.5	16.46	0.270	16.73	30.00	
		11	16.32	0.569	16.89	30.00	

802.11g Mode		Rate (Mbps)	Measured Power (dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)	Power Level Setting
Frequency [MHz]	Channel No.						
2412	1	6	16.43	0.343	16.77	30.00	18
		9	16.20	0.430	16.63	30.00	
		12	16.22	0.649	16.87	30.00	
		18	15.96	0.769	16.73	30.00	
		24	15.80	1.019	16.82	30.00	
		36	15.37	1.632	17.00	30.00	
		48	15.10	1.719	16.82	30.00	16
		54	15.04	1.853	16.89	30.00	
2437	6	6	17.78	0.343	18.12	30.00	18
		9	17.66	0.430	18.09	30.00	
		12	17.36	0.649	18.01	30.00	
		18	17.37	0.769	18.14	30.00	
		24	17.22	1.019	18.24	30.00	
		36	16.90	1.632	18.53	30.00	
		48	15.02	1.719	16.74	30.00	16
		54	14.90	1.853	16.75	30.00	
2462	11	6	14.81	0.343	15.15	30.00	16
		9	14.78	0.430	15.21	30.00	
		12	14.63	0.649	15.28	30.00	
		18	14.44	0.769	15.21	30.00	
		24	14.15	1.019	15.17	30.00	
		36	13.87	1.632	15.50	30.00	
		48	12.28	1.719	14.00	30.00	
		54	12.20	1.853	14.05	30.00	

802.11n(HT20) Mode		MCS Index	Measured Power (dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)	Power Level Setting
Frequency [MHz]	Channel No.						
2412	1	0	15.94	0.368	16.31	30.00	17
		1	15.60	0.547	16.15	30.00	
		2	15.51	0.969	16.48	30.00	
		3	15.29	1.191	16.48	30.00	
		4	14.95	1.353	16.30	30.00	
		5	13.47	1.988	15.46	30.00	14.5
		6	13.31	2.128	15.44	30.00	
		7	13.18	2.286	15.47	30.00	
2437	6	0	16.28	0.368	16.65	30.00	17
		1	16.10	0.547	16.65	30.00	
		2	15.91	0.969	16.88	30.00	
		3	15.72	1.191	16.91	30.00	
		4	15.40	1.353	16.75	30.00	
		5	13.19	1.988	15.18	30.00	14.5
		6	13.18	2.128	15.31	30.00	
		7	12.84	2.286	15.13	30.00	
2462	11	0	13.21	0.368	13.58	30.00	15
		1	13.09	0.547	13.64	30.00	
		2	12.88	0.969	13.85	30.00	
		3	12.67	1.191	13.86	30.00	
		4	12.39	1.353	13.74	30.00	
		5	11.27	1.988	13.26	30.00	
		6	11.09	2.128	13.22	30.00	
		7	10.91	2.286	13.20	30.00	

9.4 POWER SPECTRAL DENSITY


Mode	Frequency (MHz)	Channel No.	Test Result			
			Measured PSD (dBm)	Duty Cycle Factor	Measured PSD(dBm) + Duty Cycle Factor	Limit (dBm)
802.11b	2412	1	0.315	0.569	0.884	8
	2437	6	0.962	0.569	1.531	8
	2462	11	-1.585	0.569	-1.016	8
802.11g	2412	1	-3.914	1.632	-2.282	8
	2437	6	-2.040	1.632	-0.408	8
	2462	11	-5.490	1.632	-3.858	8
802.11n	2412	1	-3.928	1.191	-2.737	8
	2437	6	-3.493	1.191	-2.302	8
	2462	11	-6.713	1.191	-5.522	8

Note :


- Spectrum reading values are not plot data.
The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.
- Spectrum offset = Attenuator loss(20 dB) + Cable loss(2ea) + EUT Cable(For Conducted)
- 21.39 dB is offset for 2.4 GHz Band.

☐ Test Plots


Power Spectral Density (802.11b-CH 6)



Power Spectral Density (802.11g-CH 6)



Power Spectral Density (802.11n_HT20 -CH 6)



Note :

In order to simplify the report, attached plots were only the worst case PSD channel.


9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS

Test Result : please refer to the plot below.


In order to simplify the report, attached plots were only the worst case channel and data rate.

☐ Test Plots(BandEdge)


Band Edge (802.11b-CH1)




Band Edge (802.11b-CH11)




Band Edge (802.11g-CH1)




Band Edge (802.11g-CH11)



Band Edge (802.11n_HT20 -CH1)




Band Edge (802.11n_HT20 -CH11)



Test Plots(Conducted Spurious Emission)


30 MHz ~ 1 GHz

Conducted Spurious Emission (802.11b_Ch.1_11 Mbps)




1 GHz ~ 3 GHz

Conducted Spurious Emission (802.11b_Ch.1_11 Mbps)




3 GHz ~ 5 GHz

Conducted Spurious Emission (802.11b_Ch.1_11 Mbps)




5 GHz ~ 7 GHz

Conducted Spurious Emission (802.11b_Ch.1_11 Mbps)




7 GHz ~ 9 GHz

Conducted Spurious Emission (802.11b_Ch.1_11 Mbps)




9 GHz ~ 11 GHz

Conducted Spurious Emission (802.11b_Ch.1_11 Mbps)




11 GHz ~ 13 GHz

Conducted Spurious Emission (802.11b_Ch.1_11 Mbps)




13 GHz ~ 15 GHz

Conducted Spurious Emission (802.11b_Ch.1_11 Mbps)




15 GHz ~ 17 GHz

Conducted Spurious Emission (802.11b_Ch.1_11 Mbps)




17 GHz ~ 19 GHz

Conducted Spurious Emission (802.11b_Ch.1_11 Mbps)




19 GHz ~ 21 GHz

Conducted Spurious Emission (802.11b_Ch.1_11 Mbps)




21 GHz ~ 23 GHz

Conducted Spurious Emission (802.11b_Ch.1_11 Mbps)



23 GHz ~ 25 GHz

Conducted Spurious Emission (802.11b_Ch.1_11 Mbps)



9.6 RADIATED SPURIOUS EMISSIONS

Frequency Range : 9 kHz – 30MHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB)
3. Limit line = specific Limits (dBuV) + Distance extrapolation factor
4. Radiated test is performed with hopping off.

Frequency Range : Below 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

Frequency Range : Above 1 GHz

Operation Mode: 802.11b
 Transfer Rate: 1 Mbps
 Operating Frequency 2412
 Channel No. 01 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	50.60	1.95	V	52.55	73.98	21.43	PK
4824	38.63	1.95	V	40.58	53.98	13.40	AV
7236	49.38	9.86	V	59.24	73.98	14.74	PK
7236	37.51	9.86	V	47.37	53.98	6.61	AV
4824	51.95	1.95	H	53.90	73.98	20.08	PK
4824	39.46	1.95	H	41.41	53.98	12.57	AV
7236	50.07	9.86	H	59.93	73.98	14.05	PK
7236	37.96	9.86	H	47.82	53.98	6.16	AV

Operation Mode: 802.11b
 Transfer Rate: 1 Mbps
 Operating Frequency 2437
 Channel No. 06 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	50.12	2.33	V	52.45	73.98	21.53	PK
4874	37.62	2.33	V	39.95	53.98	14.03	AV
7311	49.48	10.14	V	59.62	73.98	14.36	PK
7311	36.80	10.14	V	46.94	53.98	7.04	AV
4874	50.68	2.33	H	53.01	73.98	20.97	PK
4874	39.19	2.33	H	41.52	53.98	12.46	AV
7311	50.76	10.14	H	60.90	73.98	13.08	PK
7311	37.86	10.14	H	48.00	53.98	5.98	AV

Operation Mode: 802.11b
 Transfer Rate: 1 Mbps
 Operating Frequency: 2462
 Channel No.: 11 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	49.81	2.28	V	52.09	73.98	21.89	PK
4924	38.22	2.28	V	40.50	53.98	13.48	AV
7386	48.62	9.81	V	58.43	73.98	15.55	PK
7386	36.99	9.81	V	46.80	53.98	7.18	AV
4924	51.44	2.28	H	53.72	73.98	20.26	PK
4924	38.63	2.28	H	40.91	53.98	13.07	AV
7386	49.13	9.81	H	58.94	73.98	15.04	PK
7386	37.11	9.81	H	46.92	53.98	7.06	AV

Operation Mode: 802.11g
 Transfer Rate: 6 Mbps
 Operating Frequency: 2412
 Channel No. 01 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4824	50.88	0.00	1.95	V	52.83	73.98	21.15	PK
4824	37.52	0.34	1.95	V	39.81	53.98	14.17	AV
7236	50.02	0.00	9.86	V	59.88	73.98	14.10	PK
7236	37.19	0.34	9.86	V	47.39	53.98	6.59	AV
4824	51.32	0.00	1.95	H	53.27	73.98	20.71	PK
4824	38.82	0.34	1.95	H	41.11	53.98	12.87	AV
7236	50.42	0.00	9.86	H	60.28	73.98	13.70	PK
7236	38.12	0.34	9.86	H	48.32	53.98	5.66	AV

Operation Mode: 802.11g
 Transfer Rate: 6 Mbps
 Operating Frequency: 2437
 Channel No. 06 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4874	50.51	0.00	2.33	V	52.84	73.98	21.14	PK
4874	37.94	0.34	2.33	V	40.61	53.98	13.37	AV
7311	49.63	0.00	10.14	V	59.77	73.98	14.21	PK
7311	37.77	0.34	10.14	V	48.25	53.98	5.73	AV
4874	51.08	0.00	2.33	H	53.41	73.98	20.57	PK
4874	38.88	0.34	2.33	H	41.55	53.98	12.43	AV
7311	50.35	0.00	10.14	H	60.49	73.98	13.49	PK
7311	37.98	0.34	10.14	H	48.46	53.98	5.52	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4924	49.82	0.00	2.28	V	52.10	73.98	21.88	PK
4924	37.66	0.34	2.28	V	40.28	53.98	13.70	AV
7386	48.63	0.00	9.81	V	58.44	73.98	15.54	PK
7386	36.80	0.34	9.81	V	46.95	53.98	7.03	AV
4924	50.35	0.00	2.28	H	52.63	73.98	21.35	PK
4924	38.08	0.34	2.28	H	40.70	53.98	13.28	AV
7386	48.97	0.00	9.81	H	58.78	73.98	15.20	PK
7386	37.22	0.34	9.81	H	47.37	53.98	6.61	AV

Operation Mode: 802.11n (HT20)
 Transfer MCS Index: 0
 Operating Frequency: 2412
 Channel No.: 01 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4824	50.50	0.00	1.95	V	52.45	73.98	21.53	PK
4824	37.65	0.37	1.95	V	39.97	53.98	14.01	AV
7236	50.10	0.00	9.86	V	59.96	73.98	14.02	PK
7236	37.19	0.37	9.86	V	47.42	53.98	6.56	AV
4824	51.38	0.00	1.95	H	53.33	73.98	20.65	PK
4824	38.84	0.37	1.95	H	41.16	53.98	12.82	AV
7236	50.24	0.00	9.86	H	60.10	73.98	13.88	PK
7236	37.07	0.37	9.86	H	47.30	53.98	6.68	AV

Operation Mode: 802.11n (HT20)
 Transfer MCS Index: 0
 Operating Frequency: 2437
 Channel No.: 06 Ch


Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4874	50.99	0.00	2.33	V	53.32	73.98	20.66	PK
4874	37.88	0.37	2.33	V	40.58	53.98	13.40	AV
7311	49.99	0.00	10.14	V	60.13	73.98	13.85	PK
7311	37.22	0.37	10.14	V	47.73	53.98	6.25	AV
4874	51.19	0.00	2.33	H	53.52	73.98	20.46	PK
4874	38.92	0.37	2.33	H	41.62	53.98	12.36	AV
7311	51.45	0.00	10.14	H	61.59	73.98	12.39	PK
7311	38.01	0.37	10.14	H	48.52	53.98	5.46	AV

Operation Mode: 802.11n (HT20)
 Transfer MCS Index: 0
 Operating Frequency: 2462
 Channel No.: 11 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4924	49.65	0.00	2.28	V	51.93	73.98	22.05	PK
4924	37.26	0.37	2.28	V	39.91	53.98	14.07	AV
7386	48.32	0.00	9.81	V	58.13	73.98	15.85	PK
7386	36.19	0.37	9.81	V	46.37	53.98	7.61	AV
4924	50.08	0.00	2.28	H	52.36	73.98	21.62	PK
4924	38.11	0.37	2.28	H	40.76	53.98	13.22	AV
7386	49.16	0.00	9.81	H	58.97	73.98	15.01	PK
7386	37.24	0.37	9.81	H	47.42	53.98	6.56	AV


Test Plots (Worst case : Y-H)

Radiated Spurious Emissions plot – Average Reading (802.11n (HT20)_MCS0, Ch.6 3rd Harmonic)



Date: 1.NOV.2019 13:54:16

Radiated Spurious Emissions plot – Peak Reading (802.11n (HT20)_MCS0, Ch.6 3rd Harmonic)



Date: 1.NOV.2019 13:55:10

Note:

Plot of worst case are only reported.

9.7 RADIATED RESTRICTED BAND EDGES

Operation Mode: 802.11b
 Transfer Rate: 1 Mbps
 Operating Frequency: 2412 MHz, 2462 MHz
 Channel No. 01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.+D.F. -A.G+ATT [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	54.50	0.85	H	55.35	73.98	18.63	PK
2390.0	45.36	0.85	H	46.21	53.98	7.77	AV
2390.0	53.22	0.85	V	54.07	73.98	19.91	PK
2390.0	44.18	0.85	V	45.03	53.98	8.95	AV
2483.5	55.96	1.13	H	57.09	73.98	16.89	PK
2483.5	44.53	1.13	H	45.66	53.98	8.32	AV
2483.5	54.27	1.13	V	55.40	73.98	18.58	PK
2483.5	45.07	1.13	V	46.20	53.98	7.78	AV

Operation Mode: 802.11g
 Transfer Rate: 6 Mbps
 Operating Frequency: 2412 MHz, 2462 MHz
 Channel No. 01 Ch, 10 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. -A.G+ATT. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	66.98	0.00	0.85	H	67.83	73.98	6.15	PK
2390.0	49.16	0.34	0.85	H	50.35	53.98	3.63	AV
2390.0	64.16	0.00	0.85	V	65.01	73.98	8.97	PK
2390.0	48.33	0.34	0.85	V	49.52	53.98	4.46	AV
2483.5	67.69	0.00	1.13	H	68.82	73.98	5.16	PK
2483.5	49.51	0.34	1.13	H	50.98	53.98	3.00	AV
2483.5	66.85	0.00	1.13	H	67.98	73.98	6.00	PK
2483.5	48.14	0.34	1.13	H	49.61	53.98	4.37	AV

Operation Mode: 802.11g
 Transfer Rate: 6 Mbps
 Operating Frequency: 2462 MHz
 Channel No.: 11 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F -A.G+ATT. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	65.89	0.00	1.13	H	67.02	73.98	6.96	PK
2483.5	47.71	0.34	1.13	H	49.18	53.98	4.80	AV
2483.5	64.71	0.00	1.13	V	65.84	73.98	8.14	PK
2483.5	46.63	0.34	1.13	V	48.10	53.98	5.88	AV

Operation Mode: 802.11n (HT20)
 Transfer Rate: 0
 Operating Frequency: 2412 MHz, 2462 MHz
 Channel No.: 01 Ch, 10 Ch


Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F -A.G+ATT. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	66.39	0.00	0.85	H	67.24	73.98	6.74	PK
2390.0	48.52	0.37	0.85	H	49.74	53.98	4.24	AV
2390.0	65.15	0.00	0.85	V	66.00	73.98	7.98	PK
2390.0	47.94	0.37	0.85	V	49.16	53.98	4.82	AV
2483.5	61.92	0.00	1.13	H	63.05	73.98	10.93	PK
2483.5	46.77	0.37	1.13	H	48.27	53.98	5.71	AV
2483.5	60.42	0.00	1.13	H	61.55	73.98	12.43	PK
2483.5	45.11	0.37	1.13	H	46.61	53.98	7.37	AV

Operation Mode: 802.11n (HT20)
 Transfer Rate: 0
 Operating Frequency: 2462 MHz
 Channel No. 11 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F -A.G+ATT [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2483.5	65.49	0.00	1.13	H	66.62	73.98	7.36	PK
2483.5	47.66	0.37	1.13	H	49.16	53.98	4.82	AV
2483.5	64.71	0.00	1.13	V	65.84	73.98	8.14	PK
2483.5	46.70	0.37	1.13	V	48.20	53.98	5.78	AV


■ Test Plots (Worst case : Y-H)

Radiated Restricted Band Edges plot – Average Reading (802.11g_6Mbps Ch.11)



Date: 6.NOV.2019 11:12:50

Radiated Restricted Band Edges plot – Peak Reading (802.11g_6Mbps Ch.11)



Date: 6.NOV.2019 11:14:48

Note:

Plot of worst case are only reported.

9.8 RECEIVER SPURIOUS EMISSIONS

Frequency Range : Below 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

Frequency Range : Above 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

9.9 POWERLINE CONDUCTED EMISSIONS

Conducted Emissions (Line 1)

Test


1 / 2

HCT TEST Report

Common Information

EUT: SM-T307U
 Manufacturer: SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions: WLAN_2.4G_L1

FCC CLASS B_Exten Cable



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
 — Preview Result 2-AVG X Final Result 1-QPK X Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.466000	43.5	9.000	Off	L1	9.8	13.0	56.6
0.472000	43.9	9.000	Off	L1	9.8	12.6	56.5
0.476000	42.5	9.000	Off	L1	9.8	13.9	56.4
0.484000	43.7	9.000	Off	L1	9.8	12.5	56.3
0.488000	42.0	9.000	Off	L1	9.8	14.2	56.2
0.888000	40.5	9.000	Off	L1	9.9	15.5	56.0
1.266000	41.0	9.000	Off	L1	9.9	15.0	56.0
1.278000	41.6	9.000	Off	L1	9.9	14.4	56.0
1.344000	42.2	9.000	Off	L1	9.9	13.8	56.0
1.382000	41.2	9.000	Off	L1	9.9	14.8	56.0
1.442000	41.7	9.000	Off	L1	9.9	14.3	56.0
1.488000	42.3	9.000	Off	L1	9.9	13.7	56.0
5.196000	35.4	9.000	Off	L1	10.1	24.6	60.0
5.304000	37.3	9.000	Off	L1	10.1	22.7	60.0
5.310000	37.3	9.000	Off	L1	10.1	22.7	60.0
5.364000	37.0	9.000	Off	L1	10.1	23.0	60.0
5.372000	35.5	9.000	Off	L1	10.1	24.5	60.0
5.448000	34.8	9.000	Off	L1	10.1	25.2	60.0

2019-10-24

오후 1:31:15

Test

2 / 2

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.468000	28.2	9.000	Off	L1	9.8	18.4	46.5
0.480000	32.4	9.000	Off	L1	9.8	13.9	46.3
0.488000	33.5	9.000	Off	L1	9.8	12.7	46.2
0.852000	30.3	9.000	Off	L1	9.9	15.7	46.0
0.888000	28.8	9.000	Off	L1	9.9	17.2	46.0
0.894000	28.5	9.000	Off	L1	9.9	17.5	46.0
1.120000	32.7	9.000	Off	L1	9.9	13.3	46.0
1.328000	31.4	9.000	Off	L1	9.9	14.6	46.0
1.402000	32.0	9.000	Off	L1	9.9	14.0	46.0
1.488000	31.8	9.000	Off	L1	9.9	14.2	46.0
1.508000	32.5	9.000	Off	L1	9.9	13.5	46.0
1.596000	31.1	9.000	Off	L1	9.9	14.9	46.0
5.304000	28.7	9.000	Off	L1	10.1	21.3	50.0
5.406000	27.7	9.000	Off	L1	10.1	22.3	50.0
5.448000	26.8	9.000	Off	L1	10.1	23.2	50.0
5.472000	27.8	9.000	Off	L1	10.1	22.2	50.0
5.480000	27.6	9.000	Off	L1	10.1	22.4	50.0
19.282000	27.6	9.000	Off	L1	10.7	22.4	50.0

2019-10-24

오후 1:31:15

Conducted Emissions (Line 2)

Test


1 / 2

HCT TEST Report

Common Information

EUT: SM-T307U
 Manufacturer: SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions: WLAN_2.4G_N

FCC CLASS B_Exten Cable



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
 — Preview Result 2-AVG X Final Result 1-QPK X Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	38.8	9.000	Off	N	9.8	27.2	66.0
0.154000	38.7	9.000	Off	N	9.8	27.0	65.8
0.170000	35.6	9.000	Off	N	9.8	29.3	65.0
0.188000	34.7	9.000	Off	N	9.8	29.5	64.1
0.200000	32.5	9.000	Off	N	9.8	31.2	63.6
0.494000	39.6	9.000	Off	N	9.8	16.5	56.1
1.204000	35.5	9.000	Off	N	9.9	20.5	56.0
1.304000	37.9	9.000	Off	N	9.9	18.1	56.0
1.356000	38.2	9.000	Off	N	9.9	17.8	56.0
1.464000	38.2	9.000	Off	N	9.9	17.8	56.0
1.508000	36.1	9.000	Off	N	9.9	19.9	56.0
1.578000	36.4	9.000	Off	N	9.9	19.6	56.0
5.374000	32.7	9.000	Off	N	10.1	27.3	60.0
5.424000	31.5	9.000	Off	N	10.1	28.5	60.0
5.518000	31.1	9.000	Off	N	10.1	28.9	60.0
5.530000	30.5	9.000	Off	N	10.1	29.5	60.0
5.548000	31.7	9.000	Off	N	10.1	28.3	60.0
5.766000	30.9	9.000	Off	N	10.1	29.1	60.0

2019-10-24

오후 1:20:42

Test

2 / 2

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.154000	27.9	9.000	Off	N	9.8	27.9	55.8
0.158000	28.2	9.000	Off	N	9.8	27.3	55.6
0.164000	28.1	9.000	Off	N	9.8	27.2	55.3
0.170000	25.6	9.000	Off	N	9.8	29.3	55.0
0.188000	25.2	9.000	Off	N	9.8	28.9	54.1
0.502000	28.2	9.000	Off	N	9.8	17.8	46.0
1.250000	29.6	9.000	Off	N	9.9	16.4	46.0
1.306000	28.9	9.000	Off	N	9.9	17.1	46.0
1.358000	29.0	9.000	Off	N	9.9	17.0	46.0
1.414000	29.8	9.000	Off	N	9.9	16.2	46.0
1.458000	29.0	9.000	Off	N	9.9	17.0	46.0
1.476000	28.1	9.000	Off	N	9.9	17.9	46.0
5.318000	25.4	9.000	Off	N	10.1	24.6	50.0
5.374000	25.5	9.000	Off	N	10.1	24.5	50.0
5.424000	24.9	9.000	Off	N	10.1	25.1	50.0
5.472000	24.5	9.000	Off	N	10.1	25.5	50.0
19.576000	24.1	9.000	Off	N	10.8	25.9	50.0
19.716000	23.6	9.000	Off	N	10.8	26.4	50.0

2019-10-24

오후 1:20:42

Conducted Emissions (Line 3)

Test


1 / 2

HCT TEST Report

Common Information

EUT: SM-T307U
 Manufacturer: SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions: 2.4G_L1_Fast Charge

FCC CLASS B_Exten Cable



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
 — Preview Result 2-AVG × Final Result 1-QPK × Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.158000	45.7	9.000	Off	L1	9.8	19.8	65.6
0.162000	45.7	9.000	Off	L1	9.8	19.7	65.4
0.170000	33.9	9.000	Off	L1	9.8	31.1	65.0
0.176000	35.9	9.000	Off	L1	9.8	28.8	64.7
0.184000	37.4	9.000	Off	L1	9.8	26.9	64.3
0.212000	40.8	9.000	Off	L1	9.8	22.3	63.1
1.402000	30.5	9.000	Off	L1	9.9	25.5	56.0
1.406000	30.4	9.000	Off	L1	9.9	25.6	56.0
1.966000	30.2	9.000	Off	L1	9.9	25.8	56.0
1.982000	29.7	9.000	Off	L1	9.9	26.3	56.0
2.016000	29.9	9.000	Off	L1	9.9	26.1	56.0
2.636000	28.0	9.000	Off	L1	9.9	28.0	56.0
12.426000	33.1	9.000	Off	L1	10.4	26.9	60.0
12.526000	33.2	9.000	Off	L1	10.4	26.8	60.0
12.594000	33.3	9.000	Off	L1	10.4	26.7	60.0
12.782000	32.5	9.000	Off	L1	10.4	27.5	60.0
16.710000	31.6	9.000	Off	L1	10.6	28.4	60.0
16.794000	31.2	9.000	Off	L1	10.6	28.8	60.0

2019-11-20

오후 1:23:37

Test

2 / 2

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.158000	34.0	9.000	Off	L1	9.8	21.6	55.6
0.162000	34.2	9.000	Off	L1	9.8	21.2	55.4
0.166000	27.8	9.000	Off	L1	9.8	27.4	55.2
0.170000	22.7	9.000	Off	L1	9.8	32.3	55.0
0.176000	23.2	9.000	Off	L1	9.8	31.5	54.7
0.212000	28.9	9.000	Off	L1	9.8	24.2	53.1
1.402000	18.4	9.000	Off	L1	9.9	27.6	46.0
1.406000	18.7	9.000	Off	L1	9.9	27.3	46.0
1.968000	17.7	9.000	Off	L1	9.9	28.3	46.0
1.982000	16.4	9.000	Off	L1	9.9	29.6	46.0
2.016000	16.0	9.000	Off	L1	9.9	30.0	46.0
2.636000	16.4	9.000	Off	L1	9.9	29.6	46.0
12.370000	24.4	9.000	Off	L1	10.4	25.6	50.0
12.526000	24.3	9.000	Off	L1	10.4	25.7	50.0
12.782000	23.4	9.000	Off	L1	10.4	26.6	50.0
12.792000	23.4	9.000	Off	L1	10.4	26.6	50.0
16.710000	15.9	9.000	Off	L1	10.6	34.1	50.0
16.794000	15.5	9.000	Off	L1	10.6	34.5	50.0

2019-11-20

오후 1:23:37

Conducted Emissions (Line 4)

Test


1 / 2

HCT TEST Report

Common Information

EUT: SM-T307U
 Manufacturer: SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions: 2.4G_N_Fast Charge

FCC CLASS B_Exten Cable



— FCC CLASS B_OP — FCC CLASS B_AV — Preview Result 1-PK+
— Preview Result 2-AVG x Final Result 1-QPK x Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.154000	39.4	9.000	Off	N	9.8	26.4	65.8
0.164000	37.3	9.000	Off	N	9.8	27.9	65.3
0.172000	42.5	9.000	Off	N	9.8	22.4	64.9
0.176000	44.4	9.000	Off	N	9.8	20.3	64.7
0.180000	39.2	9.000	Off	N	9.8	25.3	64.5
0.218000	40.2	9.000	Off	N	9.8	22.7	62.9
0.884000	18.8	9.000	Off	N	9.8	37.2	56.0
0.898000	22.3	9.000	Off	N	9.8	33.7	56.0
1.124000	19.8	9.000	Off	N	9.9	36.2	56.0
1.134000	20.6	9.000	Off	N	9.9	35.4	56.0
1.398000	22.2	9.000	Off	N	9.9	33.8	56.0
1.444000	22.8	9.000	Off	N	9.9	33.2	56.0
13.720000	26.1	9.000	Off	N	10.5	33.9	60.0
15.860000	26.0	9.000	Off	N	10.6	34.0	60.0
15.910000	26.2	9.000	Off	N	10.6	33.8	60.0
15.938000	26.0	9.000	Off	N	10.6	34.0	60.0
16.016000	25.7	9.000	Off	N	10.6	34.3	60.0
16.038000	25.7	9.000	Off	N	10.6	34.3	60.0

2019-11-20

오후 2:57:52

Test

2 / 2

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	23.5	9.000	Off	N	9.8	32.5	56.0
0.160000	23.4	9.000	Off	N	9.8	32.1	55.5
0.164000	24.5	9.000	Off	N	9.8	30.8	55.3
0.170000	26.8	9.000	Off	N	9.8	28.1	55.0
0.174000	31.4	9.000	Off	N	9.8	23.3	54.8
0.218000	27.4	9.000	Off	N	9.8	25.5	52.9
0.884000	11.4	9.000	Off	N	9.8	34.6	46.0
0.920000	8.6	9.000	Off	N	9.9	37.4	46.0
1.048000	8.9	9.000	Off	N	9.9	37.1	46.0
1.134000	12.9	9.000	Off	N	9.9	33.1	46.0
1.312000	11.1	9.000	Off	N	9.9	34.9	46.0
1.448000	13.6	9.000	Off	N	9.9	32.4	46.0
13.768000	18.2	9.000	Off	N	10.5	31.8	50.0
15.670000	12.0	9.000	Off	N	10.6	38.0	50.0
15.860000	11.8	9.000	Off	N	10.6	38.2	50.0
15.910000	11.8	9.000	Off	N	10.6	38.2	50.0
16.016000	11.5	9.000	Off	N	10.6	38.5	50.0
16.038000	11.4	9.000	Off	N	10.6	38.6	50.0

2019-11-20

오후 2:57:52

9.10 CONFIRMATION OF GEO-LOCATION MECHANISM


The device uses MCC information obtained from the public cellular carrier to determine that it is operating outside the U.S. and then enable channels 12 and 13 only if a non-US MCC that supports channel 12 and 13 is confirmed.

The device uses a geo-location mechanism based on the Country in order to only enable certain WLAN DTS bands when the device is not in the USA.

WLAN	Country code = US	Country code = KR(Korea)
CH 12	Did not connect	Connected
CH 13	Did not connect	Connected

The verification tests confirmed the operational of the geo-location mechanism.

Test Setup



Test Procedure

In case of Country code

1. Open Command Prompt.
2. At the Command Prompt, enter the command.
 - C:\adb>adb remount
 - C:\adb>adb shell
 - gts4lv:/ # wpa_cli driver country US // Setting the country.
 - gts4lv:/ # iw list // Channel list is obtain.

In case of airplane mode

1. airplane mode on
 2. Wifi on
 3. Open Command Prompt.
 4. At the Command Prompt, enter the command.
- C:\adb>adb remount
 - C:\adb>adb shell
 - gta4lv:/ # iw reg get // support band in case of airplane mode

Setting the country for product

Country code = US
<pre>gta4s:/ # wpa_cli DRIVER_COUNTRY US wpa_cli DRIVER_COUNTRY US Using interface 'wlan0' OK gta4s:/ # wpa_cli DRIVER_GETREGULATORY 0 wpa_cli DRIVER_GETREGULATORY 0 Using interface 'wlan0' country US:DFS-ETSI (2402-2472 @ 40), (N/A, 30) (5170-5250 @ 80), (N/A, 23) (5250-5330 @ 80), (N/A, 23), DFS (5490-5730 @ 160), (N/A, 23), DFS (5735-5835 @ 80), (N/A, 30) Channels: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 144, 149, 153, 157, 161, 165 gta4s:/ #</pre>
Country code = KR(Korea)
<pre>gta4s:/ # wpa_cli DRIVER_COUNTRY KR wpa_cli DRIVER_COUNTRY KR Using interface 'wlan0' OK gta4s:/ # wpa_cli DRIVER_GETREGULATORY 0 wpa_cli DRIVER_GETREGULATORY 0 Using interface 'wlan0' country KR:DFS-JAPAN (2402-2482 @ 40), (N/A, 20) (5170-5250 @ 80), (N/A, 20), NO_OUTDOOR (5250-5330 @ 80), (N/A, 20), DFS (5470-5730 @ 160), (N/A, 30), DFS (5725-5850 @ 80), (N/A, 30) Channels: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 144, 149, 153, 157, 161, 165 gta4s:/ #</pre>

Setting the country for product

Country code = US	Country code = KR(Korea)

Did not connect Airplane mode	
Airplane off	<pre> gta4s:/ # wpa_cli DRIVER_GETREGULATORY 0 wpa_cli DRIVER_GETREGULATORY 0 Using interface 'wlan0' country KR:DFS-JAPAN (2402-2482 @ 40), (N/A, 20) (5170-5250 @ 80), (N/A, 20), NO_OUTDOOR (5250-5330 @ 80), (N/A, 20), DFS (5470-5730 @ 160), (N/A, 30), DFS (5725-5850 @ 80), (N/A, 30) Channels: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 144, 149, 153, 157, 161, 165 gta4s:/ # </pre>
Airplane on	<pre> gta4s:/ # wpa_cli DRIVER_GETREGULATORY 0 wpa_cli DRIVER_GETREGULATORY 0 Using interface 'wlan0' country US:DFS-ETSI (2402-2472 @ 40), (N/A, 30) (5170-5250 @ 80), (N/A, 23) (5250-5330 @ 80), (N/A, 23), DFS (5490-5730 @ 160), (N/A, 23), DFS (5735-5835 @ 80), (N/A, 30) Channels: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 144, 149, 153, 157, 161, 165 gta4s:/ # </pre>

Note : The frequency range is occupied band, not center frequency.

10. LIST OF TEST EQUIPMENT

Conducted Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216 / LISN	09/11/2019	Annual	102245
Rohde & Schwarz	ESCI / Test Receiver	06/18/2019	Annual	100584
ESPACE	SU-642 / Temperature Chamber	03/12/2019	Annual	0093008124
Agilent	N9020A / Signal Analyzer	05/23/2019	Annual	MY51110085
Agilent	N9030A / Signal Analyzer	05/09/2019	Annual	MY49432108
Agilent	N1911A / Power Meter	04/10/2019	Annual	MY45100523
Agilent	N1921A / Power Sensor	04/10/2019	Annual	MY52260025
Agilent	87300B / Directional Coupler	11/11/2019	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	05/24/2019	Annual	05001
Hewlett Packard	E3632A / DC Power Supply	06/18/2019	Annual	KR75303960
Agilent	8493C / Attenuator(10 dB)	07/02/2019	Annual	07560
Rohde & Schwarz	EMC32 / Software	N/A	N/A	N/A
HCT CO., LTD.	FCC WLAN&BT&BLE Conducted Test Software v3.0	N/A	N/A	N/A
Rohde & Schwarz	CBT / Bluetooth Tester	05/16/2019	Annual	100422

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Radiated Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Innco system	CO3000 / Controller(Antenna mast)	N/A	N/A	CO3000-4p
Innco system	MA4640/800-XP-EP / Antenna Position Tower	N/A	N/A	N/A
Audix	EM1000 / Controller	N/A	N/A	060520
Audix	Turn Table	N/A	N/A	N/A
Rohde & Schwarz	Loop Antenna	08/23/2018	Biennial	1513-175
Schwarzbeck	VULB 9168 / Hybrid Antenna	08/31/2018	Biennial	00895
Schwarzbeck	VULB 9168 / Hybrid Antenna	08/09/2018	Biennial	3368
Schwarzbeck	BBHA 9120D / Horn Antenna	06/28/2019	Biennial	1300
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	04/29/2019	Biennial	BBHA9170342
Rohde & Schwarz	FSP(9 kHz ~ 40 GHz) / Spectrum Analyzer	07/16/2019	Annual	100843
Wainwright Instruments	WHK3.0/18G-10EF / High Pass Filter	01/03/2019	Annual	F6
Wainwright Instruments	WHFX7.0/18G-8SS / High Pass Filter	05/03/2019	Annual	29
Wainwright Instruments	WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter	06/19/2019	Annual	2
Wainwright Instruments	WRCJV5100/5850-40/50-8EEK / Band Reject Filter	01/03/2019	Annual	2
Weinschel	2-3 / Attenuator (3 dB)	10/08/2019	Annual	BR0617
H+S	5910-N-50-010 / Attenuator(10 dB)	10/29/2019	Annual	None
CERNEX	CBLU1183540B-01 / Power Amplifier	12/21/2018	Annual	25540
CERNEX	CBL06185030 / Power Amplifier	03/26/2019	Annual	28550
CERNEX	CBL18265035 / Power Amplifier	01/03/2019	Annual	22966
CERNEX	CBL26405040 / Power Amplifier	06/18/2019	Annual	25956
TESCOM	TC-3000C / Bluetooth Tester	03/26/2019	Annual	3000C000276

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
3. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5(Version : 2017).

11. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-1911-FI019-P