



LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	170531_31 171001687 24]	5GHz_LP[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.83	42.93	PK	33.1	-24.9	0	51.13	-	-	74	-22.87	-	-	0-360	250	H
2	* 3.83	35.8	PK	33.1	-24.9	0	44	-	-	74	-30	-	-	0-360	150	V
3	* 7.659	30.07	PK	35.8	-20	0	45.87	-	-	74	-28.13	-	-	0-360	250	H
6	* 11.486	20.03	PK	38.2	-15.9	0	42.33	-	-	74	-31.67	-	-	0-360	250	H
4	* 7.66	27.44	PK	35.8	-20	0	43.24	-	-	74	-30.76	-	-	0-360	149	V
5	* 11.489	19.64	PK	38.2	-15.9	0	41.94	-	-	74	-32.06	-	-	0-360	149	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak Detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117 [00168724]	5GHz_LP[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 3.83	46.1	PK-U	33.1	-25	0	54.2	-	-	74	-19.8	-	-	4	180	H
* 3.83	42.63	ADR	33.1	-25	0	50.73	54	-3.27	-	-	-	-	4	180	H
* 3.83	41.17	PK-U	33.1	-25	0	49.27	-	-	74	-24.73	-	-	37	237	V
* 3.83	34.28	ADR	33.1	-25	0	42.38	54	-11.62	-	-	-	-	37	237	V
* 7.66	30.61	ADR	35.8	-20	0	46.41	54	-7.59	-	-	-	-	351	320	H
* 7.66	27.4	ADR	35.8	-20	0	43.2	54	-10.8	-	-	-	-	208	149	V
* 7.66	37.68	PK-U	35.8	-20	0	53.48	-	-	74	-20.52	-	-	351	320	H
* 7.66	36.12	PK-U	35.8	-20	0	51.92	-	-	74	-22.08	-	-	208	149	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK-U - U-NII: Maximum Peak

ADR - U-NII AD primary method, RMS average

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117 [00168724]	5GHz_LP[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.857	42.73	PK	33.1	-24.7	0	51.13	-	-	74	-22.87	-	-	0-360	250	H
2	* 3.857	36.34	PK	33.1	-24.7	0	44.74	-	-	74	-29.26	-	-	0-360	250	V
3	* 7.713	29.71	PK	35.7	-19.8	0	45.61	-	-	74	-28.39	-	-	0-360	250	H
6	* 11.558	19.27	PK	38.2	-15.9	0	41.57	-	-	74	-32.43	-	-	0-360	250	H
4	* 7.713	27.21	PK	35.7	-19.8	0	43.11	-	-	74	-30.89	-	-	0-360	150	V
5	* 11.56	20.12	PK	38.2	-15.9	0	42.42	-	-	74	-31.58	-	-	0-360	250	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117 [00168724]	5GHz_LP[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 3.857	46.05	PK-U	33.1	-24.8	0	54.35	-	-	74	-19.65	-	-	7	343	H
* 3.857	42.44	ADR	33.1	-24.7	0	50.84	54	-3.16	-	-	-	-	7	343	H
* 3.857	39.97	PK-U	33.1	-24.7	0	48.37	-	-	74	-25.63	-	-	191	145	V
* 3.857	33.5	ADR	33.1	-24.7	0	41.9	54	-12.1	-	-	-	-	191	145	V
* 7.713	26.3	ADR	35.7	-19.8	0	42.2	54	-11.8	-	-	-	-	215	131	V
* 7.713	29.22	ADR	35.7	-19.8	0	45.12	54	-8.88	-	-	-	-	349	300	H
* 7.713	34.83	PK-U	35.7	-19.8	0	50.73	-	-	74	-23.27	-	-	215	131	V
* 7.713	36.4	PK-U	35.7	-19.8	0	52.3	-	-	74	-21.7	-	-	349	300	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK-U - U-NII: Maximum Peak

ADR - U-NII AD primary method, RMS average

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	170531_31 17[001687 24]	5GHz_LP[d B]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.883	42.67	PK	33.1	-24.7	0	51.07	-	-	74	-22.93	-	-	0-360	250	H
2	* 3.883	35.86	PK	33.1	-24.7	0	44.26	-	-	74	-29.74	-	-	0-360	250	V
3	7.767	29	PK	35.8	-20.3	0	44.5	-	-	-	-	68.2	-23.7	0-360	250	H
5	* 11.651	18.59	PK	38.1	-15.7	0	40.99	-	-	74	-33.01	-	-	0-360	150	H
7	17.476	17.67	PK	41.2	-12.2	0	46.67	-	-	-	-	68.2	-21.53	0-360	150	H
4	7.766	27.03	PK	35.8	-20.2	0	42.63	-	-	-	-	68.2	-25.57	0-360	150	V
6	* 11.65	18.42	PK	38.1	-15.7	0	40.82	-	-	74	-33.18	-	-	0-360	250	V
8	17.473	17.34	PK	41.3	-12.2	0	46.44	-	-	-	-	68.2	-21.76	0-360	150	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak Detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117 [00168724]	5GHz_LP[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 3.883	45.46	PK-U	33.1	-24.7	0	53.86	-	-	74	-20.14	-	-	8	392	H
* 3.883	41.96	ADR	33.1	-24.7	0	50.36	54	-3.64	-	-	-	-	8	392	H
* 3.883	40.82	PK-U	33.1	-24.7	0	49.22	-	-	74	-24.78	-	-	67	104	V
* 3.883	35.12	ADR	33.1	-24.7	0	43.52	54	-10.48	-	-	-	-	67	104	V
7.767	27.17	ADR	35.8	-20.3	0	42.67	-	-	-	-	-	-	208	146	V
7.767	29.61	ADR	35.8	-20.3	0	45.11	-	-	-	-	-	-	356	345	H
7.767	35.69	PK-U	35.8	-20.3	0	51.19	-	-	-	-	68.2	-17.01	208	146	V
7.767	37.28	PK-U	35.8	-20.3	0	52.78	-	-	-	-	68.2	-15.42	356	345	H


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK-U - U-NII: Maximum Peak

ADR - U-NII AD primary method, RMS average

10.4.3. TX ABOVE 1GHz 802.11n HT40 MODE IN THE 5.8GHz BAND BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK PLOT




HORIZONTAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	20170531 _3117_00 168717	10dB_ATT(dB)_17080 9	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.725	-59.17	PK	34.5	-21.2	11.8	0	-34.07	26.97	-61.04	328	105	H
2	5.642	-65.34	PK	34.4	-21.2	11.8	0	-40.34	-27	-13.34	328	105	H

Pk - Peak detector

VERTICAL PEAK PLOT



VERTICAL DATA


Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	20170531_3117_00_168717	10dB_ATT(dB)_17080_9	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.725	-61.48	Pk	34.5	-21.2	11.8	0	-36.38	26.97	-63.35	42	100	V
2	5.645	-65.22	Pk	34.4	-21.3	11.8	0	-40.32	-27	-13.32	42	100	V

Pk - Peak detector

BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK PLOT




HORIZONTAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	20170531_3117_00	10dB_ATT(dB)_170809	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.85	-68.39	Pk	34.5	-21.1	11.8	0	-43.19	26.94	-70.13	297	289	H
2	5.97	-65.19	Pk	34.7	-20.9	11.8	0	-39.59	-27	-12.59	297	289	H

Pk - Peak detector

VERTICAL PEAK PLOT




VERTICAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBm)	Det	20170531_3117_00_168717	10dB_ATT(dB)_170809	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.85	-68	Pk	34.5	-21.1	11.8	0	-42.8	26.94	-69.74	341	105	V
2	5.984	-65.42	Pk	34.7	-20.9	11.8	0	-39.82	-27	-12.82	341	105	V

Pk - Peak detector

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	170531_31 17[001687 24]	5GHz_LP[d B]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.837	41.45	PK	33.1	-24.9	0	49.65	-	-	74	-24.35	-	-	0-360	250	H
2	* 3.837	36.49	PK	33.1	-24.9	0	44.69	-	-	74	-29.31	-	-	0-360	250	V
3	* 7.673	27.86	PK	35.8	-20	0	43.66	-	-	74	-30.34	-	-	0-360	150	H
6	* 11.498	19.86	PK	38.2	-15.9	0	42.16	-	-	74	-31.84	-	-	0-360	150	H
4	* 7.673	27.46	PK	35.8	-20	0	43.26	-	-	74	-30.74	-	-	0-360	150	V
5	* 11.501	19.86	PK	38.2	-15.9	0	42.16	-	-	74	-31.84	-	-	0-360	250	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak Detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117 [00168724]	5GHz_LP[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 3.837	45.04	PK-U	33.1	-24.9	0	53.24	-	-	74	-20.76	-	-	4	117	H
* 3.837	41.31	ADR	33.1	-24.9	0	49.51	54	-4.49	-	-	-	-	4	117	H
* 3.837	41.15	PK-U	33.1	-24.9	0	49.35	-	-	74	-24.65	-	-	62	102	V
* 3.837	36.19	ADR	33.1	-24.9	0	44.39	54	-9.61	-	-	-	-	62	102	V
* 7.673	27.55	ADR	35.8	-20	0	43.35	54	-10.65	-	-	-	-	209	147	V
* 7.673	28.66	ADR	35.8	-20	0	44.46	54	-9.54	-	-	-	-	352	368	H
* 7.674	35.59	PK-U	35.8	-20	0	51.39	-	-	74	-22.61	-	-	209	147	V
* 7.673	36.28	PK-U	35.8	-20	0	52.08	-	-	74	-21.92	-	-	352	368	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK-U - U-NII: Maximum Peak

ADR - U-NII AD primary method, RMS average

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117 [00168724]	5GHz_LP[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.863	41.42	PK	33.1	-24.7	0	49.82	-	-	74	-24.18	-	-	0-360	150	H
2	* 3.863	35.76	PK	33.1	-24.7	0	44.16	-	-	74	-29.84	-	-	0-360	250	V
3	* 7.727	27.6	PK	35.8	-19.8	0	43.6	-	-	74	-30.4	-	-	0-360	150	H
6	* 11.593	19.04	PK	38.2	-15.8	0	41.44	-	-	74	-32.56	-	-	0-360	150	H
4	* 7.726	26.8	PK	35.8	-19.8	0	42.8	-	-	74	-31.2	-	-	0-360	150	V
5	* 11.591	18.76	PK	38.2	-15.9	0	41.06	-	-	74	-32.94	-	-	0-360	250	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak Detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117 [00168724]	5GHz_LP[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 3.863	44.84	PK-U	33.1	-24.7	0	53.24	-	-	74	-20.76	-	-	31	131	H
* 3.863	40.04	ADR	33.1	-24.7	0	48.44	54	-5.56	-	-	-	-	31	131	H
* 3.863	41.69	PK-U	33.1	-24.7	0	50.09	-	-	74	-23.91	-	-	64	236	V
* 3.863	36.37	ADR	33.1	-24.7	0	44.77	54	-9.23	-	-	-	-	64	236	V
* 7.727	25.25	ADR	35.8	-19.8	0	41.25	54	-12.75	-	-	-	-	206	117	V
* 7.727	28.4	ADR	35.8	-19.8	0	44.4	54	-9.6	-	-	-	-	0	393	H
* 7.726	35.51	PK-U	35.8	-19.8	0	51.51	-	-	74	-22.49	-	-	206	117	V
* 7.727	36.28	PK-U	35.8	-19.8	0	52.28	-	-	74	-21.72	-	-	0	393	H


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK-U - U-NII: Maximum Peak

ADR - U-NII AD primary method, RMS average

**10.4.4.TX ABOVE 1GHz 802.11ac VHT80 MODE IN THE 5.8GHz BAND
 RESTRICTED BANDEDGE (MID CHANNEL)**

HORIZONTAL PEAK AND AVERAGE PLOT




HORIZONTAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	20170531_3117_00_168717	10dB_ATT(dB)_170809	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.85	-61.9	PK	34.5	-21.1	11.8	0	-36.7	26.94	-63.64	303	103	H
2	5.937	-63.74	PK	34.6	-21	11.8	0	-38.34	-27	-11.34	303	103	H

Pk - Peak detector

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA


Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	20170531_3117_00_168717	10dB_ATT(dB)_170809	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.85	-68.26	Pk	34.5	-21.1	11.8	0	-43.06	26.94	-70	332	100	V
2	6	-65.31	Pk	34.8	-20.8	11.8	0	-39.51	-27	-12.51	332	100	V


Pk - Peak detector

HARMONICS AND SPURIOUS EMISSIONS

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	170531_31 171001687 24]	5GHz_LP[d B]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.85	40.67	PK	33.1	-24.8	0	48.97	-	-	74	-25.03	-	-	0-360	250	H
2	* 3.85	35.44	PK	33.1	-24.8	0	43.74	-	-	74	-30.26	-	-	0-360	150	V
3	* 7.699	27.8	PK	35.7	-19.8	0	43.7	-	-	74	-30.3	-	-	0-360	150	H
6	* 11.55	19.79	PK	38.2	-15.9	0	42.09	-	-	74	-31.91	-	-	0-360	150	H
4	* 7.699	28.72	PK	35.7	-19.8	0	44.62	-	-	74	-29.38	-	-	0-360	150	V
5	* 11.549	19.28	PK	38.2	-15.9	0	41.58	-	-	74	-32.42	-	-	0-360	250	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak Detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117 [00168724]	5GHz_LP[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 3.85	44.55	PK-U	33.1	-24.8	0	52.85	-	-	74	-21.15	-	-	29	132	H
* 3.85	38.94	ADR	33.1	-24.8	0	47.24	54	-6.76	-	-	-	-	29	132	H
* 3.85	41.61	PK-U	33.1	-24.8	0	49.91	-	-	74	-24.09	-	-	67	118	V
* 3.85	34.54	ADR	33.1	-24.8	0	42.84	54	-11.16	-	-	-	-	67	118	V
* 7.7	26.25	ADR	35.7	-19.8	0	42.15	54	-11.85	-	-	-	-	207	145	V
* 7.7	27.23	ADR	35.7	-19.8	0	43.13	54	-10.87	-	-	-	-	350	327	H
* 7.7	35.29	PK-U	35.7	-19.8	0	51.19	-	-	74	-22.81	-	-	207	145	V
* 7.7	35.46	PK-U	35.7	-19.8	0	51.36	-	-	74	-22.64	-	-	350	327	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK-U - U-NII: Maximum Peak

ADR - U-NII AD primary method, RMS average

10.5. BANDEDGE (on Worst case) equipped with protective case



Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	20170531_3117_0016 8717	10dB_ATT(dB)_17080 9	DC Corr (dB)	Corrected Reading (dBuV/m)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.725	43.27	Pk	34.4	-21.2	0	56.47	68.2	-11.73	326	121	H
2	5.726	46.62	Pk	34.4	-21.2	0	59.82	68.2	-8.38	326	121	H

Pk - Peak detector


Note : Band Edge emission is lower than stand alone condition.

10.6. HARMONICS AND SPURIOUS EMISSIONS (on Worst case) equipped with protective case

HORIZONTAL



VERTICAL



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	170531_31 17[001687 24]	5GHz_LP[d B]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 3.883	42.58	PK	33.1	-24.7	0	50.98	-	-	74	-23.02	-	-	0-360	250	H
2	* 3.883	36.14	PK	33.1	-24.7	0	44.54	-	-	74	-29.46	-	-	0-360	150	V
3	7.766	26.9	PK	35.8	-20.2	0	42.5	-	-	-	-	68.2	-25.7	0-360	250	H
5	* 11.651	18.6	PK	38.1	-15.7	0	41	-	-	74	-33	-	-	0-360	250	H
4	7.767	27.72	PK	35.8	-20.3	0	43.22	-	-	-	-	68.2	-24.98	0-360	150	V
6	* 11.654	19.56	PK	38.1	-15.8	0	41.86	-	-	74	-32.14	-	-	0-360	250	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	170531_3117 [00168724]	5GHz_LP[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 3.883	46.06	PK-U	33.1	-24.7	0	54.46	-	-	74	-19.54	-	-	355	116	H
* 3.883	42.39	ADR	33.1	-24.7	0	50.79	54	-3.21	-	-	-	-	355	116	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK-U - U-NII: Maximum Peak

ADR - U-NII AD primary method, RMS average


Note : Harmonic and spurious emission is lower than stand alone condition.

11. WORST-CASE BELOW 1 GHz (in the 5.3 GHz Band)

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)



Below 1G Data

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	750_20170831	30-1000MHz[dB]	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	42.416	34.2	Pk	19.1	-29.4	23.9	40	-16.1	0-360	400	H
2	* 250.287	35.88	Pk	18.4	-27.4	26.88	46.02	-19.14	0-360	100	H
3	437.594	35.74	Pk	22	-26	31.74	46.02	-14.28	0-360	100	H
4	31.746	40.13	Pk	16.2	-29.6	26.73	40	-13.27	0-360	100	V
5	42.319	36.47	Pk	19.1	-29.4	26.17	40	-13.83	0-360	100	V
6	* 250.19	32.95	Pk	18.4	-27.4	23.95	46.02	-22.07	0-360	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

12. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

6 WORST EMISSIONS

LINE 1 PLOT



LINE 1 RESULTS


Trace Markers

Range 1: Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_L1_wit h extension	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
1	.249	35.41	Pk	9.5	.2	45.11	61.79	-16.68	-	-
2	.249	17.15	Av	9.5	.2	26.85	-	-	51.79	-24.94
3	.501	33.78	Pk	9.7	.2	43.68	56	-12.32	-	-
4	.501	17.17	Av	9.7	.2	27.07	-	-	46	-18.93
5	.897	35.19	Pk	9.7	.3	45.19	56	-10.81	-	-
6	.897	16.8	Av	9.7	.3	26.8	-	-	46	-19.2
7	2.202	29.33	Pk	9.9	.3	39.53	56	-16.47	-	-
8	2.157	10.92	Av	9.9	.3	21.12	-	-	46	-24.88
9	9.384	32.92	Pk	9.7	.4	43.02	60	-16.98	-	-
10	9.474	17.57	Av	9.7	.4	27.67	-	-	50	-22.33
11	14.028	31.93	Pk	9.8	.4	42.13	60	-17.87	-	-
12	13.992	15.81	Av	9.8	.4	26.01	-	-	50	-23.99

Pk - Peak detector
 Av - Average detection

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Range 2: Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_N_with extension	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
13	.249	32.61	Pk	9.6	.2	42.41	61.79	-19.38	-	-
14	.249	16.12	Av	9.6	.2	25.92	-	-	51.79	-25.87
15	.501	30.29	Pk	9.8	.2	40.29	56	-15.71	-	-
16	.501	14.37	Av	9.8	.2	24.37	-	-	46	-21.63
17	.897	33.02	Pk	9.7	.3	43.02	56	-12.98	-	-
18	.897	14.14	Av	9.7	.3	24.14	-	-	46	-21.86
19	2.193	27.93	Pk	9.9	.3	38.13	56	-17.87	-	-
20	2.148	9.4	Av	9.9	.3	19.6	-	-	46	-26.4
21	9.456	30.7	Pk	9.8	.4	40.9	60	-19.1	-	-
22	9.465	16.39	Av	9.8	.4	26.59	-	-	50	-23.41
23	14.109	30.94	Pk	9.9	.4	41.24	60	-18.76	-	-
24	14.118	14.04	Av	9.9	.4	24.34	-	-	50	-25.66

Pk - Peak detector

Av - Average detection

13. DYNAMIC FREQUENCY SELECTION

13.1. OVERVIEW

13.1.1. LIMITS

FCC

§15.407 (h), FCC KDB 905462 D02 “COMPLIANCE MEASUREMENT PROCEDURES FOR UNLICENSED-NATIONAL INFORMATION INFRASTRUCTURE DEVICES OPERATING IN THE 5250-5350 MHz AND 5470-5725 MHz BANDS INCORPORATING DYNAMIC FREQUENCY SELECTION” and KDB 905462 D03 “U-NII CLIENT DEVICES WITHOUT RADAR DETECTION CAPABILITY”.

Table 1: Applicability of DFS requirements prior to use of a channel

Requirement	Operational Mode		
	Master	Client (without radar detection)	Client (with radar detection)
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode		
	Master	Client (without DFS)	Client (with DFS)
DFS Detection Threshold	Yes	Not required	Yes
Channel Closing Transmission Time	Yes	Yes	Yes
Channel Move Time	Yes	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required	Yes

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar DFS	Client (without DFS)
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required
Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in all 20 MHz channel blocks and a null frequency between the bonded 20 MHz channel blocks.		

Table 3: Interference Threshold values, Master or Client incorporating In-Service Monitoring

Maximum Transmit Power	Value (see notes)
E.I.R.P. \geq 200 mill watt	-64 dBm
E.I.R.P. < 200 mill watt and power spectral density < 10 dBm/MHz	-62 dBm
E.I.R.P. < 200 mill watt that do not meet power spectral density requirement	-64 dBm
<p>Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note 3: E.I.R.P. is based on the highest antenna gain. For MIMO devices refer to KDB publication 662911 D01.</p>	

Table 4: DFS Response requirement values

Parameter	Value
<i>Non-occupancy period</i>	30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds (See Note 1)
<i>Channel Closing Transmission Time</i>	200 milliseconds + approx. 60 milliseconds over remaining 10 second period. (See Notes 1 and 2)
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U-NII 99% transmission power bandwidth. (See Note 3)
<p>Note 1: <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel</i> move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.</p>	

Table 5 – Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (usec)	PRI (usec)	Pulses	Minimum Percentage of Successful Detection	Minimum Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in table 5a	Roundup: $\{(1/360) \times (19 \times 10^6 \text{ PRI}_{\text{usec}})\}$	60%	30
		Test B: 15 unique PRI values randomly selected within the range of 518-3066 usec. With a minimum increment of 1 usec, excluding PRI values selected in Test A			
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the <i>Detection Bandwidth</i> test, <i>Channel Move Time</i> , and <i>Channel Closing Time</i> tests.					

Table 6 – Long Pulse Radar Test Signal


Radar Waveform Type	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Pulses per Burst	Number of Bursts	Minimum Percentage of Successful Detection	Minimum Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

Table 7 – Frequency Hopping Radar Test Signal

Radar Waveform Type	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Trials
6	1	333	9	0.333	300	70%	30

13.1.1. TEST AND MEASUREMENT SYSTEM

CONDUCTED METHOD SYSTEM BLOCK DIAGRAM



SYSTEM OVERVIEW

The short pulse and long pulse signal generating system utilizes the Keysite Signal Studio for Pulse Building as N5172B. The Vector Signal Generator has been validated by the NTIA. The hopping signal generating system utilizes the CCS simulated hopping method and system, which has been validated by the DoD, FCC and NTIA. The software selects waveform parameters from within the bounds of the signal type on a random basis using uniform distribution.

The short pulse types 1, 2, 3 and 4, and the long pulse type 5 parameters are randomized at run-time.

The hopping type 6 pulse parameters are fixed while the hopping sequence is based on the August 2005 NTIA Hopping Frequency List. The initial starting point randomized at run-time and each subsequent starting point is incremented by 475. Each frequency in the 100-length segment is compared to the boundaries of the EUT Detection Bandwidth and the software creates a hopping burst pattern in accordance with Section 7.4.1.3 Method #2 Simulated Frequency Hopping Radar Waveform Generating Subsystem of KDB 905462 D02. The frequency of the signal generator is incremented in 1 MHz steps from F_L to F_H for each successive trial. This incremental sequence is repeated as required to generate a minimum of 30 total trials and to maintain a uniform frequency distribution over the entire Detection Bandwidth.

The signal monitoring equipment consists of a spectrum analyzer. The aggregate ON time is calculated by multiplying the number of bins above a threshold during a particular observation period by the dwell time per bin, with the analyzer set to peak detection and max hold.

SYSTEM CALIBRATION

A 50-ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to a horn antenna via a coaxial cable, with the reference level offset set to (horn antenna gain – coaxial cable loss). The signal generator is set to CW mode. The amplitude of the signal generator is adjusted to yield a level of –64 dBm as measured on the spectrum analyzer.

Without changing any of the instrument settings, the spectrum analyzer is reconnected to the Common port of the Spectrum Analyzer Combiner/Divider. The Reference Level Offset of the spectrum analyzer is adjusted so that the displayed amplitude of the signal is –64 dBm.

The spectrum analyzer displays the level of the signal generator as received at the antenna ports of the Master Device. The interference detection threshold may be varied from the calibrated value of –64 dBm and the spectrum analyzer will still indicate the level as received by the Master Device.

ADJUSTMENT OF DISPLAYED TRAFFIC LEVEL

A link is established between the Master and Slave and the distance between the units is adjusted as needed to provide a suitable received level at the Master and Slave devices. The video test file is streamed to generate WLAN traffic. The monitoring antenna is adjusted so that the WLAN traffic level, as displayed on the spectrum analyzer, is at lower amplitude than the radar detection threshold.


TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the DFS tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	S/N	Cal Due
Spectrum Analyzer, 7 GHz	Agilent / HP	N9010A	MY54200580	08-07-18
Vector Signal Generator, 6GHz	Agilent / HP	N5182B	MY53051241	08-07-18

13.1.2. SETUP OF EUT

CONDUCTED METHOD EUT TEST SETUP



SUPPORT EQUIPMENT

The following support equipment was utilized for the DFS tests documented in this report:

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
Wireless Access Point	Cisco	AIR-CAP3702E-A-K9	FTX182276QX	LDK102087
PC (Controller/Server)	HP	HP EliteDesk 800 G1 TWR	CZC4125J25	DoC

13.1.3. DESCRIPTION OF EUT

The EUT operates over the 5250-5350 MHz and 5470-5725 MHz ranges.

The EUT is a Slave Device without Radar Detection.

The highest power level within these bands is 12.063 dBm in the 5250-5350 MHz band and 12.004 dBm in the 5470-5725 MHz band.

The antenna gain assembly utilized with the EUT are -0.7 dBi in the 5250-5350 MHz band and -1.1 dBi in the 5470-5725 MHz band.

The rated output power of the Master unit is > 23dBm (EIRP). Therefore the required interference threshold level is -64 dBm. After correction for procedural adjustments, the required conducted threshold at the antenna port is $-64 + 1 = -63$ dBm.

The calibrated radiated DFS Detection Threshold level is set to -64 dBm. The tested level is lower than the required level hence it provides a margin to the limit.

The EUT uses one transmitter/receiver chain connected to an antenna to perform radiated tests.

WLAN traffic that meets or exceeds the minimum required loading was generated by transferring a data stream from the controller/server PC to the EUT using iPerf version 2.0.5 software package.

TPC is not required since the maximum EIRP is less than 500 mW (27 dBm).

The EUT utilizes the 802.11ac architecture. Three nominal channel bandwidths are implemented: 20 MHz, 40 MHz and 80 MHz.

The software installed in the access point is 12.4(25d)JA1.

UNIFORM CHANNEL SPREADING

This requirement is not applicable to Slave radio devices.

OVERVIEW OF MASTER DEVICE WITH RESPECT TO §15.407 (h) REQUIREMENTS

The Master Device is a Cisco Access Point, FCC ID: LDK102087. The minimum antenna gain for the Master Device is 6 dBi.

The rated output power of the Master unit is > 23dBm (EIRP). Therefore the required interference threshold level is -64 dBm. After correction for procedural adjustments, the required radiated threshold at the antenna port is $-64 + 1 = -63$ dBm.

The calibrated radiated DFS Detection Threshold level is set to -64 dBm. The tested level is lower than the required level hence it provides a margin to the limit.


13.1. RESULTS FOR 20 MHz BANDWIDTH

13.1.1. TEST CHANNEL


All tests were performed at a channel center frequency of 5500 MHz.

13.1.2. RADAR WAVEFORM AND TRAFFIC

RADAR WAVEFORM



TRAFFIC



13.1.3.OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

13.1.4.MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS



Channel Move Time (sec)	Limit (sec)
0.714	10

Aggregate Channel Closing Transmission Time (msec)	Limit (msec)
3.750	60

MOVE TIME & CHANNEL CLOSING TIME

AGGREGATE CHANNEL CLOSING TRANSMISSION TIME


No transmissions are observed during the aggregate monitoring period.



NON-OCCUPANCY PERIOD

RESULTS

No EUT transmissions were observed on the test channel during the 10-minute observation time.




13.2. RESULTS FOR 40 MHz BANDWIDTH

13.2.1. TEST CHANNEL


All tests were performed at a channel center frequency of 5510 MHz.

13.2.2. RADAR WAVEFORM AND TRAFFIC

RADAR WAVEFORM



TRAFFIC



13.2.3.OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

13.2.4.MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS



Channel Move Time (sec)	Limit (sec)
0.730	10

Aggregate Channel Closing Transmission Time (msec)	Limit (msec)
4.500	60

MOVE TIME & CHANNEL CLOSING TIME

AGGREGATE CHANNEL CLOSING TRANSMISSION TIME


No transmissions are observed during the aggregate monitoring period.




NON-OCCUPANCY PERIOD

RESULTS

No EUT transmissions were observed on the test channel during the 10-minute observation time.



TRAFFIC



13.3.3.OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

13.3.4.MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS



Channel Move Time (sec)	Limit (sec)
1.048	10

Aggregate Channel Closing Transmission Time (msec)	Limit (msec)
0.375	60

MOVE TIME & CHANNEL CLOSING TIME

AGGREGATE CHANNEL CLOSING TRANSMISSION TIME

No transmissions are observed during the aggregate monitoring period.



NON-OCCUPANCY PERIOD

RESULTS

No EUT transmissions were observed on the test channel during the 10-minute observation time.

