



FCC RF TEST REPORT

47 CFR FCC Part 15 Subpart C § 15.249

APPLICANT : Samsung Electronics Co., Ltd.
EQUIPMENT : Tablet PC
BRAND NAME : SAMSUNG
MODEL NAME : SM-T555C
FCC ID : A3LSMT555C

The product was received on Mar. 19, 2015 and testing was completed on Apr. 16, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Nanshan District, Shenzhen, Guangdong, P. R. China



Table of Contents

1. SUMMARY OF THE TEST RESULT4

2. GENERAL INFORMATION.....5

2.1 Applicant5

2.2 Manufacturer5

2.3 Product Details.....5

2.4 Table for Test Modes6

2.5 Table for Testing Locations.....7

2.6 Test Configurations8

3. TEST RESULT9

3.1 AC Power Line Conducted Emissions Measurement9

3.2 20dB and & 99% Occupied Bandwidth13

3.3 Field Strength of Fundamental Emissions and Radiated Spurious Emissions16

3.4 Antenna Requirements21

4. LIST OF MEASURING EQUIPMENT22

APPENDIX A. RADIATED TEST RESULTS



1. SUMMARY OF THE TEST RESULT

| Applied Standard: | | | | |
|-------------------|--------------|---|----------|-------------------------|
| Part | FCC Rule | Description of Test | Result | Under Limit |
| 3.1 | 15.207 | AC Power Line Conducted Emissions | Complies | 13.97 dB at 0.440MHz |
| 3.2 | 2.1049 | 20dB & 99% Occupied Bandwidth | Complies | - |
| 3.3 | 15.249(a) | Field Strength of Fundamental Emissions | Complies | 16.68 dB at 2441.000MHz |
| 3.3 | 15.249(a)(d) | Radiated Spurious Emissions | Complies | 7.63 dB at 39.700MHz |
| 3.4 | 15.203 | Antenna Requirements | Complies | - |

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

| | |
|---|--------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 2.3 dB |
|---|--------|

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

| | |
|---|--------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 3.9 dB |
|---|--------|



2. GENERAL INFORMATION

2.1 Applicant

Samsung Electronics Co., Ltd.

No.9 WeiWu Rd, Micro Electronic Industrial Park, Jingang Highway, Xiqing District, Tianjin, China

2.2 Manufacturer

Samsung Electronics Co., Ltd.

No.9 WeiWu Rd, Micro Electronic Industrial Park, Jingang Highway, Xiqing District, Tianjin, China

2.3 Product Details

For more detailed features description, please refer to the manufacturer's specifications or user's manual.

| Product Feature | |
|----------------------------|--|
| Equipment | Tablet PC |
| Brand Name | SAMSUNG |
| Model Name | SM-T555C |
| FCC ID | A3LSMT555C |
| GSM Operating Band(s) | GSM900/1800 (non-US bands) GSM1900/850MHz (US bands) |
| GPRS/EGPRS Multislot Class | GPRS Class 33, EGPRS Class 33 |
| WCDMA Operating Band(s) | FDD Band I/VIII (non-US bands) FDD Band II/V (US bands) |
| LTE Operating Band(s) | FDD Band 1/3/8/28 (non-US bands) TDD Band 41 (US band) |
| Wi-Fi Specification | 2.4GHz 802.11b/g/n HT20 5GHz 802.11a/n HT20/ HT40 |
| Bluetooth Version | Bluetooth v3.0 + EDR/Bluetooth v4.0 LE |
| ANT+ Specification | 2.4GHz |
| IMEI Code | Conducted: 354377050002652 Radiated: 354377050003239 Conduction: 354377050002652 |
| HW Version | REV1.0 |
| SW Version | T555C.001 |
| EUT Stage | Identical Prototype |



| Items | Description |
|-------------------------------|-------------------|
| Modulation | GFSK |
| Channel Bandwidth (99%) | 0.894MHz |
| Max. Field Strength (Peak) | 97.32dB μ V/m |
| Max. Field Strength (Average) | 46.26dB μ V/m |
| ANT+ Channel Number | 79 |
| ANT+ Frequency Range | 2402-2480MHz |

2.4 Table for Test Modes

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

| Test Items | Mode |
|---|------|
| AC Power Line Conducted Emissions | CTX |
| Field Strength of Fundamental Emissions | CTX |
| Bandwidth | CTX |
| Radiated Emissions | CTX |

Note:

1. CTX=continuously transmitting.
2. The programmed RF utility, the engineering test program was provided and enabled to make EUT continuous transmit/receive.




2.5 Table for Testing Locations

| | | |
|---------------------------|---|-----------------------------|
| Test Site | SPORTON INTERNATIONAL (SHENZHEN) INC. | |
| Test Site Location | 1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595 | |
| Test Site No. | Sporton Site No. | |
| | TH01-SZ | CO01-SZ |
| Test Site | SPORTON INTERNATIONAL (SHENZHEN) INC. | |
| Test Site Location | No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398 | |
| Test Site No. | Sporton Site No. | FCC Registration No. |
| | 03CH01-SZ | 831040 |


Note: The test site complies with ANSI C63.4 2009 requirement.

2.6 Test Configurations

<AC Conducted Emissions>



<Radiated Spurious Emissions>





3. TEST RESULT

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit

For a Low-power Radio-frequency device which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

| Frequency (MHz) | QP Limit (dB μ V) | AV Limit (dB μ V) |
|-----------------|-----------------------|-----------------------|
| 0.15~0.5 | 66~56 | 56~46 |
| 0.5~5 | 56 | 46 |
| 5~30 | 60 | 50 |


3.1.2 Measuring Instruments

Please refer to section 4 of equipment list in this report.

3.1.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

3.1.4 Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω. LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

3.1.5 Test Deviation

There is no deviation with the original standard.

3.1.6 EUT Operation during Test


The EUT was placed on the test table and programmed in transmitting function.



3.1.7 Results of AC Power Line Conducted Emissions Measurement

| | | | |
|---------------|---|---------------|------------------------|
| Test Date | Apr. 16, 2015 | Test Site No. | CO01-SZ |
| Temperature | 21~23°C | Humidity | 41~43% |
| Test Engineer | Jack Tian | Configuration | ANT+ Transmitting Mode |
| Mode | GSM850 Idle + USB Cable (Charging from Adapter) + Earphone + ANT+TX | | |

Line




Site : CO01-SZ
 Condition: FCC 15C_QP LISN_L_20140304 LINE

IMEI : 354377050002652

| | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark |
|-----|------|-------|------------|------------|------------|-------------|------------|---------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | dB | |
| 1 | 0.38 | 22.75 | -25.59 | 48.34 | 12.29 | 0.28 | 10.18 | Average |
| 2 | 0.38 | 38.85 | -19.49 | 58.34 | 28.39 | 0.28 | 10.18 | QP |
| 3 * | 0.44 | 33.05 | -13.97 | 47.02 | 22.60 | 0.29 | 10.16 | Average |
| 4 | 0.44 | 41.45 | -15.57 | 57.02 | 31.00 | 0.29 | 10.16 | QP |
| 5 | 0.52 | 28.04 | -17.96 | 46.00 | 17.61 | 0.28 | 10.15 | Average |
| 6 | 0.52 | 38.34 | -17.66 | 56.00 | 27.91 | 0.28 | 10.15 | QP |
| 7 | 0.65 | 24.26 | -21.74 | 46.00 | 13.90 | 0.21 | 10.15 | Average |
| 8 | 0.65 | 37.06 | -18.94 | 56.00 | 26.70 | 0.21 | 10.15 | QP |
| 9 | 0.85 | 25.47 | -20.53 | 46.00 | 15.10 | 0.22 | 10.15 | Average |
| 10 | 0.85 | 36.47 | -19.53 | 56.00 | 26.10 | 0.22 | 10.15 | QP |
| 11 | 1.00 | 24.21 | -21.79 | 46.00 | 13.80 | 0.26 | 10.15 | Average |
| 12 | 1.00 | 34.11 | -21.89 | 56.00 | 23.70 | 0.26 | 10.15 | QP |



Neutral



Site : CO01-SZ
 Condition: FCC 15C_QP LISN_N_20140304 NEUTRAL

IMEI : 354377050002652

| | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark |
|-----|------|-------|------------|------------|------------|-------------|------------|---------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | dB | |
| 1 | 0.20 | 28.11 | -25.34 | 53.45 | 17.50 | 0.32 | 10.29 | Average |
| 2 | 0.20 | 39.61 | -23.84 | 63.45 | 29.00 | 0.32 | 10.29 | QP |
| 3 | 0.36 | 28.56 | -20.27 | 48.83 | 18.00 | 0.38 | 10.18 | Average |
| 4 | 0.36 | 39.66 | -19.17 | 58.83 | 29.10 | 0.38 | 10.18 | QP |
| 5 * | 0.44 | 29.56 | -17.51 | 47.07 | 19.00 | 0.40 | 10.16 | Average |
| 6 | 0.44 | 36.66 | -20.41 | 57.07 | 26.10 | 0.40 | 10.16 | QP |
| 7 | 0.53 | 26.24 | -19.76 | 46.00 | 15.71 | 0.38 | 10.15 | Average |
| 8 | 0.53 | 36.44 | -19.56 | 56.00 | 25.91 | 0.38 | 10.15 | QP |
| 9 | 0.76 | 25.12 | -20.88 | 46.00 | 14.70 | 0.27 | 10.15 | Average |
| 10 | 0.76 | 34.52 | -21.48 | 56.00 | 24.10 | 0.27 | 10.15 | QP |
| 11 | 1.20 | 22.90 | -23.10 | 46.00 | 12.40 | 0.34 | 10.16 | Average |
| 12 | 1.20 | 34.30 | -21.70 | 56.00 | 23.80 | 0.34 | 10.16 | QP |

3.2 20dB and & 99% Occupied Bandwidth

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20 dB bandwidth of the emissions in the specific band.


3.2.2 Measuring Instruments

Please refer to section 4 of equipment list in this report.

3.2.3 Test Procedures

1. The transmitter output port was connected to the spectrum analyzer.
2. Measured the spectrum width with highest power setting.

3.2.4 Test Setup Layout



3.2.5 Test Deviation

There is no deviation with the original standard.

3.2.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.




3.2.7 Test Result of 20dB Spectrum Bandwidth


| | | | |
|---------------|---------------|---------------|---------|
| Test Date | Apr. 01, 2015 | Test Site No. | TH01-SZ |
| Temperature | 24~26°C | Humidity | 50~53% |
| Test Engineer | Fly Liang | | |

| Frequency | 20dB BW (MHz) | 99% OBW (MHz) |
|-----------|---------------|---------------|
| 2402MHz | 0.714 | 0.894 |
| 2441MHz | 0.744 | 0.864 |
| 2480MHz | 0.774 | 0.870 |

20 dB Bandwidth Plot on 2402MHz



99% Bandwidth Plot on 2402MHz




Date: 1.APR.2015 10:44:06

Date: 1.APR.2015 10:12:17




20 dB Bandwidth Plot on 2441MHz




Date: 1.APR.2015 10:19:26

99% Bandwidth Plot on 2441MHz




Date: 1.APR.2015 10:39:31

20 dB Bandwidth Plot on 2480MHz



Date: 1.APR.2015 10:25:46

99% Bandwidth Plot on 2480MHz



Date: 1.APR.2015 10:33:52

3.3 Field Strength of Fundamental Emissions and Radiated Spurious Emissions

3.3.1 Limit

The field strength measured at 3 meters shall not exceed the limits in the following table:

| Fundamental Frequencies(MHz) | Field Strength(millivolts/m) | |
|------------------------------|------------------------------|-----------|
| | Fundamental | Harmonics |
| 902~928 | 50 | 0.5 |
| 2400~2483.5 | 50 | 0.5 |
| 5725~5875 | 50 | 0.5 |

Note: The limits shown in the above table are based on measurements using an average detector, except for the fundamental emission in the frequency band 902-928 MHz, which is based on measurements using a CISPR quasi-peak detector.

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general field strength limits listed in 15.209 as below, whichever is less stringent.

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009 – 0.490 | 2400/F(kHz) | 300 |
| 0.490 – 1.705 | 24000/F(kHz) | 30 |
| 1.705 – 30.0 | 30 | 30 |
| 30 – 88 | 100 | 3 |
| 88 – 216 | 150 | 3 |
| 216 - 960 | 200 | 3 |
| Above 960 | 500 | 3 |



3.3.2 Measuring Instruments

Please refer to section 4 of equipment list in this report.

3.3.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.

Remark:

1. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
2. For average measurement: use duty cycle correction factor method per 15.35(c).

Duty cycle = On time/100 milliseconds


On time = $N1*L1+N2*L2+...+Nn-1*LNn-1+Nn*Ln$

Where N1 is number of type 1 pulses, L1 is length of type 1 pulses, etc.


Average Emission Level = Peak Emission Level + 20*log(Duty cycle)

3.3.4 Test Setup Layout


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.3.5 Test Deviation

There is no deviation with the original standard.

3.3.6 EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

3.3.7 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.3.8 Duty cycle correction factor for average measurement

On time (One Pulse) Plot on 2441MHz



On time (Count Pulses) Plot on 2441MHz



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 0.14 / 100 = 0.28 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -51.06 \text{ dB}$

3.3.9 Test Result of Field Strength of Fundamental Emissions and Spurious Emissions

Please refer to Appendix A.



3.4 Antenna Requirements

3.4.1 Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

3.4.2 Antenna Connector Construction

Embedded in Antenna.



4. LIST OF MEASURING EQUIPMENT

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|-----------------------------------|----------------------|----------------------------------|--------------|---------------------------|------------------|---------------|---------------|-----------------------|
| Spectrum Analyzer | R&S | FSP30 | 101400 | 9kHz~30GHz | Jan. 28, 2015 | Apr. 01, 2015 | Jan. 27, 2016 | Conducted (TH01-SZ) |
| Power meter | Anritsu | ML2495A | 1218010 | 10Hz~40GHz | Jan. 28, 2015 | Apr. 01, 2015 | Jan. 27, 2016 | Conducted (TH01-SZ) |
| Power Sensor | Anritsu | MA2411B | 1207253 | 0.3GHz~40GHz | Jan. 28, 2015 | Apr. 01, 2015 | Jan. 27, 2016 | Conducted (TH01-SZ) |
| EMI TEST Receiver | R&S | ESCI7 | 100768 | 9kHz~3GHz | May 04, 2014 | Apr. 07, 2015 | May 03, 2015 | Radiation (03CH01-SZ) |
| Spectrum Analyzer | Agilent Technologies | N9038A | MY52260185 | 20Hz~26.5GHz | May 26, 2014 | Apr. 07, 2015 | May 25, 2015 | Radiation (03CH01-SZ) |
| Loop Antenna | R&S | HFH2-Z2 | 100354 | 9kHz~30MHz | May 09, 2014 | Apr. 07, 2015 | May 08, 2015 | Radiation (03CH01-SZ) |
| Bilog Antenna | TESEQ | CBL 6112D | 37877 | 30MHz~2GHz | Oct. 15, 2014 | Apr. 07, 2015 | Oct. 14, 2015 | Radiation (03CH01-SZ) |
| Double Ridge Horn Antenna | ETS Lindgren | 3117 | 00119436 | 1GHz~18GHz | Oct. 15, 2014 | Apr. 07, 2015 | Oct. 14, 2015 | Radiation (03CH01-SZ) |
| Double Ridged Horn Antenna | COM-POWER | AH-840 | 101073 | 18GHz~40GHz | Jun. 09, 2014 | Apr. 07, 2015 | Jun. 08, 2015 | Radiation (03CH01-SZ) |
| Amplifier | ADVANTEST | BB525C | E9007003 | 9kHz~3000MHz GAIN 30db | Jan. 28, 2015 | Apr. 07, 2015 | Jan. 27, 2016 | Radiation (03CH01-SZ) |
| Amplifier | Chengyi | AMF-7D-001 01800-30-10 P-R | 1707137 | 1GHz~18GHz | May 08, 2014 | Apr. 07, 2015 | May 07, 2015 | Radiation (03CH01-SZ) |
| Amplifier | Yiai | AV3860B | 04030 | 2GHz~26.5GHz | May 08, 2014 | Apr. 07, 2015 | May 07, 2015 | Radiation (03CH01-SZ) |
| AC Source | Chroma | 61601ACSO URCE | 616010002470 | 100Vac~240Vac | NCR | Apr. 07, 2015 | NCR | Radiation (03CH01-SZ) |
| Turn Table | EM Electronics | EM 1000 | N/A | 0~360 degree | NCR | Apr. 07, 2015 | NCR | Radiation (03CH01-SZ) |
| Antenna Mast | EM Electronics | EM 1000 | N/A | 1 m~4 m | NCR | Apr. 07, 2015 | NCR | Radiation (03CH01-SZ) |
| EMI TEST Receiver | R&S | ESCI7 | 100768 | 9kHz~3GHz | May 04, 2014 | Apr. 16, 2015 | May 03, 2015 | Conduction (CO01-SZ) |
| AC LISN | EMCO | 3816/2SH | 00103912 | 9kHz~30MHz | Feb. 02, 2015 | Apr. 16, 2015 | Feb. 01, 2016 | Conduction (CO01-SZ) |
| AC LISN (for auxiliary equipment) | EMCO | 3816/2SH | 00103892 | 9kHz~30MHz | Feb. 02, 2015 | Apr. 16, 2015 | Feb. 01, 2016 | Conduction (CO01-SZ) |
| AC Power Source | Chroma | 61602 | 616020000891 | 100Vac~250Vac | Sep. 29, 2014 | Apr. 16, 2015 | Sep. 28, 2015 | Conduction (CO01-SZ) |
| System Simulator | R&S | CMU 200 | 116456 | Full-Band | Aug. 11, 2014 | Apr. 16, 2015 | Aug. 10, 2015 | Conduction (CO01-SZ) |

Note: Test equipment calibration is traceable to the procedure of ISO17025.



Appendix A. Radiated Spurious Emission

15C 2.4GHz 2400~2483.5MHz

ANT+ (Band Edge @ 3m)

| ANT+ | Note | Frequency | Level | Over | Limit | Read | Antenna | Cable | Preamp | Ant | Table | Peak | Pol. |
|--------------------------|------|-----------|------------|--------|------------|----------|----------|--------|--------|--------|---------|---------|---------|
| | | (MHz) | (dBμV/m) | (dB) | (dBμV/m) | (dBμV) | (dB/m) | (dB) | (dB) | (cm) | (deg) | (P/A) | (H/V) |
| ANT+ CH00 2402MHz | | 2400 | 56.11 | -17.89 | 74 | 44.17 | 32.6 | 8.6 | 29.26 | 196 | 108 | P | H |
| | | 2400 | 5.05 | -48.95 | 54 | - | - | - | - | 196 | 108 | A | H |
| | | 2402 | 96.7 | -17.3 | 114 | 84.76 | 32.6 | 8.6 | 29.26 | 196 | 108 | P | H |
| | | 2402 | 45.64 | -48.36 | 94 | - | - | - | - | 196 | 108 | A | H |
| | | 2400 | 50.23 | -23.77 | 74 | 38.29 | 32.6 | 8.6 | 29.26 | 182 | 212 | P | V |
| | | 2400 | -0.83 | -54.83 | 54 | - | - | - | - | 182 | 212 | A | V |
| | | 2402 | 91.18 | -22.82 | 114 | 79.24 | 32.6 | 8.6 | 29.26 | 182 | 212 | P | V |
| | | 2402 | 40.12 | -53.88 | 94 | - | - | - | - | 182 | 212 | A | V |
| ANT+ CH 39 2441MHz | | 2400 | 50.22 | -23.78 | 74 | 38.28 | 32.6 | 8.6 | 29.26 | 103 | 126 | P | H |
| | | 2400 | -0.84 | -54.84 | 54 | - | - | - | - | 103 | 126 | A | H |
| | | 2441 | 97.32 | -16.68 | 114 | 85.18 | 32.65 | 8.69 | 29.2 | 103 | 126 | P | H |
| | | 2441 | 46.26 | -47.74 | 94 | - | - | - | - | 103 | 126 | A | H |
| | | 2483.5 | 50.07 | -23.93 | 74 | 37.77 | 32.68 | 8.78 | 29.16 | 103 | 126 | P | H |
| | | 2483.5 | -0.99 | -54.99 | 54 | - | - | - | - | 103 | 126 | A | H |
| | | 2400 | 50.1 | -23.9 | 74 | 38.16 | 32.6 | 8.6 | 29.26 | 186 | 93 | P | V |
| | | 2400 | -0.96 | -54.96 | 54 | - | - | - | - | 186 | 93 | A | V |
| | | 2441 | 93.58 | -20.42 | 114 | 81.44 | 32.65 | 8.69 | 29.2 | 186 | 93 | P | V |
| | | 2441 | 42.52 | -51.48 | 94 | - | - | - | - | 186 | 93 | A | V |
| | | 2483.5 | 50.78 | -23.22 | 74 | 38.48 | 32.68 | 8.78 | 29.16 | 186 | 93 | P | V |
| | | 2483.5 | -0.28 | -54.28 | 54 | - | - | - | - | 186 | 93 | A | V |



| | | | | | | | | | | | | | |
|-----------------------------------|--|--------|-------|--------|-----|-------|-------|------|-------|-----|-----|---|---|
| ANT+ CH 78 2480MHz | | 2480 | 96.02 | -17.98 | 114 | 83.72 | 32.68 | 8.78 | 29.16 | 144 | 121 | P | H |
| | | 2480 | 44.96 | -49.04 | 94 | - | - | - | - | 144 | 121 | A | H |
| | | 2483.5 | 51.01 | -22.99 | 74 | 38.71 | 32.68 | 8.78 | 29.16 | 144 | 121 | P | H |
| | | 2483.5 | -0.05 | -54.05 | 54 | - | - | - | - | 144 | 121 | A | H |
| | | 2480 | 92.62 | -21.38 | 114 | 80.32 | 32.68 | 8.78 | 29.16 | 186 | 81 | P | V |
| | | 2480 | 41.56 | -52.44 | 94 | - | - | - | - | 186 | 81 | A | V |
| | | 2483.5 | 50.68 | -23.32 | 74 | 38.38 | 32.68 | 8.78 | 29.16 | 186 | 81 | P | V |
| | | 2483.5 | -0.38 | -54.38 | 54 | - | - | - | - | 186 | 81 | A | V |
| Remark | <ol style="list-style-type: none">1. No other spurious found.2. All results are PASS against Peak and Average limit line. | | | | | | | | | | | | |



15C 2.4GHz 2400~2483.5MHz

ANT+ (Harmonic @ 3m)

| ANT+ | Note | Frequency | Level | Over | Limit | Read | Antenna | Cable | Preamp | Ant | Table | Peak | Pol. |
|--------------------------|---|-----------|------------|--------|-------|----------|----------|--------|--------|--------|---------|-------|-------|
| | | (MHz) | (dBμV/m) | (dB) | Limit | Level | Factor | Loss | Factor | Pos | Pos | Avg. | |
| | | | | | Line | (dBμV) | (dB/m) | (dB) | (dB) | (cm) | (deg) | (P/A) | (H/V) |
| ANT+ CH 00 2402MHz | | 4804 | 42.59 | -31.41 | 74 | 46.14 | 34.39 | 12.86 | 50.8 | 151 | 219 | P | H |
| | | 4804 | 41.61 | -32.39 | 74 | 45.16 | 34.39 | 12.86 | 50.8 | 151 | 219 | P | V |
| ANT+ CH 39 2441MHz | | 4882 | 43.88 | -30.12 | 74 | 47.05 | 34.43 | 12.98 | 50.58 | 115 | 258 | P | H |
| | | 7323 | 44.46 | -29.54 | 74 | 44.4 | 36.23 | 14.71 | 50.88 | 152 | 309 | P | H |
| | | 4882 | 42.39 | -31.61 | 74 | 45.56 | 34.43 | 12.98 | 50.58 | 115 | 258 | P | V |
| | | 7323 | 44.02 | -29.98 | 74 | 43.96 | 36.23 | 14.71 | 50.88 | 152 | 309 | P | V |
| ANT+ CH 78 2480MHz | | 4960 | 40.82 | -33.18 | 74 | 43.55 | 34.48 | 13.1 | 50.31 | 118 | 289 | P | H |
| | | 7440 | 42.82 | -31.18 | 74 | 42.65 | 36.28 | 14.77 | 50.88 | 158 | 273 | P | H |
| | | 4960 | 41.37 | -32.63 | 74 | 44.1 | 34.48 | 13.1 | 50.31 | 118 | 289 | P | V |
| | | 7440 | 43.01 | -30.99 | 74 | 42.84 | 36.28 | 14.77 | 50.88 | 158 | 273 | P | V |
| Remark | 1. No other spurious found. 2. All results are PASS against Peak and Average limit line. | | | | | | | | | | | | |



15C 2.4GHz 2400~2483.5MHz

ANT+ (LF)

| ANT+ | Note | Frequency | Level | Over | Limit | Read | Antenna | Cable | Preamp | Ant | Table | Peak | Pol. |
|----------------------|--|-----------|------------|--------|------------|--------|----------|--------|--------|--------|---------|-------|-------|
| | | | | Limit | Line | Level | Factor | Loss | Factor | Pos | Pos | Avg. | |
| | | (MHz) | (dBμV/m) | (dB) | (dBμV/m) | (dBμV) | (dB/m) | (dB) | (dB) | (cm) | (deg) | (P/A) | (H/V) |
| 2.4GHz ANT+ LF | | 99.84 | 33.47 | -10.03 | 43.5 | 46 | 11.7 | 1.55 | 25.78 | 100 | 360 | P | H |
| | | 198.78 | 22.75 | -20.75 | 43.5 | 34.21 | 11.6 | 2.2 | 25.26 | | | P | H |
| | | 397.63 | 29.1 | -16.9 | 46 | 36.35 | 15.37 | 3.18 | 25.8 | | | P | H |
| | | 730.34 | 29.75 | -16.25 | 46 | 30.67 | 20.96 | 4.43 | 26.31 | | | P | H |
| | | 806.97 | 30.34 | -15.66 | 46 | 29.4 | 22.44 | 4.65 | 26.15 | | | P | H |
| | | 1000 | 31.03 | -22.97 | 54 | 29.8 | 21.2 | 5.14 | 25.11 | | | P | H |
| | | 39.7 | 32.37 | -7.63 | 40 | 42.93 | 14.5 | 0.96 | 26.02 | 100 | 360 | P | V |
| | | 99.84 | 31.26 | -12.24 | 43.5 | 43.79 | 11.7 | 1.55 | 25.78 | | | P | V |
| | | 355.92 | 25.43 | -20.57 | 46 | 33.08 | 14.83 | 2.99 | 25.47 | | | P | V |
| | | 614.91 | 27.84 | -18.16 | 46 | 30.41 | 19.79 | 4.07 | 26.43 | | | P | V |
| | | 813.76 | 30.11 | -15.89 | 46 | 29.15 | 22.38 | 4.71 | 26.13 | | | P | V |
| | | 982.54 | 30.92 | -23.08 | 54 | 29.77 | 21.27 | 5.12 | 25.24 | | | P | V |
| Remark | 1. No other spurious found. 2. All results are PASS against limit line. | | | | | | | | | | | | |



Note symbol

| | |
|-----|--|
| * | Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.249(c). |
| ! | Test result is over limit line. |
| P/A | Peak or Average |
| H/V | Horizontal or Vertical |



A calculation example for radiated spurious emission is shown as below:

| ANT+ | Note | Frequency | Level | Over | Limit | Read | Antenna | Cable | Preamp | Ant | Table | Peak | Pol. |
|-------------------------|------|-----------|------------|--------|------------|----------|----------|--------|--------|--------|---------|---------|---------|
| | | (MHz) | (dBμV/m) | (dB) | (dBμV/m) | (dBμV) | (dB/m) | (dB) | (dB) | (cm) | (deg) | (P/A) | (H/V) |
| ANT+ CH00 2402MHz | | 2400 | 56.11 | -17.89 | 74 | 44.17 | 32.6 | 8.6 | 29.26 | 196 | 108 | P | H |
| | | 2400 | 5.05 | -48.95 | 54 | - | - | - | - | 196 | 108 | A | H |

- Level(dBμV/m) =
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2400MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.6 (dB/m) + 8.6 (dB) + 44.17 (dBμV) –29.26 (dB)
= 56.11 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 56.11 (dBμV/m) – 74(dBμV/m)
= -17.89 (dB)

For Average Limit @ 2400MHz:

- Level(dBμV/m)
= Peak Level (dBμV/m) + Duty cycle correction factor (dB)
= 56.11 (dBμV/m) – 51.06 (dB)
= 5.05 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 5.05 (dBμV/m) – 54(dBμV/m)
= -48.95 (dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.