



**FCC CFR47 PART 15 SUBPART C**

**CERTIFICATION TEST REPORT**

**FOR**

**GSM/WCDMA Tablet + Bluetooth, DTS b/g/n**

**MODEL NUMBER : SM-T561M**

**FCC ID: A3LSMT561M**

**REPORT NUMBER: 15K20331-E2**

**ISSUE DATE: APRIL 24, 2015**

*Prepared for*

**SAMSUNG ELECTRONICS CO., LTD.  
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,  
GYEONGGI-DO, 443-742, KOREA**

*Prepared by*

**UL Korea, Ltd. Suwon Laboratory  
218 Maeyeong-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 443-823, Korea  
TEL: (031) 337-9902  
FAX: (031) 213-5433**



**ACCREDITED**

**TL-637**

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	04/24/15	Initial issue	CY Choi

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>4</b>
<b>2. TEST METHODOLOGY .....</b>	<b>5</b>
<b>3. FACILITIES AND ACCREDITATION .....</b>	<b>5</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>5</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>	<i>5</i>
4.2. <i>SAMPLE CALCULATION .....</i>	<i>5</i>
4.3. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>6</i>
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>7</b>
5.1. <i>DESCRIPTION OF EUT .....</i>	<i>7</i>
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	<i>7</i>
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	<i>7</i>
5.4. <i>WORST-CASE CONFIGURATION AND MODE.....</i>	<i>7</i>
5.5. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>8</i>
<b>6. TEST AND MEASUREMENT EQUIPMENT .....</b>	<b>10</b>
<b>7. MEASUREMENT METHODS .....</b>	<b>11</b>
<b>8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS .....</b>	<b>11</b>
8.1. <i>ON TIME AND DUTY CYCLE RESULTS.....</i>	<i>11</i>
<b>9. SUMMARY TABLE .....</b>	<b>12</b>
<b>10. ANTENNA PORT TEST RESULTS .....</b>	<b>13</b>
10.1. <i>6 dB BANDWIDTH .....</i>	<i>13</i>
10.2. <i>99% BANDWIDTH .....</i>	<i>17</i>
10.3. <i>OUTPUT POWER.....</i>	<i>21</i>
10.4. <i>AVERAGE POWER .....</i>	<i>25</i>
10.5. <i>PSD.....</i>	<i>26</i>
10.6. <i>CONDUCTED SPURIOUS EMISSIONS .....</i>	<i>30</i>
<b>11. RADIATED TEST RESULTS .....</b>	<b>37</b>
11.1. <i>LIMITS AND PROCEDURE.....</i>	<i>37</i>
11.2. <i>TRANSMITTER ABOVE 1 GHz.....</i>	<i>38</i>
11.3. <i>WORST-CASE BELOW 1 GHz .....</i>	<i>51</i>
<b>12. AC POWER LINE CONDUCTED EMISSIONS .....</b>	<b>54</b>
<b>13. SETUP PHOTOS .....</b>	<b>57</b>

# 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** SAMSUNG ELECTRONICS CO., LTD.  
**EUT DESCRIPTION:** GSM/WCDMA Tablet + Bluetooth and DTS b/g/n  
**MODEL NUMBER:** SM-T561M  
**SERIAL NUMBER:** R32G301WP2N (RADIATED); R32G301WPDV (CONDUCTED)  
**DATE TESTED:** MARCH 11 - APRIL 20, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For  
UL Korea, Ltd. By:

Tested By:



Ji Ho Choi  
Suwon Lab Manager  
UL Korea, Ltd.

CY Choi  
Suwon Lab Engineer  
UL Korea, Ltd.

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

## 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-823, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
<input checked="" type="checkbox"/>	Chamber 1
<input type="checkbox"/>	Chamber 2

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

### 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	4.14 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA Tablet + Bluetooth and DTS b/g/n.  
This test report addresses the DTS (BLE) operational mode.

### 5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum total conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402 - 2480	BLE	7.88	6.13

### 5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antennas, with a maximum gain of -0.19 dBi.

### 5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

## 5.5. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA12EWE	N/A	N/A
Data Cable	SAMSUNG	ECB-DU68WC	N/A	N/A
Earphone	SAMSUNG	GH59-11129H	N/A	N/A


### I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	0.8m	N/A
2	Audio	1	Mini-Jack	Unshielded	1.0m	N/A

### TEST SETUP

The EUT is a stand-alone unit during the tests. Test software exercised the radio card.

**SETUP DIAGRAM FOR TESTS**



## 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	950	11-17-15
Antenna, Horn, 18 GHz	ETS	3115	00167211	09-20-15
Antenna, Horn, 40 GHz	ETS	3116C	00166255	09-23-15
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	09-29-15
Preamplifier, 1000 MHz	Sonoma	310N	341282	11-17-15
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	11-18-15
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	09-23-15
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	11-17-15
Average Power Sensor	R&S	NRZ-Z91	102681	11-17-15
Average Power Sensor	Agilent / HP	U2000	MY54270007	09-23-15
EMI Test Receive, 40 GHz	R&S	ESU40	100439	11-17-15
EMI Test Receive, 3 GHz	R&S	ESR3	101832	11-17-15
Attenuator / Switch driver	HP	11713A	3748A04272	N/A
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	009	11-17-15
High Pass Filter 5GHz	Micro-Tronics	HPS17542	009	11-17-15
High Pass Filter 6GHz	Micro-Tronics	HPM17543	010	11-17-15

## 7. MEASUREMENT METHODS

KDB 558074 D01 DTS Meas Guidance v03r02: Measurement Procedure AVGPM-G is used for power and AVGPS-3 is used for power spectral density.

Unwanted emissions within Restricted Bands are measured using traditional radiated procedures.

Band edge emissions within Restricted Bands are measured using RMS with duty cycle factor offset method.

## 8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS

### LIMITS

None; for reporting purposes only.

### PROCEDURE

KDB 789033 Zero-Span Spectrum Analyzer Method.

### 8.1. ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)
<b>2400MHz Bands</b>						
BLE	0.389	0.625	0.622	62.2%	2.06	2.572

## 9. SUMMARY TABLE

The FCC ID: A3LSMT561M shares the same enclosure and circuit board as FCC ID: A3LSMT561Y. The BLE circuitry and layout, including antennas, are almost identical between the two units. The BLE antennas and surrounding circuitry are the same between these two units.

After confirming through preliminary radiated emissions that the performance of the FCC ID: A3LSMT561M remains representative of FCC ID: A3LSMT561Y, test data for FCC ID: A3LSMT561Y is being submitted for this application to cover BLE features.

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.247 (a)(2)	Occupied Band width (6dB)	>500KHz	Conducted	Pass	0.688 MHz
2.1051, 15.247 (d)	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-44.831 dBm
15.247	TX conducted output power	<30dBm		Pass	7.88 dBm
15.247	PSD	<8dBm		Pass	-5.91 dBm
15.207 (a)	AC Power Line conducted emissions	Section 10	Power Line conducted	Pass	43.97 dBuV (PK)
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m	Radiated	Pass	51.53 dBuV/m (AV)

## 10. ANTENNA PORT TEST RESULTS

### 10.1. 6 dB BANDWIDTH

#### LIMITS

FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.

#### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

#### RESULTS


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.714	0.5
Mid	2440	0.704	0.5
High	2480	0.688	0.5
Worst		0.688	

**6 dB BANDWIDTH PLOTS**


**LOW CHANNEL**



### MID CHANNEL



### HIGH CHANNEL



## 10.2. 99% BANDWIDTH

### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE


Reference to KDB558074 D01 DTS Meas Guidance v03r02: The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth and to 1% of the span. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

### RESULTS


Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.064
Mid	2440	1.064
High	2480	1.063
Worst		1.064

**99% BANDWIDTH PLOTS**


**LOW CHANNEL**



**MID CHANNEL**



### HIGH CHANNEL



### 10.3. OUTPUT POWER

#### LIMITS

FCC §15.247 (b)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

#### TEST PROCEDURE


Peak power is measured using KDB558074 D01 DTS Meas Guidance v03r02 under section 9.1.1 utilizing spectrum analyzer.

#### RESULTS


Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	8.327	30.000	-21.673
Mid	2440	8.498	30.000	-21.502
High	2480	8.580	30.000	-21.420
Worst		8.580		-21.420

**OUTPUT POWER PLOTS**


**LOW CHANNEL**



### MID CHANNEL



### HIGH CHANNEL



## 10.4. AVERAGE POWER

### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE

The transmitter output is connected to a power meter.

### RESULTS

The cable assembly insertion loss of 10.1 dB (including 10 dB pad and 0.1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	7.83
Middle	2440	7.88
High	2480	7.83

## 10.5. PSD

### LIMITS

FCC §15.247

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### TEST PROCEDURE


Power Spectral Density was performed utilizing the “Method PKPSD (Peak PSD)” under KDB558074 D01 DTS Meas Guidance v03r02

### RESULTS

Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Margin (dB)
Low	2402	-6.24	8.00	-14.24
Mid	2440	-5.91	8.00	-13.91
High	2480	-6.16	8.00	-14.16

**POWER SPECTRAL DENSITY PLOTS**

**LOW CHANNEL**







## **10.6. CONDUCTED SPURIOUS EMISSIONS**

### **LIMITS**

FCC §15.247 (d)

Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dB.

### **TEST PROCEDURE**


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


**RESULTS**

**SPURIOUS EMISSIONS, LOW CHANNEL**

**LOW CHANNEL BANDEDGE**




### LOW CHANNEL SPURIOUS




**SPURIOUS EMISSIONS, MID CHANNEL**

**MID CHANNEL REFERENCE**




### MID CHANNEL SPURIOUS



**SPURIOUS EMISSIONS, HIGH CHANNEL**

**HIGH CHANNEL BANDEDGE**





## 11. RADIATED TEST RESULTS

### 11.1. LIMITS AND PROCEDURE

#### LIMITS

FCC §15.205 and §15.209

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

#### TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4 - 2009. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.


For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and add duty cycle factor for average measurements. Duty cycle factor =  $10 \log(1/x)$ . For this sample: DCF =  $10 \log(1/0.607) = 2.17 \text{ dB}$  (Spectrum Analyzer round it up to 2.17dB)

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

## 11.2. TRANSMITTER ABOVE 1 GHz RESTRICTED BANDEDGE (LOW CHANNEL)

### HORIZONTAL PEAK AND AVERAGE PLOT



### HORIZONTAL DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3115D Factor	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	40.4	PK	27.9	-22.8	0	45.5	-	-	74	-28.5	34	100	H
2	* 2.347	43.26	PK	27.8	-22.9	0	48.16	-	-	74	-25.84	34	100	H
3	* 2.39	31.09	RMS	27.9	-22.8	2.17	38.36	54	-15.64	-	-	34	100	H
4	* 2.39	31.52	RMS	27.9	-22.8	2.17	38.79	54	-15.21	-	-	34	100	H

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

**VERTICAL PEAK AND AVERAGE PLOT**



**VERTICAL DATA**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3115D Factor	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	39.07	PK	27.9	-22.8	0	44.17	-	-	74	-29.83	272	317	V
2	* 2.336	43.4	PK	27.8	-22.9	0	48.3	-	-	74	-25.7	272	317	V
3	* 2.39	30.56	RMS	27.9	-22.8	2.17	37.83	54	-16.17	-	-	272	317	V
4	* 2.387	31.13	RMS	27.9	-22.8	2.17	38.4	54	-15.6	-	-	272	317	V


\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

## AUTHORIZED BANDEDGE (HIGH CHANNEL)

### HORIZONTAL PEAK AND AVERAGE PLOT



### HORIZONTAL DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3115D Factor	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	49.94	Pk	27.9	-22.6	0	55.24	-	-	74	-18.76	3	102	H
2	* 2.485	50.29	Pk	27.9	-22.6	0	55.59	-	-	74	-18.41	3	102	H
3	* 2.484	44.06	RMS	27.9	-22.6	2.17	51.53	54	-2.47	-	-	3	102	H
4	* 2.484	43.87	RMS	27.9	-22.6	2.17	51.34	54	-2.66	-	-	3	102	H

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

**VERTICAL PEAK AND AVERAGE PLOT**



**VERTICAL DATA**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3115D Factor	Path_2_10dB	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	45.51	Pk	27.9	-22.6	0	50.81	-	-	74	-23.19	185	362	V
2	* 2.484	46.69	Pk	27.9	-22.6	0	51.99	-	-	74	-22.01	185	362	V
3	* 2.484	38.47	RMS	27.9	-22.6	2.17	45.94	54	-8.06	-	-	185	362	V
4	* 2.484	38.6	RMS	27.9	-22.6	2.17	46.07	54	-7.93	-	-	185	362	V


\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection


**HARMONICS AND SPURIOUS EMISSIONS**

**LOW CHANNEL HORIZONTAL**



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

### LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

**LOW CHANNEL DATA**


Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	31150 Factor	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.809	29.71	PK	31.9	-29.8	0	31.81	-	-	74	-42.19	0-360	200	H
4	7.212	26.03	PK	37	-25.4	0	37.63	-	-	-	-	0-360	200	H
5	9.603	22.99	PK	37.7	-21	0	39.69	-	-	-	-	0-360	200	H
2	* 4.802	28.79	PK	31.9	-29.8	0	30.89	-	-	74	-43.11	0-360	100	V
3	7.209	26.11	PK	37	-25.4	0	37.71	-	-	-	-	0-360	200	V
6	9.611	23.16	PK	37.7	-21	0	39.86	-	-	-	-	0-360	200	V

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK – Peak Detector

### MID CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

### MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

**MID CHANNEL DATA**


Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3115D Factor	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.87	28.41	PK	32	-29.2	0	31.21	-	-	74	-42.79	0-360	200	H
4	* 7.321	26.45	PK	37.1	-25.6	0	37.95	-	-	74	-36.05	0-360	100	H
5	9.751	23.61	PK	37.6	-21.9	0	39.31	-	-	-	-	0-360	200	H
2	* 4.869	27.83	PK	32	-29.2	0	30.63	-	-	74	-43.37	0-360	100	V
3	* 7.322	26.55	PK	37.2	-25.6	0	38.15	-	-	74	-35.85	0-360	200	V
6	9.752	23.28	PK	37.6	-22	0	38.88	-	-	-	-	0-360	200	V

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK – Peak Detector

### HIGH CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

### HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

## HIGH CHANNEL DATA

### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	31150 Factor	Path_3_3GHP	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.971	28.49	PK	32.2	-28.8	0	31.89	-	-	74	-42.11	0-360	100	H
4	* 7.454	26.36	PK	37.3	-24.8	0	38.86	-	-	74	-35.14	0-360	200	H
5	9.767	23.59	PK	37.6	-22.1	0	39.09	-	-	-	-	0-360	200	H
2	* 4.973	28.52	PK	32.2	-28.8	0	31.92	-	-	74	-42.08	0-360	100	V
3	* 7.456	26.75	PK	37.3	-24.8	0	39.25	-	-	74	-34.75	0-360	100	V
6	9.759	23.66	PK	37.6	-22	0	39.26	-	-	-	-	0-360	100	V


\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak Detector


### 11.3. WORST-CASE BELOW 1 GHz

#### SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)

#### HORIZONTAL PLOT



### VERTICAL PLOT



**BELOW 1 GHz TABLE**

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163-750	Bi-Log	DC Corr (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	60.09	51.05	Pk	12.6	-29.9	0	33.75	40	-6.25	0-360	400	H
5	180.4075	43.39	Pk	9.4	-28.3	0	24.49	43.52	-19.03	0-360	200	H
1	60.09	55.51	Pk	12.6	-29.9	0	38.21	40	-1.79	0-360	100	V
3	79.98	47.87	Pk	6.9	-29.6	0	25.17	40	-14.83	0-360	100	V
4	180.4075	40.51	Pk	9.4	-28.3	0	21.61	43.52	-21.91	0-360	100	V
6	* 240.5	57.21	Pk	12.1	-27.8	0	41.51	46.02	-4.51	0-360	101	H
7	* 240.5	53.13	Pk	12.1	-27.8	0	37.43	46.02	-8.59	0-360	101	V
8	504	43.88	Pk	17.1	-26.2	0	34.78	46.02	-11.24	0-360	101	V

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

Radiated Emissions

Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163-750	Bi-Log	DC Corr (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
58.46	52.46	Qp	12.8	-30	0	35.26	40	-4.74	26	125	V
* 240.496	55.45	Qp	12.1	-27.8	0	39.75	46.02	-6.27	210	123	H

\* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Qp - Quasi-Peak detector

## 12. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.


### TEST PROCEDURE

ANSI C63.4 - 2009

**RESULTS**

**6 WORST EMISSIONS**

**LINE 1 PLOT**



**LINE 1 RESULTS**


Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_N	CE Shield Room	Corrected Reading (dBuV)	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
1	.2175	33.3	Pk	9.9	0	43.2	62.91	-19.71	-	-
2	.2085	10.43	Av	9.9	0	20.33	-	-	53.26	-32.93
3	.4065	33.97	Pk	10	0	43.97	57.72	-13.75	-	-
4	.4065	23.03	Av	10	0	33.03	-	-	47.72	-14.69
5	.6135	21.54	Pk	10.1	0	31.64	56	-24.36	-	-
6	.6135	6.24	Av	10.1	0	16.34	-	-	46	-29.66
7	.933	13.53	Pk	9.9	0	23.43	56	-32.57	-	-
8	.9285	1.9	Av	9.9	0	11.8	-	-	46	-34.2
9	6.3555	19.38	Pk	9.7	.1	29.18	60	-30.82	-	-
10	6.4185	.35	Av	9.7	.1	10.15	-	-	50	-39.85
11	22.1775	15.77	Pk	9.8	.2	25.77	60	-34.23	-	-
12	22.1595	4.79	Av	9.8	.2	14.79	-	-	50	-35.21

Pk - Peak detector

Av - Average detection

### LINE 2 PLOT



### LINE 2 RESULTS

Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_L 1	CE Shield Room	Corrected Reading (dBuV)	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
13	.222	30.15	Pk	9.6	0	39.75	62.74	-22.99	-	-
14	.2355	11.59	Av	9.7	0	21.29	-	-	52.25	-30.96
15	.4065	24.37	Pk	9.9	0	34.27	57.72	-23.45	-	-
16	.402	17.83	Av	9.9	0	27.73	-	-	47.81	-20.08
17	.6405	13.92	Pk	9.9	0	23.82	56	-32.18	-	-
18	.645	2.99	Av	9.9	0	12.89	-	-	46	-33.11
19	.933	13.47	Pk	9.5	0	22.97	56	-33.03	-	-
20	.933	2.04	Av	9.5	0	11.54	-	-	46	-34.46
21	5.7705	18.39	Pk	9.4	.1	27.89	60	-32.11	-	-
22	5.7615	4.37	Av	9.4	.1	13.87	-	-	50	-36.13
23	20.8365	20.25	Pk	9.4	.2	29.85	60	-30.15	-	-
24	20.8365	7.14	Av	9.4	.2	16.74	-	-	50	-33.26

Pk - Peak detector  
 Av - Average detection