

On your side



# TEST REPORT

FCC LTE Test for SM-T725

Certification

APPLICANT

SAMSUNG Electronics Co., Ltd.

REPORT NO.

HCT-RF-1906-FC016-R1

DATE OF ISSUE

17 June 2019


**HCT Co., Ltd.**

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA

Tel. +82 31 634 6300 F ax. +82 31 645 6401



HCT Co., Ltd.  
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 Fax. +82 31 645 6401



REPORT NO.  
HCT-RF-1906-FC016-R1

DATE OF ISSUE  
17 June 2019

Other ID  
FCC: A3LSMT725U

Applicant	SAMSUNG Electronics Co., Ltd. 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
Eut Type	Tablet
Model Name	SM-T725
Additional Model(s)	SM-T725N, SM-T727
Date of Receipt	May 10, 2019
FCC Rule Part(s)	§ 27, § 2
FCC Classification	PCS Licensed Transmitter (PCB)
Manufacturer	SAMSUNG Electronics Co., Ltd.

Tested by  
Kwon Jeong

Technical Manager  
Jong Seok Lee

HCT CO., LTD.  
Soo Chan Lee  
SooChan Lee / CEO

**EVISION HISTORY**

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	June 10, 2019	Initial Release
1	June 17, 2019	Revised the date of test Revised the date of test equipment

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

**CONTENTS**

1. GENERAL INFORMATION	5
1.1. MAXIMUM OUTPUT POWER	5
2. INTRODUCTION	6
2.1. DESCRIPTION OF EUT	6
2.2. MEASURING INSTRUMENT CALIBRATION	6
2.3. TEST FACILITY	6
3. DESCRIPTION OF TESTS	7
3.1 TEST PROCEDURE	7
3.2 RADIATED POWER	8
3.3 RADIATED SPURIOUS EMISSIONS	10
3.4 OCCUPIED BANDWIDTH.	11
3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	12
3.6 BAND EDGE	13
3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	15
3.8 WORST CASE(RADIATED TEST)	16
3.9 WORST CASE(CONDUCTED TEST)	17
4. LIST OF TEST EQUIPMENT	18
5. MEASUREMENT UNCERTAINTY	19
6. SUMMARY OF TEST RESULTS	20
6.1 Test Condition : Conducted Test	20
6.2 Test Condition : Radiated Test	20
7. SAMPLE CALCULATION	21
8. TEST DATA	23
8.1 EFFECTIVE RADIATED POWER	23
8.2 RADIATED SPURIOUS EMISSIONS	24
8.3 OCCUPIED BANDWIDTH	27
8.4 CONDUCTED SPURIOUS EMISSIONS	28
8.5 BAND EDGE	28
8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	29
9. TEST PLOTS	33
10. APPENDIX A_ TEST SETUP PHOTO	56

**MEASUREMENT REPORT****1. GENERAL INFORMATION**

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMT725U
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter (PCB)
FCC Rule Part(s):	§ 27, § 2
EUT Type:	Tablet
Model(s):	SM-T725
Additional Model(s):	T725N, T727
Keyboard Information	Model : EH-FT720 Manufacture: SAMSUNG
Charging Doc Information	Model : EE-D3200 Manufacture: SAMSUNG
Data Reuse	According to the Evaluation report, all of the data contained herein is reused from the reference FCC ID : A3LSMT725 report.
Tx Frequency:	779.5 MHz –784.5 MHz (LTE – Band 13 (5MHz)) 782 MHz (LTE – Band 13 (10 MHz))
Date(s) of Tests:	March 04, 2019 ~ March 13, 2019

**1.1. MAXIMUM OUTPUT POWER**

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	ERP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band13 (5)	779.5 –784.5	4M49G7D	QPSK	0.030	14.70
		4M50W7D	16QAM	0.024	13.77
		4M51W7D	64QAM	0.019	12.82
LTE – Band13 (10)	782.0	8M98G7D	QPSK	0.030	14.79
		8M97W7D	16QAM	0.024	13.89
		8M98W7D	64QAM	0.019	12.88

## 2. INTRODUCTION

### 2.1. DESCRIPTION OF EUT

The EUT was a Tablet with GSM/GPRS/EGPRS/UMTS and LTE.

It also supports IEEE 802.11 a/b/g/n/ac (HT20/40/80), ANT+, Bluetooth, BT LE.

### 2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

### 2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.

### 3. DESCRIPTION OF TESTS

#### 3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI C63.26-2015 – Section 5.2 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

## 3.2 RADIATED POWER

### Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

### Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq$  3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $>$  2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

### Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d(\text{dBm}) = P_g(\text{dBm}) - \text{cable loss } (\text{dB}) + \text{antenna gain } (\text{dB})$$

Where:  $P_d$  is the dipole equivalent power and  $P_g$  is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

### 3.3 RADIATED SPURIOUS EMISSIONS

#### Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.


#### Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq 3 \times$  RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $> 2 \times$  span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10<sup>th</sup> harmonics from 9 kHz.

#### Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin  $> 20$  dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data

### 3.4 OCCUPIED BANDWIDTH.



#### Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

#### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq$  3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### 3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



#### Test setup


#### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

#### Test Settings

1. RBW = 1 MHz
2. VBW  $\geq$  3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time = auto
6. Number of points in sweep  $\geq 2 * \text{Span} / \text{RBW}$

### 3.6 BAND EDGE



#### Test setup

#### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

#### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1% of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points  $\geq 2 \times \text{Span}/\text{RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize


**Test Notes**

According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels (low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

### 3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



#### Test setup

#### Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

2. Primary Supply Voltage:

- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.
- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

#### Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

### 3.8 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
- The worst case is reported with the EUT positioning, modulations, and paging service configurations shown in the test data.
- SM-T725 & additional models were tested and the worst case results are reported.  
(Worst case : SM-T725)
- SM-T725 with Stand alone&Keyboard&Charging pad were tested and the worst case results are reported.  
(Worst case : Stand alone)
- Please refer to the table below.

[ Worst case ]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM	1	0	X
Radiated Spurious and Harmonic Emissions	QPSK	1	0	X

### 3.9 WORST CASE(CONDUCTED TEST)

- Worst case : Of all modulation, We have tested modulation of the high Conducted Output Power.  
Conducted Output Power value can be confirmed on the SAR report.

[ Worst case ]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM	5, 10	Mid	Full RB	0
Band Edge	* QPSK	5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		5, 10	Low, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	* QPSK	5, 10	Low, Mid, High	1	0

- All modes of operation were investigated and the worst case configuration results are reported.

- SM-T725 & additional models were tested and the worst case results are reported.

(Worst case : SM-T725)

**4. LIST OF TEST EQUIPMENT**

Manufacturer	Model/ Equipment	Serial Number	Calibration Date	Calibration Interval	Calibration Due
REOHDE & SCHWARZ	SCU 18 / AMPLIFIER	10094	04/17/2018	Annual	04/17/2019
Wainwright	WHK1.2/15G-10EF/H.P.F	4	04/04/2018	Annual	04/04/2019
Wainwright	WHK3.3/18G-10EF/H.P.F	2	04/04/2018	Annual	04/04/2019
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	5001	06/07/2018	Annual	06/07/2019
Agilent	E3632A/DC Power Supply	KR75303243	05/09/2018	Annual	05/09/2019
Schwarzbeck	UHAP/ Dipole Antenna	557	03/31/2017	Biennial	03/31/2019
Schwarzbeck	UHAP/ Dipole Antenna	558	03/31/2017	Biennial	03/31/2019
ESPEC	SU-642 / Chamber	93000718	08/07/2018	Annual	08/07/2019
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	09/14/2018	Annual	09/14/2019
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	9120D-1298	10/04/2018	Annual	10/04/2019
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/25/2017	Biennial	04/25/2019
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	04/25/2017	Biennial	04/25/2019
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY52090906	06/08/2018	Annual	06/08/2019
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/21/2018	Annual	06/21/2019
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer(10Hz~40GHz)	100931	10/22/2018	Annual	10/22/2019
Agilent	8960 (E5515C)/ Base Station	MY48360800	09/27/2018	Annual	09/27/2019
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	08/23/2018	Biennial	08/23/2020
Schwarzbeck	VULB9160/ Bilog Antenna	9160-3368	08/09/2018	Biennial	08/09/2020
Schwarzbeck	VULB9160/Hybrid Antenna	760	04/06/2017	Biennial	04/06/2019
Anritsu Corp.	MT8821C/Wideband Radio Communication Tester	6201502997	08/13/2018	Annual	08/13/2019
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	01/30/2019	Annual	01/30/2020
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/19/2018	Annual	07/19/2019
REOHDE & SCHWARZ	ESU40 / EMI TEST RECEIVER	100524	07/27/2018	Annual	07/27/2019
HCT CO., LTD.,	FCC LTE Mobile Conducted RF Automation Test Software	-	-	-	-

**Note:**

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

## 5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	E
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.71

## 6. SUMMARY OF TEST RESULTS

### 6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§ 2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§ 2.1051, § 27.53(c)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§ 2.1046	N/A	<u>See Note1</u>
Frequency stability / variation of ambient temperature	§ 2.1055, § 27.54	Emission must remain in band	PASS

Note:

1. See SAR Report
2. The same samples were used for SAR and EMC

### 6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Effective Radiated Power	27.50(b)(10)	< 3 Watts max. ERP	PASS
Radiated Spurious and Harmonic Emissions	§ 2.1053, § 27.53(g)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS
Undesirable Emissions in the 1559 – 1610 MHz band	2.1053, 27.53(f)	< -70dBW/MHz EIRP (wideband) < -80dBW EIRP (narrowband)	PASS

**Note regarding all Emission Mask test plots:**

The FCC limit is  $65 + 10\log_{10}(P[\text{Watts}]) = -35$  dBm in a 6.25 kHz bandwidth. Since it was not possible to set the resolution bandwidth to 6.25 kHz with the available equipment, a bandwidth of 10 kHz was used instead to show compliance.

(Limit = -35.0 dBm)

## 7. SAMPLE CALCULATION

### 7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

### 7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

### 7.3. Emission Designator

#### GSM Emission Designator

**Emission Designator = 249KGXW**

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

#### EDGE Emission Designator

**Emission Designator = 249KG7W**

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

#### WCDMA Emission Designator

**Emission Designator = 4M17F9W**

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

#### QPSK Modulation

**Emission Designator = 4M48G7D**

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

#### 16QAM Modulation

**Emission Designator = 4M48W7D**

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

## 8. TEST DATA

## 8.1 EFFECTIVE RADIATED POWER

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP		
								W	W	dBm	
779.5	LTE B13 (5 MHz)	QPSK	-32.89	25.85	-10.32	0.83	H	< 3.00	0.030	14.70	
		16-QAM	-33.82	24.92	-10.32	0.83	H		0.024	13.77	
		64-QAM	-34.77	23.97	-10.32	0.83	H		0.019	12.82	
782.0		QPSK	-33.11	25.79	-10.33	0.83	H	< 3.00	0.029	14.63	
		16-QAM	-33.97	24.93	-10.33	0.83	H		0.024	13.77	
		64-QAM	-34.95	23.95	-10.33	0.83	H		0.019	12.79	
784.5		QPSK	-33.54	25.62	-10.34	0.83	H	< 3.00	0.028	14.46	
		16-QAM	-34.24	24.92	-10.34	0.83	H		0.024	13.76	
		64-QAM	-35.24	23.92	-10.34	0.83	H		0.019	12.76	

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
782.0	LTE B13 (10 MHz)	QPSK	-32.95	25.95	-10.33	0.83	H	< 3.00	0.030	14.79
		16-QAM	-33.85	25.05	-10.33	0.83	H		0.024	13.89
		64-QAM	-34.86	24.04	-10.33	0.83	H		0.019	12.88

**8.2 RADIATED SPURIOUS EMISSIONS**

OPERATING FREQUENCY: 779.50 MHz  
 MEASURED OUTPUT POWER: 14.70 dBm = 0.030 W  
 MODE: LTE B13  
 MODULATION SIGNAL: 5 MHz QPSK  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  27.70 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBd)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
23205 (779.5)	1,559.0	-55.57	6.73	-63.92	1.23	H	-60.57	75.27
	2,338.5	-53.74	7.87	-59.04	1.56	H	-54.88	69.58
	3,118.0	-56.18	9.21	-60.77	1.83	V	-55.54	70.24
23230 (782.0)	1,564.0	-52.57	6.76	-61.05	1.23	H	-57.68	72.38
	2,346.0	-54.58	7.92	-59.88	1.55	H	-55.66	70.36
	3,128.0	-57.52	9.21	-61.98	1.82	V	-56.74	71.44
23255 (784.5)	1,569.0	-51.82	6.78	-60.43	1.23	V	-57.03	71.73
	2,353.5	-56.32	7.97	-61.62	1.53	H	-57.33	72.03
	3,138.0	-56.31	9.20	-60.88	1.84	H	-55.67	70.37

OPERATING FREQUENCY: 782.00 MHz  
 MEASURED OUTPUT POWER: 14.79 dBm = 0.030 W  
 MODE: LTE B13  
 MODULATION SIGNAL: 10 MHz QPSK  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  27.79 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBd)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
23230 (782.0)	1,564.0	-55.55	6.76	-68.33	1.23	H	-60.66	75.44
	2,346.0	-54.44	7.92	-64.04	1.55	H	-55.52	70.31
	3,128.0	-57.65	9.21	-66.41	1.82	V	-56.87	71.66

## 1559 MHz ~ 1610 MHz BAND

OPERATING FREQUENCY: 779.5 MHz, 782.0 MHz, 784.5 MHz  
 MEASURED OUTPUT POWER: 5 MHz QPSK  
 DISTANCE: 3 meters  
 WIDEBAND EMISSION LIMIT: -70 dBW/ MHz (= -40 dBm/ MHz)

Operating Frequency (MHz)	Measured Frequency (MHz)	EMISSION TYPE	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Margin (dB)
779.5	1569.67	WIDEBAND	-55.56	6.78	-64.17	1.23	V	-60.77	20.77
782.0	1559.68		-51.75	6.73	-60.10	1.23	H	-56.75	16.75
784.5	1564.57		-50.43	6.76	-58.91	1.23	H	-55.54	15.54

OPERATING FREQUENCY: 782.0 MHz  
 MEASURED OUTPUT POWER: 10 MHz QPSK  
 DISTANCE: 3 meters  
 WIDEBAND EMISSION LIMIT: -70 dBW/ MHz (= -40 dBm/ MHz)

Operating Frequency (MHz)	Measured Frequency (MHz)	EMISSION TYPE	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Margin (dB)
782.0	1565.01	WIDEBAND	-55.52	6.76	-64.00	1.23	V	-60.63	20.63

**8.3 OCCUPIED BANDWIDTH**

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data ( MHz )	
13	5 MHz	782.0	QPSK	25	0	4.4941	
			16-QAM	25	0	4.5013	
			64-QAM	25	0	4.5046	
	10 MHz		QPSK	50	0	8.9793	
			16-QAM	50	0	8.9737	
			64-QAM	50	0	8.9775	

**Note:**

1. Plots of the EUT's Occupied Bandwidth are shown Page 34 ~ 39.

#### 8.4 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
13	5	779.5	3.7124	27.976	-67.214	-39.238	-13.00
		782.0	3.7084	27.976	-67.193	-39.217	
		784.5	3.7284	27.976	-67.349	-39.373	
	10	782.0	3.6910	27.976	-67.320	-39.344	

**Note:**

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 52 ~ 55.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131

#### 8.5 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 40 ~ 51.

**8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE**

MODE: LTE 13


OPERATING FREQUENCY: 779,500,000 Hz

CHANNEL: 23205 (5 MHz)

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	779 499 992	0.00	0.000 000	0.0000
100%		-30	779 499 988	-4.60	-0.000 001	-0.0059
100%		-20	779 499 997	4.80	0.000 001	0.0062
100%		-10	779 499 995	2.20	0.000 000	0.0028
100%		0	779 499 997	4.90	0.000 001	0.0063
100%		+10	779 499 995	2.20	0.000 000	0.0028
100%		+30	779 499 990	-2.30	0.000 000	-0.0030
100%		+40	779 499 999	7.00	0.000 001	0.0090
100%		+50	779 499 995	2.80	0.000 000	0.0036
Batt. Endpoint	3.400	+20	779 499 987	-5.30	-0.000 001	-0.0068



MODE: LTE 13


OPERATING FREQUENCY: 782,000,000 Hz

CHANNEL: 23230 (5 MHz)

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	781 999 998	0.00	0.000 000	0.0000
100%		-30	781 999 991	-6.70	-0.000 001	-0.0086
100%		-20	781 999 996	-1.80	0.000 000	-0.0023
100%		-10	781 999 991	-6.50	-0.000 001	-0.0083
100%		0	782 000 002	3.80	0.000 000	0.0049
100%		+10	782 000 001	3.50	0.000 000	0.0045
100%		+30	781 999 993	-4.70	-0.000 001	-0.0060
100%		+40	781 999 991	-6.60	-0.000 001	-0.0084
100%		+50	782 000 003	5.40	0.000 001	0.0069
Batt. Endpoint	3.400	+20	782 000 004	5.60	0.000 001	0.0072



MODE: LTE 13


OPERATING FREQUENCY: 784,500,000 Hz

CHANNEL: 23255 (5 MHz)

REFERENCE VOLTAGE: 3.85 VDC


DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	784 500 009	0.00	0.000 000	0.0000
100%		-30	784 500 018	9.40	0.000 001	0.0120
100%		-20	784 500 019	9.70	0.000 001	0.0124
100%		-10	784 500 017	8.20	0.000 001	0.0105
100%		0	784 500 014	5.00	0.000 001	0.0064
100%		+10	784 500 011	2.20	0.000 000	0.0028
100%		+30	784 500 017	7.70	0.000 001	0.0098
100%		+40	784 500 016	6.60	0.000 001	0.0084
100%		+50	784 500 013	4.40	0.000 001	0.0056
Batt. Endpoint	3.400	+20	784 500 014	4.50	0.000 001	0.0057




MODE: LTE 13  
 OPERATING FREQUENCY: 782,000,000 Hz  
 CHANNEL: 23230 (10 MHz)  
 REFERENCE VOLTAGE: 3.85 VDC  
 DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	781 999 993	0.00	0.000 000	0.0000
100%		-30	781 999 991	-2.50	0.000 000	-0.0032
100%		-20	781 999 988	-5.60	-0.000 001	-0.0072
100%		-10	781 999 982	-10.80	-0.000 001	-0.0138
100%		0	781 999 990	-3.50	0.000 000	-0.0045
100%		+10	781 999 985	-7.70	-0.000 001	-0.0098
100%		+30	781 999 989	-4.60	-0.000 001	-0.0059
100%		+40	781 999 989	-4.10	-0.000 001	-0.0052
100%		+50	781 999 988	-5.00	-0.000 001	-0.0064
Batt. Endpoint	3.400	+20	781 999 989	-3.80	0.000 000	-0.0049




## 9. TEST PLOTS


## BAND 13. Occupied Bandwidth Plot (Ch.23230 QPSK RB 25) 5 MHz




## BAND 13. Occupied Bandwidth Plot (Ch.23230 16-QAM RB 25) 5 MHz




## BAND 13. Occupied Bandwidth Plot (Ch.23230 64-QAM RB 25) 5 MHz




## BAND 13. Occupied Bandwidth Plot (Ch.23230 QPSK RB 50) 10 MHz




## BAND 13. Occupied Bandwidth Plot (Ch.23230 16-QAM RB 50) 10 MHz



## BAND 13. Occupied Bandwidth Plot (Ch.23230 64-QAM RB 50) 10 MHz



## Band 13 Lower Band Edge Plot (5M BW Ch.23205 QPSK\_RB1 OFFSET\_0)



## Band 13 Lower Band Edge Plot (5M BW Ch.23205 QPSK\_RB\_25)




## Band 13 Lower Emission Mask (763 MHz ~ 775 MHz) Plot (5M BW Ch.23205 QPSK\_RB25\_0)

**Note:**

The limit of plot is incorrect. (Limit = -35dBm)

The measured data did not exceed -35dBm, so there is no problem.


## Band 13 Lower Band Edge Plot (10M BW Ch.23230 QPSK\_RB1 OFFSET\_0)



## BAND 13. Lower &amp; Upper Band Edge Plot (10M BW Ch.23230 QPSK RB\_50)



## Band 13 Lower Emission Mask (763 MHz ~ 775 MHz) Plot (10M BW Ch.23230 QPSK\_RB50\_0)

**Note:**

The limit of plot is incorrect. (Limit = -35dBm)

The measured data did not exceed -35dBm, so there is no problem.

## Band 13 Upper Band Edge Plot (5M BW Ch.23255 QPSK\_RB1\_Offset 24)



## Band 13 Upper Band Edge Plot (5M BW Ch.23255 QPSK\_RB\_25)




## Band 13 Upper Emission Mask (793 MHz ~805 MHz) Plot (5M BW Ch.23255 QPSK\_RB25\_0)

**Note:**

The limit of plot is incorrect. (Limit = -35dBm)

The measured data did not exceed -35dBm, so there is no problem.

## Band 13 Upper Band Edge Plot (10M BW Ch.23230 QPSK\_RB1\_Offset\_49)



## Band 13 Upper Band Edge Plot (10M BW Ch.23230 QPSK\_ QPSK\_RB\_50)




## Band 13 Upper Emission Mask (793 MHz ~805 MHz) Plot (10M BW Ch.23230 QPSK\_RB50\_0)

**Note:**


The limit of plot is incorrect. (Limit = -35dBm)

The measured data did not exceed -35dBm, so there is no problem.


## BAND 13. Conducted Spurious Plot (23205ch\_5MHz\_QPSK\_RB 1\_0)




## BAND 13. Conducted Spurious Plot (23230ch\_5MHz\_QPSK\_RB 1\_0)



## BAND 13. Conducted Spurious Plot (23255ch\_5MHz\_QPSK\_RB 1\_0)



## BAND 13. Conducted Spurious Plot (Ch.23230 10 MHz QPSK RB 1, Offset 0)



## 10. APPENDIX A\_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-1906-FC016-P