

On your side



TEST REPORT

FCC LTE Test for SM-T725

Certification

APPLICANT

SAMSUNG Electronics Co., Ltd.

REPORT NO.

HCT-RF-1906-FC017

DATE OF ISSUE

10 June 2019

HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA

Tel. +82 31 634 6300 F ax. +82 31 645 6401



HCT Co., Ltd.
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401



REPORT NO.
HCT-RF-1906-FC017

DATE OF ISSUE
10 June 2019

Other ID
FCC: A3LSMT725U

Applicant	SAMSUNG Electronics Co., Ltd. 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
Eut Type	Tablet
Model Name	SM-T725
Additional Model(s)	SM-T725N, SM-T727
Date of Receipt	May 10, 2019
FCC Rule Part(s)	§27, §2
FCC Classification	PCS Licensed Transmitter (PCB)
Manufacturer	SAMSUNG Electronics Co., Ltd.

Tested by
Kwon Jeong

Technical Manager
Jong Seok Lee

HCT CO., LTD.
Soo Chan Lee
SooChan Lee / CEO

VISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	June 10, 2019	Initial Release

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

CONTENTS

1. GENERAL INFORMATION	5
1.1. MAXIMUM OUTPUT POWER	6
2. INTRODUCTION	7
2.1. DESCRIPTION OF EUT	7
2.2. MEASURING INSTRUMENT CALIBRATION	7
2.3. TEST FACILITY	7
3. DESCRIPTION OF TESTS	8
3.1 TEST PROCEDURE	8
3.2 RADIATED POWER	9
3.3 RADIATED SPURIOUS EMISSIONS	11
3.4 PEAK- TO- AVERAGE RATIO	12
3.5 OCCUPIED BANDWIDTH.	15
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	16
3.7 CHANNEL EDGE	17
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	19
3.9 WORST CASE(RADIATED TEST)	20
3.10 WORST CASE(CONDUCTED TEST)	21
4. LIST OF TEST EQUIPMENT	22
5. MEASUREMENT UNCERTAINTY	23
6. SUMMARY OF TEST RESULTS	24
7. SAMPLE CALCULATION	25
8. TEST DATA	27
8.1 EQUIVALENT ISOTROPIC RADIATED POWER	27
8.2 RADIATED SPURIOUS EMISSIONS	29
8.3 PEAK-TO-AVERAGE RATIO	33
8.4 OCCUPIED BANDWIDTH	34
8.5 CONDUCTED SPURIOUS EMISSIONS	35
8.6 CHANNEL EDGE	36
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	37
8.8 GEO-LOCATION MECHANISM	49
9. TEST PLOTS	58
10. ANNEX A_ TEST SETUP PHOTO	139

MEASUREMENT REPORT**1. GENERAL INFORMATION**

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMT725U
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter (PCB)
FCC Rule Part(s):	§ 27, § 2
EUT Type:	Tablet
Model(s):	SM-T725
Additional Model(s):	T725N, T727
Keyboard Information	Model : EH-FT720 Manufacture: SAMSUNG
Charging Doc Information	Model : EE-D3200 Manufacture: SAMSUNG
Tx Frequency:	2498.5 – 2687.5 : 5 MHz 2501.0 – 2685.0 : 10 MHz 2503.5 – 2682.5 : 15 MHz 2506.0 – 2680.0 : 20 MHz
Date(s) of Tests:	May 10, 2019 ~ June 05, 2019

1.1. MAXIMUM OUTPUT POWER

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band 41 (5)	2498.5 – 2687.5	4M51G7D	QPSK	0.282	24.50
		4M50W7D	16QAM	0.231	23.64
		4M51W7D	64QAM	0.187	22.71
LTE – Band 41 (10)	2501.0 – 2685.0	8M95G7D	QPSK	0.279	24.46
		8M96W7D	16QAM	0.230	23.61
		8M99W7D	64QAM	0.185	22.66
LTE – Band 41 (15)	2503.5 – 2682.5	13M4G7D	QPSK	0.244	23.88
		13M5W7D	16QAM	0.200	23.02
		13M4W7D	64QAM	0.160	22.04
LTE – Band 41 (20)	2506.0 – 2680.0	18M0G7D	QPSK	0.263	24.20
		17M9W7D	16QAM	0.217	23.36
		17M9W7D	64QAM	0.172	22.35

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Tablet with GSM/GPRS/EGPRS/UMTS and LTE.

It also supports IEEE 802.11 a/b/g/n/ac (HT20/40/80), ANT+, Bluetooth, BT LE.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Channel Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4 - ANSI C63.26-2015 – Section 5.2.6(only GSM)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $>$ 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d(\text{dBm}) = P_g(\text{dBm}) - \text{cable loss } (\text{dB}) + \text{antenna gain } (\text{dB})$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.


Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW \geq 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $>$ 2 x span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin $>$ 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - .- for continuous transmissions, set to 1 ms,
 - .- or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1%.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R_{(dB)} = P_{Pk\ (dBm)} - P_{Avg\ (dBm)} \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)

The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.

1. Set the RBW \geq OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times$ (number of points in sweep) \times (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to 2 \times to 3 \times the OBW.
2. Set RBW \geq OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:

Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep

(automation-compatible) measurement. The transmission period is the (on + off) time.


6. Detector = power averaging (rms).
7. Set sweep trigger to “free run.”
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually

configured sweep time, increase the sweep time.)

9. Use the peak marker function to determine the maximum amplitude level.

10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6 \text{ dB}$ if the duty cycle is a constant 25%.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. $RBW = 1 - 5\%$ of the expected OBW
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW \geq 3 MHz
3. Detector = Peak
4. Trace Mode = max hold
5. Sweep time = auto
6. Number of points in sweep $\geq 2 * \text{Span} / \text{RBW}$

3.7 CHANNEL EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the channel edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 2% of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span}/\text{RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes


1. The attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz

channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz.

2. All measurements were done at 3 channels.

3. The channel edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

2. Primary Supply Voltage:

- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value

for other than hand carried battery equipment.

- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the

battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).

2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.

3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
- The worst case is reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data.
- Please refer to the table below.
- All modes of operation were investigated and the worst case configuration results are reported.
- SM-T725 & additional models were tested and the worst case results are reported.

(Worst case : SM-T725)

- SM-T725 with Stand alone&Keyboard&Charging pad were tested and the worst case results are reported.

(Worst case : Stand alone)

[Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM	1	0	Z
Radiated Spurious and Harmonic Emissions	QPSK	1	0	Z

3.10 WORST CASE(CONDUCTED TEST)

- Worst case : Of all modulation, We have tested modulation of the high Conducted Output Power.

Conducted Output Power value can be confirmed on the SAR report.

- SM-T725 & additional models were tested and the worst case results are reported.

(Worst case : SM-T725)

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM	5, 10, 15, 20	Mid	Full RB	0
Peak-To-Average Radio	QPSK, 16QAM, 64QAM	5, 10, 15, 20	Mid	Full RB	0
Channel Edge	QPSK	5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		15	Low	1	0
			High	1	74
		20	Low	1	0
			High	1	99
		5, 10, 15, 20	Low, Mid, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	QPSK	5, 10, 15, 20	Low, Mid, High	1	0

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibration Interval	Calibration Due
REOHDE & SCHWARZ	SCU 18 / AMPLIFIER	10094	04/16/2019	Annual	04/16/2020
Wainwright	WHK1.2/15G-10EF/H.P.F	4	04/02/2019	Annual	04/02/2020
Wainwright	WHK3.3/18G-10EF/H.P.F	2	04/02/2019	Annual	04/02/2020
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	11275	05/03/2019	Annual	05/03/2020
Agilent	E3632A/DC Power Supply	MY40004326	07/05/2018	Annual	07/05/2019
Schwarzbeck	UHAP/ Dipole Antenna	557	03/29/2019	Biennial	03/29/2021
Schwarzbeck	UHAP/ Dipole Antenna	558	03/29/2019	Biennial	03/29/2021
ESPEC	SU-642 / Chamber	93000718	08/07/2018	Annual	08/07/2019
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	09/14/2018	Annual	09/14/2019
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	9120D-1298	10/04/2018	Annual	10/04/2019
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/29/2019	Biennial	04/29/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	01/28/2019	Biennial	01/28/2021
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY51110063	05/08/2019	Annual	05/08/2020
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/21/2018	Annual	06/21/2019
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer(10Hz~40GHz)	100931	10/22/2018	Annual	10/22/2019
Agilent	8960 (E5515C)/ Base Station	MY48360800	09/27/2018	Annual	09/27/2019
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	08/23/2018	Biennial	08/23/2020
Schwarzbeck	VULB9160/ Bilog Antenna	9160-3368	08/09/2018	Biennial	08/09/2020
Schwarzbeck	VULB9160/ Hybrid Antenna	760	03/22/2019	Biennial	03/22/2021
Anritsu Corp.	MT8821C/Wideband Radio Communication Tester	6201502997	08/13/2018	Annual	08/13/2019
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	01/30/2019	Annual	01/30/2020
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/19/2018	Annual	07/19/2019
REOHDE & SCHWARZ	ESU40 / EMI TEST RECEIVER	100524	07/27/2018	Annual	07/27/2019
HCT CO., LTD.,	FCC LTE Mobile Conducted RF Automation Test Software	-	-	-	-

Note:

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	E
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.71

6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§ 2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§ 2.1051, § 27.53(m)(4)	<ul style="list-style-type: none">■ $< 40 + 10\log_{10} (P[\text{Watts}])$ at Channel edges■ $< 43 + 10\log_{10} (P[\text{Watts}])$ between 5 and X MHz from Channel edges■ $< 55 + 10\log_{10} (P[\text{Watts}])$ beyond X MHz beyond from Channel edges■ $< 43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz	PASS
Conducted Output Power	§ 2.1046	N/A	<u>See Note1</u>
Frequency stability / variation of ambient temperature	§ 2.1055, § 27.54	Emission must remain in band	PASS

Note:

1. See SAR Report
2. The same samples were used for SAR and EMC

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§ 27.50(h)(2)	< 2 Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§ 2.1053, § 27.53(m)(4)	$< 55 + 10\log_{10} (P[\text{Watts}])$	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
40620	2593.0	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

16QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

64QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP			
									W	W	dBm	
2498.5	LTE B41/ 5 MHz	QPSK	-20.86	13.78	10.98	1.60	H	< 2.00	0.207	23.16		
		16-QAM	-21.81	12.83	10.98	1.60	H		0.166	22.21		
		64-QAM	-22.78	11.86	10.98	1.60	H		0.133	21.24		
2593.0		QPSK	-21.28	13.47	11.06	1.63	H		0.195	22.90		
		16-QAM	-22.20	12.55	11.06	1.63	H		0.158	21.98		
		64-QAM	-23.22	11.53	11.06	1.63	H		0.125	20.96		
2687.5		QPSK	-20.28	15.00	11.15	1.65	H		0.282	24.50		
		16-QAM	-21.14	14.14	11.15	1.65	H		0.231	23.64		
		64-QAM	-22.07	13.21	11.15	1.65	H		0.187	22.71		

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP			
									W	W	dBm	
2501.0	LTE B41/ 10 MHz	QPSK	-20.85	13.79	10.98	1.60	H	< 2.00	0.208	23.17		
		16-QAM	-21.80	12.84	10.98	1.60	H		0.167	22.22		
		64-QAM	-22.76	11.88	10.98	1.60	H		0.134	21.26		
2593.0		QPSK	-21.37	13.38	11.06	1.63	H		0.191	22.81		
		16-QAM	-22.21	12.54	11.06	1.63	H		0.157	21.97		
		64-QAM	-23.24	11.51	11.06	1.63	H		0.124	20.94		
2685.0		QPSK	-20.20	14.96	11.15	1.65	H		0.279	24.46		
		16-QAM	-21.05	14.11	11.15	1.65	H		0.230	23.61		
		64-QAM	-22.00	13.16	11.15	1.65	H		0.185	22.66		

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP		
									W	W	dBm
2503.5	LTE B41/ 15 MHz	QPSK	-20.84	13.73	10.98	1.61	H	< 2.00	0.204	23.10	
		16-QAM	-21.78	12.79	10.98	1.61	H		0.164	22.16	
		64-QAM	-22.75	11.82	10.98	1.61	H		0.131	21.19	
2593.0		QPSK	-21.18	13.57	11.06	1.63	H		0.200	23.00	
		16-QAM	-22.09	12.66	11.06	1.63	H		0.162	22.09	
		64-QAM	-23.10	11.65	11.06	1.63	H		0.128	21.08	
2682.5		QPSK	-20.66	14.37	11.15	1.64	H		0.244	23.88	
		16-QAM	-21.52	13.51	11.15	1.64	H		0.200	23.02	
		64-QAM	-22.50	12.53	11.15	1.64	H		0.160	22.04	

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP		
									W	W	dBm
2506.0	LTE B41/ 20 MHz	QPSK	-20.89	13.68	10.98	1.61	H	< 2.00	0.202	23.05	
		16-QAM	-21.79	12.78	10.98	1.61	H		0.164	22.15	
		64-QAM	-22.77	11.80	10.98	1.61	H		0.131	21.17	
2593.0		QPSK	-21.70	13.05	11.06	1.63	H		0.177	22.48	
		16-QAM	-22.57	12.18	11.06	1.63	H		0.145	21.61	
		64-QAM	-23.56	11.19	11.06	1.63	H		0.115	20.62	
2680.0		QPSK	-20.34	14.69	11.15	1.64	H		0.263	24.20	
		16-QAM	-21.18	13.85	11.15	1.64	H		0.217	23.36	
		64-QAM	-22.19	12.84	11.15	1.64	H		0.172	22.35	

8.2 RADIATED SPURIOUS EMISSIONS

OPERATING FREQUENCY : 2687.50 MHz
 MEASURED OUTPUT POWER: 24.50 dBm = 0.282 W
 MODE: LTE B41
 MODULATION SIGNAL: 5 MHz QPSK
 DISTANCE: 1 meters
 LIMIT: $55 + 10 \log_{10} (W) =$ 48.50 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39675 (2498.5)	4,997.00	-47.58	12.89	-61.27	2.47	V	-50.85	75.36
	7,495.50	-37.27	11.51	-44.01	2.97	V	-35.47	59.97
	9,994.00	-45.82	11.21	-48.27	3.48	H	-40.54	65.05
40620 (2593.0)	5,186.00	-47.38	13.05	-59.98	2.58	H	-49.51	74.01
	7,779.00	-41.47	11.98	-48.99	2.93	V	-39.94	64.45
	10,372.00	-45.69	10.96	-48.68	3.62	H	-41.34	65.84
41565 (2687.5)	5,375.00	-41.87	13.49	-55.15	2.65	V	-44.31	68.82
	8,062.50	-41.41	11.46	-46.23	3.05	H	-37.82	62.32
	10,750.00	-47.31	10.99	-50.21	3.67	H	-42.89	67.39

OPERATING FREQUENCY: 2685.00 MHz
 MEASURED OUTPUT POWER: 24.46 dBm = 0.279 W
 MODE: LTE B41
 MODULATION SIGNAL: 10 MHz QPSK
 DISTANCE: 1 meters
 LIMIT: $55 + 10 \log_{10} (W) =$ 49.46 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39700 (2501.0)	5,002.00	-47.38	12.89	-61.07	2.47	H	-50.65	75.12
	7,503.00	-38.12	11.53	-44.55	2.92	H	-35.95	60.41
	10,004.00	-47.92	11.25	-50.76	3.41	V	-42.92	67.38
40620 (2593.0)	5,186.00	-46.82	13.05	-59.42	2.58	H	-48.95	73.41
	7,779.00	-40.71	11.98	-48.23	2.93	H	-39.18	63.64
	10,372.00	-47.47	10.96	-50.46	3.62	H	-43.12	67.58
41540 (2685.0)	5,370.00	-41.94	13.50	-55.52	2.65	H	-44.67	69.13
	8,055.00	-41.35	11.46	-46.24	3.05	H	-37.84	62.30
	10,740.00	-47.11	10.98	-49.92	3.62	H	-42.56	67.02

OPERATING FREQUENCY: 2682.50 MHz
 MEASURED OUTPUT POWER: 23.88 dBm = 0.244 W
 MODE: LTE B41
 MODULATION SIGNAL: 15 MHz QPSK
 DISTANCE: 1 meters
 LIMIT: $55 + 10 \log_{10} (W) =$ 48.88 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39725 (2503.5)	5,007.00	-49.74	12.86	-63.87	2.49	H	-53.50	77.38
	7,510.50	-37.81	11.54	-43.95	2.90	V	-35.31	59.19
	10,014.00	-47.69	11.27	-50.85	3.40	V	-42.99	66.86
	12,517.50	-53.24	14.23	-57.55	4.05	V	-47.37	71.25
40620 (2593.0)	5,186.00	-46.73	13.05	-59.33	2.58	H	-48.86	72.74
	7,779.00	-39.87	11.98	-47.39	2.93	V	-38.34	62.22
	10,372.00	-47.80	10.96	-50.79	3.62	H	-43.45	67.33
41515 (2682.5)	5,365.00	-42.57	13.51	-56.22	2.64	H	-45.35	69.23
	8,047.50	-43.03	11.45	-48.00	3.05	H	-39.60	63.48
	10,730.00	-48.65	10.98	-51.46	3.60	H	-44.08	67.96

OPERATING FREQUENCY: 2680.00 MHz
 MEASURED OUTPUT POWER: 24.20 dBm = 0.263 W
 MODE: LTE B41
 MODULATION SIGNAL: 20 MHz QPSK
 DISTANCE: 1 meters
 LIMIT: $55 + 10 \log_{10} (W) =$ 49.20 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
39750 (2506.0)	5,012.00	-49.92	12.86	-64.05	2.49	H	-53.68	77.88
	7,518.00	-38.25	11.57	-43.56	2.93	H	-34.92	59.12
	10,024.00	-48.48	11.29	-51.31	3.48	H	-43.49	67.69
40620 (2593.0)	5,186.00	-48.30	13.05	-60.90	2.58	H	-50.43	74.63
	7,779.00	-38.40	11.98	-45.92	2.93	H	-36.87	61.07
	10,372.00	-47.69	10.96	-50.68	3.62	V	-43.34	67.54
41490 (2680.0)	5,360.00	-43.58	13.51	-57.30	2.63	H	-46.42	70.62
	8,040.00	-42.51	11.46	-47.41	3.06	H	-39.01	63.20
	10,720.00	-49.16	10.97	-51.79	3.66	V	-44.48	68.68

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)		
41	5 MHz	2593.0	QPSK	25	0	4.90		
			16-QAM			6.05		
			64-QAM			6.53		
	10 MHz		QPSK	50		4.97		
			16-QAM			6.08		
			64-QAM			6.58		
	15 MHz		QPSK	75		4.83		
			16-QAM			6.03		
			64-QAM			6.59		
	20 MHz		QPSK	100		4.85		
			16-QAM			5.97		
			64-QAM			6.55		

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 73 ~ 84.

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)		
41	5 MHz	2593.0	QPSK	25	0	4.5068		
			16-QAM			4.4947		
			64-QAM			4.5110		
	10 MHz		QPSK	50		8.9475		
			16-QAM			8.9631		
			64-QAM			8.9886		
	15 MHz		QPSK	75		13.418		
			16-QAM			13.453		
			64-QAM			13.414		
	20 MHz		QPSK	100		17.956		
			16-QAM			17.874		
			64-QAM			17.895		

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 61 ~ 72.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
41	5	2498.5	26.2352	30.131	-66.733	-36.602	-25.00
		2593.0	25.9130	30.131	-66.093	-35.962	
		2687.5	25.8173	27.976	-66.476	-38.500	
	10	2501.0	25.8359	30.131	-66.125	-35.994	
		2593.0	25.9637	30.131	-66.914	-36.783	
		2685.0	26.1184	30.131	-66.641	-36.510	
	15	2503.5	25.1643	30.131	-66.919	-36.788	
		2593.0	26.1551	30.131	-66.499	-36.368	
		2682.5	5.3789	28.591	-66.731	-38.140	
	20	2506.0	26.3696	30.131	-66.489	-36.358	
		2593.0	26.4794	30.131	-66.921	-36.790	
		2680.0	3.6935	27.976	-66.548	-38.572	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 113 ~ 140.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131

8.6 CHANNEL EDGE

Band Width	Frequency (MHz)	Modulation	RB (Size/Offset)	2 495 MHz ~ 2 496 MHz	C.E ~ (C.E +1MHz)	2 490.5 MHz ~ 2 495 MHz	(C.E + 1 MHz) ~ (C.E + 5 MHz)	Below 2 490.5 MHz	(C.E + 5 MHz) ~ (C.E + X MHz)	Above (C.E + X MHz)
				Lower	Upper	Lower	Upper	Lower	Upper	Upper
5 MHz	2498.5	QPSK	25/0	-25.37	-25.07	-26.27	-24.65	-36.47	-35.58	-35.84
10 MHz	2501.0	QPSK	50/0	-25.42	-25.90	-28.62	-25.64	-31.59	-30.08	-38.97
15 MHz	2503.5	QPSK	75/0	-27.05	-26.00	-30.15	-27.08	-32.82	-29.43	-41.16
20 MHz	2506.0	QPSK	100/0	-27.13	-25.54	-30.25	-28.03	-33.02	-29.39	-42.50
Limit				-13.0	-10.0	-13.0	-10.0	-25.0	-13.0	-25.0

Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	C.E ~ (C.E ± 1MHz)		(C.E ± 1 MHz) ~ (C.E ± 5 MHz)	
					Lower	Upper	Lower	Upper
5 MHz	2593.0	QPSK	25	0	-26.45	-26.39	-31.46	-34.11
	2687.5	QPSK	25	0	-27.02	-26.52	-24.25	-25.13
10 MHz	2593.0	QPSK	50	0	-28.36	-28.18	-30.40	-33.70
	2685.0	QPSK	50	0	-29.22	-29.34	-24.74	-26.08
15 MHz	2593.0	QPSK	75	0	-28.22	-28.87	-32.18	-34.73
	2682.5	QPSK	75	0	-26.01	-25.89	-22.25	-22.28
20 MHz	2593.0	QPSK	100	0	-28.11	-28.62	-30.67	-33.62
	2680.0	QPSK	100	0	-25.38	-25.93	-21.74	-22.53
Limit				-10.0		-10.0		

Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	(C.E ± 5 MHz) ~ (C.E ± X MHz)		Above (C.E ± X MHz)	
					Lower	Upper	Lower	Upper
5 MHz	2593.0	QPSK	25	0	-39.77	-40.21	-40.42	-40.88
	2687.5	QPSK	25	0	-41.21	-39.80	-42.94	-42.40
10 MHz	2593.0	QPSK	50	0	-36.55	-35.81	-41.37	-41.15
	2685.0	QPSK	50	0	-30.09	-30.97	-45.18	-42.46
15 MHz	2593.0	QPSK	75	0	-33.95	-34.92	-41.28	-40.83
	2682.5	QPSK	75	0	-25.19	-25.24	-45.34	-43.70
20 MHz	2593.0	QPSK	100	0	-33.47	-34.96	-42.58	-41.73
	2680.0	QPSK	100	0	-24.87	-24.77	-44.65	-46.47
Limit				-13.0		-25.0		


Note:

1. C.E = Channel Edge
2. X = X is the greater of 6MHz or the actual emission bandwidth.
3. X = 6MHz(5MHz Bandwidth), 10MHz(10MHz Bandwidth), 15MHz(15MHz Bandwidth), 20MHz(20MHz Bandwidth)
4. Plots of the EUT's Channel Edge are shown Page 85 ~ 112. (1RB & Full RB)

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

MODE: LTE 41
 OPERATING FREQUENCY: 2498,500,000 Hz
 BANDWIDTH: 39675 (5 MHz)
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2498 500 006	0.0	0.000 000	0.000
100%		-30	2498 500 011	5.4	0.000 000	0.002
100%		-20	2498 500 016	10.0	0.000 000	0.004
100%		-10	2498 500 002	-3.6	0.000 000	-0.001
100%		0	2498 500 022	16.0	0.000 001	0.006
100%		+10	2498 500 018	12.5	0.000 001	0.005
100%		+30	2498 500 023	16.7	0.000 001	0.007
100%		+40	2498 500 015	9.3	0.000 000	0.004
100%		+50	2498 500 016	10.0	0.000 000	0.004
85%	3.400	+20	2498 500 010	3.9	0.000 000	0.002



MODE: LTE 41


OPERATING FREQUENCY: 2501,000,000 Hz

BANDWIDTH: 39700 (10 MHz)

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2500 999 991	0.0	0.000 000	0.000
100%		-30	2500 999 977	-14.0	-0.000 001	-0.006
100%		-20	2500 999 975	-15.9	-0.000 001	-0.006
100%		-10	2500 999 968	-23.0	-0.000 001	-0.009
100%		0	2500 999 978	-12.1	0.000 000	-0.005
100%		+10	2500 999 981	-9.5	0.000 000	-0.004
100%		+30	2500 999 978	-12.5	0.000 000	-0.005
100%		+40	2500 999 987	-3.8	0.000 000	-0.002
100%		+50	2500 999 976	-14.7	-0.000 001	-0.006
85%	3.400	+20	2500 999 974	-16.2	-0.000 001	-0.006



MODE: LTE 41


OPERATING FREQUENCY: 2503,500,000 Hz

BANDWIDTH: 39725 (15 MHz)

REFERENCE VOLTAGE: 3.85 VDC


DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2503 499 995	0.0	0.000 000	0.000
100%		-30	2503 500 003	8.2	0.000 000	0.003
100%		-20	2503 500 001	6.4	0.000 000	0.003
100%		-10	2503 499 982	-12.9	-0.000 001	-0.005
100%		0	2503 499 986	-8.9	0.000 000	-0.004
100%		+10	2503 499 987	-7.4	0.000 000	-0.003
100%		+30	2503 499 993	-2.0	0.000 000	-0.001
100%		+40	2503 499 998	3.7	0.000 000	0.001
100%		+50	2503 499 999	4.0	0.000 000	0.002
85%	3.400	+20	2503 499 997	2.2	0.000 000	0.001



MODE: LTE 41
 OPERATING FREQUENCY: 2506,000,000 Hz
 BANDWIDTH: 39750 (20 MHz)
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2506 000 012	0.0	0.000 000	0.000
100%		-30	2506 000 022	10.4	0.000 000	0.004
100%		-20	2506 000 023	11.6	0.000 000	0.005
100%		-10	2506 000 010	-2.3	0.000 000	-0.001
100%		0	2506 000 022	10.0	0.000 000	0.004
100%		+10	2506 000 009	-3.3	0.000 000	-0.001
100%		+30	2506 000 006	-6.0	0.000 000	-0.002
100%		+40	2506 000 025	12.9	0.000 001	0.005
100%		+50	2506 000 023	11.0	0.000 000	0.004
85%	3.400	+20	2506 000 020	8.2	0.000 000	0.003



MODE: LTE 41


OPERATING FREQUENCY: 2593,000,000 Hz

BANDWIDTH: 40620 (5 MHz)

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2593 000 019	0.0	0.000 000	0.000
100%		-30	2593 000 027	8.7	0.000 000	0.003
100%		-20	2593 000 035	16.9	0.000 001	0.007
100%		-10	2593 000 031	12.0	0.000 000	0.005
100%		0	2593 000 027	8.7	0.000 000	0.003
100%		+10	2593 000 037	18.9	0.000 001	0.007
100%		+30	2593 000 026	7.9	0.000 000	0.003
100%		+40	2593 000 027	8.5	0.000 000	0.003
100%		+50	2593 000 008	-10.9	0.000 000	-0.004
85%	3.400	+20	2593 000 024	5.0	0.000 000	0.002



MODE: LTE 41


OPERATING FREQUENCY: 2593,000,000 Hz

BANDWIDTH: 40620 (10 MHz)

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2593 000 008	0.0	0.000 000	0.000
100%		-30	2593 000 015	6.9	0.000 000	0.003
100%		-20	2593 000 011	3.1	0.000 000	0.001
100%		-10	2593 000 013	5.0	0.000 000	0.002
100%		0	2593 000 017	9.1	0.000 000	0.004
100%		+10	2593 000 024	16.1	0.000 001	0.006
100%		+30	2593 000 012	4.5	0.000 000	0.002
100%		+40	2593 000 013	5.3	0.000 000	0.002
100%		+50	2593 000 019	11.2	0.000 000	0.004
85%	3.400	+20	2593 000 022	14.5	0.000 001	0.006



MODE: LTE 41


OPERATING FREQUENCY: 2593,000,000 Hz

BANDWIDTH: 40620 (15 MHz)

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2593 000 013	0.0	0.000 000	0.000
100%		-30	2593 000 027	13.8	0.000 001	0.005
100%		-20	2593 000 022	9.7	0.000 000	0.004
100%		-10	2593 000 010	-2.7	0.000 000	-0.001
100%		0	2593 000 023	10.1	0.000 000	0.004
100%		+10	2593 000 019	6.3	0.000 000	0.002
100%		+30	2593 000 018	5.4	0.000 000	0.002
100%		+40	2593 000 020	7.5	0.000 000	0.003
100%		+50	2593 000 028	14.9	0.000 001	0.006
85%	3.400	+20	2593 000 010	-2.6	0.000 000	-0.001



MODE: LTE 41


OPERATING FREQUENCY: 2593,000,000 Hz

BANDWIDTH: 40620 (20 MHz)

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2593 000 003	0.0	0.000 000	0.000
100%		-30	2593 000 009	5.4	0.000 000	0.002
100%		-20	2593 000 020	17.1	0.000 001	0.007
100%		-10	2593 000 021	17.9	0.000 001	0.007
100%		0	2593 000 008	4.5	0.000 000	0.002
100%		+10	2593 000 008	4.8	0.000 000	0.002
100%		+30	2593 000 011	7.7	0.000 000	0.003
100%		+40	2593 000 016	12.7	0.000 000	0.005
100%		+50	2593 000 009	5.3	0.000 000	0.002
85%	3.400	+20	2593 000 011	8.0	0.000 000	0.003



MODE: LTE 41


OPERATING FREQUENCY: 2687,500,000 Hz

BANDWIDTH: 41565 (5 MHz)

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2687 499 998	0.0	0.000 000	0.000
100%		-30	2687 500 000	2.4	0.000 000	0.001
100%		-20	2687 499 984	-14.2	-0.000 001	-0.005
100%		-10	2687 499 993	-4.9	0.000 000	-0.002
100%		0	2687 500 005	6.8	0.000 000	0.003
100%		+10	2687 500 005	7.4	0.000 000	0.003
100%		+30	2687 499 986	-11.9	0.000 000	-0.004
100%		+40	2687 499 997	-1.2	0.000 000	0.000
100%		+50	2687 499 987	-11.4	0.000 000	-0.004
85%	3.400	+20	2687 499 983	-14.8	-0.000 001	-0.006



MODE: LTE 41


OPERATING FREQUENCY: 2685,000,000 Hz

BANDWIDTH: 41540 (10 MHz)

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2685 000 005	0.0	0.000 000	0.000
100%		-30	2685 000 001	-4.1	0.000 000	-0.002
100%		-20	2684 999 995	-10.3	0.000 000	-0.004
100%		-10	2684 999 990	-14.8	-0.000 001	-0.006
100%		0	2684 999 984	-21.5	-0.000 001	-0.008
100%		+10	2684 999 997	-8.0	0.000 000	-0.003
100%		+30	2684 999 996	-9.3	0.000 000	-0.003
100%		+40	2685 000 002	-3.1	0.000 000	-0.001
100%		+50	2685 000 011	6.0	0.000 000	0.002
85%	3.400	+20	2685 000 013	8.1	0.000 000	0.003



MODE: LTE 41


OPERATING FREQUENCY: 2682,500,000 Hz

BANDWIDTH: 41515 (15 MHz)

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2682 499 986	0.0	0.000 000	0.000
100%		-30	2682 499 974	-12.0	0.000 000	-0.004
100%		-20	2682 499 978	-8.7	0.000 000	-0.003
100%		-10	2682 499 989	2.8	0.000 000	0.001
100%		0	2682 499 971	-15.4	-0.000 001	-0.006
100%		+10	2682 499 968	-18.5	-0.000 001	-0.007
100%		+30	2682 499 970	-16.7	-0.000 001	-0.006
100%		+40	2682 499 972	-14.7	-0.000 001	-0.005
100%		+50	2682 499 976	-10.0	0.000 000	-0.004
85%	3.400	+20	2682 499 977	-9.2	0.000 000	-0.003



MODE: LTE 41


OPERATING FREQUENCY: 2680,000,000 Hz

BANDWIDTH: 41490 (20 MHz)

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	2680 000 009	0.0	0.000 000	0.000
100%		-30	2680 000 019	10.0	0.000 000	0.004
100%		-20	2680 000 008	-1.7	0.000 000	-0.001
100%		-10	2680 000 020	10.6	0.000 000	0.004
100%		0	2680 000 015	5.9	0.000 000	0.002
100%		+10	2680 000 021	11.9	0.000 000	0.004
100%		+30	2680 000 013	3.5	0.000 000	0.001
100%		+40	2680 000 013	3.2	0.000 000	0.001
100%		+50	2680 000 016	6.3	0.000 000	0.002
85%	3.400	+20	2680 000 023	13.4	0.000 000	0.005




8.8 GEO-LOCATION MECHANISM


The device uses a geo-location mechanism based on the cellular MCC codes in order to only enable certain LTE bands when the device is not in the USA.


The validation of this mechanism is provided below. The device was configured for cellular communications to a test set and the MCC code was adjusted on the test set between the US MCC and then an MCC code valid for a country where the LTE band is supported.


Band	MCC = USA	MCC = non US
7	Did not connect	Connected (Canada)
38	Did not connect	Connected (Canada)
40	Did not connect	Connected (Canada)
41	Connected	Connected (Canada)


The verification tests confirmed the operational of the geo-location mechanism.


Verification test



















9. TEST PLOTS


BAND 41. Occupied Bandwidth Plot (5 MHz Ch.40620 QPSK RB 25)




BAND 41. Occupied Bandwidth Plot (5 MHz Ch.40620 16-QAM RB 25)




BAND 41. Occupied Bandwidth Plot (5 MHz Ch.40620 64-QAM RB 25)




BAND 41. Occupied Bandwidth Plot (10 MHz Ch.40620 QPSK RB 50)




BAND 41. Occupied Bandwidth Plot (10 MHz Ch.40620 16-QAM RB 50)




BAND 41. Occupied Bandwidth Plot (10 MHz Ch.40620 64-QAM RB 50)




BAND 41. Occupied Bandwidth Plot (15 MHz Ch.40620 QPSK RB 75)




BAND 41. Occupied Bandwidth Plot (15 MHz Ch.40620 16-QAM RB 75)




BAND 41. Occupied Bandwidth Plot (15 MHz Ch.40620 64-QAM RB 75)




BAND 41. Occupied Bandwidth Plot (20 MHz Ch.40620 QPSK RB 100)




BAND 41. Occupied Bandwidth Plot (20 MHz Ch.40620 16-QAM RB 100)




BAND 41. Occupied Bandwidth Plot (20 MHz Ch.40620 64-QAM RB 100)




BAND 41. PAR Plot (5M BW_Ch.40620_QPSK_RB25_0)




BAND 41. PAR Plot (5M BW_Ch.40620_16QAM_RB25_0)




BAND 41. PAR Plot (5M BW_Ch.40620_64QAM_RB25_0)




BAND 41. PAR Plot (10M BW_Ch.40620_QPSK_RB50_0)




BAND 41. PAR Plot (10M BW_Ch.40620_16QAM_RB50_0)



BAND 41. PAR Plot (10M BW_Ch.40620_64QAM_RB50_0)



BAND 41. PAR Plot (15M BW_Ch.40620_QPSK_RB75_0)



BAND 41. PAR Plot (15M BW_Ch.40620_16QAM_RB75_0)

