

TEST REPORT

FCC DTS Test for SM-T727V
Certification

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-1905-FC037-R4

DATE OF ISSUE
June 19, 2019

HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 F ax. +82 31 645 6401

**HCT Co., Ltd.**

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

TEST REPORT

FCC DTS Test for
SM-T727V

REPORT NO.

HCT-RF-1905-FC037-R4

DATE OF ISSUE

June 19, 2019

Other ID

-

Applicant

SAMSUNG Electronics Co., Ltd.

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

**Eut Type
Model Name**

Tablet
SM-T727V

FCC ID

A3LSMT727V

Average Output Power

802.11b : 18.15 dBm / 802.11g : 18.69 dBm / 802.11n(HT20) : 19.24 dBm

Modulation type

CCK/DSSS/OFDM

FCC Classification

Digital Transmission System(DTS)

FCC Rule Part(s)

Part 15.247

Tested by
Jae Ryang Do

(signature)

Technical Manager
Jong Seok Lee

(signature)

HCT CO., LTD.

Soo Chan Lee
SooChan Lee / CEO

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	June 05, 2019	Initial Release
1	June 13, 2019	Revised the PSD procedure (page 12) Revised the PSD result (Edit typo, page 37). Edit typo (page 17) Added the Worst case configuration (page 24.) Added the AP Information (page 71)
2	June 17, 2019	The procedure for 30 MHz under has been revised. (page 17, 24) Revised the Confirmation of Geo-Location Mechanism.
3	June 18, 2019	Revised the Confirmation of Geo-Location Mechanism.
4	June 19, 2019	Added the note for emission result(page 17, 18) Revised the Confirmation of Geo-Location Mechanism(airplane mode)

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

CONTENTS

1. EUT DESCRIPTION.....	5
2. TEST METHODOLOGY	6
EUT CONFIGURATION.....	6
EUT EXERCISE	6
GENERAL TEST PROCEDURES	6
DESCRIPTION OF TEST MODES.....	7
3. INSTRUMENT CALIBRATION	7
4. FACILITIES AND ACCREDITATIONS.....	7
FACILITIES.....	7
EQUIPMENT	7
5. ANTENNA REQUIREMENTS	8
6. MEASUREMENT UNCERTAINTY	8
7. DESCRIPTION OF TESTS	9
8. SUMMARY TEST OF RESULTS	25
9. TEST RESULT	26
9.1 DUTY CYCLE	26
9.2 6dB BANDWIDTH	29
9.3 OUTPUT POWER	32
9.4 POWER SPECTRAL DENSITY	38
9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS.....	41
9.6 RADIATED SPURIOUS EMISSIONS.....	52
9.7 RADIATED RESTRICTED BAND EDGES.....	60
9.8 POWERLINE CONDUCTED EMISSIONS.....	64
9.9 CONFIRMATION OF GEO-LOCATION MECHANISM.....	68
10. LIST OF TEST EQUIPMENT	73
11. ANNEX A_ TEST SETUP PHOTO	75

1. EUT DESCRIPTION

Model	SM-T727V
EUT Type	Tablet
Power Supply	DC 3.85 V
Battery Information	Model: EB-BT725ABU Type: Li-ion Battery
Travel Adapter Information	Model : EP-TA200 Manufacture: SOLUM
Keyboard Information	Model : EJ-FT720 Manufacture: SAMSUNG
Charging Doc Information	Model : EE-D3200 Manufacture: SAMSUNG
Ear-jack Information	Model : EHS64AVFWE Manufacture: ALMUS
Frequency Range	2412 MHz - 2462 MHz
Max. RF Output Power	<u>Peak Power</u> (For information only) 802.11b : 20.97 dBm 802.11g : 26.96 dBm 802.11n(HT20) : 26.97 dBm <u>Average Power</u> 802.11b : 18.15 dBm 802.11g : 18.69 dBm 802.11n(HT20) : 19.24 dBm
Modulation Type	DSSS/CCK : 802.11b OFDM : 802.11g, 802.11n
Number of Channels	11 Channels
Antenna Specification	Antenna type: Metal Peak Gain : -5.50 dBi
Date(s) of Tests	May 03, 2019~ June 18, 2019

2. TEST METHODOLOGY

FCC KDB 558074 D01 15.247 Meas Guidance v05r02 dated April 02, 2019 entitled “guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices and the measurement procedure described in ANSI C63.10 (Version : 2013) ‘the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices’.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3.75 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013)

DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment's, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

4. FACILITIES AND ACCREDITATIONS

FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032).

EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5. ANTENNA REQUIREMENTS

According to FCC 47 CFR § 15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

* The antennas of this E.U.T are permanently attached.

* The E.U.T Complies with the requirement of § 15.203

6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of

ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence.


The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (\pm dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.71

7. DESCRIPTION OF TESTS

7.1. Duty Cycle

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to the zero-span measurement method.

The largest available value of RBW is 8 MHz and VBW is 50 MHz.

The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.


1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz (\geq RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = $T_{\text{on}} / T_{\text{total}}$ and Duty Cycle Factor = $10 \cdot \log(1/\text{Duty Cycle})$

7.2. 6dB Bandwidth

Limit

The minimum permissible 6 dB bandwidth is 500 kHz.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Procedure 11.8.1 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW $\geq 3 \times$ RBW
- 3) Detector = Peak
- 4) Trace mode = max hold
- 5) Sweep = auto couple
- 6) Allow the trace to stabilize
- 7) We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.


Note : We tested OBW using the automatic bandwidth measurement capability of a spectrum analyzer.

7.3. Output Power

Limit

The maximum permissible conducted output power is 1 Watt.

Test Configuration



Test Procedure

The transmitter output is connected to the Power Meter.

- Peak Power (Procedure 11.9.1.3 in ANSI 63.10-2013)
: Measure the peak power of the transmitter.

- Average Power (Procedure 11.9.2.3 in ANSI 63.10-2013)
 - 1) Measure the duty cycle.
 - 2) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
 - 3) Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

Sample Calculation


- Conducted Output Power(Peak) = Reading Value + ATT loss + Cable loss
- Conducted Output Power(Average) = Reading Value + ATT loss + Cable loss + Duty Cycle Factor

7.4. Power Spectral Density

Limit

The transmitter power density average over 1-second interval shall not be greater than 8dBm in any 3kHz BW.

Test Configuration



Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to Procedure 8.4 in KDB 558074 v05r02, Procedure 11.10 in ANSI 63.10-2013.

The spectrum analyzer is set to :

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set span to at least 1.5 times the OBW.
- 3) $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$.
- 4) $VBW \geq 3 \times RBW$.
- 5) Sweep = auto couple
- 6) Detector = power averaging (rms) or sample detector (when rms not available).
- 7) Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / RBW]$.
- 8) Employ trace averaging (rms) mode over a minimum of 100 traces
- 9) Use the peak marker function to determine the maximum amplitude level.
- 10) Use the peak marker function to determine the maximum amplitude level within the RBW.
If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11) if then duty factor shall be added to adjust the result if the duty cycle is less than 98%

Sample Calculation

- Power Spectral Density = Reading Value + ATT loss + Cable loss

7.5. Conducted Band Edge(Out of Band Emissions) & Conducted Spurious Emissions


Limit

The maximum conducted (Average) output power was used to demonstrate compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least

30 dB relative to the maximum in-band peak PSD level in 100 kHz.

[Conducted > 30 dBc]

Test Configuration



Test Procedure

The transmitter output is connected to the spectrum analyzer.

(Procedure 11.11 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW $\geq 3 \times$ RBW
- 3) Set span to encompass the spectrum to be examined
- 4) Detector = Peak
- 5) Trace Mode = max hold
- 6) Sweep time = auto couple
- 7) Ensure that the number of measurement points $\geq 2 \times \text{Span} / \text{RBW}$
- 8) Allow trace to fully stabilize.
- 9) Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

Factors for frequency

Freq(MHz)	Factor(dB)
30	11.17
100	9.7
200	10.06
300	10
400	10.1
500	10.12
600	10.19
700	10.22
800	10.22
900	10.21
1000	10.26
2000	10.51
2400*	10.52
2500*	10.54
3000	10.55
4000	10.76
5000	10.94
6000	10.93
7000	11.22
8000	11.19
9000	11.35
10000	11.43
11000	11.43
12000	11.55
13000	11.7
14000	11.77
15000	11.85
16000	11.91
17000	11.89
18000	11.95
19000	11.94
20000	12.01
21000	12.04
22000	12.18
23000	12.47
24000	12.21
25000	12.4
26000	11.89

Note : 1. ‘**’ is fundamental frequency range.

2. Factor = Attenuator loss + Cable loss


7.6. Radiated Test

Limit


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	$2400/F(\text{kHz})$	300
0.490 – 1.705	$24000/F(\text{kHz})$	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



Test Procedure of Radiated spurious emissions(Below 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the ground plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor(0.009 MHz – 0.490 MHz) = $40 \cdot \log(3 \text{ m}/300 \text{ m}) = -80 \text{ dB}$
Measurement Distance : 3 m
7. Distance Correction Factor(0.490 MHz – 30 MHz) = $40 \cdot \log(3 \text{ m}/30 \text{ m}) = -40 \text{ dB}$
Measurement Distance : 3 m
8. Spectrum Setting
 - Frequency Range = 9 kHz ~ 30 MHz
 - Detector = Peak
 - Trace = Maxhold
 - RBW = 9 kHz
 - VBW $\geq 3 \cdot \text{RBW}$
9. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

KDB 414788 OFS and Chamber Correlation Justification

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

Test Procedure of Radiated spurious emissions(Below 1GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

5. Spectrum Setting**(1) Measurement Type(Peak):**

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 100 kHz
- VBW $\geq 3 \times$ RBW

(2) Measurement Type(Quasi-peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Quasi-Peak
- RBW = 120 kHz

*In general, (1) is used mainly

6. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L)
7. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

Test Procedure of Radiated spurious emissions (Above 1 GHz)

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor(reference distance : 3 m).
*Distance extrapolation factor = $20 \cdot \log(\text{test distance} / \text{specific distance})$ (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting (Method 8.6 in KDB 558074 v05r02, Procedure 11.12 in ANSI 63.10-2013)

(1) Measurement Type(Peak):

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW $\geq 3 \cdot \text{RBW}$

(2) Measurement Type(Average): Duty cycle $\geq 98\%$

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \cdot \text{RBW}$
- Sweep time = auto.
- Trace mode = average (at least 100 traces).

(3) Measurement Type(Average): Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)

- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.
- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

11. Total(Measurement Type : Peak)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle $\geq 98\%$)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

Total(Measurement Type : Average, Duty cycle < 98%)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)
+ Duty Cycle Factor

Test Procedure of Radiated Restricted Band Edge

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor(reference distance : 3 m).
*Distance extrapolation factor = $20 \times \log(\text{test distance} / \text{specific distance})$ (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.

7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

8. The unit was tested with its standard battery.

9. Spectrum Setting

(1) Measurement Type(Peak):

- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW

(2) Measurement Type(Average): Duty cycle $\geq 98\%$,

- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).

(3) Measurement Type(Average): Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

- Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle.
- Duty Cycle Factor (dB) : Please refer to the please refer to section 9.1.

10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

11. Total(Measurement Type : Peak)

$$= \text{Reading Value} + \text{Antenna Factor(A.F)} + \text{Cable Loss(C.L)} + \text{Distance Factor(D.F)}$$
Total(Measurement Type : Average, Duty cycle \geq 98%)
$$= \text{Reading Value} + \text{Antenna Factor(A.F)} + \text{Cable Loss(C.L)} + \text{Distance Factor(D.F)}$$
Total(Measurement Type : Average, Duty cycle $<$ 98%)
$$= \text{Reading Value} + \text{Antenna Factor(A.F)} + \text{Cable Loss(C.L)} + \text{Distance Factor(D.F)} \\ + \text{Duty Cycle Factor}$$

7.7. AC Power line Conducted Emissions

Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

*Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

7.8. Worst case configuration and mode

Radiated test

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone, Stand alone + External accessories(Keyboard, Charging Doc, Earphone, etc)
 - Worstcase : Stand alone
2. EUT Axis
 - Radiated Spurious Emissions : Y
 - Radiated Restricted Band Edge : X
3. Duty cycle factor applies only 802.11g/n(Duty cycle < 98%).
4. All data rate of operation were investigated and the test results are worst case in lowest datarate of each mode.
 - 802.11b : 1Mbps
 - 802.11g : 6Mbps
 - 802.11n_HT20 : MCS0
5. All position of loop antenna were investigated and the test result is a no critical peak found at all positions.
 - Position : Horizontal, Vertical, Parallel to the ground plane

AC Power line Conducted Emissions

1. All modes of operation were investigated and the worst case configuration results are reported.
 - Mode : Stand alone + External accessories(Keyboard, Charging Doc, Earphone, etc)+Travel Adapter, Stand alone + Travel Adapter
 - Worstcase : Stand alone + Travel Adapter

Conducted test

1. The EUT was configured with data rate of highest power.

8. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§ 15.247(a)(2)	> 500 kHz	Conducted	PASS
Conducted Maximum Output Power	§ 15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§ 15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge (Out of Band Emissions)	§ 15.247(d)	Conducted > 30 dBc		PASS
AC Power line Conducted Emissions	§ 15.207	cf. Section 7.7		PASS
Radiated Spurious Emissions	§ 15.247(d), 15.205, 15.209	cf. Section 7.6	Radiated	PASS
Radiated Restricted Band Edge	§ 15.247(d), 15.205, 15.209	cf. Section 7.6		PASS


9. TEST RESULT

9.1 DUTY CYCLE


Mode	Data Rate (Mbps)	T _{on} (ms)	T _{total} (ms)	Duty Cycle	Duty Cycle Factor (dB)
802.11b	1	8.618	8.754	0.985	0.068
	2	4.309	4.339	0.993	0.030
	5.5	1.629	1.659	0.982	0.081
	11	0.863	0.894	0.965	0.154
802.11g	6	1.430	1.468	0.975	0.112
	9	0.961	0.998	0.963	0.163
	12	0.727	0.764	0.952	0.214
	18	0.492	0.529	0.929	0.318
	24	0.376	0.414	0.909	0.413
	36	0.256	0.292	0.876	0.575
	48	0.200	0.236	0.847	0.719
	54	0.180	0.216	0.833	0.792
802.11n (HT20)	6.5 (MCS0)	1.339	1.378	0.972	0.122
	13 (MCS1)	0.688	0.725	0.948	0.232
	19.5 (MCS2)	0.471	0.509	0.927	0.331
	26 (MCS3)	0.364	0.402	0.907	0.424
	39 (MCS4)	0.256	0.292	0.876	0.574
	52 (MCS5)	0.200	0.236	0.846	0.726
	58.5 (MCS6)	0.184	0.220	0.835	0.784
	65 (MCS7)	0.168	0.204	0.824	0.843

Test Plots


Duty cycle plot (802.11b(1Mbps))



Duty cycle plot (802.11g(6Mbps))



Duty cycle plot (802.11n(MCS0))



Note:

In order to simplify the report, attached plots were only the most lowest datarate.

9.2 6dB BANDWIDTH


802.11b Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.		
2412	1	8.567	0.5
2437	6	8.543	0.5
2462	11	8.605	0.5

802.11g Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.		
2412	1	15.27	0.5
2437	6	15.18	0.5
2462	11	15.38	0.5

802.11n Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.		
2412	1	15.99	0.5
2437	6	15.18	0.5
2462	11	16.29	0.5

Test Plots


6dB Bandwidth plot (802.11b-CH 6)



6dB Bandwidth plot (802.11g-CH 6)



6dB Bandwidth plot (802.11n_HT20-CH 6)



Note:

In order to simplify the report, attached plots were only the most narrow 6 dB BW channel.

9.3 OUTPUT POWER

Peak Power

1. Power Meter offset = Attenuator loss + Cable loss

2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.

So, 10.52 dB is offset for 2.4 GHz Band

802.11b Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)	Power Level Setting
Frequency[MHz]	Channel No.				
2412	1	1	20.56	30	17
		2	20.68	30	
		5.5	20.66	30	
		11	20.53	30	
2437	6	1	20.78	30	17
		2	20.90	30	
		5.5	20.91	30	
		11	20.97	30	
2462	11	1	20.68	30	17
		2	20.78	30	
		5.5	20.72	30	
		11	20.61	30	

802.11g Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)	Power Level Setting
Frequency[MHz]	Channel No.				
2412	1	6	23.74	30	18
		9	23.79	30	
		12	23.70	30	
		18	25.35	30	
		24	24.96	30	
		36	26.63	30	
		48	26.80	30	
		54	26.65	30	
2437	6	6	23.92	30	18
		9	24.04	30	
		12	23.84	30	
		18	25.52	30	
		24	25.06	30	
		36	26.78	30	
		48	26.96	30	
		54	26.82	30	
2462	11	6	23.69	30	18
		9	23.71	30	
		12	23.58	30	
		18	25.12	30	
		24	25.15	30	
		36	26.49	30	
		48	26.53	30	
		54	26.37	30	

802.11n Mode		MCS Index	Measured Power(dBm)	Limit (dBm)	Power Level Setting
Frequency[MHz]	Channel No.				
2412	1	0	22.90	30	17
		1	23.01	30	
		2	24.59	30	
		3	24.14	30	
		4	26.53	30	
		5	26.18	30	
		6	26.37	30	
		7	26.28	30	
2437	6	0	24.31	30	18.5
		1	24.32	30	
		2	25.48	30	
		3	25.12	30	
		4	26.97	30	
		5	26.74	30	
		6	26.92	30	
		7	26.80	30	
2462	11	0	24.02	30	18.5
		1	24.00	30	
		2	25.10	30	
		3	24.81	30	
		4	26.50	30	
		5	26.30	30	
		6	26.41	30	
		7	26.19	30	

Average Power

1. Power Meter offset = Attenuator loss + Cable loss

2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB.

So, 10.52 dB is offset for 2.4 GHz Band.

802.11b Mode		Rate (Mbps)	Measured Power (dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor(dB)	Limit (dBm)	Power Level Setting
Frequency [MHz]	Channel No.						
2412	1	1	17.71	0.068	17.78	30	17
		2	17.95	0.030	17.98	30	
		5.5	17.84	0.081	17.92	30	
		11	17.80	0.154	17.95	30	
2437	6	1	18.00	0.068	18.07	30	17
		2	18.03	0.030	18.06	30	
		5.5	18.07	0.081	18.15	30	
		11	17.92	0.154	18.07	30	
2462	11	1	17.52	0.068	17.59	30	17
		2	17.70	0.030	17.73	30	
		5.5	17.58	0.081	17.66	30	
		11	17.56	0.154	17.71	30	

802.11g Mode		Rate (Mbps)	Measured Power (dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)	Power Level Setting
Frequency [MHz]	Channel No.						
2412	1	6	17.59	0.112	17.70	30	18
		9	17.51	0.163	17.67	30	
		12	17.45	0.214	17.66	30	
		18	18.15	0.318	18.47	30	
		24	17.96	0.413	18.37	30	
		36	17.92	0.575	18.49	30	
		48	17.80	0.719	18.52	30	
		54	17.72	0.792	18.51	30	
2437	6	6	17.80	0.112	17.91	30	18
		9	17.74	0.163	17.90	30	
		12	17.67	0.214	17.88	30	
		18	18.32	0.318	18.64	30	
		24	18.14	0.413	18.55	30	
		36	18.08	0.575	18.65	30	
		48	17.97	0.719	18.69	30	
		54	17.86	0.792	18.65	30	
2462	11	6	17.52	0.112	17.63	30	18
		9	17.48	0.163	17.64	30	
		12	17.42	0.214	17.63	30	
		18	18.10	0.318	18.42	30	
		24	17.87	0.413	18.28	30	
		36	17.82	0.575	18.39	30	
		48	17.72	0.719	18.44	30	
		54	17.58	0.792	18.37	30	

802.11n Mode		MCS Index	Measured Power (dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)	Power Level Setting
Frequency [MHz]	Channel No.						
2412	1	0	16.55	0.122	16.67	30	17
		1	16.38	0.232	16.61	30	
		2	17.14	0.331	17.47	30	
		3	17.07	0.424	17.49	30	
		4	17.12	0.574	17.69	30	
		5	16.96	0.726	17.69	30	
		6	16.93	0.784	17.71	30	
		7	16.80	0.843	17.64	30	
2437	6	0	18.18	0.122	18.30	30	18.5
		1	17.99	0.232	18.22	30	
		2	18.71	0.331	19.04	30	
		3	18.58	0.424	19.00	30	
		4	18.52	0.574	19.09	30	
		5	18.51	0.726	19.24	30	
		6	18.32	0.784	19.10	30	
		7	18.23	0.843	19.07	30	
2462	11	0	17.96	0.122	18.08	30	18.5
		1	17.71	0.232	17.94	30	
		2	18.46	0.331	18.79	30	
		3	18.37	0.424	18.79	30	
		4	18.42	0.574	18.99	30	
		5	18.22	0.726	18.95	30	
		6	18.19	0.784	18.97	30	
		7	18.09	0.843	18.93	30	

9.4 POWER SPECTRAL DENSITY

Mode	Frequency (MHz)	Channel No.	Test Result			
			Measured PSD (dBm)	Duty Cycle Factor	Measured PSD(dBm) + Duty Cycle Factor	Limit (dBm)
802.11b	2412	1	1.221	0.030	1.251	8
	2437	6	1.185	0.081	1.266	8
	2462	11	1.343	0.003	1.373	8
802.11g	2412	1	-1.475	0.719	-0.756	8
	2437	6	-1.100	0.719	-0.381	8
	2462	11	-1.015	0.719	-0.296	8
802.11n	2412	1	-2.162	0.784	-1.378	8
	2437	6	-0.444	0.726	0.282	8
	2462	11	-0.770	0.574	-0.196	8

Note :

1. Spectrum reading values are not plot data.


The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.

2. Spectrum offset = Attenuator loss + Cable loss


3. 10.52 dB is offset for 2.4 GHz Band.

Test Plots


Power Spectral Density (802.11b-CH 11)



Power Spectral Density (802.11g-CH 11)



Power Spectral Density (802.11n_HT20 -CH 6)



Note :

In order to simplify the report, attached plots were only the worstcase PSD channel.


9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS

Test Result : please refer to the plot below.


In order to simplify the report, attached plots were only the worst case channel and data rate.

Test Plots(BandEdge)


Band Edge (802.11b-CH1)




Band Edge (802.11b-CH11)




Band Edge (802.11g-CH1)




Band Edge (802.11g-CH11)



Band Edge (802.11n(HT20)-CH1)




Band Edge (802.11n(HT20)-CH11)



Test Plots(Conducted Spurious Emission)


30 MHz ~ 1 GHz

Conducted Spurious Emission (802.11n(HT20)_Ch.6_MCS5)




1 GHz ~ 3 GHz

Conducted Spurious Emission (802.11n(HT20)_Ch.6_MCS5)




3 GHz ~ 5 GHz

Conducted Spurious Emission (802.11n(HT20)_Ch.6_MCS5)




5 GHz ~ 7 GHz

Conducted Spurious Emission (802.11n(HT20)_Ch.6_MCS5)




7 GHz ~ 9 GHz

Conducted Spurious Emission (802.11n(HT20)_Ch.6_MCS5)




9 GHz ~ 11 GHz

Conducted Spurious Emission (802.11n(HT20)_Ch.6_MCS5)




11 GHz ~ 13 GHz

Conducted Spurious Emission (802.11n(HT20)_Ch.6_MCS5)




13 GHz ~ 15 GHz

Conducted Spurious Emission (802.11n(HT20)_Ch.6_MCS5)




15 GHz ~ 17 GHz

Conducted Spurious Emission (802.11n(HT20)_Ch.6_MCS5)




17 GHz ~ 19 GHz

Conducted Spurious Emission (802.11n(HT20)_Ch.6_MCS5)




19 GHz ~ 21 GHz

Conducted Spurious Emission (802.11n(HT20)_Ch.6_MCS5)




21 GHz ~ 23 GHz

Conducted Spurious Emission (802.11n(HT20)_Ch.6_MCS5)



23 GHz ~ 25 GHz

Conducted Spurious Emission (802.11n(HT20)_Ch.6_MCS5)



9.6 RADIATED SPURIOUS EMISSIONS

Frequency Range : 9 kHz – 30MHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor = $40 \cdot \log(\text{specific distance} / \text{test distance})$ (dB)
3. Limit line = specific Limits (dBuV) + Distance extrapolation factor
4. Radiated test is performed with hopping off.

Frequency Range : Below 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

Frequency Range : Above 1 GHz

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	52.04	0.56	V	52.60	73.98	21.39	PK
4824	45.60	0.56	V	46.16	53.98	7.83	AV
7236	45.39	9.47	V	54.86	73.98	19.12	PK
7236	33.62	9.47	V	43.09	53.98	10.89	AV
4824	52.98	0.56	H	53.54	73.98	20.45	PK
4824	46.30	0.56	H	46.86	53.98	7.13	AV
7236	45.40	9.47	H	54.87	73.98	19.11	PK
7236	33.45	9.47	H	42.92	53.98	11.06	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	49.52	0.00	0.56	V	50.08	73.98	23.91	PK
4824	38.48	0.11	0.56	V	39.15	53.98	14.83	AV
7236	45.31	0.00	9.47	V	54.78	73.98	19.20	PK
7236	33.02	0.11	9.47	V	42.60	53.98	11.38	AV
4824	50.46	0.00	0.56	H	51.02	73.98	22.97	PK
4824	38.61	0.11	0.56	H	39.28	53.98	14.70	AV
7236	45.50	0.00	9.47	H	54.97	73.98	19.01	PK
7236	33.09	0.11	9.47	H	42.67	53.98	11.31	AV

Operation Mode: 802.11n (HT20)
 Transfer MCS Index: 0
 Operating Frequency: 2412
 Channel No. 01 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4824	49.68	0.00	0.56	V	50.24	73.98	23.75	PK
4824	38.44	0.12	0.56	V	39.12	53.98	14.86	AV
7236	44.81	0.00	9.47	V	54.28	73.98	19.70	PK
7236	32.98	0.12	9.47	V	42.57	53.98	11.41	AV
4824	50.26	0.00	0.56	H	50.82	73.98	23.17	PK
4824	38.56	0.12	0.56	H	39.24	53.98	14.74	AV
7236	45.02	0.00	9.47	H	54.49	73.98	19.49	PK
7236	33.08	0.12	9.47	H	42.67	53.98	11.31	AV

Operation Mode: 802.11b

Transfer Rate: 1 Mbps

Operating Frequency: 2437

Channel No. 06 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	51.14	0.87	V	52.01	73.98	21.98	PK
4874	44.08	0.87	V	44.95	53.98	9.04	AV
7311	44.89	9.16	V	54.05	73.98	19.93	PK
7311	33.66	9.16	V	42.82	53.98	11.16	AV
4874	51.59	0.87	H	52.46	73.98	21.53	PK
4874	44.47	0.87	H	45.34	53.98	8.65	AV
7311	45.54	9.16	H	54.70	73.98	19.28	PK
7311	33.83	9.16	H	42.99	53.98	10.99	AV

Operation Mode: 802.11g

Transfer Rate: 6 Mbps

Operating Frequency: 2437

Channel No. 06 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4874	48.54	0.00	0.87	V	49.41	73.98	24.58	PK
4874	38.00	0.11	0.87	V	38.98	53.98	15.00	AV
7311	45.19	0.00	9.16	V	54.35	73.98	19.63	PK
7311	33.75	0.11	9.16	V	43.02	53.98	10.96	AV
4874	49.93	0.00	0.87	H	50.80	73.98	23.19	PK
4874	38.08	0.11	0.87	H	39.06	53.98	14.92	AV
7311	45.58	0.00	9.16	H	54.74	73.98	19.24	PK
7311	33.84	0.11	9.16	H	43.11	53.98	10.87	AV

Operation Mode:	802.11n (HT20)
Transfer MCS Index:	0
Operating Frequency	2437
Channel No.	06 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4874	49.16	0.00	0.87	V	50.03	73.98	23.96	PK
4874	38.01	0.12	0.87	V	39.00	53.98	14.98	AV
7311	45.12	0.00	9.16	V	54.28	73.98	19.70	PK
7311	33.65	0.12	9.16	V	42.93	53.98	11.05	AV
4874	50.04	0.00	0.87	H	50.91	73.98	23.08	PK
4874	38.12	0.12	0.87	H	39.11	53.98	14.87	AV
7311	45.54	0.00	9.16	H	54.70	73.98	19.28	PK
7311	33.78	0.12	9.16	H	43.06	53.98	10.92	AV

Operation Mode: 802.11b

Transfer Rate: 1 Mbps

Operating Frequency: 2462

Channel No.: 11 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.-A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	53.26	0.81	V	54.07	73.98	19.92	PK
4924	47.84	0.81	V	48.65	53.98	5.33	AV
7386	44.95	9.38	V	54.33	73.98	19.65	PK
7386	33.68	9.38	V	43.06	53.98	10.92	AV
4924	54.05	0.81	H	54.86	73.98	19.13	PK
4924	48.51	0.81	H	49.32	53.98	4.67	AV
7386	45.84	9.38	H	55.22	73.98	18.76	PK
7386	33.72	9.38	H	43.10	53.98	10.88	AV

Operation Mode: 802.11g

Transfer Rate: 6 Mbps

Operating Frequency: 2462

Channel No.: 11 Ch


Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	51.89	0.00	0.81	V	52.70	73.98	21.29	PK
4924	39.75	0.11	0.81	V	40.67	53.98	13.31	AV
7386	44.85	0.00	9.38	V	54.23	73.98	19.75	PK
7386	33.65	0.11	9.38	V	43.14	53.98	10.84	AV
4924	52.63	0.00	0.81	H	53.44	73.98	20.55	PK
4924	40.00	0.11	0.81	H	40.92	53.98	13.06	AV
7386	45.73	0.00	9.38	H	55.11	73.98	18.87	PK
7386	33.74	0.11	9.38	H	43.23	53.98	10.75	AV

Operation Mode:	802.11n (HT20)
Transfer MCS Index:	0
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.- A.G+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4924	50.88	0.00	0.81	V	51.69	73.98	22.30	PK
4924	39.05	0.12	0.81	V	39.98	53.98	14.00	AV
7386	45.46	0.00	9.38	V	54.84	73.98	19.14	PK
7386	33.59	0.12	9.38	V	43.09	53.98	10.89	AV
4924	51.62	0.00	0.81	H	52.43	73.98	21.56	PK
4924	39.15	0.12	0.81	H	40.08	53.98	13.90	AV
7386	45.98	0.00	9.38	H	55.36	73.98	18.62	PK
7386	33.72	0.12	9.38	H	43.22	53.98	10.76	AV


Test Plots (Worst case : Y-H)

Radiated Spurious Emissions plot – Average Reading (802.11b, Ch.11 2nd Harmonic)



Date: 9.MAY.2019 17:30:55

Radiated Spurious Emissions plot – Peak Reading (802.11b, Ch.11 2nd Harmonic)



Date: 9.MAY.2019 17:31:35

Note:

Plot of worst case are only reported.

9.7 RADIATED RESTRICTED BAND EDGES

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+C.L.+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	26.83	33.39	H	60.22	73.98	13.76	PK
2390.0	14.28	33.39	H	47.67	53.98	6.31	AV
2390.0	26.70	33.39	V	60.09	73.98	13.89	PK
2390.0	14.06	33.39	V	47.45	53.98	6.53	AV
2483.5	25.76	33.39	H	59.15	73.98	14.83	PK
2483.5	14.50	33.39	H	47.89	53.98	6.09	AV
2483.5	25.61	33.39	V	59.00	73.98	14.98	PK
2483.5	14.41	33.39	V	47.80	53.98	6.18	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	33.16	0.00	33.39	H	66.55	73.98	7.43	PK
* 2389 ~ 2390	17.63	0.11	33.39	H	51.13	53.98	2.85	AV
2310 ~ 2389	17.33	0.11	33.39	H	50.83	53.98	3.15	AV
2390.0	29.19	0.00	33.39	V	62.58	73.98	11.40	PK
2390.0	16.96	0.11	33.39	V	50.46	53.98	3.52	AV
2483.5	29.83	0.00	33.39	H	63.22	73.98	10.76	PK
2483.5	16.50	0.11	33.39	H	50.00	53.98	3.98	AV
2483.5	29.64	0.00	33.39	V	63.03	73.98	10.95	PK
2483.5	16.25	0.11	33.39	V	49.75	53.98	4.23	AV

Note:

* : Procedure 11.13.3 (Integration method) in ANSI 63.10-2013

Operation Mode: 802.11n (HT20)
Transfer MCS Index: 0
Operating Frequency: 2412 MHz, 2462 MHz
Channel No. 01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	32.10	0.00	33.39	H	65.49	73.98	8.49	PK
* 2389 ~ 2390	18.00	0.12	33.39	H	51.51	53.98	2.47	AV
* 2388 ~ 2389	16.87	0.12	33.39	H	50.38	53.98	3.60	AV
2388	17.07	0.12	33.39	H	50.58	53.98	3.40	AV
2390.0	31.58	0.00	33.39	V	64.97	73.98	9.01	PK
* 2389 ~ 2390	17.85	0.12	33.39	V	51.36	53.98	2.62	AV
* 2388 ~ 2389	16.44	0.12	33.39	V	49.95	53.98	4.03	AV
2388	16.84	0.12	33.39	V	50.35	53.98	3.63	AV
2483.5	30.99	0.00	33.39	H	64.38	73.98	9.60	PK
* 2483.5 ~ 2484.5	17.78	0.12	33.39	H	51.29	53.98	2.69	AV
2484.5 ~ 2500	18.12	0.12	33.39	H	51.63	53.98	2.35	AV
2483.5	30.58	0.00	33.39	V	63.97	73.98	10.01	PK
* 2483.5 ~ 2484.5	17.61	0.12	33.39	V	51.12	53.98	2.86	AV
2484.5 ~ 2500	17.99	0.12	33.39	V	51.50	53.98	2.48	AV

Note:


* : Procedure 11.13.3 (Integration method) in ANSI 63.10-2013

Operation Mode: 802.11n (HT20)
Transfer MCS Index: 0
Operating Frequency: 2422 MHz
Channel No. 2 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor [dB]	A.F.+C.L.+D.F. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	25.82	0.00	33.39	H	59.21	73.98	14.77	PK
2390.0	14.84	0.12	33.39	H	48.35	53.98	5.63	AV


Test Plots (Worst case : X-H)

Radiated Restricted Band Edges plot – Average Reading (802.11n(HT20) Ch.11)_ 2483.5 MHz ~2484.5 MHz




Date: 9.MAY.2019 15:12:38

Radiated Restricted Band Edges plot – Peak Reading (802.11n(HT20) Ch.11)_ 2483.5 MHz ~2500 MHz



Date: 9.MAY.2019 15:09:30

Radiated Restricted Band Edges plot – Average Reading (802.11n(HT20) Ch.11)_ 2484.5 MHz ~ 2.5 GHz



Date: 9.MAY.2019 15:14:47

Note:

Plot of worst case are only reported.

9.8 POWERLINE CONDUCTED EMISSIONS

Conducted Emissions (Line 1)

Test


1 / 2

HCT TEST Report

Common Information

EUT: SM-T727V
 Manufacturer: SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions: WLAN 2.4G MODE

FCC CLASS B_Exten Cable



Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.152000	50.7	9.000	Off	N	9.8	15.2	65.9
0.160000	44.4	9.000	Off	N	9.8	21.1	65.5
0.170000	36.8	9.000	Off	N	9.8	28.2	65.0
0.224000	46.1	9.000	Off	N	9.9	16.6	62.7
0.228000	44.6	9.000	Off	N	9.9	17.9	62.5
0.304000	40.3	9.000	Off	N	9.9	19.8	60.1
3.986000	40.3	9.000	Off	N	10.2	15.7	56.0
4.360000	39.1	9.000	Off	N	10.2	16.9	56.0
4.414000	39.6	9.000	Off	N	10.2	16.4	56.0
4.666000	37.4	9.000	Off	N	10.2	18.6	56.0
4.736000	37.4	9.000	Off	N	10.2	18.6	56.0
4.864000	37.3	9.000	Off	N	10.2	18.7	56.0
9.250000	35.5	9.000	Off	N	10.4	24.5	60.0
9.262000	35.5	9.000	Off	N	10.4	24.5	60.0
9.358000	34.8	9.000	Off	N	10.4	25.2	60.0
9.482000	33.3	9.000	Off	N	10.4	26.7	60.0
12.744000	41.1	9.000	Off	N	10.6	18.9	60.0
13.252000	39.4	9.000	Off	N	10.6	20.6	60.0

2019-05-17

오전 9:06:25

Test

2 / 2

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.154000	34.6	9.000	Off	N	9.8	21.1	55.8
0.158000	30.5	9.000	Off	N	9.8	25.1	55.6
0.166000	32.7	9.000	Off	N	9.8	22.5	55.2
0.170000	29.5	9.000	Off	N	9.8	25.4	55.0
0.224000	33.7	9.000	Off	N	9.9	19.0	52.7
0.228000	29.6	9.000	Off	N	9.9	22.9	52.5
4.294000	32.5	9.000	Off	N	10.2	13.5	46.0
4.360000	32.5	9.000	Off	N	10.2	13.5	46.0
4.370000	32.2	9.000	Off	N	10.2	13.8	46.0
4.414000	32.5	9.000	Off	N	10.2	13.5	46.0
4.586000	31.6	9.000	Off	N	10.2	14.4	46.0
4.666000	30.8	9.000	Off	N	10.2	15.2	46.0
9.174000	28.2	9.000	Off	N	10.4	21.8	50.0
9.250000	28.2	9.000	Off	N	10.4	21.8	50.0
9.262000	28.1	9.000	Off	N	10.4	21.9	50.0
9.358000	27.2	9.000	Off	N	10.4	22.8	50.0
12.744000	33.1	9.000	Off	N	10.6	16.9	50.0
13.252000	30.0	9.000	Off	N	10.6	20.0	50.0

2019-05-17

오전 9:06:25

Conducted Emissions (Line 2)

Test


1 / 2

HCT TEST Report

Common Information

EUT: SM-T727V
 Manufacturer: SAMSUNG
 Test Site: SHIELD ROOM
 Operating Conditions: WLAN 2.4G MODE

FCC CLASS B_Exten Cable



— FCC CLASS B_OP — FCC CLASS B_AV — Preview Result 1-PK+
 — Preview Result 2-AVG — Final Result 1-QPK — Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	49.3	9.000	Off	L1	9.7	16.7	66.0
0.154000	47.7	9.000	Off	L1	9.7	18.1	65.8
0.222000	44.4	9.000	Off	L1	9.7	18.3	62.7
0.226000	43.7	9.000	Off	L1	9.7	18.9	62.6
0.668000	44.4	9.000	Off	L1	9.8	11.6	56.0
0.748000	43.1	9.000	Off	L1	9.8	12.9	56.0
3.780000	38.7	9.000	Off	L1	10.0	17.3	56.0
3.888000	39.9	9.000	Off	L1	10.0	16.1	56.0
3.896000	39.7	9.000	Off	L1	10.0	16.3	56.0
3.936000	40.4	9.000	Off	L1	10.0	15.6	56.0
3.946000	40.7	9.000	Off	L1	10.0	15.3	56.0
4.118000	39.7	9.000	Off	L1	10.0	16.3	56.0
12.126000	41.3	9.000	Off	L1	10.3	18.7	60.0
12.256000	41.3	9.000	Off	L1	10.3	18.7	60.0
12.270000	41.3	9.000	Off	L1	10.3	18.7	60.0
12.738000	41.1	9.000	Off	L1	10.3	18.9	60.0
12.806000	40.7	9.000	Off	L1	10.3	19.3	60.0
12.938000	40.4	9.000	Off	L1	10.3	19.6	60.0

2019-05-17

오전 9:15:00

Test

2 / 2

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	37.6	9.000	Off	L1	9.7	18.4	56.0
0.156000	31.7	9.000	Off	L1	9.7	24.0	55.7
0.222000	33.9	9.000	Off	L1	9.7	18.8	52.7
0.226000	32.4	9.000	Off	L1	9.7	20.2	52.6
0.670000	37.9	9.000	Off	L1	9.8	8.1	46.0
0.748000	34.5	9.000	Off	L1	9.8	11.5	46.0
3.780000	31.7	9.000	Off	L1	10.0	14.3	46.0
3.888000	31.9	9.000	Off	L1	10.0	14.1	46.0
3.896000	32.2	9.000	Off	L1	10.0	13.8	46.0
3.936000	32.7	9.000	Off	L1	10.0	13.3	46.0
3.946000	32.6	9.000	Off	L1	10.0	13.4	46.0
4.170000	32.4	9.000	Off	L1	10.0	13.6	46.0
12.420000	33.8	9.000	Off	L1	10.3	16.2	50.0
12.432000	33.8	9.000	Off	L1	10.3	16.2	50.0
12.556000	33.5	9.000	Off	L1	10.3	16.5	50.0
12.666000	33.3	9.000	Off	L1	10.3	16.7	50.0
12.806000	32.5	9.000	Off	L1	10.3	17.5	50.0
12.938000	31.7	9.000	Off	L1	10.3	18.3	50.0

2019-05-17

오전 9:15:00

9.9 CONFIRMATION OF GEO-LOCATION MECHANISM


The device uses MCC information obtained from the public cellular carrier to determine that it is operating outside the U.S. and then enable channels 12 and 13 only if a non-US MCC that supports channel 12 and 13 is confirmed.

The device uses a geo-location mechanism based on the Country in order to only enable certain WLAN DTS bands when the device is not in the USA.

WLAN	Country code = US	Country code = KR(Korea)
CH 12	Did not connect	Connected
CH 13	Did not connect	Connected

The verification tests confirmed the operational of the geo-location mechanism.

Test Setup



Test Procedure

In case of Country code

1. Open Command Prompt.
2. At the Command Prompt, enter the command.
 - C:\adb>adb remount
 - C:\adb>adb shell
 - gts4lv:/ # wpa_cli driver country US // Setting the country.
 - gts4lv:/ # iw list // Channel list is obtain.

In case of airplane mode

1. airplane mode on
2. Wifi on
3. Open Command Prompt.
4. At the Command Prompt, enter the command.
 - C:\adb>adb remount
 - C:\adb>adb shell
 - gts4lv:/ # iw reg get // support band in case of airplane mode

Setting the country for product

Country code = US	
	<pre>C:\wadb>adb shell gts4lv:/ # wpa_cli driver country US wpa_cli driver country US Using interface 'wlan0' OK gts4lv:/ # iw list iw list</pre>
Country code = KR(Korea)	
	<pre>gts4lv:/ # wpa_cli driver country KR wpa_cli driver country KR Using interface 'wlan0' OK gts4lv:/ # iw list iw list</pre>

Verification test

<p>Did not connect</p> <p>(Country code = US)</p> <p>Frequencies:</p> <ul style="list-style-type: none"> * 2412 MHz [1] (30.0 dBm) * 2417 MHz [2] (30.0 dBm) * 2422 MHz [3] (30.0 dBm) * 2427 MHz [4] (30.0 dBm) * 2432 MHz [5] (30.0 dBm) * 2437 MHz [6] (30.0 dBm) * 2442 MHz [7] (30.0 dBm) * 2447 MHz [8] (30.0 dBm) * 2452 MHz [9] (30.0 dBm) * 2457 MHz [10] (30.0 dBm) * 2462 MHz [11] (30.0 dBm) * 2467 MHz [12] (disabled) * 2472 MHz [13] (disabled) * 2484 MHz [14] (disabled)
<p>Connected</p> <p>(Country code = KR)</p> <p>Frequencies:</p> <ul style="list-style-type: none"> * 2412 MHz [1] (20.0 dBm) * 2417 MHz [2] (20.0 dBm) * 2422 MHz [3] (20.0 dBm) * 2427 MHz [4] (20.0 dBm) * 2432 MHz [5] (20.0 dBm) * 2437 MHz [6] (20.0 dBm) * 2442 MHz [7] (20.0 dBm) * 2447 MHz [8] (20.0 dBm) * 2452 MHz [9] (20.0 dBm) * 2457 MHz [10] (20.0 dBm) * 2462 MHz [11] (20.0 dBm) * 2467 MHz [12] (20.0 dBm) * 2472 MHz [13] (20.0 dBm) * 2484 MHz [14] (disabled)

Did not connect Airplane mode	
Airplane off	<pre> gts4lv:/ # iw reg get iw reg get global country KR: DFS-JP <2402 - 2482 @ 40>, <N/A, 20>, <N/A> <5170 - 5250 @ 80>, <N/A, 20>, <N/A>, AUTO-BW <5250 - 5330 @ 80>, <N/A, 20>, <0 ms>, DFS, AUTO-BW <5490 - 5730 @ 80>, <N/A, 30>, <0 ms>, DFS <5735 - 5835 @ 80>, <N/A, 30>, <N/A> phy#0 country US: DFS-FCC <2402 - 2472 @ 40>, <N/A, 30>, <N/A> <5170 - 5250 @ 80>, <N/A, 23>, <N/A>, AUTO-BW <5250 - 5330 @ 80>, <N/A, 23>, <0 ms>, DFS, AUTO-BW <5490 - 5730 @ 160>, <N/A, 23>, <0 ms>, DFS <5735 - 5835 @ 80>, <N/A, 30>, <N/A> </pre>
Airplane on	<pre> gts4lv:/ # iw reg get iw reg get global country US: DFS-FCC <2402 - 2472 @ 40>, <N/A, 30>, <N/A> <5170 - 5250 @ 80>, <N/A, 23>, <N/A>, AUTO-BW <5250 - 5330 @ 80>, <N/A, 23>, <0 ms>, DFS, AUTO-BW <5490 - 5730 @ 160>, <N/A, 23>, <0 ms>, DFS <5735 - 5835 @ 80>, <N/A, 30>, <N/A> phy#0 country US: DFS-FCC <2402 - 2472 @ 40>, <N/A, 30>, <N/A> <5170 - 5250 @ 80>, <N/A, 23>, <N/A>, AUTO-BW <5250 - 5330 @ 80>, <N/A, 23>, <0 ms>, DFS, AUTO-BW <5490 - 5730 @ 160>, <N/A, 23>, <0 ms>, DFS <5735 - 5835 @ 80>, <N/A, 30>, <N/A> </pre>

Note : The frequency range is occupied band, not center frequency.

10. LIST OF TEST EQUIPMENT

Conducted Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216 / LISN	12/12/2018	Annual	102245
Rohde & Schwarz	ESCI / Test Receiver	06/27/2018	Annual	100033
ESPACE	SU-642 / Temperature Chamber	03/12/2019	Annual	0093008124
Agilent	N9020A / Signal Analyzer	05/23/2019	Annual	MY51110085
Agilent	N9020A / Signal Analyzer	05/24/2019	Annual	MY52090906
Agilent	N9030A / Signal Analyzer	01/10/2019	Annual	MY49431210
Rohde & Schwarz	OSP 120 / Power Measurement Set	07/26/2018	Annual	101231
Agilent	N1911A / Power Meter	04/10/2019	Annual	MY45100523
Agilent	N1921A / Power Sensor	04/10/2019	Annual	MY52260025
Agilent	87300B / Directional Coupler	11/20/2018	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	05/24/2019	Annual	05001
Hewlett Packard	E3632A / DC Power Supply	06/26/2018	Annual	KR75303960
Agilent	8493C / Attenuator(10 dB)	07/10/2018	Annual	07560
Rohde & Schwarz	EMC32 / Software	N/A	N/A	N/A
HCT CO., LTD.	FCC WLAN&BT&BLE Conducted Test Software v3.0	N/A	N/A	N/A

Radiated Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Innco system	CO3000 / Controller(Antenna mast)	N/A	N/A	CO3000-4p
Innco system	MA4640/800-XP-EP / Antenna Position Tower	N/A	N/A	N/A
Audix	EM1000 / Controller	N/A	N/A	060520
Audix	Turn Table	N/A	N/A	N/A
Rohde & Schwarz	Loop Antenna	08/23/2018	Biennial	1513-175
Schwarzbeck	VULB 9168 / Hybrid Antenna	03/22/2019	Biennial	760
Schwarzbeck	VULB 9160 / TRILOG Antenna	08/09/2018	Biennial	9160-3368
Schwarzbeck	BBHA 9120D / Horn Antenna	08/01/2017	Biennial	1151
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	12/04/2017	Biennial	BBHA9170541
Rohde & Schwarz	FSP(9 kHz ~ 30 GHz) / Spectrum Analyzer	09/03/2018	Annual	100688
Rohde & Schwarz	FSV40-N / Spectrum Analyzer	09/28/2018	Annual	101068-SZ
Agilent	N9020A / Signal Analyzer	05/23/2019	Annual	MY51110085
Wainwright Instruments	WHK3.0/18G-10EF / High Pass Filter	05/23/2019	Annual	8
Wainwright Instruments	WHKX7.0/18G-8SS / High Pass Filter	05/03/2019	Annual	29
Wainwright Instruments	WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter	06/29/2018	Annual	2
Wainwright Instruments	WRCJV5100/5850-40/50-8EEK / Band Reject Filter	01/03/2019	Annual	2
Api tech.	18B-03 / Attenuator (3 dB)	06/04/2019	Annual	1
Agilent	8493C-10 / Attenuator(10 dB)	07/17/2018	Annual	08285
CERNEX	CBLU1183540 / Power Amplifier	07/10/2018	Annual	22964
CERNEX	CBL06185030 / Power Amplifier	07/10/2018	Annual	22965
CERNEX	CBL18265035 / Power Amplifier	01/03/2019	Annual	22966
CERNEX	CBL26405040 / Power Amplifier	06/29/2018	Annual	25956

Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

11. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-1905-FC037-P