

6.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) §27.53(g) §27.53(h) §27.53(m)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level for Band 41 is as noted in the Test Notes on the following page.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 v02r02 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW \geq 1% of the emission bandwidth
4. VBW \geq 3 x RBW
5. Detector = RMS
6. Number of sweep points \geq 2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-3. Test Instrument & Measurement Setup


Test Notes

Per 22.917(b), 24.238(a) and 27.53(h), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 63 of 142

Per 27.53(g) for operations in the 698-746 MHz band, in the 100 kHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 30 kHz may be employed to demonstrate compliance with the out-of-band emissions limit.

Per 27.53(m) for operations in the BRS/EBS bands, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz.



Plot 6-96. Lower Band Edge Plot (Band 12 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 64 of 142




Plot 6-97. Lower Extended Band Edge Plot (Band 12 – 1.4MHz QPSK – RB Size 6)




Plot 6-98. Upper Band Edge Plot (Band 12 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 65 of 142




Plot 6-99. Upper Extended Band Edge Plot (Band 12 – 1.4MHz QPSK – RB Size 6)




Plot 6-100. Lower Band Edge Plot (Band 12 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMT817P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 66 of 142



Plot 6-101. Lower Extended Band Edge Plot (Band 12 – 3.0MHz QPSK – RB Size 15)




Plot 6-102. Upper Band Edge Plot (Band 12 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMT817P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 67 of 142




Plot 6-103. Upper Extended Band Edge Plot (Band 12 – 3.0MHz QPSK – RB Size 15)




Plot 6-104. Lower Band Edge Plot (Band 12 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMT817P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 68 of 142



Plot 6-105. Lower Extended Band Edge Plot (Band 12 – 5.0MHz QPSK – RB Size 25)




Plot 6-106. Upper Band Edge Plot (Band 12 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 69 of 142




Plot 6-107. Upper Extended Band Edge Plot (Band 12 – 5.0MHz QPSK – RB Size 25)




Plot 6-108. Lower Band Edge Plot (Band 12 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 70 of 142



Plot 6-109. Upper Band Edge Plot (Band 12 – 10.0MHz QPSK – RB Size 50)



Plot 6-110. Lower Band Edge Plot (Band 5/26 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 71 of 142



Plot 6-111. Lower Extended Band Edge Plot (Band 5/26 – 1.4MHz QPSK – RB Size 6)




Plot 6-112. Upper Band Edge Plot (Band 5/26 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 72 of 142



Plot 6-113. Upper Extended Band Edge Plot (Band 5/26 – 1.4MHz QPSK – RB Size 6)




Plot 6-114. Lower Band Edge Plot (Band 5/26 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 73 of 142



Plot 6-115. Lower Extended Band Edge Plot (Band 5/26 – 3.0MHz QPSK – RB Size 15)




Plot 6-116. Upper Band Edge Plot (Band 5/26 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMT817P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 74 of 142




Plot 6-117. Upper Extended Band Edge Plot (Band 5/26 – Band 5 – 3.0MHz QPSK – RB Size 15)




Plot 6-118. Lower Band Edge Plot (Band 5/26 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMT817P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 75 of 142



Plot 6-119. Lower Extended Band Edge Plot (Band 5/26 – 5.0MHz QPSK – RB Size 25)




Plot 6-120. Upper Band Edge Plot (Band 5/26 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 76 of 142



Plot 6-121. Upper Extended Band Edge Plot (Band 5/26 – 5.0MHz QPSK – RB Size 25)




Plot 6-122. Lower Band Edge Plot (Band 5/26 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 77 of 142




Plot 6-123. Upper Band Edge Plot (Band 5/26 – 10.0MHz QPSK – RB Size 50)




Plot 6-124. Lower Band Edge Plot (Band 26 – 15.0MHz QPSK – RB Size 75)



FCC ID: A3LSMT817P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 78 of 142




Plot 6-125. Upper Band Edge Plot (Band 26 – 15.0MHz QPSK – RB Size 75)




Plot 6-126. Lower Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 79 of 142




Plot 6-127. Lower Extended Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)




Plot 6-128. Upper Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 80 of 142



Plot 6-129. Upper Extended Band Edge Plot (Band 4 – 1.4MHz QPSK – RB Size 6)



Plot 6-130. Lower Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 81 of 142




Plot 6-131. Lower Extended Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)




Plot 6-132. Upper Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMT817P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 82 of 142




Plot 6-133. Upper Extended Band Edge Plot (Band 4 – 3.0MHz QPSK – RB Size 15)



Plot 6-134. Lower Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMT817P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 83 of 142




Plot 6-135. Lower Extended Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)




Plot 6-136. Upper Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMT817P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 84 of 142




Plot 6-137. Upper Extended Band Edge Plot (Band 4 – 5.0MHz QPSK – RB Size 25)




Plot 6-138. Lower Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 85 of 142




Plot 6-139. Lower Extended Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)




Plot 6-140. Upper Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 86 of 142




Plot 6-141. Upper Extended Band Edge Plot (Band 4 – 10.0MHz QPSK – RB Size 50)




Plot 6-142. Lower Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 87 of 142




Plot 6-143. Lower Extended Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)




Plot 6-144. Upper Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 88 of 142




Plot 6-145. Upper Extended Band Edge Plot (Band 4 – 15.0MHz QPSK – RB Size 75)




Plot 6-146. Lower Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 89 of 142




Plot 6-147. Lower Extended Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)




Plot 6-148. Upper Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 90 of 142



Plot 6-149. Upper Extended Band Edge Plot (Band 4 – 20.0MHz QPSK – RB Size 100)




Plot 6-150. Lower Band Edge Plot (Band 2/25 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMT817P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 91 of 142



Plot 6-151. Lower Extended Band Edge Plot (Band 2/25 – 1.4MHz QPSK – RB Size 6)




Plot 6-152. Upper Band Edge Plot (Band 2/25 – 1.4MHz QPSK – RB Size 6)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 92 of 142




Plot 6-153. Upper Extended Band Edge Plot (Band 2/25 – 1.4MHz QPSK – RB Size 6)




Plot 6-154. Lower Band Edge Plot (Band 2/25 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 93 of 142




Plot 6-155. Lower Extended Band Edge Plot (Band 2/25 – 3.0MHz QPSK – RB Size 15)




Plot 6-156. Upper Band Edge Plot (Band 2/25 – 3.0MHz QPSK – RB Size 15)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 94 of 142




Plot 6-157. Upper Extended Band Edge Plot (Band 2/25 – 3.0MHz QPSK – RB Size 15)



Plot 6-158. Lower Band Edge Plot (Band 2/25 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMT817P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 95 of 142




Plot 6-159. Lower Extended Band Edge Plot (Band 2/25 – 5.0MHz QPSK – RB Size 25)




Plot 6-160. Upper Band Edge Plot (Band 2/25 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMT817P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 96 of 142




Plot 6-161. Upper Extended Band Edge Plot (Band 2/25 – 5.0MHz QPSK – RB Size 25)




Plot 6-162. Lower Band Edge Plot (Band 2/25 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 97 of 142




Plot 6-163. Lower Extended Band Edge Plot (Band 2/25 – 10.0MHz QPSK – RB Size 50)




Plot 6-164. Upper Band Edge Plot (Band 2/25 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 98 of 142




Plot 6-165. Upper Extended Band Edge Plot (Band 2/25 – 10.0MHz QPSK – RB Size 50)




Plot 6-166. Lower Band Edge Plot (Band 2/25 – 15.0MHz QPSK – RB Size 75)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 99 of 142




Plot 6-167. Lower Extended Band Edge Plot (Band 2/25 – 15.0MHz QPSK – RB Size 75)




Plot 6-168. Upper Band Edge Plot (Band 2/25 – 15.0MHz QPSK – RB Size 75)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 100 of 142




Plot 6-169. Upper Extended Band Edge Plot (Band 2/25 – 15.0MHz QPSK – RB Size 75)




Plot 6-170. Lower Band Edge Plot (Band 2/25 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 101 of 142




Plot 6-171. Lower Extended Band Edge Plot (Band 2/25 – 20.0MHz QPSK – RB Size 100)




Plot 6-172. Upper Band Edge Plot (Band 2/25 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 102 of 142




Plot 6-173. Upper Extended Band Edge Plot (Band 2/25 – 20.0MHz QPSK – RB Size 100)




Plot 6-174. Lower ACP Plot (Band 41 – 5.0MHz QPSK – RB Size 25)

FCC ID: A3LSMT817P	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 103 of 142




Plot 6-175. Upper ACP Plot (Band 41 – 5.0MHz QPSK – RB Size 25)




Plot 6-176. Lower ACP Plot (Band 41 – 10.0MHz QPSK – RB Size 50)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 104 of 142




Plot 6-177. Upper ACP Plot (Band 41 – 10.0MHz QPSK – RB Size 50)




Plot 6-178. Lower ACP Plot (Band 41 – 15.0MHz QPSK – RB Size 75)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 105 of 142




Plot 6-179. Upper ACP Plot (Band 41 – 15.0MHz QPSK – RB Size 75)



Plot 6-180. Lower ACP Plot (Band 41 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 106 of 142



Plot 6-181. Upper ACP Plot (Band 41 – 20.0MHz QPSK – RB Size 100)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 107 of 142

6.5 Peak-Average Ratio

§24.232(d)

Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

Test Procedure Used

KDB 971168 v02r02 – Section 5.7.1

Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-4. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 108 of 142




Plot 6-182. PAR Plot (Band 2/25 – 1.4MHz QPSK – RB Size 6)




Plot 6-183. PAR Plot (Band 2/25 – 1.4MHz 16-QAM – RB Size 6)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 109 of 142




Plot 6-184. PAR Plot (Band 2/25 – 3.0MHz QPSK – RB Size 15)




Plot 6-185. PAR Plot (Band 2/25 – 3.0MHz 16-QAM – RB Size 15)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 110 of 142




Plot 6-186. PAR Plot (Band 2/25 – 5.0MHz QPSK – RB Size 25)




Plot 6-187. PAR Plot (Band 2/25 – 5.0MHz 16-QAM – RB Size 25)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 111 of 142




Plot 6-188. PAR Plot (Band 2/25 – 10.0MHz QPSK – RB Size 50)




Plot 6-189. PAR Plot (Band 2/25 – 10.0MHz 16-QAM – RB Size 50)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 112 of 142




Plot 6-190. PAR Plot (Band 2/25 – 15.0MHz QPSK – RB Size 75)




Plot 6-191. PAR Plot (Band 2/25 – 15.0MHz 16-QAM – RB Size 75)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 113 of 142



Plot 6-192. PAR Plot (Band 2/25 – 20.0MHz QPSK – RB Size 100)



Plot 6-193. PAR Plot (Band 2/25 – 20.0MHz 16-QAM – RB Size 100)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 114 of 142

6.6 Radiated Power (ERP/EIRP)

§22.913(a.2) §24.232(c.2) §27.50(h.2) §27.50(c.10) §27.50(d.4)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.



Test Procedures Used

KDB 971168 v02r02 – Section 5.2.1

ANSI/TIA-603-C-2004 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer's "time domain power" measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW \geq 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points \geq 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the "gating" function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 115 of 142

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-5. Test Instrument & Measurement Setup



Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 116 of 142	

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	Ant. Pol. [H/V]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
699.70	1.4	QPSK	Standard	1 / 5	11.85	0.92	V	12.77	34.77	-22.00
707.50	1.4	QPSK	Standard	1 / 5	11.98	1.07	V	13.05	34.77	-21.72
715.30	1.4	QPSK	Standard	3 / 2	15.33	1.23	V	16.56	34.77	-18.22
699.70	1.4	16-QAM	Standard	1 / 5	10.80	0.92	V	11.72	34.77	-23.05
707.50	1.4	16-QAM	Standard	1 / 5	10.93	1.07	V	12.00	34.77	-22.77
715.30	1.4	16-QAM	Standard	3 / 2	14.45	1.23	V	15.68	34.77	-19.10
700.50	3	QPSK	Standard	1 / 14	14.42	0.92	V	15.34	34.77	-19.43
707.50	3	QPSK	Standard	1 / 14	14.53	1.07	V	15.60	34.77	-19.17
714.50	3	QPSK	Standard	1 / 0	14.81	1.21	V	16.02	34.77	-18.75
700.50	3	16-QAM	Standard	1 / 14	13.34	0.92	V	14.26	34.77	-20.51
707.50	3	16-QAM	Standard	1 / 14	14.06	1.07	V	15.13	34.77	-19.64
714.50	3	16-QAM	Standard	1 / 0	13.91	1.21	V	15.12	34.77	-19.65
701.50	5	QPSK	Standard	1 / 24	14.47	0.94	V	15.41	34.77	-19.36
707.50	5	QPSK	Standard	1 / 24	14.61	1.07	V	15.68	34.77	-19.09
713.50	5	QPSK	Standard	1 / 0	14.87	1.19	V	16.06	34.77	-18.71
701.50	5	16-QAM	Standard	1 / 24	13.36	0.94	V	14.30	34.77	-20.47
707.50	5	16-QAM	Standard	1 / 24	14.02	1.07	V	15.09	34.77	-19.68
713.50	5	16-QAM	Standard	1 / 0	14.02	1.19	V	15.21	34.77	-19.56
704.00	10	QPSK	Standard	1 / 49	14.42	1.00	V	15.42	34.77	-19.35
707.50	10	QPSK	Standard	1 / 49	14.53	1.07	V	15.60	34.77	-19.17
711.00	10	QPSK	Standard	1 / 0	14.81	1.14	V	15.95	34.77	-18.82
704.00	10	16-QAM	Standard	1 / 49	13.41	1.00	V	14.41	34.77	-20.36
707.50	10	16-QAM	Standard	1 / 49	14.03	1.07	V	15.10	34.77	-19.67
711.00	10	16-QAM	Standard	1 / 0	14.00	1.14	V	15.14	34.77	-19.63

Table 6-2. ERP Data (Band 12)



FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 117 of 142	

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	Ant. Pol. [H/V]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
824.70	1.4	QPSK	Standard	1 / 5	15.43	2.98	V	18.41	38.45	-20.04
836.50	1.4	QPSK	Standard	1 / 0	16.32	3.04	V	19.36	38.45	-19.09
848.30	1.4	QPSK	Standard	1 / 0	14.87	3.10	V	17.97	38.45	-20.48
824.70	1.4	16-QAM	Standard	1 / 5	14.27	2.98	V	17.25	38.45	-21.20
836.50	1.4	16-QAM	Standard	1 / 0	15.20	3.04	V	18.24	38.45	-20.21
848.30	1.4	16-QAM	Standard	1 / 0	13.94	3.10	V	17.04	38.45	-21.41
825.50	3	QPSK	Standard	1 / 14	15.51	2.98	V	18.49	38.45	-19.96
836.50	3	QPSK	Standard	1 / 0	16.40	3.04	V	19.44	38.45	-19.01
847.50	3	QPSK	Standard	1 / 0	15.03	3.10	V	18.13	38.45	-20.32
825.50	3	16-QAM	Standard	1 / 14	14.48	2.98	V	17.46	38.45	-20.99
836.50	3	16-QAM	Standard	1 / 0	15.33	3.04	V	18.37	38.45	-20.08
847.50	3	16-QAM	Standard	1 / 0	14.10	3.10	V	17.20	38.45	-21.25
826.50	5	QPSK	Standard	1 / 24	15.66	2.99	V	18.65	38.45	-19.80
836.50	5	QPSK	Standard	1 / 0	16.46	3.04	V	19.50	38.45	-18.95
846.50	5	QPSK	Standard	1 / 0	15.10	3.09	V	18.19	38.45	-20.26
826.50	5	16-QAM	Standard	1 / 24	14.59	2.99	V	17.58	38.45	-20.87
836.50	5	16-QAM	Standard	1 / 0	15.46	3.04	V	18.50	38.45	-19.95
846.50	5	16-QAM	Standard	1 / 0	14.21	3.09	V	17.30	38.45	-21.15
829.00	10	QPSK	Standard	1 / 49	15.60	3.00	V	18.60	38.45	-19.85
836.50	10	QPSK	Standard	1 / 25	16.44	3.04	V	19.48	38.45	-18.97
844.00	10	QPSK	Standard	1 / 0	15.07	3.08	V	18.15	38.45	-20.30
829.00	10	16-QAM	Standard	1 / 49	14.52	3.00	V	17.52	38.45	-20.93
836.50	10	16-QAM	Standard	1 / 25	15.41	3.04	V	18.45	38.45	-20.00
844.00	10	16-QAM	Standard	1 / 0	14.16	3.08	V	17.24	38.45	-21.21

Table 6-3. ERP Data (Band 5/26)


Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBd]	Ant. Pol. [H/V]	ERP [dBm]	ERP Limit [dBm]	Margin [dB]
831.50	15	QPSK	Standard	1 / 74	15.52	3.01	V	18.53	38.45	-19.92
836.50	15	QPSK	Standard	1 / 0	16.35	3.04	V	19.39	38.45	-19.06
841.50	15	QPSK	Standard	1 / 0	14.96	3.07	V	18.03	38.45	-20.42
831.50	15	16-QAM	Standard	1 / 74	14.47	3.01	V	17.48	38.45	-20.97
836.50	15	16-QAM	Standard	1 / 0	15.28	3.04	V	18.32	38.45	-20.13
841.50	15	16-QAM	Standard	1 / 0	14.00	3.07	V	17.07	38.45	-21.38

Table 6-4. ERP Data (Band 26)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 118 of 142	



Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	Ant. Pol. [H/V]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1710.70	1.4	QPSK	Standard	1 / 0	11.11	9.28	V	20.39	30.00	-9.61
1732.50	1.4	QPSK	Standard	1 / 0	10.80	9.00	V	19.80	30.00	-10.20
1754.30	1.4	QPSK	Standard	1 / 0	9.75	8.72	V	18.47	30.00	-11.53
1710.70	1.4	16-QAM	Standard	1 / 0	10.30	9.28	V	19.58	30.00	-10.42
1732.50	1.4	16-QAM	Standard	1 / 0	9.92	9.00	V	18.92	30.00	-11.08
1754.30	1.4	16-QAM	Standard	1 / 0	8.81	8.72	V	17.53	30.00	-12.47
1711.50	3	QPSK	Standard	1 / 0	11.35	9.27	V	20.62	30.00	-9.38
1732.50	3	QPSK	Standard	1 / 0	10.90	9.00	V	19.90	30.00	-10.10
1753.50	3	QPSK	Standard	1 / 0	9.99	8.73	V	18.72	30.00	-11.28
1711.50	3	16-QAM	Standard	1 / 0	10.53	9.27	V	19.80	30.00	-10.20
1732.50	3	16-QAM	Standard	1 / 0	10.04	9.00	V	19.04	30.00	-10.96
1753.50	3	16-QAM	Standard	1 / 0	9.14	8.73	V	17.87	30.00	-12.13
1712.50	5	QPSK	Standard	1 / 0	11.34	9.26	V	20.60	30.00	-9.40
1732.50	5	QPSK	Standard	1 / 0	10.90	9.00	V	19.90	30.00	-10.10
1752.50	5	QPSK	Standard	1 / 0	10.26	8.74	V	19.00	30.00	-11.00
1712.50	5	16-QAM	Standard	1 / 0	10.34	9.26	V	19.60	30.00	-10.40
1732.50	5	16-QAM	Standard	1 / 0	9.91	9.00	V	18.91	30.00	-11.09
1752.50	5	16-QAM	Standard	1 / 0	9.33	8.74	V	18.07	30.00	-11.93
1715.00	10	QPSK	Standard	1 / 25	11.57	9.22	V	20.79	30.00	-9.21
1732.50	10	QPSK	Standard	1 / 0	11.01	9.00	V	20.01	30.00	-9.99
1750.00	10	QPSK	Standard	1 / 25	10.36	8.77	V	19.13	30.00	-10.87
1715.00	10	16-QAM	Standard	1 / 25	10.46	9.22	V	19.68	30.00	-10.32
1732.50	10	16-QAM	Standard	1 / 0	10.07	9.00	V	19.07	30.00	-10.93
1750.00	10	16-QAM	Standard	1 / 25	9.48	8.77	V	18.25	30.00	-11.75
1717.50	15	QPSK	Standard	1 / 0	11.43	9.19	V	20.62	30.00	-9.38
1732.50	15	QPSK	Standard	1 / 0	10.90	9.00	V	19.90	30.00	-10.10
1747.50	15	QPSK	Standard	1 / 0	10.11	8.80	V	18.91	30.00	-11.09
1717.50	15	16-QAM	Standard	1 / 0	10.12	9.19	V	19.31	30.00	-10.69
1732.50	15	16-QAM	Standard	1 / 0	9.90	9.00	V	18.90	30.00	-11.10
1747.50	15	16-QAM	Standard	1 / 0	9.15	8.80	V	17.95	30.00	-12.05
1720.00	20	QPSK	Standard	1 / 0	11.52	9.16	V	20.68	30.00	-9.32
1732.50	20	QPSK	Standard	1 / 0	11.08	9.00	V	20.08	30.00	-9.92
1745.00	20	QPSK	Standard	1 / 0	10.22	8.83	V	19.05	30.00	-10.95
1720.00	20	16-QAM	Standard	1 / 0	10.38	9.16	V	19.54	30.00	-10.46
1732.50	20	16-QAM	Standard	1 / 0	9.97	9.00	V	18.97	30.00	-11.03
1745.00	20	16-QAM	Standard	1 / 0	9.25	8.83	V	18.08	30.00	-11.92

Table 6-5. EIRP Data (Band 4)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 119 of 142	



Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	Ant. Pol. [H/V]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
1850.70	1.4	QPSK	Standard	1 / 0	13.37	8.34	V	21.71	33.01	-11.30
1880.00	1.4	QPSK	Standard	1 / 0	13.54	8.46	V	22.00	33.01	-11.01
1909.30	1.4	QPSK	Standard	1 / 0	14.02	8.64	V	22.66	33.01	-10.35
1850.70	1.4	16-QAM	Standard	1 / 0	12.03	8.34	V	20.37	33.01	-12.64
1880.00	1.4	16-QAM	Standard	1 / 0	12.23	8.46	V	20.69	33.01	-12.32
1909.30	1.4	16-QAM	Standard	1 / 5	13.11	8.64	V	21.75	33.01	-11.26
1851.50	3	QPSK	Standard	1 / 0	13.45	8.35	V	21.80	33.01	-11.21
1880.00	3	QPSK	Standard	1 / 0	13.55	8.46	V	22.01	33.01	-11.00
1908.50	3	QPSK	Standard	1 / 14	14.24	8.63	V	22.87	33.01	-10.14
1851.50	3	16-QAM	Standard	1 / 0	12.24	8.35	V	20.59	33.01	-12.42
1880.00	3	16-QAM	Standard	1 / 0	12.45	8.46	V	20.91	33.01	-12.10
1908.50	3	16-QAM	Standard	1 / 14	13.38	8.63	V	22.01	33.01	-11.00
1852.50	5	QPSK	Standard	1 / 12	13.61	8.35	V	21.96	33.01	-11.05
1880.00	5	QPSK	Standard	1 / 0	13.66	8.46	V	22.12	33.01	-10.89
1907.50	5	QPSK	Standard	1 / 24	14.51	8.62	V	23.13	33.01	-9.88
1852.50	5	16-QAM	Standard	1 / 12	12.42	8.35	V	20.77	33.01	-12.24
1880.00	5	16-QAM	Standard	1 / 0	12.69	8.46	V	21.15	33.01	-11.86
1907.50	5	16-QAM	Standard	1 / 24	13.58	8.62	V	22.20	33.01	-10.81
1855.00	10	QPSK	Standard	1 / 0	13.57	8.36	V	21.93	33.01	-11.08
1880.00	10	QPSK	Standard	1 / 0	13.54	8.46	V	22.00	33.01	-11.01
1905.00	10	QPSK	Standard	1 / 49	14.45	8.59	V	23.04	33.01	-9.97
1855.00	10	16-QAM	Standard	1 / 0	12.38	8.36	V	20.74	33.01	-12.27
1880.00	10	16-QAM	Standard	1 / 0	12.65	8.46	V	21.11	33.01	-11.90
1905.00	10	16-QAM	Standard	1 / 49	13.46	8.59	V	22.05	33.01	-10.96
1857.50	15	QPSK	Standard	1 / 0	13.43	8.37	V	21.80	33.01	-11.21
1880.00	15	QPSK	Standard	1 / 0	13.44	8.46	V	21.90	33.01	-11.11
1902.50	15	QPSK	Standard	1 / 74	14.42	8.56	V	22.98	33.01	-10.03
1857.50	15	16-QAM	Standard	1 / 0	12.23	8.37	V	20.60	33.01	-12.41
1880.00	15	16-QAM	Standard	1 / 0	12.50	8.46	V	20.96	33.01	-12.05
1902.50	15	16-QAM	Standard	1 / 74	13.44	8.56	V	22.00	33.01	-11.01
1860.00	20	QPSK	Standard	1 / 0	13.35	8.38	V	21.73	33.01	-11.28
1880.00	20	QPSK	Standard	1 / 0	13.34	8.46	V	21.80	33.01	-11.21
1900.00	20	QPSK	Standard	1 / 99	14.38	8.53	V	22.91	33.01	-10.10
1860.00	20	16-QAM	Standard	1 / 0	12.02	8.38	V	20.40	33.01	-12.61
1880.00	20	16-QAM	Standard	1 / 0	12.44	8.46	V	20.90	33.01	-12.11
1900.00	20	16-QAM	Standard	1 / 99	13.29	8.53	V	21.82	33.01	-11.19

Table 6-6. EIRP Data (Band 2/25)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 120 of 142	

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Ant. Gain [dBi]	Ant. Pol. [H/V]	EIRP [dBm]	EIRP Limit [dBm]	Margin [dB]
2498.50	5	QPSK	Standard	1 / 0	11.59	7.09	V	18.68	33.01	-14.33
2593.00	5	QPSK	Standard	1 / 12	14.32	7.55	V	21.87	33.01	-11.14
2687.50	5	QPSK	Standard	1 / 0	12.54	7.82	V	20.36	33.01	-12.65
2498.50	5	16-QAM	Standard	1 / 0	10.65	7.09	V	17.74	33.01	-15.27
2593.00	5	16-QAM	Standard	1 / 12	13.16	7.55	V	20.71	33.01	-12.30
2687.50	5	16-QAM	Standard	1 / 0	11.51	7.82	V	19.33	33.01	-13.68
2501.00	10	QPSK	Standard	1 / 0	11.45	7.08	V	18.53	33.01	-14.48
2593.00	10	QPSK	Standard	1 / 0	14.15	7.55	V	21.70	33.01	-11.31
2685.00	10	QPSK	Standard	1 / 0	12.44	7.81	V	20.25	33.01	-12.76
2501.00	10	16-QAM	Standard	1 / 0	10.52	7.08	V	17.60	33.01	-15.41
2593.00	10	16-QAM	Standard	1 / 0	13.17	7.55	V	20.72	33.01	-12.29
2685.00	10	16-QAM	Standard	1 / 0	11.41	7.81	V	19.22	33.01	-13.79
2503.50	15	QPSK	Standard	1 / 37	11.67	7.10	V	18.77	33.01	-14.24
2593.00	15	QPSK	Standard	1 / 37	14.16	7.55	V	21.71	33.01	-11.30
2682.50	15	QPSK	Standard	1 / 0	13.28	7.81	V	21.09	33.01	-11.92
2503.50	15	16-QAM	Standard	1 / 37	10.46	7.10	V	17.56	33.01	-15.45
2593.00	15	16-QAM	Standard	1 / 37	12.36	7.55	V	19.91	33.01	-13.10
2682.50	15	16-QAM	Standard	1 / 0	11.50	7.81	V	19.31	33.01	-13.70
2506.00	20	QPSK	Standard	1 / 0	11.44	7.11	V	18.55	33.01	-14.46
2593.00	20	QPSK	Standard	1 / 0	14.06	7.55	V	21.61	33.01	-11.40
2680.00	20	QPSK	Standard	1 / 0	13.25	7.80	V	21.05	33.01	-11.96
2506.00	20	16-QAM	Standard	1 / 0	10.34	7.11	V	17.45	33.01	-15.56
2593.00	20	16-QAM	Standard	1 / 0	12.17	7.55	V	19.72	33.01	-13.29
2680.00	20	16-QAM	Standard	1 / 0	11.39	7.80	V	19.19	33.01	-13.82

Table 6-7. EIRP Data (Band 41)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 121 of 142	

6.7 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a) §24.238(a) §27.53(g) §27.53(h) §27.53(m)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-C-2004 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 v02r02 – Section 5.8

ANSI/TIA-603-C-2004 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-6. Test Instrument & Measurement Setup

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 122 of 142



Test Notes

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.
- 3) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 4) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.

OPERATING FREQUENCY: 699.70 MHz
 CHANNEL: 23017
 MEASURED OUTPUT POWER: 12.77 dBm = 0.019 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 25.77 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1399.40	-67.03	5.64	-61.39	H	74.2
2099.10	-66.02	6.61	-59.42	H	72.2
2798.80	-68.92	7.84	-61.08	H	73.9

Table 6-8. Radiated Spurious Data (Band 12 – Low Channel)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 123 of 142	

OPERATING FREQUENCY: 707.50 MHz
 CHANNEL: 23095
 MEASURED OUTPUT POWER: 13.05 dBm = 0.020 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 26.05 dBc



Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1415.00	-64.43	5.73	-58.69	H	71.7
2122.50	-65.95	6.73	-59.22	H	72.3
2830.00	-68.59	7.80	-60.79	H	73.8

Table 6-9. Radiated Spurious Data (Band 12 – Mid Channel)

OPERATING FREQUENCY: 715.30 MHz
 CHANNEL: 23173
 MEASURED OUTPUT POWER: 16.56 dBm = 0.045 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 1.4 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 29.56 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1430.60	-67.56	5.82	-61.74	H	78.3
2145.90	-66.41	6.86	-59.56	H	76.1
2861.20	-68.54	7.75	-60.78	H	77.3

Table 6-10. Radiated Spurious Data (Band 12 – High Channel)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 124 of 142	

OPERATING FREQUENCY: 826.50 MHz
 CHANNEL: 26815
 MEASURED OUTPUT POWER: 18.65 dBm = 0.073 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 31.65 dBc



Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1653.00	-67.41	6.56	-60.85	H	79.5
2479.50	-67.51	7.31	-60.20	H	78.9
3306.00	-66.05	7.38	-58.67	H	77.3

Table 6-11. Radiated Spurious Data (Band 5/26 – Low Channel)

OPERATING FREQUENCY: 836.50 MHz
 CHANNEL: 26915
 MEASURED OUTPUT POWER: 19.50 dBm = 0.089 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 32.50 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1673.00	-67.62	6.55	-61.07	H	80.6
2509.50	-66.99	7.34	-59.64	H	79.1
3346.00	-65.45	7.44	-58.01	H	77.5

Table 6-12. Radiated Spurious Data (Band 5/26 – Mid Channel)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 125 of 142	

OPERATING FREQUENCY: 846.50 MHz
 CHANNEL: 27015
 MEASURED OUTPUT POWER: 18.19 dBm = 0.066 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 31.19 dBc



Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBd]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
1693.00	-67.38	6.55	-60.83	H	79.0
2539.50	-66.73	7.36	-59.37	H	77.6
3386.00	-65.24	7.50	-57.74	H	75.9

Table 6-13. Radiated Spurious Data (Band 5/26 – High Channel)

OPERATING FREQUENCY: 1715.00 MHz
 CHANNEL: 20000
 MEASURED OUTPUT POWER: 20.79 dBm = 0.120 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 33.79 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3430.00	-62.81	9.69	-53.12	H	73.9
5145.00	-61.29	10.67	-50.62	H	71.4
6860.00	-60.73	11.74	-48.99	H	69.8

Table 6-14. Radiated Spurious Data (Band 4 – Low Channel)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 126 of 142	

OPERATING FREQUENCY: 1732.50 MHz
 CHANNEL: 20175
 MEASURED OUTPUT POWER: 20.01 dBm = 0.100 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 33.01 dBc



Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3465.00	-62.63	9.71	-52.93	H	72.9
5197.50	-60.52	10.59	-49.93	H	69.9
6930.00	-60.24	11.75	-48.49	H	68.5

Table 6-15. Radiated Spurious Data (Band 4 – Mid Channel)

OPERATING FREQUENCY: 1750.00 MHz
 CHANNEL: 20350
 MEASURED OUTPUT POWER: 19.13 dBm = 0.082 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 32.13 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3500.00	-62.64	9.73	-52.91	H	72.0
5250.00	-60.87	10.63	-50.24	H	69.4
7000.00	-59.93	11.76	-48.18	H	67.3

Table 6-16. Radiated Spurious Data (Band 4 – High Channel)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 127 of 142	

OPERATING FREQUENCY: 1852.50 MHz
 CHANNEL: 18625
 MEASURED OUTPUT POWER: 21.96 dBm = 0.157 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 34.96 dBc



Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3705.00	-57.89	9.43	-48.47	H	70.4
5557.50	-54.98	10.80	-44.18	H	66.1
7410.00	-55.48	10.71	-44.77	H	66.7

Table 6-17. Radiated Spurious Data (Band 2/25 – Low Channel)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 18900
 MEASURED OUTPUT POWER: 22.12 dBm = 0.163 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 35.12 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3760.00	-59.68	9.28	-50.40	H	72.5
5640.00	-57.86	11.03	-46.82	H	68.9
7520.00	-55.27	10.97	-44.30	H	66.4

Table 6-18. Radiated Spurious Data (Band 2/25 – Mid Channel)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 128 of 142	

OPERATING FREQUENCY: 1907.50 MHz
 CHANNEL: 19175
 MEASURED OUTPUT POWER: 23.13 dBm = 0.206 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 36.13 dBc



Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
3815.00	-57.19	9.19	-48.00	H	71.1
5722.50	-54.95	11.27	-43.68	H	66.8
7630.00	-56.64	11.17	-45.47	H	68.6

Table 6-19. Radiated Spurious Data (Band 2/25 – High Channel)

OPERATING FREQUENCY: 2498.50 MHz
 CHANNEL: 39675
 MEASURED OUTPUT POWER: 18.68 dBm = 0.074 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $55 + 10 \log_{10}(W) =$ 43.68 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
4997.00	-62.20	10.93	-51.27	H	69.9
7495.50	-56.40	10.92	-45.48	H	64.2
9994.00	-54.24	12.02	-42.21	H	60.9

Table 6-20. Radiated Spurious Data (Band 41 – Low Channel)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 129 of 142	

OPERATING FREQUENCY: 2593.00 MHz
 CHANNEL: 40620
 MEASURED OUTPUT POWER: 21.87 dBm = 0.154 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $55 + 10 \log_{10}(W) =$ 46.87 dBc



Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
5186.00	-59.61	10.60	-49.01	H	70.9
7779.00	-55.75	11.22	-44.53	H	66.4
10372.00	-52.79	12.36	-40.44	H	62.3

Table 6-21. Radiated Spurious Data (Band 41 – Mid Channel)

OPERATING FREQUENCY: 2687.50 MHz
 CHANNEL: 41565
 MEASURED OUTPUT POWER: 20.36 dBm = 0.109 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 5.0 MHz
 DISTANCE: 3 meters
 LIMIT: $55 + 10 \log_{10}(W) =$ 45.36 dBc

Frequency [MHz]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Ant. Pol. [H/V]	[dBc]
5375.00	-60.94	10.58	-50.36	H	70.7
8062.50	-55.26	11.10	-44.16	H	64.5
10750.00	-53.48	12.60	-40.88	H	61.2

Table 6-22. Radiated Spurious Data (Band 41 – High Channel)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 130 of 142	

6.8 Frequency Stability / Temperature Variation

§2.1055 §22.355 §24.235 §27.54

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-C-2004. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24 and Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI/TIA-603-C-2004

Test Settings



1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 131 of 142

Band 12 Frequency Stability Measurements

§2.1055 §27.54



OPERATING FREQUENCY: 707,500,000 Hz
 CHANNEL: 23790
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	707,500,154	154	0.0000218
100 %		- 30	707,499,654	-346	-0.0000489
100 %		- 20	707,500,077	77	0.0000109
100 %		- 10	707,500,193	193	0.0000273
100 %		0	707,500,055	55	0.0000078
100 %		+ 10	707,499,750	-250	-0.0000353
100 %		+ 20	707,499,953	-47	-0.0000066
100 %		+ 30	707,499,686	-314	-0.0000444
100 %		+ 40	707,500,141	141	0.0000199
100 %		+ 50	707,500,008	8	0.0000011
BATT. ENDPOINT	3.45	+ 20	707,500,073	73	0.0000103

Table 6-23. Frequency Stability Data (Band 12)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 132 of 142	

Band 12 Frequency Stability Measurements
§2.1055 §27.54






Figure 6-7. Frequency Stability Graph (Band 12)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 133 of 142	



Band 5/26 Frequency Stability Measurements

§2.1055 §22.355

OPERATING FREQUENCY: 831,500,000 Hz
 CHANNEL: 26865
 REFERENCE VOLTAGE: 3.85 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	831,499,812	-188	-0.0000226
100 %		- 30	831,500,055	55	0.0000066
100 %		- 20	831,499,929	-71	-0.0000085
100 %		- 10	831,499,881	-119	-0.0000143
100 %		0	831,500,060	60	0.0000072
100 %		+ 10	831,500,008	8	0.0000010
100 %		+ 20	831,499,635	-365	-0.0000439
100 %		+ 30	831,500,091	91	0.0000109
100 %		+ 40	831,500,170	170	0.0000204
100 %		+ 50	831,500,162	162	0.0000195
BATT. ENDPOINT	3.45	+ 20	831,500,126	126	0.0000152

Table 6-24. Frequency Stability Data (Band 5/26)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 134 of 142	

Band 5/26 Frequency Stability Measurements
§2.1055 §22.355




Figure 6-8. Frequency Stability Graph (Band 5/26)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 135 of 142	

Band 4 Frequency Stability Measurements

§2.1055 §§27.54



OPERATING FREQUENCY: 1,732,500,000 Hz
 CHANNEL: 20175
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,732,500,119	119	0.0000069
100 %		- 30	1,732,499,891	-109	-0.0000063
100 %		- 20	1,732,500,338	338	0.0000195
100 %		- 10	1,732,499,882	-118	-0.0000068
100 %		0	1,732,500,203	203	0.0000117
100 %		+ 10	1,732,500,051	51	0.0000029
100 %		+ 20	1,732,500,060	60	0.0000035
100 %		+ 30	1,732,500,188	188	0.0000109
100 %		+ 40	1,732,500,118	118	0.0000068
100 %		+ 50	1,732,499,998	-2	-0.0000001
BATT. ENDPOINT		3.45	+ 20	1,732,499,844	-156

Table 6-25. Frequency Stability Data (Band 4)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 136 of 142	

Band 4 Frequency Stability Measurements
§2.1055 §§27.54




Figure 6-9. Frequency Stability Graph (Band 4)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 137 of 142

Band 2/25 Frequency Stability Measurements

§2.1055 §24.235



OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 18900
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,880,000,316	316	0.0000168
100 %		- 30	1,880,000,290	290	0.0000154
100 %		- 20	1,879,999,972	-28	-0.0000015
100 %		- 10	1,880,000,014	14	0.0000007
100 %		0	1,880,000,024	24	0.0000013
100 %		+ 10	1,880,000,204	204	0.0000109
100 %		+ 20	1,880,000,068	68	0.0000036
100 %		+ 30	1,880,000,029	29	0.0000015
100 %		+ 40	1,880,000,157	157	0.0000084
100 %		+ 50	1,879,999,713	-287	-0.0000153
BATT. ENDPOINT	3.45	+ 20	1,879,999,744	-256	-0.0000136

Table 6-26. Frequency Stability Data (Band 2/25)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 138 of 142	

Band 2/25 Frequency Stability Measurements
§2.1055 §24.235






Figure 6-10. Frequency Stability Graph (Band 2/25)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 139 of 142	

Band 41 Frequency Stability Measurements

§2.1055 §27.54



OPERATING FREQUENCY: 2,593,000,000 Hz
 CHANNEL: 40620
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	2,592,999,861	-139	-0.0000054
100 %		- 30	2,593,000,130	130	0.0000050
100 %		- 20	2,592,999,753	-247	-0.0000095
100 %		- 10	2,593,000,313	313	0.0000121
100 %		0	2,592,999,906	-94	-0.0000036
100 %		+ 10	2,593,000,372	372	0.0000143
100 %		+ 20	2,592,999,821	-179	-0.0000069
100 %		+ 30	2,592,999,976	-24	-0.0000009
100 %		+ 40	2,592,999,579	-421	-0.0000162
100 %		+ 50	2,593,000,084	84	0.0000032
BATT. ENDPOINT	3.45	+ 20	2,592,999,961	-39	-0.0000015

Table 6-27. Frequency Stability Data (Band 41)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 140 of 142	

Band 41 Frequency Stability Measurements
§2.1055 §27.54






Figure 6-11. Frequency Stability Graph (Band 41)

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet		Page 141 of 142

7.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Tablet FCC ID: A3LSMT817P** complies with all the requirements of Parts 22, 24, & 27 of the FCC rules for LTE operation only.

FCC ID: A3LSMT817P		FCC Pt. 22, 24, & 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1507071382.A3L	Test Dates: 7/7 - 7/29/2015	EUT Type: Portable Tablet	Page 142 of 142	