



FCC CFR47 PART 15 SUBPART C

Bluetooth

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE Tablet + Bluetooth/BLE, DTS/UNII a/b/g/n/ac and ANT+

MODEL NUMBER : SM-T825C

FCC ID: A3LSMT825C

REPORT NUMBER: 4787821324-E3V2

ISSUE DATE: MAR 13, 2017

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Prepared by
UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	02/24/17	Initial issue	Junwhan Lee
V2	03/13/17	Revised section 10	Junwhan Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	6
4.2. <i>SAMPLE CALCULATION</i>	6
4.3. <i>MEASUREMENT UNCERTAINTY</i>	6
5. EQUIPMENT UNDER TEST	7
5.1. <i>DESCRIPTION OF EUT</i>	7
5.2. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	7
5.3. <i>WORST-CASE CONFIGURATION AND MODE</i>	7
5.4. <i>DESCRIPTION OF TEST SETUP</i>	8
6. TEST AND MEASUREMENT EQUIPMENT	10
7. REFERENCE MEASUREMENT RESULTS	11
7.1. <i>20 dB AND 99% BANDWIDTH</i>	11
7.1.1. <i>BASIC DATA RATE GFSK MODULATION</i>	11
7.1.2. <i>ENHANCED DATA RATE Pi/4-DQPSK MODULATION</i>	11
7.1.3. <i>ENHANCED DATA RATE 8PSK MODULATION</i>	11
7.1.4. <i>20 dB AND 99% BANDWIDTH PLOTS</i>	12
8. SUMMARY TABLE	15
9. ANTENNA PORT TEST RESULTS	16
9.1. <i>HOPPING FREQUENCY SEPARATION</i>	16
9.2. <i>NUMBER OF HOPPING CHANNELS</i>	17
9.3. <i>AVERAGE TIME OF OCCUPANCY</i>	19
9.4. <i>OUTPUT POWER</i>	23
9.4.1. <i>BASIC DATA RATE GFSK MODULATION</i>	23
9.4.2. <i>ENHANCED DATA RATE Pi/4-DPSK MODULATION</i>	23
9.4.3. <i>ENHANCED DATA RATE 8PSK MODULATION</i>	23
9.4.4. <i>OUTPUT POWER PLOTS</i>	24
9.5. <i>AVERAGE POWER</i>	27
9.5.1. <i>BASIC DATA RATE GFSK MODULATION</i>	27
9.5.2. <i>DATA RATE PI/4-DQPSK MODULATION</i>	27
9.5.3. <i>ENHANCED DATA RATE 8PSK MODULATION</i>	27
9.6. <i>CONDUCTED SPURIOUS EMISSIONS</i>	28
9.6.1. <i>BASIC DATA RATE GFSK MODULATION</i>	29

10. RADIATED TEST RESULTS	41
10.1. LIMITS AND PROCEDURE.....	41
10.2. TRANSMITTER ABOVE 1 GHz.....	43
10.2.1. BASIC DATA RATE GFSK MODULATION.....	43
10.2.2. ENHANCED DATA RATE 8PSK MODULATION.....	53
10.3. WORST-CASE BELOW 1 GHz.....	63
11. AC POWER LINE CONDUCTED EMISSIONS	65
12. SETUP PHOTOS	70

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: GSM/WCDMA/LTE Tablet + Bluetooth/BLE, DTS/UNII a/b/g/n/ac and ANT+
MODEL NUMBER: SM-T825C
SERIAL NUMBER: R22HC00979E, R22HC0097BK (RADIATED);
R22HC00975D, R22HC00QNAA (CONDUCTED)
DATE TESTED: JAN 24, 2017 - JAN 31, 2017

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:

Tested By:



SungGil Park
Suwon Lab Engineer
UL Korea, Ltd.



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. FCC DA 00-705 Filling and measurement guidelines for FHSS systems
4. ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
<input checked="" type="checkbox"/>	Chamber 1
<input type="checkbox"/>	Chamber 2

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	4.14 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Tablet + Bluetooth/BLE, DTS/UNII a/b/g/n/ac and ANT+. This test report addresses the DSS (BT) operational mode.

The transmitter has a maximum conducted output power as follows:

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2402 - 2480	Basic GFSK	Average	8.745	7.490
		Peak	9.055	8.045
	Enhanced Pi/4-DPSK	Average	5.671	3.691
		Peak	8.030	6.353
	Enhanced 8PSK	Average	5.672	3.691
		Peak	8.540	7.145

5.2. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an internal antenna, with a maximum gain of -1.83 dBi.

5.3. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.

Note: GFSK, Pi/4-DQPSK, 8PSK average Power are all investigated, The GFSK & 8PSK Power are the worst case. Testing is based on this mode to showing compliance. For average power data please refer to section 9.5.

5.4. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Adapter	SAMSUNG	EP-TA200	R37HB5B0CH1SE3	N/A
Data Cable	SAMSUNG	EP-DN930CWE	N/A	N/A
Earphone	SAMSUNG	EO-EG920BW	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	C Type USB	Shielded	1.2m	N/A
2	Audio	2	Mini-Jack	Unshielded	1.1m	N/A

TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests.
Test software in hidden menu exercised the EUT to enable BT communications.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	10-14-18
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	04-25-17
Antenna, Horn, 18 GHz	ETS	3115	00167211	10-14-18
Antenna, Horn, 18 GHz	ETS	3115	00161451	03-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168724	06-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168717	06-17-17
Antenna, Horn, 40 GHz	ETS	3116C	00166155	11-30-17
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	12-15-17
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	11-25-17
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-17-17
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-16-17
Preamplifier	ETS	3115-PA	00167475	08-17-17
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-16-17
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-17-17
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-16-17
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	08-18-17
Average Power Sensor	R&S	NRP-Z91	102681	08-16-17
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-17-17
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-17-17
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-16-17
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-16-17
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	08-17-17
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	08-16-17
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	08-17-17
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	08-16-17
High Pass Filter 6GHz	Micro-Tronics	HPM17542	009	08-17-17
High Pass Filter 6GHz	Micro-Tronics	HPM17542	016	08-16-17
LISN	R&S	ENV-216	101836	08-16-17
LISN	R&S	ENV-216	101837	08-16-17
Attenuator	PASTERNAK	PE7087-10	A009	08-16-17
Combiner	WEINSHEL	1575	2151	08-17-17
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	

7. REFERENCE MEASUREMENT RESULTS

7.1. 20 dB AND 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to \geq 1% of the 20 dB bandwidth. The VBW is set to \geq RBW. The sweep time is coupled.

RESULTS

7.1.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	20 dB Bandwidth [KHz]	99% Bandwidth [KHz]
Low	2402	891.200	896.890
Mid	2441	970.000	927.680
High	2480	970.100	901.090
Worst		970.100	927.680

7.1.2. ENHANCED DATA RATE Pi/4-DQPSK MODULATION


Channel	Frequency [MHz]	20 dB Bandwidth [MHz]	99% Bandwidth [MHz]
Low	2402	1.241	1.164
Mid	2441	1.241	1.131
High	2480	1.251	1.163
Worst		1.251	1.164

7.1.3. ENHANCED DATA RATE 8PSK MODULATION


Channel	Frequency [MHz]	20 dB Bandwidth [MHz]	99% Bandwidth [MHz]
Low	2402	1.265	1.162
Mid	2441	1.265	1.163
High	2480	1.267	1.131
Worst		1.267	1.163

7.1.4. 20 dB AND 99% BANDWIDTH PLOTS


GFSK BANDWIDTH



Pi/4-DQPSK BANDWIDTH



8PSK BANDWIDTH



8. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Worst Case
2.1051, 15.247 (d)	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-38.653 dBm
15.247 (b)(1)	TX conducted output power	<21dBm		Pass	9.055 dBm (Peak)
15.247 (a)(1)	Hopping frequency separation	> 25KHz		Pass	1 MHz
15.247 (a)(1)(iii)	Number of Hopping channels	More than 15 non-overlapping channels		Pass	79
15.247 (a)(1)(iii)	Avg Time of Occupancy	< 0.4sec		Pass	0.34584 sec
15.207 (a)	AC Power Line conducted emissions	Section 10	Power Line conducted	Pass	40.68 dBuV (Qp)
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m	Radiated	Pass	41.76 dBuV/m (Av)

9. ANTENNA PORT TEST RESULTS

9.1. HOPPING FREQUENCY SEPARATION

LIMIT

FCC §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

HOPPING FREQUENCY SEPARATION PLOT



9.2. NUMBER OF HOPPING CHANNELS

LIMIT

FCC §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.

TEST PROCEDURE


DA 00-705: The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.


RESULTS

Normal Mode: 79 Channels observed.

NUMBER OF HOPPING CHANNELS PLOTS

NUMBER OF HOPPING CHANNELS (100 MHz SPAN)





9.3. AVERAGE TIME OF OCCUPANCY

LIMIT

FCC §15.247 (a) (1) (iii)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.


The average time of occupancy in the specified 31.6 second period (79 channels * 0.4 s) is equal to $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{ pulse width}$.

For AFH mode, the average time of occupancy in the specified 8 second period (20 channels * 0.4 seconds) is equal to $10 * (\# \text{ of pulses in } 0.8 \text{ s}) * \text{ pulse width}$.


RESULTS

DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK Normal					
DH1	0.378	32	0.121024	0.4	-0.2790
DH3	1.634	17	0.277780	0.4	-0.1222
DH5	2.882	12	0.345840	0.4	-0.0542
GFSK AFH					
DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK AFH					
DH1	0.378	8	0.030256	0.4	-0.36974
DH3	1.634	4.25	0.069445	0.4	-0.33056
DH5	2.882	3	0.086460	0.4	-0.31354


DH1



DH3



DH5



9.4. OUTPUT POWER

LIMIT

§15.247 (b) (1)

The maximum antenna gain is less than 6 dBi, therefore the limit is 21 dBm.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

RESULTS

9.4.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	Output Power [dBm]	Limit [dBm]	Margin [dB]
Low	2402	9.028	21	-11.972
Middle	2441	9.055	21	-11.945
High	2480	8.635	21	-12.365
Worst		9.055	21	-11.945

9.4.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION

Channel	Frequency [MHz]	Output Power [dBm]	Limit [dBm]	Margin [dB]
Low	2402	8.020	21	-12.980
Middle	2441	8.030	21	-12.970
High	2480	7.600	21	-13.400
Worst		8.030	21	-12.970

9.4.3. ENHANCED DATA RATE 8PSK MODULATION


Channel	Frequency [MHz]	Output Power [dBm]	Limit [dBm]	Margin [dB]
Low	2402	8.537	21	-12.463
Middle	2441	8.540	21	-12.460
High	2480	8.088	21	-12.912
Worst		8.540	21	-12.460

9.4.4. OUTPUT POWER PLOTS


GFSK OUTPUT POWER

<p>GFSK Low CH</p>	<p>Key parameters for GFSK Low CH:</p> <ul style="list-style-type: none"> Center: 2.402000 GHz Res BW: 3.0 MHz Span: 10.00 MHz VBW: 50 MHz Sweep: 1.333 ms (20001 pts) Peak Power (Mkr1): 2.4021335 GHz, 9.028 dBm
<p>GFSK Middle CH</p>	<p>Key parameters for GFSK Middle CH:</p> <ul style="list-style-type: none"> Center: 2.441000 GHz Res BW: 3.0 MHz Span: 10.00 MHz VBW: 50 MHz Sweep: 1.333 ms (20001 pts) Peak Power (Mkr1): 2.4410475 GHz, 9.055 dBm
<p>GFSK High CH</p>	<p>Key parameters for GFSK High CH:</p> <ul style="list-style-type: none"> Center: 2.480000 GHz Res BW: 3.0 MHz Span: 10.00 MHz VBW: 50 MHz Sweep: 1.333 ms (20001 pts) Peak Power (Mkr1): 2.4800960 GHz, 8.635 dBm

Pi/4-DPSK OUTPUT POWER



8PSK OUTPUT POWER



9.5. AVERAGE POWER

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss was entered as an offset in the power meter to allow for direct reading of power.

9.5.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2402	8.714	7.44
Middle	2441	8.745	7.49
High	2480	8.325	6.80

9.5.2. DATA RATE PI/4-DQPSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2402	5.671	3.69
Middle	2441	5.633	3.66
High	2480	5.182	3.30

9.5.3. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2402	5.672	3.69
Middle	2441	5.643	3.67
High	2480	5.188	3.30

9.6. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

Limit = -20 dBc

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.


RESULTS

9.6.1. BASIC DATA RATE GFSK MODULATION

GFSK Mode









BandEdge Emission at GFSK Hopping Mode


[GFSK Hopping Mode] Low Channel BandEdge





[GFSK Hopping Mode] High Channel BandEdge



PI/4-DQPSK Mode









BandEdge Emission at PI/4-DQPSK Hopping Mode


[PI/4-DQPSK Hopping Mode] Low Channel BandEdge






[PI/4-DQPSK Hopping Mode] High Channel BandEdge



8PSK Mode









BandEdge Emission at 8PSK Hopping Mode

[8PSK Hopping Mode] Low Channel BandEdge



[8PSK Hopping Mode] High Channel BandEdge



10. RADIATED TEST RESULTS

10.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements.(Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 KHz for peak measurements.)

For band edge measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 1/T (on time) for average measurement.

$$\text{GFSK} = 1/T = 1 / 0.0029\text{S} = 350\text{Hz}.$$

The minimum VBW was 350Hz, but test receiver(ESU40) couldn't set value 350Hz. Due to this reason, testing VBW was set to 500Hz(Worst cases).

The spectrum from 1GHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.
(From 30MHz to 1GHz, test was performed with the EUT set to transmit at the channel with highest output power)

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.


Note : Emission was pre-scanned from 9KHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit (consider distance correction factor).
Per FCC part 15.31(o), test results were not reported.

10.2. TRANSMITTER ABOVE 1 GHz

10.2.1. BASIC DATA RATE GFSK MODULATION

RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	10dB[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	45.44	Pk	31.8	-28.4	48.84	-	-	74	-25.16	246	130	H
2	* 2.372	49.77	PK	31.8	-28.5	53.07	-	-	74	-20.93	246	130	H
3	* 2.39	36.23	VA1T	31.8	-28.4	39.63	54	-14.37	-	-	246	130	H
4	* 2.345	36.89	VA1T	31.7	-28.5	40.09	54	-13.91	-	-	246	130	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average $V_B=1/T_{on}$ where: T_{on} is transmit duration

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	10dB[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	47.02	Pk	31.8	-28.4	50.42	-	-	74	-23.58	285	230	V
2	* 2.361	49.49	Pk	31.7	-28.4	52.79	-	-	74	-21.21	285	230	V
3	* 2.39	36.02	VA1T	31.8	-28.4	39.42	54	-14.58	-	-	285	230	V
4	* 2.385	36.8	VA1T	31.8	-28.5	40.1	54	-13.9	-	-	285	230	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average $VB=1/Ton$ where: Ton is transmit duration

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	10dB[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	54.01	Pk	32	-28.3	57.71	-	-	74	-16.29	241	147	H
2	* 2.484	55.34	Pk	32	-28.3	59.04	-	-	74	-14.96	241	147	H
3	* 2.484	37.05	VA1T	32	-28.3	40.75	54	-13.25	-	-	241	147	H
4	* 2.486	38.06	VA1T	32	-28.3	41.76	54	-12.24	-	-	241	147	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average $V_B=1/T_{on}$ where: T_{on} is transmit duration

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	10dB[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	51.81	Pk	32	-28.3	55.51	-	-	74	-18.49	240	149	V
2	* 2.484	52.91	Pk	32	-28.3	56.61	-	-	74	-17.39	240	149	V
3	* 2.484	36.53	VA1T	32	-28.3	40.23	54	-13.77	-	-	240	149	V
4	* 2.486	36.8	VA1T	32	-28.3	40.5	54	-13.5	-	-	240	149	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector


VA1T - FHSS: Linear Voltage Average $V_B=1/T_{on}$ where: T_{on} is transmit duration

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	3GHz_HP[d B]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.803	35.14	Pk	34	-33.5	35.64	-	-	74	-38.36	0-360	250	H
3	7.205	33.59	Pk	35.7	-30.6	38.69	-	-	74	-35.31	0-360	150	H
5	9.61	30.4	Pk	37	-27.4	40	-	-	74	-34	0-360	250	H
2	* 4.804	35.47	Pk	34	-33.5	35.97	-	-	74	-38.03	0-360	150	V
4	7.204	33.23	Pk	35.7	-30.6	38.33	-	-	74	-35.67	0-360	250	V
6	9.607	31.01	Pk	37	-27.4	40.61	-	-	74	-33.39	0-360	250	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


Pk – Peak detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	3GHz_HP[d B]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.883	35.26	Pk	34	-33.5	35.76	-	-	74	-38.24	0-360	150	H
3	* 7.323	34.92	Pk	35.8	-30.6	40.12	-	-	74	-33.88	0-360	250	H
5	9.765	30.87	Pk	37.2	-26.6	41.47	-	-	74	-32.53	0-360	250	H
2	* 4.887	35.47	Pk	34	-33.5	35.97	-	-	74	-38.03	0-360	250	V
4	* 7.323	34.72	Pk	35.8	-30.6	39.92	-	-	74	-34.08	0-360	150	V
6	9.77	30.28	Pk	37.2	-26.5	40.98	-	-	74	-33.02	0-360	150	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


Pk – Peak detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	3GHz_HP[d B]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.964	35.69	Pk	34	-33.6	36.09	-	-	74	-37.91	0-360	150	H
3	* 7.44	33.79	Pk	35.8	-30.4	39.19	-	-	74	-34.81	0-360	250	H
5	9.921	30.25	Pk	37.4	-27.1	40.55	-	-	74	-33.45	0-360	150	H
2	* 4.96	35.37	Pk	34	-33.6	35.77	-	-	74	-38.23	0-360	250	V
4	* 7.44	34.05	Pk	35.8	-30.4	39.45	-	-	74	-34.55	0-360	150	V
6	9.927	29.87	Pk	37.4	-26.9	40.37	-	-	74	-33.63	0-360	150	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk – Peak detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

10.2.2. ENHANCED DATA RATE 8PSK MODULATION RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	10dB[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	48.38	Pk		-28.4	51.78	-	-	74	-22.22	248	130	H
2	* 2.344	49.62	Pk		-28.5	52.82	-	-	74	-21.18	248	130	H
3	* 2.39	35.98	VA1T		-28.4	39.38	54	-14.62	-	-	248	130	H
4	* 2.386	36.68	VA1T		-28.5	39.98	54	-14.02	-	-	248	130	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average $VB=1/Ton$ where: Ton is transmit duration

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	10dB[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	46.23	Pk	31.8	-28.4	49.63	-	-	74	-24.37	283	227	V
2	* 2.335	49.79	Pk	31.7	-28.5	52.99	-	-	74	-21.01	283	227	V
3	* 2.39	36.09	VA1T	31.8	-28.4	39.49	54	-14.51	-	-	283	227	V
4	* 2.369	36.63	VA1T	31.8	-28.4	40.03	54	-13.97	-	-	283	227	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	10dB[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	53.88	Pk	32	-28.3	57.58	-	-	74	-16.42	244	146	H
2	* 2.484	53.87	Pk	32	-28.3	57.57	-	-	74	-16.43	244	146	H
3	* 2.484	36.49	VA1T	32	-28.3	40.19	54	-13.81	-	-	244	146	H
4	* 2.486	36.86	VA1T	32	-28.3	40.56	54	-13.44	-	-	244	146	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	10dB[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	51.93	Pk	32	-28.3	55.63	-	-	74	-18.37	241	195	V
2	* 2.484	51.89	Pk	32	-28.3	55.59	-	-	74	-18.41	241	195	V
3	* 2.484	36.42	VA1T	32	-28.3	40.12	54	-13.88	-	-	241	195	V
4	* 2.486	36.82	VA1T	32	-28.3	40.52	54	-13.48	-	-	241	195	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector


VA1T - FHSS: Linear Voltage Average $V_B=1/T_{on}$ where: T_{on} is transmit duration

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	3GHz_HP[d B]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.804	35.97	Avg	34	-33.5	36.47	-	-	74	-37.53	0-360	150	H
3	7.205	32.68	Avg	35.7	-30.6	37.78	-	-	74	-36.22	0-360	150	H
5	9.61	30.62	Avg	37	-27.4	40.22	-	-	74	-33.78	0-360	150	H
2	* 4.8	35.98	Avg	34	-33.4	36.58	-	-	74	-37.42	0-360	250	V
4	7.205	32.9	Avg	35.7	-30.6	38	-	-	74	-36	0-360	150	V
6	9.612	30.86	Avg	37	-27.4	40.46	-	-	74	-33.54	0-360	250	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


Avg - Video bandwidth < Resolution bandwidth

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	3GHz_HP[d B]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.879	35.08	Pk	34	-33.5	35.58	-	-	74	-38.42	0-360	150	H
3	* 7.323	33.31	Pk	35.8	-30.6	38.51	-	-	74	-35.49	0-360	250	H
5	9.766	30.34	Pk	37.2	-26.6	40.94	-	-	74	-33.06	0-360	150	H
2	* 4.88	35.08	Pk	34	-33.5	35.58	-	-	74	-38.42	0-360	250	V
4	* 7.324	33.07	Pk	35.8	-30.6	38.27	-	-	74	-35.73	0-360	150	V
6	9.767	30.64	Pk	37.2	-26.5	41.34	-	-	74	-32.66	0-360	150	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


Pk – Peak detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	3GHz_HP[d B]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.963	35.65	Pk	34	-33.6	36.05	-	-	74	-37.95	0-360	150	H
3	* 7.438	33.01	Pk	35.8	-30.4	38.41	-	-	74	-35.59	0-360	250	H
5	9.92	30.35	Pk	37.4	-27.1	40.65	-	-	74	-33.35	0-360	150	H
2	* 4.963	35.95	Pk	34	-33.6	36.35	-	-	74	-37.65	0-360	150	V
4	* 7.44	33.43	Pk	35.8	-30.4	38.83	-	-	74	-35.17	0-360	150	V
6	9.918	30.22	Pk	37.4	-27.1	40.52	-	-	74	-33.48	0-360	150	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


Pk – Peak detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).


10.3. WORST-CASE BELOW 1 GHz

GFSK SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)

HORIZONTAL PLOT



VERTICAL PLOT



BELOW 1 GHz TABLE

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163-750	Bi-Log	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	54.6075	45.96	Pk	13.3	-30	29.26	40	-10.74	0-360	400	H
2	* 171.9075	48.1	Pk	9	-28.4	28.7	43.52	-14.82	0-360	300	H
3	196.1325	49.45	Pk	11	-28.2	32.25	43.52	-11.27	0-360	100	H
4	32.89	48.36	Pk	10.4	-30.5	28.26	40	-11.74	0-360	100	V
5	55.245	45.15	Pk	13.2	-30	28.35	40	-11.65	0-360	200	V
6	222.1	45.94	Pk	11.8	-28	29.74	46.02	-16.28	0-360	100	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

11. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

6 WORST EMISSIONS

LINE 1 PLOT



LINE 1 RESULTS

Trace Markers

Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_wit h ex-cord_L1	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
1	.168	49.98	Pk	10	0	59.98	65.06	-5.08	-	-
2	.168	31.96	Av	10	0	41.96	-	-	55.06	-13.1
3	.258	42.54	Pk	9.7	0	52.24	61.5	-9.26	-	-
4	.258	25.55	Av	9.7	0	35.25	-	-	51.5	-16.25
5	.33	35.09	Pk	9.8	0	44.89	59.45	-14.56	-	-
6	.348	14.6	Av	9.8	0	24.4	-	-	49.01	-24.61
7	.411	35.69	Pk	9.9	0	45.59	57.63	-12.04	-	-
8	.429	13.74	Av	9.9	0	23.64	-	-	47.27	-23.63
9	7.305	36.63	Pk	9.9	.1	46.63	60	-13.37	-	-
10	7.278	18.07	Av	9.9	.1	28.07	-	-	50	-21.93
11	13.713	37.55	Pk	10.1	.2	47.85	60	-12.15	-	-
12	13.767	18.06	Av	10.1	.2	28.36	-	-	50	-21.64

Pk - Peak detector

Av - Average detection


Quasi-Peak Emissions

Phase L1 .15 - 30MHz

Frequency (MHz)	Meter Reading (dBuV)	Det	101837_wit h ex-cord_L1	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
.1644	35.05	Qp	9.9	0	44.95	65.24	-20.29	-	-
.2607	28.86	Qp	9.7	0	38.56	61.41	-22.85	-	-
7.3086	29.8	Qp	9.9	.1	39.8	60	-20.2	-	-
7.278	30.21	Qp	9.9	.1	40.21	60	-19.79	-	-
13.7157	28.43	Qp	10.1	.2	38.73	60	-21.27	-	-
13.767	28.05	Qp	10.1	.2	38.35	60	-21.65	-	-

Qp – Quasi-Peak detector

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_w ith ex- cord_N	CE Shield Room	Corrected Reading (dB(uVolts)	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
13	.168	40.99	Pk	10	0	50.99	65.06	-14.07	-	-
14	.168	23.32	Av	10	0	33.32	-	-	55.06	-21.74
15	.258	34.62	Pk	9.7	0	44.32	61.5	-17.18	-	-
16	.258	19.74	Av	9.7	0	29.44	-	-	51.5	-22.06
17	.411	30.95	Pk	9.9	0	40.85	57.63	-16.78	-	-
18	.429	15.53	Av	9.9	0	25.43	-	-	47.27	-21.84
19	.537	32.23	Pk	9.9	0	42.13	56	-13.87	-	-
20	.528	17.69	Av	9.9	0	27.59	-	-	46	-18.41
21	7.575	38.63	Pk	10	.1	48.73	60	-11.27	-	-
22	7.575	20.28	Av	10	.1	30.38	-	-	50	-19.62
23	14.019	38.31	Pk	10.3	.2	48.81	60	-11.19	-	-
24	13.983	17.98	Av	10.3	.2	28.48	-	-	50	-21.52

Pk - Peak detector

Av - Average detection

Quasi-Peak Emissions

Phase N .15 - 30MHz

Frequency (MHz)	Meter Reading (dBuV)	Det	101837_wit h ex-cord_N	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
.1644	34.04	Qp	9.9	0	43.94	65.24	-21.3	-	-
.2607	27.85	Qp	9.7	0	37.55	61.41	-23.86	-	-
7.5741	30.58	Qp	10	.1	40.68	60	-19.32	-	-
14.0226	29.42	Qp	10.3	.2	39.92	60	-20.08	-	-
13.9875	28.68	Qp	10.3	.2	39.18	60	-20.82	-	-

Qp – Quasi-Peak detector