



HCT Co., Ltd.
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

COMPLIANCE SUMMARY REPORT

Applicant Name: SAMSUNG Electronics Co., Ltd. 129, Samsung-ro, Yeongtong-gu, Suwon-Si, Gyeonggi-do, 16677 Rep. of Korea	Date of Issue: Jul. 17, 2020 Test Report No.: HCT-SR-2007-FC008 Test Site: HCT CO., LTD.
--	---

FCC ID:

A3LSMT878U

Report Type:	Compliance Summary Characterization
Equipment Type:	Tablet
Model Name:	SM-T878U

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	Jul. 17, 2020	Initial Release

This test results were applied only to the test methods required by the standard.

The above Test Report is not related to the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme), which signed the ILAC-MRA.

Table of Contents

1. RF Exposure Evaluation Strategy	4
2. Time Averaging Algorithm	7
3. DEVICE UNDER TEST	9
4. RF Exposure Compliance Summary.....	10

1. RF Exposure Evaluation Strategy

The FCC RF exposure limits defined based on time-averaged RF exposure. The device under test (DUT) uses the Qualcomm Smart Transmit feature to control and manage transmitting power in real time and to ensure at all times the time-averaged RF exposure is in compliance with the FCC requirement for 2G/3G/4G/5G NR operations. Additionally, this device supports WLAN/BT/NFC/ANT+/MST technologies but the output power of these modems is not controlled by the smart transmit algorithm

Demonstrating compliance of DUT enabled with Qualcomm Smart Transmit feature is completed in three parts:

0. RF Exposure Compliance Test Report Part 0: SAR Characterization and PD Characterization

The SAR and PD Characterization, denoted as SAR Char and PD Char, determines the power limit that meets FCC exposure requirement after accounting for device design related uncertainties for each supported radio configuration and RF exposure usage scenario. The determined power limits will be loaded and stored in the EUT via the Embedded File System (EFS), and then used as inputs for Smart Transmit to operate.

For 2G/3G/4G/5G Sub6, SAR Char is derived from SAR test measurements and conducted power measurements to determine PLimit for each technology/band. For 5G mmW NR, PD Char is derived using simulation in combination with measurement as validation to determine the input.power.limit for each radio/antenna configuration (each beam). The PLimit and input.power.limit represents the maximum time-averaged power level for the corresponding radio/antenna configuration.

1.RF Exposure Compliance Test Report Part 1: Test in Static Transmission Condition

Part 1 demonstrates that DUT meets FCC SAR and PD limits when transmitting at pre-determined maximum time-averaged power level: PLimit for 2G/3G/4G/5G Sub6 NR and input.power.limit for 5G mmW NR. The SAR and PD measurement in Part 1 is under static transmission condition.

The compliance for WLAN/BT radio is demonstrated at a fixed power level (fixed = maximum RF tune-up level or power-back off level).

The exposure from the simultaneous transmission of WWAN and WLAN/BT is evaluated in Part 1 report.

2.RF Exposure Compliance Test Report Part 2: Test in Dynamic Transmission Condition

Part 2 demonstrates compliance in Tx varying transmission conditions and validates Qualcomm Smart Transmit algorithm. The test results reported in Part 2 demonstrates that DUT complies with FCC RF exposure requirement under Tx varying transmission scenarios, thereby validity of Qualcomm Smart Transmit algorithm.

Applicable Technologies	Term	Description
2G/3G/4G/5G Sub6	P_{Limit}	Power level that corresponds to the exposure design target (SAR_{design_target}) after accounting for all device design related uncertainties
	P_{Max}	Maximum tune up output power
	T_{SAR}	Defined time averaging window for $f < 6$ GHz
	SAR_{design_target}	Target SAR level resulting in maximum time-averaged exposure optimized from total uncertainty
	SAR_{Char}	Table containing P_{Limit} for all technologies
5G mmW NR	$input.power.limit$	Power level at antenna element for each beam corresponding to the exposure design target (PD_{design_target})
	T_{PD}	Defined time averaging window for $f > 6$ GHz
	PD_{design_target}	Target PD level resulting in maximum time-averaged exposure optimized from total uncertainty
	PD_{Char}	Table containing $input.power.limit$ for all beams
2G/3G/4G/5G Sub6/5G mmW NR	$regulatory\ body$	Regulatory body that the algorithm is designed to comply. Algorithm's time averaging window is dependent on either FCC or ICNIRP requirements.
	$reserve_power_margin$	Margin below P_{Limit} reserved for future transmission
	$P_{reserve}$	Minimum transmit power with a designated margin below P_{Limit}

1.2 Report Serial Number

Frequency	Report description	Report Number
Freq. < 6 GHz.	Part 0 SAR Test Report	HCT-SR-2007-FC005
	Part 1 SAR Test Report	HCT-SR-2007-FC007
Freq. > 6 GHz.	Power Density Simulation Report	Power Density Simulation Report Rev.A
	Part 0 Power Density Test Report	HCT-SR-2007-FC002
	Part 1 Power Density Test Report	HCT-SR-2007-FC003
Freq. > 6 GHz.& Freq.< 6 GHz.	Part 2 RF Exposure Report	HCT-SR-2007-FC006

2. Time Averaging Algorithm

2.1 General Information

The FCC RF exposure limit is defined based on time-averaged RF exposure. When running in a wireless device,

Qualcomm Smart Transmit algorithm enables more elegant power control mechanisms for RF exposure management. It ensures at all times the wireless device is in compliance with the FCC limit of RF exposure time-averaged over a defined time window, denoted as TSAR and TPD for specific absorption rate (SAR for transmit frequency < 6 GHz) and power density (PD for transmit frequency > 6 GHz) time windows, respectively.

The Smart Transmit algorithm not only ensures the wireless device complies with RF exposure requirement, but also improves the user experience and network performance.

For a given wireless device, RF exposure is proportional to the transmitting power.

- Once the SAR and PD of the wireless device is characterized at a transmit power level, RF exposure at a different power level for the characterized configurations can be scaled by the change in the corresponding power level.
- Therefore, for a characterized device, RF exposure compliance can be achieved through transmit power control and management.

The Smart Transmit algorithm embedded in Qualcomm modems reliably controls the transmit power of the wireless device in real time to maintain the time-averaged transmit power, in turn, time-averaged RF exposure, below the predefined time-averaged power limit for each characterized technology and band.

- This predefined time-averaged power limit is denoted as PLimit corresponding SAR limit (frequency < 6 GHz) and input.power.limit corresponding PD limit (frequency > 6 GHz) in this report.
- The wireless device continuously transmitting at PLimit level or input.power.limit level complies with the FCC RF exposure requirement.

In a simultaneous transmission scenario, the algorithm manages all active transmitters and make sure the total exposure ratio from each transmitter not exceeding to 1.

2.2 Basic concept of the feature

The Smart Transmit feature is configured to manage the instantaneous transmit power (Tx) to keep the time-averaged power and not exceed *P_{limit}*.


If time-averaged transmit power approaches the *P_{limit}*, then the modem needs to limit instantaneous transmit power to ensure the time-averaged transmit power does not exceed the *P_{limit}* in any *T_{SAR}* and *T_{PD}* time windows (i.e., the time-averaged RF exposure complies with the FCC RF exposure limit in any time window).

The wireless device can instantaneously transmit at high transmit powers and exceed the *P_{limit}* for a short duration before limiting the power to maintain the time-averaged transmit power under the *P_{limit}*.

If the wireless device transmits at high power for a long duration, then the radio link needs to be dropped to be compliant with time-averaged Tx power requirement (see [Figure 2-1](#)).


To avoid dropping the radio link, Smart Transmit feature starts the power limiting enforcement earlier in time to back off the Tx power to a reserve level (denoted as *Preserve*), so the wireless device can maintain the radio link at a minimum reserve power level for as long as needed, and at the same time ensure the time-averaged Tx power over any predefined time window is less than *P_{limit}* at all times (see [Figure 2-2](#)). At all times, Smart Transmit meets the below equation (1):

$$\text{time avg. Tx power} = \frac{1}{T} \int_t^{t+T} \text{inst. Tx power}(t) dt \leq P_{\text{limit}} \quad (1)$$



(a)

Figure 2-1 Transmit at high power when needed and permitted



(b)

Figure 2-2 Transmit with reserve power to support continuous transmission at a minimum power level (*Preserve*)

3. DEVICE UNDER TEST

3.1 General Information of the EUT

Model Name	SM-T878U	
Equipment Type	Tablet	
FCC ID	A3LSMT878U	
Application Type	Certification	
Applicant	SAMSUNG Electronics Co., Ltd.	
Device Wireless specification overview		
Band & Mode	Operating Mode	Tx Frequency
UMTS 850	Data	826.4 MHz ~ 846.6 MHz
UMTS 1700	Data	1 712.4 MHz ~ 1 752.6 MHz
UMTS 1900	Data	1 852.4 MHz ~ 1 907.6 MHz
LTE Band 2	Data	1 850.7 MHz ~ 1 909.3 MHz
LTE Band 4	Data	1 710.7 MHz ~ 1 754.3 MHz
LTE Band 5 (Cell)	Data	824.7 MHz ~ 848.3 MHz
LTE Band 7	Data	2 502.5 MHz ~ 2 567.5 MHz
LTE Band 12	Data	699.7 MHz ~ 715.3 MHz
LTE Band 13	Data	779.5 MHz ~ 784.5 MHz
LTE Band 14	Data	790.5 MHz ~ 795.5 MHz
LTE Band 25	Data	1 850.7 MHz ~ 1 914.3 MHz
LTE Band 26	Data	814.7 MHz ~ 848.3 MHz
LTE Band 30	Data	2 307.5 MHz ~ 2 312.5 MHz
LTE TDD Band 41	Data	2 498.5 MHz ~ 2 687.5 MHz
LTE Band 66 (AWS)	Data	1 710.7 MHz ~ 1 779.3 MHz
LTE Band 71	Data	665.5 MHz ~ 695.5 MHz
NR Band 2	Data	1 852.5 MHz ~ 1 907.5 MHz
NR Band 5	Data	826.5 MHz ~ 846.5 MHz
NR Band 25	Data	1852.5 MHz ~ 1912.5 MHz
NR Band 41	Data	2 506.02 MHz ~ 2 679.99 MHz
NR Band 66	Data	1 712.5 MHz ~ 1 777.5 MHz
NR Band 71	Data	665.5 MHz - 695.5 MHz
802.11b	Data	2 412 MHz ~ 2 462 MHz
U-NII-1	Data	5 180 MHz ~ 5 240 MHz
U-NII-2A	Data	5 260 MHz ~ 5 320 MHz
U-NII-2C	Data	5 500 MHz ~ 5 720 MHz
U-NII-3	Data	5 745 MHz ~ 5 825 MHz
Bluetooth	Data	2 402 MHz ~ 2 480 MHz
ANT+	Data	2 402 MHz ~ 2 480 MHz

This device uses the Qualcomm® Smart Transmit feature to control and manage transmitting power in real time and to ensure the time-averaged RF exposure is in compliance with the FCC requirement at all times for 2G/3G/4G/5G WWAN operations. Additionally, this device supports WLAN/BT/NFC /MST technologies, but

the output power of these modems is not controlled by the Smart Transmit algorithm

4. RF Exposure Compliance Summary

	RFx Evaluation	Power Level	FCC Limit W/kg	Reported RF Exposure Level W/kg	Test Report
SAR [W/kg]	Standalone 1g SAR	<i>Plimit</i>	1.6	1.24	Part 1 SAR Report
	Simultaneous Tx 1g SAR	<i>Plimit</i>	1.6	1.59	
psPD[mW/cm ²]	4cm ² psPD	<i>input.power.limit</i>	1.0	0.75	Part 1 Power Density_Report
TER	Total Exposure Ratio	<i>Plimit</i> for SAR, <i>input.power.limit</i> for psPD	1.0	0.988	Part 1 Power Density_Report